Gateway Documentation - Securities Service

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.87.1.0

[August] [2014]

Table Of Contents

1. BACKGROUND .....

2. FCUBSSecuritiesService .....

2.1. AuthorizeDealProduct .....

2.1.1. SD-AuthorizeDealProduct-Req-Full-MSG.xsd .....

2.1.2. SD-AuthorizeDealProduct-Req-IO-MSG.xsd .....

2.1.3. SD-AuthorizeDealProduct-Res-Full-MSG.xsd .....

2.1.4. SD-AuthorizeDealProduct-Res-PK-MSG.xsd .....

2.2. AuthorizeSEDealBlockRelease .....

2.2.1. SD-AuthorizeSEDealBlockRelease-Req-Full-MSG.xsd .....

2.2.2. SD-AuthorizeSEDealBlockRelease-Req-IO-MSG.xsd .....

2.2.3. SD-AuthorizeSEDealBlockRelease-Res-Full-MSG.xsd .....

2.2.4. SD-AuthorizeSEDealBlockRelease-Res-PK-MSG.xsd .....

2.3. AuthorizeSecBlockDeal .....

2.3.1. SD-AuthorizeSecBlockDeal-Req-Full-MSG.xsd .....

2.3.2. SD-AuthorizeSecBlockDeal-Req-IO-MSG.xsd .....

2.3.3. SD-AuthorizeSecBlockDeal-Res-Full-MSG.xsd .....

2.3.4. SD-AuthorizeSecBlockDeal-Res-PK-MSG.xsd .....

2.4. AuthorizeSecuritiesDeal .....

2.4.1. SD-AuthorizeSecuritiesDeal-Req-Full-MSG.xsd .....

2.4.2. SD-AuthorizeSecuritiesDeal-Req-IO-MSG.xsd .....

2.4.3. SD-AuthorizeSecuritiesDeal-Res-Full-MSG.xsd .....

2.4.4. SD-AuthorizeSecuritiesDeal-Res-PK-MSG.xsd .....

2.5. CloseDealProduct .....

2.5.1. SD-CloseDealProduct-Req-Full-MSG.xsd .....

2.5.2. SD-CloseDealProduct-Req-IO-MSG.xsd .....

2.5.3. SD-CloseDealProduct-Res-Full-MSG.xsd .....

2.5.4. SD-CloseDealProduct-Res-PK-MSG.xsd .....

2.6. CloseSecBlockDeal .....

2.6.1. SD-CloseSecBlockDeal-Req-Full-MSG.xsd .....

2.6.2. SD-CloseSecBlockDeal-Req-IO-MSG.xsd .....

2.6.3. SD-CloseSecBlockDeal-Res-Full-MSG.xsd .....

2.6.4. SD-CloseSecBlockDeal-Res-PK-MSG.xsd .....

2.7. CloseSecuritiesDeal .....

2.7.1. SD-CloseSecuritiesDeal-Req-Full-MSG.xsd .....

2.7.2. SD-CloseSecuritiesDeal-Req-IO-MSG.xsd .....

2.7.3. SD-CloseSecuritiesDeal-Res-Full-MSG.xsd .....

2.7.4. SD-CloseSecuritiesDeal-Res-PK-MSG.xsd .....

2.8. ConfirmSecBlockDeal .....

2.8.1. SD-ConfirmSecBlockDeal-Req-Full-MSG.xsd .....

2.8.2. SD-ConfirmSecBlockDeal-Req-IO-MSG.xsd .....

2.8.3. SD-ConfirmSecBlockDeal-Res-Full-MSG.xsd .....

2.8.4. SD-ConfirmSecBlockDeal-Res-PK-MSG.xsd .....

2.9. ConfirmSecuritiesDeal .....

2.9.1. SD-ConfirmSecuritiesDeal-Req-Full-MSG.xsd .....

2.9.2. SD-ConfirmSecuritiesDeal-Req-IO-MSG.xsd .....

2.9.3. SD-ConfirmSecuritiesDeal-Res-Full-MSG.xsd .....

2.9.4. SD-ConfirmSecuritiesDeal-Res-PK-MSG.xsd .....

2.10. CreateDealProduct .....

2.10.1. SD-CreateDealProduct-Req-Full-MSG.xsd .....

2.10.2. SD-CreateDealProduct-Req-IO-MSG.xsd .....

2.10.3. SD-CreateDealProduct-Res-Full-MSG.xsd .....

2.10.4. SD-CreateDealProduct-Res-PK-MSG.xsd .....

2.11. CreateSEDealBlockRelease .....

2.11.1. SD-CreateSEDealBlockRelease-Req-Full-MSG.xsd .....

2.11.2. SD-CreateSEDealBlockRelease-Req-IO-MSG.xsd .....
2.11.3. SD-CreateSEDealBlockRelease-Res-Full-MSG.xsd .....
2.11.4. SD-CreateSEDealBlockRelease-Res-PK-MSG.xsd .....
2.12. CreateSecBlockDeal .....
2.12.1. SD-CreateSecBlockDeal-Req-Full-MSG.xsd .....
2.12.2. SD-CreateSecBlockDeal-Req-IO-MSG.xsd .....
2.12.3. SD-CreateSecBlockDeal-Res-Full-MSG.xsd .....
2.12.4. SD-CreateSecBlockDeal-Res-PK-MSG.xsd .....
2.13. CreateSecuritiesDeal .....
2.13.1. SD-CreateSecuritiesDeal-Req-Full-MSG.xsd .....
2.13.2. SD-CreateSecuritiesDeal-Req-IO-MSG.xsd .....
2.13.3. SD-CreateSecuritiesDeal-Res-Full-MSG.xsd .....
2.13.4. SD-CreateSecuritiesDeal-Res-PK-MSG.xsd .....
2.14. DeleteDealProduct .....
2.14.1. SD-DeleteDealProduct-Req-Full-MSG.xsd .....
2.14.2. SD-DeleteDealProduct-Req-IO-MSG.xsd .....
2.14.3. SD-DeleteDealProduct-Res-Full-MSG.xsd .....
2.14.4. SD-DeleteDealProduct-Res-PK-MSG.xsd .....
2.15. DeleteSEDealBlockRelease .....
2.15.1. SD-DeleteSEDealBlockRelease-Req-Full-MSG.xsd .....
2.15.2. SD-DeleteSEDealBlockRelease-Req-IO-MSG.xsd .....
2.15.3. SD-DeleteSEDealBlockRelease-Res-Full-MSG.xsd .....
2.15.4. SD-DeleteSEDealBlockRelease-Res-PK-MSG.xsd .....
2.16. DeleteSecBlockDeal .....
2.16.1. SD-DeleteSecBlockDeal-Req-Full-MSG.xsd .....
2.16.2. SD-DeleteSecBlockDeal-Req-IO-MSG.xsd .....
2.16.3. SD-DeleteSecBlockDeal-Res-Full-MSG.xsd .....
2.16.4. SD-DeleteSecBlockDeal-Res-PK-MSG.xsd .....
2.17. DeleteSecuritiesDeal .....
2.17.1. SD-DeleteSecuritiesDeal-Req-Full-MSG.xsd .....
2.17.2. SD-DeleteSecuritiesDeal-Req-IO-MSG.xsd .....
2.17.3. SD-DeleteSecuritiesDeal-Res-Full-MSG.xsd .....
2.17.4. SD-DeleteSecuritiesDeal-Res-PK-MSG.xsd .....
2.18. LiquidateSEDealBlockRelease .....
2.18.1. SD-LiquidateSEDealBlockRelease-Req-Full-MSG.xsd .....
2.18.2. SD-LiquidateSEDealBlockRelease-Req-IO-MSG.xsd .....
2.18.3. SD-LiquidateSEDealBlockRelease-Res-Full-MSG.xsd .....
2.18.4. SD-LiquidateSEDealBlockRelease-Res-PK-MSG.xsd .....
2.19. LiquidateSecBlockDeal .....
2.19.1. SD-LiquidateSecBlockDeal-Req-Full-MSG.xsd .....
2.19.2. SD-LiquidateSecBlockDeal-Req-IO-MSG.xsd .....
2.19.3. SD-LiquidateSecBlockDeal-Res-Full-MSG.xsd .....
2.19.4. SD-LiquidateSecBlockDeal-Res-PK-MSG.xsd .....
2.20. LiquidateSecuritiesDeal .....
2.20.1. SD-LiquidateSecuritiesDeal-Req-Full-MSG.xsd .....
2.20.2. SD-LiquidateSecuritiesDeal-Req-IO-MSG.xsd .....
2.20.3. SD-LiquidateSecuritiesDeal-Res-Full-MSG.xsd .....
2.20.4. SD-LiquidateSecuritiesDeal-Res-PK-MSG.xsd .....
2.21. ModifyDealProduct .....
2.21.1. SD-ModifyDealProduct-Req-Full-MSG.xsd .....
2.21.2. SD-ModifyDealProduct-Req-IO-MSG.xsd .....
2.21.3. SD-ModifyDealProduct-Res-Full-MSG.xsd .....
2.21.4. SD-ModifyDealProduct-Res-PK-MSG.xsd .....
2.22. ModifySEDealBlockRelease .....
2.22.1. SD-ModifySEDealBlockRelease-Req-Full-MSG.xsd .....
2.22.2. SD-ModifySEDealBlockRelease-Req-IO-MSG.xsd .....
2.22.3. SD-ModifySEDealBlockRelease-Res-Full-MSG.xsd .....
2.22.4. SD-ModifySEDealBlockRelease-Res-PK-MSG.xsd .....

2.23. ModifySecBlockDeal .....
2.23.1. SD-ModifySecBlockDeal-Req-Full-MSG.xsd .....
2.23.2. SD-ModifySecBlockDeal-Req-IO-MSG.xsd .....
2.23.3. SD-ModifySecBlockDeal-Res-Full-MSG.xsd .....
2.23.4. SD-ModifySecBlockDeal-Res-PK-MSG.xsd .....
2.24. ModifySecuritiesDeal .....
2.24.1. SD-ModifySecuritiesDeal-Req-Full-MSG.xsd .....
2.24.2. SD-ModifySecuritiesDeal-Req-IO-MSG.xsd .....
2.24.3. SD-ModifySecuritiesDeal-Res-Full-MSG.xsd .....
2.24.4. SD-ModifySecuritiesDeal-Res-PK-MSG.xsd .....
2.25. QueryDealProduct .....
2.25.1. SD-QueryDealProduct-Req-IO-MSG.xsd .....
2.25.2. SD-QueryDealProduct-Res-Full-MSG.xsd .....
2.26. QuerySEDealBlockRelease .....
2.26.1. SD-QuerySEDealBlockRelease-Req-IO-MSG.xsd .....
2.26.2. SD-QuerySEDealBlockRelease-Res-Full-MSG.xsd .....
2.27. QuerySecBlockDeal .....
2.27.1. SD-QuerySecBlockDeal-Req-IO-MSG.xsd .....
2.27.2. SD-QuerySecBlockDeal-Res-Full-MSG.xsd .....
2.28. QuerySecuritiesDeal .....
2.28.1. SD-QuerySecuritiesDeal-Req-IO-MSG.xsd .....
2.28.2. SD-QuerySecuritiesDeal-Res-Full-MSG.xsd .....
2.29. ReopenDealProduct .....
2.29.1. SD-ReopenDealProduct-Req-Full-MSG.xsd .....
2.29.2. SD-ReopenDealProduct-Req-IO-MSG.xsd .....
2.29.3. SD-ReopenDealProduct-Res-Full-MSG.xsd .....
2.29.4. SD-ReopenDealProduct-Res-PK-MSG.xsd .....
2.30. ReopenSecuritiesDeal .....
2.30.1. SD-ReopenSecuritiesDeal-Req-Full-MSG.xsd .....
2.30.2. SD-ReopenSecuritiesDeal-Req-IO-MSG.xsd .....
2.30.3. SD-ReopenSecuritiesDeal-Res-Full-MSG.xsd .....
2.30.4. SD-ReopenSecuritiesDeal-Res-PK-MSG.xsd .....
2.31. ReverseSecBlockDeal .....
2.31.1. SD-ReverseSecBlockDeal-Req-Full-MSG.xsd .....
2.31.2. SD-ReverseSecBlockDeal-Req-IO-MSG.xsd .....
2.31.3. SD-ReverseSecBlockDeal-Res-Full-MSG.xsd .....
2.31.4. SD-ReverseSecBlockDeal-Res-PK-MSG.xsd .....
2.32. ReverseSecuritiesDeal .....
2.32.1. SD-ReverseSecuritiesDeal-Req-Full-MSG.xsd .....
2.32.2. SD-ReverseSecuritiesDeal-Req-IO-MSG.xsd .....
2.32.3. SD-ReverseSecuritiesDeal-Res-Full-MSG.xsd .....
2.32.4. SD-ReverseSecuritiesDeal-Res-PK-MSG.xsd .....
2.33. RolloverSecuritiesDeal .....
2.33.1. SD-RolloverSecuritiesDeal-Req-Full-MSG.xsd .....
2.33.2. SD-RolloverSecuritiesDeal-Req-IO-MSG.xsd .....
2.33.3. SD-RolloverSecuritiesDeal-Res-Full-MSG.xsd .....
2.33.4. SD-RolloverSecuritiesDeal-Res-PK-MSG.xsd .....
2.34. AuthorizeMarketCode .....
2.34.1. SE-AuthorizeMarketCode-Req-Full-MSG.xsd .....
2.34.2. SE-AuthorizeMarketCode-Req-IO-MSG.xsd .....
2.34.3. SE-AuthorizeMarketCode-Res-Full-MSG.xsd .....
2.34.4. SE-AuthorizeMarketCode-Res-PK-MSG.xsd .....
2.35. AuthorizePriceDtl .....
2.35.1. SE-AuthorizePriceDtl-Req-Full-MSG.xsd .....
2.35.2. SE-AuthorizePriceDtl-Req-IO-MSG.xsd .....
2.35.3. SE-AuthorizePriceDtl-Res-Full-MSG.xsd .....
2.35.4. SE-AuthorizePriceDtl-Res-PK-MSG.xsd .....

2.36. AuthorizeRecord .....
2.36.1. SE-AuthorizeRecord-Req-Full-MSG.xsd .....
2.36.2. SE-AuthorizeRecord-Req-IO-MSG.xsd .....
2.36.3. SE-AuthorizeRecord-Res-Full-MSG.xsd .....
2.36.4. SE-AuthorizeRecord-Res-PK-MSG.xsd .....
2.37. AuthorizeSEMarketCode .....
2.37.1. SE-AuthorizeSEMarketCode-Req-Full-MSG.xsd .....
2.37.2. SE-AuthorizeSEMarketCode-Req-IO-MSG.xsd .....
2.37.3. SE-AuthorizeSEMarketCode-Res-Full-MSG.xsd .....
2.37.4. SE-AuthorizeSEMarketCode-Res-PK-MSG.xsd .....
2.38. AuthorizeSEMarketPriceCodes .....
2.38.1. SE-AuthorizeSEMarketPriceCodes-Req-Full-MSG.xsd .....
2.38.2. SE-AuthorizeSEMarketPriceCodes-Req-IO-MSG.xsd .....
2.38.3. SE-AuthorizeSEMarketPriceCodes-Res-Full-MSG.xsd .....
2.38.4. SE-AuthorizeSEMarketPriceCodes-Res-PK-MSG.xsd .....
2.39. AuthorizeSEPriceDetail .....
2.39.1. SE-AuthorizeSEPriceDetail-Req-Full-MSG.xsd .....
2.39.2. SE-AuthorizeSEPriceDetail-Req-IO-MSG.xsd .....
2.39.3. SE-AuthorizeSEPriceDetail-Res-Full-MSG.xsd .....
2.39.4. SE-AuthorizeSEPriceDetail-Res-PK-MSG.xsd .....
2.40. AuthorizeSESKLocationChange .....
2.40.1. SE-AuthorizeSESKLocationChange-Req-Full-MSG.xsd .....
2.40.2. SE-AuthorizeSESKLocationChange-Req-IO-MSG.xsd .....
2.40.3. SE-AuthorizeSESKLocationChange-Res-Full-MSG.xsd .....
2.40.4. SE-AuthorizeSESKLocationChange-Res-PK-MSG.xsd .....
2.41. AuthorizeSESKLocationMaint .....
2.41.1. SE-AuthorizeSESKLocationMaint-Req-Full-MSG.xsd .....
2.41.2. SE-AuthorizeSESKLocationMaint-Req-IO-MSG.xsd .....
2.41.3. SE-AuthorizeSESKLocationMaint-Res-Full-MSG.xsd .....
2.41.4. SE-AuthorizeSESKLocationMaint-Res-PK-MSG.xsd .....
2.42. AuthorizeSKLocationMaint .....
2.42.1. SE-AuthorizeSKLocationMaint-Req-Full-MSG.xsd .....
2.42.2. SE-AuthorizeSKLocationMaint-Req-IO-MSG.xsd .....
2.42.3. SE-AuthorizeSKLocationMaint-Res-Full-MSG.xsd .....
2.42.4. SE-AuthorizeSKLocationMaint-Res-PK-MSG.xsd .....
2.43. CreateMarketCode .....
2.43.1. SE-CreateMarketCode-Req-Full-MSG.xsd .....
2.43.2. SE-CreateMarketCode-Req-IO-MSG.xsd .....
2.43.3. SE-CreateMarketCode-Res-Full-MSG.xsd .....
2.43.4. SE-CreateMarketCode-Res-PK-MSG.xsd .....
2.44. CreateNewRecord .....
2.44.1. SE-CreateNewRecord-Req-Full-MSG.xsd .....
2.44.2. SE-CreateNewRecord-Req-IO-MSG.xsd .....
2.44.3. SE-CreateNewRecord-Res-Full-MSG.xsd .....
2.44.4. SE-CreateNewRecord-Res-PK-MSG.xsd .....
2.45. CreatePriceDtl .....
2.45.1. SE-CreatePriceDtl-Req-Full-MSG.xsd .....
2.45.2. SE-CreatePriceDtl-Req-IO-MSG.xsd .....
2.45.3. SE-CreatePriceDtl-Res-Full-MSG.xsd .....
2.45.4. SE-CreatePriceDtl-Res-PK-MSG.xsd .....
2.46. CreateSEMarketCode .....
2.46.1. SE-CreateSEMarketCode-Req-Full-MSG.xsd .....
2.46.2. SE-CreateSEMarketCode-Req-IO-MSG.xsd .....
2.46.3. SE-CreateSEMarketCode-Res-Full-MSG.xsd .....
2.46.4. SE-CreateSEMarketCode-Res-PK-MSG.xsd .....
2.47. CreateSEMarketPriceCodes .....

2.47.1. SE-CreateSEMarketPriceCodes-Req-Full-MSG.xsd .....
2.47.2. SE-CreateSEMarketPriceCodes-Req-IO-MSG.xsd .....
2.47.3. SE-CreateSEMarketPriceCodes-Res-Full-MSG.xsd .....
2.47.4. SE-CreateSEMarketPriceCodes-Res-PK-MSG.xsd .....
2.48. CreateSEPriceDetail .....
2.48.1. SE-CreateSEPriceDetail-Req-Full-MSG.xsd .....
2.48.2. SE-CreateSEPriceDetail-Req-IO-MSG.xsd .....
2.48.3. SE-CreateSEPriceDetail-Res-Full-MSG.xsd .....
2.48.4. SE-CreateSEPriceDetail-Res-PK-MSG.xsd .....
2.49. CreateSESKLocationChange .....
2.49.1. SE-CreateSESKLocationChange-Req-Full-MSG.xsd .....
2.49.2. SE-CreateSESKLocationChange-Req-IO-MSG.xsd .....
2.49.3. SE-CreateSESKLocationChange-Res-Full-MSG.xsd .....
2.49.4. SE-CreateSESKLocationChange-Res-PK-MSG.xsd .....
2.50. CreateSESKLocationMaint .....
2.50.1. SE-CreateSESKLocationMaint-Req-Full-MSG.xsd .....
2.50.2. SE-CreateSESKLocationMaint-Req-IO-MSG.xsd .....
2.50.3. SE-CreateSESKLocationMaint-Res-Full-MSG.xsd .....
2.50.4. SE-CreateSESKLocationMaint-Res-PK-MSG.xsd .....
2.51. CreateSKLocationMaint .....
2.51.1. SE-CreateSKLocationMaint-Req-Full-MSG.xsd .....
2.51.2. SE-CreateSKLocationMaint-Req-IO-MSG.xsd .....
2.51.3. SE-CreateSKLocationMaint-Res-Full-MSG.xsd .....
2.51.4. SE-CreateSKLocationMaint-Res-PK-MSG.xsd .....
2.52. AuthSEDeal .....
2.52.1. SE-Deal-Auth-Req-Full-MSG.xsd .....
2.52.2. SE-Deal-Auth-Req-Msg.xsd .....
2.52.3. SE-Deal-Auth-Res-Full-MSG.xsd .....
2.52.4. SE-Deal-Auth-Res-Msg.xsd .....
2.53. AuthSDBlockRelease .....
2.53.1. SE-Deal-Blkrel-Auth-Req-Full-MSG.xsd .....
2.53.2. SE-Deal-Blkrel-Auth-Req-Msg.xsd .....
2.53.3. SE-Deal-Blkrel-Auth-Res-Full-MSG.xsd .....
2.53.4. SE-Deal-Blkrel-Auth-Res-Msg.xsd .....
2.54. CreateSDBlockRelease .....
2.54.1. SE-Deal-Blkrel-Create-Req-Full-MSG.xsd .....
2.54.2. SE-Deal-Blkrel-Create-Req-Msg.xsd .....
2.54.3. SE-Deal-Blkrel-Create-Res-Full-MSG.xsd .....
2.54.4. SE-Deal-Blkrel-Create-Res-Msg.xsd .....
2.55. DeleteSDBlockRelease .....
2.55.1. SE-Deal-Blkrel-Delete-Req-Full-MSG.xsd .....
2.55.2. SE-Deal-Blkrel-Delete-Req-Msg.xsd .....
2.55.3. SE-Deal-Blkrel-Delete-Res-Full-MSG.xsd .....
2.55.4. SE-Deal-Blkrel-Delete-Res-Msg.xsd .....
2.56. LiquidateSDBlockRelease .....
2.56.1. SE-Deal-Blkrel-Liq-Req-Full-Msg.xsd .....
2.56.2. SE-Deal-Blkrel-Liq-Req-Msg.xsd .....
2.56.3. SE-Deal-Blkrel-Liq-Res-Full-Msg.xsd .....
2.56.4. SE-Deal-Blkrel-Liq-Res-Msg.xsd .....
2.57. ModifySDBlockRelease .....
2.57.1. SE-Deal-Blkrel-Modify-Req-Full-MSG.xsd .....
2.57.2. SE-Deal-Blkrel-Modify-Req-Msg.xsd .....
2.57.3. SE-Deal-Blkrel-Modify-Res-Full-MSG.xsd .....
2.57.4. SE-Deal-Blkrel-Modify-Res-Msg.xsd .....
2.58. QuerySDBlockRelease .....
2.58.1. SE-Deal-Blkrel-Query-Req-Msg.xsd .....
2.58.2. SE-Deal-Blkrel-Query-Res-Full-MSG.xsd .....
2.59. AuthSEBlockDeal .....

2.59.1. SE-Deal-Blkreq-Auth-Req-Full-MSG.xsd .....
2.59.2. SE-Deal-Blkreq-Auth-Req-Msg.xsd .....
2.59.3. SE-Deal-Blkreq-Auth-Res-Full-MSG.xsd .....
2.59.4. SE-Deal-Blkreq-Auth-Res-Msg.xsd .....
2.60. CloseSEBlockDeal .....
2.60.1. SE-Deal-Blkreq-Close-Req-Full-MSG.xsd .....
2.60.2. SE-Deal-Blkreq-Close-Req-Msg.xsd .....
2.60.3. SE-Deal-Blkreq-Close-Res-Full-MSG.xsd .....
2.60.4. SE-Deal-Blkreq-Close-Res-Msg.xsd .....
2.61. ConfirmSEBlockDeal .....
2.61.1. SE-Deal-Blkreq-Confirm-Req-Full-MSG.xsd .....
2.61.2. SE-Deal-Blkreq-Confirm-Req-Msg.xsd .....
2.61.3. SE-Deal-Blkreq-Confirm-Res-Full-MSG.xsd .....
2.61.4. SE-Deal-Blkreq-Confirm-Res-Msg.xsd .....
2.62. CreateSEBlockDeal .....
2.62.1. SE-Deal-Blkreq-Create-Req-Full-MSG.xsd .....
2.62.2. SE-Deal-Blkreq-Create-Req-Msg.xsd .....
2.62.3. SE-Deal-Blkreq-Create-Res-Full-MSG.xsd .....
2.62.4. SE-Deal-Blkreq-Create-Res-Msg.xsd .....
2.63. DeleteSEBlockDeal .....
2.63.1. SE-Deal-Blkreq-Delete-Req-Full-MSG.xsd .....
2.63.2. SE-Deal-Blkreq-Delete-Req-Msg.xsd .....
2.63.3. SE-Deal-Blkreq-Delete-Res-Full-MSG.xsd .....
2.63.4. SE-Deal-Blkreq-Delete-Res-Msg.xsd .....
2.64. LiquidateSEBlockDeal .....
2.64.1. SE-Deal-Blkreq-Liquidate-Req-Full-MSG.xsd .....
2.64.2. SE-Deal-Blkreq-Liquidate-Req-Msg.xsd .....
2.64.3. SE-Deal-Blkreq-Liquidate-Res-Full-MSG.xsd .....
2.64.4. SE-Deal-Blkreq-Liquidate-Res-Msg.xsd .....
2.65. AmendSEBlockDeal .....
2.65.1. SE-Deal-Blkreq-Modify-Req-Full-MSG.xsd .....
2.65.2. SE-Deal-Blkreq-Modify-Req-Msg.xsd .....
2.65.3. SE-Deal-Blkreq-Modify-Res-Full-MSG.xsd .....
2.65.4. SE-Deal-Blkreq-Modify-Res-Msg.xsd .....
2.66. QuerySEBlockDeal .....
2.66.1. SE-Deal-Blkreq-Query-Req-Msg.xsd .....
2.66.2. SE-Deal-Blkreq-Query-Res-Full-MSG.xsd .....
2.67. ReverseSEBlockDeal .....
2.67.1. SE-Deal-Blkreq-Reverse-Req-Full-MSG.xsd .....
2.67.2. SE-Deal-Blkreq-Reverse-Req-Msg.xsd .....
2.67.3. SE-Deal-Blkreq-Reverse-Res-Full-MSG.xsd .....
2.67.4. SE-Deal-Blkreq-Reverse-Res-Msg.xsd .....
2.68. CloseSEDeal .....
2.68.1. SE-Deal-Close-Req-Full-MSG.xsd .....
2.68.2. SE-Deal-Close-Req-Msg.xsd .....
2.68.3. SE-Deal-Close-Res-Full-MSG.xsd .....
2.68.4. SE-Deal-Close-Res-Msg.xsd .....
2.69. ConfirmSEDeal .....
2.69.1. SE-Deal-Confirm-Req-Full-Msg.xsd .....
2.69.2. SE-Deal-Confirm-Req-Msg.xsd .....
2.69.3. SE-Deal-Confirm-Res-Full-Msg.xsd .....
2.69.4. SE-Deal-Confirm-Res-Msg.xsd .....
2.70. CancelSEDeal .....
2.70.1. SE-Deal-Reverse-Req-Full-MSG.xsd .....
2.70.2. SE-Deal-Reverse-Req-Msg.xsd .....
2.70.3. SE-Deal-Reverse-Res-Full-MSG.xsd .....
2.70.4. SE-Deal-Reverse-Res-Msg.xsd .....
2.71. RolloverSEDeal .....

2.71.1. SE-Deal-Rollover-Req-Full-Msg.xsd .....
2.71.2. SE-Deal-Rollover-Req-Msg.xsd .....
2.71.3. SE-Deal-Rollover-Res-Full-Msg.xsd .....
2.71.4. SE-Deal-Rollover-Res-Msg.xsd .....
2.72. DeleteMarketCode .....
2.72.1. SE-DeleteMarketCode-Req-Full-MSG.xsd .....
2.72.2. SE-DeleteMarketCode-Req-IO-MSG.xsd .....
2.72.3. SE-DeleteMarketCode-Res-Full-MSG.xsd .....
2.72.4. SE-DeleteMarketCode-Res-PK-MSG.xsd .....
2.73. DeletePriceDtl .....
2.73.1. SE-DeletePriceDtl-Req-Full-MSG.xsd .....
2.73.2. SE-DeletePriceDtl-Req-IO-MSG.xsd .....
2.73.3. SE-DeletePriceDtl-Res-Full-MSG.xsd .....
2.73.4. SE-DeletePriceDtl-Res-PK-MSG.xsd .....
2.74. DeleteRecord .....
2.74.1. SE-DeleteRecord-Req-Full-MSG.xsd .....
2.74.2. SE-DeleteRecord-Req-IO-MSG.xsd .....
2.74.3. SE-DeleteRecord-Res-Full-MSG.xsd .....
2.74.4. SE-DeleteRecord-Res-PK-MSG.xsd .....
2.75. DeleteSEMarketCode .....
2.75.1. SE-DeleteSEMarketCode-Req-Full-MSG.xsd .....
2.75.2. SE-DeleteSEMarketCode-Req-IO-MSG.xsd .....
2.75.3. SE-DeleteSEMarketCode-Res-Full-MSG.xsd .....
2.75.4. SE-DeleteSEMarketCode-Res-PK-MSG.xsd .....
2.76. DeleteSEMarketPriceCodes .....
2.76.1. SE-DeleteSEMarketPriceCodes-Req-Full-MSG.xsd .....
2.76.2. SE-DeleteSEMarketPriceCodes-Req-IO-MSG.xsd .....
2.76.3. SE-DeleteSEMarketPriceCodes-Res-Full-MSG.xsd .....
2.76.4. SE-DeleteSEMarketPriceCodes-Res-PK-MSG.xsd .....
2.77. DeleteSEPriceDetail .....
2.77.1. SE-DeleteSEPriceDetail-Req-Full-MSG.xsd .....
2.77.2. SE-DeleteSEPriceDetail-Req-IO-MSG.xsd .....
2.77.3. SE-DeleteSEPriceDetail-Res-Full-MSG.xsd .....
2.77.4. SE-DeleteSEPriceDetail-Res-PK-MSG.xsd .....
2.78. DeleteSESKLocationChange .....
2.78.1. SE-DeleteSESKLocationChange-Req-Full-MSG.xsd .....
2.78.2. SE-DeleteSESKLocationChange-Req-IO-MSG.xsd .....
2.78.3. SE-DeleteSESKLocationChange-Res-Full-MSG.xsd .....
2.78.4. SE-DeleteSESKLocationChange-Res-PK-MSG.xsd .....
2.79. DeleteSESKLocationMaint .....
2.79.1. SE-DeleteSESKLocationMaint-Req-Full-MSG.xsd .....
2.79.2. SE-DeleteSESKLocationMaint-Req-IO-MSG.xsd .....
2.79.3. SE-DeleteSESKLocationMaint-Res-Full-MSG.xsd .....
2.79.4. SE-DeleteSESKLocationMaint-Res-PK-MSG.xsd .....
2.80. DeleteSKLocationMaint .....
2.80.1. SE-DeleteSKLocationMaint-Req-Full-MSG.xsd .....
2.80.2. SE-DeleteSKLocationMaint-Req-IO-MSG.xsd .....
2.80.3. SE-DeleteSKLocationMaint-Res-Full-MSG.xsd .....
2.80.4. SE-DeleteSKLocationMaint-Res-PK-MSG.xsd .....
2.81. ModifyMarketCode .....
2.81.1. SE-ModifyMarketCode-Req-Full-MSG.xsd .....
2.81.2. SE-ModifyMarketCode-Req-IO-MSG.xsd .....
2.81.3. SE-ModifyMarketCode-Res-Full-MSG.xsd .....
2.81.4. SE-ModifyMarketCode-Res-PK-MSG.xsd .....
2.82. ModifyPriceDtl .....
2.82.1. SE-ModifyPriceDtl-Req-Full-MSG.xsd .....
2.82.2. SE-ModifyPriceDtl-Req-IO-MSG.xsd .....
2.82.3. SE-ModifyPriceDtl-Res-Full-MSG.xsd .....

2.82.4. SE-ModifyPriceDtl-Res-PK-MSG.xsd .....
2.83. ModifyRecord .....
2.83.1. SE-ModifyRecord-Req-Full-MSG.xsd .....
2.83.2. SE-ModifyRecord-Req-IO-MSG.xsd .....
2.83.3. SE-ModifyRecord-Res-Full-MSG.xsd .....
2.83.4. SE-ModifyRecord-Res-PK-MSG.xsd .....
2.84. ModifySEMarketCode .....
2.84.1. SE-ModifySEMarketCode-Req-Full-MSG.xsd .....
2.84.2. SE-ModifySEMarketCode-Req-IO-MSG.xsd .....
2.84.3. SE-ModifySEMarketCode-Res-Full-MSG.xsd .....
2.84.4. SE-ModifySEMarketCode-Res-PK-MSG.xsd .....
2.85. ModifySEMarketPriceCodes .....
2.85.1. SE-ModifySEMarketPriceCodes-Req-Full-MSG.xsd .....
2.85.2. SE-ModifySEMarketPriceCodes-Req-IO-MSG.xsd .....
2.85.3. SE-ModifySEMarketPriceCodes-Res-Full-MSG.xsd .....
2.85.4. SE-ModifySEMarketPriceCodes-Res-PK-MSG.xsd .....
2.86. ModifySEPriceDetail .....
2.86.1. SE-ModifySEPriceDetail-Req-Full-MSG.xsd .....
2.86.2. SE-ModifySEPriceDetail-Req-IO-MSG.xsd .....
2.86.3. SE-ModifySEPriceDetail-Res-Full-MSG.xsd .....
2.86.4. SE-ModifySEPriceDetail-Res-PK-MSG.xsd .....
2.87. ModifySESKLocationChange .....
2.87.1. SE-ModifySESKLocationChange-Req-Full-MSG.xsd .....
2.87.2. SE-ModifySESKLocationChange-Req-IO-MSG.xsd .....
2.87.3. SE-ModifySESKLocationChange-Res-Full-MSG.xsd .....
2.87.4. SE-ModifySESKLocationChange-Res-PK-MSG.xsd .....
2.88. ModifySESKLocationMaint .....
2.88.1. SE-ModifySESKLocationMaint-Req-Full-MSG.xsd .....
2.88.2. SE-ModifySESKLocationMaint-Req-IO-MSG.xsd .....
2.88.3. SE-ModifySESKLocationMaint-Res-Full-MSG.xsd .....
2.88.4. SE-ModifySESKLocationMaint-Res-PK-MSG.xsd .....
2.89. ModifySKLocationMaint .....
2.89.1. SE-ModifySKLocationMaint-Req-Full-MSG.xsd .....
2.89.2. SE-ModifySKLocationMaint-Req-IO-MSG.xsd .....
2.89.3. SE-ModifySKLocationMaint-Res-Full-MSG.xsd .....
2.89.4. SE-ModifySKLocationMaint-Res-PK-MSG.xsd .....
2.90. AuthorizeSEPortfolio .....
2.90.1. SE-Portfolio-Authorize-Req-Full-MSG.xsd .....
2.90.2. SE-Portfolio-Authorize-Req-MSG.xsd .....
2.90.3. SE-Portfolio-Authorize-Res-Full-MSG.xsd .....
2.90.4. SE-Portfolio-Authorize-Res-MSG.xsd .....
2.91. CloseSEPortfolio .....
2.91.1. SE-Portfolio-Close-Req-Full-MSG.xsd .....
2.91.2. SE-Portfolio-Close-Req-MSG.xsd .....
2.91.3. SE-Portfolio-Close-Res-Full-MSG.xsd .....
2.91.4. SE-Portfolio-Close-Res-MSG.xsd .....
2.92. CreateSEPortfolio .....
2.92.1. SE-Portfolio-Create-Req-Full-MSG.xsd .....
2.92.2. SE-Portfolio-Create-Req-MSG.xsd .....
2.92.3. SE-Portfolio-Create-Res-Full-MSG.xsd .....
2.92.4. SE-Portfolio-Create-Res-MSG.xsd .....
2.93. DeleteSEPortfolio .....
2.93.1. SE-Portfolio-Delete-Req-Full-MSG.xsd .....
2.93.2. SE-Portfolio-Delete-Req-MSG.xsd .....
2.93.3. SE-Portfolio-Delete-Res-Full-MSG.xsd .....
2.93.4. SE-Portfolio-Delete-Res-MSG.xsd .....
2.94. ModifySEPortfolio .....
2.94.1. SE-Portfolio-Modify-Req-Full-MSG.xsd .....

2.94.2. SE-Portfolio-Modify-Req-MSG.xsd .....
2.94.3. SE-Portfolio-Modify-Res-Full-MSG.xsd .....
2.94.4. SE-Portfolio-Modify-Res-MSG.xsd .....
2.95. QuerySEPortfolioSec .....
2.95.1. SE-Portfolio-Query-Req-MSG.xsd .....
2.95.2. SE-Portfolio-Query-Res-Full-MSG.xsd .....
2.96. ReopenSEPortfolio .....
2.96.1. SE-Portfolio-Reopen-Req-Full-MSG.xsd .....
2.96.2. SE-Portfolio-Reopen-Req-MSG.xsd .....
2.96.3. SE-Portfolio-Reopen-Res-Full-MSG.xsd .....
2.96.4. SE-Portfolio-Reopen-Res-MSG.xsd .....
2.97. QueryBrnPrm .....
2.97.1. SE-QueryBrnPrm-Req-IO-MSG.xsd .....
2.97.2. SE-QueryBrnPrm-Res-Full-MSG.xsd .....
2.98. QueryMarketCode .....
2.98.1. SE-QueryMarketCode-Req-IO-MSG.xsd .....
2.98.2. SE-QueryMarketCode-Res-Full-MSG.xsd .....
2.99. QueryPriceDtl .....
2.99.1. SE-QueryPriceDtl-Req-IO-MSG.xsd .....
2.99.2. SE-QueryPriceDtl-Res-Full-MSG.xsd .....
2.100. QueryRecord .....
2.100.1. SE-QueryRecord-Req-IO-MSG.xsd .....
2.100.2. SE-QueryRecord-Res-Full-MSG.xsd .....
2.101. QuerySEBrnPrm .....
2.101.1. SE-QuerySEBrnPrm-Req-IO-MSG.xsd .....
2.101.2. SE-QuerySEBrnPrm-Res-Full-MSG.xsd .....
2.102. QuerySEMarketCode .....
2.102.1. SE-QuerySEMarketCode-Req-IO-MSG.xsd .....
2.102.2. SE-QuerySEMarketCode-Res-Full-MSG.xsd .....
2.103. QuerySEMarketPriceCodes .....
2.103.1. SE-QuerySEMarketPriceCodes-Req-IO-MSG.xsd .....
2.103.2. SE-QuerySEMarketPriceCodes-Res-Full-MSG.xsd .....
2.104. QuerySEPortfolioBal .....
2.104.1. SE-QuerySEPortfolioBal-Req-IO-MSG.xsd .....
2.104.2. SE-QuerySEPortfolioBal-Res-Full-MSG.xsd .....
2.105. QuerySEPriceDetail .....
2.105.1. SE-QuerySEPriceDetail-Req-IO-MSG.xsd .....
2.105.2. SE-QuerySEPriceDetail-Res-Full-MSG.xsd .....
2.106. QuerySESKLocationChange .....
2.106.1. SE-QuerySESKLocationChange-Req-IO-MSG.xsd .....
2.106.2. SE-QuerySESKLocationChange-Res-Full-MSG.xsd .....
2.107. QuerySESKLocationMaint .....
2.107.1. SE-QuerySESKLocationMaint-Req-IO-MSG.xsd .....
2.107.2. SE-QuerySESKLocationMaint-Res-Full-MSG.xsd .....
2.108. QuerySKLocationMaint .....
2.108.1. SE-QuerySKLocationMaint-Req-IO-MSG.xsd .....
2.108.2. SE-QuerySKLocationMaint-Res-Full-MSG.xsd .....
2.109. AuthSKLocationChange .....
2.109.1. SE-SKTransfer-Auth-Req-Full-MSG.xsd .....
2.109.2. SE-SKTransfer-Auth-Req-Msg.xsd .....
2.109.3. SE-SKTransfer-Auth-Res-Full-MSG.xsd .....
2.109.4. SE-SKTransfer-Auth-Res-Msg.xsd .....
2.110. CreateSKLocationChange .....
2.110.1. SE-SKTransfer-Create-Req-Full-MSG.xsd .....
2.110.2. SE-SKTransfer-Create-Req-MSG.xsd .....
2.110.3. SE-SKTransfer-Create-Res-Full-MSG.xsd .....
2.110.4. SE-SKTransfer-Create-Res-MSG.xsd .....

2.111. DeleteSKLocationChange .....
2.111.1. SE-SKTransfer-Delete-Req-Full-MSG.xsd .....
2.111.2. SE-SKTransfer-Delete-Req-MSG.xsd .....
2.111.3. SE-SKTransfer-Delete-Res-Full-MSG.xsd .....
2.111.4. SE-SKTransfer-Delete-Res-MSG.xsd .....
2.112. ModifySKLocationChange .....
2.112.1. SE-SKTransfer-Modify-Req-Full-MSG.xsd .....
2.112.2. SE-SKTransfer-Modify-Req-MSG.xsd .....
2.112.3. SE-SKTransfer-Modify-Res-Full-MSG.xsd .....
2.112.4. SE-SKTransfer-Modify-Res-MSG.xsd .....
2.113. QuerySKLocationChange .....
2.113.1. SE-SKTransfer-Query-Req-MSG.xsd .....
2.113.2. SE-SKTransfer-Query-Res-Full-MSG.xsd .....
2.114. AuthSEInstrument .....
2.114.1. SEInstrument-Auth-Req-Full-MSG.xsd .....
2.114.2. SEInstrument-Auth-Req-MSG.xsd .....
2.114.3. SEInstrument-Auth-Res-Full-MSG.xsd .....
2.114.4. SEInstrument-Auth-Res-MSG.xsd .....
2.115. CloseSEInstrument .....
2.115.1. SEInstrument-Close-Req-Full-MSG.xsd .....
2.115.2. SEInstrument-Close-Req-MSG.xsd .....
2.115.3. SEInstrument-Close-Res-Full-MSG.xsd .....
2.115.4. SEInstrument-Close-Res-MSG.xsd .....
2.116. CreateSEInstrument .....
2.116.1. SEInstrument-Create-Req-Full-MSG.xsd .....
2.116.2. SEInstrument-Create-Req-MSG.xsd .....
2.116.3. SEInstrument-Create-Res-Full-MSG.xsd .....
2.116.4. SEInstrument-Create-Res-MSG.xsd .....
2.117. ModifySEInstrument .....
2.117.1. SEInstrument-Modify-Req-Full-MSG.xsd .....
2.117.2. SEInstrument-Modify-Req-MSG.xsd .....
2.117.3. SEInstrument-Modify-Res-Full-MSG.xsd .....
2.117.4. SEInstrument-Modify-Res-MSG.xsd .....
2.118. QuerySEInstr .....
2.118.1. SEInstrument-Query-Req-MSG.xsd .....
2.118.2. SEInstrument-Query-Res-Full-MSG.xsd .....
2.119. ReopenSEInstrument .....
2.119.1. SEInstrument-Reopen-Req-Full-MSG.xsd .....
2.119.2. SEInstrument-Reopen-Req-MSG.xsd .....
2.119.3. SEInstrument-Reopen-Res-Full-MSG.xsd .....
2.119.4. SEInstrument-Reopen-Res-MSG.xsd .....
2.120. DeleteSEInstrument .....
2.120.1. SEInstrument-delete-Req-Full-MSG.xsd .....
2.120.2. SEInstrument-delete-Req-MSG.xsd .....
2.120.3. SEInstrument-delete-Res-Full-MSG.xsd .....
2.120.4. SEInstrument-delete-Res-MSG.xsd .....
2.121. AuthorizePortfolioProduct .....
2.121.1. SP-AuthorizePortfolioProduct-Req-Full-MSG.xsd .....
2.121.2. SP-AuthorizePortfolioProduct-Req-IO-MSG.xsd .....
2.121.3. SP-AuthorizePortfolioProduct-Res-Full-MSG.xsd .....
2.121.4. SP-AuthorizePortfolioProduct-Res-PK-MSG.xsd .....
2.122. AuthorizeSecuritiesPortfolio .....
2.122.1. SP-AuthorizeSecuritiesPortfolio-Req-Full-MSG.xsd .....
2.122.2. SP-AuthorizeSecuritiesPortfolio-Req-IO-MSG.xsd .....
2.122.3. SP-AuthorizeSecuritiesPortfolio-Res-Full-MSG.xsd .....
2.122.4. SP-AuthorizeSecuritiesPortfolio-Res-PK-MSG.xsd .....
2.123. CloseSecuritiesPortfolio .....

2.123.1. SP-CloseSecuritiesPortfolio-Req-Full-MSG.xsd .....
2.123.2. SP-CloseSecuritiesPortfolio-Req-IO-MSG.xsd .....
2.123.3. SP-CloseSecuritiesPortfolio-Res-Full-MSG.xsd .....
2.123.4. SP-CloseSecuritiesPortfolio-Res-PK-MSG.xsd .....
2.124. CreatePortfolioProduct .....
2.124.1. SP-CreatePortfolioProduct-Req-Full-MSG.xsd .....
2.124.2. SP-CreatePortfolioProduct-Req-IO-MSG.xsd .....
2.124.3. SP-CreatePortfolioProduct-Res-Full-MSG.xsd .....
2.124.4. SP-CreatePortfolioProduct-Res-PK-MSG.xsd .....
2.125. CreateSecuritiesPortfolio .....
2.125.1. SP-CreateSecuritiesPortfolio-Req-Full-MSG.xsd .....
2.125.2. SP-CreateSecuritiesPortfolio-Req-IO-MSG.xsd .....
2.125.3. SP-CreateSecuritiesPortfolio-Res-Full-MSG.xsd .....
2.125.4. SP-CreateSecuritiesPortfolio-Res-PK-MSG.xsd .....
2.126. DeletePortfolioProduct .....
2.126.1. SP-DeletePortfolioProduct-Req-Full-MSG.xsd .....
2.126.2. SP-DeletePortfolioProduct-Req-IO-MSG.xsd .....
2.126.3. SP-DeletePortfolioProduct-Res-Full-MSG.xsd .....
2.126.4. SP-DeletePortfolioProduct-Res-PK-MSG.xsd .....
2.127. DeleteSecuritiesPortfolio .....
2.127.1. SP-DeleteSecuritiesPortfolio-Req-Full-MSG.xsd .....
2.127.2. SP-DeleteSecuritiesPortfolio-Req-IO-MSG.xsd .....
2.127.3. SP-DeleteSecuritiesPortfolio-Res-Full-MSG.xsd .....
2.127.4. SP-DeleteSecuritiesPortfolio-Res-PK-MSG.xsd .....
2.128. ModifyPortfolioProduct .....
2.128.1. SP-ModifyPortfolioProduct-Req-Full-MSG.xsd .....
2.128.2. SP-ModifyPortfolioProduct-Req-IO-MSG.xsd .....
2.128.3. SP-ModifyPortfolioProduct-Res-Full-MSG.xsd .....
2.128.4. SP-ModifyPortfolioProduct-Res-PK-MSG.xsd .....
2.129. ModifySecuritiesPortfolio .....
2.129.1. SP-ModifySecuritiesPortfolio-Req-Full-MSG.xsd .....
2.129.2. SP-ModifySecuritiesPortfolio-Req-IO-MSG.xsd .....
2.129.3. SP-ModifySecuritiesPortfolio-Res-Full-MSG.xsd .....
2.129.4. SP-ModifySecuritiesPortfolio-Res-PK-MSG.xsd .....
2.130. QueryPortfolioProduct .....
2.130.1. SP-QueryPortfolioProduct-Req-IO-MSG.xsd .....
2.130.2. SP-QueryPortfolioProduct-Res-Full-MSG.xsd .....
2.131. QuerySEBonusDefn .....
2.131.1. SP-QuerySEBonusDefn-Req-IO-MSG.xsd .....
2.131.2. SP-QuerySEBonusDefn-Res-Full-MSG.xsd .....
2.132. QuerySECashDefinition .....
2.132.1. SP-QuerySECashDefinition-Req-IO-MSG.xsd .....
2.132.2. SP-QuerySECashDefinition-Res-Full-MSG.xsd .....
2.133. QuerySECashDefn .....
2.133.1. SP-QuerySECashDefn-Req-IO-MSG.xsd .....
2.133.2. SP-QuerySECashDefn-Res-Full-MSG.xsd .....
2.134. QuerySECouponDefn .....
2.134.1. SP-QuerySECouponDefn-Req-IO-MSG.xsd .....
2.134.2. SP-QuerySECouponDefn-Res-Full-MSG.xsd .....
2.135. QuerySECpnDefinition .....
2.135.1. SP-QuerySECpnDefinition-Req-IO-MSG.xsd .....
2.135.2. SP-QuerySECpnDefinition-Res-Full-MSG.xsd .....
2.136. QuerySECpnDividend .....
2.136.1. SP-QuerySECpnDividend-Req-IO-MSG.xsd .....
2.136.2. SP-QuerySECpnDividend-Res-Full-MSG.xsd .....
2.137. QuerySEDividend .....
2.137.1. SP-QuerySEDividend-Req-IO-MSG.xsd .....

2.137.2. SP-QuerySEDividend-Res-Full-MSG.xsd .....
2.138. QuerySEIntRateRevision .....
2.138.1. SP-QuerySEIntRateRevision-Req-IO-MSG.xsd .....
2.138.2. SP-QuerySEIntRateRevision-Res-Full-MSG.xsd .....
2.139. QuerySERWExpiry .....
2.139.1. SP-QuerySERWExpiry-Req-IO-MSG.xsd .....
2.139.2. SP-QuerySERWExpiry-Res-Full-MSG.xsd .....
2.140. QuerySERateRevision .....
2.140.1. SP-QuerySERateRevision-Req-IO-MSG.xsd .....
2.140.2. SP-QuerySERateRevision-Res-Full-MSG.xsd .....
2.141. QuerySERedemptionDefn .....
2.141.1. SP-QuerySERedemptionDefn-Req-IO-MSG.xsd .....
2.141.2. SP-QuerySERedemptionDefn-Res-Full-MSG.xsd .....
2.142. QuerySERedmDefn .....
2.142.1. SP-QuerySERedmDefn-Req-IO-MSG.xsd .....
2.142.2. SP-QuerySERedmDefn-Res-Full-MSG.xsd .....
2.143. QuerySecuritiesPortfolio .....
2.143.1. SP-QuerySecuritiesPortfolio-Req-IO-MSG.xsd .....
2.143.2. SP-QuerySecuritiesPortfolio-Res-Full-MSG.xsd .....
2.144. ReopenSecuritiesPortfolio .....
2.144.1. SP-ReopenSecuritiesPortfolio-Req-Full-MSG.xsd .....
2.144.2. SP-ReopenSecuritiesPortfolio-Req-IO-MSG.xsd .....
2.144.3. SP-ReopenSecuritiesPortfolio-Res-Full-MSG.xsd .....
2.144.4. SP-ReopenSecuritiesPortfolio-Res-PK-MSG.xsd .....
2.145. AuthorizeSecInstrument .....
2.145.1. SS-AuthorizeSecInstrument-Req-Full-MSG.xsd .....
2.145.2. SS-AuthorizeSecInstrument-Req-IO-MSG.xsd .....
2.145.3. SS-AuthorizeSecInstrument-Res-Full-MSG.xsd .....
2.145.4. SS-AuthorizeSecInstrument-Res-PK-MSG.xsd .....
2.146. AuthorizeSecurityProduct .....
2.146.1. SS-AuthorizeSecurityProduct-Req-Full-MSG.xsd .....
2.146.2. SS-AuthorizeSecurityProduct-Req-IO-MSG.xsd .....
2.146.3. SS-AuthorizeSecurityProduct-Res-Full-MSG.xsd .....
2.146.4. SS-AuthorizeSecurityProduct-Res-PK-MSG.xsd .....
2.147. CloseSecInstrument .....
2.147.1. SS-CloseSecInstrument-Req-Full-MSG.xsd .....
2.147.2. SS-CloseSecInstrument-Req-IO-MSG.xsd .....
2.147.3. SS-CloseSecInstrument-Res-Full-MSG.xsd .....
2.147.4. SS-CloseSecInstrument-Res-PK-MSG.xsd .....
2.148. CreateSecInstrument .....
2.148.1. SS-CreateSecInstrument-Req-Full-MSG.xsd .....
2.148.2. SS-CreateSecInstrument-Req-IO-MSG.xsd .....
2.148.3. SS-CreateSecInstrument-Res-Full-MSG.xsd .....
2.148.4. SS-CreateSecInstrument-Res-PK-MSG.xsd .....
2.149. CreateSecurityProduct .....
2.149.1. SS-CreateSecurityProduct-Req-Full-MSG.xsd .....
2.149.2. SS-CreateSecurityProduct-Req-IO-MSG.xsd .....
2.149.3. SS-CreateSecurityProduct-Res-Full-MSG.xsd .....
2.149.4. SS-CreateSecurityProduct-Res-PK-MSG.xsd .....
2.150. DeleteSecInstrument .....
2.150.1. SS-DeleteSecInstrument-Req-Full-MSG.xsd .....
2.150.2. SS-DeleteSecInstrument-Req-IO-MSG.xsd .....
2.150.3. SS-DeleteSecInstrument-Res-Full-MSG.xsd .....
2.150.4. SS-DeleteSecInstrument-Res-PK-MSG.xsd .....
2.151. DeleteSecurityProduct .....
2.151.1. SS-DeleteSecurityProduct-Req-Full-MSG.xsd .....
2.151.2. SS-DeleteSecurityProduct-Req-IO-MSG.xsd .....

2.151.3. SS-DeleteSecurityProduct-Res-Full-MSG.xsd .....
2.151.4. SS-DeleteSecurityProduct-Res-PK-MSG.xsd .....
2.152. ModifySecInstrument .....
2.152.1. SS-ModifySecInstrument-Req-Full-MSG.xsd .....
2.152.2. SS-ModifySecInstrument-Req-IO-MSG.xsd .....
2.152.3. SS-ModifySecInstrument-Res-Full-MSG.xsd .....
2.152.4. SS-ModifySecInstrument-Res-PK-MSG.xsd .....
2.153. ModifySecurityProduct .....
2.153.1. SS-ModifySecurityProduct-Req-Full-MSG.xsd .....
2.153.2. SS-ModifySecurityProduct-Req-IO-MSG.xsd .....
2.153.3. SS-ModifySecurityProduct-Res-Full-MSG.xsd .....
2.153.4. SS-ModifySecurityProduct-Res-PK-MSG.xsd .....
2.154. QuerySecInstrument .....
2.154.1. SS-QuerySecInstrument-Req-IO-MSG.xsd .....
2.154.2. SS-QuerySecInstrument-Res-Full-MSG.xsd .....
2.155. QuerySecurityProduct .....
2.155.1. SS-QuerySecurityProduct-Req-IO-MSG.xsd .....
2.155.2. SS-QuerySecurityProduct-Res-Full-MSG.xsd .....
2.156. ReopenSecInstrument .....
2.156.1. SS-ReopenSecInstrument-Req-Full-MSG.xsd .....
2.156.2. SS-ReopenSecInstrument-Req-IO-MSG.xsd .....
2.156.3. SS-ReopenSecInstrument-Res-Full-MSG.xsd .....
2.156.4. SS-ReopenSecInstrument-Res-PK-MSG.xsd .....

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSSecuritiesService of SE-Module

2.FCUBSSecuritiesService

Securities ServiceSecurities Service

2.1.AuthorizeDealProduct

Authorization of SD Product Definition

2.1.1.SD-AuthorizeDealProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*

PRDTYPDESC
PRODGRPDESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link

- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr

- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions

- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access

- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr

- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access

- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr

- *CODE*
- *PRDDESC*

Tatms-Product-Scheme

- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*

- *DFLTRULE*
- *RULEDESC*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*

- GENTIME
- SUPRS
- PRIOR
- CHGREQD

Role-To-Head-Mapping
- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Branch-Ccy-Restrictions
- CCYLST
- BRNLST
- CLASCD
- CLASDESC
- Branch-List
  - BRNDISALOW
  - BRNNAME
- Ccy-List
  - BGTDLCCY
  - CCYNAME

Prod-Cust-Restrictions
- CATGLIS
- CLASCD
- Cust-Categories
  - CATGDSAW
  - DESCRIPTION
- Customers
  - CSTID
  - CUSTNAME
  - ALWD

Product-Mis-Details
- MISGRP
- POOLCD
- CSTCD1
- CSTCD2
- CSTCD4
- CSTCD5
- Default-Mis-Codes
  - MISCLS
  - MISCD

Product-Charges

Charge-Details

CHGTYP

THRDPTYTY

DRCRTYPE

NTCNSINDI

NETCONSPLSMINS

SWIFTQLF

SETTCCY

DFTWAIV

ALWRULAMND

AMNDAFTRASSOC

ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

CAPTLIZE

DISCACCRAPLB

PROPREQD

DISCNTBASIS

DFTRULE

COMPNT

EVNTFRASSC

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	**Description**	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	**Description**	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	**Description**	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	**Description**	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOCC1

Attribute	**Description**	
Name	SKLOCC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC1

Attribute	**Description**	
Name	SKACNTC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOCC2

Attribute	**Description**	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.1.2.SD-AuthorizeDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.1.3.SD-AuthorizeDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*

- *CLASDESC*

Dealproduct-Restrictions

- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access

- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr

- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access

- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr

- *CODE*
- *PRDDESC*

Tatms-Product-Scheme

- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*
  - *ALLWRULAMND*
  - *AMNDAFTRASSN*
  - *ALLWAMTAMND*

- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*

SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFID

Attribute	Description	
Name	PFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOMINLUNIT

Attribute	Description	
Name	NOMINLUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTCD

Attribute	Description	
Name	MRKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FRPAY

Attribute	Description	
Name	FRPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F,</td></tr></table>

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALWDSR

Attribute	Description

Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.1.4.SD-AuthorizeDealProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-PK*
      - *PRDCD*
    - *Cstms-Product-IO*
      - *PRDCD*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.AuthorizeSEDealBlockRelease

AuthorizeSEDealBlockRelease

2.2.1.SD-AuthorizeSEDealBlockRelease-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*

BLKREF
SEDSC
PRDDSC
ONCAUTH
Sdd
  PF
  PFDSC
  COUNTRPTY
  SKLC
  SKAC
  SKLOCDSC
  FRMTYP
  EVSQNO
  VRSN
Scd
  DLRFNO
Scd--A
  CRTNO
  QTYTOBLK
  STATS
Sdl
  MKID
  MKDTSTMP
  CKID
  CKDTSTMP
  TXNSTAT
  AUTHSTAT
Csvws-Contract-En
  LEGREFNO
  Sevws-Event-Log
    REFERENCE
    SR_NO
    EVENT
    EVENT_DATE
    MAKER_ID
    MAKER_DT_STAMP
    CHECKER_ID
    CHECKER_DT_STAMP
    Acvws-All-Ac-Entries
      BRANCH
      ACCOUNT
      DR_CR
      CODE
      DATE

VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BLKTYP

Attribute	Description
Name	BLKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLKREF

Attribute	Description
Name	BLKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SEDSC

Attribute	Description
Name	SEDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPTY

Attribute	**Description**	
Name	COUNTRPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLC

Attribute	**Description**	
Name	SKLC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKAC

Attribute	**Description**	
Name	SKAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCDSC

Attribute	**Description**	
Name	SKLOCDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description	
Name	FRMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I

TOP

EVSQNO

Attribute	Description	
Name	EVSQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VRSN

Attribute	Description	
Name	VRSN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Scd

Attribute	Description	
Name	Scd	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DLRFNO

Attribute	Description	
Name	DLRFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sdl

Attribute	Description

Name	Sdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER_ID

Attribute	**Description**	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	**Description**
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	**Description**
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	**Description**
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	**Description**
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.2.2.SD-AuthorizeSEDealBlockRelease-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-IO*
    - *DLRF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.2.3.SD-AuthorizeSEDealBlockRelease-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*
    - *BLKREF*
    - *SEDSC*
    - *PRDDSC*

ONCAUTH

Sdd

- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd

- *DLRFNO*

Scd--A

- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl

- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En

- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*
    - *VALDT*
    - *CCY*
    - *FCY_AMOUNT*

EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLQTY

Attribute	**Description**	
Name	DLQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BLKTYP

Attribute	**Description**	
Name	BLKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BLKREF

Attribute	**Description**	
Name	BLKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SEDSC

Attribute	**Description**	
Name	SEDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sdl

Attribute	Description
Name	Sdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description

Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**

Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.SD-AuthorizeSEDealBlockRelease-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Sdm-PK*
    - *DLRF*
  - *Sdm-IO*
    - *DLRF*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sdm-PK

Attribute	Description
Name	Sdm-PK
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.3.AuthorizeSecBlockDeal

AuthorizeSecBlockDeal

2.3.1.SD-AuthorizeSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

2.3.2.SD-AuthorizeSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.3.3.SD-AuthorizeSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.4.SD-AuthorizeSecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.4.AuthorizeSecuritiesDeal

AuthorizeSecuritiesDeal

2.4.1.SD-AuthorizeSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinto
- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Dealmastera

DEALREF

Ytmmaster

DEALREF

EFFDT

YTM

Certificates

DEALREF

CERTNO

CERTQT

UNIT_NOM_QUOTE

Dealmasterb

DEALREF

Contract

SERIAL

ESN

UREF

LATVERNO

PRDCODE

CPTY

TEMPSTAT

PRDTYPE

CEC

MDCODE

UDSTAT

CONTCCY

LEVENTDT

XREF

AMFLAG

FREFNO

RESPSTAT

SECUPDSTAT

STOPDT

LIBCIF

SRC

REFERCREF

Multiref

VERNO

LEGREFNO

Brokerage

CONREFNO

BOKBROKER

BROKAMT

BROKCCY

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORIGINALINTERESTAMOUNT

Attribute	**Description**	
Name	ORIGINALINTERESTAMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORIGINALPRICE

Attribute	**Description**	
Name	ORIGINALPRICE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BAREF

Attribute	**Description**	
Name	BAREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DEALTIME

Attribute	**Description**	
Name	DEALTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRD

Attribute	**Description**
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	**Description**
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	**Description**
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	**Description**
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	**Description**

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	Description	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description	
Name	Acvws-All-Ac-Entries	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.4.2.SD-AuthorizeSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.4.3.SD-AuthorizeSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- LEGREF
- CPTY
- UNEXPOSURE
- TOTEXPOSURE
- CLEANRISKLIMIT
- PSTLRISKLIMIT

Walkinfrom

- LEGREF
- WALKINNAME
- WALKINMEDIA
- ADDRLINE1
- ADDRLINE2
- ADDRLINE3
- ADDRLINE4

Detalto

- BRANCH
- DEALREF
- LGPRDCODE
- LEGREF
- LEGUSERREF
- VERSION
- EVENTCODE
- MSTLDT
- AUTOMSTL
- ORGMSTLDT
- MSTLCOMPLETED
- DEALER
- PORTREF
- PORTFOLIO
- POSITIONREFNO
- CPTY
- NETCONSIDERATION
- PCY
- PAYBRNTO
- PAYACCTO
- ACMP_WDRW
- SKACC
- FRMTYPFROM
- SKLOCTO
- SKACCTO
- FRMTYPTO
- BRKPKPDONE
- CHARGEPKPDONE
- INTREFERDONE

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP

CRRATEESN

RULE

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

Csvws-Contract

LEGREFNO

Csvws-Contract-Event-Seq

EVTCODE

EVENT_SEQ_NO

DESCRIPTION

Csvws-Contract-Event-Advice

ADVCD

SUPPRESS

PRIORITY

PRTYID

PRTYNAME

ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN
Dlintr
CMPNTDSC
COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,S

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.4.SD-AuthorizeSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.CloseDealProduct

CloseDealProduct

2.5.1.SD-CloseDealProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions
- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access
- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr
- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access
- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr
- *CODE*
- *PRDDESC*

Tatms-Product-Scheme
- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*

- ALLWRULAMND
- AMNDAFTRASSN
- ALLWAMTAMND
- AMNDAFTRAPPLN
- Rule-Mkt-Tax-Dtls
  - RULE
  - MARKET_CODE
- Product-Charges-Mkt
  - PRDCD
  - PRDDESC
  - Rule-Mkt-Chg-Dtls
    - COMPONENT
    - MRKTCD
    - RULE
- Product-Fields
  - Field-Details
    - FLDNUM
    - FLDNAME
- Product-Events
  - CLASCD
  - CLASDESC
  - Event-Details
    - EVNTCD
    - EVENTDESC
    - Accounting-Entries
      - ACCRLCD
      - AMTTAG
      - DRCRINDICTR
      - TRNCD
      - NETINDICTR
      - MISHD
      - REVALPRGL
      - REVALLSGL
      - REVALRTCD
      - REVALTXNCD
      - HOLTREAT
      - REVALREQD
      - RATE_TYPE_INDICATOR
    - Advices
      - MSGTYP
      - DESC
      - GENTIME
      - SUPRS
      - PRIOR

CHGREQD

Role-To-Head-Mapping

CLASCD

CLASDESC

Mapping-Details

ACCTRL

ROLDESC

ACCTHD

GLDESC

Branch-Ccy-Restrictions

CCYLST

BRNLST

CLASCD

CLASDESC

Branch-List

BRNDISALOW

BRNNAME

Ccy-List

BGTDLCCY

CCYNAME

Prod-Cust-Restrictions

CATGLIS

CLASCD

Cust-Categories

CATGDSAW

DESCRIPTION

Customers

CSTID

CUSTNAME

ALWD

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISCLS

MISCD

Product-Charges

Charge-Details

CHGTYP

THRDPTYTY

DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	**Description**	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	**Description**	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	**Description**	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	**Description**	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	Description	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	Description	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	Description	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOCC1

Attribute	**Description**	
Name	SKLOCC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC1

Attribute	**Description**	
Name	SKACNTC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOCC2

Attribute	**Description**	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWAMTAMND

Attribute	Description	
Name	ALLWAMTAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description	
Name	Rule-Mkt-Tax-Dtls	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	Description	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	Description	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.5.2.SD-CloseDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.5.3.SD-CloseDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*

- CLASDESC
- Dealproduct-Restrictions
  - CODE
  - PRDDESC
- Setms-Dealprod-Security-Access
  - SECURTYIDSR
  - PRDSR
  - SECURTYDESC
  - ALWDSR
- Cstms-Product-Class-Link-Dr
  - CLASCD
  - PFRESCTYPE
  - CLASDESC
- Setms-Dealprod-Pfolios-Access
  - PFID
  - PFPRODCD
  - PFDESC
  - ACSALWDFLG
- Setms-Dealproduct-Restrictions-Dr
  - CODE
  - PRDDESC
- Tatms-Product-Scheme
  - PRDORMRKTCD
  - SCHME
  - SCHMEDESC
  - Tatms-Product-Tran-Tax
    - COMP
    - STPASSN
    - TAXTYP
    - BORNBY
    - CASHOUTFLWINDI
    - NETCONSINDI
    - CONSPLUSMIN
    - SWFTQUAL
    - EVNTASSN
    - EVNTAPPLN
    - EVNTLIQDN
    - BASAMTTAG
    - DFLTRULE
    - RULEDESC
    - DFLTWAIV
    - ALLWRULAMND
    - AMNDAFTRASSN
    - ALLWAMTAMND

- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*

SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F,</td></tr></table>

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALWDSR

Attribute	Description

Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWAMTAMND

Attribute	Description	
Name	ALLWAMTAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description	
Name	Rule-Mkt-Tax-Dtls	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Cstms-Product-PK*
    - *PRDCD*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.CloseSecBlockDeal

CloseSecBlockDeal

2.6.1.SD-CloseSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

2.6.2.SD-CloseSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.6.3.SD-CloseSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	Description	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	Description	
Name	DLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.4.SD-CloseSecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.7.CloseSecuritiesDeal

CloseSecuritiesDeal

2.7.1.SD-CloseSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
  LEGREF
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSDISCOUNT

Attribute	Description	
Name	ABSDISCOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORWDPL

Attribute	Description	
Name	FORWDPL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADJDEALPRC

Attribute	Description	
Name	ADJDEALPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ABSPRICE

Attribute	Description	
Name	ABSPRICE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	Description	
Name	INTDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.7.2.SD-CloseSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
    - *Brokerage*
      - *CONREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Misdetails*
      - *CONREFNO*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *Csvws-Contract*
      - *LEGREFNO*
    - *Csvws-Contract-En*
      - *LEGREFNO*

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract

Attribute	**Description**	
Name	Csvws-Contract	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-En

Attribute	**Description**	
Name	Csvws-Contract-En	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.7.3.SD-CloseSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP

CRRATEESN

RULE

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

Csvws-Contract

LEGREFNO

Csvws-Contract-Event-Seq

EVTCODE

EVENT_SEQ_NO

DESCRIPTION

Csvws-Contract-Event-Advice

ADVCD

SUPPRESS

PRIORITY

PRTYID

PRTYNAME

ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,S

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.4.SD-CloseSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
      - *Brokerage*
        - *CONREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Misdetails*
        - *CONREFNO*
      - *Taxheadmaster*
        - *REFERENCE_NO*

Csvws-Contract

LEGREFNO

Csvws-Contract-En

LEGREFNO

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.ConfirmSecBlockDeal

ConfirmSecBlockDeal

2.8.1.SD-ConfirmSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
  LEGPRD
  MSTLDATE
  AUTOMSTL
  PORTFOLIO
  CNTPARTY
  PAYACCBRN
  PAYACC
  SKLOCATION
  SKACCNT
  BROKER
  SLRBUYSELL
  LEGDESC
  SLSKLOCATIONDESC
  DEAL_REFERENCE_NO
  MLLEGPRD
  MLLEGDESC
Svsmuldet
  PORTFOLIO
  CNTPARTY

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	**Description**
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

2.8.2.SD-ConfirmSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.8.3.SD-ConfirmSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREFNO

Attribute	Description	
Name	DEALREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.4.SD-ConfirmSecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.9.ConfirmSecuritiesDeal

ConfirmSecuritiesDeal

2.9.1.SD-ConfirmSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
  LEGREF
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	**Description**
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	**Description**
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.9.2.SD-ConfirmSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
    - *Brokerage*
      - *CONREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Misdetails*
      - *CONREFNO*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *Csvws-Contract*
      - *LEGREFNO*
    - *Csvws-Contract-En*
      - *LEGREFNO*

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.9.3.SD-ConfirmSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

- *Fundmisdetails*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Csvws-Contract*
  - *LEGREFNO*
  - *Csvws-Contract-Event-Seq*
    - *EVTCODE*
    - *EVENT_SEQ_NO*
    - *DESCRIPTION*
  - *Csvws-Contract-Event-Advice*
    - *ADVCD*
    - *SUPPRESS*
    - *PRIORITY*
    - *PRTYID*
    - *PRTYNAME*
    - *ADVDESC*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *MEDIA*

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

- *AMNTCMPCRCY*
- *PAYMNCURCY*
- *RATE*
- *AMONCURCY*
- *SIGN*

Csvwscnrt

Svwmtchdl

- *MTCHLREF*
- *STLDT*
- *MTCHQTY*

Unrelmtch

- *TOTREM*
- *TOTMTCH*
- *TOTREQD*

Lgrf

LEGREFNO

LATEVNTSQNO

LGDSCRPTN

PORTFLID

Msgs

- *VRSN*
- *MSGTP*
- *PRTID*
- *PRTNM*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *ADDRS5*
- *ADDRS6*
- *ADDNL1*
- *ADDNL2*
- *ADDNL3*
- *ADVCDSCRP*

Partdtl

- *VERSON*
- *PRTYP*
- *ADDRESS1*
- *ADDRESS2*
- *ADDRESS3*
- *ADDRESS4*
- *MSEGTP*
- *ADVICEDSCRPT*

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,S

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LEVENTDT

Attribute	Description
Name	LEVENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.4.SD-ConfirmSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
      - *Brokerage*
        - *CONREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Misdetails*
        - *CONREFNO*
      - *Taxheadmaster*
        - *REFERENCE_NO*

Csvws-Contract

LEGREFNO

Csvws-Contract-En

LEGREFNO

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.CreateDealProduct

Creation of Securities Deal Product

2.10.1.SD-CreateDealProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions
- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access
- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr
- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access
- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr
- *CODE*
- *PRDDESC*

Tatms-Product-Scheme
- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*

ALLWRULAMND
AMNDAFTRASSN
ALLWAMTAMND
AMNDAFTRAPPLN
Rule-Mkt-Tax-Dtls
RULE
MARKET_CODE
Product-Charges-Mkt
PRDCD
PRDDESC
Rule-Mkt-Chg-Dtls
COMPONENT
MRKTCD
RULE
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS
PRIOR

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY

DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	**Description**	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	**Description**	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	**Description**	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	**Description**	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	Description	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	Description	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	Description	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOCC1

Attribute	**Description**	
Name	SKLOCC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC1

Attribute	**Description**	
Name	SKACNTC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOCC2

Attribute	**Description**	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	Description	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	Description	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPL

Attribute	Description	
Name	AMNDAFTRAPPL	
Datatype	String	
Description	Indicates Amend After Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	Description	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	Description	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.10.2.SD-CreateDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *Setms-Deal-Product*
      - *RATETYP*
      - *FORW_ALLOW*
      - *SPOT_ALLOW*

BROKRGALWD
PARTRELALWD
CANCELALWD
EXTNALWD
AUTMSTL
AUTDSTL
PRICE
SECURTYIDDL
TRADEDT
MSTLDT
STLDT
PFID
NOMINLUNIT
MRKTCD
FRPAY
SPOTFRWD
PFIDC1
SKLOC
SKACNT
CLNRISKLIMTRKG
PSTLRISKLIMTRKG
SKLOCC1
SKACNTC1
SKLOCC2
SKACNTC2
BNKSACPT
CNSDRBROKFRDISC
Cstms-Product-Class-Link-Sr
SECRESTYP
Dealproduct-Restrictions
CODE
Setms-Dealprod-Security-Access
SECURTYIDSR
ALWDSR
Cstms-Product-Class-Link-Dr
PFRESCTYPE
Setms-Dealprod-Pfolios-Access
PFID
ACSALWDFLG
Setms-Dealproduct-Restrictions-Dr
CODE
Tatms-Product-Tran-Tax
STPASSN
TAXTYP

- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Rule-Mkt-Chg-Dtls

- *COMPONENT*
- *MRKTCD*
- *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *GENTIME*
    - *SUPRS*

PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
Mapping-Details
ACCTRL
ACCTHD
STAT
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Charges
Charge-Details
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND

AMNDAFTRAPPL
STPASOCIATN
ADVCHG
DISCACCRAPLB
DISCNTBASIS
DFTRULE
COMPNT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRADEDT

Attribute	**Description**	
Name	TRADEDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MSTLDT

Attribute	**Description**	
Name	MSTLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STLDT

Attribute	**Description**	
Name	STLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PFID

Attribute	**Description**	
Name	PFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOMINLUNIT

Attribute	Description	
Name	NOMINLUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTCD

Attribute	Description	
Name	MRKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FRPAY

Attribute	Description	
Name	FRPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

SPOTFRWD

Attribute	Description	
Name	SPOTFRWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALWDSR

Attribute	Description
Name	ALWDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACSALWDFLG

Attribute	**Description**	
Name	ACSALWDFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	**Description**	
Name	Setms-Dealproduct-Restrictions-Dr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Tatms-Product-Tran-Tax

Attribute	**Description**	
Name	Tatms-Product-Tran-Tax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSINDI

Attribute	Description

Name	NETCONSINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description

Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates Customer ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1

Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND

Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

2.10.3.SD-CreateDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*

- CLASDESC
- Dealproduct-Restrictions
  - CODE
  - PRDDESC
- Setms-Dealprod-Security-Access
  - SECURTYIDSR
  - PRDSR
  - SECURTYDESC
  - ALWDSR
- Cstms-Product-Class-Link-Dr
  - CLASCD
  - PFRESCTYPE
  - CLASDESC
- Setms-Dealprod-Pfolios-Access
  - PFID
  - PFPRODCD
  - PFDESC
  - ACSALWDFLG
- Setms-Dealproduct-Restrictions-Dr
  - CODE
  - PRDDESC
- Tatms-Product-Scheme
  - PRDORMRKTCD
  - SCHME
  - SCHMEDESC
  - Tatms-Product-Tran-Tax
    - COMP
    - STPASSN
    - TAXTYP
    - BORNBY
    - CASHOUTFLWINDI
    - NETCONSINDI
    - CONSPLUSMIN
    - SWFTQUAL
    - EVNTASSN
    - EVNTAPPLN
    - EVNTLIQDN
    - BASAMTTAG
    - DFLTRULE
    - RULEDESC
    - DFLTWAIV
    - ALLWRULAMND
    - AMNDAFTRASSN
    - ALLWAMTAMND

- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*

SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Setms-Deal-Product

Attribute	Description	
Name	Setms-Deal-Product	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATETYP

Attribute	Description	
Name	RATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	**Description**	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	**Description**	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	**Description**	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F,</td></tr></table>

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALWDSR

Attribute	Description

Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.4.SD-CreateDealProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-PK*
      - *PRDCD*
    - *Cstms-Product-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *PRDTYP*
      - *RTCODEPRFERD*
      - *RTTYPEPRFERD*
      - *PRDTYPDESC*
      - *PRODGRPDESC*
      - *Setms-Deal-Product*

RATETYP
FORW_ALLOW
SPOT_ALLOW
BROKRGALWD
PARTRELALWD
CANCELALWD
EXTNALWD
AUTMSTL
AUTDSTL
PRICE
SECURTYIDDL
TRADEDT
MSTLDT
STLDT
PFID
NOMINLUNIT
MRKTCD
FRPAY
SPOTFRWD
PFIDC1
SKLOC
SKACNT
CLNRISKLIMTRKG
PSTLRISKLIMTRKG
SKLOCC1
SKACNTC1
SKLOCC2
SKACNTC2
BNKSACPT
CNSDRBROKFRDISC
Cstms-Product-Class-Link-Sr
SECRESTYP
Dealproduct-Restrictions
CODE
Setms-Dealprod-Security-Access
SECURTYIDSR
ALWDSR
Cstms-Product-Class-Link-Dr
PFRESCTYPE
Setms-Dealprod-Pfolios-Access
PFID
ACSALWDFLG
Setms-Dealproduct-Restrictions-Dr
CODE

Tatms-Product-Tran-Tax
- *STPASSN*
- *TAXTYP*
- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Rule-Mkt-Chg-Dtls
- *COMPONENT*
- *MRKTCD*
- *RULE*

Product-Fields
- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events
- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*

- MSGTYP
- GENTIME
- SUPRS
- PRIOR
- CHGREQD

Role-To-Head-Mapping
- CLASCD
- Mapping-Details
  - ACCTRL
  - ACCTHD
  - STAT

Branch-Ccy-Restrictions
- CCYLST
- BRNLST
- CLASCD
- Branch-List
  - BRNDISALOW
- Ccy-List
  - BGTDLCCY
  - SOLDCCY

Prod-Cust-Restrictions
- CATGLIS
- CLASCD
- Cust-Categories
  - CATGDSAW
- Customers
  - CSTID
  - ALWD

Product-Mis-Details
- MISGRP
- POOLCD
- CSTCD1
- CSTCD2
- CSTCD4
- CSTCD5
- Default-Mis-Codes
  - MISTYP
  - MISCLS
  - MISCD
  - KYID

Product-Charges
- Charge-Details
  - SETTCCY
  - DFTWAIV

ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
DISCACCRAPLB
DISCNTBASIS
DFTRULE
COMPNT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 1
Restrictions	Restrictions: maxLength Description: 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	Description	
Name	PRDENDDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

NRMLRTVARI

Attribute	Description	
Name	NRMLRTVARI	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	Description	
Name	MAXRTVARI	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	Description	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	Description	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	Description	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	**Description**	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	**Description**	
Name	SECURTYIDDL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRADEDT

Attribute	**Description**	
Name	TRADEDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Cstms-Product-Class-Link-Sr

Attribute	**Description**	
Name	Cstms-Product-Class-Link-Sr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECRESTYP

Attribute	**Description**	
Name	SECRESTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWFTQUAL

Attribute	Description	
Name	SWFTQUAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DFLTRULE

Attribute	Description	
Name	DFLTRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DFLTWAIV

Attribute	Description	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	Description	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String

Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	**Description**	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description	Indicates the status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List

Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String

Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.CreateSEDealBlockRelease

CreateSEDealBlockRelease

2.11.1.SD-CreateSEDealBlockRelease-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*

BLKREF
SEDSC
PRDDSC
ONCAUTH
Sdd
- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd
- *DLRFNO*

Scd--A
- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl
- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En
- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*

- *VALDT*
- *CCY*
- *FCY_AMOUNT*
- *EXG_RATE*
- *LCY_AMOUNT*
- *Csvws-Contract-Ovd*
  - *OVDMSGS*
- *Csvws-Contract*
  - *LEGREFNO*
  - *Csvws-Contract-Event-Seq*
    - *EVTCODE*
    - *EVENT_SEQ_NO*
    - *DESCRIPTION*
  - *Csvws-Contract-Event-Advice*
    - *ADVCD*
    - *SUPPRESS*
    - *PRIORITY*
    - *PRTYID*
    - *PRTYNAME*
    - *ADVDESC*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *MEDIA*
    - *DESCRIPTION*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BLKTYP

Attribute	Description
Name	BLKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLKREF

Attribute	Description
Name	BLKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SEDSC

Attribute	Description
Name	SEDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPTY

Attribute	Description	
Name	COUNTRPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLC

Attribute	Description	
Name	SKLC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKAC

Attribute	Description	
Name	SKAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCDSC

Attribute	Description	
Name	SKLOCDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sdl

Attribute	Description

Name	Sdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER_ID

Attribute	**Description**	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.11.2.SD-CreateSEDealBlockRelease-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-IO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *RLSDT*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*
    - *ONCAUTH*
    - *Sdd*
      - *PF*
      - *SKLC*
      - *SKAC*
      - *EVSQNO*
      - *VRSN*
    - *Scd--A*

- CRTNO
- QTYTOBLK
- STATS

Csvws-Contract-En

- LEGREFNO
- Sevws-Event-Log
  - REFERENCE
  - SR_NO
  - EVENT
  - EVENT_DATE
  - MAKER_ID
  - MAKER_DT_STAMP
  - CHECKER_ID
  - CHECKER_DT_STAMP
  - Acvws-All-Ac-Entries
    - BRANCH
    - ACCOUNT
    - DR_CR
    - CODE
    - DATE
    - VALDT
    - CCY
    - FCY_AMOUNT
    - EXG_RATE
    - LCY_AMOUNT
  - Csvws-Contract-Ovd
    - OVDMSGS

Csvws-Contract

- LEGREFNO
- Csvws-Contract-Event-Seq
  - EVTCODE
  - EVENT_SEQ_NO
  - DESCRIPTION
- Csvws-Contract-Event-Advice
  - ADVCD
  - SUPPRESS
  - PRIORITY
  - PRTYID
  - PRTYNAME
  - ADVDESC
  - ADDRS1
  - ADDRS2
  - ADDRS3
  - ADDRS4

- *MEDIA*
- *DESCRIPTION*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
- *Issrtax*
  - *INTCOMP*
  - *RATECOD*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*

POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN

- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST4*
  - *RCVRCORRS1*
  - *RCVRCORRS2*

RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5

ORDINST5

ULTBEN5

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sdm-IO

Attribute	Description

Name	Sdm-IO
Datatype	
Description	

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 35

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLQTY

Attribute	Description
Name	DLQTY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BLKTYP

Attribute	Description
Name	BLKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description

Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Misdetails

Attribute	Description

Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	**Description**
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	**Description**
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.11.3.SD-CreateSEDealBlockRelease-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*
    - *BLKREF*
    - *SEDSC*
    - *PRDDSC*

ONCAUTH

Sdd

- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd

- *DLRFNO*

Scd--A

- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl

- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En

- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*
    - *VALDT*
    - *CCY*
    - *FCY_AMOUNT*

EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLQTY

Attribute	**Description**	
Name	DLQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BLKTYP

Attribute	**Description**	
Name	BLKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BLKREF

Attribute	**Description**	
Name	BLKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SEDSC

Attribute	**Description**	
Name	SEDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sdl

Attribute	Description
Name	Sdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description

Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**

Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs; Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.4.SD-CreateSEDealBlockRelease-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sdm-PK*
      - *DLRF*
    - *Sdm-IO*
      - *USRRF*
      - *PRD*
      - *DLRF*
      - *SECD*
      - *SECSE*
      - *RLSDT*
      - *PRTRELALLW*
      - *AUTRELALLW*
      - *DLQTY*
      - *BLKTYP*
      - *ONCAUTH*
      - *Sdd*
        - *PF*
        - *SKLC*
        - *SKAC*

- EVSQNO
- VRSN

Scd--A

- CRTNO
- QTYTOBLK
- STATS

Csvws-Contract-En

- LEGREFNO
- Sevws-Event-Log
  - REFERENCE
  - SR_NO
  - EVENT
  - EVENT_DATE
  - MAKER_ID
  - MAKER_DT_STAMP
  - CHECKER_ID
  - CHECKER_DT_STAMP
  - Acvws-All-Ac-Entries
    - BRANCH
    - ACCOUNT
    - DR_CR
    - CODE
    - DATE
    - VALDT
    - CCY
    - FCY_AMOUNT
    - EXG_RATE
    - LCY_AMOUNT
  - Csvws-Contract-Ovd
    - OVDMSGS

Csvws-Contract

- LEGREFNO
- Csvws-Contract-Event-Seq
  - EVTCODE
  - EVENT_SEQ_NO
  - DESCRIPTION
- Csvws-Contract-Event-Advice
  - ADVCD
  - SUPPRESS
  - PRIORITY
  - PRTYID
  - PRTYNAME
  - ADVDESC
  - ADDRS1

- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *MEDIA*
- *DESCRIPTION*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
- *Issrtax*
  - *INTCOMP*
  - *RATECOD*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*

RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7

- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*

REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5

REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*

REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sdm-PK

Attribute	Description
Name	Sdm-PK
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BLKTYP

Attribute	Description
Name	BLKTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER_ID

Attribute	**Description**	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description

Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description

Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**
Name	BANKPRIOR
Datatype	String

Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD

Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1

Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC

Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	**Description**	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.CreateSecBlockDeal

CreateSecBlockDeal

2.12.1.SD-CreateSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
  LEGPRD
  MSTLDATE
  AUTOMSTL
  PORTFOLIO
  CNTPARTY
  PAYACCBRN
  PAYACC
  SKLOCATION
  SKACCNT
  BROKER
  SLRBUYSELL
  LEGDESC
  SLSKLOCATIONDESC
  DEAL_REFERENCE_NO
  MLLEGPRD
  MLLEGDESC
Svsmuldet
  PORTFOLIO
  CNTPARTY

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREFNO

Attribute	Description	
Name	DEALREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	**Description**
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

2.12.2.SD-CreateSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *ABSOLUTE_PRICE*
    - *FORMAT*

REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
LEGPRD
MSTLDATE
AUTOMSTL
PORTFOLIO
CNTPARTY
PAYACCBRN
PAYACC
SKLOCATION
SKACCNT
BROKER
SLRBUYSELL
DEAL_REFERENCE_NO
MLLEGPRD
Svsmuldet
PORTFOLIO
CNTPARTY
SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description

Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SETTSKL

Attribute	**Description**	
Name	SETTSKL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	**Description**	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	**Description**	
Name	DLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,S

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Svsmuldet

Attribute	**Description**	
Name	Svsmuldet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

2.12.3.SD-CreateSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREFNO

Attribute	Description	
Name	DEALREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	Description	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	Description	
Name	DLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.4.SD-CreateSecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *PRD*
      - *DEALREFNO*
      - *USERREF*
      - *SECTYCD*
      - *MKTCD*
      - *DEALTYPE*
      - *QUOTEBY*
      - *DEALQTY*
      - *TRADEDT*
      - *INTERST*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*
      - *RECIEVE*

INPRICE
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
  LEGPRD
  MSTLDATE
  AUTOMSTL
  PORTFOLIO
  CNTPARTY
  PAYACCBRN
  PAYACC
  SKLOCATION
  SKACCNT
  BROKER
  SLRBUYSELL
  DEAL_REFERENCE_NO
  MLLEGPRD
Svsmuldet
  PORTFOLIO
  CNTPARTY
  SKLOCATION
  SKLOCDES
  SKACCNT
  BROKER
  DEALQTY
  YIELD
  PAYACCBRN
  PAYACC
  DLIPPR
  MSTLDATE

AUTOMSTL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description

Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,F

TOP

QUOTEBY

Attribute	**Description**	
Name	QUOTEBY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEALQTY

Attribute	**Description**	
Name	DEALQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRADEDT

Attribute	**Description**	
Name	TRADEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTERST

Attribute	**Description**	
Name	INTERST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

PRIQT

Attribute	Description	
Name	PRIQT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INTDT

Attribute	Description	
Name	INTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECIEVE

Attribute	Description	
Name	RECIEVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

DEAL_REFERENCE_NO

Attribute	**Description**	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTOMSTL

Attribute	Description

Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.CreateSecuritiesDeal

CreateSecuritiesDeal

2.13.1.SD-CreateSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinto
- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	**Description**
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	**Description**
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESS

Attribute	Description	
Name	PARTYPROCESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ADVPKPDONE

Attribute	Description	
Name	ADVPKPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NETCONSPROCESSED

Attribute	Description	
Name	NETCONSPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DCONCOMPLETED

Attribute	Description	
Name	DCONCOMPLETED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PMTADVPROCESSED

Attribute	Description
Name	PMTADVPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

LEGREFNOTO

Attribute	Description
Name	LEGREFNOTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.13.2.SD-CreateSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *SPOTDT*
    - *SPOTPRC*
    - *REPOINDICATOR*
    - *PARTRELEASEALLOWED*

SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
DEALER
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY

FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
INTVALDT
BROKERID
Detalfrom
- *BRANCH*
- *DEALREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRN*
- *PAYACC*
- *ACCOMLODGE*
- *SKLOC*
- *SKACC*
- *FRMTYPFROM*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*
- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESS*
- *ADVPKPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*

- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *Limitsfrom*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*

PCY
PAYBRNTO
PAYACCTO
ACMP_WDRW
SKACC
FRMTYPFROM
SKLOCTO
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
Limitsto
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  WALKINNAME

- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *Brokerage*
  - *CONREFNO*
  - *BROKAMT*
  - *BROKCCY*
  - *DISCACCRAPPL*

- *BKCCY*
- *BKAMT*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*

PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2

BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*

ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6

- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
- *Issrtax*

INTCOMP
RATECOD
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

Dlntcn

Dlintr

Csvwscnrt

CONTREFNO

Svwmtchdl

MTCHLREF

Unrelmtch

TOTREM

TOTMTCH

TOTREQD

Lgrf

LEGREFNO

LATEVNTSQNO

Msgs

VRSN

ADDRS1

ADDRS2

ADDRS3

ADDRS4

ADDRS5

ADDRS6

ADDNL1

ADDNL2

ADDNL3

Partdtl

VERSON

ADDRESS1

ADDRESS2

ADDRESS3

ADDRESS4

MSEGTP

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

YTM

Attribute	**Description**	
Name	YTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT

Attribute	**Description**	
Name	DISCOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREMIUM

Attribute	**Description**	
Name	PREMIUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ABSPREMIUM

Attribute	**Description**	
Name	ABSPREMIUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ABSDISCOUNT

Attribute	**Description**	
Name	ABSDISCOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPOINDICATOR

Attribute	**Description**	
Name	REPOINDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PARTRELEASEALLOWED

Attribute	**Description**	
Name	PARTRELEASEALLOWED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSTTLMENT

Attribute	**Description**	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	**Description**	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,S

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

UNITS

Attribute	Description
Name	UNITS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	**Description**	
Name	SECURITYTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECURITYREFNO

Attribute	**Description**	
Name	SECURITYREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECTYSERIES

Attribute	**Description**	
Name	SECTYSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

DCONREQUIRED

Attribute	Description	
Name	DCONREQUIRED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FREEPAY

Attribute	Description	
Name	FREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MKTCD

Attribute	Description	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRCTYPE

Attribute	Description	
Name	PRCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Detalfrom

Attribute	Description	
Name	Detalfrom	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	Description	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MSTLCOMPLETED

Attribute	**Description**	
Name	MSTLCOMPLETED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYPFROM

Attribute	**Description**	
Name	FRMTYPFROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYPTO

Attribute	**Description**	
Name	FRMTYPTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BRKPKPDONE

Attribute	**Description**	
Name	BRKPKPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FUNDREFNO

Attribute	**Description**	
Name	FUNDREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ADVPICKUPDONE

Attribute	**Description**	
Name	ADVPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NETCONSPROCESSED

Attribute	**Description**	
Name	NETCONSPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PMTADVPROCESSED

Attribute	Description
Name	PMTADVPROCESSED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

Limitsto

Attribute	**Description**	
Name	Limitsto	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

UNEXPOSURE

Attribute	**Description**	
Name	UNEXPOSURE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinto

Attribute	Description
Name	Walkinto
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description
Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LEVENTDT

Attribute	Description
Name	LEVENTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FREFNO

Attribute	**Description**	
Name	FREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RESPSTAT

Attribute	**Description**	
Name	RESPSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECUPDSTAT

Attribute	**Description**	
Name	SECUPDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

STOPDT

Attribute	**Description**	
Name	STOPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Brokerage

Attribute	Description

Name	Brokerage
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description

Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2

Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3

Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	**Description**	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5

Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID

Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1

Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	**Description**	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	**Description**	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	**Description**	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Dlntcn

Attribute	Description
Name	Dlntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.13.3.SD-CreateSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

- *Fundmisdetails*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Csvws-Contract*
  - *LEGREFNO*
  - *Csvws-Contract-Event-Seq*
    - *EVTCODE*
    - *EVENT_SEQ_NO*
    - *DESCRIPTION*
  - *Csvws-Contract-Event-Advice*
    - *ADVCD*
    - *SUPPRESS*
    - *PRIORITY*
    - *PRTYID*
    - *PRTYNAME*
    - *ADVDESC*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *MEDIA*

DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN
Dlintr
CMPNTDSC
COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description	
Name	DEALTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	Description	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PMTADVPROCESSED

Attribute	Description
Name	PMTADVPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

LEGREFNOTO

Attribute	Description
Name	LEGREFNOTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealmastera

Attribute	Description	
Name	Dealmastera	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LEVENTDT

Attribute	Description
Name	LEVENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.4.SD-CreateSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *FACEDEAL*
      - *YTM*
      - *DISCOUNT*
      - *PREMIUM*
      - *ABSPREMIUM*
      - *ABSDISCOUNT*
      - *FORWDPL*
      - *ADJDEALPRC*
      - *INTDAYS*
      - *INTAMT*
      - *TRADEDT*
      - *AUTOMANDSTL*
      - *DSTLCOMPLETED*
      - *DSTLDATE*

SPOTDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
DEALER
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD

PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
INTVALDT
BROKERID
Detalfrom
- *BRANCH*
- *DEALREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRN*
- *PAYACC*
- *ACCOMLODGE*
- *SKLOC*
- *SKACC*
- *FRMTYPFROM*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*
- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESS*
- *ADVPKPDONE*

- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *Limitsfrom*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRNTO
PAYACCTO
ACMP_WDRW
SKACC
FRMTYPFROM
SKLOCTO
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
Limitsto
  CPTY
  UNEXPOSURE
  TOTEXPOSURE

CLEANRISKLIMIT
PSTLRISKLIMIT
Walkinto
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
Dealmastera
DEALREF
Ytmmaster
DEALREF
EFFDT
YTM
Certificates
CERTNO
CERTQT
UNIT_NOM_QUOTE
Contract
SERIAL
ESN
UREF
LATVERNO
PRDCODE
CPTY
TEMPSTAT
PRDTYPE
CEC
MDCODE
UDSTAT
CONTCCY
LEVENTDT
XREF
AMFLAG
FREFNO
RESPSTAT
SECUPDSTAT
STOPDT
LIBCIF
SRC
REFERCREF
Multiref
Brokerage

- CONREFNO
- BROKAMT
- BROKCCY
- DISCACCRAPPL
- BKCCY
- BKAMT

Charges

- LATEVNSEQNO
- CONREFNO
- Charge-Association
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - CHRGAMT
  - LIQDSTAT

Settlements

- CONREFNO
- LATEVNSEQNO
- Contract-Settlement
  - CUSTSPREAD
  - SPREADDEFN
  - TAGCCY
  - ACCBRN
  - ACC
  - EXRATE
  - NETIND
  - ERICCY
  - ERIAMT
  - GENMSG
  - RATECD
  - CLEARNW
  - COVERBY
  - RTGSPMNT
  - BANKPRIOR
  - RTGSNW
  - PAYBY

TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2

ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
WAIVER

LIQDINDICAT
Liqdmaster
INTCOMP
Issrtax
INTCOMP
RATECOD
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY

FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
Dlntcn
Dlintr
Csvwscnrt
CONTREFNO
Svwmtchdl
MTCHLREF
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
Msgs
VRSN
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
Partdtl
VERSON
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description

Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	**Description**	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	**Description**	
Name	TXNTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CERTNOS

Attribute	**Description**	
Name	CERTNOS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BAREF

Attribute	**Description**	
Name	BAREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FREEPAY

Attribute	Description	
Name	FREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MKTCD

Attribute	Description	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRCTYPE

Attribute	Description	
Name	PRCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

DEALTYP

Attribute	Description	
Name	DEALTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Detalfrom

Attribute	Description
Name	Detalfrom

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

EVENTCODE

Attribute	Description

Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYPTO

Attribute	**Description**	
Name	FRMTYPTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BRKPKPDONE

Attribute	**Description**	
Name	BRKPKPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CHARGEPKPDONE

Attribute	**Description**	
Name	CHARGEPKPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CALBDONE

Attribute	Description
Name	CALBDONE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRKID

Attribute	**Description**	
Name	BRKID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	Description	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	Description	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Walkinfrom

Attribute	**Description**	
Name	Walkinfrom	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Detalto

Attribute	Description
Name	DetaIto
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESSED

Attribute	Description
Name	PARTYPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EFFDT

Attribute	Description

Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description
Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTCCY

Attribute	Description
Name	CONTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LEVENTDT

Attribute	Description
Name	LEVENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BROKAMT

Attribute	**Description**	
Name	BROKAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BROKCCY

Attribute	**Description**	
Name	BROKCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DISCACCRAPPL

Attribute	**Description**	
Name	DISCACCRAPPL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BKCCY

Attribute	**Description**	
Name	BKCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description	
Name	SNDTRRCVINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	**Description**	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description

Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Dlntcn

Attribute	**Description**	
Name	Dlntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Dlintr

Attribute	**Description**	
Name	Dlintr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Csvwscnrt

Attribute	**Description**	
Name	Csvwscnrt	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDNL1

Attribute	Description
Name	ADDNL1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.DeleteDealProduct

Deletion of Securities Deal Product

2.14.1.SD-DeleteDealProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions
- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access
- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr
- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access
- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr
- *CODE*
- *PRDDESC*

Tatms-Product-Scheme
- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*

- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY

DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	**Description**	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	**Description**	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	**Description**	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	**Description**	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	Description	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	Description	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	Description	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOCC1

Attribute	**Description**	
Name	SKLOCC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC1

Attribute	**Description**	
Name	SKACNTC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOCC2

Attribute	**Description**	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.14.2.SD-DeleteDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.14.3.SD-DeleteDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*

- *CLASDESC*

Dealproduct-Restrictions

- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access

- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr

- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access

- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr

- *CODE*
- *PRDDESC*

Tatms-Product-Scheme

- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*
  - *ALLWRULAMND*
  - *AMNDAFTRASSN*
  - *ALLWAMTAMND*

- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*

SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	**Description**	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	**Description**	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	**Description**	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F,</td></tr></table>

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALWDSR

Attribute	Description

Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	**Description**	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.4.SD-DeleteDealProduct-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Cstms-Product-PK*
    - *PRDCD*
  - *Cstms-Product-IO*
    - *PRDCD*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.15.DeleteSEDealBlockRelease

DeleteSEDealBlockRelease

2.15.1.SD-DeleteSEDealBlockRelease-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*

BLKREF
SEDSC
PRDDSC
ONCAUTH
Sdd
  PF
  PFDSC
  COUNTRPTY
  SKLC
  SKAC
  SKLOCDSC
  FRMTYP
  EVSQNO
  VRSN
Scd
  DLRFNO
Scd--A
  CRTNO
  QTYTOBLK
  STATS
Sdl
  MKID
  MKDTSTMP
  CKID
  CKDTSTMP
  TXNSTAT
  AUTHSTAT
Csvws-Contract-En
  LEGREFNO
  Sevws-Event-Log
    REFERENCE
    SR_NO
    EVENT
    EVENT_DATE
    MAKER_ID
    MAKER_DT_STAMP
    CHECKER_ID
    CHECKER_DT_STAMP
    Acvws-All-Ac-Entries
      BRANCH
      ACCOUNT
      DR_CR
      CODE
      DATE

- *VALDT*
- *CCY*
- *FCY_AMOUNT*
- *EXG_RATE*
- *LCY_AMOUNT*
- *Csvws-Contract-Ovd*
  - *OVDMSGS*
- *Csvws-Contract*
  - *LEGREFNO*
  - *Csvws-Contract-Event-Seq*
    - *EVTCODE*
    - *EVENT_SEQ_NO*
    - *DESCRIPTION*
  - *Csvws-Contract-Event-Advice*
    - *ADVCD*
    - *SUPPRESS*
    - *PRIORITY*
    - *PRTYID*
    - *PRTYNAME*
    - *ADVDESC*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *MEDIA*
    - *DESCRIPTION*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BLKTYP

Attribute	Description
Name	BLKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLKREF

Attribute	Description
Name	BLKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SEDSC

Attribute	Description
Name	SEDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sdl

Attribute	Description

Name	Sdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER_ID

Attribute	**Description**	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.15.2.SD-DeleteSEDealBlockRelease-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-IO*
    - *DLRF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.15.3.SD-DeleteSEDealBlockRelease-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*
    - *BLKREF*
    - *SEDSC*
    - *PRDDSC*

ONCAUTH

Sdd

- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd

- *DLRFNO*

Scd--A

- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl

- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En

- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*
    - *VALDT*
    - *CCY*
    - *FCY_AMOUNT*

EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLQTY

Attribute	**Description**	
Name	DLQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BLKTYP

Attribute	**Description**	
Name	BLKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BLKREF

Attribute	**Description**	
Name	BLKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SEDSC

Attribute	**Description**	
Name	SEDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sdl

Attribute	Description
Name	Sdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description

Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**

Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs; Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.4.SD-DeleteSEDealBlockRelease-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sdm-PK*
      - *DLRF*
    - *Sdm-IO*
      - *DLRF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sdm-PK

Attribute	Description
Name	Sdm-PK
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.16.DeleteSecBlockDeal

DeleteSecBlockDeal

2.16.1.SD-DeleteSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
  LEGPRD
  MSTLDATE
  AUTOMSTL
  PORTFOLIO
  CNTPARTY
  PAYACCBRN
  PAYACC
  SKLOCATION
  SKACCNT
  BROKER
  SLRBUYSELL
  LEGDESC
  SLSKLOCATIONDESC
  DEAL_REFERENCE_NO
  MLLEGPRD
  MLLEGDESC
Svsmuldet
  PORTFOLIO
  CNTPARTY

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

2.16.2.SD-DeleteSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.16.3.SD-DeleteSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	**Description**	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	**Description**	
Name	DLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.4.SD-DeleteSecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.17.DeleteSecuritiesDeal

DeleteSecuritiesDeal

2.17.1.SD-DeleteSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
  LEGREF
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.17.2.SD-DeleteSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.17.3.SD-DeleteSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- BKAMT
- LQSTAT
- LQREFNO
- BROKNAM

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP

CRRATEESN

RULE

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

Csvws-Contract

LEGREFNO

Csvws-Contract-Event-Seq

EVTCODE

EVENT_SEQ_NO

DESCRIPTION

Csvws-Contract-Event-Advice

ADVCD

SUPPRESS

PRIORITY

PRTYID

PRTYNAME

ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description	
Name	DEALTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	Description	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	**Description**	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	**Description**	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	**Description**	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	**Description**	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ADVPICKUPDONE

Attribute	**Description**	
Name	ADVPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NETCONSPROCESSED

Attribute	**Description**	
Name	NETCONSPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DCONCOMPLETED

Attribute	**Description**	
Name	DCONCOMPLETED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CALBDONE

Attribute	**Description**	
Name	CALBDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealmastera

Attribute	Description	
Name	Dealmastera	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	**Description**
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.4.SD-DeleteSecuritiesDeal-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Dealmaster-PK*
    - *DEALREF*
    - *VERSION*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.LiquidateSEDealBlockRelease

LiquidateSEDealBlockRelease

2.18.1.SD-LiquidateSEDealBlockRelease-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*

BLKREF
SEDSC
PRDDSC
ONCAUTH
Sdd
  PF
  PFDSC
  COUNTRPTY
  SKLC
  SKAC
  SKLOCDSC
  FRMTYP
  EVSQNO
  VRSN
Scd
  DLRFNO
Scd--A
  CRTNO
  QTYTOBLK
  STATS
Sdl
  MKID
  MKDTSTMP
  CKID
  CKDTSTMP
  TXNSTAT
  AUTHSTAT
Csvws-Contract-En
  LEGREFNO
  Sevws-Event-Log
    REFERENCE
    SR_NO
    EVENT
    EVENT_DATE
    MAKER_ID
    MAKER_DT_STAMP
    CHECKER_ID
    CHECKER_DT_STAMP
    Acvws-All-Ac-Entries
      BRANCH
      ACCOUNT
      DR_CR
      CODE
      DATE

- VALDT
- CCY
- FCY_AMOUNT
- EXG_RATE
- LCY_AMOUNT
- Csvws-Contract-Ovd
  - OVDMSGS
- Csvws-Contract
  - LEGREFNO
  - Csvws-Contract-Event-Seq
    - EVTCODE
    - EVENT_SEQ_NO
    - DESCRIPTION
  - Csvws-Contract-Event-Advice
    - ADVCD
    - SUPPRESS
    - PRIORITY
    - PRTYID
    - PRTYNAME
    - ADVDESC
    - ADDRS1
    - ADDRS2
    - ADDRS3
    - ADDRS4
    - MEDIA
    - DESCRIPTION
- Charges
  - CONREFNO
  - Charge-Association
    - COMPNT
    - CREATESN
    - RULE
    - WAIVER
    - DISACCRAPPL
    - ACCRREQD
    - DESC
  - Charge-Application
    - CREATESN
    - COMPNT
    - TGCCY
    - TGAMT
    - CHRGCCY
    - CHRGAMT
    - DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BLKTYP

Attribute	Description
Name	BLKTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLKREF

Attribute	Description
Name	BLKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SEDSC

Attribute	Description
Name	SEDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPTY

Attribute	Description	
Name	COUNTRPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLC

Attribute	Description	
Name	SKLC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKAC

Attribute	Description	
Name	SKAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCDSC

Attribute	Description	
Name	SKLOCDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sdl

Attribute	Description

Name	Sdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER_ID

Attribute	**Description**	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.18.2.SD-LiquidateSEDealBlockRelease-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-IO*
    - *DLRF*
    - *Csvws-Contract-En*
      - *LEGREFNO*
    - *Csvws-Contract*
      - *LEGREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *Misdetails*
      - *CONREFNO*
      - *MISGRP*
      - *RELACC*
      - *RELETED_REFERENCE*
      - *MISHEAD*
      - *RATEFLG*
      - *POOLCD*

REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails

Compmisdetails

Fundmisdetails

Settlements

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL

Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.18.3.SD-LiquidateSEDealBlockRelease-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*
    - *BLKREF*
    - *SEDSC*
    - *PRDDSC*

ONCAUTH

Sdd

- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd

- *DLRFNO*

Scd--A

- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl

- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En

- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*
    - *VALDT*
    - *CCY*
    - *FCY_AMOUNT*

EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DLRF

Attribute	**Description**	
Name	DLRF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECD

Attribute	**Description**	
Name	SECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECSE

Attribute	**Description**	
Name	SECSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

NMQT

Attribute	**Description**	
Name	NMQT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLQTY

Attribute	**Description**	
Name	DLQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BLKTYP

Attribute	**Description**	
Name	BLKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BLKREF

Attribute	**Description**	
Name	BLKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SEDSC

Attribute	**Description**	
Name	SEDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sdl

Attribute	Description
Name	Sdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description

Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.4.SD-LiquidateSEDealBlockRelease-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sdm-PK*
      - *DLRF*
    - *Sdm-IO*
      - *DLRF*
      - *Csvws-Contract-En*
        - *LEGREFNO*
      - *Csvws-Contract*
        - *LEGREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Taxheadmaster*
        - *REFERENCE_NO*
      - *Misdetails*
        - *CONREFNO*
        - *MISGRP*
        - *RELACC*
        - *RELETED_REFERENCE*

MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7

FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Settlements
CONREFNO
LATEVNSEQNO
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sdm-PK

Attribute	Description
Name	Sdm-PK
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO

Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.LiquidateSecBlockDeal

LiquidateSecBlockDeal

2.19.1.SD-LiquidateSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
  LEGPRD
  MSTLDATE
  AUTOMSTL
  PORTFOLIO
  CNTPARTY
  PAYACCBRN
  PAYACC
  SKLOCATION
  SKACCNT
  BROKER
  SLRBUYSELL
  LEGDESC
  SLSKLOCATIONDESC
  DEAL_REFERENCE_NO
  MLLEGPRD
  MLLEGDESC
Svsmuldet
  PORTFOLIO
  CNTPARTY

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	**Description**
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

2.19.2.SD-LiquidateSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.19.3.SD-LiquidateSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	**Description**	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	**Description**	
Name	DLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.4.SD-LiquidateSecBlockDeal-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Svsblkdlmas-PK*
    - *DEALREFNO*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.20.LiquidateSecuritiesDeal

LiquidateSecuritiesDeal

2.20.1.SD-LiquidateSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
  LEGREF
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4

Dealmastera

DEALREF

Ytmmaster

DEALREF

EFFDT

YTM

Certificates

DEALREF

CERTNO

CERTQT

UNIT_NOM_QUOTE

Dealmasterb

DEALREF

Contract

SERIAL

ESN

UREF

LATVERNO

PRDCODE

CPTY

TEMPSTAT

PRDTYPE

CEC

MDCODE

UDSTAT

CONTCCY

LEVENTDT

XREF

AMFLAG

FREFNO

RESPSTAT

SECUPDSTAT

STOPDT

LIBCIF

SRC

REFERCREF

Multiref

VERNO

LEGREFNO

Brokerage

CONREFNO

BOKBROKER

BROKAMT

BROKCCY

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	**Description**
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	**Description**
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	**Description**
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	**Description**
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	**Description**
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESS

Attribute	Description	
Name	PARTYPROCESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ADVPKPDONE

Attribute	Description	
Name	ADVPKPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NETCONSPROCESSED

Attribute	Description	
Name	NETCONSPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DCONCOMPLETED

Attribute	Description	
Name	DCONCOMPLETED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Certificates

Attribute	**Description**	
Name	Certificates	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CERTNO

Attribute	**Description**	
Name	CERTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CERTQT

Attribute	**Description**	
Name	CERTQT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNIT_NOM_QUOTE

Attribute	**Description**

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	**Description**
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.20.2.SD-LiquidateSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
    - *Brokerage*
      - *CONREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Misdetails*
      - *CONREFNO*
      - *MISGRP*
      - *RELACC*
      - *RELETED_REFERENCE*
      - *MISHEAD*
      - *RATEFLG*
      - *POOLCD*

REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails

Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Csvws-Contract

LEGREFNO

Csvws-Contract-En

LEGREFNO

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	Description	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Brokerage

Attribute	Description	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract

Attribute	**Description**	
Name	Csvws-Contract	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-En

Attribute	**Description**

Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.20.3.SD-LiquidateSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- BKAMT
- LQSTAT
- LQREFNO
- BROKNAM

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP

CRRATEESN

RULE

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

Csvws-Contract

LEGREFNO

Csvws-Contract-Event-Seq

EVTCODE

EVENT_SEQ_NO

DESCRIPTION

Csvws-Contract-Event-Advice

ADVCD

SUPPRESS

PRIORITY

PRTYID

PRTYNAME

ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,S

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	**Description**	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	**Description**	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	**Description**	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	**Description**	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealmastera

Attribute	Description	
Name	Dealmastera	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Certificates

Attribute	**Description**	
Name	Certificates	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CERTNO

Attribute	**Description**	
Name	CERTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CERTQT

Attribute	**Description**	
Name	CERTQT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNIT_NOM_QUOTE

Attribute	**Description**

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	**Description**
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.4.SD-LiquidateSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
      - *Brokerage*
        - *CONREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Misdetails*
        - *CONREFNO*
        - *MISGRP*
        - *RELACC*

RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Taxheadmaster
REFERENCE_NO
Csvws-Contract
LEGREFNO
Csvws-Contract-En
LEGREFNO
Cntdl
CONTREFNO
Csvwscnrt
CONTREFNO
Lgrf
LEGREFNO
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.ModifyDealProduct

Modification of Securities Deal Product

2.21.1.SD-ModifyDealProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions
- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access
- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr
- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access
- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr
- *CODE*
- *PRDDESC*

Tatms-Product-Scheme
- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*

- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY

DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	**Description**	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	**Description**	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	**Description**	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	**Description**	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	Description	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	Description	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	Description	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOCC1

Attribute	**Description**	
Name	SKLOCC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC1

Attribute	**Description**	
Name	SKACNTC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOCC2

Attribute	**Description**	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	Description	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	Description	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	Description	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.21.2.SD-ModifyDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *MAKER*
    - *MAKERSTAMP*
    - *Setms-Deal-Product*
      - *RATETYP*
      - *FORW_ALLOW*
      - *SPOT_ALLOW*
      - *BROKRGALWD*

PARTRELALWD
CANCELALWD
EXTNALWD
AUTMSTL
AUTDSTL
PRICE
SECURTYIDDL
TRADEDT
MSTLDT
STLDT
PFID
NOMINLUNIT
MRKTCD
FRPAY
SPOTFRWD
PFIDC1
SKLOC
SKACNT
PSTLRISKLIMTRKG
SKLOCC1
SKACNTC1
SKLOCC2
SKACNTC2
BNKSACPT
CNSDRBROKFRDISC
Cstms-Product-Class-Link-Sr
CLASCD
SECRESTYP
Dealproduct-Restrictions
CODE
Setms-Dealprod-Security-Access
SECURTYIDSR
ALWDSR
Cstms-Product-Class-Link-Dr
CLASCD
PFRESCTYPE
Setms-Dealprod-Pfolios-Access
Setms-Dealproduct-Restrictions-Dr
CODE
Tatms-Product-Tran-Tax
COMP
STPASSN
TAXTYP
BORNBY

- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *COMPONENT*
  - *MARKET_CODE*
  - *PRODUCT*
- *Rule-Mkt-Chg-Dtls*
  - *PRODUCT*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Events*
  - *CLASCD*
  - *Event-Details*
    - *EVNTCD*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*
      - *MISHD*
      - *REVALPRGL*
      - *REVALLSGL*
      - *REVALRTCD*
      - *REVALTXNCD*
      - *HOLTREAT*

REVALREQD
Advices
MSGTYP
SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
Mapping-Details
ACCTRL
ACCTHD
STAT
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Charges
Charge-Details
SETTCCY

DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
DFTRULE
COMPNT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MSTLDT

Attribute	**Description**	
Name	MSTLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STLDT

Attribute	**Description**	
Name	STLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PFID

Attribute	**Description**	
Name	PFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOMINLUNIT

Attribute	**Description**	
Name	NOMINLUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTCD

Attribute	Description	
Name	MRKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FRPAY

Attribute	Description	
Name	FRPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

SPOTFRWD

Attribute	Description	
Name	SPOTFRWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,F,

TOP

PFIDC1

Attribute	Description	
Name	PFIDC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Setms-Dealprod-Security-Access

Attribute	Description	
Name	Setms-Dealprod-Security-Access	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

SECURTYIDSR

Attribute	Description	
Name	SECURTYIDSR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ALWDSR

Attribute	Description	
Name	ALWDSR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description

Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWFTQUAL

Attribute	**Description**	
Name	SWFTQUAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTASSN

Attribute	**Description**	
Name	EVNTASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTAPPLN

Attribute	**Description**	
Name	EVNTAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTLIQDN

Attribute	**Description**	
Name	EVNTLIQDN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODUCT

Attribute	**Description**	
Name	PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COMPONENT

Attribute	**Description**	
Name	COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MRKTCD

Attribute	**Description**	
Name	MRKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Accounting-Entries

Attribute	**Description**	
Name	Accounting-Entries	
Datatype		
Description	Accounting Entry Details for Events	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR

Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description

Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SOLDCCY

Attribute	Description	
Name	SOLDCCY	
Datatype	String	
Description	Indicates Sold Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD2

Attribute	Description
Name	CSTCD2

Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

2.21.3.SD-ModifyDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*

- CLASDESC
- Dealproduct-Restrictions
  - CODE
  - PRDDESC
- Setms-Dealprod-Security-Access
  - SECURTYIDSR
  - PRDSR
  - SECURTYDESC
  - ALWDSR
- Cstms-Product-Class-Link-Dr
  - CLASCD
  - PFRESCTYPE
  - CLASDESC
- Setms-Dealprod-Pfolios-Access
  - PFID
  - PFPRODCD
  - PFDESC
  - ACSALWDFLG
- Setms-Dealproduct-Restrictions-Dr
  - CODE
  - PRDDESC
- Tatms-Product-Scheme
  - PRDORMRKTCD
  - SCHME
  - SCHMEDESC
  - Tatms-Product-Tran-Tax
    - COMP
    - STPASSN
    - TAXTYP
    - BORNBY
    - CASHOUTFLWINDI
    - NETCONSINDI
    - CONSPLUSMIN
    - SWFTQUAL
    - EVNTASSN
    - EVNTAPPLN
    - EVNTLIQDN
    - BASAMTTAG
    - DFLTRULE
    - RULEDESC
    - DFLTWAIV
    - ALLWRULAMND
    - AMNDAFTRASSN
    - ALLWAMTAMND

- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*

SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	**Description**	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	**Description**	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	**Description**	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F,</td></tr></table>

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALWDSR

Attribute	Description

Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	Description	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	Description	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPL

Attribute	Description	
Name	AMNDAFTRAPPL	
Datatype	String	
Description	Indicates Amend After Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	Description	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	Description	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.4.SD-ModifyDealProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-PK*
      - *PRDCD*
    - *Cstms-Product-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RTTYPEPRFERD*
      - *MAKER*
      - *MAKERSTAMP*
      - *Setms-Deal-Product*
        - *RATETYP*

FORW_ALLOW
SPOT_ALLOW
BROKRGALWD
PARTRELALWD
CANCELALWD
EXTNALWD
AUTMSTL
AUTDSTL
PRICE
SECURTYIDDL
TRADEDT
MSTLDT
STLDT
PFID
NOMINLUNIT
MRKTCD
FRPAY
SPOTFRWD
PFIDC1
SKLOC
SKACNT
PSTLRISKLIMTRKG
SKLOCC1
SKACNTC1
SKLOCC2
SKACNTC2
BNKSACPT
CNSDRBROKFRDISC
Cstms-Product-Class-Link-Sr
CLASCD
SECRESTYP
Dealproduct-Restrictions
CODE
Setms-Dealprod-Security-Access
SECURTYIDSR
ALWDSR
Cstms-Product-Class-Link-Dr
CLASCD
PFRESCTYPE
Setms-Dealprod-Pfolios-Access
Setms-Dealproduct-Restrictions-Dr
CODE
Tatms-Product-Tran-Tax
COMP

- *STPASSN*
- *TAXTYP*
- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *COMPONENT*
  - *MARKET_CODE*
  - *PRODUCT*

Rule-Mkt-Chg-Dtls

- *PRODUCT*
- *COMPONENT*
- *MRKTCD*
- *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*

REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
Advices
MSGTYP
SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
Mapping-Details
ACCTRL
ACCTHD
STAT
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID

Product-Charges

Charge-Details

SETTCCY

DFTWAIV

ALWRULAMND

AMNDAFTRASSOC

ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

DFTRULE

COMPNT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description

Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RATETYP

Attribute	**Description**	
Name	RATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

FORW_ALLOW

Attribute	**Description**	
Name	FORW_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	Description	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	Description	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	Description	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	Description	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOCC2

Attribute	Description	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	Description	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	Description	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,A</td></tr></table>

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ALWDSR

Attribute	Description
Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Tatms-Product-Tran-Tax

Attribute	**Description**	
Name	Tatms-Product-Tran-Tax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	**Description**	
Name	Rule-Mkt-Tax-Dtls	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRODUCT

Attribute	Description

Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Field-Details

Attribute	**Description**	
Name	Field-Details	
Datatype		
Description	Indicates Field Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNUM

Attribute	**Description**	
Name	FLDNUM	
Datatype	Number	
Description	Indicates Field Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Events

Attribute	**Description**	
Name	Product-Events	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD

Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description

Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	

Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWAMTAMND

Attribute	**Description**	
Name	ALWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendement Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPL

Attribute	**Description**	
Name	AMNDAFTRAPPL	
Datatype	String	
Description	Indicates Amend After Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	**Description**	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**
Name	ADVCHG
Datatype	String

Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.ModifySEDealBlockRelease

ModifySEDealBlockRelease

2.22.1.SD-ModifySEDealBlockRelease-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*

BLKREF
SEDSC
PRDDSC
ONCAUTH
Sdd
  PF
  PFDSC
  COUNTRPTY
  SKLC
  SKAC
  SKLOCDSC
  FRMTYP
  EVSQNO
  VRSN
Scd
  DLRFNO
Scd--A
  CRTNO
  QTYTOBLK
  STATS
Sdl
  MKID
  MKDTSTMP
  CKID
  CKDTSTMP
  TXNSTAT
  AUTHSTAT
Csvws-Contract-En
  LEGREFNO
  Sevws-Event-Log
    REFERENCE
    SR_NO
    EVENT
    EVENT_DATE
    MAKER_ID
    MAKER_DT_STAMP
    CHECKER_ID
    CHECKER_DT_STAMP
    Acvws-All-Ac-Entries
      BRANCH
      ACCOUNT
      DR_CR
      CODE
      DATE

- VALDT
- CCY
- FCY_AMOUNT
- EXG_RATE
- LCY_AMOUNT
- Csvws-Contract-Ovd
  - OVDMSGS
- Csvws-Contract
  - LEGREFNO
  - Csvws-Contract-Event-Seq
    - EVTCODE
    - EVENT_SEQ_NO
    - DESCRIPTION
  - Csvws-Contract-Event-Advice
    - ADVCD
    - SUPPRESS
    - PRIORITY
    - PRTYID
    - PRTYNAME
    - ADVDESC
    - ADDRS1
    - ADDRS2
    - ADDRS3
    - ADDRS4
    - MEDIA
    - DESCRIPTION
- Charges
  - CONREFNO
  - Charge-Association
    - COMPNT
    - CREATESN
    - RULE
    - WAIVER
    - DISACCRAPPL
    - ACCRREQD
    - DESC
  - Charge-Application
    - CREATESN
    - COMPNT
    - TGCCY
    - TGAMT
    - CHRGCCY
    - CHRGAMT
    - DISACCRAPPL

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

BLKTYP

Attribute	Description
Name	BLKTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLKREF

Attribute	Description
Name	BLKREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SEDSC

Attribute	Description
Name	SEDSC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

PRDDSC

Attribute	Description
Name	PRDDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPTY

Attribute	Description	
Name	COUNTRPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLC

Attribute	Description	
Name	SKLC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKAC

Attribute	Description	
Name	SKAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCDSC

Attribute	Description	
Name	SKLOCDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,D,I</td></tr></table>

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DLRFNO

Attribute	Description
Name	DLRFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Sdl

Attribute	Description

Name	Sdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER_ID

Attribute	**Description**	
Name	MAKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	Description	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description	
Name	SNDRRCVRINFO3	
Datatype	String	
Description	Indicates Sender Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO4

Attribute	Description	
Name	SNDRRCVRINFO4	
Datatype	String	
Description	Indicates Sender Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO5

Attribute	Description	
Name	SNDRRCVRINFO5	
Datatype	String	
Description	Indicates Sender Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.22.2.SD-ModifySEDealBlockRelease-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-IO*
    - *USRRF*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *RLSDT*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *Sdd*
      - *PF*
      - *PFDSC*
      - *COUNTRPTY*
      - *COUNTRPRTYDSC*
      - *SKLC*
      - *SKAC*
      - *SKLOCDSC*
      - *FRMTYP*
      - *PRTREF*

Csvws-Contract-En
- *LEGREFNO*

Csvws-Contract
- *LEGREFNO*
- *Csvws-Contract-Event-Advice*
  - *SUPPRESS*

Charges
- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxheadmaster
- *REFERENCE_NO*

Misdetails
- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*

REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Settlements
CONREFNO

LATEVNSEQNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *CONTREFNO*
  - *ESN*
  - *COMPNT*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *AMTTAG*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*

SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRTYDSC

Attribute	Description
Name	COUNTRPRTYDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

PRTREF

Attribute	Description
Name	PRTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	**Description**	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Settlement

Attribute	**Description**	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

IBANACNO

Attribute	**Description**	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**

Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	**Description**	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

2.22.3.SD-ModifySEDealBlockRelease-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sdm-Full*
    - *VRNO*
    - *VERSION_NO*
    - *USRRF*
    - *PRD*
    - *DLRF*
    - *SECD*
    - *SECSE*
    - *NMQT*
    - *BLKDT*
    - *RLSDT*
    - *TRN_DATE*
    - *PRTRELALLW*
    - *AUTRELALLW*
    - *DLQTY*
    - *BLKTYP*
    - *BLKREF*
    - *SEDSC*
    - *PRDDSC*

ONCAUTH

Sdd

- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd

- *DLRFNO*

Scd--A

- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl

- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En

- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*
    - *VALDT*
    - *CCY*
    - *FCY_AMOUNT*

EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Charges
CONREFNO
Charge-Association
COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6

- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TRN_DATE

Attribute	Description
Name	TRN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLQTY

Attribute	**Description**	
Name	DLQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BLKTYP

Attribute	**Description**	
Name	BLKTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BLKREF

Attribute	**Description**	
Name	BLKREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SEDSC

Attribute	**Description**	
Name	SEDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DLRFNO

Attribute	Description
Name	DLRFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sdl

Attribute	Description
Name	Sdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description

Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**

Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	**Description**	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	**Description**	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	**Description**	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1

Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	**Description**	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC

Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1

Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String

Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description

Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	**Description**	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	**Description**	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	**Description**	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	Description	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.4.SD-ModifySEDealBlockRelease-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sdm-PK*
      - *DLRF*
    - *Sdm-IO*
      - *USRRF*
      - *DLRF*
      - *SECD*
      - *SECSE*
      - *RLSDT*
      - *PRTRELALLW*
      - *AUTRELALLW*
      - *DLQTY*
      - *Sdd*
        - *PF*
        - *PFDSC*
        - *COUNTRPTY*
        - *COUNTRPRTYDSC*
        - *SKLC*
        - *SKAC*

- *SKLOCDSC*
- *FRMTYP*
- *PRTREF*

Csvws-Contract-En

- *LEGREFNO*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Advice*
  - *SUPPRESS*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxheadmaster

- *REFERENCE_NO*

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails

- *Fundmisdetails*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *Settlement-Detail*
      - *INSTRCD1*
      - *INSTRCD2*
      - *INSTRCD3*
      - *INSTRCD4*
      - *ITIMEIND1*
      - *ITIMEIND2*
      - *ITIMEIND3*
      - *INSTRCD5*
      - *CONTREFNO*
      - *ESN*
      - *COMPNT*
      - *BANKOPERCD*
      - *INSTRCD6*
      - *TRNSTYPCD*
      - *REGREP1*
      - *REGREP2*
      - *REGREP3*
      - *ENVCONT1*
      - *ENVCONT2*
      - *ENVCONT3*
      - *ENVCONT4*
      - *ENVCONT5*
    - *Lcl_Clearing*
      - *AMTTAG*

SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sdm-PK

Attribute	Description
Name	Sdm-PK
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTRELALLW

Attribute	Description
Name	PRTRELALLW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTRELALLW

Attribute	Description
Name	AUTRELALLW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLQTY

Attribute	Description
Name	DLQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Sdd

Attribute	Description
Name	Sdd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PF

Attribute	Description
Name	PF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PFDSC

Attribute	Description
Name	PFDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPTY

Attribute	Description
Name	COUNTRPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COUNTRPRTYDSC

Attribute	Description
Name	COUNTRPRTYDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,D,I</td></tr></table>

TOP

PRTREF

Attribute	Description
Name	PRTREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	Description	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,CRED,SPAY,SPRI,SSTD</td></tr></table>

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

TRNSTYPCD

Attribute	Description

Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1

Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	**Description**	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	**Description**	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**

Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC

Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.ModifySecBlockDeal

ModifySecBlockDeal

2.23.1.SD-ModifySecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
  LEGPRD
  MSTLDATE
  AUTOMSTL
  PORTFOLIO
  CNTPARTY
  PAYACCBRN
  PAYACC
  SKLOCATION
  SKACCNT
  BROKER
  SLRBUYSELL
  LEGDESC
  SLSKLOCATIONDESC
  DEAL_REFERENCE_NO
  MLLEGPRD
  MLLEGDESC
Svsmuldet
  PORTFOLIO
  CNTPARTY

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,PRI,PPR,PRM,PPM,YTM</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	**Description**	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	**Description**
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

2.23.2.SD-ModifySecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *DEALTYPE*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*
    - *FORMAT*
    - *REMRKS*
    - *FCVALUT*
    - *FCVALDL*

BRANCH
PRODTYP
SECTYP
SECSCTY
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
LCYPRICE
DEALER
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *DEALQTY*
- *SLDEALINP*
- *SLABSPRI*
- *SLYIELDFRINFO*
- *SLRBUYSELL*

Svsmuldet
- *PORTFOLIO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

FCVALUT

Attribute	Description
Name	FCVALUT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCVALDL

Attribute	Description
Name	FCVALDL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTYP

Attribute	Description
Name	SECTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSCTY

Attribute	Description
Name	SECSCTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

LCYPRICE

Attribute	**Description**	
Name	LCYPRICE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	**Description**	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	**Description**	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLDEALINP

Attribute	Description
Name	SLDEALINP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRI

Attribute	Description
Name	SLABSPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYIELDFRINFO

Attribute	Description
Name	SLYIELDFRINFO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.23.3.SD-ModifySecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	**Description**	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	**Description**	
Name	DLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOWP

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.4.SD-ModifySecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
      - *SECTYCD*
      - *MKTCD*
      - *DEALTYPE*
      - *DEALQTY*
      - *TRADEDT*
      - *INTERST*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*
      - *RECIEVE*
      - *INPRICE*
      - *YIELD*
      - *FORMAT*

REMRKS
FCVALUT
FCVALDL
BRANCH
PRODTYP
SECTYP
SECSCTY
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
LCYPRICE
DEALER
Svssingdet
LEGPRD
MSTLDATE
AUTOMSTL
PORTFOLIO
CNTPARTY
PAYACCBRN
PAYACC
SKLOCATION
SKACCNT
BROKER
DEALQTY
SLDEALINP
SLABSPRI
SLYIELDFRINFO
SLRBUYSELL
Svsmuldet
PORTFOLIO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

DELIVER

Attribute	**Description**	
Name	DELIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

PRIQT

Attribute	**Description**	
Name	PRIQT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	**Description**	
Name	DSTLDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDT

Attribute	**Description**	
Name	INTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,D,I,C</td></tr></table>

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCVALUT

Attribute	Description
Name	FCVALUT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCVALDL

Attribute	Description
Name	FCVALDL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

PRODTYP

Attribute	Description
Name	PRODTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTYP

Attribute	Description
Name	SECTYP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSCTY

Attribute	Description
Name	SECSCTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLDEALINP

Attribute	Description
Name	SLDEALINP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRI

Attribute	Description
Name	SLABSPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYIELDFRINFO

Attribute	Description
Name	SLYIELDFRINFO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

Svsmuldet

Attribute	**Description**	
Name	Svsmuldet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.ModifySecuritiesDeal

ModifySecuritiesDeal

2.24.1.SD-ModifySecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
  LEGREF
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4

Dealmastera
- *DEALREF*

Ytmmaster
- *DEALREF*
- *EFFDT*
- *YTM*

Certificates
- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb
- *DEALREF*

Contract
- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref
- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	**Description**
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	**Description**
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.24.2.SD-ModifySecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DLVRFREEPAY*
    - *RECVFREEPAY*
    - *DEALREF*
    - *VERSION*
    - *Brokerage*
      - *CONREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
      - *Charge-Association*
        - *COMPNT*
        - *CREATESN*
        - *RULE*
        - *WAIVER*
        - *DISACCRAPPL*
        - *ACCRREQD*
        - *DESC*
      - *Charge-Application*

- *COMPNT*
- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *Settlement-Detail*
      - *INSTRCD1*
      - *INSTRCD2*
      - *INSTRCD3*
      - *INSTRCD4*
      - *ITIMEIND1*
      - *ITIMEIND2*
      - *ITIMEIND3*
      - *INSTRCD5*
      - *CONTREFNO*
      - *ESN*
      - *COMPNT*
      - *BANKOPERCD*
      - *INSTRCD6*

TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Taxheadmaster
REFERENCE_NO
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Advice
SUPPRESS
Csvws-Contract-En
LEGREFNO
Cntdl
CONTREFNO
Csvwscnrt
CONTREFNO
Lgrf
LEGREFNO
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 1

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**
	minOccurs / 1
Restrictions	**Restrictions** / **Description**
	maxLength / 10

TOP

CREATESN

Attribute	**Description**

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3

Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Csvws-Contract-En

Attribute	Description

Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.24.3.SD-ModifySecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- BKAMT
- LQSTAT
- LQREFNO
- BROKNAM

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

- *Fundmisdetails*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Csvws-Contract*
  - *LEGREFNO*
  - *Csvws-Contract-Event-Seq*
    - *EVTCODE*
    - *EVENT_SEQ_NO*
    - *DESCRIPTION*
  - *Csvws-Contract-Event-Advice*
    - *ADVCD*
    - *SUPPRESS*
    - *PRIORITY*
    - *PRTYID*
    - *PRTYNAME*
    - *ADVDESC*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *MEDIA*

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

- *AMNTCMPCRCY*
- *PAYMNCURCY*
- *RATE*
- *AMONCURCY*
- *SIGN*

Csvwscnrt

Svwmtchdl

- *MTCHLREF*
- *STLDT*
- *MTCHQTY*

Unrelmtch

- *TOTREM*
- *TOTMTCH*
- *TOTREQD*

Lgrf

LEGREFNO

LATEVNTSQNO

LGDSCRPTN

PORTFLID

Msgs

- *VRSN*
- *MSGTP*
- *PRTID*
- *PRTNM*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *ADDRS5*
- *ADDRS6*
- *ADDNL1*
- *ADDNL2*
- *ADDNL3*
- *ADVCDSCRP*

Partdtl

- *VERSON*
- *PRTYP*
- *ADDRESS1*
- *ADDRESS2*
- *ADDRESS3*
- *ADDRESS4*
- *MSEGTP*
- *ADVICEDSCRPT*

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description	
Name	DEALTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	Description	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealmastera

Attribute	Description	
Name	Dealmastera	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	**Description**
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	**Description**
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	**Description**
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	**Description**

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	Description	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.4.SD-ModifySecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DLVRFREEPAY*
      - *RECVFREEPAY*
      - *DEALREF*
      - *VERSION*
      - *Brokerage*
        - *CONREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
        - *Charge-Association*
          - *COMPNT*
          - *CREATESN*
          - *RULE*
          - *WAIVER*

- *DISACCRAPPL*
- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*
    - *INSTRCD4*
    - *ITIMEIND1*
    - *ITIMEIND2*
    - *ITIMEIND3*
    - *INSTRCD5*
    - *CONTREFNO*

ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2

REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9

FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Taxheadmaster
REFERENCE_NO
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Advice
SUPPRESS
Csvws-Contract-En
LEGREFNO
Cntdl
CONTREFNO
Csvwscnrt
CONTREFNO
Lgrf
LEGREFNO
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	**Description**	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement

Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1

Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description

Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2

Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	**Description**	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	14

TOP

PMNTTYP

Attribute	**Description**	
Name	PMNTTYP	
Datatype	String	
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract

Attribute	**Description**

Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Lgrf

Attribute	**Description**	
Name	Lgrf	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.QueryDealProduct

Query of Securities Deal Product

2.25.1.SD-QueryDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.25.2.SD-QueryDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-IO*
      - *PRDCD*
    - *Cstms-Product-Full*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *PRDTYP*
      - *RTCODEPRFERD*
      - *RTTYPEPRFERD*
      - *PRDTYPDESC*
      - *PRODGRPDESC*
      - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
  RATETYP
  FORW_ALLOW
  SPOT_ALLOW
  BROKRGALWD
  PARTRELALWD
  CANCELALWD
  EXTNALWD
  AUTMSTL
  AUTDSTL
  PRICE
  SECURTYIDDL
  TRADEDT
  MSTLDT
  STLDT
  PFID
  NOMINLUNIT
  MRKTCD
  FRPAY
  SPOTFRWD
  PFIDC1
  SKLOC
  SKACNT
  CLNRISKLIMTRKG
  PSTLRISKLIMTRKG
  SKLOCC1
  SKACNTC1
  SKLOCC2
  SKACNTC2
  BNKSACPT
  CNSDRBROKFRDISC
  MRKTDESC
  SKLOCDESC
  SKLOCDESCFRM
  SKLOCDESCTO
Cstms-Product-Class-Link
  CLASCD
  CLASDESC

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions
- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access
- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr
- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access
- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr
- *CODE*
- *PRDDESC*

Tatms-Product-Scheme
- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*

ALLWRULAMND
AMNDAFTRASSN
ALLWAMTAMND
AMNDAFTRAPPLN
Rule-Mkt-Tax-Dtls
RULE
MARKET_CODE
Product-Charges-Mkt
PRDCD
PRDDESC
Rule-Mkt-Chg-Dtls
COMPONENT
MRKTCD
RULE
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS
PRIOR

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY

DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,B,</td></tr></table>

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EXTNALWD

Attribute	Description
Name	EXTNALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTMSTL

Attribute	Description
Name	AUTMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTDSTL

Attribute	Description
Name	AUTDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNT

Attribute	**Description**	
Name	SKACNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CLNRISKLIMTRKG

Attribute	**Description**	
Name	CLNRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACNTC2

Attribute	Description
Name	SKACNTC2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BNKSACPT

Attribute	Description
Name	BNKSACPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CNSDRBROKFRDISC

Attribute	Description
Name	CNSDRBROKFRDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Cstms-Product-Class-Link-Sr

Attribute	**Description**	
Name	Cstms-Product-Class-Link-Sr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

SECRESTYP

Attribute	**Description**	
Name	SECRESTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ALWDSR

Attribute	Description
Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PFRESCTYPE

Attribute	**Description**	
Name	PFRESCTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	**Description**	
Name	Setms-Dealprod-Pfolios-Access	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description

Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONSPLUSMIN

Attribute	**Description**	
Name	CONSPLUSMIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWFTQUAL

Attribute	**Description**	
Name	SWFTQUAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTASSN

Attribute	**Description**	
Name	EVNTASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTAPPLN

Attribute	**Description**	
Name	EVNTAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTLIQDN

Attribute	**Description**	
Name	EVNTLIQDN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRULE

Attribute	**Description**	
Name	DFLTRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number

Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,A</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description

Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String

Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**	
Name	EVNTFRASSC	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRLIQ

Attribute	**Description**	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	**Description**	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.QuerySEDealBlockRelease

QuerySEDealBlockRelease

2.26.1.SD-QuerySEDealBlockRelease-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Sdm-IO*
  - *DLRF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.26.2.SD-QuerySEDealBlockRelease-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sdm-IO*
      - *DLRF*
    - *Sdm-Full*
      - *VRNO*
      - *VERSION_NO*
      - *USRRF*
      - *PRD*
      - *DLRF*
      - *SECD*
      - *SECSE*
      - *NMQT*
      - *BLKDT*
      - *RLSDT*
      - *TRN_DATE*
      - *PRTRELALLW*
      - *AUTRELALLW*
      - *DLQTY*
      - *BLKTYP*

BLKREF
SEDSC
PRDDSC
ONCAUTH
Sdd
- *PF*
- *PFDSC*
- *COUNTRPTY*
- *SKLC*
- *SKAC*
- *SKLOCDSC*
- *FRMTYP*
- *EVSQNO*
- *VRSN*

Scd
- *DLRFNO*

Scd--A
- *CRTNO*
- *QTYTOBLK*
- *STATS*

Sdl
- *MKID*
- *MKDTSTMP*
- *CKID*
- *CKDTSTMP*
- *TXNSTAT*
- *AUTHSTAT*

Csvws-Contract-En
- *LEGREFNO*
- *Sevws-Event-Log*
  - *REFERENCE*
  - *SR_NO*
  - *EVENT*
  - *EVENT_DATE*
  - *MAKER_ID*
  - *MAKER_DT_STAMP*
  - *CHECKER_ID*
  - *CHECKER_DT_STAMP*
  - *Acvws-All-Ac-Entries*
    - *BRANCH*
    - *ACCOUNT*
    - *DR_CR*
    - *CODE*
    - *DATE*

- *VALDT*
- *CCY*
- *FCY_AMOUNT*
- *EXG_RATE*
- *LCY_AMOUNT*
- *Csvws-Contract-Ovd*
  - *OVDMSGS*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*
  - *ADDRS3*
  - *ADDRS4*
  - *MEDIA*
  - *DESCRIPTION*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*

- *WAIVER*
- *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3

- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sdm-IO

Attribute	Description
Name	Sdm-IO
Datatype	
Description	

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sdm-Full

Attribute	Description
Name	Sdm-Full
Datatype	
Description	

TOP

VRNO

Attribute	Description
Name	VRNO
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION_NO

Attribute	Description
Name	VERSION_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

USRRF

Attribute	Description
Name	USRRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DLRF

Attribute	Description
Name	DLRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECD

Attribute	Description
Name	SECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECSE

Attribute	Description
Name	SECSE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

NMQT

Attribute	Description
Name	NMQT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,N</td></tr></table>

TOP

BLKDT

Attribute	Description
Name	BLKDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RLSDT

Attribute	Description
Name	RLSDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TRN_DATE

Attribute	**Description**	
Name	TRN_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRTRELALLW

Attribute	**Description**	
Name	PRTRELALLW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTRELALLW

Attribute	**Description**	
Name	AUTRELALLW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLQTY

Attribute	**Description**	
Name	DLQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BLKTYP

Attribute	**Description**
Name	BLKTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLKREF

Attribute	Description
Name	BLKREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SEDSC

Attribute	Description
Name	SEDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRDDSC

Attribute	Description
Name	PRDDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ONCAUTH

Attribute	Description
Name	ONCAUTH
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sdd

Attribute	**Description**	
Name	Sdd	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PF

Attribute	**Description**	
Name	PF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PFDSC

Attribute	**Description**	
Name	PFDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPTY

Attribute	**Description**	
Name	COUNTRPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDSC

Attribute	Description
Name	SKLOCDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Scd

Attribute	Description
Name	Scd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DLRFNO

Attribute	Description
Name	DLRFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Scd--A

Attribute	Description
Name	Scd--A
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRTNO

Attribute	Description
Name	CRTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

QTYTOBLK

Attribute	Description
Name	QTYTOBLK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STATS

Attribute	Description
Name	STATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Sdl

Attribute	Description
Name	Sdl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CKID

Attribute	Description
Name	CKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CKDTSTMP

Attribute	Description
Name	CKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H,L,Y

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description

Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	Description	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	Description	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO

Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDINDICAT

Attribute	Description	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	Description	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description

Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	**Description**	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND

Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	**Description**	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description

Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3

Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5

Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	Description	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	**Description**	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER

Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String

Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>34</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.27.QuerySecBlockDeal

QuerySecBlockDeal

2.27.1.SD-QuerySecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.27.2.SD-QuerySecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
    - *Svsblkdlmas-Full*
      - *PRD*
      - *DEALREFNO*
      - *USERREF*
      - *SECTYCD*
      - *MKTCD*
      - *TRANDTE*
      - *DEALTYPE*
      - *QUOTEBY*
      - *DEALQTY*
      - *TRADEDT*
      - *INTERST*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description

Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description	
Name	SECCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPOT_PRICE

Attribute	Description	
Name	SPOT_PRICE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SETTSKL

Attribute	Description	
Name	SETTSKL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	Description	
Name	ISMA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	**Description**	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	**Description**	
Name	AUTHORIZED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	Description	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	Description	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	Description	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CNTPARTY

Attribute	Description	
Name	CNTPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PAYACCBRN

Attribute	Description	
Name	PAYACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PAYACC

Attribute	Description	
Name	PAYACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SKLOCATION

Attribute	Description	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	Description	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,S</td></tr></table>

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SLSKLOCATIONDESC

Attribute	Description
Name	SLSKLOCATIONDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.QuerySecuritiesDeal

QuerySecuritiesDeal

2.28.1.SD-QuerySecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION

Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.28.2.SD-QuerySecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-Full*
      - *FACEDEAL*
      - *YTM*
      - *DISCOUNT*
      - *PREMIUM*
      - *ABSPREMIUM*
      - *ABSDISCOUNT*
      - *FORWDPL*
      - *ADJDEALPRC*
      - *ABSPRICE*
      - *INTDAYS*
      - *INTAMT*
      - *TRADEDT*
      - *AUTOMANDSTL*
      - *DSTLCOMPLETED*

DSTLDATE
ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF

DEALTIME
PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*

ORGMSTLDT
MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT

- *DESCRIPTION*
- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*

FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
  LEGREF
  CPTY
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Walkinto
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3

- *ADDRLINE4*
- *Dealmastera*
  - *DEALREF*
- *Ytmmaster*
  - *DEALREF*
  - *EFFDT*
  - *YTM*
- *Certificates*
  - *DEALREF*
  - *CERTNO*
  - *CERTQT*
  - *UNIT_NOM_QUOTE*
- *Dealmasterb*
  - *DEALREF*
- *Contract*
  - *SERIAL*
  - *ESN*
  - *UREF*
  - *LATVERNO*
  - *PRDCODE*
  - *CPTY*
  - *TEMPSTAT*
  - *PRDTYPE*
  - *CEC*
  - *MDCODE*
  - *UDSTAT*
  - *CONTCCY*
  - *LEVENTDT*
  - *XREF*
  - *AMFLAG*
  - *FREFNO*
  - *RESPSTAT*
  - *SECUPDSTAT*
  - *STOPDT*
  - *LIBCIF*
  - *SRC*
  - *REFERCREF*
- *Multiref*
  - *VERNO*
  - *LEGREFNO*
  - *Brokerage*
    - *CONREFNO*
    - *BOKBROKER*
    - *BROKAMT*

- *BROKCCY*
- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*

ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3

ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*

ITIMEIND2
ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4

SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4

COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8

- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*

ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY

- *SIGN*
  - *Dlintr*
    - *CMPNTDSC*
    - *COMPNTCRCY*
    - *AMNTCMPCRCY*
    - *PAYMNCURCY*
    - *RATE*
    - *AMONCURCY*
    - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*

ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,S

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	**Description**	
Name	TXNTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CERTNOS

Attribute	**Description**	
Name	CERTNOS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

LIMITSTRACKINGREQD

Attribute	**Description**	
Name	LIMITSTRACKINGREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATETYPE

Attribute	**Description**	
Name	RATETYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	**Description**	
Name	RATEPCYSCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SCCY

Attribute	**Description**	
Name	SCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INTVALDT

Attribute	**Description**	
Name	INTVALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BROKERID

Attribute	**Description**	
Name	BROKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYPFROM

Attribute	**Description**	
Name	FRMTYPFROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CALBDONE

Attribute	Description
Name	CALBDONE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BRKID

Attribute	**Description**	
Name	BRKID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description	
Name	WALKINMEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDRLINE1

Attribute	Description	
Name	ADDRLINE1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FUNDREFNO

Attribute	Description	
Name	FUNDREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PMTADVPROCESSED

Attribute	Description
Name	PMTADVPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

UNEXPOSURE

Attribute	**Description**	
Name	UNEXPOSURE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PORTREF

Attribute	Description	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	Description	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	Description	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYPFROM

Attribute	**Description**	
Name	FRMTYPFROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PARTYPROCESSED

Attribute	Description
Name	PARTYPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PMTADVPROCESSED

Attribute	Description
Name	PMTADVPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

LEGREFNOTO

Attribute	Description
Name	LEGREFNOTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Walkinto

Attribute	**Description**	
Name	Walkinto	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Ytmmaster

Attribute	**Description**	
Name	Ytmmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EFFDT

Attribute	**Description**	
Name	EFFDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

YTM

Attribute	**Description**	
Name	YTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Certificates

Attribute	**Description**

Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description
Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UREF

Attribute	**Description**	
Name	UREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LATVERNO

Attribute	**Description**	
Name	LATVERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	22

TOP

PRDCODE

Attribute	**Description**	
Name	PRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2

TOP

UDSTAT

Attribute	Description
Name	UDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

LEVENTDT

Attribute	Description
Name	LEVENTDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERNO

Attribute	Description

Name	VERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.ReopenDealProduct

ReopenDealProduct

2.29.1.SD-ReopenDealProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*
- *CLASDESC*

Dealproduct-Restrictions
- *CODE*
- *PRDDESC*

Setms-Dealprod-Security-Access
- *SECURTYIDSR*
- *PRDSR*
- *SECURTYDESC*
- *ALWDSR*

Cstms-Product-Class-Link-Dr
- *CLASCD*
- *PFRESCTYPE*
- *CLASDESC*

Setms-Dealprod-Pfolios-Access
- *PFID*
- *PFPRODCD*
- *PFDESC*
- *ACSALWDFLG*

Setms-Dealproduct-Restrictions-Dr
- *CODE*
- *PRDDESC*

Tatms-Product-Scheme
- *PRDORMRKTCD*
- *SCHME*
- *SCHMEDESC*
- *Tatms-Product-Tran-Tax*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*
  - *DFLTRULE*
  - *RULEDESC*
  - *DFLTWAIV*

- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*

CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY

DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,

TOP

RTTYPEPRFERD

Attribute	**Description**	
Name	RTTYPEPRFERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODGRPDESC

Attribute	**Description**	
Name	PRODGRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPOT_ALLOW

Attribute	**Description**	
Name	SPOT_ALLOW	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BROKRGALWD

Attribute	**Description**	
Name	BROKRGALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTRELALWD

Attribute	**Description**	
Name	PARTRELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CANCELALWD

Attribute	**Description**	
Name	CANCELALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	Description	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	Description	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	Description	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	Description
Name	SECURTYIDDL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NOMINLUNIT

Attribute	Description
Name	NOMINLUNIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRPAY

Attribute	Description
Name	FRPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,F,

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMTRKG

Attribute	**Description**	
Name	PSTLRISKLIMTRKG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SKLOCC1

Attribute	**Description**	
Name	SKLOCC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC1

Attribute	**Description**	
Name	SKACNTC1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOCC2

Attribute	**Description**	
Name	SKLOCC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealproduct-Restrictions

Attribute	Description
Name	Dealproduct-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

ALWDSR

Attribute	Description
Name	ALWDSR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWAMTAMND

Attribute	Description	
Name	ALLWAMTAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description	
Name	Rule-Mkt-Tax-Dtls	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	Description	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	Description	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.29.2.SD-ReopenDealProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *MAKER*
    - *MAKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.29.3.SD-ReopenDealProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *PRDTYP*
    - *RTCODEPRFERD*
    - *RTTYPEPRFERD*
    - *PRDTYPDESC*
    - *PRODGRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Setms-Deal-Product
- *RATETYP*
- *FORW_ALLOW*
- *SPOT_ALLOW*
- *BROKRGALWD*
- *PARTRELALWD*
- *CANCELALWD*
- *EXTNALWD*
- *AUTMSTL*
- *AUTDSTL*
- *PRICE*
- *SECURTYIDDL*
- *TRADEDT*
- *MSTLDT*
- *STLDT*
- *PFID*
- *NOMINLUNIT*
- *MRKTCD*
- *FRPAY*
- *SPOTFRWD*
- *PFIDC1*
- *SKLOC*
- *SKACNT*
- *CLNRISKLIMTRKG*
- *PSTLRISKLIMTRKG*
- *SKLOCC1*
- *SKACNTC1*
- *SKLOCC2*
- *SKACNTC2*
- *BNKSACPT*
- *CNSDRBROKFRDISC*
- *MRKTDESC*
- *SKLOCDESC*
- *SKLOCDESCFRM*
- *SKLOCDESCTO*

Cstms-Product-Class-Link
- *CLASCD*
- *CLASDESC*

Cstms-Product-Class-Link-Sr
- *CLASCD*
- *SECRESTYP*

- CLASDESC
- Dealproduct-Restrictions
  - CODE
  - PRDDESC
- Setms-Dealprod-Security-Access
  - SECURTYIDSR
  - PRDSR
  - SECURTYDESC
  - ALWDSR
- Cstms-Product-Class-Link-Dr
  - CLASCD
  - PFRESCTYPE
  - CLASDESC
- Setms-Dealprod-Pfolios-Access
  - PFID
  - PFPRODCD
  - PFDESC
  - ACSALWDFLG
- Setms-Dealproduct-Restrictions-Dr
  - CODE
  - PRDDESC
- Tatms-Product-Scheme
  - PRDORMRKTCD
  - SCHME
  - SCHMEDESC
  - Tatms-Product-Tran-Tax
    - COMP
    - STPASSN
    - TAXTYP
    - BORNBY
    - CASHOUTFLWINDI
    - NETCONSINDI
    - CONSPLUSMIN
    - SWFTQUAL
    - EVNTASSN
    - EVNTAPPLN
    - EVNTLIQDN
    - BASAMTTAG
    - DFLTRULE
    - RULEDESC
    - DFLTWAIV
    - ALLWRULAMND
    - AMNDAFTRASSN
    - ALLWAMTAMND

- *AMNDAFTRAPPLN*
- *Rule-Mkt-Tax-Dtls*
  - *RULE*
  - *MARKET_CODE*

Product-Charges-Mkt

- *PRDCD*
- *PRDDESC*
- *Rule-Mkt-Chg-Dtls*
  - *COMPONENT*
  - *MRKTCD*
  - *RULE*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*

- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*
- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*

SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL
STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / M,B,

TOP

RTTYPEPRFERD

Attribute	Description
Name	RTTYPEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PRODGRPDESC

Attribute	Description
Name	PRODGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Setms-Deal-Product

Attribute	Description
Name	Setms-Deal-Product
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RATETYP

Attribute	Description
Name	RATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

FORW_ALLOW

Attribute	Description
Name	FORW_ALLOW

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPOT_ALLOW

Attribute	Description
Name	SPOT_ALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BROKRGALWD

Attribute	Description
Name	BROKRGALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTRELALWD

Attribute	Description
Name	PARTRELALWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CANCELALWD

Attribute	Description
Name	CANCELALWD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXTNALWD

Attribute	**Description**	
Name	EXTNALWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTMSTL

Attribute	**Description**	
Name	AUTMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTDSTL

Attribute	**Description**	
Name	AUTDSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURTYIDDL

Attribute	Description	
Name	SECURTYIDDL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MSTLDT

Attribute	Description	
Name	MSTLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STLDT

Attribute	Description	
Name	STLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PFID

Attribute	Description	
Name	PFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NOMINLUNIT

Attribute	Description	
Name	NOMINLUNIT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTCD

Attribute	Description	
Name	MRKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FRPAY

Attribute	Description	
Name	FRPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

SPOTFRWD

Attribute	Description
Name	SPOTFRWD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F,</td></tr></table>

TOP

PFIDC1

Attribute	Description
Name	PFIDC1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACNT

Attribute	Description
Name	SKACNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CLNRISKLIMTRKG

Attribute	Description
Name	CLNRISKLIMTRKG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PSTLRISKLIMTRKG

Attribute	Description
Name	PSTLRISKLIMTRKG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SKLOCC1

Attribute	Description
Name	SKLOCC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACNTC1

Attribute	Description
Name	SKACNTC1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOCC2

Attribute	Description
Name	SKLOCC2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACNTC2

Attribute	**Description**	
Name	SKACNTC2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BNKSACPT

Attribute	**Description**	
Name	BNKSACPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CNSDRBROKFRDISC

Attribute	**Description**	
Name	CNSDRBROKFRDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCFRM

Attribute	Description
Name	SKLOCDESCFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Cstms-Product-Class-Link

Attribute	Description
Name	Cstms-Product-Class-Link
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Cstms-Product-Class-Link-Sr

Attribute	Description
Name	Cstms-Product-Class-Link-Sr
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

SECRESTYP

Attribute	Description
Name	SECRESTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Dealproduct-Restrictions

Attribute	**Description**	
Name	Dealproduct-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	**Description**	
Name	CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Setms-Dealprod-Security-Access

Attribute	Description
Name	Setms-Dealprod-Security-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURTYIDSR

Attribute	Description
Name	SECURTYIDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDSR

Attribute	Description
Name	PRDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECURTYDESC

Attribute	Description
Name	SECURTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALWDSR

Attribute	Description

Name	ALWDSR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Cstms-Product-Class-Link-Dr

Attribute	Description
Name	Cstms-Product-Class-Link-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

PFRESCTYPE

Attribute	Description
Name	PFRESCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Setms-Dealprod-Pfolios-Access

Attribute	Description
Name	Setms-Dealprod-Pfolios-Access
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PFPRODCD

Attribute	Description
Name	PFPRODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACSALWDFLG

Attribute	Description
Name	ACSALWDFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Setms-Dealproduct-Restrictions-Dr

Attribute	Description
Name	Setms-Dealproduct-Restrictions-Dr
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tatms-Product-Scheme

Attribute	Description
Name	Tatms-Product-Scheme

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHMEDESC

Attribute	Description
Name	SCHMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tatms-Product-Tran-Tax

Attribute	Description
Name	Tatms-Product-Tran-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,S,</td></tr></table>

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Mkt-Tax-Dtls

Attribute	Description
Name	Rule-Mkt-Tax-Dtls
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MARKET_CODE

Attribute	Description
Name	MARKET_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Charges-Mkt

Attribute	Description
Name	Product-Charges-Mkt
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rule-Mkt-Chg-Dtls

Attribute	Description
Name	Rule-Mkt-Chg-Dtls
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

MRKTCD

Attribute	Description
Name	MRKTCD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Event-Details

Attribute	Description	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	Description	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

EVENTDESC

Attribute	Description	
Name	EVENTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description	
Name	NTCNSINDI	
Datatype	String	
Description	Indicates Net Consideration Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description	
Name	NETCONSPLSMINS	
Datatype	String	
Description	Indicates Add/Subtract Add : A Subtract : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**	
Name	PROPREQD	
Datatype	String	
Description	Indicates Propagation Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**
Name	DFTRULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.4.SD-ReopenDealProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-PK*
      - *PRDCD*
    - *Cstms-Product-IO*
      - *PRDCD*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.ReopenSecuritiesDeal

ReopenSecuritiesDeal

2.30.1.SD-ReopenSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinto
- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Dealmastera
- *DEALREF*

Ytmmaster
- *DEALREF*
- *EFFDT*
- *YTM*

Certificates
- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb
- *DEALREF*

Contract
- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref
- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUMEXINDICATOR

Attribute	**Description**	
Name	CUMEXINDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BUYLEG

Attribute	**Description**	
Name	BUYLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LGPRDCODE

Attribute	**Description**	
Name	LGPRDCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDNL1

Attribute	**Description**	
Name	ADDNL1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDNL2

Attribute	**Description**	
Name	ADDNL2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDNL3

Attribute	**Description**	
Name	ADDNL3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADVCDSCRP

Attribute	**Description**	
Name	ADVCDSCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.30.2.SD-ReopenSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
    - *Brokerage*
      - *CONREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Misdetails*
      - *CONREFNO*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *Csvws-Contract*
      - *LEGREFNO*
    - *Csvws-Contract-En*
      - *LEGREFNO*

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract

Attribute	**Description**	
Name	Csvws-Contract	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-En

Attribute	**Description**	
Name	Csvws-Contract-En	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.30.3.SD-ReopenSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- LEGREF
- CPTY
- UNEXPOSURE
- TOTEXPOSURE
- CLEANRISKLIMIT
- PSTLRISKLIMIT

Walkinfrom

- LEGREF
- WALKINNAME
- WALKINMEDIA
- ADDRLINE1
- ADDRLINE2
- ADDRLINE3
- ADDRLINE4

Detalto

- BRANCH
- DEALREF
- LGPRDCODE
- LEGREF
- LEGUSERREF
- VERSION
- EVENTCODE
- MSTLDT
- AUTOMSTL
- ORGMSTLDT
- MSTLCOMPLETED
- DEALER
- PORTREF
- PORTFOLIO
- POSITIONREFNO
- CPTY
- NETCONSIDERATION
- PCY
- PAYBRNTO
- PAYACCTO
- ACMP_WDRW
- SKACC
- FRMTYPFROM
- SKLOCTO
- SKACCTO
- FRMTYPTO
- BRKPKPDONE
- CHARGEPKPDONE
- INTREFERDONE

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- BKAMT
- LQSTAT
- LQREFNO
- BROKNAM

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP

CRRATEESN

RULE

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

Csvws-Contract

LEGREFNO

Csvws-Contract-Event-Seq

EVTCODE

EVENT_SEQ_NO

DESCRIPTION

Csvws-Contract-Event-Advice

ADVCD

SUPPRESS

PRIORITY

PRTYID

PRTYNAME

ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN
Dlintr
CMPNTDSC
COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description	
Name	DEALTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	Description	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	**Description**	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	**Description**	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	**Description**	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	**Description**	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SETTLEPICKUPDONE

Attribute	Description
Name	SETTLEPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXPICKUPDONE

Attribute	Description
Name	TAXPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MISPICKUPDONE

Attribute	Description
Name	MISPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	**Description**
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	**Description**
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	**Description**
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	**Description**

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.4.SD-ReopenSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
      - *Brokerage*
        - *CONREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Misdetails*
        - *CONREFNO*
      - *Taxheadmaster*
        - *REFERENCE_NO*

Csvws-Contract

LEGREFNO

Csvws-Contract-En

LEGREFNO

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.ReverseSecBlockDeal

ReverseSecBlockDeal

2.31.1.SD-ReverseSecBlockDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

RECIEVE
INPRICE
YIELD
ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*

SKLOCATION
SKLOCDES
SKACCNT
BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREFNO

Attribute	Description	
Name	DEALREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SCTYDESC

Attribute	Description
Name	SCTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DEAL_STATUS

Attribute	Description
Name	DEAL_STATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,S,V,L,H,R</td></tr></table>

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Svssingdet

Attribute	Description
Name	Svssingdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGPRD

Attribute	Description
Name	LEGPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDES

Attribute	Description
Name	SKLOCDES
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	**Description**
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

2.31.2.SD-ReverseSecBlockDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-IO*
    - *DEALREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.31.3.SD-ReverseSecBlockDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsblkdlmas-Full*
    - *PRD*
    - *DEALREFNO*
    - *USERREF*
    - *SECTYCD*
    - *MKTCD*
    - *TRANDTE*
    - *DEALTYPE*
    - *QUOTEBY*
    - *DEALQTY*
    - *TRADEDT*
    - *INTERST*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *RECIEVE*
    - *INPRICE*
    - *YIELD*

ABSOLUTE_PRICE
FORMAT
REMRKS
PMNTCCY
RATE
SECCCY
SPOT_PRICE
SETTSKL
ISMA
DLTYP
PRIORITY
DEALER
PRDDESC
SCTYDESC
MRKTDESC
DEAL_STATUS
AUTHORIZED
CHECKERID
CHECKERSTAMP
MAKERID
MAKERSTAMP
Svssingdet
- *LEGPRD*
- *MSTLDATE*
- *AUTOMSTL*
- *PORTFOLIO*
- *CNTPARTY*
- *PAYACCBRN*
- *PAYACC*
- *SKLOCATION*
- *SKACCNT*
- *BROKER*
- *SLRBUYSELL*
- *LEGDESC*
- *SLSKLOCATIONDESC*
- *DEAL_REFERENCE_NO*
- *MLLEGPRD*
- *MLLEGDESC*

Svsmuldet
- *PORTFOLIO*
- *CNTPARTY*
- *SKLOCATION*
- *SKLOCDES*
- *SKACCNT*

BROKER
DEALQTY
YIELD
PAYACCBRN
PAYACC
DLIPPR
MSTLDATE
DEALREF
AUTOMSTL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsblkdlmas-Full

Attribute	Description
Name	Svsblkdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDTE

Attribute	Description
Name	TRANDTE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTERST

Attribute	Description
Name	INTERST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PPR,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECIEVE

Attribute	Description
Name	RECIEVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,F,P

TOP

INPRICE

Attribute	Description
Name	INPRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSOLUTE_PRICE

Attribute	Description
Name	ABSOLUTE_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,D,I,C

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PMNTCCY

Attribute	Description
Name	PMNTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SPOT_PRICE

Attribute	Description
Name	SPOT_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTSKL

Attribute	Description
Name	SETTSKL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DLTYP

Attribute	Description
Name	DLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,HIGH,NORM,LOWP

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCTYDESC

Attribute	Description	
Name	SCTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MRKTDESC

Attribute	Description	
Name	MRKTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_STATUS

Attribute	Description	
Name	DEAL_STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,S,V,L,H,R

TOP

AUTHORIZED

Attribute	Description
Name	AUTHORIZED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,U</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svssingdet

Attribute	**Description**	
Name	Svssingdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGPRD

Attribute	**Description**	
Name	LEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MSTLDATE

Attribute	**Description**	
Name	MSTLDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,S

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCATIONDESC

Attribute	Description	
Name	SLSKLOCATIONDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEAL_REFERENCE_NO

Attribute	Description	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsmuldet

Attribute	Description
Name	Svsmuldet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CNTPARTY

Attribute	Description
Name	CNTPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDES

Attribute	Description

Name	SKLOCDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYACCBRN

Attribute	Description
Name	PAYACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DLIPPR

Attribute	Description
Name	DLIPPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MSTLDATE

Attribute	Description
Name	MSTLDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.4.SD-ReverseSecBlockDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsblkdlmas-PK*
      - *DEALREFNO*
    - *Svsblkdlmas-IO*
      - *DEALREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsblkdlmas-PK

Attribute	Description
Name	Svsblkdlmas-PK
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsblkdlmas-IO

Attribute	Description
Name	Svsblkdlmas-IO
Datatype	
Description	

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.32.ReverseSecuritiesDeal

ReverseSecuritiesDeal

2.32.1.SD-ReverseSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinto
- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Dealmastera
- *DEALREF*

Ytmmaster
- *DEALREF*
- *EFFDT*
- *YTM*

Certificates
- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb
- *DEALREF*

Contract
- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref
- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEALREF

Attribute	**Description**
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CUMEXINDICATOR

Attribute	**Description**
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BUYLEG

Attribute	**Description**
Name	BUYLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKETDESC

Attribute	Description
Name	MARKETDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRODUCTDESC

Attribute	Description
Name	PRODUCTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFFRM

Attribute	Description
Name	LGRFFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.32.2.SD-ReverseSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

2.32.3.SD-ReverseSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- BKAMT
- LQSTAT
- LQREFNO
- BROKNAM

Charges

- CONREFNO
- Charge-Association
  - COMPNT
  - CREATESN
  - RULE
  - WAIVER
  - DISACCRAPPL
  - ACCRREQD
  - DESC
- Charge-Application
  - CREATESN
  - COMPNT
  - TGCCY
  - TGAMT
  - CHRGCCY
  - CHRGAMT
  - DISACCRAPPL
  - WAIVER
  - LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT

Settlements

- CONREFNO
- Contract-Settlement
  - IBANACNO
  - CUSTSPREAD
  - SPREADDEFN
  - COMPNT
  - TAGCCY
  - ACCBRN
  - ACC
  - ACCCCY
  - EXRATE
  - NETIND
  - ERICCY

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

- *Fundmisdetails*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
  - *Issrtax*
    - *INTCOMP*
    - *CRRATESN*
    - *RATECOD*
    - *WAIVER*
- *Csvws-Contract*
  - *LEGREFNO*
  - *Csvws-Contract-Event-Seq*
    - *EVTCODE*
    - *EVENT_SEQ_NO*
    - *DESCRIPTION*
  - *Csvws-Contract-Event-Advice*
    - *ADVCD*
    - *SUPPRESS*
    - *PRIORITY*
    - *PRTYID*
    - *PRTYNAME*
    - *ADVDESC*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *MEDIA*

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description	
Name	DEALTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	Description	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LEGREFNOFROM

Attribute	Description	
Name	LEGREFNOFROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LEGFRMDSCRPT

Attribute	Description	
Name	LEGFRMDSCRPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Limitsfrom

Attribute	Description	
Name	Limitsfrom	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	Indicates Debit/Credit Debit : D Credit : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	**Description**
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDNL1

Attribute	**Description**	
Name	ADDNL1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDNL2

Attribute	**Description**	
Name	ADDNL2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDNL3

Attribute	**Description**	
Name	ADDNL3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADVCDSCRP

Attribute	**Description**	
Name	ADVCDSCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.4.SD-ReverseSecuritiesDeal-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Dealmaster-PK*
    - *DEALREF*
    - *VERSION*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.RolloverSecuritiesDeal

RolloverSecuritiesDeal

2.33.1.SD-RolloverSecuritiesDeal-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*

ACTUALDSTLDT
SE_TXNDATE
SPOTDT
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME

PRD
BRN
DEALREF
CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*

MSTLCOMPLETED
DEALER
PORTREF
PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION

- *LEGREFNOFROM*
- *LEGFRMDSCRPT*
- *Limitsfrom*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinfrom*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*

BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESSED
ADVPICKUPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
LEGREFNOTO
LEGDESCRPTN
Limitsto
- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinto
- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*

- *RULE*
- *DISCACCRAPPL*
- *BKCCY*
- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

Csvws-Contract

- *LEGREFNO*
- *Csvws-Contract-Event-Seq*
  - *EVTCODE*
  - *EVENT_SEQ_NO*
  - *DESCRIPTION*
- *Csvws-Contract-Event-Advice*
  - *ADVCD*
  - *SUPPRESS*
  - *PRIORITY*
  - *PRTYID*
  - *PRTYNAME*
  - *ADVDESC*
  - *ADDRS1*
  - *ADDRS2*

ADDRS3
ADDRS4
MEDIA
DESCRIPTION
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Cntdl
CONTREFNO
INTDAYS
CUMEX
SIGNVL
TOTDY
SIGNVL1
TOTDY1
Dlntcn
COMP
CMPNTCCY
AMNTCMPCCY
PYMNCCY
RATE
AMTPCY
SIGN

- *Dlintr*
  - *CMPNTDSC*
  - *COMPNTCRCY*
  - *AMNTCMPCRCY*
  - *PAYMNCURCY*
  - *RATE*
  - *AMONCURCY*
  - *SIGN*
- *Csvwscnrt*
  - *Svwmtchdl*
    - *MTCHLREF*
    - *STLDT*
    - *MTCHQTY*
  - *Unrelmtch*
    - *TOTREM*
    - *TOTMTCH*
    - *TOTREQD*
- *Lgrf*
  - *LEGREFNO*
  - *LATEVNTSQNO*
  - *LGDSCRPTN*
  - *PORTFLID*
  - *Msgs*
    - *VRSN*
    - *MSGTP*
    - *PRTID*
    - *PRTNM*
    - *ADDRS1*
    - *ADDRS2*
    - *ADDRS3*
    - *ADDRS4*
    - *ADDRS5*
    - *ADDRS6*
    - *ADDNL1*
    - *ADDNL2*
    - *ADDNL3*
    - *ADVCDSCRP*
  - *Partdtl*
    - *VERSON*
    - *PRTYP*
    - *ADDRESS1*
    - *ADDRESS2*
    - *ADDRESS3*
    - *ADDRESS4*

MSEGTP

ADVICEDSCRPT

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Dealmaster-Full

Attribute	Description

Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSPREMIUM

Attribute	Description
Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,S</td></tr></table>

TOP

AUTOMANUALFLAG

Attribute	Description
Name	AUTOMANUALFLAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,HIGH,NORM,LOW

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CORPACTIONTYPE

Attribute	**Description**	
Name	CORPACTIONTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

UNITS

Attribute	**Description**	
Name	UNITS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEFLAG

Attribute	**Description**	
Name	EXERCISEFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C,V,L,H,R,X</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

RECVFREEPAY

Attribute	**Description**	
Name	RECVFREEPAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,F,P

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUMEXINDICATOR

Attribute	**Description**	
Name	CUMEXINDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BUYLEG

Attribute	**Description**	
Name	BUYLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SELLLEG

Attribute	Description
Name	SELLLEG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

RELDEALREFERENCE

Attribute	Description
Name	RELDEALREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FREEPAY

Attribute	Description
Name	FREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,F

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

DEAL_QUANTITY

Attribute	**Description**	
Name	DEAL_QUANTITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

FACEVALPERUNIT

Attribute	**Description**	
Name	FACEVALPERUNIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCQUOTE

Attribute	**Description**	
Name	PRCQUOTE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

PAYCCY

Attribute	**Description**
Name	PAYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1000</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>22</td></tr></table>

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LEGREFNOFROM

Attribute	Description
Name	LEGREFNOFROM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGFRMDSCRPT

Attribute	Description
Name	LEGFRMDSCRPT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsfrom

Attribute	Description
Name	Limitsfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO

Attribute	**Description**	
Name	PORTFOLIO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POSITIONREFNO

Attribute	**Description**	
Name	POSITIONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	Description	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Csvws-Contract-Event-Seq

Attribute	**Description**	
Name	Csvws-Contract-Event-Seq	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVTCODE

Attribute	**Description**	
Name	EVTCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVENT_SEQ_NO

Attribute	**Description**	
Name	EVENT_SEQ_NO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DIntcn

Attribute	Description
Name	DIntcn
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CMPNTCCY

Attribute	Description
Name	CMPNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCCY

Attribute	Description
Name	AMNTCMPCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CMPNTDSC

Attribute	Description
Name	CMPNTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COMPNTCRCY

Attribute	Description
Name	COMPNTCRCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMNTCMPCRCY

Attribute	Description
Name	AMNTCMPCRCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNCURCY

Attribute	Description
Name	PAYMNCURCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.33.2.SD-RolloverSecuritiesDeal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-IO*
    - *DEALREF*
    - *VERSION*
    - *Brokerage*
      - *CONREFNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Misdetails*
      - *CONREFNO*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *Csvws-Contract*
      - *LEGREFNO*
    - *Csvws-Contract-En*
      - *LEGREFNO*

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract

Attribute	**Description**	
Name	Csvws-Contract	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-En

Attribute	**Description**	
Name	Csvws-Contract-En	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.33.3.SD-RolloverSecuritiesDeal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Dealmaster-Full*
    - *FACEDEAL*
    - *YTM*
    - *DISCOUNT*
    - *PREMIUM*
    - *ABSPREMIUM*
    - *ABSDISCOUNT*
    - *FORWDPL*
    - *ADJDEALPRC*
    - *ABSPRICE*
    - *INTDAYS*
    - *INTAMT*
    - *TRADEDT*
    - *AUTOMANDSTL*
    - *DSTLCOMPLETED*
    - *DSTLDATE*
    - *ACTUALDSTLDT*
    - *SE_TXNDATE*
    - *SPOTDT*

SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
REPOINDICATOR
PARTRELEASEALLOWED
SECSTTLMENT
ISMAIND
DEALTYPE
AUTOMANUALFLAG
PRIORITY
TXNTYPE
CERTNOS
LIMITSTRACKINGREQD
RATETYPE
CORPACTIONTYPE
UNITS
EXERCISEFLAG
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
AUTHSTAT
TXNSTAT
DEALER
YIELD
CORPACTIONID
DLVRFREEPAY
RECVFREEPAY
REMARKS
LCYQTY
LCYPRC
BLOCK_DEALREFNO
BLOCKTYPE
BLOCKREFNO
ABSWHT
ORGDSTLDT
ORIGINALINTERESTAMOUNT
ORIGINALPRICE
BAREF
DEALTIME
PRD
BRN
DEALREF

CUMEXINDICATOR
BUYLEG
SELLLEG
RELDEALREFERENCE
VERSION
SECTYCD
SECURITYTYPE
SECURITYREFNO
SECTYSERIES
DCONREQUIRED
FREEPAY
MKTCD
PRCTYPE
DEALTYP
QUOTEBY
DEAL_QUANTITY
FACEVALPERUNIT
PRCQUOTE
INPUTPRC
PAYCCY
RATEPCYSCY
SCCY
INTVALDT
BROKERID
SECUTRIY_DESC
MARKETDESC
PRODUCTDESC
LGRFFRM
LGRFNTO
LATVERNO
Detalfrom
- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*

PORTFOLIO
POSITIONREFNO
CPTY
NETCONSIDERATION
PCY
PAYBRN
PAYACC
ACCOMLODGE
SKLOC
SKACC
FRMTYPFROM
SKACCTO
FRMTYPTO
BRKPKPDONE
CHARGEPKPDONE
INTREFERDONE
SETTLEPICKUPDONE
TAXPICKUPDONE
MISPICKUPDONE
PARTYPROCESS
ADVPKPDONE
NETCONSPROCESSED
DCONCOMPLETED
CALBDONE
BLOKDONE
SKLCDONE
UNEXPOSURE
TOTEXPOSURE
BRKID
CLEANRISKLIMIT
PSTLRISKLIMIT
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
FUNDREFNO
ADDRLINE3
ADDRLINE4
PMTADVPROCESSED
SUBSYSTEMSTAT
DESCRIPTION
LEGREFNOFROM
LEGFRMDSCRPT
Limitsfrom

- *LEGREF*
- *CPTY*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*

Walkinfrom

- *LEGREF*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*

Detalto

- *BRANCH*
- *DEALREF*
- *LGPRDCODE*
- *LEGREF*
- *LEGUSERREF*
- *VERSION*
- *EVENTCODE*
- *MSTLDT*
- *AUTOMSTL*
- *ORGMSTLDT*
- *MSTLCOMPLETED*
- *DEALER*
- *PORTREF*
- *PORTFOLIO*
- *POSITIONREFNO*
- *CPTY*
- *NETCONSIDERATION*
- *PCY*
- *PAYBRNTO*
- *PAYACCTO*
- *ACMP_WDRW*
- *SKACC*
- *FRMTYPFROM*
- *SKLOCTO*
- *SKACCTO*
- *FRMTYPTO*
- *BRKPKPDONE*
- *CHARGEPKPDONE*
- *INTREFERDONE*

- *SETTLEPICKUPDONE*
- *TAXPICKUPDONE*
- *MISPICKUPDONE*
- *PARTYPROCESSED*
- *ADVPICKUPDONE*
- *NETCONSPROCESSED*
- *DCONCOMPLETED*
- *CALBDONE*
- *BLOKDONE*
- *SKLCDONE*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *BRKID*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *FUNDREFNO*
- *ADDRLINE3*
- *ADDRLINE4*
- *PMTADVPROCESSED*
- *SUBSYSTEMSTAT*
- *LEGREFNOTO*
- *LEGDESCRPTN*
- *Limitsto*
  - *LEGREF*
  - *CPTY*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Walkinto*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*

Dealmastera

- *DEALREF*

Ytmmaster

- *DEALREF*
- *EFFDT*
- *YTM*

Certificates

- *DEALREF*
- *CERTNO*
- *CERTQT*
- *UNIT_NOM_QUOTE*

Dealmasterb

- *DEALREF*

Contract

- *SERIAL*
- *ESN*
- *UREF*
- *LATVERNO*
- *PRDCODE*
- *CPTY*
- *TEMPSTAT*
- *PRDTYPE*
- *CEC*
- *MDCODE*
- *UDSTAT*
- *CONTCCY*
- *LEVENTDT*
- *XREF*
- *AMFLAG*
- *FREFNO*
- *RESPSTAT*
- *SECUPDSTAT*
- *STOPDT*
- *LIBCIF*
- *SRC*
- *REFERCREF*

Multiref

- *VERNO*
- *LEGREFNO*
- *Brokerage*
  - *CONREFNO*
  - *BOKBROKER*
  - *BROKAMT*
  - *BROKCCY*
  - *RULE*
  - *DISCACCRAPPL*
  - *BKCCY*

- *BKAMT*
- *LQSTAT*
- *LQREFNO*
- *BROKNAM*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2
REPRES3
REPRES4
RCVRACC

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP

CRRATEESN

RULE

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

Csvws-Contract

LEGREFNO

Csvws-Contract-Event-Seq

EVTCODE

EVENT_SEQ_NO

DESCRIPTION

Csvws-Contract-Event-Advice

ADVCD

SUPPRESS

PRIORITY

PRTYID

PRTYNAME

ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION

Csvws-Contract-En

LEGREFNO

Sevws-Event-Log

REFERENCE

SR_NO

EVENT

EVENT_DATE

MAKER_ID

MAKER_DT_STAMP

CHECKER_ID

CHECKER_DT_STAMP

Acvws-All-Ac-Entries

BRANCH

ACCOUNT

DR_CR

CODE

DATE

VALDT

CCY

FCY_AMOUNT

EXG_RATE

LCY_AMOUNT

Csvws-Contract-Ovd

OVDMSGS

Cntdl

CONTREFNO

INTDAYS

CUMEX

SIGNVL

TOTDY

SIGNVL1

TOTDY1

Dlntcn

COMP

CMPNTCCY

AMNTCMPCCY

PYMNCCY

RATE

AMTPCY

SIGN

Dlintr

CMPNTDSC

COMPNTCRCY

AMNTCMPCRCY
PAYMNCURCY
RATE
AMONCURCY
SIGN
Csvwscnrt
Svwmtchdl
MTCHLREF
STLDT
MTCHQTY
Unrelmtch
TOTREM
TOTMTCH
TOTREQD
Lgrf
LEGREFNO
LATEVNTSQNO
LGDSCRPTN
PORTFLID
Msgs
VRSN
MSGTP
PRTID
PRTNM
ADDRS1
ADDRS2
ADDRS3
ADDRS4
ADDRS5
ADDRS6
ADDNL1
ADDNL2
ADDNL3
ADVCDSCRP
Partdtl
VERSON
PRTYP
ADDRESS1
ADDRESS2
ADDRESS3
ADDRESS4
MSEGTP
ADVICEDSCRPT
TXNUDFDETAILS

FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Dealmaster-Full

Attribute	Description
Name	Dealmaster-Full
Datatype	
Description	

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPREMIUM

Attribute	Description

Name	ABSPREMIUM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSDISCOUNT

Attribute	Description
Name	ABSDISCOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAMT

Attribute	Description
Name	INTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLCOMPLETED

Attribute	Description
Name	DSTLCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DSTLDATE

Attribute	Description
Name	DSTLDATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_TXNDATE

Attribute	Description
Name	SE_TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPOINDICATOR

Attribute	Description
Name	REPOINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PARTRELEASEALLOWED

Attribute	Description
Name	PARTRELEASEALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALTYPE

Attribute	Description	
Name	DEALTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,S

TOP

AUTOMANUALFLAG

Attribute	Description	
Name	AUTOMANUALFLAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

TXNTYPE

Attribute	Description
Name	TXNTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CERTNOS

Attribute	Description
Name	CERTNOS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

LIMITSTRACKINGREQD

Attribute	Description
Name	LIMITSTRACKINGREQD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RATETYPE

Attribute	Description
Name	RATETYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

CORPACTIONTYPE

Attribute	Description
Name	CORPACTIONTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXERCISEFLAG

Attribute	Description
Name	EXERCISEFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C,V,L,H,R,X

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPACTIONID

Attribute	Description
Name	CORPACTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,F,P

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLOCK_DEALREFNO

Attribute	Description
Name	BLOCK_DEALREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BLOCKREFNO

Attribute	Description
Name	BLOCKREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALINTERESTAMOUNT

Attribute	Description
Name	ORIGINALINTERESTAMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORIGINALPRICE

Attribute	Description
Name	ORIGINALPRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CUMEXINDICATOR

Attribute	Description
Name	CUMEXINDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SELLLEG

Attribute	**Description**	
Name	SELLLEG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

RELDEALREFERENCE

Attribute	**Description**	
Name	RELDEALREFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECURITYTYPE

Attribute	Description
Name	SECURITYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECURITYREFNO

Attribute	Description
Name	SECURITYREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DCONREQUIRED

Attribute	Description
Name	DCONREQUIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FREEPAY

Attribute	Description
Name	FREEPAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,F,P</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,F</td></tr></table>

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

DEAL_QUANTITY

Attribute	Description
Name	DEAL_QUANTITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

FACEVALPERUNIT

Attribute	Description
Name	FACEVALPERUNIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PPR,PRM,PPM,YTM

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

BROKERID

Attribute	Description
Name	BROKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MARKETDESC

Attribute	Description	
Name	MARKETDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRODUCTDESC

Attribute	Description	
Name	PRODUCTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFFRM

Attribute	Description	
Name	LGRFFRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LGRFNTO

Attribute	Description
Name	LGRFNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

Detalfrom

Attribute	Description
Name	Detalfrom
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTREFERDONE

Attribute	**Description**	
Name	INTREFERDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PARTYPROCESS

Attribute	Description
Name	PARTYPROCESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPKPDONE

Attribute	Description
Name	ADVPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LEGREFNOFROM

Attribute	Description	
Name	LEGREFNOFROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

LEGFRMDSCRPT

Attribute	Description	
Name	LEGFRMDSCRPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Limitsfrom

Attribute	Description	
Name	Limitsfrom	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Walkinfrom

Attribute	Description
Name	Walkinfrom
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Detalto

Attribute	Description
Name	Detalto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLCOMPLETED

Attribute	Description
Name	MSTLCOMPLETED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POSITIONREFNO

Attribute	Description
Name	POSITIONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NETCONSIDERATION

Attribute	Description
Name	NETCONSIDERATION
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCY

Attribute	Description
Name	PCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACMP_WDRW

Attribute	Description
Name	ACMP_WDRW
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BRKPKPDONE

Attribute	Description
Name	BRKPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHARGEPKPDONE

Attribute	Description
Name	CHARGEPKPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTREFERDONE

Attribute	Description
Name	INTREFERDONE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SETTLEPICKUPDONE

Attribute	**Description**	
Name	SETTLEPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXPICKUPDONE

Attribute	**Description**	
Name	TAXPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MISPICKUPDONE

Attribute	**Description**	
Name	MISPICKUPDONE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PARTYPROCESSED

Attribute	**Description**	
Name	PARTYPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ADVPICKUPDONE

Attribute	Description
Name	ADVPICKUPDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSPROCESSED

Attribute	Description
Name	NETCONSPROCESSED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCONCOMPLETED

Attribute	Description
Name	DCONCOMPLETED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALBDONE

Attribute	Description
Name	CALBDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BLOKDONE

Attribute	Description
Name	BLOKDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLCDONE

Attribute	Description
Name	SKLCDONE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FUNDREFNO

Attribute	Description
Name	FUNDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE4

Attribute	**Description**	
Name	ADDRLINE4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PMTADVPROCESSED

Attribute	**Description**	
Name	PMTADVPROCESSED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SUBSYSTEMSTAT

Attribute	**Description**	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	500

TOP

LEGREFNOTO

Attribute	**Description**	
Name	LEGREFNOTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LEGDESCRPTN

Attribute	Description
Name	LEGDESCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Limitsto

Attribute	Description
Name	Limitsto
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Walkinto

Attribute	Description
Name	Walkinto

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Dealmastera

Attribute	Description
Name	Dealmastera
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ytmmaster

Attribute	Description
Name	Ytmmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Certificates

Attribute	Description
Name	Certificates
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNIT_NOM_QUOTE

Attribute	Description

Name	UNIT_NOM_QUOTE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,N

TOP

Dealmasterb

Attribute	Description
Name	Dealmasterb
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERIAL

Attribute	Description
Name	SERIAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDCODE

Attribute	Description
Name	PRDCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CPTY

Attribute	Description
Name	CPTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEMPSTAT

Attribute	Description
Name	TEMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CEC

Attribute	Description
Name	CEC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MDCODE

Attribute	Description
Name	MDCODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDSTAT

Attribute	**Description**	
Name	UDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CONTCCY

Attribute	**Description**	
Name	CONTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LEVENTDT

Attribute	**Description**	
Name	LEVENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMFLAG

Attribute	Description
Name	AMFLAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FREFNO

Attribute	Description
Name	FREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESPSTAT

Attribute	Description
Name	RESPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECUPDSTAT

Attribute	Description
Name	SECUPDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIBCIF

Attribute	Description
Name	LIBCIF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

REFERCREF

Attribute	Description
Name	REFERCREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Multiref

Attribute	Description
Name	Multiref
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Brokerage

Attribute	**Description**	
Name	Brokerage	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BOKBROKER

Attribute	Description
Name	BOKBROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

BROKCCY

Attribute	Description
Name	BROKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DISCACCRAPPL

Attribute	Description
Name	DISCACCRAPPL
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BKCCY

Attribute	Description
Name	BKCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BKAMT

Attribute	Description
Name	BKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQSTAT

Attribute	Description
Name	LQSTAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LQREFNO

Attribute	Description
Name	LQREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BROKNAM

Attribute	Description
Name	BROKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description	
Name	ERICCY	
Datatype	String	
Description	Indicates ERI Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**	
Name	RTGSNW	
Datatype	String	
Description	Indicates RTGS Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

PAYBY

Attribute	**Description**	
Name	PAYBY	
Datatype	String	
Description	Indicates Payment By Message : M Instrument : I Clearing : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	**Description**	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	**Description**	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	**Description**	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	**Description**	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST4

Attribute	**Description**	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,HIGH,NORM,LOW</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MEDIA

Attribute	**Description**	
Name	MEDIA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description

Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length; Description: 3 Restrictions: pattern; Description: [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description

Name	CUMEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL

Attribute	Description
Name	SIGNVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY

Attribute	Description
Name	TOTDY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

SIGNVL1

Attribute	Description
Name	SIGNVL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

TOTDY1

Attribute	Description
Name	TOTDY1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

DIntcn

Attribute	**Description**	
Name	DIntcn	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CMPNTCCY

Attribute	**Description**	
Name	CMPNTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCCY

Attribute	**Description**	
Name	AMNTCMPCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PYMNCCY

Attribute	Description
Name	PYMNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Dlintr

Attribute	Description
Name	Dlintr
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CMPNTDSC

Attribute	**Description**	
Name	CMPNTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COMPNTCRCY

Attribute	**Description**	
Name	COMPNTCRCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMNTCMPCRCY

Attribute	**Description**	
Name	AMNTCMPCRCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PAYMNCURCY

Attribute	**Description**	
Name	PAYMNCURCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMONCURCY

Attribute	Description
Name	AMONCURCY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svwmtchdl

Attribute	Description
Name	Svwmtchdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MTCHLREF

Attribute	Description
Name	MTCHLREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

STLDT

Attribute	Description
Name	STLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MTCHQTY

Attribute	Description
Name	MTCHQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Unrelmtch

Attribute	Description
Name	Unrelmtch
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTREM

Attribute	Description
Name	TOTREM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTMTCH

Attribute	Description
Name	TOTMTCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

TOTREQD

Attribute	Description
Name	TOTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

LATEVNTSQNO

Attribute	Description
Name	LATEVNTSQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDSCRPTN

Attribute	Description
Name	LGDSCRPTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

PORTFLID

Attribute	Description
Name	PORTFLID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Msgs

Attribute	Description
Name	Msgs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRSN

Attribute	Description
Name	VRSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSGTP

Attribute	Description
Name	MSGTP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

PRTNM

Attribute	Description
Name	PRTNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS2

Attribute	Description

Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS5

Attribute	Description
Name	ADDRS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS6

Attribute	Description
Name	ADDRS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL1

Attribute	Description
Name	ADDNL1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL2

Attribute	Description
Name	ADDNL2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDNL3

Attribute	Description
Name	ADDNL3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADVCDSCRP

Attribute	Description
Name	ADVCDSCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Partdtl

Attribute	Description
Name	Partdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VERSON

Attribute	Description
Name	VERSON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYP

Attribute	Description
Name	PRTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS2

Attribute	Description

Name	ADDRESS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS4

Attribute	Description
Name	ADDRESS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MSEGTP

Attribute	Description
Name	MSEGTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ADVICEDSCRPT

Attribute	Description
Name	ADVICEDSCRPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.4.SD-RolloverSecuritiesDeal-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Dealmaster-PK*
      - *DEALREF*
      - *VERSION*
    - *Dealmaster-IO*
      - *DEALREF*
      - *VERSION*
      - *Brokerage*
        - *CONREFNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Misdetails*
        - *CONREFNO*
      - *Taxheadmaster*
        - *REFERENCE_NO*

Csvws-Contract

LEGREFNO

Csvws-Contract-En

LEGREFNO

Cntdl

CONTREFNO

Csvwscnrt

CONTREFNO

Lgrf

LEGREFNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Dealmaster-PK

Attribute	Description
Name	Dealmaster-PK
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Dealmaster-IO

Attribute	Description
Name	Dealmaster-IO
Datatype	
Description	

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	

TOP

Brokerage

Attribute	Description
Name	Brokerage
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract

Attribute	**Description**	
Name	Csvws-Contract	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Csvws-Contract-En

Attribute	**Description**	
Name	Csvws-Contract-En	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFNO

Attribute	**Description**	
Name	LEGREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Cntdl

Attribute	Description
Name	Cntdl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Csvwscnrt

Attribute	Description
Name	Csvwscnrt
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Lgrf

Attribute	Description
Name	Lgrf
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.AuthorizeMarketCode

Authorization of Market Definition

2.34.1.SE-AuthorizeMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-Full*
    - *MKTCD*
    - *MKTDESC*
    - *MKTTYPE*
    - *MKTIDCD*
    - *OTCOSYSN*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*
    - *PRICECD*
    - *HOLTP*
    - *HOLCCY*
    - *CPNBAS*
    - *DIVDBAS*
    - *WARBAS*
    - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Authorization of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDYCNT

Attribute	**Description**	
Name	SPTDYCNT	
Datatype	String	
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	**Description**	
Name	SPTDAYS	
Datatype	Number	
Description	Indicates Spot Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKSPTDT

Attribute	**Description**	
Name	WEKSPTDT	
Datatype	String	
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	**Description**
Name	IFSPTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET

Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT

Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String

Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	**Description**	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	Description	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	Description	
Name	AMNDAFTASSO	
Datatype	String	
Description	Indicates Amend After Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STOPASSOC

Attribute	Description	
Name	STOPASSOC	
Datatype	String	
Description	Indicates Stop Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXMOD

Attribute	Description	
Name	TAXMOD	
Datatype	String	
Description	Indicates Module	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.34.2.SE-AuthorizeMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-IO*
    - *MKTCD*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Authorization of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

2.34.3.SE-AuthorizeMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-IO*
      - *MKTCD*
      - *MODNO*
    - *Market-Master-Full*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*

RIGBAS
SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*

- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*

TAXMOD

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Authorization of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Market-Master-Full

Attribute	Description

Name	Market-Master-Full
Datatype	
Description	Authorization of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description	
Name	HOLTP	
Datatype	String	
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	Description	
Name	HOLCCY	
Datatype	String	
Description	Indicates Holiday Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBAS

Attribute	Description	
Name	CPNBAS	
Datatype	String	
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXDTMT

Attribute	**Description**	
Name	EXDTMT	
Datatype	String	
Description	Indicates Expiry Date Method ROLLING : R FIXED : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDTCNTBAS

Attribute	**Description**	
Name	EXDTCNTBAS	
Datatype	String	
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	**Description**	
Name	EXDAYS	
Datatype	Number	
Description	Indicates Expiry Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKEXDT

Attribute	**Description**
Name	WEKEXDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET

Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH

Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTNUMMET

Attribute	**Description**	
Name	ACDNTNUMMET	
Datatype	String	
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	**Description**	
Name	ACDNTDENMET	
Datatype	String	
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	**Description**	
Name	ACDNTDENMETBS	
Datatype	String	
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	**Description**	
Name	REVNADHMNT	
Datatype	String	
Description	Indicates Adhere To Month End Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ZEINTFOREXPD

Attribute	**Description**	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	**Description**	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	**Description**
Name	LIQDDCBAS
Datatype	String

Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description	
Name	SPTDTHOL	
Datatype	String	
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,F,B

TOP

Market-Ex-Date

Attribute	Description	
Name	Market-Ex-Date	
Datatype		
Description	Includes Expiry date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EXMKTCD

Attribute	Description	
Name	EXMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXFRMDY

Attribute	Description	
Name	EXFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME

Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description

Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.34.4.SE-AuthorizeMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-PK*
      - *MKTCD*
    - *Market-Master-IO*
      - *MKTCD*
      - *MODNO*
    - *Market-Master-Full*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*

DIVDBAS
WARBAS
RIGBAS
SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*

- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*

AMNDAFTASSO
STOPASSOC
TAXMOD
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-PK

Attribute	Description
Name	Market-Master-PK
Datatype	
Description	Authorization of Market Definition PK Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Authorization of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Authorization of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String

Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,T,</td></tr></table>

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,C</td></tr></table>

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,E,U</td></tr></table>

TOP

BNDCNTDR

Attribute	Description

Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET

Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String

Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String

Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String

Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EXMKTCD

Attribute	**Description**	
Name	EXMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXFRMDY

Attribute	**Description**	
Name	EXFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXTODY

Attribute	**Description**	
Name	EXTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXMNTIND

Attribute	**Description**	
Name	EXMNTIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,F,B</td></tr></table>

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Market-Issr-Tax

Attribute	**Description**	
Name	Market-Issr-Tax	
Datatype		
Description	Includes Tax details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MKTISSRTAX

Attribute	**Description**	
Name	MKTISSRTAX	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CMPNT

Attribute	**Description**	
Name	CMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	**Description**	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.AuthorizePriceDtl

Authorization of Securities Price Definition

2.35.1.SE-AuthorizePriceDtl-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-Full*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Price-Detail*
      - *BRCODE*
      - *SECURITYCODE*
      - *PRICECODE*
      - *MARKETVALUEDATE*

PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Details of Authorize Price Details

TOP

BRRCODE

Attribute	Description	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECODE

Attribute	**Description**	
Name	PRICECODE	
Datatype	String	
Description	Indicates Price Code	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARKETVALUEDATE

Attribute	**Description**	
Name	MARKETVALUEDATE	
Datatype	Date	
Description	Indicates Market Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICEQUOTATIONMETHOD

Attribute	**Description**	
Name	PRICEQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description	
Name	INTERESTQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	Number	
Description	Indicates Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRICE

Attribute	Description	
Name	LCYPRICE	
Datatype	Number	
Description	Indicates Local Currency Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	Description	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.35.2.SE-AuthorizePriceDtl-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-IO*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Indicates Branch Code, Security Code, Modification Number.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.35.3.SE-AuthorizePriceDtl-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MODNO*
    - *Price-Master-Full*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*

PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only Description for Authorize Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Price-Master-Full

Attribute	**Description**
Name	Price-Master-Full
Datatype	
Description	Contains Full Description for Authorize Price Details

TOP

BRRCODE

Attribute	**Description**	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	

Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Contains the error details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains the warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.4.SE-AuthorizePriceDtl-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-PK*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MODNO*
    - *Price-Master-Full*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*

Price-Detail
BRCODE
SECURITYCODE
PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-PK

Attribute	Description
Name	Price-Master-PK
Datatype	
Description	Contains Primary Key Description for Authorize Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only Description for Authorize Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Description for Authorize Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Statuus	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Price-Detail

Attribute	**Description**	
Name	Price-Detail	
Datatype		
Description	Includes Price Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRCODE

Attribute	**Description**	
Name	BRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description

Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.AuthorizeRecord

Authorization of Securities Market Price Codes

2.36.1.SE-AuthorizeRecord-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-Full*
    - *PCODE*
    - *PDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Contains Full Details of Request of Authorize Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.36.2.SE-AuthorizeRecord-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-IO*
    - *PCODE*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Indicates Market Price Code, Modification Number.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

2.36.3.SE-AuthorizeRecord-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-IO*
      - *PCODE*
      - *MODNO*
    - *Price-Code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-IO

Attribute	Description
Name	Price-Code-IO
Datatype	
Description	Contains Input only response of Authorize SE Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

Price-Code-Full

Attribute	Description
Name	Price-Code-Full
Datatype	
Description	Contains Full response of Authorize SE Record

TOP

PCODE

Attribute	Description

Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.4.SE-AuthorizeRecord-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-PK*
      - *PCODE*
    - *Price-code-IO*
      - *PCODE*
      - *MODNO*
    - *Price-code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-PK

Attribute	Description
Name	Price-Code-PK
Datatype	
Description	Indicates Market Price Code.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Indicates Market Price Code and Modification Number.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Indicates full Price Code details in FCUBS Response.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.37.AuthorizeSEMarketCode

AuthorizeSEMarketCode

2.37.1.SE-AuthorizeSEMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*

OTSYSNARR
CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*

- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Smm-Full

Attribute	Description
Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description
Name	TRNVPRD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	**Description**	
Name	TBILLANNLMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISCCURRPRD

Attribute	**Description**	
Name	PRMDISCCURRPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTDSC

Attribute	**Description**	
Name	MKTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L,C</td></tr></table>

TOP

HOLCCY

Attribute	Description
Name	HOLCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMTHD

Attribute	**Description**	
Name	SPTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	**Description**	
Name	SPTDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	**Description**	
Name	SPTDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

ADDM

Attribute	Description

Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

LDDB

Attribute	**Description**	
Name	LDDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	**Description**	
Name	LDINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	**Description**	
Name	DCNTMTHDSWIFTIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDCOUPN

Attribute	**Description**	
Name	PRDCOUPN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWASYNCREV

Attribute	Description	
Name	ALLWASYNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRDREV

Attribute	Description	
Name	PRDREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPNFREQ

Attribute	Description	
Name	COUPNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description	
Name	COUPNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description
Name	COUPNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RVSNFREQ

Attribute	Description
Name	RVSNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description
Name	RVSNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description
Name	RVSNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

Tps

Attribute	Description
Name	Tps
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description

Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.37.2.SE-AuthorizeSEMarketCode-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Smm-IO*
  - *MKTCD*
  - *CHECKER*
  - *CHECKERSTAMP*
  - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.37.3.SE-AuthorizeSEMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*
    - *OTSYSNARR*
    - *CTRYCD*
    - *LOCCCY*

SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
  RDNGBASIS
  RATDENMBASIS
  ADNM
  ADDM
  ADDB
  ADINCLDTODT
  LDNM
  LDDM
  LDDB
  LDINCLDTODT
  DCNTMTHDSWIFTIND
  PRDCOUPN
  ALLWASYNCREV
  PRDREV
  COUPNFREQ
  COUPNWEEKDAY
  COUPNADHRETOMNTHEND
  RVSNFREQ

- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_ERROR_RESP

ERROR

- *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Smm-Full

Attribute	Description

Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description

Name	TRNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRYCCD

Attribute	Description	
Name	PRYCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTYP

Attribute	Description	
Name	HOLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXTDTMTHD

Attribute	Description	
Name	EXTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description	
Name	EXDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description	
Name	EXDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	**Description**	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	**Description**	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	**Description**	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	**Description**	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ZEROINTFREXPRD

Attribute	Description	
Name	ZEROINTFREXPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description	
Name	ACCRDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description	
Name	LQDDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Smsd

Attribute	Description	
Name	Smsd	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFSPTDT

Attribute	**Description**	
Name	DAYOFSPTDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Tps

Attribute	**Description**	
Name	Tps	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMKTCD

Attribute	**Description**
Name	PRDORMKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Smm-PK*
      - *MKTCD*
    - *Smm-IO*
      - *MKTCD*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Smm-PK

Attribute	Description
Name	Smm-PK
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.38.AuthorizeSEMarketPriceCodes

AuthorizeSEMarketPriceCodes

2.38.1.SE-AuthorizeSEMarketPriceCodes-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stpricd-Full

Attribute	Description
Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICE_CODE_DESC

Attribute	**Description**	
Name	PRICE_CODE_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.38.2.SE-AuthorizeSEMarketPriceCodes-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Stpricd-IO
PRICE_CODE
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.38.3.SE-AuthorizeSEMarketPriceCodes-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stpricd-Full

Attribute	Description

Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stpricd-PK*
      - *PRICE_CODE*
    - *Stpricd-IO*
      - *PRICE_CODE*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stpricd-PK

Attribute	Description
Name	Stpricd-PK
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.AuthorizeSEPriceDetail

AuthorizeSEPriceDetail

2.39.1.SE-AuthorizeSEPriceDetail-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*

INTEREST_QUOTATION_METHOD
PRICE
INT_AUTH_STAT
LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description

Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

2.39.2.SE-AuthorizeSEPriceDetail-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-IO*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *Stprcdtl*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*
      - *INTEREST_QUOTATION_METHOD*
      - *PRICE*
      - *INT_AUTH_STAT*
      - *LCY_PRICE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,PRI,PRM,PPM,PPR,YTM</td></tr></table>

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,,F</td></tr></table>

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.39.3.SE-AuthorizeSEPriceDetail-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*
      - *INTEREST_QUOTATION_METHOD*
      - *PRICE*
      - *INT_AUTH_STAT*

LCY_PRICE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description	
Name	BR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITY_CODE

Attribute	Description	
Name	SECURITY_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.39.4.SE-AuthorizeSEPriceDetail-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stprcmas-PK*
      - *SECURITY_CODE*
      - *BR_CODE*
    - *Stprcmas-IO*
      - *BR_CODE*
      - *SECURITY_CODE*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *Stprcdtl*
        - *MARKET_VALUE_DATE*
        - *PRICE_QUOTATION_METHOD*
        - *INTEREST_QUOTATION_METHOD*
        - *PRICE*
        - *INT_AUTH_STAT*
        - *LCY_PRICE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stprcmas-PK

Attribute	Description
Name	Stprcmas-PK
Datatype	
Description	

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Stprcdtl

Attribute	**Description**	
Name	Stprcdtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MARKET_VALUE_DATE

Attribute	**Description**	
Name	MARKET_VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICE_QUOTATION_METHOD

Attribute	**Description**	
Name	PRICE_QUOTATION_METHOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	**Description**	
Name	INTEREST_QUOTATION_METHOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,,F

TOP

PRICE

Attribute	**Description**

Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.40.AuthorizeSESKLocationChange

AuthorizeSESKLocationChange

2.40.1.SE-AuthorizeSESKLocationChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*

PORTFOLIO
PORTDESC
CPTY
CNTRPTYDESC
SKLOCATION
SKLOCTNDESC
SKACCNT
FRMTYP
SKLOCTNTO
SKLOCTNDESCTO
SKACCNTTO
SE_FORM_TYPE

Csvwsevntlogdtls

DEAL_REFERENCE_NO
ESN
INPUTBY
MAKDTTIME
CHECHKERID
CHKDTTIME
AUTHSTAT
ACTIVE

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*
  - *REIMINST4*
  - *RCVRCORRS1*

RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15

ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*

NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En

LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsdlmas-Full

Attribute	Description
Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description
Name	CNTRPTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESC

Attribute	Description
Name	SKLOCTNDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYP

Attribute	Description
Name	FRMTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / A,

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3

Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	**Description**	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4

Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5

Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

2.40.2.SE-AuthorizeSESKLocationChange-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-IO*
    - *CONTRACTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.40.3.SE-AuthorizeSESKLocationChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*
      - *PORTFOLIO*
      - *PORTDESC*
      - *CPTY*

CNTRPTYDESC
SKLOCATION
SKLOCTNDESC
SKACCNT
FRMTYP
SKLOCTNTO
SKLOCTNDESCTO
SKACCNTTO
SE_FORM_TYPE

Csvwsevntlogdtls

DEAL_REFERENCE_NO
ESN
INPUTBY
MAKDTTIME
CHECHKERID
CHKDTTIME
AUTHSTAT
ACTIVE

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE

- SR_NO
- EVENT
- EVENT_DATE
- MAKER_ID
- MAKER_DT_STAMP
- CHECKER_ID
- CHECKER_DT_STAMP
- Acvws-All-Ac-Entries
  - BRANCH
  - ACCOUNT
  - DR_CR
  - CODE
  - DATE
  - VALDT
  - CCY
  - FCY_AMOUNT
  - EXG_RATE
  - LCY_AMOUNT
- Csvws-Contract-Ovd
  - OVDMSGS
- Csvws-Contract
  - LEGREFNO
  - Csvws-Contract-Event-Seq
    - EVTCODE
    - EVENT_SEQ_NO
    - DESCRIPTION
  - Csvws-Contract-Event-Advice
    - ADVCD
    - SUPPRESS
    - PRIORITY
    - PRTYID
    - PRTYNAME
    - ADVDESC
    - ADDRS1
    - ADDRS2
    - ADDRS3
    - ADDRS4
    - MEDIA
    - DESCRIPTION
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC
- FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsdlmas-Full

Attribute	Description

Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description	
Name	CNTRPTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCATION

Attribute	Description	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCTNDESC

Attribute	Description	
Name	SKLOCTNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKACCNT

Attribute	Description	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,D,I,G,C</td></tr></table>

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsdlmas-PK*
      - *CONTRACTREFNO*
    - *Svsdlmas-IO*
      - *CONTRACTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsdlmas-PK

Attribute	Description
Name	Svsdlmas-PK
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.41.AuthorizeSESKLocationMaint

AuthorizeSESKLocationMaint

2.41.1.SE-AuthorizeSESKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

Skacc

SKACC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	**Description**	
Name	CORPACTAUTOCOLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	**Description**	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	**Description**	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BANKACCEP

Attribute	Description	
Name	BANKACCEP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Skacc

Attribute	Description
Name	Skacc

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	150
minLength	0

TOP

2.41.2.SE-AuthorizeSESKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-IO*
    - *SKLOCID*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.41.3.SE-AuthorizeSESKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Skacc*
      - *SKACC*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,A

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MSGTOICS

Attribute	Description

Name	MSGTOICS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Skloc-PK*
      - *SKLOCID*
    - *Skloc-IO*
      - *SKLOCID*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Skloc-PK

Attribute	Description
Name	Skloc-PK
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.AuthorizeSKLocationMaint

Authorization of Securities - Safe Keeping Location Maintenance

2.42.1.SE-AuthorizeSKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAC*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACPTN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*

RECSTAT

ONCEAUTH

Sk-Account

SKLOCID

SKACC

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullRequest

TOP

Sk-Location-Full

Attribute	Description
Name	Sk-Location-Full
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance Full Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.42.2.SE-AuthorizeSKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-IO*
    - *SKLOCID*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

2.42.3.SE-AuthorizeSKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance PK Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance Full Type

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.42.4.SE-AuthorizeSKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance PK Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Authorization of Securities - Safe Keeping Location Maintenance Full Type

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	Description	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.CreateMarketCode

Creation of Market Definition

2.43.1.SE-CreateMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-Full*
    - *MKTCD*
    - *MKTDESC*
    - *MKTTYPE*
    - *MKTIDCD*
    - *OTCOSYSN*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*
    - *PRICECD*
    - *HOLTP*
    - *HOLCCY*
    - *CPNBAS*
    - *DIVDBAS*
    - *WARBAS*
    - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Creation of Market Definition Full Type.

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	**Description**	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	**Description**	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	**Description**	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	**Description**	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET

Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT

Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String

Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXMNTIND

Attribute	**Description**	
Name	EXMNTIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,P,

TOP

EXPRVMNT

Attribute	**Description**	
Name	EXPRVMNT	
Datatype	Number	
Description	Indicates Previous Months	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXDYEXDT

Attribute	**Description**	
Name	EXDYEXDT	
Datatype	Number	
Description	Indicates Expiry Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXWKDDT

Attribute	**Description**	
Name	EXWKDDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	**Description**	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.43.2.SE-CreateMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-IO*
    - *MKTCD*
    - *MKTDESC*
    - *MKTTYPE*
    - *MKTIDCD*
    - *OTCOSYSN*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*
    - *PRICECD*
    - *HOLTP*
    - *HOLCCY*
    - *CPNBAS*
    - *DIVDBAS*
    - *WARBAS*
    - *RIGBAS*
    - *SPTDTMET*
    - *SPTDYCNT*
    - *SPTDAYS*

WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*

- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

- *FUNCTIONID*
- *FIELD_NAME*

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Market-Master-IO

Attribute	Description

Name	Market-Master-IO
Datatype	
Description	Creation of Market Definition IO Type

TOP

MKTCD

Attribute	Description	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYPE

Attribute	Description	
Name	MKTTYPE	
Datatype	String	
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,O,X,

TOP

MKTIDCD

Attribute	Description	
Name	MKTIDCD	
Datatype	String	
Description	Indicates Market Identifier Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description	
Name	HOLTP	
Datatype	String	
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	Description	
Name	HOLCCY	
Datatype	String	
Description	Indicates Holiday Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBAS

Attribute	Description	
Name	CPNBAS	
Datatype	String	
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXDTMT

Attribute	Description	
Name	EXDTMT	
Datatype	String	
Description	Indicates Expiry Date Method ROLLING : R FIXED : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDTCNTBAS

Attribute	Description	
Name	EXDTCNTBAS	
Datatype	String	
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description	
Name	EXDAYS	
Datatype	Number	
Description	Indicates Expiry Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET

Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT

Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String

Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXMNTIND

Attribute	**Description**	
Name	EXMNTIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,P,

TOP

EXPRVMNT

Attribute	**Description**	
Name	EXPRVMNT	
Datatype	Number	
Description	Indicates Previous Months	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXDYEXDT

Attribute	**Description**	
Name	EXDYEXDT	
Datatype	Number	
Description	Indicates Expiry Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXWKDDT

Attribute	**Description**	
Name	EXWKDDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.43.3.SE-CreateMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-IO*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*
      - *RIGBAS*
      - *SPTDTMET*
      - *SPTDYCNT*

SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*

- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*
  - *MKTISSRTAX*
  - *CMPNT*

EVNTFORASS
BASAMTTAG
DFLTRTCD
DFLTWAIVER
ALRTCDAMND
AMNDAFTASSO
STOPASSOC
TAXMOD
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Market-Master-Full
MKTCD
MKTDESC
MKTTYPE
MKTIDCD
OTCOSYSN
CTRYCD
LOCCCY
SKLOCID
PRICECD
HOLTP
HOLCCY
CPNBAS
DIVDBAS
WARBAS
RIGBAS
SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR

BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date
- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*

- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Creation of Market Definition Master IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	S,O,X,

TOP

MKTIDCD

Attribute	Description	
Name	MKTIDCD	
Datatype	String	
Description	Indicates Market Identifier Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	Description	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description	
Name	HOLTP	
Datatype	String	
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	Description	
Name	HOLCCY	
Datatype	String	
Description	Indicates Holiday Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number

Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD

Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String

Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY

Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String

Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number

Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String

Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description

Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX

Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	**Description**	
Name	AMNDAFTASSO	
Datatype	String	
Description	Indicates Amend After Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STOPASSOC

Attribute	**Description**
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXMOD

Attribute	**Description**	
Name	TAXMOD	
Datatype	String	
Description	Indicates Module	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

MKTISSRTAX

Attribute	**Description**	
Name	MKTISSRTAX	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CMPNT

Attribute	**Description**	
Name	CMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	**Description**	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Creation of Market Definition Full type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	S,O,X,

TOP

MKTIDCD

Attribute	Description	
Name	MKTIDCD	
Datatype	String	
Description	Indicates Market Identifier Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	Description	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description	
Name	HOLTP	
Datatype	String	
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	Description	
Name	HOLCCY	
Datatype	String	
Description	Indicates Holiday Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number

Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD

Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String

Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY

Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String

Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number

Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String

Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description

Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX

Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	**Description**	
Name	AMNDAFTASSO	
Datatype	String	
Description	Indicates Amend After Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STOPASSOC

Attribute	**Description**
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXMOD

Attribute	**Description**	
Name	TAXMOD	
Datatype	String	
Description	Indicates Module	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

MKTISSRTAX

Attribute	**Description**	
Name	MKTISSRTAX	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CMPNT

Attribute	**Description**	
Name	CMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	**Description**	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description

Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.43.4.SE-CreateMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-PK*
      - *MKTCD*
    - *Market-Master-IO*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*
      - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

MKTISSRTAX
CMPNT
EVNTFORASS
BASAMTTAG
DFLTRTCD
DFLTWAIVER
ALRTCDAMND
AMNDAFTASSO
STOPASSOC
TAXMOD
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Market-Master-Full
MKTCD
MKTDESC
MKTTYPE
MKTIDCD
OTCOSYSN
CTRYCD
LOCCCY
SKLOCID
PRICECD
HOLTP
HOLCCY
CPNBAS
DIVDBAS
WARBAS
RIGBAS
SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD

ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date
- *SPTMKTCD*

- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

- *FUNCTIONID*

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-PK

Attribute	Description
Name	Market-Master-PK
Datatype	
Description	Creation of Market Definition PK Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Creation of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Market-Interest

Attribute	**Description**	
Name	Market-Interest	
Datatype		
Description	Includes Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String

Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	Description	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	Description	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description	
Name	SPTMNTHIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number

Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	Description	
Name	AMNDAFTASSO	
Datatype	String	
Description	Indicates Amend After Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STOPASSOC

Attribute	Description	
Name	STOPASSOC	
Datatype	String	
Description	Indicates Stop Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXMOD

Attribute	Description	
Name	TAXMOD	
Datatype	String	
Description	Indicates Module	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

MKTISSRTAX

Attribute	Description	
Name	MKTISSRTAX	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CMPNT

Attribute	Description	
Name	CMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	Description	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	Description	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Creation of Market Definition Master Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDTCNTBAS

Attribute	**Description**	
Name	EXDTCNTBAS	
Datatype	String	
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	**Description**	
Name	EXDAYS	
Datatype	Number	
Description	Indicates Expiry Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKEXDT

Attribute	**Description**	
Name	WEKEXDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	**Description**
Name	IFEXDTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Market-Interest

Attribute	**Description**	
Name	Market-Interest	
Datatype		
Description	Includes Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description	
Name	ACDNTDENMET	
Datatype	String	
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description	
Name	ACDNTDENMETBS	
Datatype	String	
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTINCDT

Attribute	Description	
Name	ACDNTINCDT	
Datatype	String	
Description	Indicates Include To Date Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String

Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	Description	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	Description	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description	
Name	SPTMNTHIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number

Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description	
Name	CMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFORASS

Attribute	Description	
Name	EVNTFORASS	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	Description	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.44.CreateNewRecord

Creation of Securities Market Price Codes

2.44.1.SE-CreateNewRecord-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-Full*
    - *PCODE*
    - *PDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Indicates full Price Code details in FCUBS Request.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.44.2.SE-CreateNewRecord-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-IO*
    - *PCODE*
    - *PDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Contains Input Only response of SE Create New Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.44.3.SE-CreateNewRecord-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-IO*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Price-Code-Full*

PCODE
PDESC
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-IO

Attribute	Description
Name	Price-Code-IO
Datatype	
Description	Contains Input Only Details of Create New Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Price-Code-Full

Attribute	Description
Name	Price-Code-Full
Datatype	
Description	ContainsFull Details of Create New Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String

Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.44.4.SE-CreateNewRecord-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-PK*
      - *PCODE*
    - *Price-Code-IO*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE

Price-Code-Full

PCODE

PDESC

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-PK

Attribute	Description
Name	Price-Code-PK
Datatype	
Description	Contains Primary Key Response of SE Create New Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-Code-IO

Attribute	Description
Name	Price-Code-IO
Datatype	
Description	Contains Input Only Response of SE Create New Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Price-Code-Full

Attribute	Description

Name	Price-Code-Full
Datatype	
Description	Contains Full Response of SE Create New Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description

Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.CreatePriceDtl

Creation of Securities Price Definition

2.45.1.SE-CreatePriceDtl-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-Full*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Price-Detail*
      - *BRCODE*
      - *SECURITYCODE*
      - *PRICECODE*
      - *MARKETVALUEDATE*

PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Details of Create Price Details

TOP

BRRCODE

Attribute	Description	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECODE

Attribute	**Description**	
Name	PRICECODE	
Datatype	String	
Description	Indicates Price Code	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARKETVALUEDATE

Attribute	**Description**	
Name	MARKETVALUEDATE	
Datatype	Date	
Description	Indicates Market Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICEQUOTATIONMETHOD

Attribute	**Description**	
Name	PRICEQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.45.2.SE-CreatePriceDtl-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-IO*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Price-Detail*
      - *BRCODE*
      - *SECURITYCODE*
      - *PRICECODE*
      - *MARKETVALUEDATE*
      - *PRICEQUOTATIONMETHOD*
      - *INTERESTQUOTATIONMETHOD*
      - *PRICE*

LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only details of Create Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description

Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.45.3.SE-CreatePriceDtl-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*
        - *PRICECODE*
        - *MARKETVALUEDATE*
        - *PRICEQUOTATIONMETHOD*
        - *INTERESTQUOTATIONMETHOD*

PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Price-Master-Full
BRRCODE
SECURITYCODE
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Price-Detail
BRCODE
SECURITYCODE
PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only Details of Create Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description

Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Details of Create Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String

Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	**Description**	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.45.4.SE-CreatePriceDtl-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-PK*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*
        - *PRICECODE*

MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Price-Master-Full
BRRCODE
SECURITYCODE
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Price-Detail
BRCODE
SECURITYCODE
PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Price-Master-PK

Attribute	Description
Name	Price-Master-PK
Datatype	
Description	Contains Primary Key response for Create Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	ContainsInput Only response for Create Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String

Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRICE

Attribute	**Description**	
Name	LCYPRICE	
Datatype	Number	
Description	Indicates Local Currency Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	**Description**	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Price-Master-Full

Attribute	Description

Name	Price-Master-Full
Datatype	
Description	Contains Full response for Create Price Details

TOP

BRRCODE

Attribute	Description	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String

Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.CreateSEMarketCode

CreateSEMarketCode

2.46.1.SE-CreateSEMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*

OTSYSNARR
CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
  RDNGBASIS
  RATDENMBASIS
  ADNM
  ADDM
  ADDB
  ADINCLDTODT
  LDNM
  LDDM
  LDDB
  LDINCLDTODT
  DCNTMTHDSWIFTIND
  PRDCOUPN
  ALLWASYNCREV
  PRDREV
  COUPNFREQ

- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Smm-Full

Attribute	Description
Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description
Name	TRNVPRD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	**Description**	
Name	TBILLANNLMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISCCURRPRD

Attribute	**Description**	
Name	PRMDISCCURRPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTDSC

Attribute	**Description**	
Name	MKTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L,C</td></tr></table>

TOP

HOLCCY

Attribute	Description
Name	HOLCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMTHD

Attribute	**Description**	
Name	SPTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	**Description**	
Name	SPTDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	**Description**	
Name	SPTDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

ADDM

Attribute	Description

Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

LDDB

Attribute	**Description**	
Name	LDDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	**Description**	
Name	LDINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	**Description**	
Name	DCNTMTHDSWIFTIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDCOUPN

Attribute	**Description**	
Name	PRDCOUPN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description
Name	COUPNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RVSNFREQ

Attribute	Description
Name	RVSNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description
Name	RVSNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description
Name	RVSNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

Tps

Attribute	Description
Name	Tps
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description

Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.46.2.SE-CreateSEMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-IO*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*
    - *OTSYSNARR*
    - *CTRYCD*
    - *LOCCCY*

SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
Smi
  RDNGBASIS
  RATDENMBASIS
  ADNM
  ADDM
  ADDB
  ADINCLDTODT
  LDNM
  LDDM
  LDDB
  LDINCLDTODT
  DCNTMTHDSWIFTIND
  PRDCOUPN
  ALLWASYNCREV
  PRDREV
  COUPNFREQ
  COUPNWEEKDAY
  COUPNADHRETOMNTHEND
  RVSNFREQ
  RVSNWEEKDAY
  RVSNADHRETOMNTHEND
  ZEROINTFREXPRD
  ACCRDCNTBASIS366
  LQDDCNTBASIS366
Smsd
  MKTCD

FRMDY
TODY
MONTHIND
FUTMON
DAYOFSPTDT
WEEKDAYOFSPTDT
IFSPTDTISHOL
Tps
SCHM
MODL
Tmit
CMPNT
EVNTFRASSOC
BASISAMTTAG
DFLTRATCD
DFLTWAIVR
ALLWRATECDAMMNDMENT
AMNDAFTRASSOC
STPASSOC
Smed
FRMDY
TODY
MNTHIND
PREVMNTHS
DAYOFEXDT
WEEKDAYOFEXDT
IFEXDTISHOL
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,T</td></tr></table>

TOP

RNVPRD

Attribute	Description
Name	RNVPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,E,U

TOP

TDCD

Attribute	Description	
Name	TDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,H

TOP

UBF

Attribute	Description	
Name	UBF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNVPRD

Attribute	Description	
Name	TRNVPRD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	Description	
Name	TBILLANNLMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,O,X</td></tr></table>

TOP

MKIDCD

Attribute	Description
Name	MKIDCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRYCCD

Attribute	**Description**	
Name	PRYCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTYP

Attribute	**Description**	
Name	HOLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	**Description**	
Name	HOLCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBASIS

Attribute	**Description**	
Name	CPNBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DVDNDBASIS

Attribute	Description	
Name	DVDNDBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

WARRNTBASIS

Attribute	Description	
Name	WARRNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

RYTSBASIS

Attribute	Description	
Name	RYTSBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMTHD

Attribute	Description	
Name	SPTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	**Description**	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	**Description**	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	**Description**	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	**Description**	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ZEROINTFREXPRD

Attribute	Description	
Name	ZEROINTFREXPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description	
Name	ACCRDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description	
Name	LQDDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Smsd

Attribute	Description	
Name	Smsd	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,F</td></tr></table>

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFSPTDT

Attribute	**Description**	
Name	DAYOFSPTDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Tps

Attribute	**Description**	
Name	Tps	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SCHM

Attribute	**Description**
Name	SCHM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description

Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.46.3.SE-CreateSEMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*
    - *OTSYSNARR*
    - *CTRYCD*
    - *LOCCCY*

SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
  RDNGBASIS
  RATDENMBASIS
  ADNM
  ADDM
  ADDB
  ADINCLDTODT
  LDNM
  LDDM
  LDDB
  LDINCLDTODT
  DCNTMTHDSWIFTIND
  PRDCOUPN
  ALLWASYNCREV
  PRDREV
  COUPNFREQ
  COUPNWEEKDAY
  COUPNADHRETOMNTHEND
  RVSNFREQ

RVSNWEEKDAY
RVSNADHRETOMNTHEND
ZEROINTFREXPRD
ACCRDCNTBASIS366
LQDDCNTBASIS366
Smsd
MKTCD
FRMDY
TODY
MONTHIND
FUTMON
DAYOFSPTDT
WEEKDAYOFSPTDT
IFSPTDTISHOL
Tps
PRDORMKTCD
SCHM
MODL
Tmit
CMPNT
EVNTFRASSOC
BASISAMTTAG
DFLTRATCD
DFLTWAIVR
ALLWRATECDAMMNDMENT
AMNDAFTRASSOC
STPASSOC
CLASSDSC
EVNTDSCR
DSC3
Smed
FRMDY
TODY
MNTHIND
PREVMNTHS
DAYOFEXDT
WEEKDAYOFEXDT
IFEXDTISHOL
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Smm-Full

Attribute	Description

Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description

Name	TRNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYP

Attribute	**Description**	
Name	MKTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,O,X

TOP

MKIDCD

Attribute	**Description**	
Name	MKIDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTSYSNARR

Attribute	**Description**	
Name	OTSYSNARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	**Description**	
Name	CTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXTDTMTHD

Attribute	Description	
Name	EXTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description	
Name	EXDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description	
Name	EXDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	**Description**	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	**Description**	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	**Description**	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	**Description**	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,F</td></tr></table>

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFSPTDT

Attribute	**Description**	
Name	DAYOFSPTDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Tps

Attribute	**Description**	
Name	Tps	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMKTCD

Attribute	**Description**
Name	PRDORMKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MNTHIND

Attribute	**Description**	
Name	MNTHIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,F

TOP

PREVMNTHS

Attribute	**Description**	
Name	PREVMNTHS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFEXDT

Attribute	**Description**	
Name	DAYOFEXDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	**Description**	
Name	WEEKDAYOFEXDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	**Description**
Name	IFEXDTISHOL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.46.4.SE-CreateSEMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Smm-PK*
      - *MKTCD*
    - *Smm-IO*
      - *MKTCAT*
      - *RNVPRD*
      - *ANNLMTHD*
      - *BDCN*
      - *BDCD*
      - *TDCN*
      - *TDCD*
      - *UBF*
      - *TRNVPRD*
      - *TBILLANNLMTHD*
      - *PRMDISCCURRPRD*
      - *MKTCD*
      - *MKTDSC*
      - *MKTTYP*
      - *MKIDCD*

OTSYSNARR
CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*
- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*

LQDDCNTBASIS366
Smsd
MKTCD
FRMDY
TODY
MONTHIND
FUTMON
DAYOFSPTDT
WEEKDAYOFSPTDT
IFSPTDTISHOL
Tps
SCHM
MODL
Tmit
CMPNT
EVNTFRASSOC
BASISAMTTAG
DFLTRATCD
DFLTWAIVR
ALLWRATECDAMMNDMENT
AMNDAFTRASSOC
STPASSOC
Smed
FRMDY
TODY
MNTHIND
PREVMNTHS
DAYOFEXDT
WEEKDAYOFEXDT
IFEXDTISHOL
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Smm-PK

Attribute	Description
Name	Smm-PK
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,T</td></tr></table>

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description
Name	TRNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,R,F</td></tr></table>

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description	
Name	EXDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	Description	
Name	WEEKDAYOFEXDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description	
Name	IFEXDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Smi

Attribute	Description	
Name	Smi	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

ADDB

Attribute	Description

Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	**Description**	
Name	LDINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	**Description**	
Name	DCNTMTHDSWIFTIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDCOUPN

Attribute	**Description**	
Name	PRDCOUPN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWASYNCREV

Attribute	**Description**	
Name	ALLWASYNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRDREV

Attribute	Description	
Name	PRDREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPNFREQ

Attribute	Description	
Name	COUPNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description	
Name	COUPNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	Description
Name	RVSNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description
Name	RVSNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description
Name	RVSNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FRMDY

Attribute	Description
Name	FRMDY

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

Tps

Attribute	Description
Name	Tps
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STPASSOC

Attribute	Description
Name	STPASSOC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 150 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.CreateSEMarketPriceCodes

CreateSEMarketPriceCodes

2.47.1.SE-CreateSEMarketPriceCodes-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stpricd-Full

Attribute	Description
Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.47.2.SE-CreateSEMarketPriceCodes-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-IO*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.47.3.SE-CreateSEMarketPriceCodes-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stpricd-Full

Attribute	Description

Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.47.4.SE-CreateSEMarketPriceCodes-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stpricd-PK*
      - *PRICE_CODE*
    - *Stpricd-IO*
      - *PRICE_CODE*
      - *PRICE_CODE_DESC*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stpricd-PK

Attribute	Description
Name	Stpricd-PK
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.48.CreateSEPriceDetail

CreateSEPriceDetail

2.48.1.SE-CreateSEPriceDetail-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*

INTEREST_QUOTATION_METHOD
PRICE
INT_AUTH_STAT
LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description

Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

2.48.2.SE-CreateSEPriceDetail-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Stprcmas-IO*
  - *BR_CODE*
  - *SECURITY_CODE*
  - *Stprcdtl*
    - *PRICE_CODE*
    - *MARKET_VALUE_DATE*
    - *PRICE_QUOTATION_METHOD*
    - *INTEREST_QUOTATION_METHOD*
    - *PRICE*
    - *INT_AUTH_STAT*
    - *LCY_PRICE*
  - *UDFDETAILS*
    - *FLDNAM*
    - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.48.3.SE-CreateSEPriceDetail-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*
      - *INTEREST_QUOTATION_METHOD*
      - *PRICE*
      - *INT_AUTH_STAT*

LCY_PRICE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description	
Name	BR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITY_CODE

Attribute	Description	
Name	SECURITY_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.48.4.SE-CreateSEPriceDetail-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stprcmas-PK*
      - *SECURITY_CODE*
      - *BR_CODE*
    - *Stprcmas-IO*
      - *BR_CODE*
      - *SECURITY_CODE*
      - *Stprcdtl*
        - *PRICE_CODE*
        - *MARKET_VALUE_DATE*
        - *PRICE_QUOTATION_METHOD*
        - *INTEREST_QUOTATION_METHOD*
        - *PRICE*
        - *INT_AUTH_STAT*
        - *LCY_PRICE*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stprcmas-PK

Attribute	Description
Name	Stprcmas-PK
Datatype	
Description	

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.CreateSESKLocationChange

CreateSESKLocationChange

2.49.1.SE-CreateSESKLocationChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*

PORTFOLIO
PORTDESC
CPTY
CNTRPTYDESC
SKLOCATION
SKLOCTNDESC
SKACCNT
FRMTYP
SKLOCTNTO
SKLOCTNDESCTO
SKACCNTTO
SE_FORM_TYPE

Csvwsevntlogdtls

DEAL_REFERENCE_NO
ESN
INPUTBY
MAKDTTIME
CHECHKERID
CHKDTTIME
AUTHSTAT
ACTIVE

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*
  - *REIMINST4*
  - *RCVRCORRS1*

RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15

ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*

NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En

LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsdlmas-Full

Attribute	Description
Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description
Name	CNTRPTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESC

Attribute	Description
Name	SKLOCTNDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYP

Attribute	Description
Name	FRMTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	**Description**	
Name	Csvwsevntlogdtls	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_REFERENCE_NO

Attribute	**Description**	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INPUTBY

Attribute	**Description**	
Name	INPUTBY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / A,

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3

Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	**Description**	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4

Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5

Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

2.49.2.SE-CreateSESKLocationChange-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-IO*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *Svsdldtl*
      - *PORTFOLIO*
      - *CPTY*
      - *SKLOCATION*
      - *SKACCNT*
      - *FRMTYP*
      - *SKLOCTNTO*
      - *SKACCNTTO*
      - *SE_FORM_TYPE*

Csvwsevntlogdtls

- *DEAL_REFERENCE_NO*
- *ESN*
- *INPUTBY*
- *MAKDTTIME*
- *CHECHKERID*
- *CHKDTTIME*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*

- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN

- WAIVER
- LIQDINDICAT
- Liqdmaster
  - INTCOMP
- Issrtax
  - INTCOMP
  - RATECOD
- Csvws-Contract-En
  - LEGREFNO
  - Sevws-Event-Log
    - REFERENCE
    - SR_NO
    - EVENT
    - EVENT_DATE
    - MAKER_ID
    - MAKER_DT_STAMP
    - CHECKER_ID
    - CHECKER_DT_STAMP
    - Acvws-All-Ac-Entries
      - BRANCH
      - ACCOUNT
      - DR_CR
      - CODE
      - DATE
      - VALDT
      - CCY
      - FCY_AMOUNT
      - EXG_RATE
      - LCY_AMOUNT
    - Csvws-Contract-Ovd
      - OVDMSGS
- Csvws-Contract
  - LEGREFNO
  - Csvws-Contract-Event-Seq
    - EVTCODE
    - EVENT_SEQ_NO
    - DESCRIPTION
  - Csvws-Contract-Event-Advice
    - ADVCD
    - SUPPRESS
    - PRIORITY
    - PRTYID
    - PRTYNAME
    - ADVDESC

ADDRS1

ADDRS2

ADDRS3

ADDRS4

MEDIA

DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

QUOTEBY

Attribute	**Description**	
Name	QUOTEBY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

SECTYSERIES

Attribute	**Description**	
Name	SECTYSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

SETMETD

Attribute	**Description**	
Name	SETMETD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	**Description**	
Name	DEALQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I,G,C

TOP

SKLOCTNTO

Attribute	**Description**	
Name	SKLOCTNTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNTTO

Attribute	**Description**	
Name	SKACCNTTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	**Description**	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	**Description**	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	**Description**	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY

Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	Description	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description

Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

2.49.3.SE-CreateSESKLocationChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*
      - *PORTFOLIO*
      - *PORTDESC*
      - *CPTY*

- *CNTRPTYDESC*
- *SKLOCATION*
- *SKLOCTNDESC*
- *SKACCNT*
- *FRMTYP*
- *SKLOCTNTO*
- *SKLOCTNDESCTO*
- *SKACCNTTO*
- *SE_FORM_TYPE*

Csvwsevntlogdtls

- *DEAL_REFERENCE_NO*
- *ESN*
- *INPUTBY*
- *MAKDTTIME*
- *CHECHKERID*
- *CHKDTTIME*
- *AUTHSTAT*
- *ACTIVE*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE

- SR_NO
- EVENT
- EVENT_DATE
- MAKER_ID
- MAKER_DT_STAMP
- CHECKER_ID
- CHECKER_DT_STAMP
- Acvws-All-Ac-Entries
  - BRANCH
  - ACCOUNT
  - DR_CR
  - CODE
  - DATE
  - VALDT
  - CCY
  - FCY_AMOUNT
  - EXG_RATE
  - LCY_AMOUNT
- Csvws-Contract-Ovd
  - OVDMSGS
- Csvws-Contract
  - LEGREFNO
  - Csvws-Contract-Event-Seq
    - EVTCODE
    - EVENT_SEQ_NO
    - DESCRIPTION
  - Csvws-Contract-Event-Advice
    - ADVCD
    - SUPPRESS
    - PRIORITY
    - PRTYID
    - PRTYNAME
    - ADVDESC
    - ADDRS1
    - ADDRS2
    - ADDRS3
    - ADDRS4
    - MEDIA
    - DESCRIPTION
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC
- FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsdlmas-Full

Attribute	Description

Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SvsdIdtl

Attribute	Description
Name	SvsdIdtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description
Name	CNTRPTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCTNDESC

Attribute	Description
Name	SKLOCTNDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,D,I,G,C</td></tr></table>

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	**Description**	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.49.4.SE-CreateSESKLocationChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsdlmas-PK*
      - *CONTRACTREFNO*
    - *Svsdlmas-IO*
      - *PRD*
      - *CONTRACTREFNO*
      - *USRREF*
      - *SECTYCD*
      - *QUOTEBY*
      - *SECTYSERIES*
      - *SETMETD*
      - *DEALQTY*
      - *DSTLDT*
      - *Svsdldtl*
        - *PORTFOLIO*
        - *CPTY*
        - *SKLOCATION*
        - *SKACCNT*
        - *FRMTYP*

- SKLOCTNTO
- SKACCNTTO
- SE_FORM_TYPE

Csvwsevntlogdtls

- DEAL_REFERENCE_NO
- ESN
- INPUTBY
- MAKDTTIME
- CHECHKERID
- CHKDTTIME

Misdetails

- CONREFNO
- LATESN
- MISGRP
- RELACC
- RELETED_REFERENCE
- MISHEAD
- RATEFLG
- POOLCD
- REFINANCE_RATE
- REFRATETYP
- PROCALCMTH
- REFSPREAD
- REFRATECD
- COSTCD1
- COSTCD2
- COSTCD3
- COSTCD4
- COSTCD5
- TXNMIS1
- TXNMIS10
- TXNMIS2
- TXNMIS3
- TXNMIS4
- TXNMIS5
- TXNMIS6
- TXNMIS7
- TXNMIS8
- TXNMIS9
- MISGRPCOMP
- MISGRPTXN
- COMPMIS1
- COMPMIS10
- COMPMIS2

- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*

TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3

ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER

Appln
INTCOMP
CRRATESN
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
Issrtax
INTCOMP
RATECOD
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY

PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsdlmas-PK

Attribute	Description
Name	Svsdlmas-PK
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 16

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

SECTYSERIES

Attribute	Description	
Name	SECTYSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

SETMETD

Attribute	Description	
Name	SETMETD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	Description	
Name	DEALQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl

Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECHKERID

Attribute	**Description**	
Name	CHECHKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	16

TOP

Charge-Association

Attribute	Description

Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT

Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String

Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description	
Name	CLEARNW	
Datatype	String	
Description	Indicates Network Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String

Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description

Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String

Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	**Description**	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	**Description**	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	**Description**	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	**Description**	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4

Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String

Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing

Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SUPPID

Attribute	Description	
Name	SUPPID	
Datatype	String	
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,R,1,2

TOP

PAYERID

Attribute	Description	
Name	PAYERID	
Datatype	String	
Description	Indicates Payer Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3

Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description

Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	
Restrictions	

Restrictions	Description
maxLength	1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.50.CreateSESKLocationMaint

CreateSESKLocationMaint

2.50.1.SE-CreateSESKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

Skacc

SKACC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	**Description**	
Name	CORPACTAUTOCOLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	**Description**	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	**Description**	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BANKACCEP

Attribute	Description	
Name	BANKACCEP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Skacc

Attribute	Description
Name	Skacc

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	150
minLength	0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-IO*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *Skacc*
      - *SKACC*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description	
Name	CORPACTAUTOCOLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	Description	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	Description	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BANKACCEP

Attribute	Description	
Name	BANKACCEP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

2.50.3.SE-CreateSESKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Skacc*
      - *SKACC*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,A

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MSGTOICS

Attribute	Description

Name	MSGTOICS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.50.4.SE-CreateSESKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Skloc-PK*
      - *SKLOCID*
    - *Skloc-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAUTOCOLL*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACCEP*
      - *Skacc*
        - *SKACC*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Skloc-PK

Attribute	Description
Name	Skloc-PK
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.CreateSKLocationMaint

Creation of Securities - Safe Keeping Location

2.51.1.SE-CreateSKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAC*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACPTN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullRequest

TOP

Sk-Location-Full

Attribute	Description
Name	Sk-Location-Full
Datatype	
Description	Creation of Securities - Safe Keeping Location Full Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.51.2.SE-CreateSKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-IO*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAC*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACPTN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Sk-Account*

SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Creation of Securities - Safe Keeping Location IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String

Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	**Description**	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.51.3.SE-CreateSKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Creation of Securities - Safe Keeping Location PK Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Creation of Securities - Safe Keeping Location IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Creation of Securities - Safe Keeping Location Full Type

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.51.4.SE-CreateSKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Creation of Securities - Safe Keeping Location PK Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Creation of Securities - Safe Keeping Location IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Creation of Securities - Safe Keeping Location Full Type

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	Description	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.AuthSEDeal

Authorization of Securities Deal Input

2.52.1.SE-Deal-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*

NEWDISPVAL

FLDDESC

Rekey-Fields

SECCODE

INPR

DEALQTY

TRDDT

DSTLDT

PFID

MSTDT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for authorization request of the SE Deal contract

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Authorization of Securities Deal Input Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRDCD

Attribute	Description
Name	PRDCD

Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Override details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED

Datatype	String
Description	Indicates Confirmed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Override Messages
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Display Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Display Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

FLDDESC

Attribute	**Description**	
Name	FLDDESC	
Datatype	String	
Description	Indicates Field Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Rekey-Fields

Attribute	**Description**	
Name	Rekey-Fields	
Datatype		
Description	Includes Rekey details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

INPR

Attribute	**Description**	
Name	INPR	
Datatype	Number	
Description	Indicates Input Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.52.2.SE-Deal-Auth-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*
        - *NEWDISPVAL*
        - *FLDDESC*
    - *Rekey-Fields*

SECCODE

INPR

DEALQTY

TRDDT

DSTLDT

PFID

MSTDT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for authorization request of the SE Deal contract

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Authorization of Securities Deal Input Master type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Override details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVDMSGS

Attribute	**Description**	
Name	OVDMSGS	
Datatype	String	
Description	Indicates Override Messages	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Contract-Change-Log

Attribute	**Description**	
Name	Contract-Change-Log	
Datatype		
Description	Includes Contract Change Log details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

OLDDISPVAL

Attribute	**Description**	
Name	OLDDISPVAL	
Datatype	String	
Description	Indicates Old Display Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

NEWDISPVAL

Attribute	**Description**	
Name	NEWDISPVAL	
Datatype	String	
Description	Indicates New Display Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes Rekey details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

MSTDT

Attribute	Description

Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.52.3.SE-Deal-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREF*
    - *DEALREFNO*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *REVDREFNO*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALTYP*
    - *DEALQTY*
    - *TRADEDT*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
LMTRACK
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
SECTYSERIES
BAREF
PRIORITY
DEALER
ISMAIND
REMARKS
SMNTSK
CERTNO
ORGINTAMT
ORGPRICE
FORM
DEALTYPE

PRODDESC
PRDTYP
LCCY
YIELDEC
Deal-Detail-To
- *FCCREF*
- *XREF*
- *PRD*
- *DEALREFNO*
- *LGPRDCODE*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGUSERREF*
- *LEG_REFERNCENO*
- *LGDESC*
- *SKLOCDESCTO*
- *BUYSELL*
- *Deal-Limits-To*
  - *LEGREF*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Deal-Walkin-To*
  - *LEGREF*
- *CONTRACT1*
  - *FCCREF*
  - *VERNO*
  - *PREVVERNO*
  - *Settlement-Addl-Details*
    - *ACCBRN*
    - *ACC_CCY*
    - *ACC*
    - *AMTTAG*
    - *CUSTSPRD*
    - *ERIAMT*
    - *ERICCY*
    - *XRATE*
    - *GENMSG*

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME

IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1

- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3

INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6

AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY

AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4

- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
  - *CPTY*
- *CONTRACT*
  - *FCCREF*
  - *BRKDETAILS*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*

LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP
CHGCCY

CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*
- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT

MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3

- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*
  - *SIGN*

COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT

WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE

WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET

CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3

- *RCVR_CORRESP4*
- *RCVR_CORRESP5*
- *RCVR_CORRESP6*
- *RECEIVER*
- *RTGSNW*
- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*
- *INTMEDRY3*
- *INTMEDRY4*

INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC

DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2

INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6

TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1

ADD2

Deal-Netcons

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX

Deal-Interest

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC

SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6

AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6

ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3

ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch

LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
DEAL_WALKIN
LEGREF
UNEXPOSURE
TOTEXPOSURE
CLEANRISKLIMIT
PSTLRISKLIMIT
CPTY
CONTRACT
FCCREF
BRKDETAILS
FCCREF

- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*

MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2

- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

SECUDF

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Sevws-Matched-Deal

- *FCCREF*
- *VER*
- *BUYLEG*
- *SELLEG*
- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*

DEAL_MESSAGES

- *FCCREF*
- *LEGREF*
- *VERSION*

MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT

- PSTLRISKLIMIT
- DEAL_WALKIN1
  - LEGREF
  - UNMATCHED
- Tax-Master
  - TXTREF
  - Tran-Tax-Assoc
    - CRRATESN
    - INTCOMP
    - RULE
    - WAIVER
    - CONTREF
  - Tran-Tax-Appln
    - CRRATESN
    - INTCOMP
    - TAGCCY
    - TAGAMNT
    - TAXCCY
    - TAXAMNT
    - WAIVER
    - LIQINDICAT
    - CONTREF
- DEAL_CERTIFICATE_DETAILS
  - FCCREF
  - DEALREF
  - CERTNO
  - CERTQT
- CONTRACT
  - FCCREF
  - BRKDETAILS
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT

LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6

FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10

- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*

INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF

PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2

ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
SKLOCTO
SKACCTO
Ytm-Master
DEALREF
DEALREFNO
EFFDT
YTM

Contract-Event-Log

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

TXTCSTAT

CONTSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full response of the authorization request of SE Deal contract

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Authorization of Securities Deal Input Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Block Deal Reference Number
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [A-Z0-9]*

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	**Restrictions** / **Description** maxLength / 15 pattern / [a-zA-Z0-9]*

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates Reversed Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates Local Currency Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates Original DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates Transaction Date
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P

TOP

SPOTINTVALDT

Attribute	**Description**	
Name	SPOTINTVALDT	
Datatype	Date	
Description	Indicates Spot Interest Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPOTPRC

Attribute	**Description**	
Name	SPOTPRC	
Datatype	Number	
Description	Indicates Spot Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT

Attribute	**Description**	
Name	DISCOUNT	
Datatype	Number	
Description	Indicates Discount	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREMIUM

Attribute	**Description**	
Name	PREMIUM	
Datatype	Number	
Description	Indicates Premium	
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

FORWDPL

Attribute	**Description**
Name	FORWDPL

Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates Actual DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LMTRACK

Attribute	Description
Name	LMTRACK
Datatype	String
Description	Indicates whether limit tracking is required or not Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 16 pattern / [a-zA-Z0-9]{16}

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates Placement/Loan Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 16 pattern / [a-zA-Z0-9]{16}

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3

TOP

DEALER

Attribute	Description	
Name	DEALER	
Datatype	Number	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description	Indicates Conforms to ISMA Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	255
	pattern	[a-zA-Z0-9]{255}

TOP

SMNTSK

Attribute	Description	
Name	SMNTSK	
Datatype	String	
Description	Indicates Safe Keeping Location (Sk Loc) for the market	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

ORGINTAMT

Attribute	Description
Name	ORGINTAMT
Datatype	Number
Description	Indicates Original Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGPRICE

Attribute	Description
Name	ORGPRICE
Datatype	Number
Description	Indicates Original Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z]

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

LCCY

Attribute	Description
Name	LCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

YIELDEC

Attribute	Description
Name	YIELDEC
Datatype	Number
Description	Indicates Yield For Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description

Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Deal-Walkin-To

Attribute	**Description**	
Name	Deal-Walkin-To	
Datatype		
Description	Includes Deal Walkin To details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	**Description**	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	Description	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	Description	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4

Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE

Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	**Description**	
Name	CERTNO	
Datatype	String	
Description	Indicates Certificate Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0

TOP

CERTQT

Attribute	**Description**	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description	
Name	BRKDETAILS	
Datatype		
Description	Includes Broker details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

BROKER

Attribute	Description	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description

Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description

Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String

Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description

Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12
minLength	1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16
minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description

Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4; minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4

Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT3

Attribute	Description	
Name	INSTRCDTXT3	
Datatype	String	
Description	Indicates the Instruction Code Text3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	Description	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	Description	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description

Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description

Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES

Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3

Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String

Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEAL_WALKIN1

Attribute	**Description**	
Name	DEAL_WALKIN1	
Datatype		
Description	Includes Deal Walkin details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description

Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINDICAT

Attribute	**Description**	
Name	LIQINDICAT	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	**Description**	
Name	LEG_REFERNCENO	
Datatype	String	
Description	Indicates Leg User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LGDESC

Attribute	**Description**	
Name	LGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	**Description**	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	**Description**	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	

Attribute	Description
minOccurs	0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	

Attribute	Description
minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	

Attribute	Description
minOccurs	0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10
minLength	1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	**Description**	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT

Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Deal-Limits-To

Attribute	**Description**	
Name	Deal-Limits-To	
Datatype		
Description	Includes Deal To Limits	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6

Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**	
Name	BNFINSTCVR6	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	**Description**	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**
Name	BENEF_INST3

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST1

Attribute	**Description**	
Name	ORDER_CUST1	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST2

Attribute	**Description**	
Name	ORDER_CUST2	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**
Name	ORDER_INST2
Datatype	String

Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6

Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**	
Name	BNFINSTCVR6	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	**Description**	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**
Name	BENEF_INST3

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST2

Attribute	Description	
Name	INT_REIM_INST2	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST3

Attribute	Description	
Name	INT_REIM_INST3	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST4

Attribute	Description	
Name	INT_REIM_INST4	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST1

Attribute	**Description**	
Name	ORDER_CUST1	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST2

Attribute	**Description**	
Name	ORDER_CUST2	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String

Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**
Name	TAG_CCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2

Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description

Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description

Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String

Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

BRKID

Attribute	Description	
Name	BRKID	
Datatype	String	
Description	Indicates Broker Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 0; pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 0; pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

PREVVERNO

Attribute	Description	
Name	PREVVERNO	
Datatype	Number	
Description	Indicates Previous Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>BS,CS,WI,BB,CB,LG</td></tr></table>

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String

Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	**Description**	
Name	INTDAYS	
Datatype	Number	
Description	Indicates Interest Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	**Description**	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Unrel-Unmatch

Attribute	**Description**	
Name	Unrel-Unmatch	
Datatype		
Description	Includes Unrel Unmatch details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNMATCHED

Attribute	**Description**
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK

Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN

Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF

Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String

Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	**Description**	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description

Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	

Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description	
Name	CERTNO	
Datatype	String	
Description	Indicates Certificate Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0

TOP

CERTQT

Attribute	Description	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT

Attribute	Description	
Name	CONTRACT	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1 pattern: [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

CHGCOMP

Attribute	Description	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 15 minInclusive: 0 totalDigits: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description

Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log

Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description

Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.52.4.SE-Deal-Auth-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master*
      - *FCCREF*
      - *XREF*
      - *VERNO*
    - *Deal-Masters*
      - *DEALREF*
      - *XREF*
      - *Cont-Event-Log*
        - *LEGDESC*
        - *BUYSELL*
        - *ESN*
        - *EVENTCD*
        - *PRDCD*
        - *DEALREFE*
        - *USREF*
        - *Contract-Ovd*
          - *CONFIRMED*
          - *OVDMSGS*

Contract-Change-Log

OLDDISPVAL

NEWDISPVAL

FLDDESC

Rekey-Fields

SECCODE

INPR

DEALQTY

TRDDT

DSTLDT

PFID

MSTDT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for primary key response of the authorization request SE Deal contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	Authorization of Securities Deal Input Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Authorization of ecurities Deal Input Deal master.

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log

Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String

Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Override details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Override Messages
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL

Datatype	String
Description	Indicates Old Display Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Display Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes Rekey details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

INPR

Attribute	Description	
Name	INPR	
Datatype	Number	
Description	Indicates Input Price	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

DEALQTY

Attribute	Description	
Name	DEALQTY	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRDDT

Attribute	Description	
Name	TRDDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description	Indicates Settlement Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.AuthSDBlockRelease

Authorization of Securities Deal Input - Block Securities

2.53.1.SE-Deal-Blkrel-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*

NEWDISPVAL

FLDDESC

Rekey-Fields

SECCODE

INPR

DEALQTY

TRDDT

DSTLDT

PFID

MSTDT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for authorization request of the SDblockrelease

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Authorization of Securities Deal Input - Block Securities Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREFE

Attribute	**Description**	
Name	DEALREFE	
Datatype	String	
Description	Indicates Deal Reference No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USREF

Attribute	**Description**	
Name	USREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Ovd

Attribute	**Description**	
Name	Contract-Ovd	
Datatype		
Description	Includes Contract Overrides details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates Confirmed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes Rekey fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.53.2.SE-Deal-Blkrel-Auth-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters-IO*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*
        - *NEWDISPVAL*
        - *FLDDESC*
    - *Rekey-Fields*

SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for authorization request of the SDblockrelease

TOP

Deal-Masters-IO

Attribute	Description
Name	Deal-Masters-IO
Datatype	
Description	Authorization of Securities Deal Input - Block Securities IO Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String

Description	Indicates Overrides
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes Rekey details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

2.53.3.SE-Deal-Blkrel-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*
        - *NEWDISPVAL*
        - *FLDDESC*
    - *Rekey-Fields*

SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full response of the authorization request

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Authorization of Securities Deal Input - Block Securities Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String

Description	Indicates Confirmed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes Rekey fields details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date

Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.53.4.SE-Deal-Blkrel-Auth-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Blockrelease-PK*
      - *DEALREF*
      - *USERREF*
      - *XREF*
      - *VERNO*
      - *Event-Log*
        - *LEGDESC*
        - *BUYSELL*
        - *ESN*
        - *EVENTCD*
        - *PRDCD*
        - *DEALREFE*
        - *USREF*
        - *Contract-Ovd*
          - *CONFIRMED*
          - *OVDMSGS*
        - *Contract-Change-Log*
          - *OLDDISPVAL*

NEWDISPVAL
FLDDESC
Fields
SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
Deal-Masters-IO
DEALREF
XREF
Cont-Event-Log
LEGDESC
BUYSELL
ESN
EVENTCD
PRDCD
DEALREFE
USREF
Contract-Ovd
CONFIRMED
OVDMSGS
Contract-Change-Log
OLDDISPVAL
NEWDISPVAL
FLDDESC
Rekey-Fields
SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for primary key response of the authorization request

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Blockrelease-PK

Attribute	Description
Name	Deal-Blockrelease-PK
Datatype	
Description	Authorization of Securities Deal Input - Block Securities PK Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Event-Log

Attribute	Description
Name	Event-Log
Datatype	
Description	Includes Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd

Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Fields

Attribute	Description
Name	Fields
Datatype	
Description	Includes Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID

Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Masters-IO

Attribute	Description
Name	Deal-Masters-IO
Datatype	
Description	Authorization of Securities Deal Input - Block Securities IO Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log

Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes Rekey details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number

Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.54.CreateSDBlockRelease

Creation of Securities Deal Input - Block Securities

2.54.1.SE-Deal-Blkrel-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *PROD*
    - *XREF*
    - *SECCODE*
    - *SECDESC*
    - *SECSERIES*
    - *NOMQUOT*
    - *TXNDATE*
    - *BLOCKDATE*
    - *RELSDATE*
    - *PARTRELALLOW*
    - *AUTORELALLOW*
    - *DEALQTY*
    - *BLOCKREF*
    - *BLOCKTYPE*
    - *Deal-Details*

- *FORMTYPE*
- *PORTFOLIO*
- *PORTFDESC*
- *CPTY*
- *CPTYDESC*
- *SKLOC*
- *SKLOCDESC*
- *SKACC*

Cert_Detail

- *DEALREFNO*

Cert_Detail__A

- *CERTFNO*
- *OTYTOBLOCK*
- *STATUS*

Contract_Event_Log

- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*

TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Contract
FCCREF
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1

ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Contract-Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7

FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full request for SD blockrelease Contract creation

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Creation of Securities Deal Input - Block Securities Master Type

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String

Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOMQUOT

Attribute	Description
Name	NOMQUOT
Datatype	String
Description	Indicates Quote By Units : U Normal : N
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

BLOCKDATE

Attribute	Description
Name	BLOCKDATE
Datatype	Date
Description	Indicates Block Date

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

PARTRELALLOW

Attribute	Description
Name	PARTRELALLOW
Datatype	String
Description	Indicates Partial Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTORELALLOW

Attribute	Description
Name	AUTORELALLOW
Datatype	String
Description	Indicates Auto Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BLOCKREF

Attribute	Description
Name	BLOCKREF
Datatype	String

Description	Indicates Block Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	Indicates Block Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDESC

Attribute	Description	
Name	PORTFDESC	
Datatype	String	
Description	Indicates Portfolio Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYDESC

Attribute	Description	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOC

Attribute	Description	
Name	SKLOC	
Datatype	String	
Description	Indicates SK Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Cert_Detail

Attribute	Description
Name	Cert_Detail
Datatype	
Description	Includes Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cert_Detail__A

Attribute	Description
Name	Cert_Detail__A
Datatype	

Description	Includes Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CERTFNO

Attribute	Description
Name	CERTFNO
Datatype	Number
Description	Indicates Certificate Number
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

OTYTOBLOCK

Attribute	Description
Name	OTYTOBLOCK
Datatype	String
Description	Indicates Quantity To Be Blocked
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	Date
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract_Event_Log

Attribute	Description
Name	Contract_Event_Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description

Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Liquidated : L Reversed : V Hold : H Reopened : R Closed : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RATECOD

Attribute	Description	
Name	RATECOD	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description

Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract

Attribute	Description	
Name	Contract	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	Description	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	Description
Name	CRNESN

Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event sequence number.
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Regulatory Report 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Contract-Advices

Attribute	Description
Name	Contract-Advices
Datatype	
Description	Includes Contract Advices details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MEDIUM

Attribute	**Description**	
Name	MEDIUM	
Datatype	String	
Description	Indicates Medium Through Which An Advice Is Generated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

SUPPRESS

Attribute	**Description**	
Name	SUPPRESS	
Datatype	String	
Description	Indicates whether the Message should be suppressed or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates the priority of the message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	1

TOP

CHGREQ

Attribute	**Description**
Name	CHGREQ
Datatype	String
Description	Indicates Change Request

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

2.54.2.SE-Deal-Blkrel-Create-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *PROD*
    - *USERREF*
    - *XREF*
    - *SECCODE*
    - *SECSERIES*
    - *NOMQUOT*
    - *TXNDATE*
    - *BLOCKDATE*
    - *RELSDATE*
    - *PARTRELALLOW*
    - *AUTORELALLOW*
    - *DEALQTY*
    - *BLOCKREF*
    - *BLOCKTYPE*
    - *Deal-Details*
      - *FORMTYPE*
      - *PORTFOLIO*
      - *PORTFDESC*

CPTY
CPTYDESC
SKLOC
SKLOCDESC
SKACC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only request for SD blockrelease contract creation

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Creation of Securities Deal Input - Block Securities Master Type

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOMQUOT

Attribute	Description
Name	NOMQUOT
Datatype	String
Description	Indicates Quote By Units : U Normal : N
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

BLOCKDATE

Attribute	Description
Name	BLOCKDATE
Datatype	Date
Description	Indicates Block Date

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

PARTRELALLOW

Attribute	Description
Name	PARTRELALLOW
Datatype	String
Description	Indicates Partial Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTORELALLOW

Attribute	Description
Name	AUTORELALLOW
Datatype	String
Description	Indicates Auto Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BLOCKREF

Attribute	Description
Name	BLOCKREF
Datatype	String
Description	Indicates Block Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	Indicates Block Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,I,D</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDESC

Attribute	Description
Name	PORTFDESC
Datatype	String
Description	Indicates Portfolio Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String

Description	Indicates Customer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

2.54.3.SE-Deal-Blkrel-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *XREF*
    - *FCCREF*
    - *VERNO*
    - *PREVVERNO*
    - *SECCODE*
    - *SECSERIES*
    - *NOMQUOT*
    - *BLOCKDATE*
    - *RELSDATE*
    - *TXNDATE*
    - *PARTRELALLOW*
    - *AUTORELALLOW*
    - *DEALQTY*
    - *BLOCKTYPE*
    - *SECDESC*
    - *TEMPLATE*
    - *PROD*
    - *DEALREF*

PRODDESC
VERSION
USERREF
ESN
EVNTCD
PRODTYPE
SECTYP
SCY
REDEDEMPOREXPIRYDT
SECREF
MARKETCD
Deal-Details
  PORTFOLIO
  PORTFDESC
  CPTY
  CPTYDESC
  SKLOC
  SKACC
  SKLOCDESC
  FORMTYPE
Cert-Detail
  DEALREFNO
Cert-Detail--A
  CERTFNO
  OTYTOBLOCK
  STATUS
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
Tax-Master
  FNDREFNO
  VERSNO
  SECID
  TXTREF
  SECREF
  Issr-Tax-Assoc
    CRRATESN
    INTCOMP
    RATECOD
    WAIVER

- CONTREF
- Tran-Tax-Assoc
  - CRRATESN
  - INTCOMP
  - RULE
  - WAIVER
  - CONTREF
- Tran-Tax-Appln
  - CRRATESN
  - INTCOMP
  - TAGCCY
  - TAGAMNT
  - TAXCCY
  - TAXAMNT
  - WAIVER
  - LIQINDICAT
  - CONTREF
- Tran-Tax-Liqd-Master
  - INTCOMP
  - TAXCCY
  - TAXAMNT
  - CONTREF

Contract

- FCCREF
- Charge-Application
  - CHGCOMP
  - CRNESN
  - TGCCY
  - TGAMT
  - CHGCCY
  - CHGAMT
  - WAIVER
  - LIQINTR
  - DISACR
- Charge-Association
  - CHGCOMP
  - CRNESN
  - RULE
  - WAIVER
  - DISACR
  - ACCREQ
  - CHGDESC
- Charge-Liquidation
  - ESN

- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Contract-Advices

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*

MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Screen Response for SD Blockrelease Contract creation

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Creation of Securities Deal Input - Block Securities Masster Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOMQUOT

Attribute	Description
Name	NOMQUOT
Datatype	String
Description	Indicates Quote By Units : U Normal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLOCKDATE

Attribute	Description
Name	BLOCKDATE
Datatype	Date
Description	Indicates Block Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

PARTRELALLOW

Attribute	Description	
Name	PARTRELALLOW	
Datatype	String	
Description	Indicates Partial Release Allow Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTORELALLOW

Attribute	Description	
Name	AUTORELALLOW	
Datatype	String	
Description	Indicates Auto Release Allow Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	Description	
Name	DEALQTY	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BLOCKTYPE

Attribute	Description	
Name	BLOCKTYPE	
Datatype	String	
Description	Indicates Block Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEMPLATE

Attribute	Description
Name	TEMPLATE
Datatype	String
Description	Indicates Template
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRODDESC

Attribute	Description
Name	PRODDESC

Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODTYPE

Attribute	**Description**	
Name	PRODTYPE	
Datatype	String	
Description	Indicates Product type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECTYP

Attribute	**Description**	
Name	SECTYP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SCY

Attribute	**Description**	
Name	SCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REDEDEMPOREXPIRYDT

Attribute	**Description**	
Name	REDEDEMPOREXPIRYDT	
Datatype	String	
Description	Indicates Expiry date	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECREF

Attribute	Description	
Name	SECREF	
Datatype	String	
Description	Indicates Security Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARKETCD

Attribute	Description	
Name	MARKETCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Deal-Details

Attribute	Description	
Name	Deal-Details	
Datatype		
Description	Includes Deal details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PORTFOLIO

Attribute	Description	
Name	PORTFOLIO	
Datatype	String	
Description	Indicates Portfolio	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDESC

Attribute	Description
Name	PORTFDESC
Datatype	String
Description	Indicates Portfolio Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

Cert-Detail

Attribute	Description
Name	Cert-Detail
Datatype	
Description	Includes Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cert-Detail--A

Attribute	Description
Name	Cert-Detail--A
Datatype	
Description	Includes Certificate details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CERTFNO

Attribute	Description
Name	CERTFNO
Datatype	Number
Description	Indicates Certificate Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr></table>

TOP

OTYTOBLOCK

Attribute	Description
Name	OTYTOBLOCK
Datatype	String
Description	Indicates Quantity To Be Blocked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	Date
Description	Indicates Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Liquidated : L Reversed : V Hold : H Reopened : R Closed : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Indicates Security Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc

Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description	
Name	CONTREF	
Datatype	String	
Description	Specifies The Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Tran-Tax-Assoc

Attribute	Description	
Name	Tran-Tax-Assoc	
Datatype		
Description	Specifies The Association Details Of Transaction Level Tax.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN

Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description	Specifies The Tax Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINDICAT

Attribute	**Description**	
Name	LIQINDICAT	
Datatype	String	
Description	Specifies whether to be liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Specifies The Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS

Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Contract-Advices

Attribute	Description
Name	Contract-Advices
Datatype	
Description	Includes Contract Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String

Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	1

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description	Indicates Change Request	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

Mis-Details

Attribute	**Description**	
Name	Mis-Details	
Datatype		
Description	Includes MIS details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.54.4.SE-Deal-Blkrel-Create-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Blockrelease-PK*
      - *DEALREF*
      - *USERREF*
      - *XREF*
      - *VERNO*
      - *Event-Log*
        - *LEGDESC*
        - *BUYSELL*
        - *ESN*
        - *EVENTCD*
        - *PRDCD*
        - *DEALREFE*
        - *USREF*
        - *Contract-Ovd*
          - *CONFIRMED*
          - *OVDMSGS*
        - *Contract-Change-Log*
          - *OLDDISPVAL*

NEWDISPVAL
FLDDESC
Fields
SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
Deal-Masters
PROD
USERREF
XREF
SECCODE
SECSERIES
NOMQUOT
TXNDATE
BLOCKDATE
RELSDATE
PARTRELALLOW
AUTORELALLOW
DEALQTY
BLOCKREF
BLOCKTYPE
Deal-Details
FORMTYPE
PORTFOLIO
PORTFDESC
CPTY
CPTYDESC
SKLOC
SKLOCDESC
SKACC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key Response for SD Blockrelease Contract creation

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Blockrelease-PK

Attribute	Description
Name	Deal-Blockrelease-PK
Datatype	
Description	Creation of Securities Deal Input - Block Securities PK Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Event-Log

Attribute	**Description**	
Name	Event-Log	
Datatype		
Description	Includes Event Log details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGDESC

Attribute	**Description**	
Name	LEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BUYSELL

Attribute	**Description**	
Name	BUYSELL	
Datatype	String	
Description	Indicates Buy Sell	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	2

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Fields

Attribute	Description
Name	Fields
Datatype	
Description	Includes Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Creation of Securities Deal Input - Block Securities Deal Type

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOMQUOT

Attribute	Description
Name	NOMQUOT
Datatype	String
Description	Indicates Quote By Units : U Normal : N
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

BLOCKDATE

Attribute	Description
Name	BLOCKDATE
Datatype	Date
Description	Indicates Block Date

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

PARTRELALLOW

Attribute	Description
Name	PARTRELALLOW
Datatype	String
Description	Indicates Partial Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTORELALLOW

Attribute	Description
Name	AUTORELALLOW
Datatype	String
Description	Indicates Auto Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BLOCKREF

Attribute	Description
Name	BLOCKREF
Datatype	String
Description	Indicates Block Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	Indicates Block Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

PORTFOLIO

Attribute	Description	
Name	PORTFOLIO	
Datatype	String	
Description	Indicates Portfolio	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDESC

Attribute	Description	
Name	PORTFDESC	
Datatype	String	
Description	Indicates Portfolio Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYDESC

Attribute	Description	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.55.DeleteSDBlockRelease

Deletion of Securities Deal Input - Block Securities

2.55.1.SE-Deal-Blkrel-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Blockrelease-Delete*
    - *DEALREF*
    - *XREF*
    - *VERNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full screen requst for SD Blockrelease contract Deletion

TOP

Deal-Blockrelease-Delete

Attribute	Description
Name	Deal-Blockrelease-Delete
Datatype	
Description	Deletion of Securities Deal Input - Block Securities Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.55.2.SE-Deal-Blkrel-Delete-Req-Msg.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Deal-Blockrelease-Delete*
  - *DEALREF*
  - *XREF*
  - *VERNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary Key requst for SD Blockrelease contract Deletion

TOP

Deal-Blockrelease-Delete

Attribute	Description
Name	Deal-Blockrelease-Delete
Datatype	
Description	Deletion of Securities Deal Input - Block Securities Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.55.3.SE-Deal-Blkrel-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *USERREF*
    - *XREF*
    - *VERNO*
    - *Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*
        - *NEWDISPVAL*

FLDDESC

Fields

SECCODE

INPR

DEALQTY

TRDDT

DSTLDT

PFID

MSTDT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Screen response for the SD BlockRelease Contract deletion

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Deletion of Securities Deal Input - Block Securities Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

Event-Log

Attribute	Description
Name	Event-Log
Datatype	
Description	Includes Event Log details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 2

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Fields

Attribute	Description
Name	Fields
Datatype	
Description	Includes Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT

Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.55.4.SE-Deal-Blkrel-Delete-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Blockrelease-PK*
      - *DEALREF*
      - *USERREF*
      - *XREF*
      - *VERNO*
      - *Event-Log*
        - *LEGDESC*
        - *BUYSELL*
        - *ESN*
        - *EVENTCD*
        - *PRDCD*
        - *DEALREFE*
        - *USREF*
        - *Contract-Ovd*
          - *CONFIRMED*
          - *OVDMSGS*
        - *Contract-Change-Log*
          - *OLDDISPVAL*

NEWDISPVAL
FLDDESC
Fields
SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
Deal-Blockrelease-Delete
DEALREF
XREF
VERNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key response for the SD BlockRelease Contract deletion

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Blockrelease-PK

Attribute	Description
Name	Deal-Blockrelease-PK
Datatype	
Description	Deletion of Securities Deal Input - Block Securities PK Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Event-Log

Attribute	Description
Name	Event-Log
Datatype	
Description	Includes Event Log details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE

Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes Contract Overrides details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105

TOP

Fields

Attribute	Description
Name	Fields
Datatype	
Description	Includes Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Blockrelease-Delete

Attribute	Description
Name	Deal-Blockrelease-Delete
Datatype	
Description	Deletion of Securities Deal Input - Block Securities Type

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.LiquidateSDBlockRelease

Liquidation of Securities Deal Input - Block Securities

2.56.1.SE-Deal-Blkrel-Liq-Req-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Liqd-Deal*
    - *DEALREFERENCE*
    - *XREF*
    - *UNRELUNIT*
    - *UNITTOREL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for request of SD BlockRelease contract Liquidation

TOP

Liqd-Deal

Attribute	Description
Name	Liqd-Deal
Datatype	
Description	Liquidation of Securities Deal Input - Block Securities Type

TOP

DEALREFERENCE

Attribute	Description
Name	DEALREFERENCE
Datatype	String
Description	Indicates Contract Referennce Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

UNRELUNIT

Attribute	**Description**	
Name	UNRELUNIT	
Datatype	Number	
Description	Indicates Blocked Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

UNITTOREL

Attribute	**Description**	
Name	UNITTOREL	
Datatype	Number	
Description	Indicates Release Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

2.56.2.SE-Deal-Blkrel-Liq-Req-Msg.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Liqd-Deal*
  - *DEALREFERENCE*
  - *XREF*
  - *UNRELUNIT*
  - *UNITTOREL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for request of SD BlockRelease contract Liquidation

TOP

Liqd-Deal

Attribute	Description
Name	Liqd-Deal
Datatype	
Description	Liquidation of Securities Deal Input - Block Securities Type

TOP

DEALREFERENCE

Attribute	Description
Name	DEALREFERENCE
Datatype	String
Description	Indicates Contract Referennce Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

UNRELUNIT

Attribute	**Description**	
Name	UNRELUNIT	
Datatype	Number	
Description	Indicates Blocked Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

UNITTOREL

Attribute	**Description**	
Name	UNITTOREL	
Datatype	Number	
Description	Indicates Release Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

2.56.3.SE-Deal-Blkrel-Liq-Res-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal*
    - *DEALREFERENCE*
    - *XREF*
    - *UNRELUNIT*
    - *UNITTOREL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Response of SD BlockRelease contract Liquidation

TOP

Deal

Attribute	Description
Name	Deal
Datatype	
Description	Liquidation of Securities Deal Input - Block Securities Type

TOP

DEALREFERENCE

Attribute	Description
Name	DEALREFERENCE
Datatype	String
Description	Indicates Contract Referennce Number

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNRELUNIT

Attribute	Description
Name	UNRELUNIT
Datatype	Number
Description	Indicates Blocked Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

UNITTOREL

Attribute	Description
Name	UNITTOREL
Datatype	Number
Description	Indicates Release Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.56.4.SE-Deal-Blkrel-Liq-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal*
      - *DEALREFERENCE*
      - *XREF*
      - *UNRELUNIT*
      - *UNITTOREL*
    - *Liqd-Deal*
      - *DEALREFERENCE*
      - *XREF*
      - *UNRELUNIT*
      - *UNITTOREL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Response of SD BlockRelease contract Liquidation

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal

Attribute	Description
Name	Deal
Datatype	
Description	Liquidation of Securities Deal Input - Block Securities

TOP

DEALREFERENCE

Attribute	Description
Name	DEALREFERENCE
Datatype	String
Description	Indicates Contract Referennce Number
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNRELUNIT

Attribute	Description
Name	UNRELUNIT
Datatype	Number
Description	Indicates Blocked Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

UNITTOREL

Attribute	Description
Name	UNITTOREL
Datatype	Number
Description	Indicates Release Quantity

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Liqd-Deal

Attribute	Description
Name	Liqd-Deal
Datatype	
Description	Liquidation of Securities Deal Input - Block Securities Type

TOP

DEALREFERENCE

Attribute	Description
Name	DEALREFERENCE
Datatype	String
Description	Indicates Contract Referennce Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNRELUNIT

Attribute	Description
Name	UNRELUNIT
Datatype	Number
Description	Indicates Blocked Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

UNITTOREL

Attribute	Description
Name	UNITTOREL
Datatype	Number
Description	Indicates Release Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.57.ModifySDBlockRelease

Modification of Securities Deal Input - Block Securities

2.57.1.SE-Deal-Blkrel-Modify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *USERREF*
    - *SECCODE*
    - *SECSERIES*
    - *RELSDATE*
    - *PARTRELALLOW*
    - *AUTORELALLOW*
    - *DEALQTY*
    - *PORTFOLIO*
    - *Deal-Details*
      - *FORMTYPE*
      - *PORTFOLIO*
      - *SKLOC*
      - *SKACC*

- *Tax-Master*
  - *FNDREFNO*
  - *VERSNO*
  - *SECID*
  - *TXTREF*
  - *SECREF*
  - *Issr-Tax-Assoc*
    - *CRRATESN*
    - *INTCOMP*
    - *RATECOD*
    - *WAIVER*
    - *CONTREF*
  - *Tran-Tax-Assoc*
    - *CRRATESN*
    - *INTCOMP*
    - *RULE*
    - *WAIVER*
    - *CONTREF*
  - *Tran-Tax-Appln*
    - *CRRATESN*
    - *INTCOMP*
    - *TAGCCY*
    - *TAGAMNT*
    - *TAXCCY*
    - *TAXAMNT*
    - *WAIVER*
    - *LIQINDICAT*
    - *CONTREF*
  - *Tran-Tax-Liqd-Master*
    - *INTCOMP*
    - *TAXCCY*
    - *TAXAMNT*
    - *CONTREF*
- *Contract*
  - *FCCREF*
  - *Charge-Application*
    - *CHGCOMP*
    - *CRNESN*
    - *TGCCY*
    - *TGAMT*
    - *CHGCCY*
    - *CHGAMT*
    - *WAIVER*
    - *LIQINTR*

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Settlement-Details

AMTTAG

TRNTPCD

BNKOPRCD

REGREP1

REGREP2

REGREP3

ENV_CONT1

ENV_CONT2

ENV_CONT3

ENV_CONT4

ENV_CONT5

TIMEIND1

TIMEIND2

TIMEIND3

INSTRCDLT

INSTRCDLT1

INSTRCDLT2

INSTRCDLT3

INSTRCDLT4

INSTRCDLT5

INSTRCDTXT

INSTRCDTXT1

INSTRCDTXT2

INSTRCDTXT3

INSTRCDTXT4

INSTRCDTXT5

Contract-Advices

MSGTYPE

PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3

COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8

TXNMIS9LBL9

TXNMIS10LBL10

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Screen Request of modification of SD BlockRelease contract

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Modification of Securities Deal Input - Block Securities Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	Restrictions: maxLength; Description: 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	Restrictions: maxLength; Description: 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Restrictions	Restrictions: maxLength; Description: 16

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Restrictions	Restrictions: maxLength; Description: 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

PARTRELALLOW

Attribute	Description	
Name	PARTRELALLOW	
Datatype	String	
Description	Indicates Partial Release Allow Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTORELALLOW

Attribute	Description	
Name	AUTORELALLOW	
Datatype	String	
Description	Indicates Auto Release Allow Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	Description	
Name	DEALQTY	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description

Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description

Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract

Attribute	**Description**	
Name	Contract	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**
Name	CRNESN

Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCREQ

Attribute	**Description**	
Name	ACCREQ	
Datatype	String	
Description	Indicates the Accrual required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CHGDESC

Attribute	**Description**	
Name	CHGDESC	
Datatype	String	
Description	The Charge Component Code description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates the Event sequence number.	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Regulatory Report 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	**Description**	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	**Description**	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	**Description**	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Contract-Advices

Attribute	Description
Name	Contract-Advices
Datatype	
Description	Includes Contract Advices details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MEDIUM

Attribute	**Description**	
Name	MEDIUM	
Datatype	String	
Description	Indicates Medium Through Which An Advice Is Generated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

SUPPRESS

Attribute	**Description**	
Name	SUPPRESS	
Datatype	String	
Description	Indicates whether the Message should be suppressed or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	Number	
Description	Indicates the priority of the message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	1

TOP

CHGREQ

Attribute	**Description**
Name	CHGREQ
Datatype	String
Description	Indicates Change Request

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

2.57.2.SE-Deal-Blkrel-Modify-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *USERREF*
    - *SECCODE*
    - *SECSERIES*
    - *RELSDATE*
    - *PARTRELALLOW*
    - *AUTORELALLOW*
    - *DEALQTY*
    - *PORTFOLIO*
    - *Deal-Details*
      - *FORMTYPE*
      - *PORTFOLIO*
      - *SKLOC*
      - *SKACC*
    - *Mis-Details*
      - *BRANCH*
      - *CUSTNO*

MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for IO Request of modification of SD BlockRelease contract

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Modification of Securities Deal Input - Block Securities Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

PARTRELALLOW

Attribute	Description	
Name	PARTRELALLOW	
Datatype	String	
Description	Indicates Partial Release Allow Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTORELALLOW

Attribute	Description	
Name	AUTORELALLOW	
Datatype	String	
Description	Indicates Auto Release Allow Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	Description	
Name	DEALQTY	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PORTFOLIO

Attribute	Description	
Name	PORTFOLIO	
Datatype	String	
Description	Indicates Portfolio	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,I,D</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

2.57.3.SE-Deal-Blkrel-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *XREF*
    - *FCCREF*
    - *VERNO*
    - *PREVVERNO*
    - *SECCODE*
    - *SECSERIES*
    - *NOMQUOT*
    - *BLOCKDATE*
    - *RELSDATE*
    - *TXNDATE*
    - *PARTRELALLOW*
    - *AUTORELALLOW*
    - *DEALQTY*
    - *BLOCKTYPE*
    - *SECDESC*
    - *TEMPLATE*
    - *PROD*
    - *DEALREF*

PRODDESC
VERSION
USERREF
ESN
EVNTCD
PRODTYPE
SECTYP
SCY
REDEDEMPOREXPIRYDT
SECREF
MARKETCD
Deal-Details
  PORTFOLIO
  PORTFDESC
  CPTY
  CPTYDESC
  SKLOC
  SKACC
  SKLOCDESC
  FORMTYPE
Cert-Detail
  DEALREFNO
Cert-Detail--A
  CERTFNO
  OTYTOBLOCK
  STATUS
Contract-Event-Log
  MAKERID
  MAKERSTAMP
  CHECKERID
  CHECKERSTAMP
  AUTHSTAT
  CONTSTAT
Tax-Master
  FNDREFNO
  VERSNO
  SECID
  TXTREF
  SECREF
  Issr-Tax-Assoc
    CRRATESN
    INTCOMP
    RATECOD
    WAIVER

- CONTREF
- Tran-Tax-Assoc
  - CRRATESN
  - INTCOMP
  - RULE
  - WAIVER
  - CONTREF
- Tran-Tax-Appln
  - CRRATESN
  - INTCOMP
  - TAGCCY
  - TAGAMNT
  - TAXCCY
  - TAXAMNT
  - WAIVER
  - LIQINDICAT
  - CONTREF
- Tran-Tax-Liqd-Master
  - INTCOMP
  - TAXCCY
  - TAXAMNT
  - CONTREF

Contract

- FCCREF
- Charge-Application
  - CHGCOMP
  - CRNESN
  - TGCCY
  - TGAMT
  - CHGCCY
  - CHGAMT
  - WAIVER
  - LIQINTR
  - DISACR
- Charge-Association
  - CHGCOMP
  - CRNESN
  - RULE
  - WAIVER
  - DISACR
  - ACCREQ
  - CHGDESC
- Charge-Liquidation
  - ESN

- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Contract-Advices

- *MSGTYPE*
- *PARTYID*
- *MEDIUM*
- *SUPPRESS*
- *PRIORITY*
- *CHGREQ*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*

MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Screen Response of modification of SD BlockRelease contract

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Modification of Securities Deal Input - Block Securities Master Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOMQUOT

Attribute	Description
Name	NOMQUOT
Datatype	String
Description	Indicates Quote By Units : U Normal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLOCKDATE

Attribute	Description
Name	BLOCKDATE
Datatype	Date
Description	Indicates Block Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

PARTRELALLOW

Attribute	Description
Name	PARTRELALLOW
Datatype	String
Description	Indicates Partial Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTORELALLOW

Attribute	Description
Name	AUTORELALLOW
Datatype	String
Description	Indicates Auto Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	Indicates Block Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEMPLATE

Attribute	Description
Name	TEMPLATE
Datatype	String
Description	Indicates Template
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRODDESC

Attribute	Description
Name	PRODDESC

Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates Event Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODTYPE

Attribute	**Description**	
Name	PRODTYPE	
Datatype	String	
Description	Indicates Product type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECTYP

Attribute	**Description**	
Name	SECTYP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SCY

Attribute	**Description**	
Name	SCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REDEDEMPOREXPIRYDT

Attribute	**Description**	
Name	REDEDEMPOREXPIRYDT	
Datatype	String	
Description	Indicates Expiry date	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Indicates Security Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETCD

Attribute	Description
Name	MARKETCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDESC

Attribute	Description	
Name	PORTFDESC	
Datatype	String	
Description	Indicates Portfolio Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Customer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CPTYDESC

Attribute	Description	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SKLOC

Attribute	Description	
Name	SKLOC	
Datatype	String	
Description	Indicates SK Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

Cert-Detail

Attribute	Description
Name	Cert-Detail
Datatype	
Description	Includes Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cert-Detail--A

Attribute	Description
Name	Cert-Detail--A
Datatype	
Description	Includes Certificate details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CERTFNO

Attribute	Description
Name	CERTFNO
Datatype	Number
Description	Indicates Certificate Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr></table>

TOP

OTYTOBLOCK

Attribute	Description
Name	OTYTOBLOCK
Datatype	String
Description	Indicates Quantity To Be Blocked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	Date
Description	Indicates Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the User Identification who inputted the record	
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the inputting time of the record	
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Identification who authorised the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

AUTHSTAT

Attribute	**Description**

Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Liquidated : L Reversed : V Hold : H Reopened : R Closed : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Indicates Security Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc

Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN

Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description	Specifies The Tax Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINDICAT

Attribute	**Description**	
Name	LIQINDICAT	
Datatype	String	
Description	Specifies whether to be liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Specifies The Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS

Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description	
Name	INSTRCDTXT1	
Datatype	String	
Description	Indicates the Instruction Code Text1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT2

Attribute	Description	
Name	INSTRCDTXT2	
Datatype	String	
Description	Indicates the Instruction Code Text2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Contract-Advices

Attribute	Description
Name	Contract-Advices
Datatype	
Description	Includes Contract Advices details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String

Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	1

TOP

CHGREQ

Attribute	**Description**	
Name	CHGREQ	
Datatype	String	
Description	Indicates Change Request	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

Mis-Details

Attribute	**Description**	
Name	Mis-Details	
Datatype		
Description	Includes MIS details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description	Indicates The Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.57.4.SE-Deal-Blkrel-Modify-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Blockrelease-PK*
      - *DEALREF*
      - *USERREF*
      - *XREF*
      - *VERNO*
      - *Event-Log*
        - *LEGDESC*
        - *BUYSELL*
        - *ESN*
        - *EVENTCD*
        - *PRDCD*
        - *DEALREFE*
        - *USREF*
        - *Contract-Ovd*
          - *CONFIRMED*
          - *OVDMSGS*
        - *Contract-Change-Log*
          - *OLDDISPVAL*

- *NEWDISPVAL*
- *FLDDESC*
- *Fields*
  - *SECCODE*
  - *INPR*
  - *DEALQTY*
  - *TRDDT*
  - *DSTLDT*
  - *PFID*
  - *MSTDT*
- *Deal-Masters*
  - *DEALREF*
  - *XREF*
  - *USERREF*
  - *SECCODE*
  - *SECSERIES*
  - *RELSDATE*
  - *PARTRELALLOW*
  - *AUTORELALLOW*
  - *DEALQTY*
  - *PORTFOLIO*
  - *Deal-Details*
    - *FORMTYPE*
    - *PORTFOLIO*
    - *SKLOC*
    - *SKACC*
  - *Mis-Details*
    - *BRANCH*
    - *CUSTNO*
    - *MISGRP*
    - *REL_REF*
    - *REL_ACC*
    - *MISHD*
    - *POOLCD*
    - *REFRT*
    - *REFRTTYPE*
    - *REFXRT*
    - *CALCMETH*
    - *MISGRPTXN*
    - *REFRTCD*
    - *REFRTSPRD*
    - *FUNDMIS1*
    - *FUNDMIS2*
    - *FUNDMIS3*

FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7

FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key Response of modification of SD BlockRelease contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Blockrelease-PK

Attribute	Description
Name	Deal-Blockrelease-PK
Datatype	
Description	Modification of Securities Deal Input - Block Securities PK Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERNO

Attribute	Description	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Event-Log

Attribute	Description	
Name	Event-Log	
Datatype		
Description	Includes Event Log details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC

Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy Sell
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Period

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREFE

Attribute	**Description**	
Name	DEALREFE	
Datatype	String	
Description	Indicates Deal Reference No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USREF

Attribute	**Description**	
Name	USREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Ovd

Attribute	**Description**	
Name	Contract-Ovd	
Datatype		
Description	Includes Contract Overrides details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates Confirmed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates Overrides
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes Contract Change Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates Old Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates New Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates Field Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Fields

Attribute	Description
Name	Fields
Datatype	
Description	Includes Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description

Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Modification of Securities Deal Input - Block Securities Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

PARTRELALLOW

Attribute	Description
Name	PARTRELALLOW
Datatype	String
Description	Indicates Partial Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTORELALLOW

Attribute	Description
Name	AUTORELALLOW
Datatype	String
Description	Indicates Auto Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String

Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.58.QuerySDBlockRelease

Query of Securities Deal Input - Block Securities

2.58.1.SE-Deal-Blkrel-Query-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Blockrelease*
    - *DEALREF*
    - *XREF*
    - *VERNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Created

TOP

Deal-Blockrelease

Attribute	Description
Name	Deal-Blockrelease
Datatype	
Description	Includes Securities Deal Block Release Query type details

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.58.2.SE-Deal-Blkrel-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Masters*
      - *XREF*
      - *FCCREF*
      - *VERNO*
      - *PREVVERNO*
      - *SECCODE*
      - *SECSERIES*
      - *NOMQUOT*
      - *BLOCKDATE*
      - *RELSDATE*
      - *TXNDATE*
      - *PARTRELALLOW*
      - *AUTORELALLOW*
      - *DEALQTY*
      - *BLOCKTYPE*
      - *SECDESC*
      - *TEMPLATE*
      - *PROD*

DEALREF
PRODDESC
VERSION
USERREF
ESN
EVNTCD
PRODTYPE
SECTYP
SCY
REDEDEMPOREXPIRYDT
SECREF
MARKETCD
Deal-Details
- *PORTFOLIO*
- *PORTFDESC*
- *CPTY*
- *CPTYDESC*
- *SKLOC*
- *SKACC*
- *SKLOCDESC*
- *FORMTYPE*

Cert-Detail
- *DEALREFNO*

Cert-Detail--A
- *CERTFNO*
- *OTYTOBLOCK*
- *STATUS*

Contract-Event-Log
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Tax-Master
- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*

WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Contract
FCCREF
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation

ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Contract-Advices
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF

REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Deal-Blockrelease
DEALREF
XREF
VERNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Includes Securities Deal Block Release Query Master type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

NOMQUOT

Attribute	Description
Name	NOMQUOT
Datatype	String
Description	Indicates Quote By Units : U Normal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

BLOCKDATE

Attribute	Description
Name	BLOCKDATE
Datatype	Date
Description	Indicates Block Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RELSDATE

Attribute	Description
Name	RELSDATE
Datatype	Date
Description	Indicates Release Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

PARTRELALLOW

Attribute	Description
Name	PARTRELALLOW
Datatype	String
Description	Indicates Partial Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTORELALLOW

Attribute	Description
Name	AUTORELALLOW
Datatype	String
Description	Indicates Auto Release Allow Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BLOCKTYPE

Attribute	Description
Name	BLOCKTYPE
Datatype	String
Description	Indicates Block Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEMPLATE

Attribute	Description
Name	TEMPLATE
Datatype	String
Description	Indicates Template
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF

Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates Event Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODTYPE

Attribute	**Description**	
Name	PRODTYPE	
Datatype	String	
Description	Indicates Product type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECTYP

Attribute	**Description**	
Name	SECTYP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SCY

Attribute	**Description**	
Name	SCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REDEDEMPOREXPIRYDT

Attribute	Description
Name	REDEDEMPOREXPIRYDT
Datatype	String
Description	Indicates Expiry date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Indicates Security Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETCD

Attribute	Description
Name	MARKETCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Deal-Details

Attribute	Description
Name	Deal-Details
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDESC

Attribute	Description
Name	PORTFDESC
Datatype	String
Description	Indicates Portfolio Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Customer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOC

Attribute	Description

Name	SKLOC
Datatype	String
Description	Indicates SK Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates SK Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	Indicates Form Type Script Based : S Dematerialized : D Immobolized : I
Restrictions	**Restrictions** / **Description** enumeration / S,I,D

TOP

Cert-Detail

Attribute	Description
Name	Cert-Detail
Datatype	
Description	Includes Certificate details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Deal Reference No
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cert-Detail--A

Attribute	Description
Name	Cert-Detail--A
Datatype	
Description	Includes Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CERTFNO

Attribute	Description
Name	CERTFNO
Datatype	Number
Description	Indicates Certificate Number
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

OTYTOBLOCK

Attribute	Description
Name	OTYTOBLOCK
Datatype	String
Description	Indicates Quantity To Be Blocked
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

STATUS

Attribute	Description
Name	STATUS

Datatype	Date
Description	Indicates Status
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status. Active : A Liquidated : L Reversed : V Hold : H Reopened : R Closed : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF

Datatype	String
Description	Indicates Security Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description

Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract

Attribute	Description
Name	Contract
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	String
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LQDSTS

Attribute	**Description**	
Name	LQDSTS	
Datatype	String	
Description	Indicates the Liquidation Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Settlement-Details

Attribute	**Description**	
Name	Settlement-Details	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

TRNTPCD

Attribute	**Description**	
Name	TRNTPCD	
Datatype	String	
Description	Indicates Transaction Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Contract-Advices

Attribute	Description
Name	Contract-Advices

Datatype	
Description	Includes Contract Advices details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the Message Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Specify The Customer To Whom The Advice Is Being Despatched
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates Medium Through Which An Advice Is Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates whether the Message should be suppressed or not
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority of the message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ
Datatype	String
Description	Indicates Change Request
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Deal-Blockrelease

Attribute	Description
Name	Deal-Blockrelease
Datatype	
Description	Includes Securities Deal Block Release Query type details

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.59.AuthSEBlockDeal

Authorization of Securities Block Deal - Detail

2.59.1.SE-Deal-Blkreq-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Authorized

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Block Deal Master Authorization type details

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	Description	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLSNGMUL

Attribute	**Description**	
Name	MLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.59.2.SE-Deal-Blkreq-Auth-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Authorized

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Includes Securities Block Deal Master Authorization Input Only type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	**Description**	
Name	RATE	
Datatype	Number	
Description	Indicates Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SCY

Attribute	**Description**	
Name	SCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPOTPRICE

Attribute	Description	
Name	SPOTPRICE	
Datatype	Number	
Description	Indicates Spot Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SETTLMTSK

Attribute	Description	
Name	SETTLMTSK	
Datatype	String	
Description	Indicates Settlement SKL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	Description	
Name	ISMA	
Datatype	String	
Description	Indicates Conforms to ISMA Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALTPADD

Attribute	Description	
Name	DEALTPADD	
Datatype	String	
Description	Indicates Deal Type Primary : P Secondary : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	**Description**	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	**Description**	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.59.3.SE-Deal-Blkreq-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Authorized

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Block Deal Master Authorization type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description	Indicates Multiple Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Multipleleg-Detail

Attribute	Description	
Name	Multipleleg-Detail	
Datatype		
Description	Includes Multiple Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLBLKDEALREF

Attribute	Description	
Name	MLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	Description	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.59.4.SE-Deal-Blkreq-Auth-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Authorized

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Block Deal Master Authorization type details

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Includes Securities Block Deal Master Authorization Input Only type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLATHSTAT

Attribute	**Description**	
Name	MLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALSTAT

Attribute	**Description**	
Name	MLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLLCYPRICE

Attribute	**Description**	
Name	MLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.60.CloseSEBlockDeal

Closure of Securities Block Deal

2.60.1.SE-Deal-Blkreq-Close-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Closed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Closure of Securities Block Deal Master Type

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	Description	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description	
Name	SLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.60.2.SE-Deal-Blkreq-Close-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Closed

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Closure of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	**Description**	
Name	RATE	
Datatype	Number	
Description	Indicates Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SCY

Attribute	**Description**	
Name	SCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 3 Restrictions: totalDigits; Description: 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	Attribute: minOccurs; Description: 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	**Description**	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	**Description**	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.60.3.SE-Deal-Blkreq-Close-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Closed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Closure of Securities Block Deal Master Type.

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	**Description**	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description
Name	SLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCDESC

Attribute	Description
Name	SLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.60.4.SE-Deal-Blkreq-Close-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Closed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Closure of Securities Block Deal Master Type

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Closure of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

QUOTBY

Attribute	Description	
Name	QUOTBY	
Datatype	String	
Description	Indicates Quote By Units : U Nominal : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALQT

Attribute	Description	
Name	DEALQT	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT

Attribute	Description	
Name	INT	
Datatype	String	
Description	Indicates Interest Flat : F Plus Accrued : P	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description	Indicates Deliver Free : F Against Payment : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIQT

Attribute	Description	
Name	PRIQT	
Datatype	String	
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description	Indicates DSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDT

Attribute	Description	
Name	INTDT	
Datatype	Date	
Description	Indicates Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.61.ConfirmSEBlockDeal

Confirmation of Securities Block Deal

2.61.1.SE-Deal-Blkreq-Confirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Confirmed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Confirmation of Securities Block Deal Master Type.

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description	
Name	SLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.61.2.SE-Deal-Blkreq-Confirm-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Confirmed

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Confirmation of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.61.3.SE-Deal-Blkreq-Confirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Confirmed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Confirmation of Securities Block Deal Master Type.

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	**Description**	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description
Name	SLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCDESC

Attribute	Description
Name	SLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.61.4.SE-Deal-Blkreq-Confirm-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Confirmed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Confirmation of Securities Block Deal Master Type

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Confirmation of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description	Indicates Deliver Free : F Against Payment : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIQT

Attribute	Description	
Name	PRIQT	
Datatype	String	
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description	Indicates DSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDT

Attribute	Description	
Name	INTDT	
Datatype	Date	
Description	Indicates Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLATHSTAT

Attribute	**Description**	
Name	MLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALSTAT

Attribute	**Description**	
Name	MLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLLCYPRICE

Attribute	**Description**	
Name	MLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Type	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.62.CreateSEBlockDeal

Creation of Securities Block Deal

2.62.1.SE-Deal-Blkreq-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Created

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Creation of Securities Block Deal Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	Description	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	Description	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	Description	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	Description	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description	
Name	SLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLSNGMUL

Attribute	**Description**	
Name	MLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.62.2.SE-Deal-Blkreq-Create-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Created

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Creation of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.62.3.SE-Deal-Blkreq-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Created

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Creation of Securities Block Deal Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	**Description**	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description
Name	SLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLSKLOCDESC

Attribute	Description
Name	SLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description	Indicates Multiple Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Multipleleg-Detail

Attribute	Description	
Name	Multipleleg-Detail	
Datatype		
Description	Includes Multiple Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLBLKDEALREF

Attribute	Description	
Name	MLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	Description	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.62.4.SE-Deal-Blkreq-Create-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Created

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Creation of Securities Block Deal Master Type

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Creation of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

QUOTBY

Attribute	Description	
Name	QUOTBY	
Datatype	String	
Description	Indicates Quote By Units : U Nominal : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALQT

Attribute	Description	
Name	DEALQT	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT

Attribute	Description	
Name	INT	
Datatype	String	
Description	Indicates Interest Flat : F Plus Accrued : P	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.63.DeleteSEBlockDeal

Deletion of Securities Block Deal

2.63.1.SE-Deal-Blkreq-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Deleted

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Deletion of Securities Block Deal Master Type

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	Description	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	Attribute: minOccurs; Description: 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	Description	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	Description	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	Description	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	Description	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.63.2.SE-Deal-Blkreq-Delete-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Deleted

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Deletion of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	**Description**	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	**Description**	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.63.3.SE-Deal-Blkreq-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Deleted

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Deletion of Securities Block Deal Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.63.4.SE-Deal-Blkreq-Delete-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Deleted

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Deletion of Securities Block Deal Master Type

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Deletion of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

QUOTBY

Attribute	Description	
Name	QUOTBY	
Datatype	String	
Description	Indicates Quote By Units : U Nominal : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALQT

Attribute	Description	
Name	DEALQT	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT

Attribute	Description	
Name	INT	
Datatype	String	
Description	Indicates Interest Flat : F Plus Accrued : P	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.64.LiquidateSEBlockDeal

Liquidation of Securities Block Deal

2.64.1.SE-Deal-Blkreq-Liquidate-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Liquidated

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Liquidation of Securities Block Deal Master Type

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	Description	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	Description	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	Description	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	Description	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	Description	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description	
Name	SLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.64.2.SE-Deal-Blkreq-Liquidate-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Liquidated

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Liquidation of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 3 Restrictions: totalDigits; Description: 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	Attribute: minOccurs; Description: 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	**Description**	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	**Description**	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.64.3.SE-Deal-Blkreq-Liquidate-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Liquidated

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Liquidation of Securities Block Deal Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	**Description**	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description	Indicates Multiple Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Multipleleg-Detail

Attribute	Description	
Name	Multipleleg-Detail	
Datatype		
Description	Includes Multiple Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLBLKDEALREF

Attribute	Description	
Name	MLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	Description	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.64.4.SE-Deal-Blkreq-Liquidate-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Liquidated

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Liquidation of Securities Block Deal Master Type

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Liquidation of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

QUOTBY

Attribute	Description	
Name	QUOTBY	
Datatype	String	
Description	Indicates Quote By Units : U Nominal : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALQT

Attribute	Description	
Name	DEALQT	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT

Attribute	Description	
Name	INT	
Datatype	String	
Description	Indicates Interest Flat : F Plus Accrued : P	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description	Indicates Deliver Free : F Against Payment : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIQT

Attribute	Description	
Name	PRIQT	
Datatype	String	
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description	Indicates DSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDT

Attribute	Description	
Name	INTDT	
Datatype	Date	
Description	Indicates Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLATHSTAT

Attribute	**Description**	
Name	MLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALSTAT

Attribute	**Description**	
Name	MLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLLCYPRICE

Attribute	**Description**	
Name	MLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.65.AmendSEBlockDeal

Modification of Securities Block Deal

2.65.1.SE-Deal-Blkreq-Modify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Confirmed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Modification of Securities Block Deal Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	Attribute: minOccurs Description: 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	Attribute: minOccurs Description: 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	Attribute: minOccurs Description: 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	Attribute: minOccurs Description: 0
Restrictions	Restrictions: maxLength Description: 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	Attribute: minOccurs Description: 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description	
Name	SLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.65.2.SE-Deal-Blkreq-Modify-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Confirmed

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Modification of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 3 Restrictions: totalDigits; Description: 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	Attribute: minOccurs; Description: 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	**Description**	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	**Description**	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.65.3.SE-Deal-Blkreq-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Confirmed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Modification of Securities Block Deal Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALQT

Attribute	Description	
Name	DEALQT	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT

Attribute	Description	
Name	INT	
Datatype	String	
Description	Indicates Interest Flat : F Plus Accrued : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description	Indicates Deliver Free : F Against Payment : P	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	**Description**	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.65.4.SE-Deal-Blkreq-Modify-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Confirmed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Modification of Securities Block Deal Master type

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Modification of Securities Block Deal IO Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description	Indicates Deliver Free : F Against Payment : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIQT

Attribute	Description	
Name	PRIQT	
Datatype	String	
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description	Indicates DSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDT

Attribute	Description	
Name	INTDT	
Datatype	Date	
Description	Indicates Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	**Description**	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLATHSTAT

Attribute	**Description**	
Name	MLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALSTAT

Attribute	**Description**	
Name	MLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLLCYPRICE

Attribute	**Description**	
Name	MLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Type	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.66.QuerySEBlockDeal

Query of Securities Block Deal

2.66.1.SE-Deal-Blkreq-Query-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Queried

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Includes Securities Deal Block Request Query Master Input Only type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	**Description**	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.66.2.SE-Deal-Blkreq-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*
      - *REC*
      - *IPPRICE*

YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*

SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
Block-Deal-Master-IO
PRD

DEALREF
USERREF
SECCODE
MKTCD
TRANDT
DEALTP
QUOTBY
DEALQT
TRADEDT
INT
DELIVER
PRIQT
DSTLDT
INTDT
REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*

SLMSTLDT
SLAUTOMAN
SLPORFOLTID
SLCPTY
SLPAYACCBRN
SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Queried

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Deal Block Request Query Master type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description

Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKER_DT_STAMP

Attribute	**Description**	
Name	MAKER_DT_STAMP	
Datatype	Date	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	Description	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	Description	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	**Description**	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLBRN

Attribute	**Description**	
Name	MLBRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLLEGPRD

Attribute	**Description**	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLSNGMUL

Attribute	**Description**	
Name	MLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER

Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String

Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Includes Securities Deal Block Request Query Master Input Only type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String

Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String

Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description

Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY

Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	**Description**	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	**Description**	
Name	SLDEALQTY	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SLDEALIP

Attribute	**Description**	
Name	SLDEALIP	
Datatype	Number	
Description	Indicates Deal Input Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLABSPRICE

Attribute	**Description**	
Name	SLABSPRICE	
Datatype	Number	
Description	Indicates Absolute Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	**Description**	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	**Description**	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	**Description**	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description

Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.ReverseSEBlockDeal

Reversal of Securities Block Deal

2.67.1.SE-Deal-Blkreq-Reverse-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*

SLPAYACC
SLSKLOC
SLSKACC
SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Reversed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Deal Block Request Reverse Master type details

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALREF

Attribute	Description	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USERREF

Attribute	Description	
Name	USERREF	
Datatype	String	
Description	Indicates User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	Description	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**	
Name	BRN	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	Description	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	Description	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	Description	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	Description	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description

Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	Date
Description	Indicates Maker Date Time:

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTH_STATUS

Attribute	**Description**	
Name	AUTH_STATUS	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Singleleg-Detail

Attribute	Description	
Name	Singleleg-Detail	
Datatype		
Description	Includes Single Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLBLKDEALREF

Attribute	Description	
Name	SLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLEXREF

Attribute	Description	
Name	SLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF

Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	**Description**	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description	
Name	SLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLEGDESC

Attribute	**Description**	
Name	SLLEGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Includes Multiple Leg details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY

Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

2.67.2.SE-Deal-Blkreq-Reverse-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master-IO*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*
- *SLDEALSTAT*
- *SLLCYPRICE*
- *SLRBUYSELL*

MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Reversed

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Includes Securities Deal Block Request Reverse Input Only type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE

Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATE

Attribute	**Description**	
Name	RATE	
Datatype	Number	
Description	Indicates Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SCY

Attribute	**Description**	
Name	SCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPOTPRICE

Attribute	**Description**	
Name	SPOTPRICE	
Datatype	Number	
Description	Indicates Spot Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SETTLMTSK

Attribute	**Description**	
Name	SETTLMTSK	
Datatype	String	
Description	Indicates Settlement SKL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISMA

Attribute	**Description**	
Name	ISMA	
Datatype	String	
Description	Indicates Conforms to ISMA Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALTPADD

Attribute	**Description**	
Name	DEALTPADD	
Datatype	String	
Description	Indicates Deal Type Primary : P Secondary : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description

Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SLSNGMUL

Attribute	**Description**	
Name	SLSNGMUL	
Datatype	String	
Description	Indicates Single Multiple Leg	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	Description	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 3 Restrictions: totalDigits; Description: 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	Attribute: minOccurs; Description: 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number

Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description

Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLAUTOMAN

Attribute	Description
Name	MLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLPORFOLTID

Attribute	Description
Name	MLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLCPTY

Attribute	Description
Name	MLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLPAYACCBRN

Attribute	Description
Name	MLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLPAYACC

Attribute	Description
Name	MLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MLSKLOC

Attribute	Description
Name	MLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLSKACC

Attribute	Description
Name	MLSKACC

Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.67.3.SE-Deal-Blkreq-Reverse-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Block-Deal-Master*
    - *PRD*
    - *DEALREF*
    - *USERREF*
    - *SECCODE*
    - *MKTCD*
    - *TRANDT*
    - *DEALTP*
    - *QUOTBY*
    - *DEALQT*
    - *TRADEDT*
    - *INT*
    - *DELIVER*
    - *PRIQT*
    - *DSTLDT*
    - *INTDT*
    - *REC*
    - *IPPRICE*
    - *YLD*

ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
CHECKER_ID
CHECKER_DT_STAMP
MAKER_ID
MAKER_DT_STAMP
AUTH_STATUS
ONCEAUTH
PRDDESC
SECDESC
MKTDESC
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*

SLBROKER
SLDEALQTY
SLDEALIP
SLABSPRICE
SLYLDFORINFO
SLATHSTAT
SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
SLLEGDESC
SLCPTYDESC
SLSKLOCDESC
MLDEALREF
MLLEGPRD
MLLEGDESC
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
MLLEGDESC
MLCPTYDESC
MLSKLOCDESC
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Blockdeal that has been successfully Reversed

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Deal Block Request Reverse Master type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRANDT

Attribute	Description
Name	TRANDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTP

Attribute	Description
Name	DEALTP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

QUOTBY

Attribute	Description
Name	QUOTBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALQT

Attribute	Description
Name	DEALQT
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INT

Attribute	Description
Name	INT
Datatype	String
Description	Indicates Interest Flat : F Plus Accrued : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DELIVER

Attribute	Description
Name	DELIVER
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIQT

Attribute	Description
Name	PRIQT
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDT

Attribute	Description
Name	INTDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	This field is internally used by GUI.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FACVALUNIT

Attribute	**Description**	
Name	FACVALUNIT	
Datatype	Number	
Description	Indicates Face Value Per Unit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FACVALDEAL

Attribute	**Description**	
Name	FACVALDEAL	
Datatype	Number	
Description	Indicates Face Value Of Deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PRDTYPE

Attribute	**Description**	
Name	PRDTYPE	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

SECTP

Attribute	**Description**	
Name	SECTP	
Datatype	String	
Description	Indicates Security Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECSER

Attribute	**Description**	
Name	SECSER	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

PMTCCY

Attribute	**Description**	
Name	PMTCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	Date
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP

Datatype	Date
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTH_STATUS

Attribute	Description
Name	AUTH_STATUS
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

SLMSTLDT

Attribute	Description
Name	SLMSTLDT

Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLAUTOMAN

Attribute	Description
Name	SLAUTOMAN
Datatype	String
Description	Indicates Auto MSTL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLPORFOLTID

Attribute	Description
Name	SLPORFOLTID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLCPTY

Attribute	Description
Name	SLCPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLPAYACCBRN

Attribute	Description
Name	SLPAYACCBRN
Datatype	String
Description	Indicates Pay Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLPAYACC

Attribute	Description
Name	SLPAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SLSKLOC

Attribute	Description
Name	SLSKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLSKACC

Attribute	Description
Name	SLSKACC
Datatype	String
Description	Indicates Safe keeping location account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLATHSTAT

Attribute	Description
Name	SLATHSTAT
Datatype	String
Description	Indicates Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLDEALSTAT

Attribute	Description
Name	SLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLCYPRICE

Attribute	Description
Name	SLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLRBUYSELL

Attribute	Description
Name	SLRBUYSELL
Datatype	String
Description	Indicates BUY_SELL Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SLLEGDESC

Attribute	Description
Name	SLLEGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLCPTYDESC

Attribute	Description	
Name	SLCPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLSKLOCDESC

Attribute	Description	
Name	SLSKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLDEALREF

Attribute	Description	
Name	MLDEALREF	
Datatype	String	
Description	Indicates Multiple Leg Deal Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLLEGPRD

Attribute	Description	
Name	MLLEGPRD	
Datatype	String	
Description	Indicates Multiple Leg Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

MLLEGDESC

Attribute	Description	
Name	MLLEGDESC	
Datatype	String	
Description	Indicates Multiple Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Multipleleg-Detail

Attribute	Description	
Name	Multipleleg-Detail	
Datatype		
Description	Includes Multiple Leg details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLBLKDEALREF

Attribute	Description	
Name	MLBLKDEALREF	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLEXREF

Attribute	Description	
Name	MLEXREF	
Datatype	String	
Description	Indicates External Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF

Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLMSTLDT

Attribute	Description
Name	MLMSTLDT
Datatype	Date
Description	Indicates MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	**Description**	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	**Description**	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	**Description**	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	**Description**	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description	
Name	MLBROKER	
Datatype	String	
Description	Indicates Broker	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MLATHSTAT

Attribute	Description
Name	MLATHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLDEALSTAT

Attribute	Description
Name	MLDEALSTAT
Datatype	String
Description	Indicates Deal Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MLLCYPRICE

Attribute	Description
Name	MLLCYPRICE
Datatype	Number
Description	Indicates Price in Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLLEGDESC

Attribute	Description
Name	MLLEGDESC
Datatype	String
Description	Indicates Multiple Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLCPTYDESC

Attribute	Description
Name	MLCPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MLSKLOCDESC

Attribute	Description
Name	MLSKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.67.4.SE-Deal-Blkreq-Reverse-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Block-Deal-Master*
      - *BLKDEALREF*
    - *Block-Deal-Master-IO*
      - *PRD*
      - *DEALREF*
      - *USERREF*
      - *SECCODE*
      - *MKTCD*
      - *TRANDT*
      - *DEALTP*
      - *QUOTBY*
      - *DEALQT*
      - *TRADEDT*
      - *INT*
      - *DELIVER*
      - *PRIQT*
      - *DSTLDT*
      - *INTDT*

REC
IPPRICE
YLD
ABSTPRICE
BLKDLSTAT
FORMAT
REMARKS
FACVALUNIT
FACVALDEAL
BRN
PRDTYPE
SECTP
SECSER
PMTCCY
RATE
SCY
SPOTPRICE
SETTLMTSK
ISMA
DEALTPADD
PRIORITY
LCYPRIC
DEALER
Singleleg-Detail
- *SLBLKDEALREF*
- *SLEXREF*
- *SLDEALREF*
- *SLBRN*
- *SLLEGPRD*
- *SLSNGMUL*
- *SLMSTLDT*
- *SLAUTOMAN*
- *SLPORFOLTID*
- *SLCPTY*
- *SLPAYACCBRN*
- *SLPAYACC*
- *SLSKLOC*
- *SLSKACC*
- *SLBROKER*
- *SLDEALQTY*
- *SLDEALIP*
- *SLABSPRICE*
- *SLYLDFORINFO*
- *SLATHSTAT*

SLDEALSTAT
SLLCYPRICE
SLRBUYSELL
MLDEALREF
MLLEGPRD
Multipleleg-Detail
MLBLKDEALREF
MLEXREF
MLDEALREF
MLBRN
MLLEGPRD
MLSNGMUL
MLMSTLDT
MLAUTOMAN
MLPORFOLTID
MLCPTY
MLPAYACCBRN
MLPAYACC
MLSKLOC
MLSKACC
MLBROKER
MLDEALQTY
MLDEALIP
MLABSPRICE
MLYLDFORINFO
MLATHSTAT
MLDEALSTAT
MLLCYPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the primary information relating the Contract that has been successfully Reversed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Block-Deal-Master

Attribute	Description
Name	Block-Deal-Master
Datatype	
Description	Includes Securities Deal Block Request Reverse Master type details

TOP

BLKDEALREF

Attribute	Description
Name	BLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Block-Deal-Master-IO

Attribute	Description
Name	Block-Deal-Master-IO
Datatype	
Description	Includes Securities Deal Block Request Reverse Input Only type details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates User Reference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECCODE

Attribute	**Description**	
Name	SECCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TRANDT

Attribute	**Description**	
Name	TRANDT	
Datatype	Date	
Description	Indicates Transaction Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEALTP

Attribute	**Description**	
Name	DEALTP	
Datatype	String	
Description	Indicates Deal Type Spot : S Forward : F	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

QUOTBY

Attribute	Description	
Name	QUOTBY	
Datatype	String	
Description	Indicates Quote By Units : U Nominal : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DEALQT

Attribute	Description	
Name	DEALQT	
Datatype	Number	
Description	Indicates Deal Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	Description	
Name	TRADEDT	
Datatype	Date	
Description	Indicates Trade Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT

Attribute	Description	
Name	INT	
Datatype	String	
Description	Indicates Interest Flat : F Plus Accrued : P	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DELIVER

Attribute	Description	
Name	DELIVER	
Datatype	String	
Description	Indicates Deliver Free : F Against Payment : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIQT

Attribute	Description	
Name	PRIQT	
Datatype	String	
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DSTLDT

Attribute	Description	
Name	DSTLDT	
Datatype	Date	
Description	Indicates DSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDT

Attribute	Description	
Name	INTDT	
Datatype	Date	
Description	Indicates Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REC

Attribute	Description
Name	REC
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IPPRICE

Attribute	Description
Name	IPPRICE
Datatype	Number
Description	Indicates Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YLD

Attribute	Description
Name	YLD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSTPRICE

Attribute	Description
Name	ABSTPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLKDLSTAT

Attribute	Description
Name	BLKDLSTAT
Datatype	String
Description	Indicates This field is internally used by GUI.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FORMAT

Attribute	Description
Name	FORMAT
Datatype	String
Description	Indicates Format Script Based : S Dematerialized : D Immobilized : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FACVALUNIT

Attribute	Description
Name	FACVALUNIT
Datatype	Number
Description	Indicates Face Value Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACVALDEAL

Attribute	Description
Name	FACVALDEAL
Datatype	Number
Description	Indicates Face Value Of Deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDTYPE

Attribute	Description
Name	PRDTYPE
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SECTP

Attribute	Description
Name	SECTP
Datatype	String
Description	Indicates Security Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECSER

Attribute	Description
Name	SECSER
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PMTCCY

Attribute	Description
Name	PMTCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRICE

Attribute	Description
Name	SPOTPRICE
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMTSK

Attribute	Description
Name	SETTLMTSK
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISMA

Attribute	Description
Name	ISMA
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DEALTPADD

Attribute	Description
Name	DEALTPADD
Datatype	String
Description	Indicates Deal Type Primary : P Secondary : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

LCYPRIC

Attribute	Description
Name	LCYPRIC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Singleleg-Detail

Attribute	Description
Name	Singleleg-Detail
Datatype	
Description	Indicates Includes Single Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SLBLKDEALREF

Attribute	Description
Name	SLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLEXREF

Attribute	Description
Name	SLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLDEALREF

Attribute	Description
Name	SLDEALREF
Datatype	String
Description	Indicates Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLBRN

Attribute	Description
Name	SLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SLLEGPRD

Attribute	Description
Name	SLLEGPRD
Datatype	String
Description	Indicates Leg Product
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SLSNGMUL

Attribute	Description
Name	SLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLMSTLDT

Attribute	**Description**	
Name	SLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLAUTOMAN

Attribute	**Description**	
Name	SLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLPORFOLTID

Attribute	**Description**	
Name	SLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLCPTY

Attribute	**Description**	
Name	SLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLPAYACCBRN

Attribute	Description	
Name	SLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SLPAYACC

Attribute	Description	
Name	SLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SLSKLOC

Attribute	Description	
Name	SLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLSKACC

Attribute	Description	
Name	SLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SLBROKER

Attribute	Description
Name	SLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLDEALQTY

Attribute	Description
Name	SLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

SLDEALIP

Attribute	Description
Name	SLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLABSPRICE

Attribute	Description
Name	SLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SLYLDFORINFO

Attribute	Description
Name	SLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLATHSTAT

Attribute	**Description**	
Name	SLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLDEALSTAT

Attribute	**Description**	
Name	SLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SLLCYPRICE

Attribute	**Description**	
Name	SLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SLRBUYSELL

Attribute	**Description**	
Name	SLRBUYSELL	
Datatype	String	
Description	Indicates BUY_SELL Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Multipleleg-Detail

Attribute	Description
Name	Multipleleg-Detail
Datatype	
Description	Indicates Includes Multiple Leg details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLBLKDEALREF

Attribute	Description
Name	MLBLKDEALREF
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLEXREF

Attribute	Description
Name	MLEXREF

Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLDEALREF

Attribute	Description
Name	MLDEALREF
Datatype	String
Description	Indicates Multiple Leg Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MLBRN

Attribute	Description
Name	MLBRN
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MLLEGPRD

Attribute	Description
Name	MLLEGPRD
Datatype	String
Description	Indicates Multiple Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

MLSNGMUL

Attribute	Description
Name	MLSNGMUL
Datatype	String
Description	Indicates Single Multiple Leg

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLMSTLDT

Attribute	Description	
Name	MLMSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLAUTOMAN

Attribute	Description	
Name	MLAUTOMAN	
Datatype	String	
Description	Indicates Auto MSTL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLPORFOLTID

Attribute	Description	
Name	MLPORFOLTID	
Datatype	String	
Description	Indicates Portfolio Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLCPTY

Attribute	Description	
Name	MLCPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MLPAYACCBRN

Attribute	Description	
Name	MLPAYACCBRN	
Datatype	String	
Description	Indicates Pay Account Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MLPAYACC

Attribute	Description	
Name	MLPAYACC	
Datatype	String	
Description	Indicates Pay Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MLSKLOC

Attribute	Description	
Name	MLSKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MLSKACC

Attribute	Description	
Name	MLSKACC	
Datatype	String	
Description	Indicates Safe keeping location account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MLBROKER

Attribute	Description
Name	MLBROKER
Datatype	String
Description	Indicates Broker
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MLDEALQTY

Attribute	Description
Name	MLDEALQTY
Datatype	Number
Description	Indicates Deal Quantity
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MLDEALIP

Attribute	Description
Name	MLDEALIP
Datatype	Number
Description	Indicates Deal Input Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLABSPRICE

Attribute	Description
Name	MLABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MLYLDFORINFO

Attribute	Description
Name	MLYLDFORINFO
Datatype	Number
Description	Indicates Yield for Information

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MLATHSTAT

Attribute	**Description**	
Name	MLATHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLDEALSTAT

Attribute	**Description**	
Name	MLDEALSTAT	
Datatype	String	
Description	Indicates Deal Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MLLCYPRICE

Attribute	**Description**	
Name	MLLCYPRICE	
Datatype	Number	
Description	Indicates Price in Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes FCUBS Error Response details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**

Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.68.CloseSEDeal

Closure of Securities Deal Input

2.68.1.SE-Deal-Close-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *REVDREFNO*
    - *MKTCD*
    - *DEALTYP*
    - *DEALQTY*
    - *TRADEDT*

PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
DEALTIME
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
LMTRACK
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
SECTYSERIES
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS
SMNTSK
CERTNO
ORGINTAMT
ORGPRICE
Contract_Event_Log
  MAKERID
  MAKERSTAMP

- *CHECKERID*
- *CHECKERSTAMP*
- *TXTCSTAT*
- *CONTSTAT*
- *AUTHSTAT*

Deal-Detail

- *FCCREF*
- *XREF*
- *PRD*
- *DEALREFNO*
- *LGPRDCODE*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGUSERREF*
- *LEG_REFERNCENO*
- *LGDESC*
- *SKLOCDESCTO*
- *BUYSELL*
- *Deal-Limits-To*
  - *LEGREF*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Deal-Walkin-To*
  - *LEGREF*
- *CONTRACT1*
  - *FCCREF*
  - *VERNO*
  - *PREVVERNO*
  - *Settlement-Addl-Details*
    - *ACCBRN*
    - *ACC_CCY*
    - *ACC*
    - *AMTTAG*
    - *CUSTSPRD*
    - *ERIAMT*
    - *ERICCY*
    - *XRATE*

GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*

INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1

ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*

ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4

ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1

ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP

AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3

- *ADDRLINE4*
- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
  - *CPTY*
- *CONTRACT*
  - *FCCREF*
  - *BRKDETAILS*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*

LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP

CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10

COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5

TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4

COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9

TXNMIS10LBL10

Settlement-Details

AMTTAG

TRNTPCD

BNKOPRCD

REGREP1

REGREP2

REGREP3

ENV_CONT1

ENV_CONT2

ENV_CONT3

ENV_CONT4

ENV_CONT5

TIMEIND1

TIMEIND2

TIMEIND3

INSTRCDLT

INSTRCDLT1

INSTRCDLT2

INSTRCDLT3

INSTRCDLT4

INSTRCDLT5

INSTRCDTXT

INSTRCDTXT1

INSTRCDTXT2

INSTRCDTXT3

INSTRCDTXT4

INSTRCDTXT5

AMTTAG

TRNTPCD

BNKOPRCD

REGREP1

REGREP2

REGREP3

ENV_CONT1

ENV_CONT2

ENV_CONT3

ENV_CONT4

ENV_CONT5

TIMEIND1

TIMEIND2

TIMEIND3

INSTRCDLT

INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG

- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*

DEAL_MESSAGES

- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*
- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*

- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*

SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY

TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail-To
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5

BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1

- *RCVR_CORRESP2*
- *RCVR_CORRESP3*
- *RCVR_CORRESP4*
- *RCVR_CORRESP5*
- *RCVR_CORRESP6*
- *RECEIVER*
- *RTGSNW*
- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE

INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4

SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2

PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN

COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO

- *CERTQT*
- *DEAL_LIMITS*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*
- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
  - *CPTY*
- *CONTRACT*
  - *FCCREF*
  - *BRKDETAILS*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*

RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN

RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF

LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4

- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*
- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*

DEAL_PARTIES

- *LEGREF*
- *PTYPE*
- *ADDR1*
- *ADDR2*
- *ADDR3*
- *ADDR4*
- *LEGREF*
- *PTYPE*
- *ADDR1*
- *ADDR2*
- *ADDR3*
- *ADDR4*

DEAL_NETCONS

- *LEGREF*
- *BUYSEL*

COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE

WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full request for SE Deal Contract Close operation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Closure of Securities Deal Input Master Type.

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Latest Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	**Restrictions** / **Description** maxLength / 15 pattern / [a-zA-Z0-9]*

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates Reversed Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates Local Currency Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates Original DSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALTIME

Attribute	Description

Name	DEALTIME
Datatype	Date
Description	Indicates Deal Input Time

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates Spot Interest Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates Spot Price

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT

Attribute	**Description**	
Name	DISCOUNT	
Datatype	Number	
Description	Indicates Discount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREMIUM

Attribute	**Description**	
Name	PREMIUM	
Datatype	Number	
Description	Indicates Premium	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORWDPL

Attribute	**Description**	
Name	FORWDPL	
Datatype	Number	
Description	Indicates Forward P and L	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FACEDEAL

Attribute	**Description**	
Name	FACEDEAL	
Datatype	Number	
Description	Indicates Deal Nominal	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADJDEALPRC

Attribute	**Description**	
Name	ADJDEALPRC	
Datatype	Number	
Description	Indicates Adjusted Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates Actual DSTL Date

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LMTRACK

Attribute	Description
Name	LMTRACK
Datatype	String
Description	Indicates whether limit tracking is required or not Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RATEPCYSCY

Attribute	**Description**	
Name	RATEPCYSCY	
Datatype	String	
Description	Indicates Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

SECSTTLMENT

Attribute	**Description**	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates Settlement SKL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	16
	pattern	[a-zA-Z0-9]{16}

TOP

SPOTDT

Attribute	**Description**	
Name	SPOTDT	
Datatype	Date	
Description	Indicates Spot Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYSERIES

Attribute	**Description**	
Name	SECTYSERIES	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 30 minLength: 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates Placement/Loan Reference
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 16 pattern: [a-zA-Z0-9]{16}

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,S

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	Number

Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 255 pattern / [a-zA-Z0-9]{255}

TOP

SMNTSK

Attribute	Description
Name	SMNTSK
Datatype	String
Description	Indicates Safe Keeping Location (Sk Loc) for the market
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

ORGINTAMT

Attribute	Description
Name	ORGINTAMT
Datatype	Number
Description	Indicates Original Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGPRICE

Attribute	Description
Name	ORGPRICE
Datatype	Number
Description	Indicates Original Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract_Event_Log

Attribute	Description
Name	Contract_Event_Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description
Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes Deal details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates Safe Keeping To Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACCTO

Attribute	**Description**
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates Auto MSTL A for On; M for Off	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description	Indicates Leg User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To

Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number

Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String

Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	Description	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	Description	
Name	ORDER_INST5	
Datatype	String	
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description	
Name	AMTCCY	
Datatype	Number	
Description	Indicates Amount Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description	
Name	AMTPCY	
Datatype	Number	
Description	Indicates Amount In Payment Currency	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	**Description**
Name	ADDRLINE3

Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

CONTRACT

Attribute	**Description**	
Name	CONTRACT	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	**Description**	
Name	BRKDETAILS	
Datatype		
Description	Includes Broker details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description

Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description

Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description

Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDTLS

Attribute	**Description**	
Name	PARTYDTLS	
Datatype		
Description	Includes Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	**Description**	
Name	SNDRINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP

Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYCCY

Attribute	**Description**	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	**Description**	
Name	AMTPCY	
Datatype	Number	
Description	Indicates Amount In Payment Currency	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SIGN

Attribute	**Description**	
Name	SIGN	
Datatype	String	
Description	Indicates Sign (+/-)	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPDESC

Attribute	**Description**

Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description

Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates Safe Keeping To Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACCTO

Attribute	**Description**
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates Auto MSTL A for On; M for Off	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description	Indicates Leg User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To

Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number

Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String

Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	Description	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	**Description**	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	Attribute: minOccurs; Description: 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	Attribute: minOccurs; Description: 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	Attribute: minOccurs; Description: 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	Attribute: minOccurs; Description: 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	Attribute: minOccurs; Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	Attribute: minOccurs; Description: 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	Attribute: minOccurs; Description: 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	Attribute: minOccurs; Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	Attribute: minOccurs; Description: 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	**Description**
Name	ADDRLINE3

Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description

Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description

Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{2}</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z]</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description

Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDTLS

Attribute	**Description**	
Name	PARTYDTLS	
Datatype		
Description	Includes Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	**Description**	
Name	SNDRINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP

Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYCCY

Attribute	**Description**	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	**Description**	
Name	AMTPCY	
Datatype	Number	
Description	Indicates Amount In Payment Currency	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SIGN

Attribute	**Description**	
Name	SIGN	
Datatype	String	
Description	Indicates Sign (+/-)	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPDESC

Attribute	**Description**

Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description

Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

2.68.2.SE-Deal-Close-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *XREF*
    - *VERNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only request for SE Deal contract Close operation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Closure of Securities Deal Input Master Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.68.3.SE-Deal-Close-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREF*
    - *DEALREFNO*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *REVDREFNO*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALTYP*
    - *DEALQTY*
    - *TRADEDT*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
LMTRACK
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
SECTYSERIES
BAREF
PRIORITY
DEALER
ISMAIND
REMARKS
SMNTSK
CERTNO
ORGINTAMT
ORGPRICE
FORM
DEALTYPE

PRODDESC
PRDTYP
LCCY
YIELDEC
Deal-Detail-To
- *FCCREF*
- *XREF*
- *PRD*
- *DEALREFNO*
- *LGPRDCODE*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGUSERREF*
- *LEG_REFERNCENO*
- *LGDESC*
- *SKLOCDESCTO*
- *BUYSELL*
- *Deal-Limits-To*
  - *LEGREF*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Deal-Walkin-To*
  - *LEGREF*
- *CONTRACT1*
  - *FCCREF*
  - *VERNO*
  - *PREVVERNO*
  - *Settlement-Addl-Details*
    - *ACCBRN*
    - *ACC_CCY*
    - *ACC*
    - *AMTTAG*
    - *CUSTSPRD*
    - *ERIAMT*
    - *ERICCY*
    - *XRATE*
    - *GENMSG*

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME

IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1

- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3

INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6

- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

Deal-Messages

- *LEGREF*
- *VERSION*
- *MSG*
- *ADVDESC*
- *PARTYID*
- *PARTYNAME*
- *Deal-Parties*
  - *PTY*
  - *ADD1*
  - *ADD2*
  - *PTY*
  - *ADD1*
  - *ADD2*
- *LEGREF*
- *VERSION*
- *MSG*
- *ADVDESC*
- *PARTYID*
- *PARTYNAME*
- *Deal-Parties*
  - *PTY*
  - *ADD1*
  - *ADD2*
  - *PTY*
  - *ADD1*
  - *ADD2*

Deal-Netcons

- *LEGREF*
- *BUYSEL*
- *COMPTYP*
- *COMP*
- *AMTTAG*

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY

AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4

- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
  - *CPTY*
- *CONTRACT*
  - *FCCREF*
  - *BRKDETAILS*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*

LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP
CHGCCY

CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*
- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT

MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3

- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*
  - *SIGN*

COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT

WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE

WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET

CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3

- *RCVR_CORRESP4*
- *RCVR_CORRESP5*
- *RCVR_CORRESP6*
- *RECEIVER*
- *RTGSNW*
- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*
- *INTMEDRY3*
- *INTMEDRY4*

INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC

DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2

INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6

TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1

ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS

CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC

SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6

AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6

ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3

ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch

LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
DEAL_WALKIN
LEGREF
UNEXPOSURE
TOTEXPOSURE
CLEANRISKLIMIT
PSTLRISKLIMIT
CPTY
CONTRACT
FCCREF
BRKDETAILS
FCCREF

- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*

MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION

- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*
- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*
  - *SIGN*
  - *COMPDESC*
  - *INTDAYS*
  - *CUMEX*
- *DEAL_LIMITS1*
  - *LEGREF*
  - *CLEANRISKLIMIT*

- PSTLRISKLIMIT
- DEAL_WALKIN1
  - LEGREF
  - UNMATCHED
- Tax-Master
  - TXTREF
  - Tran-Tax-Assoc
    - CRRATESN
    - INTCOMP
    - RULE
    - WAIVER
    - CONTREF
  - Tran-Tax-Appln
    - CRRATESN
    - INTCOMP
    - TAGCCY
    - TAGAMNT
    - TAXCCY
    - TAXAMNT
    - WAIVER
    - LIQINDICAT
    - CONTREF
- DEAL_CERTIFICATE_DETAILS
  - FCCREF
  - DEALREF
  - CERTNO
  - CERTQT
- CONTRACT
  - FCCREF
  - BRKDETAILS
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT

LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6

FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10

- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*

INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF

PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2

ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
SKLOCTO
SKACCTO
Ytm-Master
DEALREF
DEALREFNO
EFFDT
YTM

Contract-Event-Log

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

TXTCSTAT

CONTSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Screen Response for SE Deal Contract Close operation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Closure of Securities Deal Input Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Block Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SRC

Attribute	Description	
Name	SRC	
Datatype	String	
Description	Indicates Source	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	pattern	[a-zA-Z0-9]*

TOP

SECTYCD

Attribute	Description	
Name	SECTYCD	
Datatype	String	
Description	Indicates Security Code	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

REVDREFNO

Attribute	Description	
Name	REVDREFNO	
Datatype	String	
Description	Indicates Reversed Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

MKTCD

Attribute	Description	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50 minLength / 0

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	**Restrictions** / **Description** enumeration / S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates Local Currency Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates Original DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates Transaction Date
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates Spot Interest Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates Discount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates Premium
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

FORWDPL

Attribute	Description
Name	FORWDPL

Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates Actual DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LMTRACK

Attribute	Description
Name	LMTRACK
Datatype	String
Description	Indicates whether limit tracking is required or not Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 16 pattern / [a-zA-Z0-9]{16}

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates Placement/Loan Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 16 pattern / [a-zA-Z0-9]{16}

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3

TOP

DEALER

Attribute	Description	
Name	DEALER	
Datatype	Number	
Description	Indicates Dealer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISMAIND

Attribute	Description	
Name	ISMAIND	
Datatype	String	
Description	Indicates Conforms to ISMA Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	255
	pattern	[a-zA-Z0-9]{255}

TOP

SMNTSK

Attribute	Description	
Name	SMNTSK	
Datatype	String	
Description	Indicates Safe Keeping Location (Sk Loc) for the market	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

ORGINTAMT

Attribute	Description
Name	ORGINTAMT
Datatype	Number
Description	Indicates Original Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGPRICE

Attribute	Description
Name	ORGPRICE
Datatype	Number
Description	Indicates Original Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z]

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

LCCY

Attribute	Description
Name	LCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

YIELDEC

Attribute	Description
Name	YIELDEC
Datatype	Number
Description	Indicates Yield For Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description

Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Deal-Walkin-To

Attribute	**Description**	
Name	Deal-Walkin-To	
Datatype		
Description	Includes Deal Walkin To details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	Description	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	Description	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	Description	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4

Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE

Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 0; pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3; minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description	
Name	BRKDETAILS	
Datatype		
Description	Includes Broker details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

BROKER

Attribute	Description	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description

Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description

Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String

Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	Attribute: minOccurs; Description: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 15 Restrictions: minInclusive; Description: 0 Restrictions: totalDigits; Description: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

REFXRT

Attribute	Description

Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12
minLength	1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16
minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description

Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4

Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT3

Attribute	**Description**	
Name	INSTRCDTXT3	
Datatype	String	
Description	Indicates the Instruction Code Text3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description

Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description

Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES

Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3

Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String

Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEAL_WALKIN1

Attribute	**Description**	
Name	DEAL_WALKIN1	
Datatype		
Description	Includes Deal Walkin details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description

Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	**Description**	
Name	LEG_REFERNCENO	
Datatype	String	
Description	Indicates Leg User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LGDESC

Attribute	**Description**	
Name	LGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	**Description**	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	**Description**	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	**Description**	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT

Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6

Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST1

Attribute	**Description**	
Name	ORDER_CUST1	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST2

Attribute	**Description**	
Name	ORDER_CUST2	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String

Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6

Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST1

Attribute	**Description**	
Name	ORDER_CUST1	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST2

Attribute	**Description**	
Name	ORDER_CUST2	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String

Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**
Name	TAG_CCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	**Description**	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	**Description**
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2

Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	**Description**	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	**Description**
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description

Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description

Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String

Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

BRKID

Attribute	Description	
Name	BRKID	
Datatype	String	
Description	Indicates Broker Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGUSERREF

Attribute	Description	
Name	LEGUSERREF	
Datatype	String	
Description	Indicates Leg User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	Description	
Name	LEG_REFERNCENO	
Datatype	String	
Description	Indicates Leg User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LGDESC

Attribute	Description	
Name	LGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SKLOCDESCTO

Attribute	Description	
Name	SKLOCDESCTO	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

PREVVERNO

Attribute	Description	
Name	PREVVERNO	
Datatype	Number	
Description	Indicates Previous Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	**Description**	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	**Description**
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>BS,CS,WI,BB,CB,LG</td></tr></table>

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String

Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	**Description**	
Name	INTDAYS	
Datatype	Number	
Description	Indicates Interest Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	**Description**	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Unrel-Unmatch

Attribute	**Description**	
Name	Unrel-Unmatch	
Datatype		
Description	Includes Unrel Unmatch details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNMATCHED

Attribute	**Description**
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKID

Attribute	**Description**	
Name	BRKID	
Datatype	String	
Description	Indicates Broker Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

MSTLDT

Attribute	**Description**	
Name	MSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGMSTLDT

Attribute	**Description**	
Name	ORGMSTLDT	
Datatype	Date	
Description	Indicates Actual MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	**Description**	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK

Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN

Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30
minLength	0

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF

Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String

Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	**Description**	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_NETCONS

Attribute	Description	
Name	DEAL_NETCONS	
Datatype		
Description	Includes Deal Net cons details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description

Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	

Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description	
Name	CERTNO	
Datatype	String	
Description	Indicates Certificate Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0

TOP

CERTQT

Attribute	Description	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT

Attribute	Description	
Name	CONTRACT	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1 pattern: [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2LBL2

Attribute	Description	
Name	TXNMIS2LBL2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3LBL3

Attribute	Description	
Name	TXNMIS3LBL3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4LBL4

Attribute	Description	
Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	Description	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	Description	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	Description	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description

Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log

Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description

Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.68.4.SE-Deal-Close-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-PK*
      - *FCCREF*
      - *XREF*
      - *VERNO*
    - *Deal-Master*
      - *FCCREF*
      - *XREF*
      - *VERNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key Response for SE Deal Contract Close operation

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-PK

Attribute	Description
Name	Deal-PK
Datatype	
Description	Closure of Securities Deal Input PK Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Closure of Securities Deal Input Master Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.69.ConfirmSEDeal

Confirmation of Securities Deal Input

2.69.1.SE-Deal-Confirm-Req-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Confirm*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALTYP*
    - *DEALQTY*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
PAYCCY
SCCY
RATEPCYSCY
SPOTDT
FORM
DEALTYPE
ISMAIND
PRODDESC
PRDTYP
CPTYCONFREF
CPTYCONFDT
CPTYCONFREM
CONFTYPE
LEGTYPE
LEGREFFROM
LEGREFTO
LEGUREFFROM
LEGUREFTO
TRADEDT
SETTLMNTDT
UNITS
Deal-Detail-To

FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*
- *INTMEDRY3*
- *INTMEDRY4*

INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC

DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2

INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6

- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*

BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4

ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2

ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2

ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG

BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY

SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN

- *COMPDESC*
- *INTDAYS*
- *CUMEX*
- *Unrel-Unmatch*
  - *LEGREF*
  - *UNMATCHED*
  - *LEGREF*
  - *UNMATCHED*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *SKLOCDESC*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *SCLNRISKLMTRK*
- *SPSTLRISKLMTRK*
- *TOTEXPLINE*
- *UNDEXPLINE*
- *PAYBRN*
- *PAYACC*
- *ACTMSTLDT*
- *DEAL_CERTIFICATE_DETAILS*
  - *FCCREF*
  - *DEALREF*
  - *CERTNO*
  - *CERTQT*
- *DEAL_LIMITS*
  - *LEGREF*
  - *WALKINNAME*
  - *WALKINMEDIA*
  - *ADDRLINE1*
  - *ADDRLINE2*
  - *ADDRLINE3*
  - *ADDRLINE4*
- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*

- PSTLRISKLIMIT
- CPTY
- CONTRACT
  - FCCREF
  - BRKDETAILS
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT
      - LREFNO
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT
      - LREFNO
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT
      - LREFNO
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT

LREFNO

Charge-Application

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

CHGCOMP

CRNESN

TGCCY

TGAMT

CHGCCY

CHGAMT

WAIVER

LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

ESN

CHGCOMP

CHGCCY

CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP

CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH

CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1

TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1

REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1

INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED

DEALQTY

DEAL_MESSAGES

FCCREF

LEGREF

VERSION

MSG

PARTYID

PARTYNAME

SNDRINFO1

SNDRINFO2

SNDRINFO3

SNDRINFO4

SNDRINFO5

SNDRINFO6

ADDLINFO1

ADDLINFO2

ADDLINFO3

PARTYDTLS

LEGREF

PTYPE

ADDR1

ADDR2

ADDR3

ADDR4

LEGREF

PTYPE

ADDR1

ADDR2

ADDR3

ADDR4

FCCREF

LEGREF

VERSION

MSG

PARTYID

PARTYNAME

SNDRINFO1

SNDRINFO2

SNDRINFO3

SNDRINFO4

SNDRINFO5

SNDRINFO6

ADDLINFO1

ADDLINFO2

ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL

COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP

TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE

WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*

INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP

ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC

XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW

- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*

ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3

ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD

ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1

INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4

ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP

COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP

AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL

LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6
      AGRID
      AMTTAG
      BNKPRIO
      BNFINSTCVR1
      BNFINSTCVR2

BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5

ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION

MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT

CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
  FCCREF
  DEALREF
  CERTNO
  CERTQT
DEAL_LIMITS
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4
DEAL_WALKIN
  LEGREF
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
  CPTY
CONTRACT
  FCCREF
  BRKDETAILS
    FCCREF
    ESN
    BROKER
    BRKAMT
    BRKCCY
    RULE

- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*

CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10

FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2

TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2

- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*
  - *SIGN*
  - *COMPDESC*
  - *INTDAYS*
  - *CUMEX*
- *DEAL_LIMITS1*
  - *LEGREF*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *DEAL_WALKIN1*
  - *LEGREF*
  - *UNMATCHED*
- *Tax-Master*

- *TXTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*

DEAL_CERTIFICATE_DETAILS

- *FCCREF*
- *DEALREF*
- *CERTNO*
- *CERTQT*

CONTRACT

- *FCCREF*
- *BRKDETAILS*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*

LREFNO
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE

WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7

FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1

COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP

COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5

COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD

- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*
- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

SECUDF

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*
- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Sevws-Matched-Deal

- *FCCREF*

VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4

LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1

ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
SKLOCTO
SKACCTO
Ytm-Master
DEALREF
DEALREFNO
EFFDT
YTM
Contract-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP

TXTCSTAT

CONTSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for request of SE Deal contract confirmation

TOP

Contract-Confirm

Attribute	Description
Name	Contract-Confirm
Datatype	
Description	Confirmation of Securities Deal Input

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	Restrictions: pattern — Description: [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	

Restrictions	Description
length	4
pattern	[a-zA-Z0-9]{4}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	

Restrictions	Description
totalDigits	4

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Latest Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code

Restrictions	

Restrictions	Description
maxLength	16
minLength	0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Restrictions	

Restrictions	Description
maxLength	16
minLength	0

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Restrictions	

Restrictions	Description
maxLength	105
minLength	0

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Restrictions	

Restrictions	Description
maxLength	105
minLength	0

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	

Restrictions	Description
enumeration	S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date

Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P

TOP

SPOTINTVALDT

Attribute	**Description**	
Name	SPOTINTVALDT	
Datatype	Date	
Description	Indicates Spot Interest Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPOTPRC

Attribute	**Description**	
Name	SPOTPRC	
Datatype	Number	
Description	Indicates Spot Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT

Attribute	**Description**	
Name	DISCOUNT	
Datatype	Number	
Description	Indicates Discount	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREMIUM

Attribute	**Description**	
Name	PREMIUM	
Datatype	Number	
Description	Indicates Premium	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FORWDPL

Attribute	**Description**
Name	FORWDPL

Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYCONFREF

Attribute	Description
Name	CPTYCONFREF
Datatype	String
Description	Indicates Counterparty Confirmation Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYCONFDT

Attribute	Description
Name	CPTYCONFDT
Datatype	Date
Description	Indicates Counterparty Confirmation Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYCONFREM

Attribute	Description	
Name	CPTYCONFREM	
Datatype	String	
Description	Indicates Counterparty Confirmation Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFTYPE

Attribute	Description	
Name	CONFTYPE	
Datatype	String	
Description	Indicates Type of Confirmation Delivery : D Counterparty : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

LEGTYPE

Attribute	Description	
Name	LEGTYPE	
Datatype	String	
Description	Indicates Leg Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S

TOP

LEGREFFROM

Attribute	Description	
Name	LEGREFFROM	
Datatype	String	
Description	Indicates From Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates To Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUREFFROM

Attribute	Description
Name	LEGUREFFROM
Datatype	String
Description	Indicates From Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUREFTO

Attribute	Description
Name	LEGUREFTO
Datatype	String
Description	Indicates To Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTLMNTDT

Attribute	Description
Name	SETTLMNTDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description

Name	UNITS
Datatype	Number
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description

Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LGDESC

Attribute	Description	
Name	LGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SKLOCDESCTO

Attribute	Description	
Name	SKLOCDESCTO	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSELL

Attribute	Description	
Name	BUYSELL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description	
Name	Deal-Limits-To	
Datatype		
Description	Includes Deal To Limits	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF

Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	**Description**
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1; pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1; pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1; pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	9
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4

Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE

Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 0; pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3; minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details

Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN

Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description

Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	**Description**	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1 pattern: [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	**Description**

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	Attribute: minOccurs — Description: 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	Restrictions: maxLength — Description: 15 Restrictions: minLength — Description: 0 Restrictions: pattern — Description: [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description

Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTREF

Attribute	**Description**	
Name	TXTREF	
Datatype	String	
Description	Indicates Text Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	**Description**	
Name	Tran-Tax-Assoc	
Datatype		
Description	Includes Transaction Tax Association details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**
Name	RULE

Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**
Name	TAXCCY

Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description

Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Deal-Walkin-To

Attribute	**Description**	
Name	Deal-Walkin-To	
Datatype		
Description	Includes Deal Walkin To details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	Description	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String

Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 0; pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs: 2 minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String

Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,A</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	

Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	**Description**	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	Description	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	Description	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	Description	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	Description	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	Description	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description**: maxLength / 25; minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description

Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	

Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description	
Name	SCLNRISKLMTRK	
Datatype	String	
Description	Indicates Track Clean Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description	
Name	SPSTLRISKLMTRK	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TOTEXPLINE

Attribute	Description	
Name	TOTEXPLINE	
Datatype	String	
Description	Indicates Total Exposure Line	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 0 pattern: [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 0 pattern: [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3 minLength: 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	**Description**	
Name	DEAL_CERTIFICATE_DETAILS	
Datatype		
Description	Includes Deal Certificate details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	**Description**
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	**Description**	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	

Attribute	Description
minOccurs	0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	9
minLength	1
pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10
minLength	1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

BRKNAM

Attribute	**Description**	
Name	BRKNAM	
Datatype	String	
Description	Indicates Broker name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	**Description**	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	Attribute: minOccurs; Description: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: fractionDigits; Description: 15 Restrictions: minInclusive; Description: 0 Restrictions: totalDigits; Description: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

REFXRT

Attribute	Description

Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1

Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2

Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1

Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Sevws-Matched-Deal

Attribute	Description	
Name	Sevws-Matched-Deal	
Datatype		
Description	Includes Matched deal details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE

Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LIQSTAT

Attribute	Description

Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT

Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6

Attribute	**Description**

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Regulatory Report 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String
Description	Regulatory Report 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	**Description**	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT

Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SCHEME

Attribute	Description	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	**Description**	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGTYPE

Attribute	**Description**	
Name	LEGTYPE	
Datatype	String	
Description	Indicates Leg Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S

TOP

UNMATCHED

Attribute	**Description**	
Name	UNMATCHED	
Datatype	Number	
Description	Indicates Total Remaining	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTMATCHED

Attribute	**Description**	
Name	TOTMATCHED	
Datatype	String	
Description	Indicates Total Matched	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z]

TOP

DEALQTY

Attribute	**Description**
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description	
Name	PARTYDTLS	
Datatype		
Description	Includes Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description

Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String

Description	Indicates Party Type
Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	

Attribute	Description
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	Attribute: minOccurs; Description: 0

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16 Restrictions: minLength; Description: 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20 Restrictions: pattern; Description: [a-zA-Z0-9]*

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	Attribute: maxOccurs; Description: 2 Attribute: minOccurs; Description: 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXTCSTAT

Attribute	Description
Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

2.69.2.SE-Deal-Confirm-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Confirm*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALTYP*
    - *DEALQTY*
    - *PRCTYPE*
    - *DLVRFREEPAY*
    - *PRCQUOTE*
    - *DSTLDT*

INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
PAYCCY
SCCY
RATEPCYSCY
SPOTDT
FORM
DEALTYPE
ISMAIND
PRODDESC
PRDTYP
CPTYCONFREF
CPTYCONFDT
CPTYCONFREM
CONFTYPE
LEGTYPE
LEGREFFROM
LEGREFTO
LEGUREFFROM
LEGUREFTO
TRADEDT
SETTLMNTDT
UNITS
Deal-Detail-To
- *FCCREF*
- *XREF*
- *PRD*

DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1

ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1

ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN

WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

Deal-Messages

- *LEGREF*
- *VERSION*
- *MSG*
- *ADVDESC*
- *PARTYID*
- *PARTYNAME*
- *Deal-Parties*
  - *PTY*
  - *ADD1*
  - *ADD2*
  - *PTY*
  - *ADD1*
  - *ADD2*
- *LEGREF*
- *VERSION*
- *MSG*
- *ADVDESC*
- *PARTYID*
- *PARTYNAME*
- *Deal-Parties*
  - *PTY*
  - *ADD1*
  - *ADD2*
  - *PTY*
  - *ADD1*
  - *ADD2*

Deal-Netcons

- *LEGREF*
- *BUYSEL*
- *COMPTYP*
- *COMP*
- *AMTTAG*
- *COMPCCY*
- *AMTCCY*
- *PAYCCY*
- *RATE*
- *AMTPCY*
- *SIGN*
- *COMPDESC*
- *INTDAYS*

CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX

Unrel-Unmatch

LEGREF

UNMATCHED

LEGREF

UNMATCHED

BRKID

MSTLDT

ORGMSTLDT

CPTYDESC

SKLOCDESC

WALKINNAME

WALKINMEDIA

ADDRLINE1

ADDRLINE2

ADDRLINE3

ADDRLINE4

SCLNRISKLMTRK

SPSTLRISKLMTRK

TOTEXPLINE

UNDEXPLINE

PAYBRN

PAYACC

ACTMSTLDT

DEAL_CERTIFICATE_DETAILS

FCCREF

DEALREF

CERTNO

CERTQT

DEAL_LIMITS

LEGREF

WALKINNAME

WALKINMEDIA

ADDRLINE1

ADDRLINE2

ADDRLINE3

ADDRLINE4

DEAL_WALKIN

LEGREF

UNEXPOSURE

TOTEXPOSURE

CLEANRISKLIMIT

PSTLRISKLIMIT

CPTY

CONTRACT

FCCREF

BRKDETAILS

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Charge-Application

- *CHGCOMP*

CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF

REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1

ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4

INSTRCDTXT5

Taxdetails-Main

SCHEME

WAIVER

SCHEMEDESC

SCHEME

WAIVER

SCHEMEDESC

SECUDF

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Sevws-Matched-Deal

FCCREF

VER

BUYLEG

SELLEG

DSTLDT

MATCH

LEGREF

LEGTYPE

UNMATCHED

TOTMATCHED

DEALQTY

FCCREF

VER

BUYLEG

SELLEG

DSTLDT

MATCH

LEGREF

LEGTYPE

UNMATCHED

TOTMATCHED

DEALQTY

DEAL_MESSAGES

FCCREF

LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
  LEGREF
  PTYPE
  ADDR1
  ADDR2
  ADDR3
  ADDR4
  LEGREF
  PTYPE
  ADDR1
  ADDR2
  ADDR3
  ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
  LEGREF

PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY

TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln

CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*

INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3

ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*

AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6

ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3

ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4

INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC

DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY

AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY

PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO

LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6
      AGRID
      AMTTAG
      BNKPRIO
      BNFINSTCVR1
      BNFINSTCVR2
      BNFINSTCVR3
      BNFINSTCVR4
      BNFINSTCVR5

BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY

PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID

PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME

WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
  FCCREF
  DEALREF
  CERTNO
  CERTQT
DEAL_LIMITS
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4
DEAL_WALKIN
  LEGREF
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
  CPTY
CONTRACT
  FCCREF
  BRKDETAILS
    FCCREF
    ESN
    BROKER
    BRKAMT
    BRKCCY
    RULE
    DSCACR
    BRKNAM
    RULEDESC

- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *Charge-Application*
  - *CHGCOMP*
  - *CRNESN*
  - *TGCCY*
  - *TGAMT*
  - *CHGCCY*
  - *CHGAMT*
  - *WAIVER*
  - *LIQINTR*
  - *DISACR*
- *Charge-Association*
  - *CHGCOMP*
  - *CRNESN*
  - *RULE*
  - *WAIVER*
  - *DISACR*
  - *ACCREQ*
  - *CHGDESC*
- *Charge-Liquidation*
  - *ESN*
  - *CHGCOMP*
  - *CHGCCY*
  - *CHGAMT*
  - *LQDSTS*
- *Mis-Details*
  - *BRANCH*
  - *CUSTNO*
  - *MISGRP*
  - *REL_REF*
  - *REL_ACC*
  - *MISHD*
  - *POOLCD*
  - *REFRT*
  - *REFRTTYPE*
  - *REFXRT*
  - *CALCMETH*
  - *MISGRPTXN*
  - *REFRTCD*

REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3

FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5

SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN

INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
CONTRACT
FCCREF
BRKDETAILS
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
FCCREF
ESN

- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *Charge-Application*
  - *CHGCOMP*
  - *CRNESN*
  - *TGCCY*
  - *TGAMT*
  - *CHGCCY*
  - *CHGAMT*
  - *WAIVER*
  - *LIQINTR*
  - *DISACR*
  - *CHGCOMP*
  - *CRNESN*
  - *TGCCY*
  - *TGAMT*
  - *CHGCCY*
  - *CHGAMT*
  - *WAIVER*
  - *LIQINTR*
  - *DISACR*
- *Charge-Association*
  - *CHGCOMP*
  - *CRNESN*
  - *RULE*
  - *WAIVER*
  - *DISACR*
  - *ACCREQ*

CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10

MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4

COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2

- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*
- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

SECUDF

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*
- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Sevws-Matched-Deal

- *FCCREF*
- *VER*
- *BUYLEG*
- *SELLEG*

- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*
- *FCCREF*
- *VER*
- *BUYLEG*
- *SELLEG*
- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*

DEAL_MESSAGES

- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*
- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*

ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4

DEAL_NETCONS

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX

SKLOCTO

SKACCTO

Ytm-Master

DEALREF

DEALREFNO

EFFDT

YTM

Contract-Event-Log

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

TXTCSTAT

CONTSTAT

AUTHSTAT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for request of SE Deal contract confirmation

TOP

Contract-Confirm

Attribute	Description
Name	Contract-Confirm
Datatype	
Description	Confirmation of Securities Deal Input

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Latest Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String

Description	Indicates Market Code
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	**Restrictions** / **Description** enumeration / S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String

Description	Indicates Interest Flat : F Plus Accured : P
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates Spot Interest Value Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates Discount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates Premium
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,S</td></tr></table>

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYCONFREF

Attribute	Description
Name	CPTYCONFREF
Datatype	String
Description	Indicates Counterparty Confirmation Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYCONFDT

Attribute	Description
Name	CPTYCONFDT
Datatype	Date
Description	Indicates Counterparty Confirmation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYCONFREM

Attribute	Description
Name	CPTYCONFREM
Datatype	String
Description	Indicates Counterparty Confirmation Remarks
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFTYPE

Attribute	Description
Name	CONFTYPE
Datatype	String
Description	Indicates Type of Confirmation Delivery : D Counterparty : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

LEGREFFROM

Attribute	Description
Name	LEGREFFROM
Datatype	String
Description	Indicates From Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates To Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUREFFROM

Attribute	Description
Name	LEGUREFFROM

Datatype	String
Description	Indicates From Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUREFTO

Attribute	Description
Name	LEGUREFTO
Datatype	String
Description	Indicates To Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMNTDT

Attribute	Description
Name	SETTLMNTDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

PRD

Attribute	**Description**	
Name	PRD	
Datatype	String	
Description	Indicates Product Code	
Restrictions	**Restrictions**	**Description**
	length	4
	pattern	[a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	**Description**	
Name	DEALREFNO	
Datatype	String	
Description	Indicates Block Deal Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	

Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String

Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description	
Name	BNKPRIO	
Datatype	String	
Description	Indicates Banking Priority	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

BNFINSTCVR1

Attribute	Description	
Name	BNFINSTCVR1	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	Description	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	Description	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**
Name	ACC_INST1
Datatype	String

Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description**: maxLength / 25; minLength / 1

TOP

BNKPRIO

Attribute	Description	
Name	BNKPRIO	
Datatype	String	
Description	Indicates Banking Priority	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1

TOP

BNFINSTCVR1

Attribute	Description	
Name	BNFINSTCVR1	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	Description	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	Description	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	Indicates Party Identification

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	**Description**	
Name	Deal-Parties	
Datatype		
Description	Includes Deal Parties details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PTY

Attribute	**Description**	
Name	PTY	
Datatype	String	
Description	Indicates Party	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADD1

Attribute	**Description**	
Name	ADD1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADD2

Attribute	**Description**
Name	ADD2
Datatype	String
Description	Indicates Address 2

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTY

Attribute	**Description**	
Name	PTY	
Datatype	String	
Description	Indicates Party	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADD1

Attribute	**Description**	
Name	ADD1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADD2

Attribute	**Description**	
Name	ADD2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description	
Name	Deal-Parties	
Datatype		
Description	Includes Deal Parties details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP

Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	**Description**	
Name	INTDAYS	
Datatype	Number	
Description	Indicates Interest Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	**Description**	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String

Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 3 minLength: 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	

Attribute	Description
minOccurs	0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String

Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 0; pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1; pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT

Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description	
Name	ACCREQ	
Datatype	String	
Description	Indicates the Accrual required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CHGDESC

Attribute	Description	
Name	CHGDESC	
Datatype	String	
Description	The Charge Component Code description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Charge-Liquidation

Attribute	Description	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

CHGCOMP

Attribute	Description

Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_REF

Attribute	Description
Name	REL_REF

Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	**Description**	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	**Description**	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	**Description**	
Name	MISHD	
Datatype	String	
Description	Indicates The MIS Head.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 15 minInclusive: 0 totalDigits: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2000
minLength	1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4

Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description

Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description	
Name	PARTYDTLS	
Datatype		
Description	Includes Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description

Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String

Description	Indicates Party Type
Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	

Attribute	Description
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	**Description**	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT

Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLDT

Attribute	Description

Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	

Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**
Name	TAXCCY

Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number

Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

PREVVERNO

Attribute	Description	
Name	PREVVERNO	
Datatype	Number	
Description	Indicates Previous Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2

Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String

Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String

Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String

Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	**Description**	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	**Description**
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	Description	
Name	ULT_BENEF4	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2

Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description

Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description

Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component_Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String

Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	0
pattern	[A-Za-z0-9]*

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	0
pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

PREVVERNO

Attribute	Description	
Name	PREVVERNO	
Datatype	Number	
Description	Indicates Previous Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>BS,CS,WI,BB,CB,LG</td></tr></table>

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String

Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKID

Attribute	**Description**	
Name	BRKID	
Datatype	String	
Description	Indicates Broker Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

MSTLDT

Attribute	**Description**	
Name	MSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGMSTLDT

Attribute	**Description**	
Name	ORGMSTLDT	
Datatype	Date	
Description	Indicates Actual MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	**Description**	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK

Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN

Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	

Attribute	Description
minOccurs	0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNEXPOSURE

Attribute	**Description**	
Name	UNEXPOSURE	
Datatype	String	
Description	Indicates Undelivered Exposure	
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates Total Exposure	
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String

Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	**Description**	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	Description	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_NETCONS

Attribute	Description	
Name	DEAL_NETCONS	
Datatype		
Description	Includes Deal Net cons details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description

Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	

Attribute	Description
minOccurs	0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	

Attribute	Description
minOccurs	0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	

Attribute	Description
minOccurs	0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	

Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	

Restrictions	Description
pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

BROKER

Attribute	**Description**	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	**Description**	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT

Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description

Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	

Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 15 minInclusive: 0 totalDigits: 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	Attribute: minOccurs — Description: 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	Restrictions: maxLength — Description: 15 Restrictions: minLength — Description: 0 Restrictions: pattern — Description: [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description

Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component_Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log

Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description

Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

2.69.3.SE-Deal-Confirm-Res-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALTYP*
    - *DEALQTY*
    - *PRCTYPE*
    - *DLVRFREEPAY*
    - *PRCQUOTE*
    - *DSTLDT*

INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
PAYCCY
SCCY
RATEPCYSCY
SPOTDT
FORM
DEALTYPE
ISMAIND
PRODDESC
PRDTYP
CPTYCONFREF
CPTYCONFDT
CPTYCONFREM
CONFTYPE
LEGTYPE
LEGREFFROM
LEGREFTO
LEGUREFFROM
LEGUREFTO
TRADEDT
SETTLMNTDT
UNITS
Deal-Detail-To
  FCCREF
  XREF
  PRD

DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1

ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1

ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN

WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*

BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP

PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS

CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX

Unrel-Unmatch

LEGREF

UNMATCHED

LEGREF

UNMATCHED

BRKID

MSTLDT

ORGMSTLDT

CPTYDESC

SKLOCDESC

WALKINNAME

WALKINMEDIA

ADDRLINE1

ADDRLINE2

ADDRLINE3

ADDRLINE4

SCLNRISKLMTRK

SPSTLRISKLMTRK

TOTEXPLINE

UNDEXPLINE

PAYBRN

PAYACC

ACTMSTLDT

DEAL_CERTIFICATE_DETAILS

FCCREF

DEALREF

CERTNO

CERTQT

DEAL_LIMITS

LEGREF

WALKINNAME

WALKINMEDIA

ADDRLINE1

ADDRLINE2

ADDRLINE3

ADDRLINE4

DEAL_WALKIN

LEGREF

UNEXPOSURE

TOTEXPOSURE

CLEANRISKLIMIT

PSTLRISKLIMIT

CPTY

CONTRACT

FCCREF

BRKDETAILS

- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *FCCREF*
- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Charge-Application

- *CHGCOMP*

CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF

REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4

TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1

ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4

INSTRCDTXT5

Taxdetails-Main

SCHEME

WAIVER

SCHEMEDESC

SCHEME

WAIVER

SCHEMEDESC

SECUDF

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Sevws-Matched-Deal

FCCREF

VER

BUYLEG

SELLEG

DSTLDT

MATCH

LEGREF

LEGTYPE

UNMATCHED

TOTMATCHED

DEALQTY

FCCREF

VER

BUYLEG

SELLEG

DSTLDT

MATCH

LEGREF

LEGTYPE

UNMATCHED

TOTMATCHED

DEALQTY

DEAL_MESSAGES

FCCREF

LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
  LEGREF
  PTYPE
  ADDR1
  ADDR2
  ADDR3
  ADDR4
  LEGREF
  PTYPE
  ADDR1
  ADDR2
  ADDR3
  ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
  LEGREF

PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY

TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln

CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*

INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3

ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*

AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6

ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3

ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4

INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC

DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY

AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY

PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO

LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6
      AGRID
      AMTTAG
      BNKPRIO
      BNFINSTCVR1
      BNFINSTCVR2
      BNFINSTCVR3
      BNFINSTCVR4
      BNFINSTCVR5

BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY

PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID

PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME

WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
  FCCREF
  DEALREF
  CERTNO
  CERTQT
DEAL_LIMITS
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4
DEAL_WALKIN
  LEGREF
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
  CPTY
CONTRACT
  FCCREF
  BRKDETAILS
    FCCREF
    ESN
    BROKER
    BRKAMT
    BRKCCY
    RULE
    DSCACR
    BRKNAM
    RULEDESC

- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *Charge-Application*
  - *CHGCOMP*
  - *CRNESN*
  - *TGCCY*
  - *TGAMT*
  - *CHGCCY*
  - *CHGAMT*
  - *WAIVER*
  - *LIQINTR*
  - *DISACR*
- *Charge-Association*
  - *CHGCOMP*
  - *CRNESN*
  - *RULE*
  - *WAIVER*
  - *DISACR*
  - *ACCREQ*
  - *CHGDESC*
- *Charge-Liquidation*
  - *ESN*
  - *CHGCOMP*
  - *CHGCCY*
  - *CHGAMT*
  - *LQDSTS*
- *Mis-Details*
  - *BRANCH*
  - *CUSTNO*
  - *MISGRP*
  - *REL_REF*
  - *REL_ACC*
  - *MISHD*
  - *POOLCD*
  - *REFRT*
  - *REFRTTYPE*
  - *REFXRT*
  - *CALCMETH*
  - *MISGRPTXN*
  - *REFRTCD*

REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3

FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5

SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN

INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
CONTRACT
FCCREF
BRKDETAILS
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
FCCREF
ESN

- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*
- *Charge-Application*
  - *CHGCOMP*
  - *CRNESN*
  - *TGCCY*
  - *TGAMT*
  - *CHGCCY*
  - *CHGAMT*
  - *WAIVER*
  - *LIQINTR*
  - *DISACR*
  - *CHGCOMP*
  - *CRNESN*
  - *TGCCY*
  - *TGAMT*
  - *CHGCCY*
  - *CHGAMT*
  - *WAIVER*
  - *LIQINTR*
  - *DISACR*
- *Charge-Association*
  - *CHGCOMP*
  - *CRNESN*
  - *RULE*
  - *WAIVER*
  - *DISACR*
  - *ACCREQ*

CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10

MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4

COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8

COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2

REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG

DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1

ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4

DEAL_NETCONS

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX

LEGREF

BUYSEL

COMPTYP

COMP

AMTTAG

COMPCCY

AMTCCY

PAYCCY

RATE

AMTPCY

SIGN

COMPDESC

INTDAYS

CUMEX

SKLOCTO

SKACCTO

Ytm-Master

DEALREF

DEALREFNO

EFFDT

YTM

Contract-Event-Log

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

TXTCSTAT

CONTSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for Response of SE Deal contract confirmation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Confirmation of Securities Deal Input Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Latest Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	**Restrictions** / **Description** maxLength / 15 pattern / [a-zA-Z0-9]*

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	**Restrictions** / **Description** enumeration: S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date

Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P

TOP

SPOTINTVALDT

Attribute	**Description**	
Name	SPOTINTVALDT	
Datatype	Date	
Description	Indicates Spot Interest Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPOTPRC

Attribute	**Description**	
Name	SPOTPRC	
Datatype	Number	
Description	Indicates Spot Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT

Attribute	**Description**	
Name	DISCOUNT	
Datatype	Number	
Description	Indicates Discount	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PREMIUM

Attribute	**Description**	
Name	PREMIUM	
Datatype	Number	
Description	Indicates Premium	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

FORWDPL

Attribute	**Description**
Name	FORWDPL

Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYCONFREF

Attribute	Description
Name	CPTYCONFREF
Datatype	String
Description	Indicates Counterparty Confirmation Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYCONFDT

Attribute	Description
Name	CPTYCONFDT
Datatype	Date
Description	Indicates Counterparty Confirmation Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYCONFREM

Attribute	Description	
Name	CPTYCONFREM	
Datatype	String	
Description	Indicates Counterparty Confirmation Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFTYPE

Attribute	Description	
Name	CONFTYPE	
Datatype	String	
Description	Indicates Type of Confirmation Delivery : D Counterparty : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

LEGTYPE

Attribute	Description	
Name	LEGTYPE	
Datatype	String	
Description	Indicates Leg Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S

TOP

LEGREFFROM

Attribute	Description	
Name	LEGREFFROM	
Datatype	String	
Description	Indicates From Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates To Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUREFFROM

Attribute	Description
Name	LEGUREFFROM
Datatype	String
Description	Indicates From Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUREFTO

Attribute	Description
Name	LEGUREFTO
Datatype	String
Description	Indicates To Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SETTLMNTDT

Attribute	Description
Name	SETTLMNTDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNITS

Attribute	Description

Name	UNITS
Datatype	Number
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description

Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LGDESC

Attribute	Description	
Name	LGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SKLOCDESCTO

Attribute	Description	
Name	SKLOCDESCTO	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSELL

Attribute	Description	
Name	BUYSELL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description	
Name	Deal-Limits-To	
Datatype		
Description	Includes Deal To Limits	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF

Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	**Description**	
Name	ACC	
Datatype	String	
Description	Indicates the Account that sources the funds for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1; pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1; pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 1; pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	**Description**	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	**Description**
Name	ADDRLINE4

Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE

Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 0; pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3; minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details

Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN

Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description

Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1 pattern: [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description

Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE

Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY

Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description

Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Deal-Walkin-To

Attribute	**Description**	
Name	Deal-Walkin-To	
Datatype		
Description	Includes Deal Walkin To details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String

Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 0; pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 0; pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description	
Name	SCLNRISKLMTRK	
Datatype	String	
Description	Indicates Track Clean Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description	
Name	SPSTLRISKLMTRK	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs: 2 minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String

Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,A</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	

Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105
minLength	1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105
minLength	1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105
minLength	1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

BENEF_INST4

Attribute	Description

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	Description	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	Description	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	Description	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	Description	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	Description	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	Description	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	Description	
Name	INT_REIM_INST1	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

INT_REIM_INST2

Attribute	Description	
Name	INT_REIM_INST2	
Datatype	String	
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	Description	
Name	INTDAYS	
Datatype	Number	
Description	Indicates Interest Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	Description	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Interest

Attribute	Description	
Name	Deal-Interest	
Datatype		
Description	Includes Deal Interest details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description

Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	

Attribute	Description
minOccurs	0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	

Attribute	Description
minOccurs	0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	

Attribute	Description
minOccurs	0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	

Attribute	Description
minOccurs	0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	

Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description	
Name	SCLNRISKLMTRK	
Datatype	String	
Description	Indicates Track Clean Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description	
Name	SPSTLRISKLMTRK	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TOTEXPLINE

Attribute	Description	
Name	TOTEXPLINE	
Datatype	String	
Description	Indicates Total Exposure Line	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	3
minLength	1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	20
pattern	[a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	**Description**	
Name	DEAL_CERTIFICATE_DETAILS	
Datatype		
Description	Includes Deal Certificate details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	**Description**
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	**Description**	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	

Attribute	Description
minOccurs	0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

BRKNAM

Attribute	**Description**	
Name	BRKNAM	
Datatype	String	
Description	Indicates Broker name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	**Description**	
Name	Brokerage-Details	
Datatype		
Description	Indicates Brokerage details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

REFXRT

Attribute	Description

Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4LBL4

Attribute	Description	
Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1

Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2

Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1

Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	**Description**	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	**Description**	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	**Description**	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	Attribute: minOccurs; Description: 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	Attribute: minOccurs; Description: 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	Restrictions: maxLength; Description: 15 Restrictions: minLength; Description: 0 Restrictions: pattern; Description: [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	Attribute: minOccurs; Description: 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXTREF

Attribute	**Description**	
Name	TXTREF	
Datatype	String	
Description	Indicates Text Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	**Description**	
Name	Tran-Tax-Assoc	
Datatype		
Description	Includes Transaction Tax Association details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**
Name	RULE

Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

DSCACR

Attribute	**Description**	
Name	DSCACR	
Datatype	String	
Description	Consider for Discount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

BRKNAM

Attribute	**Description**	
Name	BRKNAM	
Datatype	String	
Description	Indicates Broker name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

Brokerage-Details

Attribute	**Description**
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKCCY

Attribute	**Description**	
Name	BOOKCCY	
Datatype	String	
Description	Indicates the Booking currency for the booked amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

BKMTHD

Attribute	**Description**	
Name	BKMTHD	
Datatype	Number	
Description	Indicates Booking Method	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BOOKAMT

Attribute	**Description**	
Name	BOOKAMT	
Datatype	Number	
Description	Indicates the Booking Amount for the brokerage.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

LIQSTAT

Attribute	**Description**	
Name	LIQSTAT	
Datatype	String	
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1
	minLength	1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LIQSTAT

Attribute	Description

Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	

Restrictions	Description
maxLength	20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT

Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number

Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6

Attribute	**Description**

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description

Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description

Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5
	minLength	1

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Regulatory Report 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Regulatory Report 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String
Description	Regulatory Report 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	**Description**
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	**Description**
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	**Description**
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	**Description**
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000; minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT

Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	**Description**	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGTYPE

Attribute	**Description**	
Name	LEGTYPE	
Datatype	String	
Description	Indicates Leg Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S

TOP

UNMATCHED

Attribute	**Description**	
Name	UNMATCHED	
Datatype	Number	
Description	Indicates Total Remaining	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTMATCHED

Attribute	**Description**	
Name	TOTMATCHED	
Datatype	String	
Description	Indicates Total Matched	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z]

TOP

DEALQTY

Attribute	**Description**
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description

Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String

Description	Indicates Party Type
Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	

Attribute	Description
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**	
Name	ADDR1	
Datatype	String	
Description	Indicates Party Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXTCSTAT

Attribute	Description
Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.69.4.SE-Deal-Confirm-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master*
      - *FCCREF*
      - *XREF*
      - *VERNO*
    - *Contract-Confirm*
      - *FCCREF*
      - *UREF*
      - *PRD*
      - *VERNO*
      - *LATVERNO*
      - *DEALREF*
      - *XREF*
      - *SRC*
      - *SECTYCD*
      - *MKTCD*
      - *SECTYDESC*
      - *MRKDESC*
      - *DEALTYP*

DEALQTY
PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
PAYCCY
SCCY
RATEPCYSCY
SPOTDT
FORM
DEALTYPE
ISMAIND
PRODDESC
PRDTYP
CPTYCONFREF
CPTYCONFDT
CPTYCONFREM
CONFTYPE
LEGTYPE
LEGREFFROM
LEGREFTO
LEGUREFFROM
LEGUREFTO
TRADEDT
SETTLMNTDT

UNITS

Deal-Detail-To

- *FCCREF*
- *XREF*
- *PRD*
- *DEALREFNO*
- *LGPRDCODE*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGUSERREF*
- *LEG_REFERNCENO*
- *LGDESC*
- *SKLOCDESCTO*
- *BUYSELL*
- *Deal-Limits-To*
  - *LEGREF*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Deal-Walkin-To*
  - *LEGREF*
- *CONTRACT1*
  - *FCCREF*
  - *VERNO*
  - *PREVVERNO*
  - *Settlement-Addl-Details*
    - *ACCBRN*
    - *ACC_CCY*
    - *ACC*
    - *AMTTAG*
    - *CUSTSPRD*
    - *ERIAMT*
    - *ERICCY*
    - *XRATE*
    - *GENMSG*
    - *NETACRSMOD*
    - *PAYRCV*
    - *RATECDDEFRD*

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE

INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4

- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*

BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2

ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6

ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK

PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY

RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE

AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
DEAL_WALKIN
LEGREF
UNEXPOSURE

- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *CPTY*

CONTRACT

- *FCCREF*
- *BRKDETAILS*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
  - *FCCREF*
  - *ESN*
  - *BROKER*
  - *BRKAMT*
  - *BRKCCY*
  - *RULE*
  - *DSCACR*
  - *BRKNAM*
  - *RULEDESC*
  - *Brokerage-Details*
    - *BOOKCCY*
    - *BKMTHD*
    - *BOOKAMT*
    - *LIQSTAT*
    - *LREFNO*
    - *BOOKCCY*
    - *BKMTHD*

BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN

CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4

COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9

TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG

PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD

BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5

INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE

UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6

- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*
  - *SIGN*
  - *COMPDESC*
  - *INTDAYS*
  - *CUMEX*

LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF

CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN

INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD

ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*

INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5

SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ

XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6

- *RECEIVER*
- *RTGSNW*
- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*

ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1

ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN

WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF

BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL

COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO

ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6
      AGRID
      AMTTAG
      BNKPRIO

BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3

ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages

LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
BRKID

MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
  FCCREF
  DEALREF
  CERTNO
  CERTQT
DEAL_LIMITS
  LEGREF
  WALKINNAME
  WALKINMEDIA
  ADDRLINE1
  ADDRLINE2
  ADDRLINE3
  ADDRLINE4
DEAL_WALKIN
  LEGREF
  UNEXPOSURE
  TOTEXPOSURE
  CLEANRISKLIMIT
  PSTLRISKLIMIT
  CPTY
CONTRACT
  FCCREF
  BRKDETAILS
    FCCREF
    ESN
    BROKER
    BRKAMT

- BRKCCY
- RULE
- DSCACR
- BRKNAM
- RULEDESC
- Brokerage-Details
  - BOOKCCY
  - BKMTHD
  - BOOKAMT
  - LIQSTAT
  - LREFNO
- Charge-Application
  - CHGCOMP
  - CRNESN
  - TGCCY
  - TGAMT
  - CHGCCY
  - CHGAMT
  - WAIVER
  - LIQINTR
  - DISACR
- Charge-Association
  - CHGCOMP
  - CRNESN
  - RULE
  - WAIVER
  - DISACR
  - ACCREQ
  - CHGDESC
- Charge-Liquidation
  - ESN
  - CHGCOMP
  - CHGCCY
  - CHGAMT
  - LQDSTS
- Mis-Details
  - BRANCH
  - CUSTNO
  - MISGRP
  - REL_REF
  - REL_ACC
  - MISHD
  - POOLCD
  - REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5

- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

SECUDF

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Sevws-Matched-Deal

- *FCCREF*
- *VER*
- *BUYLEG*
- *SELLEG*
- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*

DEAL_MESSAGES

- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*

SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF

- UNMATCHED
- Tax-Master
  - TXTREF
  - Tran-Tax-Assoc
    - CRRATESN
    - INTCOMP
    - RULE
    - WAIVER
    - CONTREF
  - Tran-Tax-Appln
    - CRRATESN
    - INTCOMP
    - TAGCCY
    - TAGAMNT
    - TAXCCY
    - TAXAMNT
    - WAIVER
    - LIQINDICAT
    - CONTREF
- DEAL_CERTIFICATE_DETAILS
  - FCCREF
  - DEALREF
  - CERTNO
  - CERTQT
- CONTRACT
  - FCCREF
  - BRKDETAILS
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT
      - LREFNO
      - BOOKCCY
      - BKMTHD

BOOKAMT
LIQSTAT
LREFNO
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP

CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5

FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9

FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9

FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3

COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*

Taxdetails-Main

- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*
- *SCHEME*
- *WAIVER*
- *SCHEMEDESC*

SECUDF

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*
- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Sevws-Matched-Deal

- *FCCREF*
- *VER*
- *BUYLEG*
- *SELLEG*
- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*
- *FCCREF*
- *VER*
- *BUYLEG*
- *SELLEG*
- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*

DEAL_MESSAGES

- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*
- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*

ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF

PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
SKLOCTO
SKACCTO
Ytm-Master
DEALREF
DEALREFNO
EFFDT
YTM
Contract-Event-Log
MAKERID
MAKERSTAMP

CHECKERID
CHECKERSTAMP
TXTCSTAT
CONTSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key Response for SE Deal Contract Contract confirmation

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	Confirmation of Securities Deal Input
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

Contract-Confirm

Attribute	Description
Name	Contract-Confirm
Datatype	
Description	Confirmation of Securities Deal Input contract Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Latest Version Number
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP

Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	**Restrictions** / **Description** enumeration / S,F

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM

Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates Transaction Date

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates Spot Interest Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates Discount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number

Description	Indicates Premium
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String

Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CPTYCONFREF

Attribute	Description
Name	CPTYCONFREF
Datatype	String
Description	Indicates Counterparty Confirmation Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYCONFDT

Attribute	Description
Name	CPTYCONFDT
Datatype	Date
Description	Indicates Counterparty Confirmation Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYCONFREM

Attribute	Description
Name	CPTYCONFREM
Datatype	String
Description	Indicates Counterparty Confirmation Remarks
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFTYPE

Attribute	Description
Name	CONFTYPE
Datatype	String
Description	Indicates Type of Confirmation Delivery : D Counterparty : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

LEGREFFROM

Attribute	Description
Name	LEGREFFROM

Datatype	String
Description	Indicates From Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates To Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUREFFROM

Attribute	Description
Name	LEGUREFFROM
Datatype	String
Description	Indicates From Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUREFTO

Attribute	Description
Name	LEGUREFTO
Datatype	String
Description	Indicates To Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SETTLMNTDT

Attribute	Description
Name	SETTLMNTDT
Datatype	Date
Description	Indicates Settlement Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	Number
Description	Indicates Units
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD

Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,A</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	

Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description	
Name	DRCRIND	
Datatype	String	
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr></table>

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	**Description**	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF5

Attribute	Description	
Name	ULT_BENEF5	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF6

Attribute	Description	
Name	ULT_BENEF6	
Datatype	String	
Description	Country to which the ultimate beneficiary belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	Description	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>BS,CS,WI,BB,CB,LG</td></tr></table>

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String

Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	**Description**	
Name	INTDAYS	
Datatype	Number	
Description	Indicates Interest Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	**Description**	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description	
Name	ORGMSTLDT	
Datatype	Date	
Description	Indicates Actual MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	Description	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description	
Name	SCLNRISKLMTRK	
Datatype	String	
Description	Indicates Track Clean Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description	
Name	SPSTLRISKLMTRK	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TOTEXPLINE

Attribute	Description	
Name	TOTEXPLINE	
Datatype	String	
Description	Indicates Total Exposure Line	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	3
minLength	1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	20
pattern	[a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_LIMITS

Attribute	**Description**	
Name	DEAL_LIMITS	
Datatype		
Description	Includes Deal Limits details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	

Attribute	Description
minOccurs	0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	

Restrictions	Description
maxLength	11
minLength	0
pattern	[A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	Description	
Name	BRKCCY	
Datatype	String	
Description	Indicates the Brokerage Currency for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

DSCACR

Attribute	Description
Name	DSCACR

Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1
pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10
minLength	1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates the Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates the Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP

Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description

Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12
minLength	1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16
minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description

Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4

Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT3

Attribute	**Description**	
Name	INSTRCDTXT3	
Datatype	String	
Description	Indicates the Instruction Code Text3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description

Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

VER

Attribute	Description
Name	VER

Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	

Attribute	Description
minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	

Restrictions	Description
totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	

Attribute	Description
minOccurs	0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	

Attribute	Description
minOccurs	0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>BS,CS,WI,BB,CB,LG</td></tr></table>

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description

Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	

Attribute	Description
minOccurs	0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	

Attribute	Description
minOccurs	0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	**Description**	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_LIMITS1

Attribute	**Description**	
Name	DEAL_LIMITS1	
Datatype		
Description	Includes Deal Limits details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**
Name	PSTLRISKLIMIT
Datatype	String

Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF

Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE

Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTYDESC

Attribute	Description

Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF

Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Indicates Interest Component	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description

Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Deal-Walkin-To

Attribute	**Description**	
Name	Deal-Walkin-To	
Datatype		
Description	Includes Deal Walkin To details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{1}</td></tr></table>

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4

Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	Description	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	Description	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String

Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description	
Name	SCLNRISKLMTRK	
Datatype	String	
Description	Indicates Track Clean Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description	
Name	SPSTLRISKLMTRK	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs: 2 minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates Safe Keeping To Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACCTO

Attribute	**Description**
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates Auto MSTL A for On; M for Off	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description	Indicates Leg User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To

Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT1

Attribute	**Description**	
Name	CONTRACT1	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

VERNO

Attribute	**Description**	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

PREVVERNO

Attribute	**Description**
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String

Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description	
Name	MSTLDT	
Datatype	Date	
Description	Indicates MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGMSTLDT

Attribute	Description	
Name	ORGMSTLDT	
Datatype	Date	
Description	Indicates Actual MSTL Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	Description	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TOTEXPLINE

Attribute	**Description**	
Name	TOTEXPLINE	
Datatype	String	
Description	Indicates Total Exposure Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	**Description**	
Name	UNDEXPLINE	
Datatype	String	
Description	Indicates Undelivered Exposure Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

PAYACC

Attribute	**Description**
Name	PAYACC
Datatype	String

Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 0 pattern: [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs: 2 minOccurs: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 0 pattern: [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 0 pattern: [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details

Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description

Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String

Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRTCD

Attribute	**Description**	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

REFRTSPRD

Attribute	**Description**	
Name	REFRTSPRD	
Datatype	Number	
Description	Indicates the spread for the Refinance Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6

Attribute	**Description**

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description

Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4

Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT3

Attribute	**Description**	
Name	INSTRCDTXT3	
Datatype	String	
Description	Indicates the Instruction Code Text3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	Description	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	Description	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECUDF

Attribute	Description	
Name	SECUDF	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,S</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOTMATCHED

Attribute	**Description**	
Name	TOTMATCHED	
Datatype	String	
Description	Indicates Total Matched	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z]

TOP

DEALQTY

Attribute	**Description**
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	**Description**	
Name	DEAL_MESSAGES	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description

Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1 pattern: [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1 minLength: 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation

Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT

Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String

Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String

Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	**Description**

Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	

Restrictions	Description
totalDigits	4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	

Attribute	Description
minOccurs	0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	

Attribute	Description
minOccurs	0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT

Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	Description	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength: 15 minLength: 0 pattern: [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String

Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO

Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description
Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.70.CancelSEDeal

Reversal of Securities Deal Input

2.70.1.SE-Deal-Reverse-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *REVDREFNO*
    - *MKTCD*
    - *DEALTYP*
    - *DEALQTY*
    - *TRADEDT*

PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
DEALTIME
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
LMTRACK
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
SECTYSERIES
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS
SMNTSK
CERTNO
ORGINTAMT
ORGPRICE
Contract_Event_Log
  MAKERID
  MAKERSTAMP

- CHECKERID
- CHECKERSTAMP
- TXTCSTAT
- CONTSTAT
- AUTHSTAT

Deal-Detail

- FCCREF
- XREF
- PRD
- DEALREFNO
- LGPRDCODE
- PORTFOLIO
- CPTY
- SKLOC
- SKACC
- SKLOCTO
- SKACCTO
- ACCOMLODGE
- AUTOMSTL
- LEGREF
- LEGUSERREF
- LEG_REFERNCENO
- LGDESC
- SKLOCDESCTO
- BUYSELL
- Deal-Limits-To
  - LEGREF
  - CLEANRISKLIMIT
  - PSTLRISKLIMIT
- Deal-Walkin-To
  - LEGREF
- CONTRACT1
  - FCCREF
  - VERNO
  - PREVVERNO
  - Settlement-Addl-Details
    - ACCBRN
    - ACC_CCY
    - ACC
    - AMTTAG
    - CUSTSPRD
    - ERIAMT
    - ERICCY
    - XRATE

GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*

INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1

ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*

ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4

ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1

ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP

AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3

- *ADDRLINE4*
- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
  - *CPTY*
- *CONTRACT*
  - *FCCREF*
  - *BRKDETAILS*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*

LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP

CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10

COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5

TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4

COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9

TXNMIS10LBL10

Settlement-Details

AMTTAG

TRNTPCD

BNKOPRCD

REGREP1

REGREP2

REGREP3

ENV_CONT1

ENV_CONT2

ENV_CONT3

ENV_CONT4

ENV_CONT5

TIMEIND1

TIMEIND2

TIMEIND3

INSTRCDLT

INSTRCDLT1

INSTRCDLT2

INSTRCDLT3

INSTRCDLT4

INSTRCDLT5

INSTRCDTXT

INSTRCDTXT1

INSTRCDTXT2

INSTRCDTXT3

INSTRCDTXT4

INSTRCDTXT5

AMTTAG

TRNTPCD

BNKOPRCD

REGREP1

REGREP2

REGREP3

ENV_CONT1

ENV_CONT2

ENV_CONT3

ENV_CONT4

ENV_CONT5

TIMEIND1

TIMEIND2

TIMEIND3

INSTRCDLT

INSTRCDLT1

INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG

- *DSTLDT*
- *MATCH*
- *LEGREF*
- *LEGTYPE*
- *UNMATCHED*
- *TOTMATCHED*
- *DEALQTY*

DEAL_MESSAGES

- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*
- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *FCCREF*
- *LEGREF*
- *VERSION*
- *MSG*
- *PARTYID*
- *PARTYNAME*
- *SNDRINFO1*
- *SNDRINFO2*

- *SNDRINFO3*
- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*

SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY

TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail-To
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5

BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1

- *RCVR_CORRESP2*
- *RCVR_CORRESP3*
- *RCVR_CORRESP4*
- *RCVR_CORRESP5*
- *RCVR_CORRESP6*
- *RECEIVER*
- *RTGSNW*
- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*

INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5

ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE

INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4

SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2

PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN

COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO

- CERTQT
- DEAL_LIMITS
  - LEGREF
  - WALKINNAME
  - WALKINMEDIA
  - ADDRLINE1
  - ADDRLINE2
  - ADDRLINE3
  - ADDRLINE4
- DEAL_WALKIN
  - LEGREF
  - UNEXPOSURE
  - TOTEXPOSURE
  - CLEANRISKLIMIT
  - PSTLRISKLIMIT
  - CPTY
- CONTRACT
  - FCCREF
  - BRKDETAILS
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT
      - LREFNO
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT
      - LREFNO
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY

RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
Charge-Association
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN

RULE
WAIVER
DISACR
ACCREQ
CHGDESC
Charge-Liquidation
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2

COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7

COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6

COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1

TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF

LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4

- FCCREF
- LEGREF
- VERSION
- MSG
- PARTYID
- PARTYNAME
- SNDRINFO1
- SNDRINFO2
- SNDRINFO3
- SNDRINFO4
- SNDRINFO5
- SNDRINFO6
- ADDLINFO1
- ADDLINFO2
- ADDLINFO3
- PARTYDTLS
  - LEGREF
  - PTYPE
  - ADDR1
  - ADDR2
  - ADDR3
  - ADDR4
  - LEGREF
  - PTYPE
  - ADDR1
  - ADDR2
  - ADDR3
  - ADDR4
- DEAL_PARTIES
  - LEGREF
  - PTYPE
  - ADDR1
  - ADDR2
  - ADDR3
  - ADDR4
  - LEGREF
  - PTYPE
  - ADDR1
  - ADDR2
  - ADDR3
  - ADDR4
- DEAL_NETCONS
  - LEGREF
  - BUYSEL

COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE

WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full request for SE Deal Contract Reverse operation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Reversal of Securities Deal Input Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Latest Version Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	**Restrictions** / **Description** maxLength / 15 pattern / [a-zA-Z0-9]*

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates Reversed Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P</td></tr></table>

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates Local Currency Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates Original DSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALTIME

Attribute	Description

Name	DEALTIME
Datatype	Date
Description	Indicates Deal Input Time

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates Spot Interest Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates Spot Price

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISCOUNT

Attribute	**Description**	
Name	DISCOUNT	
Datatype	Number	
Description	Indicates Discount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREMIUM

Attribute	**Description**	
Name	PREMIUM	
Datatype	Number	
Description	Indicates Premium	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORWDPL

Attribute	**Description**	
Name	FORWDPL	
Datatype	Number	
Description	Indicates Forward P and L	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FACEDEAL

Attribute	**Description**	
Name	FACEDEAL	
Datatype	Number	
Description	Indicates Deal Nominal	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADJDEALPRC

Attribute	**Description**	
Name	ADJDEALPRC	
Datatype	Number	
Description	Indicates Adjusted Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates Actual DSTL Date

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LMTRACK

Attribute	Description
Name	LMTRACK
Datatype	String
Description	Indicates whether limit tracking is required or not Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RATEPCYSCY

Attribute	**Description**	
Name	RATEPCYSCY	
Datatype	String	
Description	Indicates Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

SECSTTLMENT

Attribute	**Description**	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates Settlement SKL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	16
	pattern	[a-zA-Z0-9]{16}

TOP

SPOTDT

Attribute	**Description**	
Name	SPOTDT	
Datatype	Date	
Description	Indicates Spot Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECTYSERIES

Attribute	**Description**	
Name	SECTYSERIES	
Datatype	String	
Description	Indicates Security Series	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 30 minLength: 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates Placement/Loan Reference
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 16 pattern: [a-zA-Z0-9]{16}

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,S

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	Number

Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 255 pattern / [a-zA-Z0-9]{255}

TOP

SMNTSK

Attribute	Description
Name	SMNTSK
Datatype	String
Description	Indicates Safe Keeping Location (Sk Loc) for the market
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

ORGINTAMT

Attribute	Description
Name	ORGINTAMT
Datatype	Number
Description	Indicates Original Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGPRICE

Attribute	Description
Name	ORGPRICE
Datatype	Number
Description	Indicates Original Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract_Event_Log

Attribute	Description
Name	Contract_Event_Log
Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description
Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes Deal details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	**Description**	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates Safe Keeping To Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACCTO

Attribute	**Description**
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates Auto MSTL A for On; M for Off	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description	Indicates Leg User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To

Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number

Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

GENMSG

Attribute	Description	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description	
Name	NETACRSMOD	
Datatype	String	
Description	Indicates Netting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String

Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	**Description**	
Name	ACC_CCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	**Description**	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	**Description**	
Name	BENEF_INST5	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST6

Attribute	**Description**	
Name	BENEF_INST6	
Datatype	String	
Description	Country to which the beneficiary institution belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description	
Name	ORDER_INST3	
Datatype	String	
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST4

Attribute	Description	
Name	ORDER_INST4	
Datatype	String	
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST5

Attribute	Description	
Name	ORDER_INST5	
Datatype	String	
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BUYSEL

Attribute	**Description**	
Name	BUYSEL	
Datatype	String	
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	**Description**
Name	ADDRLINE3

Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates Total Exposure	
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	Description	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

CONTRACT

Attribute	**Description**	
Name	CONTRACT	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	**Description**	
Name	BRKDETAILS	
Datatype		
Description	Includes Broker details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1; minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description

Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description

Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description

Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDTLS

Attribute	**Description**	
Name	PARTYDTLS	
Datatype		
Description	Includes Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR2

Attribute	**Description**	
Name	ADDR2	
Datatype	String	
Description	Indicates Party Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR3

Attribute	**Description**	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	**Description**	
Name	SNDRINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description	
Name	ADDR3	
Datatype	String	
Description	Indicates Party Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	Description	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	Description	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	Description	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP

Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

PAYCCY

Attribute	**Description**	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	**Description**	
Name	AMTPCY	
Datatype	Number	
Description	Indicates Amount In Payment Currency	
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SIGN

Attribute	**Description**	
Name	SIGN	
Datatype	String	
Description	Indicates Sign (+/-)	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPDESC

Attribute	**Description**

Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description

Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Restrictions	

Restrictions	Description
maxLength	20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates Safe Keeping To Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACCTO

Attribute	**Description**
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates Auto MSTL A for On; M for Off	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGUSERREF

Attribute	**Description**	
Name	LEGUSERREF	
Datatype	String	
Description	Indicates Leg User Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To

Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number

Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>12</td></tr><tr><td>totalDigits</td><td>24</td></tr></table>

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**	
Name	TAG_CCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String

Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP4

Attribute	**Description**
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String

Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	**Description**
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**
Name	PAYRCV
Datatype	String

Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3

Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	Description	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	Description	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	Description	
Name	ORDER_INST2	
Datatype	String	
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**	
Name	RCVR_CORRESP3	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP4

Attribute	**Description**	
Name	RCVR_CORRESP4	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP5

Attribute	**Description**

Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	**Description**	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	**Description**	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET

Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String

Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String

Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description

Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String

Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

OUR_CORRESP

Attribute	**Description**	
Name	OUR_CORRESP	
Datatype	String	
Description	Indicates Our Correspondent.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**	
Name	PMNT_DETAILS3	
Datatype	String	
Description	Indicates the details of the third payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS4

Attribute	**Description**	
Name	PMNT_DETAILS4	
Datatype	String	
Description	Indicates the details of the fourth payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**
Name	RCVR_CORRESP1
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME

Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 20 pattern: [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	**Description**	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	**Description**	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	**Description**	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	**Description**
Name	ADDRLINE3

Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure

Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates Total Exposure	
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	Description	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

CONTRACT

Attribute	**Description**	
Name	CONTRACT	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	**Description**	
Name	BRKDETAILS	
Datatype		
Description	Includes Broker details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHGAMT

Attribute	**Description**	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQINTR

Attribute	**Description**	
Name	LIQINTR	
Datatype	String	
Description	Indicates whether Liquidated or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACR

Attribute	**Description**	
Name	DISACR	
Datatype	String	
Description	Indicates that discount accrual fees will be charged.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description

Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	**Description**	
Name	CHGCOMP	
Datatype	String	
Description	The Charge Component Code required to calculate interest.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CRNESN

Attribute	**Description**	
Name	CRNESN	
Datatype	Number	
Description	Indicates the Creation ESN	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description

Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	**Description**	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	**Description**
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description

Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description

Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDTLS

Attribute	**Description**	
Name	PARTYDTLS	
Datatype		
Description	Includes Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO1

Attribute	**Description**	
Name	SNDRINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO2

Attribute	**Description**	
Name	SNDRINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO3

Attribute	**Description**	
Name	SNDRINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO4

Attribute	**Description**	
Name	SNDRINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO5

Attribute	**Description**	
Name	SNDRINFO5	
Datatype	String	
Description	Indicates Sender To Receiver Information 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP

Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description

Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description

Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

2.70.2.SE-Deal-Reverse-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *XREF*
    - *VERNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only request for SE Deal contract Reverse operation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Reversal of Securities Deal Input Master Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.70.3.SE-Deal-Reverse-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREF*
    - *DEALREFNO*
    - *XREF*
    - *SRC*
    - *SECTYCD*
    - *REVDREFNO*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALTYP*
    - *DEALQTY*
    - *TRADEDT*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
LMTRACK
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
SECTYSERIES
BAREF
PRIORITY
DEALER
ISMAIND
REMARKS
SMNTSK
CERTNO
ORGINTAMT
ORGPRICE
FORM
DEALTYPE

PRODDESC
PRDTYP
LCCY
YIELDEC
Deal-Detail-To
- *FCCREF*
- *XREF*
- *PRD*
- *DEALREFNO*
- *LGPRDCODE*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGUSERREF*
- *LEG_REFERNCENO*
- *LGDESC*
- *SKLOCDESCTO*
- *BUYSELL*
- *Deal-Limits-To*
  - *LEGREF*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
- *Deal-Walkin-To*
  - *LEGREF*
- *CONTRACT1*
  - *FCCREF*
  - *VERNO*
  - *PREVVERNO*
  - *Settlement-Addl-Details*
    - *ACCBRN*
    - *ACC_CCY*
    - *ACC*
    - *AMTTAG*
    - *CUSTSPRD*
    - *ERIAMT*
    - *ERICCY*
    - *XRATE*
    - *GENMSG*

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*

INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2

ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME

IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1

- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*

ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5

ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3

INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6

AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG

COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY

AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4

- *DEAL_WALKIN*
  - *LEGREF*
  - *UNEXPOSURE*
  - *TOTEXPOSURE*
  - *CLEANRISKLIMIT*
  - *PSTLRISKLIMIT*
  - *CPTY*
- *CONTRACT*
  - *FCCREF*
  - *BRKDETAILS*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*
      - *LREFNO*
    - *FCCREF*
    - *ESN*
    - *BROKER*
    - *BRKAMT*
    - *BRKCCY*
    - *RULE*
    - *DSCACR*
    - *BRKNAM*
    - *RULEDESC*
    - *Brokerage-Details*
      - *BOOKCCY*
      - *BKMTHD*
      - *BOOKAMT*
      - *LIQSTAT*

LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO

Charge-Application

CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

Charge-Association

CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC
CHGCOMP
CRNESN
RULE
WAIVER
DISACR
ACCREQ
CHGDESC

Charge-Liquidation

ESN
CHGCOMP
CHGCCY

CHGAMT
LQDSTS
ESN
CHGCOMP
CHGCCY
CHGAMT
LQDSTS
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1

COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6

TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5

LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Settlement-Details

- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*
- *INSTRCDLT3*
- *INSTRCDLT4*
- *INSTRCDLT5*
- *INSTRCDTXT*
- *INSTRCDTXT1*
- *INSTRCDTXT2*
- *INSTRCDTXT3*
- *INSTRCDTXT4*
- *INSTRCDTXT5*
- *AMTTAG*
- *TRNTPCD*
- *BNKOPRCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*
- *TIMEIND1*
- *TIMEIND2*
- *TIMEIND3*
- *INSTRCDLT*
- *INSTRCDLT1*
- *INSTRCDLT2*

INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT

MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3

- *SNDRINFO4*
- *SNDRINFO5*
- *SNDRINFO6*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *PARTYDTLS*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_PARTIES*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
  - *LEGREF*
  - *PTYPE*
  - *ADDR1*
  - *ADDR2*
  - *ADDR3*
  - *ADDR4*
- *DEAL_NETCONS*
  - *LEGREF*
  - *BUYSEL*
  - *COMPTYP*
  - *COMP*
  - *AMTTAG*
  - *COMPCCY*
  - *AMTCCY*
  - *PAYCCY*
  - *RATE*
  - *AMTPCY*
  - *SIGN*

COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
DEAL_WALKIN1
LEGREF
UNMATCHED
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT

WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Deal-Detail
FCCREF
XREF
PRD
LGPRDCODE
PORTFOLIO
CPTY
SKLOC
SKACC
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
MSTLDT
ORGMSTLDT
LEG_REFERNCENO
LGDESC
CPTYDESC
SKLOCDESC
BUYSELL
Deal-Limits
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin
LEGREF
Tax-Master
TXTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE

WAIVER
CONTREF
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Deal-Limits-To
LEGREF
CLEANRISKLIMIT
PSTLRISKLIMIT
Deal-Walkin-To
LEGREF
CONTRACT1
FCCREF
VERNO
PREVVERNO
Settlement-Addl-Details
ACCBRN
ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET

CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3

- *RCVR_CORRESP4*
- *RCVR_CORRESP5*
- *RCVR_CORRESP6*
- *RECEIVER*
- *RTGSNW*
- *RTGSPMNT*
- *SNDR_INFO1*
- *SNDR_INFO2*
- *SNDR_INFO3*
- *SNDR_INFO4*
- *SNDR_INFO5*
- *SNDR_INFO6*
- *TRNFRTYP*
- *ULT_BENEF1*
- *ULT_BENEF2*
- *ULT_BENEF3*
- *ULT_BENEF4*
- *ULT_BENEF5*
- *ULT_BENEF6*
- *AMTTAGDESC*
- *DISEXTBKCD*
- *PAYBNK*
- *PAYBRN*
- *WAVEINSTCHARG*
- *BNKOPRCD*
- *ENV_CONT1*
- *ENV_CONT2*
- *ENV_CONT3*
- *ENV_CONT4*
- *ENV_CONT5*

ACCBRN

ACC_CCY

ACC

AMTTAG

CUSTSPRD

ERIAMT

ERICCY

XRATE

GENMSG

NETACRSMOD

PAYRCV

RATECDDEFRD

SPRDDFN

TAG_CCY

DRCRIND

Settlement-Addl-Main

- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*
- *INST_TYPE*
- *INT_REIM_INST1*
- *INT_REIM_INST2*
- *INT_REIM_INST3*
- *INT_REIM_INST4*
- *INT_REIM_INST5*
- *INT_REIM_INST6*
- *INTMEDRY1*
- *INTMEDRY2*
- *INTMEDRY3*
- *INTMEDRY4*

INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC

DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
ACC_INST1
ACC_INST2
ACC_INST3
ACC_INST4
ACC_INST5
ACC_INST6
AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2

INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6

TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1
ADD2
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
PTY
ADD1

ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS

CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch
LEGREF
UNMATCHED
LEGREF
UNMATCHED
DEALREFNO
BRKID
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
YTM_MASTER
FCCREF
XREF
PRD
DEALREFNO
LGPRDCODE
PORTFOLIO
CPTY
SKLOC

SKACC
SKLOCTO
SKACCTO
ACCOMLODGE
AUTOMSTL
LEGREF
LEGUSERREF
LEG_REFERNCENO
LGDESC
SKLOCDESCTO
BUYSELL
Deal-Limits-To
  LEGREF
  CLEANRISKLIMIT
  PSTLRISKLIMIT
Deal-Walkin-To
  LEGREF
CONTRACT1
  FCCREF
  VERNO
  PREVVERNO
  Settlement-Addl-Details
    ACCBRN
    ACC_CCY
    ACC
    AMTTAG
    CUSTSPRD
    ERIAMT
    ERICCY
    XRATE
    GENMSG
    NETACRSMOD
    PAYRCV
    RATECDDEFRD
    SPRDDFN
    TAG_CCY
    DRCRIND
    Settlement-Addl-Main
      ACC_INST1
      ACC_INST2
      ACC_INST3
      ACC_INST4
      ACC_INST5
      ACC_INST6

AGRID
AMTTAG
BNKPRIO
BNFINSTCVR1
BNFINSTCVR2
BNFINSTCVR3
BNFINSTCVR4
BNFINSTCVR5
BNFINSTCVR6
BENEF_INST1
BENEF_INST2
BENEF_INST3
BENEF_INST4
BENEF_INST5
BENEF_INST6
CHGDET
CLGNTW
CVRBY
COVER_REQ
XPTACC
XPTBIC
XPTCLGNTW
XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6

ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3

ENV_CONT4
ENV_CONT5
Deal-Messages
LEGREF
VERSION
MSG
ADVDESC
PARTYID
PARTYNAME
Deal-Parties
PTY
ADD1
ADD2
Deal-Netcons
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Deal-Interest
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
Unrel-Unmatch

LEGREF
UNMATCHED
BRKID
MSTLDT
ORGMSTLDT
CPTYDESC
SKLOCDESC
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
SCLNRISKLMTRK
SPSTLRISKLMTRK
TOTEXPLINE
UNDEXPLINE
PAYBRN
PAYACC
ACTMSTLDT
DEAL_CERTIFICATE_DETAILS
FCCREF
DEALREF
CERTNO
CERTQT
DEAL_LIMITS
LEGREF
WALKINNAME
WALKINMEDIA
ADDRLINE1
ADDRLINE2
ADDRLINE3
ADDRLINE4
DEAL_WALKIN
LEGREF
UNEXPOSURE
TOTEXPOSURE
CLEANRISKLIMIT
PSTLRISKLIMIT
CPTY
CONTRACT
FCCREF
BRKDETAILS
FCCREF

- *ESN*
- *BROKER*
- *BRKAMT*
- *BRKCCY*
- *RULE*
- *DSCACR*
- *BRKNAM*
- *RULEDESC*
- *Brokerage-Details*
  - *BOOKCCY*
  - *BKMTHD*
  - *BOOKAMT*
  - *LIQSTAT*
  - *LREFNO*

Charge-Application

- *CHGCOMP*
- *CRNESN*
- *TGCCY*
- *TGAMT*
- *CHGCCY*
- *CHGAMT*
- *WAIVER*
- *LIQINTR*
- *DISACR*

Charge-Association

- *CHGCOMP*
- *CRNESN*
- *RULE*
- *WAIVER*
- *DISACR*
- *ACCREQ*
- *CHGDESC*

Charge-Liquidation

- *ESN*
- *CHGCOMP*
- *CHGCCY*
- *CHGAMT*
- *LQDSTS*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*

MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Details
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2

ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION

MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
DEAL_LIMITS1
LEGREF
CLEANRISKLIMIT

- PSTLRISKLIMIT
- DEAL_WALKIN1
  - LEGREF
  - UNMATCHED
- Tax-Master
  - TXTREF
  - Tran-Tax-Assoc
    - CRRATESN
    - INTCOMP
    - RULE
    - WAIVER
    - CONTREF
  - Tran-Tax-Appln
    - CRRATESN
    - INTCOMP
    - TAGCCY
    - TAGAMNT
    - TAXCCY
    - TAXAMNT
    - WAIVER
    - LIQINDICAT
    - CONTREF
- DEAL_CERTIFICATE_DETAILS
  - FCCREF
  - DEALREF
  - CERTNO
  - CERTQT
- CONTRACT
  - FCCREF
  - BRKDETAILS
    - FCCREF
    - ESN
    - BROKER
    - BRKAMT
    - BRKCCY
    - RULE
    - DSCACR
    - BRKNAM
    - RULEDESC
    - Brokerage-Details
      - BOOKCCY
      - BKMTHD
      - BOOKAMT
      - LIQSTAT

LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
FCCREF
ESN
BROKER
BRKAMT
BRKCCY
RULE
DSCACR
BRKNAM
RULEDESC
Brokerage-Details
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
BOOKCCY
BKMTHD
BOOKAMT
LIQSTAT
LREFNO
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR

DISACR

Charge-Association

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

CHGCOMP

CRNESN

RULE

WAIVER

DISACR

ACCREQ

CHGDESC

Charge-Liquidation

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

ESN

CHGCOMP

CHGCCY

CHGAMT

LQDSTS

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6

FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10

- COMPMIS1LBL1
- COMPMIS2LBL2
- COMPMIS3LBL3
- COMPMIS4LBL4
- COMPMIS5LBL5
- COMPMIS6LBL6
- COMPMIS7LBL7
- COMPMIS8LBL8
- COMPMIS9LBL9
- COMPMIS10LBL10
- TXNMIS1LBL1
- TXNMIS2LBL2
- TXNMIS3LBL3
- TXNMIS4LBL4
- TXNMIS5LBL5
- TXNMIS6LBL6
- TXNMIS7LBL7
- TXNMIS8LBL8
- TXNMIS9LBL9
- TXNMIS10LBL10

Settlement-Details

- AMTTAG
- TRNTPCD
- BNKOPRCD
- REGREP1
- REGREP2
- REGREP3
- ENV_CONT1
- ENV_CONT2
- ENV_CONT3
- ENV_CONT4
- ENV_CONT5
- TIMEIND1
- TIMEIND2
- TIMEIND3
- INSTRCDLT
- INSTRCDLT1
- INSTRCDLT2
- INSTRCDLT3
- INSTRCDLT4
- INSTRCDLT5
- INSTRCDTXT
- INSTRCDTXT1
- INSTRCDTXT2

INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
AMTTAG
TRNTPCD
BNKOPRCD
REGREP1
REGREP2
REGREP3
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
TIMEIND1
TIMEIND2
TIMEIND3
INSTRCDLT
INSTRCDLT1
INSTRCDLT2
INSTRCDLT3
INSTRCDLT4
INSTRCDLT5
INSTRCDTXT
INSTRCDTXT1
INSTRCDTXT2
INSTRCDTXT3
INSTRCDTXT4
INSTRCDTXT5
Taxdetails-Main
SCHEME
WAIVER
SCHEMEDESC
SCHEME
WAIVER
SCHEMEDESC
SECUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FUNCTIONID
FIELD_NAME

DATATYPE
FIELD_VALUE
VAL_TYPE
Sevws-Matched-Deal
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
FCCREF
VER
BUYLEG
SELLEG
DSTLDT
MATCH
LEGREF
LEGTYPE
UNMATCHED
TOTMATCHED
DEALQTY
DEAL_MESSAGES
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF

PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
FCCREF
LEGREF
VERSION
MSG
PARTYID
PARTYNAME
SNDRINFO1
SNDRINFO2
SNDRINFO3
SNDRINFO4
SNDRINFO5
SNDRINFO6
ADDLINFO1
ADDLINFO2
ADDLINFO3
PARTYDTLS
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_PARTIES
LEGREF
PTYPE
ADDR1
ADDR2

ADDR3
ADDR4
LEGREF
PTYPE
ADDR1
ADDR2
ADDR3
ADDR4
DEAL_NETCONS
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
LEGREF
BUYSEL
COMPTYP
COMP
AMTTAG
COMPCCY
AMTCCY
PAYCCY
RATE
AMTPCY
SIGN
COMPDESC
INTDAYS
CUMEX
SKLOCTO
SKACCTO
Ytm-Master
DEALREF
DEALREFNO
EFFDT
YTM

Contract-Event-Log

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

TXTCSTAT

CONTSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Screen Response for SE Deal Contract Reverse operation

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Reversal of Securities Deal Input Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates User Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates Block Deal Reference Number
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [A-Z0-9]*

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates Source
Restrictions	**Restrictions** / **Description** maxLength / 15 pattern / [a-zA-Z0-9]*

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates Security Code
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates Reversed Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECTYDESC

Attribute	Description
Name	SECTYDESC
Datatype	String
Description	Indicates Security Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates Market Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

DEALTYP

Attribute	Description
Name	DEALTYP
Datatype	String
Description	Indicates Deal Type Spot : S Forward : F
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,F</td></tr></table>

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates Trade Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates Interest Flat : F Plus Accured : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates Deliver Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates Price Quote Price : PRI Percentage Price : PPR Premium : PRM Percentage Premium : PPM Yield To Maturity(%) : YTM
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates Receive Free : F Against Payment : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates Input Price

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	Number
Description	Indicates Yield
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates Price In Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates Local Currency Quantity
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates Original DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates Absolute Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	String
Description	Indicates Deal Input Time
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates Transaction Date
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates Quote By Units : U Nominal : N
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates Spot Price Quote
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPI,PRM,PPM,YTM

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates Spot Interest Quote

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates Spot Interest Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates Spot Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates Discount
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates Premium
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

FORWDPL

Attribute	Description
Name	FORWDPL

Datatype	Number
Description	Indicates Forward P and L
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates Deal Nominal

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates Adjusted Price

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates T Bill WHT
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates Actual DSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

LMTRACK

Attribute	Description
Name	LMTRACK
Datatype	String
Description	Indicates whether limit tracking is required or not Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SCCY

Attribute	Description
Name	SCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATEPCYSCY

Attribute	Description
Name	RATEPCYSCY
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SECSTTLMENT

Attribute	Description
Name	SECSTTLMENT
Datatype	String
Description	Indicates Settlement SKL
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 16 pattern / [a-zA-Z0-9]{16}

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates Spot Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates Security Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates Placement/Loan Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 16 pattern / [a-zA-Z0-9]{16}

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates Priority HIGH : HIGH NORM : NORM LOW : LOW
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 1,2,3

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	Number
Description	Indicates Dealer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates Conforms to ISMA Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 255 pattern / [a-zA-Z0-9]{255}

TOP

SMNTSK

Attribute	Description
Name	SMNTSK
Datatype	String
Description	Indicates Safe Keeping Location (Sk Loc) for the market
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0

TOP

ORGINTAMT

Attribute	Description
Name	ORGINTAMT
Datatype	Number
Description	Indicates Original Interest Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGPRICE

Attribute	Description
Name	ORGPRICE
Datatype	Number
Description	Indicates Original Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates Securities Format Script Based : S Dematerialized : D Immobolized : I SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z]

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates Deal Type PRIMARY : P SECONDARY : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,S

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

LCCY

Attribute	Description
Name	LCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

YIELDEC

Attribute	Description
Name	YIELDEC
Datatype	Number
Description	Indicates Yield For Information
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Detail-To

Attribute	Description
Name	Deal-Detail-To
Datatype	
Description	Includes To Deal details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description

Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Deal-Walkin-To

Attribute	**Description**	
Name	Deal-Walkin-To	
Datatype		
Description	Includes Deal Walkin To details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	Attribute: minOccurs; Description: 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	Attribute: minOccurs; Description: 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	Restrictions: pattern; Description: [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	Restrictions: totalDigits; Description: 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	Restrictions: totalDigits; Description: 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	Description	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	Description	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	Description	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	Description	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	Description	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	Description	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	Description	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	pattern	[a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	**Description**	
Name	PMNT_BY	
Datatype	String	
Description	Indicates the mode of making the payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

PMNT_DETAILS1

Attribute	**Description**	
Name	PMNT_DETAILS1	
Datatype	String	
Description	Indicates the details of the first payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS2

Attribute	**Description**	
Name	PMNT_DETAILS2	
Datatype	String	
Description	Indicates the details of the second payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

PMNT_DETAILS3

Attribute	**Description**
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number

Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD

Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main

Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description

Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC

Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO

Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String

Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String

Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Deal-Messages

Attribute	Description
Name	Deal-Messages
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description

Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String

Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	**Description**	
Name	VERSION	
Datatype	Number	
Description	Indicates Version	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

MSG

Attribute	**Description**	
Name	MSG	
Datatype	String	
Description	Indicates Message	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADVDESC

Attribute	**Description**	
Name	ADVDESC	
Datatype	String	
Description	Indicates Advice Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYID

Attribute	**Description**	
Name	PARTYID	
Datatype	String	
Description	Indicates Party Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYNAME

Attribute	**Description**	
Name	PARTYNAME	
Datatype	String	
Description	Indicates Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CPTYDESC

Attribute	Description	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates Address 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4

Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE

Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	**Description**	
Name	DEALREF	
Datatype	String	
Description	Indicates Deal Reference Number	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	**Description**	
Name	CERTNO	
Datatype	String	
Description	Indicates Certificate Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0

TOP

CERTQT

Attribute	**Description**	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9]*</td></tr></table>

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String

Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description	
Name	BRKDETAILS	
Datatype		
Description	Includes Broker details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

BROKER

Attribute	Description	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description

Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description

Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String

Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description

Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	**Description**
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	**Description**
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	**Description**
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description

Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description

Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12
minLength	1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16
minLength	1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description

Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description	
Name	TIMEIND1	
Datatype	String	
Description	Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND2

Attribute	Description	
Name	TIMEIND2	
Datatype	String	
Description	Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4

Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT3

Attribute	Description	
Name	INSTRCDTXT3	
Datatype	String	
Description	Indicates the Instruction Code Text3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	Description	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	Description	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 5 minLength: 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 4 minLength: 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT3

Attribute	Description
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000 minLength: 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35 minLength: 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description	
Name	INSTRCDLT3	
Datatype	String	
Description	Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT4

Attribute	Description	
Name	INSTRCDLT4	
Datatype	String	
Description	Instruction Code 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT5

Attribute	Description	
Name	INSTRCDLT5	
Datatype	String	
Description	Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT

Attribute	Description	
Name	INSTRCDTXT	
Datatype	String	
Description	Indicates the Instruction Code Text	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5

Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Taxdetails-Main

Attribute	Description
Name	Taxdetails-Main
Datatype	
Description	Includes Tax main details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDLINFO2

Attribute	Description

Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description

Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	

Attribute	Description
minOccurs	0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES

Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3

Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String

Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number

Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	
Description	Includes Deal Limits details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEAL_WALKIN1

Attribute	**Description**	
Name	DEAL_WALKIN1	
Datatype		
Description	Includes Deal Walkin details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description

Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes Deal details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description	
Name	CPTY	
Datatype	String	
Description	Indicates Counter Party	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description	
Name	SKLOC	
Datatype	String	
Description	Indicates Safe Keeping Location	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates Accompany Withdraw Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEG_REFERNCENO

Attribute	**Description**	
Name	LEG_REFERNCENO	
Datatype	String	
Description	Indicates Leg User Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LGDESC

Attribute	**Description**	
Name	LGDESC	
Datatype	String	
Description	Indicates Leg Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CPTYDESC

Attribute	**Description**	
Name	CPTYDESC	
Datatype	String	
Description	Indicates Counterparty Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

SKLOCDESC

Attribute	**Description**	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits

Attribute	Description
Name	Deal-Limits
Datatype	
Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin

Attribute	Description
Name	Deal-Walkin
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10
	minLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	**Description**	
Name	CONTREF	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	**Description**	
Name	Tran-Tax-Appln	
Datatype		
Description	Includes Transaction Tax Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT

Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Includes Transaction Tax Liquidation Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

Deal-Limits-To

Attribute	**Description**	
Name	Deal-Limits-To	
Datatype		
Description	Includes Deal To Limits	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates Track Clean Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

PREVVERNO

Attribute	Description
Name	PREVVERNO
Datatype	Number
Description	Indicates Previous Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Includes Settlement Additional details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6

Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**	
Name	BNFINSTCVR6	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST1

Attribute	**Description**	
Name	BENEF_INST1	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	**Description**	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	**Description**
Name	BENEF_INST3

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST1

Attribute	**Description**	
Name	ORDER_CUST1	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST2

Attribute	**Description**	
Name	ORDER_CUST2	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String

Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 minLength: 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ACC_INST1

Attribute	Description	
Name	ACC_INST1	
Datatype	String	
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ACC_INST2

Attribute	Description	
Name	ACC_INST2	
Datatype	String	
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6

Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR2

Attribute	**Description**	
Name	BNFINSTCVR2	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3

Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String
Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5

Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST1

Attribute	**Description**	
Name	ORDER_CUST1	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST2

Attribute	**Description**	
Name	ORDER_CUST2	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST3

Attribute	**Description**	
Name	ORDER_CUST3	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST4

Attribute	**Description**
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST5

Attribute	**Description**	
Name	ORDER_CUST5	
Datatype	String	
Description	The Ordering Customer refers to the customer ordering the transfer	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_CUST6

Attribute	**Description**	
Name	ORDER_CUST6	
Datatype	String	
Description	Country to which the ordering customer belongs	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST1

Attribute	**Description**	
Name	ORDER_INST1	
Datatype	String	
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ORDER_INST2

Attribute	**Description**
Name	ORDER_INST2
Datatype	String

Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates Real Time Gross Settlement payment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

SNDR_INFO1

Attribute	**Description**	
Name	SNDR_INFO1	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO2

Attribute	**Description**	
Name	SNDR_INFO2	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO3

Attribute	**Description**
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO4

Attribute	**Description**	
Name	SNDR_INFO4	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO5

Attribute	**Description**	
Name	SNDR_INFO5	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

SNDR_INFO6

Attribute	**Description**	
Name	SNDR_INFO6	
Datatype	String	
Description	Indicates the sender information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

TRNFRTYP

Attribute	**Description**
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

ULT_BENEF1

Attribute	**Description**	
Name	ULT_BENEF1	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF2

Attribute	**Description**	
Name	ULT_BENEF2	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF3

Attribute	**Description**	
Name	ULT_BENEF3	
Datatype	String	
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

ULT_BENEF4

Attribute	**Description**

Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 1 pattern: [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	**Description**	
Name	PAYRCV	
Datatype	String	
Description	Pay / Receive Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	**Description**	
Name	RATECDDEFRD	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	**Description**	
Name	SPRDDFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	1
	pattern	[a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	**Description**
Name	TAG_CCY
Datatype	String
Description	Indicates Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Charge Details	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CLGNTW

Attribute	**Description**	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	**Description**	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	**Description**
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK
Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2

Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description

Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description

Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	**Description**	
Name	COMPTYP	
Datatype	String	
Description	Indicates Component Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal	
Restrictions	**Restrictions**	**Description**
	maxLength	25
	minLength	1

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String

Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String

Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Unrel-Unmatch

Attribute	Description
Name	Unrel-Unmatch
Datatype	
Description	Includes Unrel Unmatch details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

BRKID

Attribute	Description	
Name	BRKID	
Datatype	String	
Description	Indicates Broker Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates Walkin Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates Walkin Customer Media	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1

Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK
Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YTM_MASTER

Attribute	Description
Name	YTM_MASTER
Datatype	
Description	Includes Yield To Maturity Master details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates Leg Product Code
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates Portfolio
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates Safe Keeping Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates Accompany Withdraw Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates Auto MSTL A for On; M for Off
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,A

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates Leg User Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEG_REFERNCENO

Attribute	Description
Name	LEG_REFERNCENO
Datatype	String
Description	Indicates Leg User Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates Leg Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

Deal-Limits-To

Attribute	Description
Name	Deal-Limits-To
Datatype	
Description	Includes Deal To Limits
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Deal-Walkin-To

Attribute	Description
Name	Deal-Walkin-To
Datatype	
Description	Includes Deal Walkin To details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT1

Attribute	Description
Name	CONTRACT1
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

VERNO

Attribute	Description	
Name	VERNO	
Datatype	Number	
Description	Indicates Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

PREVVERNO

Attribute	Description	
Name	PREVVERNO	
Datatype	Number	
Description	Indicates Previous Version Number	
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

Settlement-Addl-Details

Attribute	Description	
Name	Settlement-Addl-Details	
Datatype		
Description	Includes Settlement Additional details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY

Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number

Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD

Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String

Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY
Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	**Description**	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	**Description**	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	**Description**	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	**Description**
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	**Description**	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	**Description**	
Name	INST_NO	
Datatype	String	
Description	Indicates the Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

INST_TYPE

Attribute	**Description**	
Name	INST_TYPE	
Datatype	String	
Description	Indicates the Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	1

TOP

INT_REIM_INST1

Attribute	**Description**
Name	INT_REIM_INST1
Datatype	String

Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 20 minLength: 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String

Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Payable Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Deal-Messages

Attribute	**Description**	
Name	Deal-Messages	
Datatype		
Description	Includes Deal Message details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	Indicates Advice Description
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Deal-Parties

Attribute	Description
Name	Deal-Parties
Datatype	
Description	Includes Deal Parties details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTY

Attribute	Description
Name	PTY
Datatype	String
Description	Indicates Party
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	Indicates Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	Indicates Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Netcons

Attribute	Description
Name	Deal-Netcons
Datatype	
Description	Includes Deal Net Cons details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	15
minLength	0
pattern	[A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	

Restrictions	Description
maxLength	25
minLength	1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	

Restrictions	Description
length	3
pattern	[A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Deal-Interest

Attribute	Description
Name	Deal-Interest
Datatype	
Description	Includes Deal Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>BS,CS,WI,BB,CB,LG</td></tr></table>

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String

Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTDAYS

Attribute	**Description**	
Name	INTDAYS	
Datatype	Number	
Description	Indicates Interest Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUMEX

Attribute	**Description**	
Name	CUMEX	
Datatype	String	
Description	Indicates Cum/Ex Coupon	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Unrel-Unmatch

Attribute	**Description**	
Name	Unrel-Unmatch	
Datatype		
Description	Includes Unrel Unmatch details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNMATCHED

Attribute	**Description**
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates Broker Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates Counterparty Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates Address 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description	
Name	ADDRLINE3	
Datatype	String	
Description	Indicates Address 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description	
Name	ADDRLINE4	
Datatype	String	
Description	Indicates Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

SCLNRISKLMTRK

Attribute	Description
Name	SCLNRISKLMTRK

Datatype	String
Description	Indicates Track Clean Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPSTLRISKLMTRK

Attribute	Description
Name	SPSTLRISKLMTRK
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TOTEXPLINE

Attribute	Description
Name	TOTEXPLINE
Datatype	String
Description	Indicates Total Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

UNDEXPLINE

Attribute	Description
Name	UNDEXPLINE
Datatype	String
Description	Indicates Undelivered Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

PAYBRN

Attribute	Description
Name	PAYBRN

Datatype	String
Description	Indicates the Payable Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates Pay Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

ACTMSTLDT

Attribute	Description
Name	ACTMSTLDT
Datatype	Date
Description	Indicates Actual MSTL Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description
Name	CERTNO
Datatype	String
Description	Indicates Certificate Number
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30
minLength	0

TOP

CERTQT

Attribute	Description
Name	CERTQT
Datatype	Number
Description	Indicates Certificate Quantity
Attributes	

Attribute	Description
minOccurs	0

TOP

DEAL_LIMITS

Attribute	Description
Name	DEAL_LIMITS
Datatype	
Description	Includes Deal Limits details
Attributes	

Attribute	Description
maxOccurs	2
minOccurs	0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates Walkin Customer Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates Walkin Customer Media
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates Address 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String

Description	Indicates Address 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates Address 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates Address 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9]*

TOP

DEAL_WALKIN

Attribute	Description
Name	DEAL_WALKIN
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF

Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates Undelivered Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates Total Exposure
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9]*

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates Counter Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

CONTRACT

Attribute	Description
Name	CONTRACT
Datatype	
Description	Includes Contract details
Attributes	**Attribute** / **Description** maxOccurs / 2 minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description

Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1 pattern / [a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String

Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number

Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 10 minLength: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN

Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2LBL2

Attribute	Description	
Name	TXNMIS2LBL2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3LBL3

Attribute	Description	
Name	TXNMIS3LBL3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4LBL4

Attribute	Description	
Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	Description	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	Description	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	Description	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	Description	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1

Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SCHEMEDESC

Attribute	**Description**	
Name	SCHEMEDESC	
Datatype	String	
Description	Indicates Scheme Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Sevws-Matched-Deal

Attribute	Description
Name	Sevws-Matched-Deal
Datatype	
Description	Includes Matched deal details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description
Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String

Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_PARTIES

Attribute	Description
Name	DEAL_PARTIES
Datatype	
Description	Includes Deal Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description

Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_LIMITS1

Attribute	Description
Name	DEAL_LIMITS1
Datatype	

Description	Includes Deal Limits details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates Track Clean Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates Track Pre-Settlement Risk Limit Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAL_WALKIN1

Attribute	Description
Name	DEAL_WALKIN1
Datatype	
Description	Includes Deal Walkin details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Indicates Text Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Includes Transaction Tax Association details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Includes Transaction Tax Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates Tax Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Indicates Tax Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

DEAL_CERTIFICATE_DETAILS

Attribute	Description
Name	DEAL_CERTIFICATE_DETAILS
Datatype	
Description	Includes Deal Certificate details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[A-Z0-9]*

TOP

CERTNO

Attribute	Description	
Name	CERTNO	
Datatype	String	
Description	Indicates Certificate Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0

TOP

CERTQT

Attribute	Description	
Name	CERTQT	
Datatype	Number	
Description	Indicates Certificate Quantity	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONTRACT

Attribute	Description	
Name	CONTRACT	
Datatype		
Description	Includes Contract details	
Attributes	**Attribute**	**Description**
	maxOccurs	2
	minOccurs	0

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

BRKDETAILS

Attribute	Description
Name	BRKDETAILS
Datatype	
Description	Includes Broker details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	Indicates the Broker Code of the broker involved in the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

BRKAMT

Attribute	Description
Name	BRKAMT
Datatype	Number
Description	Indicates the Brokerage Amount for the deal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String

Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description	Indicates Flexcube Contract Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

BROKER

Attribute	Description	
Name	BROKER	
Datatype	String	
Description	Indicates the Broker Code of the broker involved in the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1
	pattern	[a-zA-Z0-9]*

TOP

BRKAMT

Attribute	Description	
Name	BRKAMT	
Datatype	Number	
Description	Indicates the Brokerage Amount for the deal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

BRKCCY

Attribute	Description
Name	BRKCCY
Datatype	String
Description	Indicates the Brokerage Currency for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

DSCACR

Attribute	Description
Name	DSCACR
Datatype	String
Description	Consider for Discount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

BRKNAM

Attribute	Description
Name	BRKNAM
Datatype	String
Description	Indicates Broker name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Description
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

Brokerage-Details

Attribute	Description
Name	Brokerage-Details
Datatype	
Description	Indicates Brokerage details
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

BOOKCCY

Attribute	Description
Name	BOOKCCY
Datatype	String
Description	Indicates the Booking currency for the booked amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BKMTHD

Attribute	Description
Name	BKMTHD
Datatype	Number
Description	Indicates Booking Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOOKAMT

Attribute	Description
Name	BOOKAMT
Datatype	Number
Description	Indicates the Booking Amount for the brokerage.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LIQSTAT

Attribute	Description
Name	LIQSTAT
Datatype	String
Description	Indicates the liquidation status for the contract, whether the contract is liquidated.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

LREFNO

Attribute	Description
Name	LREFNO
Datatype	String
Description	Indicates Latest Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT

Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

RULE

Attribute	Description

Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10 minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String

Description	The Charge Component Code description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	This identifies the basic nature of a brokerage component. Each brokerage rule is defined by a ten-character code, called the Rule ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10; minLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCREQ

Attribute	Description
Name	ACCREQ
Datatype	String
Description	Indicates the Accrual required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGDESC

Attribute	Description
Name	CHGDESC
Datatype	String
Description	The Charge Component Code description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

LQDSTS

Attribute	Description
Name	LQDSTS
Datatype	String
Description	Indicates the Liquidation Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Details

Attribute	Description
Name	Settlement-Details
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String

Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Regulatory Report 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**
Name	ENV_CONT3
Datatype	String
Description	Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT4

Attribute	Description
Name	ENV_CONT4
Datatype	String
Description	Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT5

Attribute	Description
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TIMEIND3

Attribute	**Description**	
Name	TIMEIND3	
Datatype	String	
Description	Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT

Attribute	**Description**	
Name	INSTRCDLT	
Datatype	String	
Description	Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT1

Attribute	**Description**	
Name	INSTRCDLT1	
Datatype	String	
Description	Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDLT2

Attribute	**Description**	
Name	INSTRCDLT2	
Datatype	String	
Description	Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5
Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT4

Attribute	Description
Name	INSTRCDTXT4
Datatype	String
Description	Indicates the Instruction Code Text4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDTXT5

Attribute	Description
Name	INSTRCDTXT5
Datatype	String
Description	Indicates the Instruction Code Text5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

TRNTPCD

Attribute	Description
Name	TRNTPCD
Datatype	String
Description	Indicates Transaction Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5 minLength / 1

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Regulatory Report 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Regulatory Report 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Regulatory Report 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	Description	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	Description	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	Description	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

TIMEIND1

Attribute	Description
Name	TIMEIND1
Datatype	String
Description	Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND2

Attribute	Description
Name	TIMEIND2
Datatype	String
Description	Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TIMEIND3

Attribute	Description
Name	TIMEIND3
Datatype	String
Description	Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT

Attribute	Description
Name	INSTRCDLT
Datatype	String
Description	Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCDLT1

Attribute	Description
Name	INSTRCDLT1
Datatype	String
Description	Instruction Code 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT2

Attribute	Description
Name	INSTRCDLT2
Datatype	String
Description	Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT3

Attribute	Description
Name	INSTRCDLT3
Datatype	String
Description	Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT4

Attribute	Description
Name	INSTRCDLT4
Datatype	String
Description	Instruction Code 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCDLT5

Attribute	Description
Name	INSTRCDLT5

Datatype	String
Description	Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT

Attribute	Description
Name	INSTRCDTXT
Datatype	String
Description	Indicates the Instruction Code Text
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT1

Attribute	Description
Name	INSTRCDTXT1
Datatype	String
Description	Indicates the Instruction Code Text1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT2

Attribute	Description
Name	INSTRCDTXT2
Datatype	String
Description	Indicates the Instruction Code Text2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCDTXT3

Attribute	Description
Name	INSTRCDTXT3
Datatype	String
Description	Indicates the Instruction Code Text3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT4

Attribute	**Description**	
Name	INSTRCDTXT4	
Datatype	String	
Description	Indicates the Instruction Code Text4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCDTXT5

Attribute	**Description**	
Name	INSTRCDTXT5	
Datatype	String	
Description	Indicates the Instruction Code Text5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Taxdetails-Main

Attribute	**Description**	
Name	Taxdetails-Main	
Datatype		
Description	Includes Tax main details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SCHEME

Attribute	**Description**	
Name	SCHEME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	Indicates Scheme Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SECUDF

Attribute	Description
Name	SECUDF
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Sevws-Matched-Deal

Attribute	Description	
Name	Sevws-Matched-Deal	
Datatype		
Description	Includes Matched deal details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

VER

Attribute	Description
Name	VER
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

BUYLEG

Attribute	Description
Name	BUYLEG
Datatype	String
Description	Indicates Buy Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SELLEG

Attribute	Description
Name	SELLEG
Datatype	String
Description	Indicates Sell Leg Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date

TOP

MATCH

Attribute	Description

Name	MATCH
Datatype	Number
Description	Indicates Match Quantity

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGTYPE

Attribute	Description
Name	LEGTYPE
Datatype	String
Description	Indicates Leg Type
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [a-zA-Z0-9]{2}

TOP

UNMATCHED

Attribute	Description
Name	UNMATCHED
Datatype	Number
Description	Indicates Total Remaining
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTMATCHED

Attribute	Description
Name	TOTMATCHED
Datatype	String
Description	Indicates Total Matched
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z]

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates Deal Quantity

TOP

DEAL_MESSAGES

Attribute	Description
Name	DEAL_MESSAGES
Datatype	
Description	Includes Deal Message details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO6

Attribute	Description
Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	Number
Description	Indicates Version
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates Message
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	Indicates Party Identification
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	Indicates Party Name
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SNDRINFO1

Attribute	Description
Name	SNDRINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO2

Attribute	Description
Name	SNDRINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO3

Attribute	Description
Name	SNDRINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO4

Attribute	Description
Name	SNDRINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO5

Attribute	Description
Name	SNDRINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SNDRINFO6

Attribute	Description

Name	SNDRINFO6
Datatype	String
Description	Indicates Sender To Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYDTLS

Attribute	Description
Name	PARTYDTLS
Datatype	
Description	Includes Party details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String

Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDR4

Attribute	**Description**	
Name	ADDR4	
Datatype	String	
Description	Indicates Party Address 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_PARTIES

Attribute	**Description**	
Name	DEAL_PARTIES	
Datatype		
Description	Includes Deal Party details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates Leg Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PTYPE

Attribute	**Description**	
Name	PTYPE	
Datatype	String	
Description	Indicates Party Type	
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ADDR1

Attribute	**Description**
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PTYPE

Attribute	Description
Name	PTYPE
Datatype	String
Description	Indicates Party Type

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	Indicates Party Address 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR2

Attribute	Description
Name	ADDR2
Datatype	String
Description	Indicates Party Address 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR3

Attribute	Description
Name	ADDR3
Datatype	String
Description	Indicates Party Address 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ADDR4

Attribute	Description
Name	ADDR4
Datatype	String
Description	Indicates Party Address 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEAL_NETCONS

Attribute	Description
Name	DEAL_NETCONS
Datatype	
Description	Includes Deal Net cons details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates Leg Reference
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BUYSEL

Attribute	Description
Name	BUYSEL
Datatype	String
Description	Indicates Buy or Sell Bank Sell : BS Customer Sell : CS Withdraw : WI Bank Buy : BB Customer Buy : CB Lodge : LG
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / BS,CS,WI,BB,CB,LG

TOP

COMPTYP

Attribute	Description
Name	COMPTYP
Datatype	String
Description	Indicates Component Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	Indicates Component Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	Number
Description	Indicates Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate

TOP

AMTPCY

Attribute	Description
Name	AMTPCY
Datatype	Number
Description	Indicates Amount In Payment Currency
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SIGN

Attribute	Description
Name	SIGN
Datatype	String
Description	Indicates Sign (+/-)
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTDAYS

Attribute	Description
Name	INTDAYS
Datatype	Number
Description	Indicates Interest Days
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CUMEX

Attribute	Description
Name	CUMEX
Datatype	String
Description	Indicates Cum/Ex Coupon
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates Safe Keeping To Location
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates Safe Keeping To Account
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

Ytm-Master

Attribute	Description
Name	Ytm-Master
Datatype	
Description	Includes Yield To Maturity Master details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>2</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates Deal Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates Block Deal Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates Effective Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

YTM

Attribute	Description
Name	YTM
Datatype	Number
Description	Indicates Yield To Maturity(%)

TOP

Contract-Event-Log

Attribute	Description
Name	Contract-Event-Log

Datatype	
Description	Includes Contract Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXTCSTAT

Attribute	Description

Name	TXTCSTAT
Datatype	String
Description	Indicates Txt Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Closed : C Reversed : V Liquidated : L Hold : H Reversed : R Expired : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,V,L,H,R,X

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.70.4.SE-Deal-Reverse-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Master*
      - *FCCREF*
      - *XREF*
      - *VERNO*
    - *Deal-Master*
      - *FCCREF*
      - *XREF*
      - *VERNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key Response for SE Deal Contract Reverse operation

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	Reversal of Securities Deal Input Master Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Reversal of Securities Deal Input Master Type
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.71.RolloverSEDeal

Rollover of Securities Deal Input

2.71.1.SE-Deal-Rollover-Req-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *DEAL_MASTER*
    - *FCCREF*
    - *XREF*
    - *DSTLDT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for request of SE Deal contract Rollover

TOP

DEAL_MASTER

Attribute	Description
Name	DEAL_MASTER
Datatype	
Description	Includes Securities Deal Rollover Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.71.2.SE-Deal-Rollover-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *DEAL_MASTER*
    - *FCCREF*
    - *XREF*
    - *DSTLDT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for request of SE Deal contract Rollover

TOP

DEAL_MASTER

Attribute	Description
Name	DEAL_MASTER
Datatype	
Description	Includes Securities Deal Rollover Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.71.3.SE-Deal-Rollover-Res-Full-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *DEAL_MASTER*
    - *FCCREF*
    - *XREF*
    - *DSTLDT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Response of SE Deal contract Rollover

TOP

DEAL_MASTER

Attribute	Description
Name	DEAL_MASTER
Datatype	
Description	Includes Securities Deal Rollover Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.71.4.SE-Deal-Rollover-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-PK*
      - *FCCREF*
      - *XREF*
      - *VERNO*
    - *DEAL_MASTER*
      - *FCCREF*
      - *XREF*
      - *DSTLDT*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Primary Key Response for SE Deal Contract Contract Rollover

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-PK

Attribute	Description
Name	Deal-PK
Datatype	
Description	Includes Securities Deal Rollover Primary Key type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [A-Z0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates Version Number
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

DEAL_MASTER

Attribute	Description
Name	DEAL_MASTER
Datatype	
Description	Includes Securities Deal Rollover Master type details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates Flexcube Contract Reference Number
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Z0-9]*</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates Settlement Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.72.DeleteMarketCode

Deletion of Market Definition

2.72.1.SE-DeleteMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-Full*
    - *MKTCD*
    - *MKTDESC*
    - *MKTTYPE*
    - *MKTIDCD*
    - *OTCOSYSN*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*
    - *PRICECD*
    - *HOLTP*
    - *HOLCCY*
    - *CPNBAS*
    - *DIVDBAS*
    - *WARBAS*
    - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Deletion of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DIVDBAS

Attribute	Description	
Name	DIVDBAS	
Datatype	String	
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

WARBAS

Attribute	Description	
Name	WARBAS	
Datatype	String	
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

RIGBAS

Attribute	Description	
Name	RIGBAS	
Datatype	String	
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDYCNT

Attribute	**Description**	
Name	SPTDYCNT	
Datatype	String	
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	**Description**	
Name	SPTDAYS	
Datatype	Number	
Description	Indicates Spot Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKSPTDT

Attribute	**Description**	
Name	WEKSPTDT	
Datatype	String	
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	**Description**
Name	IFSPTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET

Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT

Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String

Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXMNTIND

Attribute	**Description**	
Name	EXMNTIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,P,

TOP

EXPRVMNT

Attribute	**Description**	
Name	EXPRVMNT	
Datatype	Number	
Description	Indicates Previous Months	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXDYEXDT

Attribute	**Description**	
Name	EXDYEXDT	
Datatype	Number	
Description	Indicates Expiry Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXWKDDT

Attribute	**Description**	
Name	EXWKDDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.72.2.SE-DeleteMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-IO*
    - *MKTCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Deletion of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.72.3.SE-DeleteMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-IO*
      - *MKTCD*
    - *Market-Master-Full*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*
      - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Deletion of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Deletion of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String

Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description

Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Market-Interest

Attribute	**Description**	
Name	Market-Interest	
Datatype		
Description	Includes Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description	
Name	ACDNTDENMET	
Datatype	String	
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description	
Name	ACDNTDENMETBS	
Datatype	String	
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTINCDT

Attribute	Description	
Name	ACDNTINCDT	
Datatype	String	
Description	Indicates Include To Date Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String

Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	Description	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	Description	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description	
Name	SPTMNTHIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number

Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.72.4.SE-DeleteMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-IO*
      - *MKTCD*
    - *Market-Master-PK*
      - *MKTCD*
    - *Market-Master-Full*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*

WARBAS
RIGBAS
SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*

- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*

STOPASSOC
TAXMOD
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Deletion of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Market-Master-PK

Attribute	Description
Name	Market-Master-PK
Datatype	
Description	Deletion of Market Definition PK Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Deletion of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description	
Name	MKTIDCD	
Datatype	String	
Description	Indicates Market Identifier Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	Description	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description	
Name	IFSPTHOL	
Datatype	String	
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXDTMT

Attribute	Description	
Name	EXDTMT	
Datatype	String	
Description	Indicates Expiry Date Method ROLLING : R FIXED : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDTCNTBAS

Attribute	Description	
Name	EXDTCNTBAS	
Datatype	String	
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKEXDT

Attribute	**Description**	
Name	WEKEXDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	**Description**	
Name	IFEXDTHOL	
Datatype	String	
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

MKTCAT

Attribute	**Description**	
Name	MKTCAT	
Datatype	String	
Description	Indicates Market Category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,T,

TOP

RENPERD

Attribute	**Description**
Name	RENPERD
Datatype	Number

Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String

Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Authorised time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY

Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String

Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number

Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String

Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description

Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX

Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.73.DeletePriceDtl

Deletion of Securities Price Definition

2.73.1.SE-DeletePriceDtl-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-Full*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Price-Detail*
      - *BRCODE*
      - *SECURITYCODE*
      - *PRICECODE*
      - *MARKETVALUEDATE*

PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Indicates full Request Price details.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECODE

Attribute	**Description**	
Name	PRICECODE	
Datatype	String	
Description	Indicates Price Code	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARKETVALUEDATE

Attribute	**Description**	
Name	MARKETVALUEDATE	
Datatype	Date	
Description	Indicates Market Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICEQUOTATIONMETHOD

Attribute	**Description**	
Name	PRICEQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description	
Name	INTERESTQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	Number	
Description	Indicates Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRICE

Attribute	Description	
Name	LCYPRICE	
Datatype	Number	
Description	Indicates Local Currency Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	Description	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.73.2.SE-DeletePriceDtl-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-IO*
    - *BRRCODE*
    - *SECURITYCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Indicates IO Price details in FCUBS Request.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.73.3.SE-DeletePriceDtl-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-Full*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*
        - *PRICECODE*

MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only Response of Delete Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Response of Delete Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Statuus	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Price-Detail

Attribute	**Description**	
Name	Price-Detail	
Datatype		
Description	Includes Price Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRCODE

Attribute	**Description**	
Name	BRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	**Description**	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	**Description**	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.73.4.SE-DeletePriceDtl-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-PK*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-Full*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Price-Detail*

BRCODE
SECURITYCODE
PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Indicates FCUBS Price details Primary Key Response.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-PK

Attribute	Description
Name	Price-Master-PK
Datatype	
Description	Indicates FCUBS Price details IO Response.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Indicates FCUBS Price details Full Response.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Statuus	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Price-Detail

Attribute	Description	
Name	Price-Detail	
Datatype		
Description	Includes Price Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRCODE

Attribute	Description	
Name	BRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECODE

Attribute	Description

Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number

Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error List.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning List.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.74.DeleteRecord

Deletion of Securities Market Price Codes

2.74.1.SE-DeleteRecord-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-Full*
    - *PCODE*
    - *PDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Indicates full Price Code details in FCUBS Request.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.74.2.SE-DeleteRecord-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-IO*
    - *PCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Indicates FCUBS Primary Key Request for deleting Proce Code

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.74.3.SE-DeleteRecord-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-IO*
      - *PCODE*
    - *Price-Code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-IO

Attribute	Description
Name	Price-Code-IO
Datatype	
Description	Indicates Product Code.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-Code-Full

Attribute	Description
Name	Price-Code-Full
Datatype	
Description	Indicates full Product details in FCUBS Response.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PDESC

Attribute	Description

Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.74.4.SE-DeleteRecord-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-IO*
      - *PCODE*
    - *Price-Code-PK*
      - *PCODE*
    - *Price-Code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*

DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-IO

Attribute	Description
Name	Price-Code-IO
Datatype	
Description	Indicates Price Code.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-Code-PK

Attribute	Description
Name	Price-Code-PK
Datatype	
Description	Indicates Price Code.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-Code-Full

Attribute	Description
Name	Price-Code-Full
Datatype	
Description	Indicates full Price details in FCUBS Response,

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.75.DeleteSEMarketCode

DeleteSEMarketCode

2.75.1.SE-DeleteSEMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*

OTSYSNARR
CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*

- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Smm-Full

Attribute	Description
Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description
Name	TRNVPRD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	**Description**	
Name	TBILLANNLMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISCCURRPRD

Attribute	**Description**	
Name	PRMDISCCURRPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTDSC

Attribute	**Description**	
Name	MKTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: enumeration; Description: ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

ADDM

Attribute	Description

Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

LDDB

Attribute	**Description**	
Name	LDDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	**Description**	
Name	LDINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	**Description**	
Name	DCNTMTHDSWIFTIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDCOUPN

Attribute	**Description**	
Name	PRDCOUPN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWASYNCREV

Attribute	Description	
Name	ALLWASYNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRDREV

Attribute	Description	
Name	PRDREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPNFREQ

Attribute	Description	
Name	COUPNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description	
Name	COUPNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	Description	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

Tps

Attribute	Description
Name	Tps
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DSC3

Attribute	**Description**	
Name	DSC3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Smed

Attribute	**Description**	
Name	Smed	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FRMDY

Attribute	**Description**	
Name	FRMDY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TODY

Attribute	**Description**	
Name	TODY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MNTHIND

Attribute	**Description**

Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.75.2.SE-DeleteSEMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-IO*
    - *MKTCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.75.3.SE-DeleteSEMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*
    - *OTSYSNARR*
    - *CTRYCD*
    - *LOCCCY*

SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
  RDNGBASIS
  RATDENMBASIS
  ADNM
  ADDM
  ADDB
  ADINCLDTODT
  LDNM
  LDDM
  LDDB
  LDINCLDTODT
  DCNTMTHDSWIFTIND
  PRDCOUPN
  ALLWASYNCREV
  PRDREV
  COUPNFREQ
  COUPNWEEKDAY
  COUPNADHRETOMNTHEND
  RVSNFREQ

RVSNWEEKDAY
RVSNADHRETOMNTHEND
ZEROINTFREXPRD
ACCRDCNTBASIS366
LQDDCNTBASIS366
Smsd
MKTCD
FRMDY
TODY
MONTHIND
FUTMON
DAYOFSPTDT
WEEKDAYOFSPTDT
IFSPTDTISHOL
Tps
PRDORMKTCD
SCHM
MODL
Tmit
CMPNT
EVNTFRASSOC
BASISAMTTAG
DFLTRATCD
DFLTWAIVR
ALLWRATECDAMMNDMENT
AMNDAFTRASSOC
STPASSOC
CLASSDSC
EVNTDSCR
DSC3
Smed
FRMDY
TODY
MNTHIND
PREVMNTHS
DAYOFEXDT
WEEKDAYOFEXDT
IFEXDTISHOL
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Smm-Full

Attribute	Description

Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description

Name	TRNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	**Description**	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	**Description**	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	**Description**	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	**Description**	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ZEROINTFREXPRD

Attribute	Description	
Name	ZEROINTFREXPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description	
Name	ACCRDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description	
Name	LQDDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Smsd

Attribute	Description	
Name	Smsd	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,F</td></tr></table>

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFSPTDT

Attribute	**Description**	
Name	DAYOFSPTDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Tps

Attribute	**Description**	
Name	Tps	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMKTCD

Attribute	**Description**
Name	PRDORMKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.75.4.SE-DeleteSEMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Smm-PK*
      - *MKTCD*
    - *Smm-IO*
      - *MKTCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Smm-PK

Attribute	Description
Name	Smm-PK
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.76.DeleteSEMarketPriceCodes

DeleteSEMarketPriceCodes

2.76.1.SE-DeleteSEMarketPriceCodes-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stpricd-Full

Attribute	Description
Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICE_CODE_DESC

Attribute	**Description**	
Name	PRICE_CODE_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.76.2.SE-DeleteSEMarketPriceCodes-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-IO*
    - *PRICE_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.76.3.SE-DeleteSEMarketPriceCodes-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stpricd-Full

Attribute	Description

Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.76.4.SE-DeleteSEMarketPriceCodes-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stpricd-PK*
      - *PRICE_CODE*
    - *Stpricd-IO*
      - *PRICE_CODE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stpricd-PK

Attribute	Description
Name	Stpricd-PK
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.77.DeleteSEPriceDetail

DeleteSEPriceDetail

2.77.1.SE-DeleteSEPriceDetail-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*

INTEREST_QUOTATION_METHOD
PRICE
INT_AUTH_STAT
LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description

Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

2.77.2.SE-DeleteSEPriceDetail-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-IO*
    - *BR_CODE*
    - *SECURITY_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.77.3.SE-DeleteSEPriceDetail-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*
      - *INTEREST_QUOTATION_METHOD*
      - *PRICE*
      - *INT_AUTH_STAT*

LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.77.4.SE-DeleteSEPriceDetail-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stprcmas-PK*
      - *SECURITY_CODE*
      - *BR_CODE*
    - *Stprcmas-IO*
      - *BR_CODE*
      - *SECURITY_CODE*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stprcmas-PK

Attribute	Description
Name	Stprcmas-PK
Datatype	
Description	

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.78.DeleteSESKLocationChange

DeleteSESKLocationChange

2.78.1.SE-DeleteSESKLocationChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*

- *PORTFOLIO*
- *PORTDESC*
- *CPTY*
- *CNTRPTYDESC*
- *SKLOCATION*
- *SKLOCTNDESC*
- *SKACCNT*
- *FRMTYP*
- *SKLOCTNTO*
- *SKLOCTNDESCTO*
- *SKACCNTTO*
- *SE_FORM_TYPE*

Csvwsevntlogdtls

- *DEAL_REFERENCE_NO*
- *ESN*
- *INPUTBY*
- *MAKDTTIME*
- *CHECHKERID*
- *CHKDTTIME*
- *AUTHSTAT*
- *ACTIVE*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*
  - *REIMINST4*
  - *RCVRCORRS1*

RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15

ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*

NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En

LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsdlmas-Full

Attribute	Description
Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description
Name	CNTRPTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESC

Attribute	Description
Name	SKLOCTNDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYP

Attribute	Description
Name	FRMTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	**Description**	
Name	Csvwsevntlogdtls	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEAL_REFERENCE_NO

Attribute	**Description**	
Name	DEAL_REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INPUTBY

Attribute	**Description**	
Name	INPUTBY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / A,

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3

Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	**Description**	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4

Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5

Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	**Description**	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST5

Attribute	**Description**	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

2.78.2.SE-DeleteSESKLocationChange-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-IO*
    - *CONTRACTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.78.3.SE-DeleteSESKLocationChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*
      - *PORTFOLIO*
      - *PORTDESC*
      - *CPTY*

- *CNTRPTYDESC*
- *SKLOCATION*
- *SKLOCTNDESC*
- *SKACCNT*
- *FRMTYP*
- *SKLOCTNTO*
- *SKLOCTNDESCTO*
- *SKACCNTTO*
- *SE_FORM_TYPE*

Csvwsevntlogdtls

- *DEAL_REFERENCE_NO*
- *ESN*
- *INPUTBY*
- *MAKDTTIME*
- *CHECHKERID*
- *CHKDTTIME*
- *AUTHSTAT*
- *ACTIVE*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE

- SR_NO
- EVENT
- EVENT_DATE
- MAKER_ID
- MAKER_DT_STAMP
- CHECKER_ID
- CHECKER_DT_STAMP
- Acvws-All-Ac-Entries
  - BRANCH
  - ACCOUNT
  - DR_CR
  - CODE
  - DATE
  - VALDT
  - CCY
  - FCY_AMOUNT
  - EXG_RATE
  - LCY_AMOUNT
- Csvws-Contract-Ovd
  - OVDMSGS
- Csvws-Contract
  - LEGREFNO
  - Csvws-Contract-Event-Seq
    - EVTCODE
    - EVENT_SEQ_NO
    - DESCRIPTION
  - Csvws-Contract-Event-Advice
    - ADVCD
    - SUPPRESS
    - PRIORITY
    - PRTYID
    - PRTYNAME
    - ADVDESC
    - ADDRS1
    - ADDRS2
    - ADDRS3
    - ADDRS4
    - MEDIA
    - DESCRIPTION
- FCUBS_ERROR_RESP
  - ERROR
    - ECODE
    - EDESC
- FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsdlmas-Full

Attribute	Description

Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description	
Name	CNTRPTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCATION

Attribute	Description	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCTNDESC

Attribute	Description	
Name	SKLOCTNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKACCNT

Attribute	Description	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,D,I,G,C</td></tr></table>

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECHKERID

Attribute	Description	
Name	CHECHKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	**Description**	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	**Description**	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	**Description**	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	**Description**	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.78.4.SE-DeleteSESKLocationChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsdlmas-PK*
      - *CONTRACTREFNO*
    - *Svsdlmas-IO*
      - *CONTRACTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsdlmas-PK

Attribute	Description
Name	Svsdlmas-PK
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.79.DeleteSESKLocationMaint

DeleteSESKLocationMaint

2.79.1.SE-DeleteSESKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

Skacc

SKACC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	**Description**	
Name	CORPACTAUTOCOLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	**Description**	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	**Description**	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BANKACCEP

Attribute	Description	
Name	BANKACCEP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Skacc

Attribute	Description
Name	Skacc

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.79.2.SE-DeleteSESKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-IO*
    - *SKLOCID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.79.3.SE-DeleteSESKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Skacc*
      - *SKACC*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,A

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MSGTOICS

Attribute	Description

Name	MSGTOICS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.79.4.SE-DeleteSESKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Skloc-PK*
      - *SKLOCID*
    - *Skloc-IO*
      - *SKLOCID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Skloc-PK

Attribute	Description
Name	Skloc-PK
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.80.DeleteSKLocationMaint

Deletion of Securities - Safe Keeping Location Maintenance

2.80.1.SE-DeleteSKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAC*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACPTN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullRequest

TOP

Sk-Location-Full

Attribute	Description
Name	Sk-Location-Full
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance Full Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.80.2.SE-DeleteSKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-IO*
    - *SKLOCID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.80.3.SE-DeleteSKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-IO*
      - *SKLOCID*
    - *Sk-Location-Full*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description
Name	Sk-Location-Full
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance Full Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.80.4.SE-DeleteSKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-IO*
      - *SKLOCID*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-Full*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*

MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance IO Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance PK Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sk-Location-Full

Attribute	Description
Name	Sk-Location-Full
Datatype	
Description	Deletion of Securities - Safe Keeping Location Maintenance Full Type

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	**Description**	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,I

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,E,O,

TOP

CORPACTAC

Attribute	**Description**	
Name	CORPACTAC	
Datatype	String	
Description	Indicates Corporation Action Collection Manual : M Auto : A	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.81.ModifyMarketCode

Modification of Market Definition

2.81.1.SE-ModifyMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-Full*
    - *MKTCD*
    - *MKTDESC*
    - *MKTTYPE*
    - *MKTIDCD*
    - *OTCOSYSN*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*
    - *PRICECD*
    - *HOLTP*
    - *HOLCCY*
    - *CPNBAS*
    - *DIVDBAS*
    - *WARBAS*
    - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Modification of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	**Description**	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	**Description**	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	**Description**	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	**Description**	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DIVDBAS

Attribute	Description	
Name	DIVDBAS	
Datatype	String	
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

WARBAS

Attribute	Description	
Name	WARBAS	
Datatype	String	
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

RIGBAS

Attribute	Description	
Name	RIGBAS	
Datatype	String	
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String

Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET

Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTNUMMET

Attribute	Description	
Name	ACDNTNUMMET	
Datatype	String	
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description	
Name	ACDNTDENMET	
Datatype	String	
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description	
Name	ACDNTDENMETBS	
Datatype	String	
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT

Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String

Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXMNTIND

Attribute	**Description**	
Name	EXMNTIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,P,

TOP

EXPRVMNT

Attribute	**Description**	
Name	EXPRVMNT	
Datatype	Number	
Description	Indicates Previous Months	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXDYEXDT

Attribute	**Description**	
Name	EXDYEXDT	
Datatype	Number	
Description	Indicates Expiry Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXWKDDT

Attribute	**Description**	
Name	EXWKDDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.81.2.SE-ModifyMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-IO*
    - *MKTCD*
    - *MKTDESC*
    - *MKTTYPE*
    - *MKTIDCD*
    - *OTCOSYSN*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*
    - *PRICECD*
    - *HOLTP*
    - *HOLCCY*
    - *CPNBAS*
    - *DIVDBAS*
    - *WARBAS*
    - *RIGBAS*
    - *SPTDTMET*
    - *SPTDYCNT*
    - *SPTDAYS*

WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MODNO
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

SPTMKTCD
SPTFRMDY
SPTTODY
SPTMNTHIND
SPTFUTMNT
SPTDYSPTDT
SPTWKDYSPT
SPTDTHOL
Market-Ex-Date
EXMKTCD
EXFRMDY
EXTODY
EXMNTIND
EXPRVMNT
EXDYEXDT
EXWKDDT
EXIFHLDY
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Modification of Market Definition IO Type

TOP

MKTCD

Attribute	Description	
Name	MKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String

Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD

Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String

Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String

Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String

Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String

Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	**Description**	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	**Description**	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	**Description**	
Name	SPTMNTHIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,F,

TOP

SPTFUTMNT

Attribute	**Description**	
Name	SPTFUTMNT	
Datatype	Number	
Description	Indicates Future Months	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,F,B</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.81.3.SE-ModifyMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-IO*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*
      - *RIGBAS*
      - *SPTDTMET*
      - *SPTDYCNT*

SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MODNO
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

- *Market-Spot-Date*
  - *SPTMKTCD*
  - *SPTFRMDY*
  - *SPTTODY*
  - *SPTMNTHIND*
  - *SPTFUTMNT*
  - *SPTDYSPTDT*
  - *SPTWKDYSPT*
  - *SPTDTHOL*
- *Market-Ex-Date*
  - *EXMKTCD*
  - *EXFRMDY*
  - *EXTODY*
  - *EXMNTIND*
  - *EXPRVMNT*
  - *EXDYEXDT*
  - *EXWKDDT*
  - *EXIFHLDY*
- *UDFDETAILS*
  - *FUNCTIONID*
  - *FIELD_NAME*
  - *DATATYPE*
  - *FIELD_VALUE*
  - *VAL_TYPE*

Market-Master-Full

- *MKTCD*
- *MKTDESC*
- *MKTTYPE*
- *MKTIDCD*
- *OTCOSYSN*
- *CTRYCD*
- *LOCCCY*
- *SKLOCID*
- *PRICECD*
- *HOLTP*
- *HOLCCY*
- *CPNBAS*
- *DIVDBAS*
- *WARBAS*
- *RIGBAS*
- *SPTDTMET*
- *SPTDYCNT*
- *SPTDAYS*
- *WEKSPTDT*

IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*

- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*

FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Modification of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description	
Name	HOLTP	
Datatype	String	
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	Description	
Name	HOLCCY	
Datatype	String	
Description	Indicates Holiday Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMET

Attribute	Description	
Name	SPTDTMET	
Datatype	String	
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDYCNT

Attribute	Description	
Name	SPTDYCNT	
Datatype	String	
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	Description	
Name	SPTDAYS	
Datatype	Number	
Description	Indicates Spot Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number

Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String

Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description

Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

RATDEN

Attribute	**Description**	
Name	RATDEN	
Datatype	String	
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTNUMMET

Attribute	**Description**	
Name	ACDNTNUMMET	
Datatype	String	
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	**Description**	
Name	ACDNTDENMET	
Datatype	String	
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	**Description**	
Name	LIDNTDENMTBS	
Datatype	String	
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LIDCINDT

Attribute	**Description**	
Name	LIDCINDT	
Datatype	String	
Description	Indicates Include To Date Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DCMTSWIND

Attribute	**Description**	
Name	DCMTSWIND	
Datatype	String	
Description	Indicates Swift Indicator	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PERCPN

Attribute	**Description**
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALWASYRV

Attribute	Description	
Name	ALWASYRV	
Datatype	String	
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PERREVN

Attribute	Description	
Name	PERREVN	
Datatype	String	
Description	Indicates Periodic Revision Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPNFRQ

Attribute	Description	
Name	CPNFRQ	
Datatype	String	
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	**Description**	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	**Description**	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	**Description**	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	**Description**	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description	
Name	EXFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXTODY

Attribute	Description	
Name	EXTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXMNTIND

Attribute	Description	
Name	EXMNTIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,P,

TOP

EXPRVMNT

Attribute	Description	
Name	EXPRVMNT	
Datatype	Number	
Description	Indicates Previous Months	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Modification of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,O,X,</td></tr></table>

TOP

MKTIDCD

Attribute	Description	
Name	MKTIDCD	
Datatype	String	
Description	Indicates Market Identifier Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	Description	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description

Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String

Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description

Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,E,U

TOP

TBICNTDR

Attribute	**Description**	
Name	TBICNTDR	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,,L,H

TOP

USBNDFM

Attribute	**Description**	
Name	USBNDFM	
Datatype	String	
Description	Indicates Use Bond Formula Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TBRENPED

Attribute	**Description**	
Name	TBRENPED	
Datatype	Number	
Description	Indicates Reinvestment Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBANNMET

Attribute	**Description**	
Name	TBANNMET	
Datatype	String	
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISPD

Attribute	Description	
Name	PRMDISPD	
Datatype	String	
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User Identification who inputted the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the inputting time of the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User Identification who authorised the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY

Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String

Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description
Name	ZEINTFOREXPD
Datatype	String
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDCBAS

Attribute	Description
Name	ACCRDCBAS
Datatype	String
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LIQDDCBAS

Attribute	Description
Name	LIQDDCBAS
Datatype	String
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Market-Spot-Date

Attribute	Description
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number

Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String

Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description

Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX

Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTASSO

Attribute	**Description**	
Name	AMNDAFTASSO	
Datatype	String	
Description	Indicates Amend After Association Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STOPASSOC

Attribute	**Description**
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXMOD

Attribute	**Description**	
Name	TAXMOD	
Datatype	String	
Description	Indicates Module	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.81.4.SE-ModifyMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-PK*
      - *MKTCD*
    - *Market-Master-IO*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*
      - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MODNO
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*

ACCRDCBAS
LIQDDCBAS
Market-Spot-Date
SPTMKTCD
SPTFRMDY
SPTTODY
SPTMNTHIND
SPTFUTMNT
SPTDYSPTDT
SPTWKDYSPT
SPTDTHOL
Market-Ex-Date
EXMKTCD
EXFRMDY
EXTODY
EXMNTIND
EXPRVMNT
EXDYEXDT
EXWKDDT
EXIFHLDY
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Market-Master-Full
MKTCD
MKTDESC
MKTTYPE
MKTIDCD
OTCOSYSN
CTRYCD
LOCCCY
SKLOCID
PRICECD
HOLTP
HOLCCY
CPNBAS
DIVDBAS
WARBAS
RIGBAS
SPTDTMET
SPTDYCNT

SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*
- *PERREVN*
- *CPNFRQ*

- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS

- *FUNCTIONID*

FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-PK

Attribute	Description
Name	Market-Master-PK
Datatype	
Description	Modification of Market Definition PK Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Modification of Market Definition IO Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTDESC

Attribute	Description	
Name	MKTDESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYPE

Attribute	Description	
Name	MKTTYPE	
Datatype	String	
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,O,X,

TOP

MKTIDCD

Attribute	Description	
Name	MKTIDCD	
Datatype	String	
Description	Indicates Market Identifier Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTCOSYSN

Attribute	Description	
Name	OTCOSYSN	
Datatype	String	
Description	Indicates Over The Counter Option System Narrative	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description	Indicates Country Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description	
Name	LOCCCY	
Datatype	String	
Description	Indicates Local Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Id	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECD

Attribute	Description	
Name	PRICECD	
Datatype	String	
Description	Indicates Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDTCNTBAS

Attribute	**Description**	
Name	EXDTCNTBAS	
Datatype	String	
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	**Description**	
Name	EXDAYS	
Datatype	Number	
Description	Indicates Expiry Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKEXDT

Attribute	**Description**	
Name	WEKEXDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	**Description**
Name	IFEXDTHOL
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String

Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description

Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTMKTCD

Attribute	**Description**	
Name	INTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RNDBAS

Attribute	**Description**	
Name	RNDBAS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

RATDEN

Attribute	**Description**	
Name	RATDEN	
Datatype	String	
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTNUMMET

Attribute	**Description**
Name	ACDNTNUMMET
Datatype	String

Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String

Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ZEINTFOREXPD

Attribute	**Description**	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	**Description**	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	**Description**	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	**Description**
Name	Market-Spot-Date
Datatype	
Description	Includes Spot date details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPTMKTCD

Attribute	Description
Name	SPTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPTFRMDY

Attribute	Description
Name	SPTFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

SPTTODY

Attribute	Description
Name	SPTTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTMNTHIND

Attribute	Description
Name	SPTMNTHIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number
Description	Indicates Future Months
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String

Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String

Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Modification of Market Definition Full Type

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

HOLTP

Attribute	Description
Name	HOLTP

Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description

Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	Indicates Spot Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKSPTDT

Attribute	Description
Name	WEKSPTDT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description
Name	IFSPTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String
Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDTCNTBAS

Attribute	Description	
Name	EXDTCNTBAS	
Datatype	String	
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description	
Name	EXDAYS	
Datatype	Number	
Description	Indicates Expiry Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKEXDT

Attribute	Description	
Name	WEKEXDT	
Datatype	String	
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description
Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

MKTCAT

Attribute	**Description**	
Name	MKTCAT	
Datatype	String	
Description	Indicates Market Category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,T,

TOP

RENPERD

Attribute	**Description**	
Name	RENPERD	
Datatype	Number	
Description	Indicates Reinvestment Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ANNMET

Attribute	**Description**	
Name	ANNMET	
Datatype	String	
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

BNDCNTNR

Attribute	**Description**	
Name	BNDCNTNR	
Datatype	String	
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorised : A UnAuthorised : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Market-Interest

Attribute	Description
Name	Market-Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTMKTCD

Attribute	Description
Name	INTMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNDBAS

Attribute	Description
Name	RNDBAS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDEN

Attribute	Description
Name	RATDEN
Datatype	String
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String

Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	Description	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	Description	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description	
Name	SPTMNTHIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number

Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	**Description**	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRTCD

Attribute	**Description**	
Name	DFLTRTCD	
Datatype	String	
Description	Indicates Default Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFLTWAIVER

Attribute	**Description**	
Name	DFLTWAIVER	
Datatype	String	
Description	Indicates Default Waiver Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALRTCDAMND

Attribute	**Description**	
Name	ALRTCDAMND	
Datatype	String	
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.82.ModifyPriceDtl

Modification of Securities Price Definition

2.82.1.SE-ModifyPriceDtl-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-Full*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *Price-Detail*
      - *BRCODE*
      - *SECURITYCODE*
      - *PRICECODE*
      - *MARKETVALUEDATE*

PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Indicates full Price details in FCUBS Request.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.82.2.SE-ModifyPriceDtl-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-IO*
    - *BRRCODE*
    - *SECURITYCODE*
    - *MODNO*
    - *Price-Detail*
      - *BRCODE*
      - *SECURITYCODE*
      - *PRICECODE*
      - *MARKETVALUEDATE*
      - *PRICEQUOTATIONMETHOD*
      - *INTERESTQUOTATIONMETHOD*
      - *PRICE*
      - *LCYPRICE*
      - *INTAUTHSTAT*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Request Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Indicates FCUBS IO Request For Modifying Price Details.

TOP

BRRCODE

Attribute	Description	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Price-Detail

Attribute	Description	
Name	Price-Detail	
Datatype		
Description	Includes Price Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRCODE

Attribute	Description

Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	**Description**	
Name	INTERESTQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	Number	
Description	Indicates Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRICE

Attribute	**Description**	
Name	LCYPRICE	
Datatype	Number	
Description	Indicates Local Currency Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	**Description**	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.82.3.SE-ModifyPriceDtl-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MODNO*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*
        - *PRICECODE*
        - *MARKETVALUEDATE*
        - *PRICEQUOTATIONMETHOD*
        - *INTERESTQUOTATIONMETHOD*
        - *PRICE*
        - *LCYPRICE*
        - *INTAUTHSTAT*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*

FIELD_VALUE
VAL_TYPE
Price-Master-Full
BRRCODE
SECURITYCODE
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Price-Detail
BRCODE
SECURITYCODE
PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only Response of Modify Price Details

TOP

BRRCODE

Attribute	Description	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Price-Detail

Attribute	Description	
Name	Price-Detail	
Datatype		
Description	Includes Price Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRCODE

Attribute	Description

Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	**Description**	
Name	INTERESTQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	Number	
Description	Indicates Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRICE

Attribute	**Description**	
Name	LCYPRICE	
Datatype	Number	
Description	Indicates Local Currency Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	**Description**	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Response of Modify Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date

Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	**Description**	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	**Description**	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.82.4.SE-ModifyPriceDtl-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-PK*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MODNO*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*
        - *PRICECODE*
        - *MARKETVALUEDATE*
        - *PRICEQUOTATIONMETHOD*
        - *INTERESTQUOTATIONMETHOD*
        - *PRICE*
        - *LCYPRICE*
        - *INTAUTHSTAT*
      - *UDFDETAILS*

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Price-Master-Full
BRRCODE
SECURITYCODE
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Price-Detail
BRCODE
SECURITYCODE
PRICECODE
MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-PK

Attribute	Description
Name	Price-Master-PK
Datatype	
Description	Indicates Branch Code and Security Code.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Indicates Modofication details in FCUBS Response.

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Indicates full Price details in FCUBS Response.

TOP

BRRCODE

Attribute	Description	
Name	BRRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description

Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String

Description	Indicates Authorization Status Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Statuus
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Price-Detail

Attribute	Description
Name	Price-Detail
Datatype	
Description	Includes Price Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRCODE

Attribute	Description
Name	BRCODE
Datatype	String
Description	Indicates Branch Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	**Description**	
Name	SECURITYCODE	
Datatype	String	
Description	Indicates Security Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICECODE

Attribute	**Description**	
Name	PRICECODE	
Datatype	String	
Description	Indicates Price Code	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARKETVALUEDATE

Attribute	**Description**	
Name	MARKETVALUEDATE	
Datatype	Date	
Description	Indicates Market Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICEQUOTATIONMETHOD

Attribute	**Description**	
Name	PRICEQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	PPM,PPR,PRI,PRM,YTM,

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description	
Name	INTERESTQUOTATIONMETHOD	
Datatype	String	
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

PRICE

Attribute	Description	
Name	PRICE	
Datatype	Number	
Description	Indicates Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYPRICE

Attribute	Description	
Name	LCYPRICE	
Datatype	Number	
Description	Indicates Local Currency Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTAUTHSTAT

Attribute	Description	
Name	INTAUTHSTAT	
Datatype	String	
Description	Indicates Interest Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.83.ModifyRecord

Modification of Securities Market Price Codes

2.83.1.SE-ModifyRecord-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-Full*
    - *PCODE*
    - *PDESC*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Indicates full Price Code details in FCUBS Request.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String

Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.83.2.SE-ModifyRecord-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-IO*
    - *PCODE*
    - *PDESC*
    - *MODNO*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Contains IO Request for Modify SE Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.83.3.SE-ModifyRecord-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-code-IO*
      - *PCODE*
      - *PDESC*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Price-code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*

AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Contains Input Only Response of Modify Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Contains Full Response of Modify Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String

Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.83.4.SE-ModifyRecord-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-PK*
      - *PCODE*
    - *Price-code-IO*
      - *PCODE*
      - *PDESC*
      - *MODNO*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*
        - *VAL_TYPE*
    - *Price-code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*

CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-PK

Attribute	Description
Name	Price-Code-PK
Datatype	
Description	Contains Primary Key Response of Modify Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Contains Input Only Response of Modify Record

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PDESC

Attribute	Description
Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Price-code-Full

Attribute	Description
Name	Price-code-Full
Datatype	
Description	Contains Full Response of Modify Record

TOP

PCODE

Attribute	**Description**	
Name	PCODE	
Datatype	String	
Description	Indicates Market Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PDESC

Attribute	**Description**	
Name	PDESC	
Datatype	String	
Description	Indicates Price Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.84.ModifySEMarketCode

ModifySEMarketCode

2.84.1.SE-ModifySEMarketCode-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*

OTSYSNARR
CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*

- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Smm-Full

Attribute	Description
Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description
Name	TRNVPRD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	**Description**	
Name	TBILLANNLMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISCCURRPRD

Attribute	**Description**	
Name	PRMDISCCURRPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTDSC

Attribute	**Description**	
Name	MKTDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,L,C</td></tr></table>

TOP

HOLCCY

Attribute	Description
Name	HOLCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMTHD

Attribute	**Description**	
Name	SPTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	**Description**	
Name	SPTDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	**Description**	
Name	SPTDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

ADDM

Attribute	Description

Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

LDDB

Attribute	**Description**	
Name	LDDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	**Description**	
Name	LDINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	**Description**	
Name	DCNTMTHDSWIFTIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDCOUPN

Attribute	**Description**	
Name	PRDCOUPN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWASYNCREV

Attribute	Description	
Name	ALLWASYNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRDREV

Attribute	Description	
Name	PRDREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPNFREQ

Attribute	Description	
Name	COUPNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description	
Name	COUPNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description
Name	COUPNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RVSNFREQ

Attribute	Description
Name	RVSNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description
Name	RVSNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description
Name	RVSNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

Tps

Attribute	Description
Name	Tps
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description

Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.84.2.SE-ModifySEMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-IO*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*
    - *OTSYSNARR*
    - *CTRYCD*
    - *LOCCCY*
    - *SKLOCID*

PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*
- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

FRMDY
TODY
MONTHIND
FUTMON
DAYOFSPTDT
WEEKDAYOFSPTDT
IFSPTDTISHOL
Smed
FRMDY
TODY
MNTHIND
PREVMNTHS
DAYOFEXDT
WEEKDAYOFEXDT
IFEXDTISHOL
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description
Name	TRNVPRD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,C</td></tr></table>

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,R,F,U</td></tr></table>

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,W</td></tr></table>

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXTDTMTHD

Attribute	**Description**	
Name	EXTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDAYSCNTBASIS

Attribute	**Description**	
Name	EXDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	**Description**	
Name	EXDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	Description	
Name	WEEKDAYOFEXDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description	
Name	IFEXDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,N</td></tr></table>

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,</td></tr></table>

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

ADDB

Attribute	**Description**	
Name	ADDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ADINCLDTODT

Attribute	**Description**	
Name	ADINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LDNM

Attribute	**Description**	
Name	LDNM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	**Description**	
Name	LDDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

LDDB

Attribute	Description	
Name	LDDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	Description	
Name	LDINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	Description	
Name	DCNTMTHDSWIFTIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDCOUPN

Attribute	Description	
Name	PRDCOUPN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description
Name	COUPNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RVSNFREQ

Attribute	Description
Name	RVSNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description
Name	RVSNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description
Name	RVSNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,Y,D</td></tr></table>

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,Y,D</td></tr></table>

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,F</td></tr></table>

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.84.3.SE-ModifySEMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-Full*
    - *MKTCAT*
    - *RNVPRD*
    - *ANNLMTHD*
    - *BDCN*
    - *BDCD*
    - *TDCN*
    - *TDCD*
    - *UBF*
    - *TRNVPRD*
    - *TBILLANNLMTHD*
    - *PRMDISCCURRPRD*
    - *MKTCD*
    - *MKTDSC*
    - *MKTTYP*
    - *MKIDCD*
    - *OTSYSNARR*
    - *CTRYCD*
    - *LOCCCY*

SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
  RDNGBASIS
  RATDENMBASIS
  ADNM
  ADDM
  ADDB
  ADINCLDTODT
  LDNM
  LDDM
  LDDB
  LDINCLDTODT
  DCNTMTHDSWIFTIND
  PRDCOUPN
  ALLWASYNCREV
  PRDREV
  COUPNFREQ
  COUPNWEEKDAY
  COUPNADHRETOMNTHEND
  RVSNFREQ

- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_ERROR_RESP

ERROR

- *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Smm-Full

Attribute	Description

Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,I,T

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,E,U

TOP

TDCD

Attribute	Description
Name	TDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,H

TOP

UBF

Attribute	Description
Name	UBF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRNVPRD

Attribute	Description

Name	TRNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTTYP

Attribute	Description	
Name	MKTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,O,X

TOP

MKIDCD

Attribute	Description	
Name	MKIDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

OTSYSNARR

Attribute	Description	
Name	OTSYSNARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CTRYCD

Attribute	Description	
Name	CTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CPNBASIS

Attribute	Description
Name	CPNBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

DVDNDBASIS

Attribute	Description
Name	DVDNDBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

WARRNTBASIS

Attribute	Description
Name	WARRNTBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,P,H</td></tr></table>

TOP

RYTSBASIS

Attribute	Description
Name	RYTSBASIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXTDTMTHD

Attribute	Description	
Name	EXTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description	
Name	EXDAYSCNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

EXDAYS

Attribute	Description	
Name	EXDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,N

TOP

RATDENMBASIS

Attribute	Description
Name	RATDENMBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADNM

Attribute	Description
Name	ADNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	Description
Name	ADDM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,360,365,ACTUAL</td></tr></table>

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	**Description**	
Name	COUPNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	**Description**	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	**Description**	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	**Description**	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,F</td></tr></table>

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFSPTDT

Attribute	**Description**	
Name	DAYOFSPTDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFSPTDT

Attribute	**Description**	
Name	WEEKDAYOFSPTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Tps

Attribute	**Description**	
Name	Tps	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMKTCD

Attribute	**Description**
Name	PRDORMKTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SCHM

Attribute	Description
Name	SCHM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPASSOC

Attribute	Description
Name	STPASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLASSDSC

Attribute	Description
Name	CLASSDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTDSCR

Attribute	Description
Name	EVNTDSCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

DSC3

Attribute	Description
Name	DSC3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MNTHIND

Attribute	**Description**	
Name	MNTHIND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,F

TOP

PREVMNTHS

Attribute	**Description**	
Name	PREVMNTHS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DAYOFEXDT

Attribute	**Description**	
Name	DAYOFEXDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEEKDAYOFEXDT

Attribute	**Description**	
Name	WEEKDAYOFEXDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	**Description**
Name	IFEXDTISHOL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.84.4.SE-ModifySEMarketCode-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Smm-PK*
      - *MKTCD*
    - *Smm-IO*
      - *RNVPRD*
      - *ANNLMTHD*
      - *BDCN*
      - *BDCD*
      - *TDCN*
      - *TDCD*
      - *UBF*
      - *TRNVPRD*
      - *TBILLANNLMTHD*
      - *PRMDISCCURRPRD*
      - *MKTCD*
      - *MKTDSC*
      - *MKTTYP*
      - *MKIDCD*
      - *OTSYSNARR*

CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*
- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*

ACCRDCNTBASIS366
LQDDCNTBASIS366
Smsd
FRMDY
TODY
MONTHIND
FUTMON
DAYOFSPTDT
WEEKDAYOFSPTDT
IFSPTDTISHOL
Smed
FRMDY
TODY
MNTHIND
PREVMNTHS
DAYOFEXDT
WEEKDAYOFEXDT
IFEXDTISHOL
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Smm-PK

Attribute	Description
Name	Smm-PK
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

RNVPRD

Attribute	Description
Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,H

TOP

TDCN

Attribute	**Description**	
Name	TDCN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,E,U

TOP

TDCD

Attribute	**Description**	
Name	TDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,H

TOP

UBF

Attribute	**Description**	
Name	UBF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNVPRD

Attribute	**Description**	
Name	TRNVPRD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	Description
Name	TBILLANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,S,O,X</td></tr></table>

TOP

MKIDCD

Attribute	Description
Name	MKIDCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

LOCCCY

Attribute	Description
Name	LOCCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRYCCD

Attribute	Description
Name	PRYCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

HOLTYP

Attribute	Description
Name	HOLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBASIS

Attribute	**Description**	
Name	CPNBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DVDNDBASIS

Attribute	**Description**	
Name	DVDNDBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

WARRNTBASIS

Attribute	**Description**	
Name	WARRNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

RYTSBASIS

Attribute	**Description**	
Name	RYTSBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMTHD

Attribute	Description
Name	SPTDTMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,B,F</td></tr></table>

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,R,F</td></tr></table>

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,W</td></tr></table>

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	**Description**	
Name	IFEXDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Smi

Attribute	**Description**	
Name	Smi	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RDNGBASIS

Attribute	Description	
Name	RDNGBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

RATDENMBASIS

Attribute	Description	
Name	RATDENMBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ADNM

Attribute	Description	
Name	ADNM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	Description	
Name	ADDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

ADDB

Attribute	Description
Name	ADDB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,C

TOP

ADINCLDTODT

Attribute	Description
Name	ADINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LDNM

Attribute	Description
Name	LDNM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description
Name	LDDM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,360,365,ACTUAL

TOP

LDDB

Attribute	Description
Name	LDDB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,A,C</td></tr></table>

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

COUPNADHRETOMNTHEND

Attribute	Description
Name	COUPNADHRETOMNTHEND
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RVSNFREQ

Attribute	**Description**	
Name	RVSNFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	**Description**	
Name	RVSNWEEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	**Description**	
Name	RVSNADHRETOMNTHEND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ZEROINTFREXPRD

Attribute	**Description**	
Name	ZEROINTFREXPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

LQDDCNTBASIS366

Attribute	Description
Name	LQDDCNTBASIS366
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,Y,D

TOP

Smsd

Attribute	Description
Name	Smsd
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description

Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,C,F

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.85.ModifySEMarketPriceCodes

ModifySEMarketPriceCodes

2.85.1.SE-ModifySEMarketPriceCodes-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stpricd-Full

Attribute	Description
Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRICE_CODE_DESC

Attribute	**Description**	
Name	PRICE_CODE_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.85.2.SE-ModifySEMarketPriceCodes-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-IO*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.85.3.SE-ModifySEMarketPriceCodes-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-Full*
    - *PRICE_CODE*
    - *PRICE_CODE_DESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stpricd-Full

Attribute	Description

Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.85.4.SE-ModifySEMarketPriceCodes-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stpricd-PK*
      - *PRICE_CODE*
    - *Stpricd-IO*
      - *PRICE_CODE*
      - *PRICE_CODE_DESC*
      - *MAKER*
      - *MAKERSTAMP*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stpricd-PK

Attribute	Description
Name	Stpricd-PK
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL

Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.86.ModifySEPriceDetail

ModifySEPriceDetail

2.86.1.SE-ModifySEPriceDetail-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*

INTEREST_QUOTATION_METHOD
PRICE
INT_AUTH_STAT
LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description

Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

2.86.2.SE-ModifySEPriceDetail-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-IO*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *MAKER*
    - *MAKERSTAMP*
    - *Stprcdtl*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*
      - *INTEREST_QUOTATION_METHOD*
      - *PRICE*
      - *INT_AUTH_STAT*
      - *LCY_PRICE*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.86.3.SE-ModifySEPriceDetail-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-Full*
    - *BR_CODE*
    - *SECURITY_CODE*
    - *SECUTRIY_DESC*
    - *BRANCH_NAME*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Stprcdtl*
      - *PRICE_CODE*
      - *MARKET_VALUE_DATE*
      - *PRICE_QUOTATION_METHOD*
      - *INTEREST_QUOTATION_METHOD*
      - *PRICE*
      - *INT_AUTH_STAT*

LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Stprcmas-Full

Attribute	Description
Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description	
Name	BR_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITY_CODE

Attribute	Description	
Name	SECURITY_CODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECUTRIY_DESC

Attribute	Description	
Name	SECUTRIY_DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MARKET_VALUE_DATE

Attribute	Description
Name	MARKET_VALUE_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRICE_QUOTATION_METHOD

Attribute	Description
Name	PRICE_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	Description
Name	INTEREST_QUOTATION_METHOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,F

TOP

PRICE

Attribute	Description
Name	PRICE

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.86.4.SE-ModifySEPriceDetail-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stprcmas-PK*
      - *SECURITY_CODE*
      - *BR_CODE*
    - *Stprcmas-IO*
      - *BR_CODE*
      - *SECURITY_CODE*
      - *MAKER*
      - *MAKERSTAMP*
      - *Stprcdtl*
        - *MARKET_VALUE_DATE*
        - *PRICE_QUOTATION_METHOD*
        - *INTEREST_QUOTATION_METHOD*
        - *PRICE*
        - *INT_AUTH_STAT*
        - *LCY_PRICE*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stprcmas-PK

Attribute	Description
Name	Stprcmas-PK
Datatype	
Description	

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description

Name	BR_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

MARKET_VALUE_DATE

Attribute	**Description**	
Name	MARKET_VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICE_QUOTATION_METHOD

Attribute	**Description**	
Name	PRICE_QUOTATION_METHOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	**Description**	
Name	INTEREST_QUOTATION_METHOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,,F

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INT_AUTH_STAT

Attribute	**Description**

Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.87.ModifySESKLocationChange

ModifySESKLocationChange

2.87.1.SE-ModifySESKLocationChange-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*

PORTFOLIO
PORTDESC
CPTY
CNTRPTYDESC
SKLOCATION
SKLOCTNDESC
SKACCNT
FRMTYP
SKLOCTNTO
SKLOCTNDESCTO
SKACCNTTO
SE_FORM_TYPE

Csvwsevntlogdtls

DEAL_REFERENCE_NO
ESN
INPUTBY
MAKDTTIME
CHECHKERID
CHKDTTIME
AUTHSTAT
ACTIVE

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*
  - *REIMINST4*
  - *RCVRCORRS1*

RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15

ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*

NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En

LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Svsdlmas-Full

Attribute	Description
Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description
Name	CNTRPTYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESC

Attribute	Description
Name	SKLOCTNDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

FRMTYP

Attribute	Description
Name	FRMTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,U</td></tr></table>

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / A,

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	Description	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	Description	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDIND

Attribute	**Description**	
Name	LIQDIND	
Datatype	String	
Description	Indicates Liquidated Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	**Description**	
Name	ERIAMT	
Datatype	Number	
Description	Indicates ERI Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GENMSG

Attribute	**Description**	
Name	GENMSG	
Datatype	String	
Description	Indicates Generate Message Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	**Description**	
Name	RATECD	
Datatype	String	
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	**Description**	
Name	COVERBY	
Datatype	String	
Description	Indicates Cover By Clearing : C Message : M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,M

TOP

RTGSPMNT

Attribute	**Description**	
Name	RTGSPMNT	
Datatype	String	
Description	Indicates RTGS Payment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	**Description**	
Name	BANKPRIOR	
Datatype	String	
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	**Description**

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3

Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	**Description**	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	**Description**	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	**Description**	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	**Description**	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4

Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	**Description**	
Name	ULTBEN1	
Datatype	String	
Description	Indicates Ultimate Beneficiary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN2

Attribute	**Description**	
Name	ULTBEN2	
Datatype	String	
Description	Indicates Ultimate Beneficiary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5

Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

2.87.2.SE-ModifySESKLocationChange-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-IO*
    - *CONTRACTREFNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *Svsdldtl*
      - *PORTFOLIO*
      - *CPTY*
      - *SKLOCATION*
      - *SKACCNT*
      - *FRMTYP*
      - *SKLOCTNTO*
      - *SKACCNTTO*
      - *SE_FORM_TYPE*
    - *Misdetails*
      - *CONREFNO*

MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4

- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*

ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Csvws-Contract-En
LEGREFNO
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Advice
SUPPRESS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

QUOTEBY

Attribute	**Description**	
Name	QUOTEBY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

SECTYSERIES

Attribute	**Description**	
Name	SECTYSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

SETMETD

Attribute	**Description**	
Name	SETMETD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	**Description**	
Name	DEALQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I,G,C

TOP

SKLOCTNTO

Attribute	**Description**	
Name	SKLOCTNTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNTTO

Attribute	**Description**	
Name	SKACCNTTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3

Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	**Description**	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.87.3.SE-ModifySESKLocationChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-Full*
    - *PRD*
    - *CONTRACTREFNO*
    - *USRREF*
    - *VERNO*
    - *LATVERNO*
    - *SECTYCD*
    - *QUOTEBY*
    - *SECTYSERIES*
    - *TXNDT*
    - *TRADEDT*
    - *SETMETD*
    - *DEALQTY*
    - *DSTLDT*
    - *PRDDESC*
    - *Svsdldtl*
      - *PORTFOLIO*
      - *PORTDESC*
      - *CPTY*

- *CNTRPTYDESC*
- *SKLOCATION*
- *SKLOCTNDESC*
- *SKACCNT*
- *FRMTYP*
- *SKLOCTNTO*
- *SKLOCTNDESCTO*
- *SKACCNTTO*
- *SE_FORM_TYPE*

Csvwsevntlogdtls

- *DEAL_REFERENCE_NO*
- *ESN*
- *INPUTBY*
- *MAKDTTIME*
- *CHECHKERID*
- *CHKDTTIME*
- *AUTHSTAT*
- *ACTIVE*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*

TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8

- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*

IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4

INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5

DRCRIND

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*

PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Assoc
INTCOMP
CRRATEESN
RULE
WAIVER
Appln
INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT
Liqdmaster
INTCOMP
TAXCCY
TAXAMNT
Issrtax
INTCOMP
CRRATESN
RATECOD
WAIVER
Csvws-Contract-En
LEGREFNO
Sevws-Event-Log
REFERENCE

SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Svsdlmas-Full

Attribute	Description

Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description	
Name	CNTRPTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCATION

Attribute	Description	
Name	SKLOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCTNDESC

Attribute	Description	
Name	SKLOCTNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKACCNT

Attribute	Description	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,D,I,G,C</td></tr></table>

TOP

SKLOCTNTO

Attribute	Description
Name	SKLOCTNTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description	
Name	MAKDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHECHKERID

Attribute	Description	
Name	CHECHKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	Description	
Name	CHKDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,U

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Charges

Attribute	**Description**	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD

Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	**Description**	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Indicates tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACCBRN

Attribute	**Description**	
Name	ACCBRN	
Datatype	String	
Description	Indicates Branch	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCCCY

Attribute	Description	
Name	ACCCCY	
Datatype	String	
Description	Indicates Account Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETIND

Attribute	Description	
Name	NETIND	
Datatype	String	
Description	Indicates Netting Indicator Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	**Description**	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	**Description**	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	Description	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	**Description**	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	**Description**	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description	
Name	ITIMEIND2	
Datatype	String	
Description	Indicates Time Indicator 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKER_DT_STAMP

Attribute	Description
Name	CHECKER_DT_STAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Acvws-All-Ac-Entries

Attribute	Description
Name	Acvws-All-Ac-Entries
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CODE

Attribute	Description
Name	CODE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

ADVDESC

Attribute	Description	
Name	ADVDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.87.4.SE-ModifySESKLocationChange-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsdlmas-PK*
      - *CONTRACTREFNO*
    - *Svsdlmas-IO*
      - *CONTRACTREFNO*
      - *SECTYCD*
      - *QUOTEBY*
      - *SECTYSERIES*
      - *SETMETD*
      - *DEALQTY*
      - *DSTLDT*
      - *Svsdldtl*
        - *PORTFOLIO*
        - *CPTY*
        - *SKLOCATION*
        - *SKACCNT*
        - *FRMTYP*
        - *SKLOCTNTO*
        - *SKACCNTTO*

SE_FORM_TYPE

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFXRATE

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*

ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*

ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Taxheadmaster
REFERENCE_NO
Csvws-Contract-En
LEGREFNO
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Advice
SUPPRESS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsdlmas-PK

Attribute	Description
Name	Svsdlmas-PK
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

SECTYSERIES

Attribute	**Description**	
Name	SECTYSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

SETMETD

Attribute	**Description**	
Name	SETMETD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	**Description**	
Name	DEALQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DSTLDT

Attribute	**Description**	
Name	DSTLDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Svsdldtl

Attribute	Description
Name	Svsdldtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKACCNT

Attribute	Description
Name	SKACCNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I,G,C

TOP

SKLOCTNTO

Attribute	**Description**	
Name	SKLOCTNTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCNTTO

Attribute	**Description**	
Name	SKACCNTTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SE_FORM_TYPE

Attribute	**Description**	
Name	SE_FORM_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC

Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String

Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String

Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4

Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	**Description**	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.88.ModifySESKLocationMaint

ModifySESKLocationMaint

2.88.1.SE-ModifySESKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*

AUTHSTAT

Skacc

SKACC

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	**Description**	
Name	CORPACTAUTOCOLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	**Description**	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	**Description**	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Skacc

Attribute	Description
Name	Skacc

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

2.88.2.SE-ModifySESKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-IO*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *Skacc*
      - *SKACC*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description

Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,A

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Skacc

Attribute	**Description**	
Name	Skacc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.88.3.SE-ModifySESKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAUTOCOLL*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACCEP*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Skacc*
      - *SKACC*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,A

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

MSGTOICS

Attribute	Description

Name	MSGTOICS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BANKACCEP

Attribute	Description
Name	BANKACCEP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.88.4.SE-ModifySESKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Skloc-PK*
      - *SKLOCID*
    - *Skloc-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAUTOCOLL*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACCEP*
      - *MAKER*
      - *MAKERSTAMP*
      - *Skacc*
        - *SKACC*
      - *UDFDETAILS*
        - *FLDNAM*

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Skloc-PK

Attribute	Description
Name	Skloc-PK
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLOCDESC

Attribute	Description

Name	SKLOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description
Name	CORPACTAUTOCOLL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	**Description**	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	**Description**	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BANKACCEP

Attribute	**Description**	
Name	BANKACCEP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.89.ModifySKLocationMaint

Modification of Securities - Safe Keeping Location Maintenance

2.89.1.SE-ModifySKLocationMaint-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-Full*
    - *SKLOCID*
    - *SKLOCDESC*
    - *CUSTID*
    - *INTEXT*
    - *EXTTYPE*
    - *CORPACTAC*
    - *SKLOCEXPLINE*
    - *MSGTOICS*
    - *BANKACPTN*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullRequest

TOP

Sk-Location-Full

Attribute	Description
Name	Sk-Location-Full
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Full type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description

Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.89.2.SE-ModifySKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-IO*
    - *SKLOCID*
    - *MODNO*
    - *Sk-Account*
      - *SKLOCID*
      - *SKACC*
    - *UDFDETAILS*
      - *FUNCTIONID*
      - *FIELD_NAME*
      - *DATATYPE*
      - *FIELD_VALUE*
      - *VAL_TYPE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Input Only type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description

Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

2.89.3.SE-ModifySKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Primary Key type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Input Only type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	**Description**	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	**Description**	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,I

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,E,O,

TOP

CORPACTAC

Attribute	**Description**
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Full type details

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.89.4.SE-ModifySKLocationMaint-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about PKResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Primary Key type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Input Only type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Includes Securities Safe Keeping Location Maintenance Modification Full type details

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sk-Account

Attribute	Description
Name	Sk-Account
Datatype	
Description	Includes Safe Keeping Account details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.90.AuthorizeSEPortfolio

Authorization of Security Portfolio Definition

2.90.1.SE-Portfolio-Authorize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Authorization*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*

CUSTOMERACC
CUSTOMERACCDESC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR

ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*

PORTFOLIOID
PORTFOLIODESC
Sec-Prod-Disallow
PRODDISALLOWCODE
PRODDISALLOWDESC
PORTFOLIOID
PORTFOLIODESC
Pfolio-Securities-Access
SECUID
SECUPRODCODE
SECUDESC
ALLOWED
PORTFOLIOID
Role-To-Head-1
PORTFOLIOID
PORTFOLIODESC
ROLETOHEAD
ROLETOHEADDESC
Role-To-Head-2
PORTFOLIOID
SECUPROD
SECUDESC
ROLETOHEADDET
ROLETOHEADDESCDET
Role-To-Head-3
PORTFOLIOID
INTERNALSECID
INTERNALSECDESC
ROLETOHEADCLASS
ROLETOHEADDESCCLASS
Pf-Sec-Price-Mapping
SPSECUID
SPPRICECODE
PORTFOLIOID
PORTFOLIODESC
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Authorization Request Full Done.

TOP

Portfolio-Authorization

Attribute	Description
Name	Portfolio-Authorization
Datatype	
Description	Includes Securities Portfolio Authorization Full type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description

Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACCBRNDESC

Attribute	Description
Name	CUSTACCBRNDESC
Datatype	String
Description	Indicates the Branch Name.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,L,F,W
	length	1

TOP

BOOKRIGHTS

Attribute	**Description**	
Name	BOOKRIGHTS	
Datatype	String	
Description	Indicates the Book Rights.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BOOKWARRANTS

Attribute	**Description**	
Name	BOOKWARRANTS	
Datatype	String	
Description	Indicates the Book Warrants.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

AUTOLIQFORCORPACT

Attribute	**Description**	
Name	AUTOLIQFORCORPACT	
Datatype	String	
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CORPUSACC

Attribute	**Description**
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

SHORTPOSALLOW

Attribute	**Description**	
Name	SHORTPOSALLOW	
Datatype	String	
Description	Indicates the Short Position Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	**Description**	
Name	ACCRUEWITHHOLDTAXCOUP	
Datatype	String	
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BANKERSACCEPT

Attribute	**Description**	
Name	BANKERSACCEPT	
Datatype	String	
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CONTRAHOLDALLOW

Attribute	**Description**
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

VALIDCONTRAHOLD

Attribute	**Description**	
Name	VALIDCONTRAHOLD	
Datatype	String	
Description	Indicates Validate When.O - Online, E - EOTI	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E
	length	1

TOP

CORPACTNOTICEREQ

Attribute	**Description**	
Name	CORPACTNOTICEREQ	
Datatype	String	
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

NOTICEDAY

Attribute	**Description**	
Name	NOTICEDAY	
Datatype	Number	
Description	Indicates the Notice Days.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

NOTICEDAYTYPE

Attribute	**Description**
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W
	length	1

TOP

CORPACTREQD

Attribute	**Description**	
Name	CORPACTREQD	
Datatype	String	
Description	Indicates the Corporate Action Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEDISCTBILL

Attribute	**Description**	
Name	ACCRUEDISCTBILL	
Datatype	String	
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUALFREQ

Attribute	**Description**	
Name	ACCRUALFREQ	
Datatype	String	
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAY

Attribute	**Description**
Name	ACCRUALSTARTDAY
Datatype	Number

Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDFREQ

Attribute	Description
Name	STATEHOLDFREQ

Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description

Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,E,Y; length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description

Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

BONDS

Attribute	Description	
Name	BONDS	
Datatype	String	
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

EQUITIES

Attribute	Description	
Name	EQUITIES	
Datatype	String	
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

RIGHTS

Attribute	Description	
Name	RIGHTS	
Datatype	String	
Description	Indicates the Rights.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

WARRANT

Attribute	Description	
Name	WARRANT	
Datatype	String	
Description	Indicates the Warrants.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,B</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,B,F</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,B,C,D,E,F,G,H,I</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXCHRATECODEDESC

Attribute	Description
Name	EXCHRATECODEDESC

Datatype	String
Description	Indicates the Exchange Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MOD_NO

Attribute	Description
Name	MOD_NO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sec-Prod-Disallow

Attribute	Description
Name	Sec-Prod-Disallow
Datatype	

Description	Includes Security Product Disallow details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRODDISALLOWCODE

Attribute	Description
Name	PRODDISALLOWCODE
Datatype	String
Description	Indicates Code of the Product which is disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRODDISALLOWDESC

Attribute	Description
Name	PRODDISALLOWDESC
Datatype	String
Description	Indicates Description of the Product which is disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD

Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description

Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description

Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>15</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>26</td></tr></table>

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISGRPTXN

Attribute	Description

Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS9LBL9

Attribute	Description	
Name	COMPMIS9LBL9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS10LBL10

Attribute	Description	
Name	COMPMIS10LBL10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS1LBL1

Attribute	Description	
Name	TXNMIS1LBL1	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

2.90.2.SE-Portfolio-Authorize-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Authorization-IO*
    - *PORTID*
    - *PORTREF*
    - *EXREF*
    - *EVNTNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Request Done for Authorization.

TOP

Portfolio-Authorization-IO

Attribute	Description
Name	Portfolio-Authorization-IO
Datatype	
Description	Includes Securities Portfolio Authorization Input Only type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	**Description**
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	**Description**
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.90.3.SE-Portfolio-Authorize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Authorization*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*
    - *CUSTOMERACC*
    - *CUSTOMERACCDESC*
    - *ASSETACCBASIS*

PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL

REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow

PRODDISALLOWCODE
PRODDISALLOWDESC
PORTFOLIOID
PORTFOLIODESC
Pfolio-Securities-Access
SECUID
SECUPRODCODE
SECUDESC
ALLOWED
PORTFOLIOID
Role-To-Head-1
PORTFOLIOID
PORTFOLIODESC
ROLETOHEAD
ROLETOHEADDESC
Role-To-Head-2
PORTFOLIOID
SECUPROD
SECUDESC
ROLETOHEADDET
ROLETOHEADDESCDET
Role-To-Head-3
PORTFOLIOID
INTERNALSECID
INTERNALSECDESC
ROLETOHEADCLASS
ROLETOHEADDESCCLASS
Pf-Sec-Price-Mapping
SPSECUID
SPPRICECODE
PORTFOLIOID
PORTFOLIODESC
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Authorization Full Response Done.

TOP

Portfolio-Authorization

Attribute	Description
Name	Portfolio-Authorization
Datatype	
Description	Includes Securities Portfolio Authorization type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description	Indicates the Portfolio Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXREF

Attribute	**Description**	
Name	EXREF	
Datatype	String	
Description	Indicates the External Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMERACC

Attribute	**Description**	
Name	CUSTOMERACC	
Datatype	String	
Description	Indicates the Customer Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CUSTOMERACCDESC

Attribute	**Description**	
Name	CUSTOMERACCDESC	
Datatype	String	
Description	Indicates the customer account Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASSETACCBASIS

Attribute	**Description**	
Name	ASSETACCBASIS	
Datatype	String	
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,N
	length	1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXCHRATECODEDESC

Attribute	**Description**	
Name	EXCHRATECODEDESC	
Datatype	String	
Description	Indicates the Exchange Rate Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESALLOW

Attribute	**Description**	
Name	RESALLOW	
Datatype	String	
Description	Indicates the allowed. A- Allowed, D - Disallowed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D
	length	1

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MOD_NO

Attribute	**Description**	
Name	MOD_NO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sec-Prod-Disallow

Attribute	**Description**	
Name	Sec-Prod-Disallow	
Datatype		
Description	Includes Security Product Disallow details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODDISALLOWCODE

Attribute	**Description**	
Name	PRODDISALLOWCODE	
Datatype	String	
Description	Indicates Code of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDISALLOWDESC

Attribute	**Description**	
Name	PRODDISALLOWDESC	
Datatype	String	
Description	Indicates Description of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	Description	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates The MIS Head.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
minLength	1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	

Attribute	Description
minOccurs	0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.90.4.SE-Portfolio-Authorize-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Authorization-PK*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
    - *Portfolio-Authorization-IO*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Authorisation Done.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Authorization-PK

Attribute	Description
Name	Portfolio-Authorization-PK
Datatype	
Description	Includes Securities Portfolio Authorization Primary Key type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

Portfolio-Authorization-IO

Attribute	Description
Name	Portfolio-Authorization-IO
Datatype	
Description	Includes Securities Portfolio Authorization Input Only type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.91.CloseSEPortfolio

Closure of Security Portfolio Definition

2.91.1.SE-Portfolio-Close-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*

CUSTOMERACC
CUSTOMERACCDESC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR

ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
Portfolio-Sk-Mapping
  SKLOCATID
  SKLACC
  PORTFOLIOID
  PORTFOLIODESC
Sec-Prod-Disallow
  PRODDISALLOWCODE
  PRODDISALLOWDESC
  PORTFOLIOID
  PORTFOLIODESC
Pfolio-Securities-Access
  SECUID
  SECUPRODCODE

- *SECUDESC*
- *ALLOWED*
- *PORTFOLIOID*

Role-To-Head-1

- *PORTFOLIOID*
- *PORTFOLIODESC*
- *ROLETOHEAD*
- *ROLETOHEADDESC*

Role-To-Head-2

- *PORTFOLIOID*
- *SECUPROD*
- *SECUDESC*
- *ROLETOHEADDET*
- *ROLETOHEADDESCDET*

Role-To-Head-3

- *PORTFOLIOID*
- *INTERNALSECID*
- *INTERNALSECDESC*
- *ROLETOHEADCLASS*
- *ROLETOHEADDESCCLASS*

Pf-Sec-Price-Mapping

- *SPSECUID*
- *SPPRICECODE*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8

FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Portfolio Close Request Full Done.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Closure of Security Portfolio Definition -Master Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMER

Attribute	**Description**	
Name	CUSTOMER	
Datatype	String	
Description	Indicates the Customer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHORTNAME

Attribute	**Description**	
Name	SHORTNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCBRN

Attribute	**Description**	
Name	CUSTACCBRN	
Datatype	String	
Description	Indicates the Customer Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: C,W length: 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**	
Name	ACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	**Description**	
Name	ACCRUEHOLDTAXTBILLDISC	
Datatype	String	
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDREQD

Attribute	**Description**	
Name	STATEHOLDREQD	
Datatype	String	
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**
Name	STATEHOLDFREQ
Datatype	String

Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD

Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,E,Y; length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description

Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXCHRATECODEDESC

Attribute	Description
Name	EXCHRATECODEDESC

Datatype	String
Description	Indicates the Exchange Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes the Portfolio SK Mapping details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates the SK Location ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates the SK Location Account.
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sec-Prod-Disallow

Attribute	Description
Name	Sec-Prod-Disallow
Datatype	
Description	Includes the Sceurity Product Disallow details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODDISALLOWCODE

Attribute	Description
Name	PRODDISALLOWCODE
Datatype	String
Description	Indicates the Product Disallow Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDISALLOWDESC

Attribute	Description
Name	PRODDISALLOWDESC
Datatype	String
Description	Indicates the Product Disallow Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes the Portfolio Securities Access details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates the security ID.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates the security Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates whether allowed or not. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y; length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates the Role to Head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates the Role to Head description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes the Role to Head detail.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String

Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates the Security Product.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates the Role to Head Additional details.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates the Role to head Additional description details.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	

Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates the Internal Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates the Internal Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates the Role to Head Class details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS

Datatype	String
Description	Indicates the Role to Head Description Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes the Portfolio Security Price Mapping.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates the Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes the Management information System.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes the Advice Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the message type.
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates the party ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates the medium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates the suppress.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ

Datatype	String
Description	Indicates the charge required.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

2.91.2.SE-Portfolio-Close-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master-IO*
    - *PORTID*
    - *PORTREF*
    - *EXREF*
    - *EVNTNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Portfolio Close Request Done.

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Closure of Security Portfolio Definition IO Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	**Description**
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	**Description**
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.91.3.SE-Portfolio-Close-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*
    - *CUSTOMERACC*
    - *CUSTOMERACCDESC*
    - *ASSETACCBASIS*

PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL

REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow

PRODDISALLOWCODE
PRODDISALLOWDESC
PORTFOLIOID
PORTFOLIODESC
Pfolio-Securities-Access
SECUID
SECUPRODCODE
SECUDESC
ALLOWED
PORTFOLIOID
Role-To-Head-1
PORTFOLIOID
PORTFOLIODESC
ROLETOHEAD
ROLETOHEADDESC
Role-To-Head-2
PORTFOLIOID
SECUPROD
SECUDESC
ROLETOHEADDET
ROLETOHEADDESCDET
Role-To-Head-3
PORTFOLIOID
INTERNALSECID
INTERNALSECDESC
ROLETOHEADCLASS
ROLETOHEADDESCCLASS
Pf-Sec-Price-Mapping
SPSECUID
SPPRICECODE
PORTFOLIOID
PORTFOLIODESC
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Portfolio Close Response Full Done.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Closure of Security Portfolio Definition Master Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description	Indicates the Portfolio Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXREF

Attribute	**Description**	
Name	EXREF	
Datatype	String	
Description	Indicates the External Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMERACC

Attribute	**Description**	
Name	CUSTOMERACC	
Datatype	String	
Description	Indicates the Customer Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CUSTOMERACCDESC

Attribute	**Description**	
Name	CUSTOMERACCDESC	
Datatype	String	
Description	Indicates the customer account Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASSETACCBASIS

Attribute	**Description**	
Name	ASSETACCBASIS	
Datatype	String	
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,N
	length	1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXCHRATECODEDESC

Attribute	**Description**	
Name	EXCHRATECODEDESC	
Datatype	String	
Description	Indicates the Exchange Rate Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESALLOW

Attribute	**Description**	
Name	RESALLOW	
Datatype	String	
Description	Indicates the allowed. A- Allowed, D - Disallowed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D
	length	1

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MOD_NO

Attribute	**Description**	
Name	MOD_NO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SUBSYSTEMSTAT

Attribute	Description	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sec-Prod-Disallow

Attribute	**Description**	
Name	Sec-Prod-Disallow	
Datatype		
Description	Includes Security Product Disallow details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODDISALLOWCODE

Attribute	**Description**	
Name	PRODDISALLOWCODE	
Datatype	String	
Description	Indicates Code of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDISALLOWDESC

Attribute	**Description**	
Name	PRODDISALLOWDESC	
Datatype	String	
Description	Indicates Description of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	Description	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates The MIS Head.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.91.4.SE-Portfolio-Close-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Master-PK*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
    - *Portfolio-Master-IO*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Portfolio Close Response Done.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Master-PK

Attribute	Description
Name	Portfolio-Master-PK
Datatype	
Description	Closure of Security Portfolio Definition PK Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Closure of Security Portfolio Definition IO Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.92.CreateSEPortfolio

Security Portfolio Definition

2.92.1.SE-Portfolio-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*

CUSTOMERACC
CUSTOMERACCDESC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR

ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
Portfolio-Sk-Mapping
  SKLOCATID
  SKLACC
  PORTFOLIOID
  PORTFOLIODESC
Sec-Prod-Disallow
  PRODDISALLOWCODE
  PRODDISALLOWDESC
  PORTFOLIOID
  PORTFOLIODESC
Pfolio-Securities-Access
  SECUID
  SECUPRODCODE

- *SECUDESC*
- *ALLOWED*
- *PORTFOLIOID*

Role-To-Head-1

- *PORTFOLIOID*
- *PORTFOLIODESC*
- *ROLETOHEAD*
- *ROLETOHEADDESC*

Role-To-Head-2

- *PORTFOLIOID*
- *SECUPROD*
- *SECUDESC*
- *ROLETOHEADDET*
- *ROLETOHEADDESCDET*

Role-To-Head-3

- *PORTFOLIOID*
- *INTERNALSECID*
- *INTERNALSECDESC*
- *ROLETOHEADCLASS*
- *ROLETOHEADDESCCLASS*

Pf-Sec-Price-Mapping

- *SPSECUID*
- *SPPRICECODE*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8

FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Create Request .

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Security Portfolio Definition Master Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMER

Attribute	**Description**	
Name	CUSTOMER	
Datatype	String	
Description	Indicates the Customer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHORTNAME

Attribute	**Description**	
Name	SHORTNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCBRN

Attribute	**Description**	
Name	CUSTACCBRN	
Datatype	String	
Description	Indicates the Customer Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: C,W length: 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**	
Name	ACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	**Description**	
Name	ACCRUEHOLDTAXTBILLDISC	
Datatype	String	
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDREQD

Attribute	**Description**	
Name	STATEHOLDREQD	
Datatype	String	
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**
Name	STATEHOLDFREQ
Datatype	String

Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD

Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,E,Y; length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description

Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXCHRATECODEDESC

Attribute	Description
Name	EXCHRATECODEDESC

Datatype	String
Description	Indicates the Exchange Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes the Portfolio SK Mapping details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates the SK Location ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates the SK Location Account.
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sec-Prod-Disallow

Attribute	Description
Name	Sec-Prod-Disallow
Datatype	
Description	Includes the Sceurity Product Disallow details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODDISALLOWCODE

Attribute	Description
Name	PRODDISALLOWCODE
Datatype	String
Description	Indicates the Product Disallow Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDISALLOWDESC

Attribute	Description
Name	PRODDISALLOWDESC
Datatype	String
Description	Indicates the Product Disallow Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes the Portfolio Securities Access details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates the security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates the security Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates whether allowed or not. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y; length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates the Role to Head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates the Role to Head description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes the Role to Head detail.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String

Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates the Security Product.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates the Role to Head Additional details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates the Role to head Additional description details.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	

Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates the Internal Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates the Internal Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates the Role to Head Class details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS

Datatype	String
Description	Indicates the Role to Head Description Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes the Portfolio Security Price Mapping.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates the Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes the Management information System.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	**Description**	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	**Description**	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	**Description**	
Name	MISHD	
Datatype	String	
Description	Indicates The MIS Head.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes the Advice Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the message type.
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates the party ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates the medium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates the suppress.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ

Datatype	String
Description	Indicates the charge required.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

2.92.2.SE-Portfolio-Create-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master-IO*
    - *PRDCD*
    - *PORTFOLIOID*
    - *EXREF*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *CURRENCY*
    - *CUSTOMER*
    - *CUSTACCBRN*
    - *CUSTOMERACC*
    - *ASSETACCBASIS*
    - *PORTFOLIOCOSTMETH*
    - *BOOKRIGHTS*
    - *BOOKWARRANTS*
    - *AUTOLIQFORCORPACT*
    - *CORPUSACC*
    - *SHORTPOSALLOW*
    - *ACCRUEWITHHOLDTAXCOUP*
    - *BANKERSACCEPT*

CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS

REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
RESALLOW

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Create Request Done.

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Security Portfolio Definition IO Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String

Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BOOKWARRANTS

Attribute	**Description**	
Name	BOOKWARRANTS	
Datatype	String	
Description	Indicates the Book Warrants.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

AUTOLIQFORCORPACT

Attribute	**Description**	
Name	AUTOLIQFORCORPACT	
Datatype	String	
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CORPUSACC

Attribute	**Description**	
Name	CORPUSACC	
Datatype	String	
Description	Indicates the Corpus Account.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

SHORTPOSALLOW

Attribute	**Description**
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	**Description**	
Name	ACCRUEWITHHOLDTAXCOUP	
Datatype	String	
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BANKERSACCEPT

Attribute	**Description**	
Name	BANKERSACCEPT	
Datatype	String	
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CONTRAHOLDALLOW

Attribute	**Description**	
Name	CONTRAHOLDALLOW	
Datatype	String	
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

VALIDCONTRAHOLD

Attribute	**Description**
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E
	length	1

TOP

CORPACTNOTICEREQ

Attribute	**Description**	
Name	CORPACTNOTICEREQ	
Datatype	String	
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

NOTICEDAY

Attribute	**Description**	
Name	NOTICEDAY	
Datatype	Number	
Description	Indicates the Notice Days.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

NOTICEDAYTYPE

Attribute	**Description**	
Name	NOTICEDAYTYPE	
Datatype	String	
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W
	length	1

TOP

CORPACTREQD

Attribute	**Description**
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEDISCTBILL

Attribute	**Description**	
Name	ACCRUEDISCTBILL	
Datatype	String	
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUALFREQ

Attribute	**Description**	
Name	ACCRUALFREQ	
Datatype	String	
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAY

Attribute	**Description**	
Name	ACCRUALSTARTDAY	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**
Name	ACCRUALSTARTMON
Datatype	Number

Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

STATEHOLDFREQ

Attribute	Description
Name	STATEHOLDFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: S,E,Y length: 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number

Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description
Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,L,X; length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,H length: 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

EQUITIES

Attribute	**Description**	
Name	EQUITIES	
Datatype	String	
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

RIGHTS

Attribute	**Description**	
Name	RIGHTS	
Datatype	String	
Description	Indicates the Rights.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

WARRANT

Attribute	**Description**	
Name	WARRANT	
Datatype	String	
Description	Indicates the Warrants.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

TBILLS

Attribute	**Description**
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

FWDACCRUAL

Attribute	**Description**	
Name	FWDACCRUAL	
Datatype	String	
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

FWDACCRUALMETH

Attribute	**Description**	
Name	FWDACCRUALMETH	
Datatype	String	
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,B,C,D,E,F,G,H,I
	length	1

TOP

FWDACCRUALFREQ

Attribute	**Description**	
Name	FWDACCRUALFREQ	
Datatype	String	
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

FWDACCRUALSTARTDAY

Attribute	**Description**

Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

2.92.3.SE-Portfolio-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*
    - *CUSTOMERACC*
    - *CUSTOMERACCDESC*
    - *ASSETACCBASIS*

PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL

REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow

PRODDISALLOWCODE
PRODDISALLOWDESC
PORTFOLIOID
PORTFOLIODESC
Pfolio-Securities-Access
SECUID
SECUPRODCODE
SECUDESC
ALLOWED
PORTFOLIOID
Role-To-Head-1
PORTFOLIOID
PORTFOLIODESC
ROLETOHEAD
ROLETOHEADDESC
Role-To-Head-2
PORTFOLIOID
SECUPROD
SECUDESC
ROLETOHEADDET
ROLETOHEADDESCDET
Role-To-Head-3
PORTFOLIOID
INTERNALSECID
INTERNALSECDESC
ROLETOHEADCLASS
ROLETOHEADDESCCLASS
Pf-Sec-Price-Mapping
SPSECUID
SPPRICECODE
PORTFOLIOID
PORTFOLIODESC
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Create Response.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Security Portfolio Definition Master Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description	Indicates the Portfolio Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXREF

Attribute	**Description**	
Name	EXREF	
Datatype	String	
Description	Indicates the External Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMERACC

Attribute	**Description**	
Name	CUSTOMERACC	
Datatype	String	
Description	Indicates the Customer Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CUSTOMERACCDESC

Attribute	**Description**	
Name	CUSTOMERACCDESC	
Datatype	String	
Description	Indicates the customer account Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASSETACCBASIS

Attribute	**Description**	
Name	ASSETACCBASIS	
Datatype	String	
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,N
	length	1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,L,X; length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,H; length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXCHRATECODEDESC

Attribute	**Description**	
Name	EXCHRATECODEDESC	
Datatype	String	
Description	Indicates the Exchange Rate Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESALLOW

Attribute	**Description**	
Name	RESALLOW	
Datatype	String	
Description	Indicates the allowed. A- Allowed, D - Disallowed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D
	length	1

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MOD_NO

Attribute	**Description**	
Name	MOD_NO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SUBSYSTEMSTAT

Attribute	Description	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sec-Prod-Disallow

Attribute	**Description**	
Name	Sec-Prod-Disallow	
Datatype		
Description	Includes Security Product Disallow details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODDISALLOWCODE

Attribute	**Description**	
Name	PRODDISALLOWCODE	
Datatype	String	
Description	Indicates Code of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDISALLOWDESC

Attribute	**Description**	
Name	PRODDISALLOWDESC	
Datatype	String	
Description	Indicates Description of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.92.4.SE-Portfolio-Create-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Master-PK*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
    - *Portfolio-Master-IO*
      - *PRDCD*
      - *PORTFOLIOID*
      - *EXREF*
      - *PORTFOLIODESC*
      - *BRANCH*
      - *CURRENCY*
      - *CUSTOMER*
      - *CUSTACCBRN*
      - *CUSTOMERACC*
      - *ASSETACCBASIS*
      - *PORTFOLIOCOSTMETH*
      - *BOOKRIGHTS*

BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH

REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
RESALLOW
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Create Response Done.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Master-PK

Attribute	Description
Name	Portfolio-Master-PK
Datatype	
Description	Security Portfolio Definition PK Type

TOP

PORTID

Attribute	**Description**	
Name	PORTID	
Datatype	String	
Description	Indicates the Portfolio ID.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Security Portfolio Definition IO Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String

Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,N length: 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,L,F,W length: 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CORPUSACC

Attribute	**Description**	
Name	CORPUSACC	
Datatype	String	
Description	Indicates the Corpus Account.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

SHORTPOSALLOW

Attribute	**Description**	
Name	SHORTPOSALLOW	
Datatype	String	
Description	Indicates the Short Position Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	**Description**	
Name	ACCRUEWITHHOLDTAXCOUP	
Datatype	String	
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BANKERSACCEPT

Attribute	**Description**
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CONTRAHOLDALLOW

Attribute	**Description**	
Name	CONTRAHOLDALLOW	
Datatype	String	
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

VALIDCONTRAHOLD

Attribute	**Description**	
Name	VALIDCONTRAHOLD	
Datatype	String	
Description	Indicates Validate When.O - Online, E - EOTI	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E
	length	1

TOP

CORPACTNOTICEREQ

Attribute	**Description**	
Name	CORPACTNOTICEREQ	
Datatype	String	
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

NOTICEDAY

Attribute	**Description**
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAY

Attribute	**Description**	
Name	ACCRUALSTARTDAY	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**	
Name	ACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	**Description**	
Name	ACCRUEHOLDTAXTBILLDISC	
Datatype	String	
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDREQD

Attribute	**Description**
Name	STATEHOLDREQD
Datatype	String

Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDFREQ

Attribute	Description
Name	STATEHOLDFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description

Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON

Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,B,C,D,E,F,G,H,I
	length	1

TOP

ACCRUALFREQRPR

Attribute	Description	
Name	ACCRUALFREQRPR	
Datatype	String	
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description	
Name	ACCRUALSTARTDAYRPR	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMONRPR

Attribute	Description	
Name	ACCRUALSTARTMONRPR	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT

Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description
Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ

Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE

Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.93.DeleteSEPortfolio

Deletion of Security Portfolio Definition

2.93.1.SE-Portfolio-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*

CUSTOMERACC
CUSTOMERACCDESC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR

ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
Portfolio-Sk-Mapping
  SKLOCATID
  SKLACC
  PORTFOLIOID
  PORTFOLIODESC
Sec-Prod-Disallow
  PRODDISALLOWCODE
  PRODDISALLOWDESC
  PORTFOLIOID
  PORTFOLIODESC
Pfolio-Securities-Access
  SECUID
  SECUPRODCODE

- *SECUDESC*
- *ALLOWED*
- *PORTFOLIOID*

Role-To-Head-1

- *PORTFOLIOID*
- *PORTFOLIODESC*
- *ROLETOHEAD*
- *ROLETOHEADDESC*

Role-To-Head-2

- *PORTFOLIOID*
- *SECUPROD*
- *SECUDESC*
- *ROLETOHEADDET*
- *ROLETOHEADDESCDET*

Role-To-Head-3

- *PORTFOLIOID*
- *INTERNALSECID*
- *INTERNALSECDESC*
- *ROLETOHEADCLASS*
- *ROLETOHEADDESCCLASS*

Pf-Sec-Price-Mapping

- *SPSECUID*
- *SPPRICECODE*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8

FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Delete Request Done.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Deletion of Security Portfolio Definition Master Type

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMER

Attribute	**Description**	
Name	CUSTOMER	
Datatype	String	
Description	Indicates the Customer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHORTNAME

Attribute	**Description**	
Name	SHORTNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCBRN

Attribute	**Description**	
Name	CUSTACCBRN	
Datatype	String	
Description	Indicates the Customer Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: D,L,F,W length: 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: C,W length: 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**	
Name	ACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	**Description**	
Name	ACCRUEHOLDTAXTBILLDISC	
Datatype	String	
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDREQD

Attribute	**Description**	
Name	STATEHOLDREQD	
Datatype	String	
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**
Name	STATEHOLDFREQ
Datatype	String

Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD

Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,E,Y; length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description

Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

FWDACCRUALSTARTDAY

Attribute	Description	
Name	FWDACCRUALSTARTDAY	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

FWDACCRUALSTARTMON

Attribute	Description	
Name	FWDACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

INTERESTACCRUAL

Attribute	Description	
Name	INTERESTACCRUAL	
Datatype	String	
Description	Indicates the Interest Accrual.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXCHRATECODEDESC

Attribute	Description
Name	EXCHRATECODEDESC

Datatype	String
Description	Indicates the Exchange Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes the Portfolio SK Mapping details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates the SK Location ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates the SK Location Account.
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sec-Prod-Disallow

Attribute	Description
Name	Sec-Prod-Disallow
Datatype	
Description	Includes the Sceurity Product Disallow details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODDISALLOWCODE

Attribute	Description
Name	PRODDISALLOWCODE
Datatype	String
Description	Indicates the Product Disallow Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDISALLOWDESC

Attribute	Description
Name	PRODDISALLOWDESC
Datatype	String
Description	Indicates the Product Disallow Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes the Portfolio Securities Access details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates the security ID.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates the security Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates whether allowed or not. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates the Role to Head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates the Role to Head description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes the Role to Head detail.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String

Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates the Security Product.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates the Role to Head Additional details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates the Role to head Additional description details.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	

Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates the Internal Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates the Internal Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates the Role to Head Class details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS

Datatype	String
Description	Indicates the Role to Head Description Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes the Portfolio Security Price Mapping.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates the Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes the Management information System.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	**Description**	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	**Description**	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	**Description**	
Name	MISHD	
Datatype	String	
Description	Indicates The MIS Head.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes the Advice Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the message type.
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 1

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates the party ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates the medium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates the suppress.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ

Datatype	String
Description	Indicates the charge required.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

2.93.2.SE-Portfolio-Delete-Req-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Portfolio-Master-IO*
  - *PORTID*
  - *PORTREF*
  - *EXREF*
  - *EVNTNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Delete Request Done.

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Deletion of Security Portfolio Definition IO Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	**Description**
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	**Description**
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

2.93.3.SE-Portfolio-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master-PK*
    - *PORTID*
    - *PORTREF*
    - *EXREF*
    - *EVNTNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Delete Response Done.

TOP

Portfolio-Master-PK

Attribute	Description
Name	Portfolio-Master-PK
Datatype	
Description	Deletion of Security Portfolio Definition PK Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.93.4.SE-Portfolio-Delete-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Master-PK*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
    - *Portfolio-Master-IO*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Delete Response Done.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Master-PK

Attribute	Description
Name	Portfolio-Master-PK
Datatype	
Description	Deletion of Security Portfolio Definition PK Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Deletion of Security Portfolio Definition IO Type

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.94.ModifySEPortfolio

Modification of Security Portfolio Definition

2.94.1.SE-Portfolio-Modify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*

CUSTOMERACC
CUSTOMERACCDESC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR

ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
Portfolio-Sk-Mapping
  SKLOCATID
  SKLACC
  PORTFOLIOID
  PORTFOLIODESC
Sec-Prod-Disallow
  PRODDISALLOWCODE
  PRODDISALLOWDESC
  PORTFOLIOID
  PORTFOLIODESC
Pfolio-Securities-Access
  SECUID
  SECUPRODCODE

- *SECUDESC*
- *ALLOWED*
- *PORTFOLIOID*

Role-To-Head-1

- *PORTFOLIOID*
- *PORTFOLIODESC*
- *ROLETOHEAD*
- *ROLETOHEADDESC*

Role-To-Head-2

- *PORTFOLIOID*
- *SECUPROD*
- *SECUDESC*
- *ROLETOHEADDET*
- *ROLETOHEADDESCDET*

Role-To-Head-3

- *PORTFOLIOID*
- *INTERNALSECID*
- *INTERNALSECDESC*
- *ROLETOHEADCLASS*
- *ROLETOHEADDESCCLASS*

Pf-Sec-Price-Mapping

- *SPSECUID*
- *SPPRICECODE*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8

FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Modify Request Done.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Includes Securities Portfolio Modification Master type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMER

Attribute	**Description**	
Name	CUSTOMER	
Datatype	String	
Description	Indicates the Customer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHORTNAME

Attribute	**Description**	
Name	SHORTNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCBRN

Attribute	**Description**	
Name	CUSTACCBRN	
Datatype	String	
Description	Indicates the Customer Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: C,W length: 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**	
Name	ACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	**Description**	
Name	ACCRUEHOLDTAXTBILLDISC	
Datatype	String	
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDREQD

Attribute	**Description**	
Name	STATEHOLDREQD	
Datatype	String	
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**
Name	STATEHOLDFREQ
Datatype	String

Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD

Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,E,Y; length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description

Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

BONDS

Attribute	Description	
Name	BONDS	
Datatype	String	
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

EQUITIES

Attribute	Description	
Name	EQUITIES	
Datatype	String	
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

RIGHTS

Attribute	Description	
Name	RIGHTS	
Datatype	String	
Description	Indicates the Rights.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

WARRANT

Attribute	Description	
Name	WARRANT	
Datatype	String	
Description	Indicates the Warrants.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	enumeration / 1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	enumeration / Y,N
	length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXCHRATECODEDESC

Attribute	Description
Name	EXCHRATECODEDESC

Datatype	String
Description	Indicates the Exchange Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes the Portfolio SK Mapping details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates the SK Location ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates the SK Location Account.
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sec-Prod-Disallow

Attribute	Description
Name	Sec-Prod-Disallow
Datatype	
Description	Includes the Sceurity Product Disallow details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODDISALLOWCODE

Attribute	Description
Name	PRODDISALLOWCODE
Datatype	String
Description	Indicates the Product Disallow Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDISALLOWDESC

Attribute	Description
Name	PRODDISALLOWDESC
Datatype	String
Description	Indicates the Product Disallow Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes the Portfolio Securities Access details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates the security ID.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates the security Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates whether allowed or not. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y; length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates the Role to Head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates the Role to Head description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes the Role to Head detail.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String

Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates the Security Product.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates the Role to Head Additional details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates the Role to head Additional description details.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	

Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates the Internal Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates the Internal Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates the Role to Head Class details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS

Datatype	String
Description	Indicates the Role to Head Description Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes the Portfolio Security Price Mapping.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates the Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes the Management information System.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes the Advice Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the message type.
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates the party ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates the medium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates the suppress.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ

Datatype	String
Description	Indicates the charge required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.94.2.SE-Portfolio-Modify-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master-IO*
    - *PRDCD*
    - *PORTFOLIOID*
    - *EXREF*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *CURRENCY*
    - *CUSTOMER*
    - *CUSTACCBRN*
    - *CUSTOMERACC*
    - *ASSETACCBASIS*
    - *PORTFOLIOCOSTMETH*
    - *BOOKRIGHTS*
    - *BOOKWARRANTS*
    - *AUTOLIQFORCORPACT*
    - *CORPUSACC*
    - *SHORTPOSALLOW*
    - *ACCRUEWITHHOLDTAXCOUP*
    - *BANKERSACCEPT*

CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS

REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
RESALLOW

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Modify Request Done.

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Includes Securities Portfolio Modification Input Master Only type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description	
Name	PORTFOLIODESC	
Datatype	String	
Description	Indicates the Portfolio Description.	
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description	Indicates the Currency.	
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTOMER

Attribute	Description	
Name	CUSTOMER	
Datatype	String	
Description	Indicates the Customer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String

Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BOOKWARRANTS

Attribute	**Description**	
Name	BOOKWARRANTS	
Datatype	String	
Description	Indicates the Book Warrants.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

AUTOLIQFORCORPACT

Attribute	**Description**	
Name	AUTOLIQFORCORPACT	
Datatype	String	
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CORPUSACC

Attribute	**Description**	
Name	CORPUSACC	
Datatype	String	
Description	Indicates the Corpus Account.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

SHORTPOSALLOW

Attribute	**Description**
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	**Description**	
Name	ACCRUEWITHHOLDTAXCOUP	
Datatype	String	
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BANKERSACCEPT

Attribute	**Description**	
Name	BANKERSACCEPT	
Datatype	String	
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CONTRAHOLDALLOW

Attribute	**Description**	
Name	CONTRAHOLDALLOW	
Datatype	String	
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

VALIDCONTRAHOLD

Attribute	**Description**
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E
	length	1

TOP

CORPACTNOTICEREQ

Attribute	**Description**	
Name	CORPACTNOTICEREQ	
Datatype	String	
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

NOTICEDAY

Attribute	**Description**	
Name	NOTICEDAY	
Datatype	Number	
Description	Indicates the Notice Days.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

NOTICEDAYTYPE

Attribute	**Description**	
Name	NOTICEDAYTYPE	
Datatype	String	
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W
	length	1

TOP

CORPACTREQD

Attribute	**Description**
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEDISCTBILL

Attribute	**Description**	
Name	ACCRUEDISCTBILL	
Datatype	String	
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUALFREQ

Attribute	**Description**	
Name	ACCRUALFREQ	
Datatype	String	
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAY

Attribute	**Description**	
Name	ACCRUALSTARTDAY	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**
Name	ACCRUALSTARTMON
Datatype	Number

Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDFREQ

Attribute	Description
Name	STATEHOLDFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: S,E,Y length: 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number

Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description
Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,L,X; length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,H length: 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

EQUITIES

Attribute	**Description**	
Name	EQUITIES	
Datatype	String	
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

RIGHTS

Attribute	**Description**	
Name	RIGHTS	
Datatype	String	
Description	Indicates the Rights.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

WARRANT

Attribute	**Description**	
Name	WARRANT	
Datatype	String	
Description	Indicates the Warrants.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

TBILLS

Attribute	**Description**
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

FWDACCRUAL

Attribute	**Description**	
Name	FWDACCRUAL	
Datatype	String	
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

FWDACCRUALMETH

Attribute	**Description**	
Name	FWDACCRUALMETH	
Datatype	String	
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,B,C,D,E,F,G,H,I
	length	1

TOP

FWDACCRUALFREQ

Attribute	**Description**	
Name	FWDACCRUALFREQ	
Datatype	String	
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

FWDACCRUALSTARTDAY

Attribute	**Description**

Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

2.94.3.SE-Portfolio-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*
    - *CUSTOMERACC*
    - *CUSTOMERACCDESC*
    - *ASSETACCBASIS*

PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL

REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow

PRODDISALLOWCODE
PRODDISALLOWDESC
PORTFOLIOID
PORTFOLIODESC
Pfolio-Securities-Access
SECUID
SECUPRODCODE
SECUDESC
ALLOWED
PORTFOLIOID
Role-To-Head-1
PORTFOLIOID
PORTFOLIODESC
ROLETOHEAD
ROLETOHEADDESC
Role-To-Head-2
PORTFOLIOID
SECUPROD
SECUDESC
ROLETOHEADDET
ROLETOHEADDESCDET
Role-To-Head-3
PORTFOLIOID
INTERNALSECID
INTERNALSECDESC
ROLETOHEADCLASS
ROLETOHEADDESCCLASS
Pf-Sec-Price-Mapping
SPSECUID
SPPRICECODE
PORTFOLIOID
PORTFOLIODESC
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Modify Response Done.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Includes Securities Portfolio Modification Master type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description	Indicates the Portfolio Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXREF

Attribute	**Description**	
Name	EXREF	
Datatype	String	
Description	Indicates the External Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	Description	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMERACC

Attribute	Description	
Name	CUSTOMERACC	
Datatype	String	
Description	Indicates the Customer Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CUSTOMERACCDESC

Attribute	Description	
Name	CUSTOMERACCDESC	
Datatype	String	
Description	Indicates the customer account Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASSETACCBASIS

Attribute	Description	
Name	ASSETACCBASIS	
Datatype	String	
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,N
	length	1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXCHRATECODEDESC

Attribute	**Description**	
Name	EXCHRATECODEDESC	
Datatype	String	
Description	Indicates the Exchange Rate Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESALLOW

Attribute	**Description**	
Name	RESALLOW	
Datatype	String	
Description	Indicates the allowed. A- Allowed, D - Disallowed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D
	length	1

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MOD_NO

Attribute	**Description**	
Name	MOD_NO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates Subsystem Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sec-Prod-Disallow

Attribute	**Description**	
Name	Sec-Prod-Disallow	
Datatype		
Description	Includes Security Product Disallow details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODDISALLOWCODE

Attribute	**Description**	
Name	PRODDISALLOWCODE	
Datatype	String	
Description	Indicates Code of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDISALLOWDESC

Attribute	**Description**	
Name	PRODDISALLOWDESC	
Datatype	String	
Description	Indicates Description of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.94.4.SE-Portfolio-Modify-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Master-PK*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
    - *Portfolio-Master-IO*
      - *PRDCD*
      - *PORTFOLIOID*
      - *EXREF*
      - *PORTFOLIODESC*
      - *BRANCH*
      - *CURRENCY*
      - *CUSTOMER*
      - *CUSTACCBRN*
      - *CUSTOMERACC*
      - *ASSETACCBASIS*
      - *PORTFOLIOCOSTMETH*
      - *BOOKRIGHTS*

BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH

REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
RESALLOW
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Modify Response.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Master-PK

Attribute	Description
Name	Portfolio-Master-PK
Datatype	
Description	Includes Securities Portfolio Modification Master Primary Key type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Includes Securities Portfolio Modification Input Master Only type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String

Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,N length: 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,L,F,W length: 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CORPUSACC

Attribute	**Description**	
Name	CORPUSACC	
Datatype	String	
Description	Indicates the Corpus Account.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

SHORTPOSALLOW

Attribute	**Description**	
Name	SHORTPOSALLOW	
Datatype	String	
Description	Indicates the Short Position Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	**Description**	
Name	ACCRUEWITHHOLDTAXCOUP	
Datatype	String	
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

BANKERSACCEPT

Attribute	**Description**
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

CONTRAHOLDALLOW

Attribute	**Description**	
Name	CONTRAHOLDALLOW	
Datatype	String	
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

VALIDCONTRAHOLD

Attribute	**Description**	
Name	VALIDCONTRAHOLD	
Datatype	String	
Description	Indicates Validate When.O - Online, E - EOTI	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E
	length	1

TOP

CORPACTNOTICEREQ

Attribute	**Description**	
Name	CORPACTNOTICEREQ	
Datatype	String	
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

NOTICEDAY

Attribute	**Description**
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

NOTICEDAYTYPE

Attribute	**Description**	
Name	NOTICEDAYTYPE	
Datatype	String	
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W
	length	1

TOP

CORPACTREQD

Attribute	**Description**	
Name	CORPACTREQD	
Datatype	String	
Description	Indicates the Corporate Action Required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUEDISCTBILL

Attribute	**Description**	
Name	ACCRUEDISCTBILL	
Datatype	String	
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

ACCRUALFREQ

Attribute	**Description**
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String

Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDFREQ

Attribute	Description
Name	STATEHOLDFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description

Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON

Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,B,C,D,E,F,G,H,I
	length	1

TOP

ACCRUALFREQRPR

Attribute	Description	
Name	ACCRUALFREQRPR	
Datatype	String	
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description	
Name	ACCRUALSTARTDAYRPR	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMONRPR

Attribute	Description	
Name	ACCRUALSTARTMONRPR	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT

Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description
Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ

Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,F; length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,F; length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B; length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

INTACCRFREQ

Attribute	**Description**
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	enumeration / D,M,Q,H,A
	length / 1

TOP

INTACCRSTARTDAY

Attribute	**Description**
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	**Description**
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	enumeration / 1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits / 2

TOP

EXCHRATECODE

Attribute	**Description**
Name	EXCHRATECODE

Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.95.QuerySEPortfolioSec

Query of Security Portfolio Definition

2.95.1.SE-Portfolio-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master-IO*
    - *PRDCD*
    - *PORTFOLIOID*
    - *EXREF*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *CURRENCY*
    - *CUSTOMER*
    - *CUSTACCBRN*
    - *CUSTOMERACC*
    - *ASSETACCBASIS*
    - *PORTFOLIOCOSTMETH*
    - *BOOKRIGHTS*
    - *BOOKWARRANTS*
    - *AUTOLIQFORCORPACT*
    - *CORPUSACC*

SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON

REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
RESALLOW

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Query Request Done.

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Includes Securities Portfolio Query Input Only type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTACCBRN

Attribute	Description

Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS

Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW

Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD

Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E length / 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String

Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number

Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDFREQ

Attribute	Description
Name	STATEHOLDFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: S,E,Y length: 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number

Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description
Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,L,X; length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,H length: 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

EQUITIES

Attribute	**Description**	
Name	EQUITIES	
Datatype	String	
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

RIGHTS

Attribute	**Description**	
Name	RIGHTS	
Datatype	String	
Description	Indicates the Rights.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

WARRANT

Attribute	**Description**	
Name	WARRANT	
Datatype	String	
Description	Indicates the Warrants.M - Market Value, B - Book Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B
	length	1

TOP

TBILLS

Attribute	**Description**
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,F
	length	1

TOP

FWDACCRUAL

Attribute	**Description**	
Name	FWDACCRUAL	
Datatype	String	
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

FWDACCRUALMETH

Attribute	**Description**	
Name	FWDACCRUALMETH	
Datatype	String	
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,B,C,D,E,F,G,H,I
	length	1

TOP

FWDACCRUALFREQ

Attribute	**Description**	
Name	FWDACCRUALFREQ	
Datatype	String	
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

FWDACCRUALSTARTDAY

Attribute	**Description**

Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

2.95.2.SE-Portfolio-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Master*
      - *PRDCD*
      - *PRDDESC*
      - *PORTFOLIOID*
      - *PORTREF*
      - *EXREF*
      - *PORTFOLIOTYPE*
      - *PORTFOLIODESC*
      - *BRANCH*
      - *BRANCHDESC*
      - *CURRENCY*
      - *CURRENCYDESC*
      - *CUSTOMER*
      - *SHORTNAME*
      - *CUSTACCBRN*
      - *CUSTACCBRNDESC*
      - *CUSTOMERACC*
      - *CUSTOMERACCDESC*

ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT

UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow

- *PRODDISALLOWCODE*
- *PRODDISALLOWDESC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Pfolio-Securities-Access

- *SECUID*
- *SECUPRODCODE*
- *SECUDESC*
- *ALLOWED*
- *PORTFOLIOID*

Role-To-Head-1

- *PORTFOLIOID*
- *PORTFOLIODESC*
- *ROLETOHEAD*
- *ROLETOHEADDESC*

Role-To-Head-2

- *PORTFOLIOID*
- *SECUPROD*
- *SECUDESC*
- *ROLETOHEADDET*
- *ROLETOHEADDESCDET*

Role-To-Head-3

- *PORTFOLIOID*
- *INTERNALSECID*
- *INTERNALSECDESC*
- *ROLETOHEADCLASS*
- *ROLETOHEADDESCCLASS*

Pf-Sec-Price-Mapping

- *SPSECUID*
- *SPPRICECODE*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*

CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10

FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Portfolio-Master-IO

PRDCD
PORTFOLIOID
EXREF
PORTFOLIODESC
BRANCH
CURRENCY
CUSTOMER
CUSTACCBRN
CUSTOMERACC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS

AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ

REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
RESALLOW
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Query Response Done.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Includes Securities Portfolio Query Master type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String

Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACCBRNDESC

Attribute	Description	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMERACC

Attribute	Description	
Name	CUSTOMERACC	
Datatype	String	
Description	Indicates the Customer Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CUSTOMERACCDESC

Attribute	Description	
Name	CUSTOMERACCDESC	
Datatype	String	
Description	Indicates the customer account Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASSETACCBASIS

Attribute	Description	
Name	ASSETACCBASIS	
Datatype	String	
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,N
	length	1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E length / 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,B,C,D,E,F,G,H,I
	length	1

TOP

ACCRUALFREQRPR

Attribute	Description	
Name	ACCRUALFREQRPR	
Datatype	String	
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description	
Name	ACCRUALSTARTDAYRPR	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMONRPR

Attribute	Description	
Name	ACCRUALSTARTMONRPR	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXCHRATECODEDESC

Attribute	**Description**	
Name	EXCHRATECODEDESC	
Datatype	String	
Description	Indicates the Exchange Rate Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESALLOW

Attribute	**Description**	
Name	RESALLOW	
Datatype	String	
Description	Indicates the allowed. A- Allowed, D - Disallowed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D
	length	1

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MOD_NO

Attribute	**Description**	
Name	MOD_NO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SUBSYSTEMSTAT

Attribute	Description	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sec-Prod-Disallow

Attribute	**Description**	
Name	Sec-Prod-Disallow	
Datatype		
Description	Includes Security Product Disallow details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODDISALLOWCODE

Attribute	**Description**	
Name	PRODDISALLOWCODE	
Datatype	String	
Description	Indicates Code of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDISALLOWDESC

Attribute	**Description**	
Name	PRODDISALLOWDESC	
Datatype	String	
Description	Indicates Description of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Includes Securities Portfolio Query Input Only type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String

Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description

Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E length / 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.96.ReopenSEPortfolio

Reopen Security Portfolio Definition

2.96.1.SE-Portfolio-Reopen-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*

CUSTOMERACC
CUSTOMERACCDESC
ASSETACCBASIS
PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR

ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL
REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow
- *PRODDISALLOWCODE*
- *PRODDISALLOWDESC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Pfolio-Securities-Access
- *SECUID*
- *SECUPRODCODE*

- *SECUDESC*
- *ALLOWED*
- *PORTFOLIOID*

Role-To-Head-1

- *PORTFOLIOID*
- *PORTFOLIODESC*
- *ROLETOHEAD*
- *ROLETOHEADDESC*

Role-To-Head-2

- *PORTFOLIOID*
- *SECUPROD*
- *SECUDESC*
- *ROLETOHEADDET*
- *ROLETOHEADDESCDET*

Role-To-Head-3

- *PORTFOLIOID*
- *INTERNALSECID*
- *INTERNALSECDESC*
- *ROLETOHEADCLASS*
- *ROLETOHEADDESCCLASS*

Pf-Sec-Price-Mapping

- *SPSECUID*
- *SPPRICECODE*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8

FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Advice-Details
MSGTYPE
PARTYID
MEDIUM
SUPPRESS
PRIORITY
CHGREQ

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Reopen Request.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Includes Securities Portfolio Reopen Master type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the Portfolio Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTOMER

Attribute	**Description**	
Name	CUSTOMER	
Datatype	String	
Description	Indicates the Customer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHORTNAME

Attribute	**Description**	
Name	SHORTNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCBRN

Attribute	**Description**	
Name	CUSTACCBRN	
Datatype	String	
Description	Indicates the Customer Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACCBRNDESC

Attribute	**Description**	
Name	CUSTACCBRNDESC	
Datatype	String	
Description	Indicates the Branch Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: C,W length: 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

ACCRUALSTARTMON

Attribute	**Description**	
Name	ACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	**Description**	
Name	ACCRUEHOLDTAXTBILLDISC	
Datatype	String	
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDREQD

Attribute	**Description**	
Name	STATEHOLDREQD	
Datatype	String	
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**
Name	STATEHOLDFREQ
Datatype	String

Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATHOSTARTDAY

Attribute	Description
Name	STATHOSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATHOSTARTMONTH

Attribute	Description
Name	STATHOSTARTMONTH
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMHOLDSNO

Attribute	Description
Name	PREVSTMHOLDSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD

Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,E,Y; length / 1

TOP

ACCRUEDISC

Attribute	Description
Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N; length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

UNSETTLEDDEALREVAL

Attribute	Description

Name	UNSETTLEDDEALREVAL
Datatype	String
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REVALLEVEL

Attribute	Description
Name	REVALLEVEL
Datatype	String
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,D length / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E length / 1

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description
Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description
Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,10,11,12</td></tr><tr><td>totalDigits</td><td>2</td></tr></table>

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,B,F</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,B,F</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,B</td></tr><tr><td>length</td><td>1</td></tr></table>

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration: M,B length: 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: M,B,F length: 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

FWDACCRUALSTARTDAY

Attribute	Description	
Name	FWDACCRUALSTARTDAY	
Datatype	Number	
Description	Indicates the Accrual Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

FWDACCRUALSTARTMON

Attribute	Description	
Name	FWDACCRUALSTARTMON	
Datatype	Number	
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

INTERESTACCRUAL

Attribute	Description	
Name	INTERESTACCRUAL	
Datatype	String	
Description	Indicates the Interest Accrual.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A; length / 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,10,11,12; totalDigits / 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

EXCHRATECODEDESC

Attribute	Description
Name	EXCHRATECODEDESC

Datatype	String
Description	Indicates the Exchange Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESALLOW

Attribute	Description
Name	RESALLOW
Datatype	String
Description	Indicates the allowed. A- Allowed, D - Disallowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D length / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes the Portfolio SK Mapping details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates the SK Location ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates the SK Location Account.
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sec-Prod-Disallow

Attribute	Description
Name	Sec-Prod-Disallow
Datatype	
Description	Includes the Sceurity Product Disallow details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRODDISALLOWCODE

Attribute	Description
Name	PRODDISALLOWCODE
Datatype	String
Description	Indicates the Product Disallow Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRODDISALLOWDESC

Attribute	Description
Name	PRODDISALLOWDESC
Datatype	String
Description	Indicates the Product Disallow Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes the Portfolio Securities Access details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates the security ID.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates the security Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates whether allowed or not. Y - Yes, N - No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y; length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates the Role to Head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates the Role to Head description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes the Role to Head detail.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String

Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates the Security Product.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates the Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates the Role to Head Additional details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates the Role to head Additional description details.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	

Description	Includes the Role to Head Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates the Internal Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates the Internal Security Description.
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates the Role to Head Class details.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS

Datatype	String
Description	Indicates the Role to Head Description Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes the Portfolio Security Price Mapping.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates the Security ID.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes the Management information System.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS5

Attribute	Description

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	Includes the Advice Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	Indicates the message type.
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	Indicates the party ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	Indicates the medium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	Indicates the suppress.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	Indicates the priority.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 1

TOP

CHGREQ

Attribute	Description
Name	CHGREQ

Datatype	String
Description	Indicates the charge required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1 minLength / 1

TOP

2.96.2.SE-Portfolio-Reopen-Req-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Portfolio-Master-IO*
  - *PORTID*
  - *PORTREF*
  - *EXREF*
  - *EVNTNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Query Request Done.

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Includes Securities Portfolio Reopen Input Only type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXREF

Attribute	**Description**	
Name	EXREF	
Datatype	String	
Description	Indicates the External reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVNTNO

Attribute	**Description**	
Name	EVNTNO	
Datatype	Number	
Description	Indicates Event number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

2.96.3.SE-Portfolio-Reopen-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Portfolio-Master*
    - *PRDCD*
    - *PRDDESC*
    - *PORTFOLIOID*
    - *PORTREF*
    - *EXREF*
    - *PORTFOLIOTYPE*
    - *PORTFOLIODESC*
    - *BRANCH*
    - *BRANCHDESC*
    - *CURRENCY*
    - *CURRENCYDESC*
    - *CUSTOMER*
    - *SHORTNAME*
    - *CUSTACCBRN*
    - *CUSTACCBRNDESC*
    - *CUSTOMERACC*
    - *CUSTOMERACCDESC*
    - *ASSETACCBASIS*

PORTFOLIOCOSTMETH
BOOKRIGHTS
BOOKWARRANTS
AUTOLIQFORCORPACT
CORPUSACC
SHORTPOSALLOW
ACCRUEWITHHOLDTAXCOUP
BANKERSACCEPT
CONTRAHOLDALLOW
VALIDCONTRAHOLD
CORPACTNOTICEREQ
NOTICEDAY
NOTICEDAYTYPE
CORPACTREQD
ACCRUEDISCTBILL
ACCRUALFREQ
ACCRUALSTARTDAY
ACCRUALSTARTMON
ACCRUEHOLDTAXTBILLDISC
STATEHOLDREQD
STATEHOLDFREQ
STATHOSTARTDAY
STATHOSTARTMONTH
PREVSTMHOLDSNO
STATETXNSREQD
STATETXNFREQ
STATTXNSTARTDAY
STATTXNSTARTMON
PREVSTMTXNSNO
ACCRUEPREMIUM
ACCRUEPREMMETH
ACCRUEDISC
ACCRUEDISCMETH
ACCRUALMETHDPR
ACCRUALFREQDPR
ACCRUALSTARTDAYDPR
ACCRUALSTARTMONTDPR
ACCRUEREDMPREM
ACCRUALMETHRPR
ACCRUALFREQRPR
ACCRUALSTARTDAYRPR
ACCRUALSTARTMONRPR
REVALUSETTLEPOSIT
UNSETTLEDDEALREVAL

REVALLEVEL
REVALMETH
REVALFREQ
REVALSTARDAY
REVALSTARTMON
REALIZEDREVAL
REALIZEDREVALMETH
LOCOMBASIS
REALIZEREVALFREQ
REALIZEREVALSTARTDAY
REALIZEREVALSTARTMON
BONDS
EQUITIES
RIGHTS
WARRANT
TBILLS
FWDACCRUAL
FWDACCRUALMETH
FWDACCRUALFREQ
FWDACCRUALSTARTDAY
FWDACCRUALSTARTMON
INTERESTACCRUAL
INTACCRFREQ
INTACCRSTARTDAY
INTACCRSTARTMON
EXCHRATECODE
EXCHRATECODEDESC
RESALLOW
RECORD_STAT
MOD_NO
SUBSYSTEMSTAT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
SECALLOWEDFLAG
CONTSTAT
Portfolio-Sk-Mapping
- *SKLOCATID*
- *SKLACC*
- *PORTFOLIOID*
- *PORTFOLIODESC*

Sec-Prod-Disallow

PRODDISALLOWCODE
PRODDISALLOWDESC
PORTFOLIOID
PORTFOLIODESC
Pfolio-Securities-Access
SECUID
SECUPRODCODE
SECUDESC
ALLOWED
PORTFOLIOID
Role-To-Head-1
PORTFOLIOID
PORTFOLIODESC
ROLETOHEAD
ROLETOHEADDESC
Role-To-Head-2
PORTFOLIOID
SECUPROD
SECUDESC
ROLETOHEADDET
ROLETOHEADDESCDET
Role-To-Head-3
PORTFOLIOID
INTERNALSECID
INTERNALSECDESC
ROLETOHEADCLASS
ROLETOHEADDESCCLASS
Pf-Sec-Price-Mapping
SPSECUID
SPPRICECODE
PORTFOLIOID
PORTFOLIODESC
Mis-Details
BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Security Portfolio Query Response Done.

TOP

Portfolio-Master

Attribute	Description
Name	Portfolio-Master
Datatype	
Description	Includes Securities Portfolio Reopen Master type details

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Portfolio Product.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTREF

Attribute	**Description**	
Name	PORTREF	
Datatype	String	
Description	Indicates the Portfolio Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EXREF

Attribute	**Description**	
Name	EXREF	
Datatype	String	
Description	Indicates the External Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIOTYPE

Attribute	Description
Name	PORTFOLIOTYPE
Datatype	String
Description	Indicates the Portfolio Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BRANCHDESC

Attribute	Description
Name	BRANCHDESC
Datatype	String
Description	Indicates the Branch Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRENCY

Attribute	Description

Name	CURRENCY
Datatype	String
Description	Indicates the Currency.
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRENCYDESC

Attribute	Description
Name	CURRENCYDESC
Datatype	String
Description	Indicates the Curreny Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHORTNAME

Attribute	Description
Name	SHORTNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCBRN

Attribute	Description
Name	CUSTACCBRN
Datatype	String
Description	Indicates the Customer Branch.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACCBRNDESC

Attribute	Description
Name	CUSTACCBRNDESC
Datatype	String
Description	Indicates the Branch Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTOMERACC

Attribute	Description
Name	CUSTOMERACC
Datatype	String
Description	Indicates the Customer Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTOMERACCDESC

Attribute	Description
Name	CUSTOMERACCDESC
Datatype	String
Description	Indicates the customer account Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASSETACCBASIS

Attribute	Description
Name	ASSETACCBASIS
Datatype	String
Description	Indicates the Asset Accounting Basis.A - Accrual, N - Non Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N length / 1

TOP

PORTFOLIOCOSTMETH

Attribute	Description
Name	PORTFOLIOCOSTMETH
Datatype	String
Description	Indicates the Portfolio Costing Method.D - Deal Matching, L - LIFO, F - FIFO, W - WAC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W length / 1

TOP

BOOKRIGHTS

Attribute	Description
Name	BOOKRIGHTS
Datatype	String
Description	Indicates the Book Rights.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

BOOKWARRANTS

Attribute	Description
Name	BOOKWARRANTS
Datatype	String
Description	Indicates the Book Warrants.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

AUTOLIQFORCORPACT

Attribute	Description
Name	AUTOLIQFORCORPACT
Datatype	String
Description	Indicates the Auto Liquidate for Corporate Actions.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CORPUSACC

Attribute	Description
Name	CORPUSACC
Datatype	String
Description	Indicates the Corpus Account.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

SHORTPOSALLOW

Attribute	Description
Name	SHORTPOSALLOW
Datatype	String
Description	Indicates the Short Position Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

ACCRUEWITHHOLDTAXCOUP

Attribute	Description
Name	ACCRUEWITHHOLDTAXCOUP
Datatype	String
Description	Indicates the Accrue Withholding Tax for Coupons.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

BANKERSACCEPT

Attribute	Description
Name	BANKERSACCEPT
Datatype	String
Description	Indicates the Bankers Acceptance.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

CONTRAHOLDALLOW

Attribute	Description
Name	CONTRAHOLDALLOW
Datatype	String
Description	Indicates the Contra Holding Allowed.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

VALIDCONTRAHOLD

Attribute	Description
Name	VALIDCONTRAHOLD
Datatype	String
Description	Indicates Validate When.O - Online, E - EOTI
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: O,E length: 1

TOP

CORPACTNOTICEREQ

Attribute	Description
Name	CORPACTNOTICEREQ
Datatype	String
Description	Indicates the Corporate Action Notice Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

NOTICEDAY

Attribute	Description
Name	NOTICEDAY
Datatype	Number
Description	Indicates the Notice Days.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

NOTICEDAYTYPE

Attribute	Description
Name	NOTICEDAYTYPE
Datatype	String
Description	Indicates the Notice Days Type.C - Calender Days, W - Working Days.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W length / 1

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates the Corporate Action Required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCTBILL

Attribute	Description
Name	ACCRUEDISCTBILL
Datatype	String
Description	Indicates the Accrue Discount for T-BILL.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALFREQ

Attribute	Description
Name	ACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D -Daily,M -Monthly,Q -Quarterly,H -Half Yearly,A -Annual.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAY

Attribute	Description
Name	ACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMON

Attribute	Description
Name	ACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEHOLDTAXTBILLDISC

Attribute	Description
Name	ACCRUEHOLDTAXTBILLDISC
Datatype	String
Description	Indicates the Accrue Withholding Tax For T-BILL Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATEHOLDREQD

Attribute	Description
Name	STATEHOLDREQD
Datatype	String
Description	Indicates the Statement Of Holdings required.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

STATEHOLDFREQ

Attribute	**Description**	
Name	STATEHOLDFREQ	
Datatype	String	
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A
	length	1

TOP

STATHOSTARTDAY

Attribute	**Description**	
Name	STATHOSTARTDAY	
Datatype	Number	
Description	Indicates the Statement Start Day.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

STATHOSTARTMONTH

Attribute	**Description**	
Name	STATHOSTARTMONTH	
Datatype	Number	
Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,8,9,10,11,12
	totalDigits	2

TOP

PREVSTMHOLDSNO

Attribute	**Description**
Name	PREVSTMHOLDSNO

Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

STATETXNSREQD

Attribute	Description
Name	STATETXNSREQD
Datatype	String
Description	Indicates the Statement Of Transactions required.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

STATETXNFREQ

Attribute	Description
Name	STATETXNFREQ
Datatype	String
Description	Indicates the Statement Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

STATTXNSTARTDAY

Attribute	Description
Name	STATTXNSTARTDAY
Datatype	Number
Description	Indicates the Statement Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

STATTXNSTARTMON

Attribute	Description
Name	STATTXNSTARTMON
Datatype	Number

Description	Indicates the Statement Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

PREVSTMTXNSNO

Attribute	Description
Name	PREVSTMTXNSNO
Datatype	Number
Description	Indicates the Statement Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 5

TOP

ACCRUEPREMIUM

Attribute	Description
Name	ACCRUEPREMIUM
Datatype	String
Description	Indicates the Accrue Premium. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEPREMMETH

Attribute	Description
Name	ACCRUEPREMMETH
Datatype	String
Description	Indicates the Accrue Premium.S - Straight Line, E - Exponential, Y - Constant Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUEDISC

Attribute	Description

Name	ACCRUEDISC
Datatype	String
Description	Indicates the Accrue Discount.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUEDISCMETH

Attribute	Description
Name	ACCRUEDISCMETH
Datatype	String
Description	Indicates the Accrue Discount.S - Straight Line, E - Exponential, Y - Constant Yield
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y length / 1

TOP

ACCRUALMETHDPR

Attribute	Description
Name	ACCRUALMETHDPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

ACCRUALFREQDPR

Attribute	Description
Name	ACCRUALFREQDPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

ACCRUALSTARTDAYDPR

Attribute	Description
Name	ACCRUALSTARTDAYDPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

ACCRUALSTARTMONTDPR

Attribute	Description
Name	ACCRUALSTARTMONTDPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

ACCRUEREDMPREM

Attribute	Description
Name	ACCRUEREDMPREM
Datatype	String
Description	Indicates the Accrue Redemption Premium.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

ACCRUALMETHRPR

Attribute	Description
Name	ACCRUALMETHRPR
Datatype	String
Description	Indicates the Accrual Method. A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: A,B,C,D,E,F,G,H,I length: 1

TOP

ACCRUALFREQRPR

Attribute	Description
Name	ACCRUALFREQRPR
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

ACCRUALSTARTDAYRPR

Attribute	Description
Name	ACCRUALSTARTDAYRPR
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

ACCRUALSTARTMONRPR

Attribute	Description
Name	ACCRUALSTARTMONRPR
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

REVALUSETTLEPOSIT

Attribute	Description
Name	REVALUSETTLEPOSIT
Datatype	String
Description	Indicates the Revaluation of Settled Positions.Y - Yes, N - No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

UNSETTLEDDEALREVAL

Attribute	**Description**	
Name	UNSETTLEDDEALREVAL	
Datatype	String	
Description	Indicates the Revaluation of Unsettled Positions.Y - Yes, N - No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N
	length	1

TOP

REVALLEVEL

Attribute	**Description**	
Name	REVALLEVEL	
Datatype	String	
Description	Indicates the Revaluation Level. P - Position, D - Deal Matching	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,D
	length	1

TOP

REVALMETH

Attribute	**Description**	
Name	REVALMETH	
Datatype	String	
Description	Indicates the Revaluation Method. M - MTM-BV, L - LOCOM, E - MTM-EIM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,L,E
	length	1

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ
Datatype	String

Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REVALSTARDAY

Attribute	Description
Name	REVALSTARDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REVALSTARTMON

Attribute	Description
Name	REVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

REALIZEDREVAL

Attribute	Description
Name	REALIZEDREVAL
Datatype	String
Description	Indicates the Realized Revaluation.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

REALIZEDREVALMETH

Attribute	Description

Name	REALIZEDREVALMETH
Datatype	String
Description	Indicates the Revaluation Method.M - MTM, L - LOCOM, X - MTM-LOCOM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X length / 1

TOP

LOCOMBASIS

Attribute	Description
Name	LOCOMBASIS
Datatype	String
Description	Indicates the LOCOM Basis. A - Acquisition Cost, H - Holding Cost
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,H length / 1

TOP

REALIZEREVALFREQ

Attribute	Description
Name	REALIZEREVALFREQ
Datatype	String
Description	Indicates the Revaluation Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

REALIZEREVALSTARTDAY

Attribute	Description
Name	REALIZEREVALSTARTDAY
Datatype	Number
Description	Indicates the Revaluation Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

REALIZEREVALSTARTMON

Attribute	Description

Name	REALIZEREVALSTARTMON
Datatype	Number
Description	Indicates the Revaluation Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

BONDS

Attribute	Description
Name	BONDS
Datatype	String
Description	Indicates the Bonds. M - Market Value, B - Book Value, F - Face Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

EQUITIES

Attribute	Description
Name	EQUITIES
Datatype	String
Description	Indicates the Equities.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

RIGHTS

Attribute	Description
Name	RIGHTS
Datatype	String
Description	Indicates the Rights.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

WARRANT

Attribute	Description
Name	WARRANT
Datatype	String
Description	Indicates the Warrants.M - Market Value, B - Book Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B length / 1

TOP

TBILLS

Attribute	Description
Name	TBILLS
Datatype	String
Description	Indicates the Treausry Bills.M - Market Value, B - Book Value, F - Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F length / 1

TOP

FWDACCRUAL

Attribute	Description
Name	FWDACCRUAL
Datatype	String
Description	Indicates the Forward P/L Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N length / 1

TOP

FWDACCRUALMETH

Attribute	Description
Name	FWDACCRUALMETH
Datatype	String
Description	Indicates the Accrual Method.A - 30(Euro)/360, B - 30(US)/360, C - Actual/360, D - 30(Euro)/365, E - 30(US)/365, F - Actual/365, G - 30(Euro)/Actual, H - 30(US)/Actual,I - Actual/Actual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I length / 1

TOP

FWDACCRUALFREQ

Attribute	Description
Name	FWDACCRUALFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A length / 1

TOP

FWDACCRUALSTARTDAY

Attribute	Description
Name	FWDACCRUALSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

FWDACCRUALSTARTMON

Attribute	Description
Name	FWDACCRUALSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11-November,12 - December
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits / 2

TOP

INTERESTACCRUAL

Attribute	Description
Name	INTERESTACCRUAL
Datatype	String
Description	Indicates the Interest Accrual.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration: Y,N length: 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates the Accrual Frequency.D - Daily, M - Monthly, Q - Quarterly, H - Half Yearly,A - Annually
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: D,M,Q,H,A length: 1

TOP

INTACCRSTARTDAY

Attribute	Description
Name	INTACCRSTARTDAY
Datatype	Number
Description	Indicates the Accrual Start Day.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 2

TOP

INTACCRSTARTMON

Attribute	Description
Name	INTACCRSTARTMON
Datatype	Number
Description	Indicates the Accrual Start Month.1 - January,2 - February, 3 - March,4 - April,5 - May,6 - June,7 - July, 8 - August,9 - September,10 - October,11- November,12 - December
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: 1,2,3,4,5,6,7,8,9,10,11,12 totalDigits: 2

TOP

EXCHRATECODE

Attribute	Description
Name	EXCHRATECODE
Datatype	String
Description	Indicates the Exchange Rate Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXCHRATECODEDESC

Attribute	**Description**	
Name	EXCHRATECODEDESC	
Datatype	String	
Description	Indicates the Exchange Rate Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESALLOW

Attribute	**Description**	
Name	RESALLOW	
Datatype	String	
Description	Indicates the allowed. A- Allowed, D - Disallowed.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D
	length	1

TOP

RECORD_STAT

Attribute	**Description**	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MOD_NO

Attribute	**Description**	
Name	MOD_NO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SUBSYSTEMSTAT

Attribute	Description	
Name	SUBSYSTEMSTAT	
Datatype	String	
Description	Indicates Subsystem Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALLOWEDFLAG

Attribute	Description
Name	SECALLOWEDFLAG
Datatype	String
Description	Indicates Securities Allowed Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status Active : A Hold : H Closed : S Cancelled : K Reversed : V
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Sk-Mapping

Attribute	Description
Name	Portfolio-Sk-Mapping
Datatype	
Description	Includes Portfolio Safe Keeping Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLOCATID

Attribute	Description
Name	SKLOCATID
Datatype	String
Description	Indicates Safe Keeping Location ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLACC

Attribute	Description
Name	SKLACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sec-Prod-Disallow

Attribute	**Description**	
Name	Sec-Prod-Disallow	
Datatype		
Description	Includes Security Product Disallow details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PRODDISALLOWCODE

Attribute	**Description**	
Name	PRODDISALLOWCODE	
Datatype	String	
Description	Indicates Code of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRODDISALLOWDESC

Attribute	**Description**	
Name	PRODDISALLOWDESC	
Datatype	String	
Description	Indicates Description of the Product which is disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIOID

Attribute	**Description**	
Name	PORTFOLIOID	
Datatype	String	
Description	Indicates the Portfolio Identification.	
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String
Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Securities-Access

Attribute	Description
Name	Pfolio-Securities-Access
Datatype	
Description	Includes Portfolio Securities Access details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECUID

Attribute	Description
Name	SECUID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPRODCODE

Attribute	Description
Name	SECUPRODCODE
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ALLOWED

Attribute	Description
Name	ALLOWED
Datatype	String
Description	Indicates Allowed Disallowed : N Allowed : Y
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y length / 1

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Role-To-Head-1

Attribute	Description
Name	Role-To-Head-1
Datatype	
Description	Includes Role To Head Mapping 1 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ROLETOHEAD

Attribute	Description
Name	ROLETOHEAD
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ROLETOHEADDESC

Attribute	Description
Name	ROLETOHEADDESC
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Role-To-Head-2

Attribute	Description
Name	Role-To-Head-2
Datatype	
Description	Includes Role To Head Mapping 2 details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECUPROD

Attribute	Description
Name	SECUPROD
Datatype	String
Description	Indicates Security Product
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECUDESC

Attribute	Description
Name	SECUDESC
Datatype	String
Description	Indicates Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADDET

Attribute	Description
Name	ROLETOHEADDET
Datatype	String
Description	Indicates Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCDET

Attribute	Description
Name	ROLETOHEADDESCDET
Datatype	String
Description	Indicates Role To Head Description
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Role-To-Head-3

Attribute	Description
Name	Role-To-Head-3
Datatype	
Description	Includes Role To Head Mapping 3 details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECID

Attribute	Description
Name	INTERNALSECID
Datatype	String
Description	Indicates Internal Security ID
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTERNALSECDESC

Attribute	Description
Name	INTERNALSECDESC
Datatype	String
Description	Indicates Internal Security Description
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

ROLETOHEADCLASS

Attribute	Description
Name	ROLETOHEADCLASS
Datatype	String
Description	Indicates Class of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ROLETOHEADDESCCLASS

Attribute	Description
Name	ROLETOHEADDESCCLASS
Datatype	String
Description	Indicates Class Description of the Role To Head
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pf-Sec-Price-Mapping

Attribute	Description
Name	Pf-Sec-Price-Mapping
Datatype	
Description	Includes Portfolio Security Price Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECUID

Attribute	Description
Name	SPSECUID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRICECODE

Attribute	Description
Name	SPPRICECODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIOID

Attribute	Description
Name	PORTFOLIOID
Datatype	String
Description	Indicates the Portfolio Identification.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFOLIODESC

Attribute	Description
Name	PORTFOLIODESC
Datatype	String

Description	Indicates the Portfolio Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number

Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description

Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates The Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RTFLAG

Attribute	**Description**	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PROCFLG

Attribute	**Description**	
Name	PROCFLG	
Datatype	String	
Description	Indicates ProcflgType R-Related Reference Number A-Related Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.96.4.SE-Portfolio-Reopen-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Portfolio-Master-PK*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
    - *Portfolio-Master-IO*
      - *PORTID*
      - *PORTREF*
      - *EXREF*
      - *EVNTNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the information relating the Security Portfolio Query Response Done.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Portfolio-Master-PK

Attribute	Description
Name	Portfolio-Master-PK
Datatype	
Description	Includes Securities Portfolio Reopen Primary Key type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TOP

Portfolio-Master-IO

Attribute	Description
Name	Portfolio-Master-IO
Datatype	
Description	Includes Securities Portfolio Reopen Input Only type details

TOP

PORTID

Attribute	Description
Name	PORTID
Datatype	String
Description	Indicates the Portfolio ID.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTREF

Attribute	Description
Name	PORTREF
Datatype	String
Description	Indicates the portfolio Reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXREF

Attribute	Description
Name	EXREF
Datatype	String
Description	Indicates the External reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVNTNO

Attribute	Description
Name	EVNTNO
Datatype	Number
Description	Indicates Event number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.97.QueryBrnPrm

Query of Securities Repo and Reverse Repo Branch Parameters

2.97.1.SE-QueryBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Se-Branch-Params-IO*
    - *BRNCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Se-Branch-Params-IO

Attribute	Description
Name	Se-Branch-Params-IO
Datatype	
Description	Includes Securities Branch Parameters Query Input Only type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.97.2.SE-QueryBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Se-Branch-Params-IO*
      - *BRNCD*
    - *Se-Branch-Params-Full*
      - *BRNCD*
      - *PROCTILLNWD*
      - *ACCVDTMVACRSMNTHS*
      - *CPNMVACRSMNTHS*
      - *REVALLVL*
      - *BTN_UDF*
      - *DEALLVLACCR*
      - *BRNNAME*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*

ONCEAUTH
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Se-Branch-Params-IO

Attribute	Description
Name	Se-Branch-Params-IO
Datatype	
Description	Includes Securities Branch Parameters Query Input Only type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Se-Branch-Params-Full

Attribute	Description
Name	Se-Branch-Params-Full
Datatype	
Description	Includes Securities Branch Parameters Query Full type details

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILLNWD

Attribute	Description
Name	PROCTILLNWD
Datatype	String
Description	Indicates the Process Till Next Working day.Y-Yes,N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCVDTMVACRSMNTHS

Attribute	Description
Name	ACCVDTMVACRSMNTHS
Datatype	String
Description	Indicates the Accounting Value Date. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPNMVACRSMNTHS

Attribute	Description
Name	CPNMVACRSMNTHS
Datatype	String
Description	Indicates the Coupon Plotting. Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALLVL

Attribute	Description
Name	REVALLVL
Datatype	String
Description	Indicates the Revaluation Level. P - Portfolio Restrictions, H - Holding.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

BTN_UDF

Attribute	Description
Name	BTN_UDF
Datatype	String
Description	Indicates the User defined Field.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALLVLACCR

Attribute	Description
Name	DEALLVLACCR
Datatype	String
Description	Indicates the Interest Accrual Level.Y - Yes, N - No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates the Branch Name.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes the UDF Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.98.QueryMarketCode

Query of Market Definition

2.98.1.SE-QueryMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Market-Master-IO*
    - *MKTCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Includes Securities Market Code Master Query Input Only type details

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.98.2.SE-QueryMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Market-Master-IO*
      - *MKTCD*
    - *Market-Master-Full*
      - *MKTCD*
      - *MKTDESC*
      - *MKTTYPE*
      - *MKTIDCD*
      - *OTCOSYSN*
      - *CTRYCD*
      - *LOCCCY*
      - *SKLOCID*
      - *PRICECD*
      - *HOLTP*
      - *HOLCCY*
      - *CPNBAS*
      - *DIVDBAS*
      - *WARBAS*
      - *RIGBAS*

SPTDTMET
SPTDYCNT
SPTDAYS
WEKSPTDT
IFSPTHOL
EXDTMT
EXDTCNTBAS
EXDAYS
WEKEXDT
IFEXDTHOL
MKTCAT
RENPERD
ANNMET
BNDCNTNR
BNDCNTDR
TBICNTNR
TBICNTDR
USBNDFM
TBRENPED
TBANNMET
PRMDISPD
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Market-Interest
- *INTMKTCD*
- *RNDBAS*
- *RATDEN*
- *ACDNTNUMMET*
- *ACDNTDENMET*
- *ACDNTDENMETBS*
- *ACDNTINCDT*
- *LIDNTNUMMT*
- *LIDNTDENMT*
- *LIDNTDENMTBS*
- *LIDCINDT*
- *DCMTSWIND*
- *PERCPN*
- *ALWASYRV*

- *PERREVN*
- *CPNFRQ*
- *CPNWEKDY*
- *CPNADHTOMNED*
- *REVNFRQ*
- *REVNWEKDY*
- *REVNADHMNT*
- *ZEINTFOREXPD*
- *ACCRDCBAS*
- *LIQDDCBAS*

Market-Spot-Date

- *SPTMKTCD*
- *SPTFRMDY*
- *SPTTODY*
- *SPTMNTHIND*
- *SPTFUTMNT*
- *SPTDYSPTDT*
- *SPTWKDYSPT*
- *SPTDTHOL*

Market-Ex-Date

- *EXMKTCD*
- *EXFRMDY*
- *EXTODY*
- *EXMNTIND*
- *EXPRVMNT*
- *EXDYEXDT*
- *EXWKDDT*
- *EXIFHLDY*

Product-Scheme

- *PRDORMKTCD*
- *SCHEME*
- *MODULE*
- *SCHONCEAUT*
- *Market-Issr-Tax*
  - *MKTISSRTAX*
  - *CMPNT*
  - *EVNTFORASS*
  - *BASAMTTAG*
  - *DFLTRTCD*
  - *DFLTWAIVER*
  - *ALRTCDAMND*
  - *AMNDAFTASSO*
  - *STOPASSOC*
  - *TAXMOD*

UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Market-Master-IO

Attribute	Description
Name	Market-Master-IO
Datatype	
Description	Includes Securities Market Code Master Query Input Only type details

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Market-Master-Full

Attribute	Description
Name	Market-Master-Full
Datatype	
Description	Includes Securities Market Code Master Query Full type details

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTDESC

Attribute	Description
Name	MKTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTTYPE

Attribute	Description
Name	MKTTYPE
Datatype	String
Description	Indicates Market Type STOCK EXCHANGE : S OVER THE COUNTER : O OTHERS : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,O,X,

TOP

MKTIDCD

Attribute	Description
Name	MKTIDCD
Datatype	String
Description	Indicates Market Identifier Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

OTCOSYSN

Attribute	Description
Name	OTCOSYSN
Datatype	String
Description	Indicates Over The Counter Option System Narrative
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	Indicates Country Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	Indicates Local Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECD

Attribute	Description
Name	PRICECD
Datatype	String
Description	Indicates Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

HOLTP

Attribute	Description
Name	HOLTP
Datatype	String
Description	Indicates Holiday Type LOCAL HOLIDAY : L CURRENCY HOLIDAY : C
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,L,C

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CPNBAS

Attribute	Description
Name	CPNBAS
Datatype	String
Description	Indicates Coupon Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

DIVDBAS

Attribute	Description
Name	DIVDBAS
Datatype	String
Description	Indicates Dividend Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

WARBAS

Attribute	Description
Name	WARBAS
Datatype	String
Description	Indicates Warrant Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

RIGBAS

Attribute	Description
Name	RIGBAS
Datatype	String
Description	Indicates Right Basis POSITIONS : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,H

TOP

SPTDTMET

Attribute	Description
Name	SPTDTMET
Datatype	String
Description	Indicates Spot Date Method ROLLING : R FIXED : F UNKNOWN : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F,U

TOP

SPTDYCNT

Attribute	Description
Name	SPTDYCNT
Datatype	String
Description	Indicates Spot Days Count Basis CALENDAR DAYS : C WORKING DAYS : W

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,W

TOP

SPTDAYS

Attribute	Description	
Name	SPTDAYS	
Datatype	Number	
Description	Indicates Spot Days	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WEKSPTDT

Attribute	Description	
Name	WEKSPTDT	
Datatype	String	
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	7,,1,2,3,4,5,6

TOP

IFSPTHOL

Attribute	Description	
Name	IFSPTHOL	
Datatype	String	
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

EXDTMT

Attribute	Description
Name	EXDTMT
Datatype	String

Description	Indicates Expiry Date Method ROLLING : R FIXED : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,R,F

TOP

EXDTCNTBAS

Attribute	Description
Name	EXDTCNTBAS
Datatype	String
Description	Indicates Expiry Days Count Basis CALENDAR DAYS : C WORKING DAYS : W
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	Indicates Expiry Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEKEXDT

Attribute	Description
Name	WEKEXDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTHOL

Attribute	Description

Name	IFEXDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	Indicates Market Category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,T,

TOP

RENPERD

Attribute	Description
Name	RENPERD
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNMET

Attribute	Description
Name	ANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BNDCNTNR

Attribute	Description
Name	BNDCNTNR
Datatype	String

Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

BNDCNTDR

Attribute	Description
Name	BNDCNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H,X

TOP

TBICNTNR

Attribute	Description
Name	TBICNTNR
Datatype	String
Description	Indicates Day Count Method Numerator ACTUAL : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,E,U

TOP

TBICNTDR

Attribute	Description
Name	TBICNTDR
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,,L,H

TOP

USBNDFM

Attribute	Description
Name	USBNDFM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBRENPED

Attribute	Description
Name	TBRENPED
Datatype	Number
Description	Indicates Reinvestment Period Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBANNMET

Attribute	Description
Name	TBANNMET
Datatype	String
Description	Indicates Annualizing Method SIMPLE : S COMPOUND : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

PRMDISPD

Attribute	Description
Name	PRMDISPD
Datatype	String
Description	Indicates Premium/Discount for Current Interest Period Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorised : A UnAuthorised : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Market-Interest

Attribute	**Description**	
Name	Market-Interest	
Datatype		
Description	Includes Interest details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTMKTCD

Attribute	Description	
Name	INTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RNDBAS

Attribute	Description	
Name	RNDBAS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

RATDEN

Attribute	Description	
Name	RATDEN	
Datatype	String	
Description	Indicates Rate Denomination Basis Per Annum : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ACDNTNUMMET

Attribute	Description
Name	ACDNTNUMMET
Datatype	String
Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACDNTDENMET

Attribute	Description
Name	ACDNTDENMET
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

ACDNTDENMETBS

Attribute	Description
Name	ACDNTDENMETBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

ACDNTINCDT

Attribute	Description
Name	ACDNTINCDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIDNTNUMMT

Attribute	Description
Name	LIDNTNUMMT
Datatype	String

Description	Indicates Numerator Method 30-EURO :30-EURO 30-US :30-US ACTUAL :ACTUAL 30-ISDA :30-ISDA 30-PSA :30-PSA ACTUAL-JAPANESE :ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIDNTDENMT

Attribute	Description
Name	LIDNTDENMT
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,360,365,ACTUAL,364

TOP

LIDNTDENMTBS

Attribute	Description
Name	LIDNTDENMTBS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,C

TOP

LIDCINDT

Attribute	Description
Name	LIDCINDT
Datatype	String
Description	Indicates Include To Date Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMTSWIND

Attribute	Description
Name	DCMTSWIND
Datatype	String
Description	Indicates Swift Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PERCPN

Attribute	Description
Name	PERCPN
Datatype	String
Description	Indicates Periodic Coupon Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALWASYRV

Attribute	Description
Name	ALWASYRV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PERREVN

Attribute	Description
Name	PERREVN
Datatype	String
Description	Indicates Periodic Revision Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNFRQ

Attribute	Description
Name	CPNFRQ
Datatype	String
Description	Indicates Coupon Frequency WEEKLY : W MONTHLY : 1M BI - MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M HALF - YEARLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS : 10M ONCE IN 11 MONTHS : 11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

CPNWEKDY

Attribute	Description
Name	CPNWEKDY
Datatype	String
Description	Indicates Weekday of Coupon MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

CPNADHTOMNED

Attribute	Description
Name	CPNADHTOMNED
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVNFRQ

Attribute	Description
Name	REVNFRQ
Datatype	String
Description	Indicates Revision Frequency WEEKLY : W MONTHLY: 1M BI - MONTHLY:2M QUARTERLY:3M ONCE IN 4 MONTHS:4M ONCE IN 5 MONTHS:5M HALF - YEARLY:6M ONCE IN 7 MONTHS:7M ONCE IN 8 MONTHS:8M ONCE IN 9 MONTHS:9M ONCE IN 10 MONTHS:10M ONCE IN 11 MONTHS:11M ANNUALLY:12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVNWEKDY

Attribute	Description
Name	REVNWEKDY
Datatype	String
Description	Indicates Weekday of Revision MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

REVNADHMNT

Attribute	Description
Name	REVNADHMNT
Datatype	String
Description	Indicates Adhere To Month End Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ZEINTFOREXPD

Attribute	Description	
Name	ZEINTFOREXPD	
Datatype	String	
Description	Indicates Zero Interest During Expiry Period Y for Yes;N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRDCBAS

Attribute	Description	
Name	ACCRDCBAS	
Datatype	String	
Description	Indicates 366 Basis LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LIQDDCBAS

Attribute	Description	
Name	LIQDDCBAS	
Datatype	String	
Description	Indicates 366 Basis of Liquidation LEAP YEAR: Y LEAP DATE: D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Market-Spot-Date

Attribute	Description	
Name	Market-Spot-Date	
Datatype		
Description	Includes Spot date details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTMKTCD

Attribute	Description	
Name	SPTMKTCD	
Datatype	String	
Description	Indicates Market Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SPTFRMDY

Attribute	Description	
Name	SPTFRMDY	
Datatype	Number	
Description	Indicates From Day	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

SPTTODY

Attribute	Description	
Name	SPTTODY	
Datatype	Number	
Description	Indicates To Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTMNTHIND

Attribute	Description	
Name	SPTMNTHIND	
Datatype	String	
Description	Indicates Month Indicator CURRENT :C FUTURE : F	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,F,

TOP

SPTFUTMNT

Attribute	Description
Name	SPTFUTMNT
Datatype	Number

Description	Indicates Future Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTDYSPTDT

Attribute	Description
Name	SPTDYSPTDT
Datatype	Number
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPTWKDYSPT

Attribute	Description
Name	SPTWKDYSPT
Datatype	String
Description	Indicates Weekday of Spot Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

SPTDTHOL

Attribute	Description
Name	SPTDTHOL
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Market-Ex-Date

Attribute	Description
Name	Market-Ex-Date
Datatype	
Description	Includes Expiry date details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMKTCD

Attribute	Description
Name	EXMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EXFRMDY

Attribute	Description
Name	EXFRMDY
Datatype	Number
Description	Indicates From Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EXTODY

Attribute	Description
Name	EXTODY
Datatype	Number
Description	Indicates To Day
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXMNTIND

Attribute	Description
Name	EXMNTIND
Datatype	String
Description	Indicates Month Indicator CURRENT :C FUTURE : F
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / C,P,

TOP

EXPRVMNT

Attribute	Description
Name	EXPRVMNT
Datatype	Number
Description	Indicates Previous Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXDYEXDT

Attribute	Description
Name	EXDYEXDT
Datatype	Number
Description	Indicates Expiry Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXWKDDT

Attribute	Description
Name	EXWKDDT
Datatype	String
Description	Indicates Weekday of Expiry Date MONDAY : 1 TUESDAY : 2 WEDNESDAY : 3 THURSDAY :4 FRIDAY :5 SATURDAY : 6 SUNDAY : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

EXIFHLDY

Attribute	Description
Name	EXIFHLDY
Datatype	String
Description	Indicates Holiday Treatment IGNORE : I BACKWARD : B FORWARD : F
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,F,B

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Includes Product Scheme details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMKTCD

Attribute	Description
Name	PRDORMKTCD
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

SCHONCEAUT

Attribute	Description
Name	SCHONCEAUT
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Market-Issr-Tax

Attribute	Description
Name	Market-Issr-Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MKTISSRTAX

Attribute	Description
Name	MKTISSRTAX
Datatype	String
Description	Indicates Market Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFORASS

Attribute	Description
Name	EVNTFORASS
Datatype	String
Description	Indicates Event For Association

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRTCD

Attribute	Description
Name	DFLTRTCD
Datatype	String
Description	Indicates Default Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVER

Attribute	Description
Name	DFLTWAIVER
Datatype	String
Description	Indicates Default Waiver Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALRTCDAMND

Attribute	Description
Name	ALRTCDAMND
Datatype	String
Description	Indicates Allow Rate Code Amendment Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTASSO

Attribute	Description
Name	AMNDAFTASSO
Datatype	String
Description	Indicates Amend After Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STOPASSOC

Attribute	Description
Name	STOPASSOC
Datatype	String
Description	Indicates Stop Association Y for Yes;N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXMOD

Attribute	Description
Name	TAXMOD
Datatype	String
Description	Indicates Module
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.99.QueryPriceDtl

Query of Securities Price Definition

2.99.1.SE-QueryPriceDtl-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-Master-IO*
    - *BRRCODE*
    - *SECURITYCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contain Primary key Fields

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE

Datatype	String
Description	Indicates Security Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.99.2.SE-QueryPriceDtl-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Master-IO*
      - *BRRCODE*
      - *SECURITYCODE*
    - *Price-Master-Full*
      - *BRRCODE*
      - *SECURITYCODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *Price-Detail*
        - *BRCODE*
        - *SECURITYCODE*
        - *PRICECODE*

MARKETVALUEDATE
PRICEQUOTATIONMETHOD
INTERESTQUOTATIONMETHOD
PRICE
LCYPRICE
INTAUTHSTAT
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Master-IO

Attribute	Description
Name	Price-Master-IO
Datatype	
Description	Contains Input Only Response of Query Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Price-Master-Full

Attribute	Description
Name	Price-Master-Full
Datatype	
Description	Contains Full Response of Query Price Details

TOP

BRRCODE

Attribute	Description
Name	BRRCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status Authorized : A UnAuthorized : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Statuus	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Price-Detail

Attribute	**Description**	
Name	Price-Detail	
Datatype		
Description	Includes Price Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRCODE

Attribute	**Description**	
Name	BRCODE	
Datatype	String	
Description	Indicates Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SECURITYCODE

Attribute	Description
Name	SECURITYCODE
Datatype	String
Description	Indicates Security Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRICECODE

Attribute	Description
Name	PRICECODE
Datatype	String
Description	Indicates Price Code
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MARKETVALUEDATE

Attribute	Description
Name	MARKETVALUEDATE
Datatype	Date
Description	Indicates Market Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRICEQUOTATIONMETHOD

Attribute	Description
Name	PRICEQUOTATIONMETHOD
Datatype	String
Description	Indicates Price Quotation Method ABSOLUTE PRICE : PRI PREMIUM / DISCOUNT : PRM %PRICE : PPR %PREMIUM / % DISCOUNT : PPM YIELD TO MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PPM,PPR,PRI,PRM,YTM,X

TOP

INTERESTQUOTATIONMETHOD

Attribute	Description
Name	INTERESTQUOTATIONMETHOD
Datatype	String
Description	Indicates Interest Quotation Method FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

PRICE

Attribute	Description
Name	PRICE
Datatype	Number
Description	Indicates Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYPRICE

Attribute	Description
Name	LCYPRICE
Datatype	Number
Description	Indicates Local Currency Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTAUTHSTAT

Attribute	Description
Name	INTAUTHSTAT
Datatype	String
Description	Indicates Interest Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.100.QueryRecord

Query of Securities Market Price Codes

2.100.1.SE-QueryRecord-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Price-code-IO*
    - *PCODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Price-code-IO

Attribute	Description
Name	Price-code-IO
Datatype	
Description	Indicates IO Product Code in FCUBS Request.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.100.2.SE-QueryRecord-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Price-Code-IO*
      - *PCODE*
    - *Price-Code-Full*
      - *PCODE*
      - *PDESC*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *UDFDETAILS*
        - *FUNCTIONID*
        - *FIELD_NAME*
        - *DATATYPE*
        - *FIELD_VALUE*

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Price-Code-IO

Attribute	Description
Name	Price-Code-IO
Datatype	
Description	Indicates FCUBS Primary Key Response.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Price-Code-Full

Attribute	Description
Name	Price-Code-Full
Datatype	
Description	Indicates FCUBS Full Response.

TOP

PCODE

Attribute	Description
Name	PCODE
Datatype	String
Description	Indicates Market Price Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PDESC

Attribute	Description

Name	PDESC
Datatype	String
Description	Indicates Price Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User id who created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user created the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User id who authorized the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates date and timestamp when the user authorized the record

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record status. Open : O Closed : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates the Once Authorization status.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.101.QuerySEBrnPrm

QuerySEBrnPrm

2.101.1.SE-QuerySEBrnPrm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Se-Branch-Params-IO*
    - *BRNCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Se-Branch-Params-IO

Attribute	Description
Name	Se-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

2.101.2.SE-QuerySEBrnPrm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Se-Branch-Params-IO*
      - *BRNCD*
    - *Se-Branch-Params-Full*
      - *BRNCD*
      - *PROCTILLNWD*
      - *ACCVDTMVACRSMNTHS*
      - *CPNMVACRSMNTHS*
      - *REVALLVL*
      - *DEALLVLACCR*
      - *BRNNAME*
      - *ACCRLVL*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Se-Branch-Params-IO

Attribute	Description
Name	Se-Branch-Params-IO
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Se-Branch-Params-Full

Attribute	Description
Name	Se-Branch-Params-Full
Datatype	
Description	

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

PROCTILLNWD

Attribute	Description
Name	PROCTILLNWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCVDTMVACRSMNTHS

Attribute	Description
Name	ACCVDTMVACRSMNTHS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CPNMVACRSMNTHS

Attribute	Description
Name	CPNMVACRSMNTHS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALLVL

Attribute	Description
Name	REVALLVL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DEALLVLACCR

Attribute	Description
Name	DEALLVLACCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

ACCRLVL

Attribute	Description
Name	ACCRLVL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.102.QuerySEMarketCode

QuerySEMarketCode

2.102.1.SE-QuerySEMarketCode-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Smm-IO*
    - *MKTCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.102.2.SE-QuerySEMarketCode-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Smm-IO*
      - *MKTCD*
    - *Smm-Full*
      - *MKTCAT*
      - *RNVPRD*
      - *ANNLMTHD*
      - *BDCN*
      - *BDCD*
      - *TDCN*
      - *TDCD*
      - *UBF*
      - *TRNVPRD*
      - *TBILLANNLMTHD*
      - *PRMDISCCURRPRD*
      - *MKTCD*
      - *MKTDSC*
      - *MKTTYP*
      - *MKIDCD*

OTSYSNARR
CTRYCD
LOCCCY
SKLOCID
PRYCCD
HOLTYP
HOLCCY
CPNBASIS
DVDNDBASIS
WARRNTBASIS
RYTSBASIS
SPTDTMTHD
SPTDAYSCNTBASIS
SPTDAYS
WEEKDAYOFSPTDT
IFSPTDTISHOL
EXTDTMTHD
EXDAYSCNTBASIS
EXDAYS
WEEKDAYOFEXDT
IFEXDTISHOL
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Smi
- *RDNGBASIS*
- *RATDENMBASIS*
- *ADNM*
- *ADDM*
- *ADDB*
- *ADINCLDTODT*
- *LDNM*
- *LDDM*
- *LDDB*
- *LDINCLDTODT*
- *DCNTMTHDSWIFTIND*
- *PRDCOUPN*
- *ALLWASYNCREV*
- *PRDREV*
- *COUPNFREQ*

- *COUPNWEEKDAY*
- *COUPNADHRETOMNTHEND*
- *RVSNFREQ*
- *RVSNWEEKDAY*
- *RVSNADHRETOMNTHEND*
- *ZEROINTFREXPRD*
- *ACCRDCNTBASIS366*
- *LQDDCNTBASIS366*

Smsd

- *MKTCD*
- *FRMDY*
- *TODY*
- *MONTHIND*
- *FUTMON*
- *DAYOFSPTDT*
- *WEEKDAYOFSPTDT*
- *IFSPTDTISHOL*

Tps

- *PRDORMKTCD*
- *SCHM*
- *MODL*
- *Tmit*
  - *CMPNT*
  - *EVNTFRASSOC*
  - *BASISAMTTAG*
  - *DFLTRATCD*
  - *DFLTWAIVR*
  - *ALLWRATECDAMMNDMENT*
  - *AMNDAFTRASSOC*
  - *STPASSOC*
  - *CLASSDSC*
  - *EVNTDSCR*
  - *DSC3*

Smed

- *FRMDY*
- *TODY*
- *MNTHIND*
- *PREVMNTHS*
- *DAYOFEXDT*
- *WEEKDAYOFEXDT*
- *IFEXDTISHOL*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Smm-IO

Attribute	Description
Name	Smm-IO
Datatype	
Description	

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Smm-Full

Attribute	Description
Name	Smm-Full
Datatype	
Description	

TOP

MKTCAT

Attribute	Description
Name	MKTCAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,I,T</td></tr></table>

TOP

RNVPRD

Attribute	Description

Name	RNVPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ANNLMTHD

Attribute	Description
Name	ANNLMTHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,C

TOP

BDCN

Attribute	Description
Name	BDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

BDCD

Attribute	Description
Name	BDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,L,H

TOP

TDCN

Attribute	Description
Name	TDCN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,E,U

TOP

TDCD

Attribute	Description	
Name	TDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,L,H

TOP

UBF

Attribute	Description	
Name	UBF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRNVPRD

Attribute	Description	
Name	TRNVPRD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNLMTHD

Attribute	Description	
Name	TBILLANNLMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,C

TOP

PRMDISCCURRPRD

Attribute	Description
Name	PRMDISCCURRPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTDSC

Attribute	Description
Name	MKTDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTTYP

Attribute	Description
Name	MKTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,O,X

TOP

MKIDCD

Attribute	Description
Name	MKIDCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

OTSYSNARR

Attribute	Description
Name	OTSYSNARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CTRYCD

Attribute	Description
Name	CTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LOCCCY

Attribute	Description
Name	LOCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRYCCD

Attribute	**Description**	
Name	PRYCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

HOLTYP

Attribute	**Description**	
Name	HOLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,L,C

TOP

HOLCCY

Attribute	**Description**	
Name	HOLCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CPNBASIS

Attribute	**Description**	
Name	CPNBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

DVDNDBASIS

Attribute	Description	
Name	DVDNDBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

WARRNTBASIS

Attribute	Description	
Name	WARRNTBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

RYTSBASIS

Attribute	Description	
Name	RYTSBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,P,H

TOP

SPTDTMTHD

Attribute	Description	
Name	SPTDTMTHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,R,F,U

TOP

SPTDAYSCNTBASIS

Attribute	Description
Name	SPTDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

SPTDAYS

Attribute	Description
Name	SPTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	Description
Name	IFSPTDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,B,F

TOP

EXTDTMTHD

Attribute	Description
Name	EXTDTMTHD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,R,F

TOP

EXDAYSCNTBASIS

Attribute	Description
Name	EXDAYSCNTBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,W

TOP

EXDAYS

Attribute	Description
Name	EXDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Smi

Attribute	Description
Name	Smi
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RDNGBASIS

Attribute	Description
Name	RDNGBASIS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,N

TOP

RATDENMBASIS

Attribute	**Description**	
Name	RATDENMBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ADNM

Attribute	**Description**	
Name	ADNM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ADDM

Attribute	**Description**	
Name	ADDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

ADDB

Attribute	**Description**	
Name	ADDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

ADINCLDTODT

Attribute	Description	
Name	ADINCLDTODT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LDNM

Attribute	Description	
Name	LDNM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LDDM

Attribute	Description	
Name	LDDM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,360,365,ACTUAL

TOP

LDDB

Attribute	Description	
Name	LDDB	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,C

TOP

LDINCLDTODT

Attribute	Description
Name	LDINCLDTODT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DCNTMTHDSWIFTIND

Attribute	Description
Name	DCNTMTHDSWIFTIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDCOUPN

Attribute	Description
Name	PRDCOUPN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLWASYNCREV

Attribute	Description
Name	ALLWASYNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDREV

Attribute	Description
Name	PRDREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COUPNFREQ

Attribute	Description
Name	COUPNFREQ
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M</td></tr></table>

TOP

COUPNWEEKDAY

Attribute	Description
Name	COUPNWEEKDAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7</td></tr></table>

TOP

COUPNADHRETOMNTHEND

Attribute	Description
Name	COUPNADHRETOMNTHEND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RVSNFREQ

Attribute	Description

Name	RVSNFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

RVSNWEEKDAY

Attribute	Description
Name	RVSNWEEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7

TOP

RVSNADHRETOMNTHEND

Attribute	Description
Name	RVSNADHRETOMNTHEND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ZEROINTFREXPRD

Attribute	Description
Name	ZEROINTFREXPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCRDCNTBASIS366

Attribute	Description
Name	ACCRDCNTBASIS366
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

LQDDCNTBASIS366

Attribute	**Description**	
Name	LQDDCNTBASIS366	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,Y,D

TOP

Smsd

Attribute	**Description**	
Name	Smsd	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FRMDY

Attribute	**Description**	
Name	FRMDY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MONTHIND

Attribute	Description
Name	MONTHIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,F

TOP

FUTMON

Attribute	Description
Name	FUTMON
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYOFSPTDT

Attribute	Description
Name	DAYOFSPTDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WEEKDAYOFSPTDT

Attribute	Description
Name	WEEKDAYOFSPTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7

TOP

IFSPTDTISHOL

Attribute	**Description**	
Name	IFSPTDTISHOL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,B,F

TOP

Tps

Attribute	**Description**	
Name	Tps	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMKTCD

Attribute	**Description**	
Name	PRDORMKTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHM

Attribute	**Description**	
Name	SCHM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

MODL

Attribute	Description
Name	MODL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

Tmit

Attribute	Description
Name	Tmit
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CMPNT

Attribute	Description
Name	CMPNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRATCD

Attribute	Description
Name	DFLTRATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFLTWAIVR

Attribute	Description
Name	DFLTWAIVR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRATECDAMMNDMENT

Attribute	Description
Name	ALLWRATECDAMMNDMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASSOC

Attribute	Description	
Name	STPASSOC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLASSDSC

Attribute	Description	
Name	CLASSDSC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVNTDSCR

Attribute	Description	
Name	EVNTDSCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DSC3

Attribute	Description	
Name	DSC3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Smed

Attribute	Description
Name	Smed
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FRMDY

Attribute	Description
Name	FRMDY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TODY

Attribute	Description
Name	TODY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MNTHIND

Attribute	Description
Name	MNTHIND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,C,F</td></tr></table>

TOP

PREVMNTHS

Attribute	Description
Name	PREVMNTHS
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYOFEXDT

Attribute	Description
Name	DAYOFEXDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WEEKDAYOFEXDT

Attribute	Description
Name	WEEKDAYOFEXDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7

TOP

IFEXDTISHOL

Attribute	Description
Name	IFEXDTISHOL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,B,F

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.103.QuerySEMarketPriceCodes

QuerySEMarketPriceCodes

2.103.1.SE-QuerySEMarketPriceCodes-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stpricd-IO*
    - *PRICE_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.103.2.SE-QuerySEMarketPriceCodes-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stpricd-IO*
      - *PRICE_CODE*
    - *Stpricd-Full*
      - *PRICE_CODE*
      - *PRICE_CODE_DESC*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Stpricd-IO

Attribute	Description
Name	Stpricd-IO
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Stpricd-Full

Attribute	Description
Name	Stpricd-Full
Datatype	
Description	

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRICE_CODE_DESC

Attribute	Description
Name	PRICE_CODE_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	**Description**	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String

Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.104.QuerySEPortfolioBal

QuerySEPortfolioBal

2.104.1.SE-QuerySEPortfolioBal-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Pfolio-Balances-Summary-IO*
    - *BRNCODE*
    - *POSTIONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Pfolio-Balances-Summary-IO

Attribute	Description
Name	Pfolio-Balances-Summary-IO
Datatype	
Description	Indicates Branch Code and Portfolio Reference.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

POSTIONREFNO

Attribute	Description
Name	POSTIONREFNO

Datatype	String
Description	Indicates Portfolio Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.104.2.SE-QuerySEPortfolioBal-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Pfolio-Balances-Summary-IO*
      - *BRNCODE*
      - *POSTIONREFNO*
    - *Pfolio-Balances-Summary-Full*
      - *BRNCODE*
      - *PFID*
      - *PFDESC*
      - *OFTYPE*
      - *SECID*
      - *SECDESC*
      - *OPENINGPOS*
      - *CURRENTPOS*
      - *OPENINGHOLD*
      - *CURRENTHOLD*
      - *SCY*
      - *CUSTACC*
      - *PFCUSTID*
      - *POSTIONREFNO*

CUSTNAME
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Pfolio-Balances-Summary-IO

Attribute	Description
Name	Pfolio-Balances-Summary-IO
Datatype	
Description	Indicates Branch Code and Portfolio Reference.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSTIONREFNO

Attribute	Description
Name	POSTIONREFNO
Datatype	String
Description	Indicates Portfolio Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Pfolio-Balances-Summary-Full

Attribute	Description
Name	Pfolio-Balances-Summary-Full
Datatype	
Description	Indicates Portfolio Balance details in FCUBS Response.

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates Portfolio Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

OFTYPE

Attribute	Description
Name	OFTYPE
Datatype	String
Description	Indicates Portfolio Type Bank : B Customer : C Issuer : I

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,I,

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Indicates Security Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECDESC

Attribute	**Description**	
Name	SECDESC	
Datatype	String	
Description	Indicates Security Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

OPENINGPOS

Attribute	**Description**	
Name	OPENINGPOS	
Datatype	Number	
Description	Indicates Opening Position	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURRENTPOS

Attribute	**Description**	
Name	CURRENTPOS	
Datatype	Number	
Description	Indicates Current Position	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OPENINGHOLD

Attribute	Description
Name	OPENINGHOLD
Datatype	Number
Description	Indicates Opening Holding
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENTHOLD

Attribute	Description
Name	CURRENTHOLD
Datatype	Number
Description	Indicates Current Holding
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCY

Attribute	Description
Name	SCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	Indicates Customer Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PFCUSTID

Attribute	Description
Name	PFCUSTID
Datatype	String
Description	Indicates Portfolio Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

POSTIONREFNO

Attribute	**Description**	
Name	POSTIONREFNO	
Datatype	String	
Description	Indicates Portfolio Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CUSTNAME

Attribute	**Description**	
Name	CUSTNAME	
Datatype	String	
Description	Indicates Portfolio Customer Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user created the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who authorized the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and timestamp when the user authorized the record	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the record Authorization status. Authorized : A UnAuthorized : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record status. Open : O Closed : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Authorization status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.105.QuerySEPriceDetail

QuerySEPriceDetail

2.105.1.SE-QuerySEPriceDetail-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stprcmas-IO*
    - *BR_CODE*
    - *SECURITY_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.105.2.SE-QuerySEPriceDetail-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stprcmas-IO*
      - *BR_CODE*
      - *SECURITY_CODE*
    - *Stprcmas-Full*
      - *BR_CODE*
      - *SECURITY_CODE*
      - *SECUTRIY_DESC*
      - *BRANCH_NAME*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Stprcdtl*
        - *PRICE_CODE*
        - *MARKET_VALUE_DATE*

PRICE_QUOTATION_METHOD
INTEREST_QUOTATION_METHOD
PRICE
INT_AUTH_STAT
LCY_PRICE
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stprcmas-IO

Attribute	Description
Name	Stprcmas-IO
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Stprcmas-Full

Attribute	Description

Name	Stprcmas-Full
Datatype	
Description	

TOP

BR_CODE

Attribute	Description
Name	BR_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 3

TOP

SECURITY_CODE

Attribute	Description
Name	SECURITY_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 16

TOP

SECUTRIY_DESC

Attribute	Description
Name	SECUTRIY_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BRANCH_NAME

Attribute	Description
Name	BRANCH_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Stprcdtl

Attribute	Description
Name	Stprcdtl
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRICE_CODE

Attribute	Description
Name	PRICE_CODE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MARKET_VALUE_DATE

Attribute	**Description**	
Name	MARKET_VALUE_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRICE_QUOTATION_METHOD

Attribute	**Description**	
Name	PRICE_QUOTATION_METHOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPM,PPR,YTM

TOP

INTEREST_QUOTATION_METHOD

Attribute	**Description**	
Name	INTEREST_QUOTATION_METHOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,,F

TOP

PRICE

Attribute	**Description**	
Name	PRICE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

INT_AUTH_STAT

Attribute	Description
Name	INT_AUTH_STAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LCY_PRICE

Attribute	Description
Name	LCY_PRICE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.106.QuerySESKLocationChange

QuerySESKLocationChange

2.106.1.SE-QuerySESKLocationChange-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Svsdlmas-IO*
    - *CONTRACTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.106.2.SE-QuerySESKLocationChange-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Svsdlmas-IO*
      - *CONTRACTREFNO*
    - *Svsdlmas-Full*
      - *PRD*
      - *CONTRACTREFNO*
      - *USRREF*
      - *VERNO*
      - *LATVERNO*
      - *SECTYCD*
      - *QUOTEBY*
      - *SECTYSERIES*
      - *TXNDT*
      - *TRADEDT*
      - *SETMETD*
      - *DEALQTY*
      - *DSTLDT*
      - *PRDDESC*
      - *Svsdldtl*

PORTFOLIO
PORTDESC
CPTY
CNTRPTYDESC
SKLOCATION
SKLOCTNDESC
SKACCNT
FRMTYP
SKLOCTNTO
SKLOCTNDESCTO
SKACCNTTO
SE_FORM_TYPE

Csvwsevntlogdtls

DEAL_REFERENCE_NO
ESN
INPUTBY
MAKDTTIME
CHECHKERID
CHKDTTIME
AUTHSTAT
ACTIVE

Misdetails

CONREFNO
LATESN
MISGRP
RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST2*
  - *REIMINST3*
  - *REIMINST4*
  - *RCVRCORRS1*

RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15

ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*

NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC

Taxheadmaster

REFERENCE_NO

Assoc

INTCOMP
CRRATEESN
RULE
WAIVER

Appln

INTCOMP
CRRATESN
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQDINDICAT

Liqdmaster

INTCOMP
TAXCCY
TAXAMNT

Issrtax

INTCOMP
CRRATESN
RATECOD
WAIVER

Csvws-Contract-En

LEGREFNO
Sevws-Event-Log
REFERENCE
SR_NO
EVENT
EVENT_DATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Acvws-All-Ac-Entries
BRANCH
ACCOUNT
DR_CR
CODE
DATE
VALDT
CCY
FCY_AMOUNT
EXG_RATE
LCY_AMOUNT
Csvws-Contract-Ovd
OVDMSGS
Csvws-Contract
LEGREFNO
Csvws-Contract-Event-Seq
EVTCODE
EVENT_SEQ_NO
DESCRIPTION
Csvws-Contract-Event-Advice
ADVCD
SUPPRESS
PRIORITY
PRTYID
PRTYNAME
ADVDESC
ADDRS1
ADDRS2
ADDRS3
ADDRS4
MEDIA
DESCRIPTION
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Svsdlmas-IO

Attribute	Description
Name	Svsdlmas-IO
Datatype	
Description	

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Svsdlmas-Full

Attribute	Description
Name	Svsdlmas-Full
Datatype	
Description	

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTRACTREFNO

Attribute	Description
Name	CONTRACTREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USRREF

Attribute	Description
Name	USRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SETMETD

Attribute	Description
Name	SETMETD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DEALQTY

Attribute	**Description**	
Name	DEALQTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

DSTLDT

Attribute	**Description**	
Name	DSTLDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Svsdldtl

Attribute	**Description**	
Name	Svsdldtl	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFOLIO

Attribute	**Description**
Name	PORTFOLIO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDESC

Attribute	Description
Name	PORTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CNTRPTYDESC

Attribute	Description
Name	CNTRPTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCATION

Attribute	Description
Name	SKLOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCTNDESC

Attribute	**Description**	
Name	SKLOCTNDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKACCNT

Attribute	**Description**	
Name	SKACCNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,D,I,G,C

TOP

SKLOCTNTO

Attribute	**Description**	
Name	SKLOCTNTO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCTNDESCTO

Attribute	Description
Name	SKLOCTNDESCTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKACCNTTO

Attribute	Description
Name	SKACCNTTO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SE_FORM_TYPE

Attribute	Description
Name	SE_FORM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,D,I,G,C

TOP

Csvwsevntlogdtls

Attribute	Description
Name	Csvwsevntlogdtls
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEAL_REFERENCE_NO

Attribute	Description
Name	DEAL_REFERENCE_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

INPUTBY

Attribute	Description
Name	INPUTBY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECHKERID

Attribute	Description
Name	CHECHKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

ACTIVE

Attribute	Description
Name	ACTIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	**Description**	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	**Description**	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	**Description**	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	**Description**	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	**Description**	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number

Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY

Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	**Description**	
Name	TRANSTYP	
Datatype	String	
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	**Description**	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	**Description**	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	**Description**	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	**Description**	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description	
Name	REIMINST2	
Datatype	String	
Description	Indicates Reimburse Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST2

Attribute	**Description**	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	**Description**	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	**Description**	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND1

Attribute	**Description**	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**	
Name	REGREP3	
Datatype	String	
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	**Description**	
Name	ENVCONT1	
Datatype	String	
Description	Indicates Envelope Contents 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT2

Attribute	**Description**	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	**Description**
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	**Description**	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ULTBANDCD

Attribute	**Description**	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	**Description**	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	**Description**	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Csvws-Contract-En

Attribute	Description
Name	Csvws-Contract-En
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sevws-Event-Log

Attribute	Description
Name	Sevws-Event-Log
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SR_NO

Attribute	Description
Name	SR_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER_ID

Attribute	**Description**	
Name	CHECKER_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Acvws-All-Ac-Entries

Attribute	**Description**	
Name	Acvws-All-Ac-Entries	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DR_CR

Attribute	Description
Name	DR_CR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DATE

Attribute	Description
Name	DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCY_AMOUNT

Attribute	Description
Name	FCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXG_RATE

Attribute	Description
Name	EXG_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCY_AMOUNT

Attribute	Description
Name	LCY_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	4000

TOP

Csvws-Contract

Attribute	Description
Name	Csvws-Contract
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

LEGREFNO

Attribute	Description
Name	LEGREFNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	16

TOP

Csvws-Contract-Event-Seq

Attribute	Description
Name	Csvws-Contract-Event-Seq
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

EVTCODE

Attribute	Description
Name	EVTCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Csvws-Contract-Event-Advice

Attribute	Description
Name	Csvws-Contract-Event-Advice
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADVDESC

Attribute	Description
Name	ADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.107.QuerySESKLocationMaint

QuerySESKLocationMaint

2.107.1.SE-QuerySESKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Skloc-IO*
    - *SKLOCID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.107.2.SE-QuerySESKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Skloc-IO*
      - *SKLOCID*
    - *Skloc-Full*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAUTOCOLL*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACCEP*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*

AUTHSTAT
Skacc
SKACC
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Skloc-IO

Attribute	Description
Name	Skloc-IO
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Skloc-Full

Attribute	Description
Name	Skloc-Full
Datatype	
Description	

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	**Description**	
Name	SKLOCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	**Description**	
Name	CUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	**Description**	
Name	INTEXT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	I,E

TOP

EXTTYPE

Attribute	**Description**	
Name	EXTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,E,O

TOP

CORPACTAUTOCOLL

Attribute	Description	
Name	CORPACTAUTOCOLL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,A

TOP

SKLOCEXPLINE

Attribute	Description	
Name	SKLOCEXPLINE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

MSGTOICS

Attribute	Description	
Name	MSGTOICS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BANKACCEP

Attribute	Description	
Name	BANKACCEP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Skacc

Attribute	Description
Name	Skacc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.108.QuerySKLocationMaint

Query of Securities - Safe Keeping Location Maintenance

2.108.1.SE-QuerySKLocationMaint-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sk-Location-IO*
    - *SKLOCID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Includes Securities Safe Keeping Location Query Input Only type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.108.2.SE-QuerySKLocationMaint-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sk-Location-PK*
      - *SKLOCID*
    - *Sk-Location-IO*
      - *SKLOCID*
      - *SKLOCDESC*
      - *CUSTID*
      - *INTEXT*
      - *EXTTYPE*
      - *CORPACTAC*
      - *SKLOCEXPLINE*
      - *MSGTOICS*
      - *BANKACPTN*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*

RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Sk-Location-Full
SKLOCID
SKLOCDESC
CUSTID
INTEXT
EXTTYPE
CORPACTAC
SKLOCEXPLINE
MSGTOICS
BANKACPTN
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Sk-Account
SKLOCID
SKACC
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Sk-Location-PK

Attribute	Description
Name	Sk-Location-PK
Datatype	
Description	Includes Securities Safe Keeping Location Query Primary Key type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sk-Location-IO

Attribute	Description
Name	Sk-Location-IO
Datatype	
Description	Includes Securities Safe Keeping Location Query Input Only type details

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates Safe Keeping Location Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	Indicates Customer Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INTEXT

Attribute	Description
Name	INTEXT
Datatype	String
Description	Indicates Internal or External External : E Internal : I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String

Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

BANKACPTN

Attribute	Description
Name	BANKACPTN
Datatype	String
Description	Indicates Bankers Acceptance Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A for Authorized; U for Unauthorized	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status (Open) O for Opened; C for Closed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	**Description**	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates Safe Keeping Location Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sk-Location-Full

Attribute	Description

Name	Sk-Location-Full
Datatype	
Description	Includes Securities Safe Keeping Location Query Full type details

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLOCDESC

Attribute	Description	
Name	SKLOCDESC	
Datatype	String	
Description	Indicates Safe Keeping Location Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description	Indicates Customer Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INTEXT

Attribute	Description	
Name	INTEXT	
Datatype	String	
Description	Indicates Internal or External External : E Internal : I	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,I

TOP

EXTTYPE

Attribute	Description
Name	EXTTYPE
Datatype	String
Description	Indicates External Type CEDEL : C EUROCLEAR : E OTHERS : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,E,O,

TOP

CORPACTAC

Attribute	Description
Name	CORPACTAC
Datatype	String
Description	Indicates Corporation Action Collection Manual : M Auto : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

SKLOCEXPLINE

Attribute	Description
Name	SKLOCEXPLINE
Datatype	String
Description	Indicates Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

MSGTOICS

Attribute	Description
Name	MSGTOICS
Datatype	String
Description	Indicates Message to Incident Command System Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKACPTN

Attribute	**Description**	
Name	BANKACPTN	
Datatype	String	
Description	Indicates Bankers Acceptance Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U for Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status (Open) O for Opened; C for Closed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sk-Account

Attribute	Description	
Name	Sk-Account	
Datatype		
Description	Includes Safe Keeping Account details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLOCID

Attribute	Description	
Name	SKLOCID	
Datatype	String	
Description	Indicates Safe Keeping Location Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	Description	
Name	SKACC	
Datatype	String	
Description	Indicates Safe Keeping Location Account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description

Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.109.AuthSKLocationChange

Authorization of Transfer Accross Safe Keeping Locations/Forms

2.109.1.SE-SKTransfer-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*

NEWDISPVAL

FLDDESC

Rekey-Fields

SECCODE

INPR

DEALQTY

TRDDT

DSTLDT

PFID

MSTDT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for authorization request of the SDblockrelease

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Authorization of Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Indicates the Contract Event Log Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates the Event Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates the Deal Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates the User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes the Contract Override Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates the Confirmed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates the Override messages.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes the Contract Change Log Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates the Old Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates the New Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates the field Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes the Rekey Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY

Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates the transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates the Portfolio ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.109.2.SE-SKTransfer-Auth-Req-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters-IO*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*
        - *NEWDISPVAL*
        - *FLDDESC*
    - *Rekey-Fields*

SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for authorization request of the SDblockrelease

TOP

Deal-Masters-IO

Attribute	Description
Name	Deal-Masters-IO
Datatype	
Description	Indicates the Deal Reference and External Reference Number in FCUBS Request.

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes the Contract Event Log details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates the Event Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates the Deal Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates the User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes the Contract Override Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates the Confirmed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

OVDMSGS

Attribute	Description

Name	OVDMSGS
Datatype	String
Description	Indicates the Override messages.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes the Contract Change Log Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates the Old Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates the New Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String

Description	Indicates the field Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes the Rekey Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates the transaction Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates the Portfolio ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.109.3.SE-SKTransfer-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Masters*
    - *DEALREF*
    - *XREF*
    - *Cont-Event-Log*
      - *LEGDESC*
      - *BUYSELL*
      - *ESN*
      - *EVENTCD*
      - *PRDCD*
      - *DEALREFE*
      - *USREF*
      - *Contract-Ovd*
        - *CONFIRMED*
        - *OVDMSGS*
      - *Contract-Change-Log*
        - *OLDDISPVAL*
        - *NEWDISPVAL*
        - *FLDDESC*
    - *Rekey-Fields*

SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full response of the authorization request

TOP

Deal-Masters

Attribute	Description
Name	Deal-Masters
Datatype	
Description	Authorization of Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal Reference.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Cont-Event-Log

Attribute	Description
Name	Cont-Event-Log
Datatype	
Description	Includes the Contract Event Log details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 2

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates the Event Sequence Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates the Event Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates the Deal Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates the User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes the Contract Override Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String

Description	Indicates the Confirmed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates the Override messages.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes the Contract Change Log Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates the Old Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates the New Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35
minLength	1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates the field Description.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes the Rekey Fields
Attributes	

Attribute	Description
minOccurs	0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates the Security Code.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates the Input Price.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates the transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates the Portfolio ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date

Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.109.4.SE-SKTransfer-Auth-Res-Msg.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Blockrelease-PK*
      - *DEALREF*
      - *USERREF*
      - *XREF*
      - *VERNO*
    - *Deal-Masters-IO*
      - *DEALREF*
      - *XREF*
      - *Cont-Event-Log*
        - *LEGDESC*
        - *BUYSELL*
        - *ESN*
        - *EVENTCD*
        - *PRDCD*
        - *DEALREFE*
        - *USREF*
        - *Contract-Ovd*
          - *CONFIRMED*

OVDMSGS
Contract-Change-Log
OLDDISPVAL
NEWDISPVAL
FLDDESC
Rekey-Fields
SECCODE
INPR
DEALQTY
TRDDT
DSTLDT
PFID
MSTDT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for primary key response of the authorization request

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Blockrelease-PK

Attribute	Description
Name	Deal-Blockrelease-PK
Datatype	
Description	Contains FCUBS Primary keys Response for Deal Block Release.

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal Reference.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

USERREF

Attribute	Description
Name	USERREF
Datatype	String
Description	Indicates the User Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates the Version Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

Deal-Masters-IO

Attribute	Description
Name	Deal-Masters-IO
Datatype	
Description	Contains FCUBS Primary keys Response for Deal.

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal Reference.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Cont-Event-Log

Attribute	Description	
Name	Cont-Event-Log	
Datatype		
Description	Includes the Contract Event Log details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LEGDESC

Attribute	Description	
Name	LEGDESC	
Datatype	String	
Description	Indicates the Leg Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BUYSELL

Attribute	Description	
Name	BUYSELL	
Datatype	String	
Description	Indicates whether Buy or sell.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	2

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates the Event Sequence Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	2

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates the Event Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALREFE

Attribute	Description
Name	DEALREFE
Datatype	String
Description	Indicates the Deal Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USREF

Attribute	Description
Name	USREF
Datatype	String
Description	Indicates the User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	Includes the Contract Override Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates the Confirmed.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	Indicates the Override messages.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

Contract-Change-Log

Attribute	Description
Name	Contract-Change-Log
Datatype	
Description	Includes the Contract Change Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OLDDISPVAL

Attribute	Description
Name	OLDDISPVAL
Datatype	String
Description	Indicates the Old Value.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

NEWDISPVAL

Attribute	Description
Name	NEWDISPVAL
Datatype	String
Description	Indicates the New Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

FLDDESC

Attribute	Description
Name	FLDDESC
Datatype	String
Description	Indicates the field Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Rekey-Fields

Attribute	Description
Name	Rekey-Fields
Datatype	
Description	Includes the Rekey Fields
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECCODE

Attribute	Description
Name	SECCODE
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INPR

Attribute	Description
Name	INPR
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRDDT

Attribute	Description
Name	TRDDT
Datatype	Date
Description	Indicates the transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates the Portfolio ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MSTDT

Attribute	Description
Name	MSTDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contain FCUBS Error List, If any.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contain FCUBS Warning List, If any.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.110.CreateSKLocationChange

Transfer Accross Safe Keeping Locations/Forms

2.110.1.SE-SKTransfer-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *BRN*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *REVDREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*

DEALQTY
TRADEDT
PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS

LEGREF
PAYBRN
PAYACC
LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*

- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*

TAXAMNT

CONTREF

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

FUNDMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

LINKGRP

CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: minInclusive / 0; totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

REVDREFNO

Attribute	**Description**	
Name	REVDREFNO	
Datatype	String	
Description	Indicates the Reversed Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description	Indicates the Security Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates the Market Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECTYDESC

Attribute	**Description**	
Name	SECTYDESC	
Datatype	String	
Description	Indicates the security Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	String
Description	Indicates the Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates the Price In Local Currency.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates the Local Currency Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote By.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates the Interest Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description

Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates the Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description	
Name	SPOTDT	
Datatype	Date	
Description	Indicates the Spot Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORM

Attribute	Description

Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTYPE

Attribute	**Description**
Name	DEALTYPE
Datatype	String
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	String
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALER

Attribute	**Description**
Name	DEALER
Datatype	String
Description	Indicates the Dealer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ISMAIND

Attribute	**Description**
Name	ISMAIND
Datatype	String
Description	Indicates the Conforms to ISMA.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates the Pay Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description	Indicates the Contract Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes the Deal Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates the Deal Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description	Indicates the Counterparty.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates the SK Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Accounts.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates the Accompany Withdraw.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates the Auto MSTL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT

Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates the To Exposure.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates the Clean Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates the Track Pre-Settlement Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates the Walk in Media.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates the Address Line 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates the Address Line 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MSGDESC

Attribute	Description
Name	MSGDESC
Datatype	String
Description	Indicates the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35; minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description**: maxLength / 25; minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Charge Application

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.110.2.SE-SKTransfer-Create-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *PRD*
    - *FCCREF*
    - *UREF*
    - *SECTYCD*
    - *TXNDATE*
    - *TRADEDT*
    - *DEALQTY*
    - *DSTLDT*
    - *PORTFOLIO*
    - *QUOTEBY*
    - *Deal-Detail*
      - *PORTFOLIO*
      - *SKLOC*
      - *SKACC*
      - *SKLOCTO*
      - *SKACCTO*
      - *FRMTYPFROM*
      - *FRMTYPTO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction date.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	String
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote by.
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Indicates the Deal Detail.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates the SK Account To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the From Type from.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the From Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.110.3.SE-SKTransfer-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *BRN*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *REVDREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALQTY*
    - *TRADEDT*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS
LEGREF
PAYBRN
PAYACC

LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*

- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
  - *CONTREF*

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC

AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*

INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3

SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	**Description**
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD

Attribute	**Description**
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minInclusive / 0 totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates the Reversed Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates the Market Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECTYDESC

Attribute	Description

Name	SECTYDESC
Datatype	String
Description	Indicates the security Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY

Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	String
Description	Indicates the Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates the Price In Local Currency.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates the Local Currency Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote By.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates the Interest Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description

Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates the Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description	
Name	SPOTDT	
Datatype	Date	
Description	Indicates the Spot Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORM

Attribute	Description

Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates the Dealer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates the Conforms to ISMA.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYBRN

Attribute	Description	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Pay Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYACC

Attribute	Description	
Name	PAYACC	
Datatype	String	
Description	Indicates the Pay Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates the Contract Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Includes the Deal Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description	Indicates the Counterparty.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates the SK Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Accounts.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates the Accompany Withdraw.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates the Auto MSTL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT

Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates the To Exposure.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates the Clean Risk Limit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates the Track Pre-Settlement Risk Limit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WALKINNAME

Attribute	Description
Name	WALKINNAME
Datatype	String
Description	Indicates the Customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates the Walk in Media.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates the Address Line 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates the Address Line 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MSGDESC

Attribute	Description
Name	MSGDESC
Datatype	String
Description	Indicates the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Specifies The TAG Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	Description	
Name	TAGAMNT	
Datatype	Number	
Description	Specifies The TAG Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Charge Application

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.110.4.SE-SKTransfer-Create-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sktransfer-Master-PK*
      - *FCCREF*
      - *SECTYCD*
      - *TXNDATE*
    - *Deal-Master*
      - *PRD*
      - *FCCREF*
      - *UREF*
      - *SECTYCD*
      - *TXNDATE*
      - *TRADEDT*
      - *DEALQTY*
      - *DSTLDT*
      - *PORTFOLIO*
      - *QUOTEBY*
      - *Deal-Detail*
        - *PORTFOLIO*
        - *SKLOC*

SKACC
SKLOCTO
SKACCTO
FRMTYPFROM
FRMTYPTO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for detailing the Full information relating the Rights and Warrants Expiry information.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sktransfer-Master-PK

Attribute	Description
Name	Sktransfer-Master-PK
Datatype	
Description	Transfer Accross Safe Keeping Locations/Forms PK Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

Deal-Master

Attribute	Description

Name	Deal-Master
Datatype	
Description	Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNDATE

Attribute	Description

Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	String
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote by.
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Indicates the Deal Detail.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String

Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates the SK Account To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the From Type from.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the From Type To.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.111.DeleteSKLocationChange

Deletion of Transfer Accross Safe Keeping Locations/Forms

2.111.1.SE-SKTransfer-Delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *BRN*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *REVDREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*

DEALQTY
TRADEDT
PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS

LEGREF
PAYBRN
PAYACC
LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*

- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*

TAXAMNT

CONTREF

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

FUNDMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

LINKGRP

CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for deleting the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Deletion of Transfer Accross Safe Keeping Locations/Forms Master Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: minInclusive / 0; totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

REVDREFNO

Attribute	**Description**	
Name	REVDREFNO	
Datatype	String	
Description	Indicates the Reversed Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description	Indicates the Security Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates the Market Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECTYDESC

Attribute	**Description**	
Name	SECTYDESC	
Datatype	String	
Description	Indicates the security Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description	Indicates the Input Price.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

YIELD

Attribute	**Description**	
Name	YIELD	
Datatype	String	
Description	Indicates the Yield.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description	Indicates the Price In Local Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description	Indicates the Local Currency Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote By.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates the Interest Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description

Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates the Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description	
Name	SPOTDT	
Datatype	Date	
Description	Indicates the Spot Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORM

Attribute	Description

Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DEALTYPE

Attribute	**Description**	
Name	DEALTYPE	
Datatype	String	
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description	Indicates the Dealer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISMAIND

Attribute	**Description**	
Name	ISMAIND	
Datatype	String	
Description	Indicates the Conforms to ISMA.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates the Pay Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description	Indicates the Contract Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes the Deal Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates the Deal Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates the Counterparty.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	Description	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Accounts.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCOMLODGE

Attribute	Description	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates the Accompany Withdraw.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTOMSTL

Attribute	Description	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates the Auto MSTL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREF

Attribute	Description	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT

Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	Description	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates the To Exposure.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	Description	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates the Clean Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	Description	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates the Track Pre-Settlement Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates the Walk in Media.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates the Address Line 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates the Address Line 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MSGDESC

Attribute	Description
Name	MSGDESC
Datatype	String
Description	Indicates the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Specifies The TAG Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	Description	
Name	TAGAMNT	
Datatype	Number	
Description	Specifies The TAG Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 12 minLength: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	**Description**	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5LBL5

Attribute	**Description**	
Name	COMPMIS5LBL5	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS6LBL6

Attribute	**Description**	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS7LBL7

Attribute	**Description**

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAVEINSTCHARG

Attribute	**Description**	
Name	WAVEINSTCHARG	
Datatype	String	
Description	Indicates the Waiving of Instrument charges maintaIned at ARC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BNKOPRCD

Attribute	**Description**	
Name	BNKOPRCD	
Datatype	String	
Description	Indicates Bank Operation Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	1

TOP

ENV_CONT1

Attribute	**Description**	
Name	ENV_CONT1	
Datatype	String	
Description	Envelope Contents	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Charge Application

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.111.2.SE-SKTransfer-Delete-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *PRD*
    - *FCCREF*
    - *UREF*
    - *SECTYCD*
    - *TXNDATE*
    - *TRADEDT*
    - *DEALQTY*
    - *DSTLDT*
    - *PORTFOLIO*
    - *QUOTEBY*
    - *Deal-Detail*
      - *PORTFOLIO*
      - *SKLOC*
      - *SKACC*
      - *SKLOCTO*
      - *SKACCTO*
      - *FRMTYPFROM*
      - *FRMTYPTO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for deleting the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	This XSD contains the Input Only details for the SE-SK Delete Transfer.

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction date.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	String
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote by.
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Indicates the Deal Detail.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates the SK Account To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the From Type from.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the From Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.111.3.SE-SKTransfer-Delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sktransfer-Master-PK*
    - *FCCREF*
    - *UREF*
    - *BRN*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *REVDREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALQTY*
    - *TRADEDT*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS
LEGREF
PAYBRN
PAYACC

LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*

- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
  - *CONTREF*

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC

AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*

INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3

SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for deleting the Full information relating the Rights and Warrants Expiry information.

TOP

Sktransfer-Master-PK

Attribute	Description
Name	Sktransfer-Master-PK
Datatype	
Description	Deletion of Transfer Accross Safe Keeping Locations/Forms PK Type

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	**Description**
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD

Attribute	**Description**
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minInclusive / 0 totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates the Reversed Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates the Market Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYDESC

Attribute	Description

Name	SECTYDESC
Datatype	String
Description	Indicates the security Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY

Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	String
Description	Indicates the Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates the Price In Local Currency.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates the Local Currency Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote By.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates the Interest Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description

Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	fractionDigits / 3
	totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates the Payment Currency.
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description	
Name	SPOTDT	
Datatype	Date	
Description	Indicates the Spot Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORM

Attribute	Description

Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DEALTYPE

Attribute	**Description**	
Name	DEALTYPE	
Datatype	String	
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description	Indicates the Dealer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISMAIND

Attribute	**Description**	
Name	ISMAIND	
Datatype	String	
Description	Indicates the Conforms to ISMA.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates the Pay Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description	Indicates the Contract Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes the Deal Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates the Deal Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description	Indicates the Counterparty.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates the SK Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Accounts.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates the Accompany Withdraw.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates the Auto MSTL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT

Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates the To Exposure.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates the Clean Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates the Track Pre-Settlement Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates the Walk in Media.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates the Address Line 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates the Address Line 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

MSGDESC

Attribute	Description
Name	MSGDESC
Datatype	String
Description	Indicates the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Charge Application

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.111.4.SE-SKTransfer-Delete-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sktransfer-Master-PK*
      - *FCCREF*
      - *SECTYCD*
      - *TXNDATE*
    - *Deal-Master*
      - *PRD*
      - *FCCREF*
      - *UREF*
      - *SECTYCD*
      - *TXNDATE*
      - *TRADEDT*
      - *DEALQTY*
      - *DSTLDT*
      - *PORTFOLIO*
      - *QUOTEBY*
      - *Deal-Detail*
        - *PORTFOLIO*
        - *SKLOC*

SKACC
SKLOCTO
SKACCTO
FRMTYPFROM
FRMTYPTO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for deleting the Full information relating the Rights and Warrants Expiry information.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sktransfer-Master-PK

Attribute	Description
Name	Sktransfer-Master-PK
Datatype	
Description	Indicates Contract Reference Number, Security Code, Transaction Date.

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

Deal-Master

Attribute	Description

Name	Deal-Master
Datatype	
Description	Indicates FCUBS Deal Response details

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNDATE

Attribute	Description

Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	String
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote by.
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Indicates the Deal Detail.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String

Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates the SK Account To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the From Type from.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the From Type To.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.112.ModifySKLocationChange

Modification of Transfer Accross Safe Keeping Locations/Forms

2.112.1.SE-SKTransfer-Modify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *BRN*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *REVDREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*

DEALQTY
TRADEDT
PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS

LEGREF
PAYBRN
PAYACC
LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*

- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*

TAXAMNT

CONTREF

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

FUNDMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

LINKGRP

CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details

ACCBRN
ACC_CCY
ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*

XPTNAME
IBANACCNO
INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT

SNDR_INFO1
SNDR_INFO2
SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format to modify the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Includes Securities Safe Keeping Transfer Modification Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number

Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: minInclusive / 0; totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

REVDREFNO

Attribute	**Description**	
Name	REVDREFNO	
Datatype	String	
Description	Indicates the Reversed Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECTYCD

Attribute	**Description**	
Name	SECTYCD	
Datatype	String	
Description	Indicates the Security Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MKTCD

Attribute	**Description**	
Name	MKTCD	
Datatype	String	
Description	Indicates the Market Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECTYDESC

Attribute	**Description**	
Name	SECTYDESC	
Datatype	String	
Description	Indicates the security Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INPUTPRC

Attribute	**Description**	
Name	INPUTPRC	
Datatype	Number	
Description	Indicates the Input Price.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

YIELD

Attribute	**Description**	
Name	YIELD	
Datatype	String	
Description	Indicates the Yield.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

LCYPRC

Attribute	**Description**	
Name	LCYPRC	
Datatype	Number	
Description	Indicates the Price In Local Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LCYQTY

Attribute	**Description**	
Name	LCYQTY	
Datatype	Number	
Description	Indicates the Local Currency Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote By.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates the Interest Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description

Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates the Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description	
Name	SPOTDT	
Datatype	Date	
Description	Indicates the Spot Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORM

Attribute	Description

Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DEALTYPE

Attribute	**Description**	
Name	DEALTYPE	
Datatype	String	
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	**Description**	
Name	PRIORITY	
Datatype	String	
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DEALER

Attribute	**Description**	
Name	DEALER	
Datatype	String	
Description	Indicates the Dealer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISMAIND

Attribute	**Description**	
Name	ISMAIND	
Datatype	String	
Description	Indicates the Conforms to ISMA.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Pay Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description	Indicates the Pay Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description	Indicates the Contract Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes the Deal Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates the Deal Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CPTY

Attribute	**Description**	
Name	CPTY	
Datatype	String	
Description	Indicates the Counterparty.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SKLOC

Attribute	**Description**	
Name	SKLOC	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACC

Attribute	**Description**	
Name	SKACC	
Datatype	String	
Description	Indicates the SK Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Accounts.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates the Accompany Withdraw.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates the Auto MSTL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT

Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates the To Exposure.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates the Clean Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates the Track Pre-Settlement Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates the Walk in Media.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates the Address Line 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates the Address Line 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MSGDESC

Attribute	Description
Name	MSGDESC
Datatype	String
Description	Indicates the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Specifies The TAG Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	Description	
Name	TAGAMNT	
Datatype	Number	
Description	Specifies The TAG Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
fractionDigits	3
totalDigits	22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	9
minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST4

Attribute	Description
Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

POSTACCNG

Attribute	**Description**	
Name	POSTACCNG	
Datatype	String	
Description	Indicates Posting Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

RCVR_CORRESP1

Attribute	**Description**	
Name	RCVR_CORRESP1	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP2

Attribute	**Description**	
Name	RCVR_CORRESP2	
Datatype	String	
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

RCVR_CORRESP3

Attribute	**Description**
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Charge Application

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

2.112.2.SE-SKTransfer-Modify-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *PRD*
    - *FCCREF*
    - *UREF*
    - *SECTYCD*
    - *TXNDATE*
    - *TRADEDT*
    - *DEALQTY*
    - *DSTLDT*
    - *PORTFOLIO*
    - *QUOTEBY*
    - *Deal-Detail*
      - *PORTFOLIO*
      - *SKLOC*
      - *SKACC*
      - *SKLOCTO*
      - *SKACCTO*
      - *FRMTYPFROM*
      - *FRMTYPTO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format to modify the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Indicates FCUBS Full Request

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction date.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	String
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote by.
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Indicates the Deal Detail.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates the SK Location To.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Account To.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FRMTYPFROM

Attribute	**Description**	
Name	FRMTYPFROM	
Datatype	String	
Description	Indicates the From Type from.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FRMTYPTO

Attribute	**Description**	
Name	FRMTYPTO	
Datatype	String	
Description	Indicates the From Type To.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

2.112.3.SE-SKTransfer-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *UREF*
    - *BRN*
    - *PRD*
    - *VERNO*
    - *LATVERNO*
    - *DEALREFNO*
    - *DEALREF*
    - *XREF*
    - *SRC*
    - *REVDREFNO*
    - *SECTYCD*
    - *MKTCD*
    - *SECTYDESC*
    - *MRKDESC*
    - *DEALQTY*
    - *TRADEDT*
    - *PRCTYPE*

DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS
LEGREF
PAYBRN
PAYACC

LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*
- *WALKINMEDIA*

- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
  - *CONTREF*

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details
ACCBRN
ACC_CCY
ACC

AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*
- *INST_NO*

INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2
SNDR_INFO3

SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format to modify the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Includes Securities Safe Keeping Transfer Modification Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	**Description**
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD

Attribute	**Description**
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minInclusive / 0 totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates the Reversed Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates the Market Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECTYDESC

Attribute	Description

Name	SECTYDESC
Datatype	String
Description	Indicates the security Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MRKDESC

Attribute	Description
Name	MRKDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	Date
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT
Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY

Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	String
Description	Indicates the Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates the Price In Local Currency.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates the Local Currency Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote By.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

SPOTPRCQT

Attribute	Description
Name	SPOTPRCQT
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPOTPRCTYPE

Attribute	Description
Name	SPOTPRCTYPE
Datatype	String
Description	Indicates the Interest Quote.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description

Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates the Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description	
Name	SPOTDT	
Datatype	Date	
Description	Indicates the Spot Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FORM

Attribute	Description

Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates the Dealer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ISMAIND

Attribute	Description
Name	ISMAIND
Datatype	String
Description	Indicates the Conforms to ISMA.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Pay Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYACC

Attribute	**Description**	
Name	PAYACC	
Datatype	String	
Description	Indicates the Pay Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description	Indicates the Contract Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes the Deal Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	**Description**	
Name	FCCREF	
Datatype	String	
Description	Indicates the Deal Reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description

Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates the Counterparty.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates the SK Accounts.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCOMLODGE

Attribute	Description
Name	ACCOMLODGE
Datatype	String
Description	Indicates the Accompany Withdraw.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTOMSTL

Attribute	Description
Name	AUTOMSTL
Datatype	String
Description	Indicates the Auto MSTL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT

Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

TOTEXPOSURE

Attribute	**Description**	
Name	TOTEXPOSURE	
Datatype	String	
Description	Indicates the To Exposure.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CLEANRISKLIMIT

Attribute	**Description**	
Name	CLEANRISKLIMIT	
Datatype	String	
Description	Indicates the Clean Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PSTLRISKLIMIT

Attribute	**Description**	
Name	PSTLRISKLIMIT	
Datatype	String	
Description	Indicates the Track Pre-Settlement Risk Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WALKINNAME

Attribute	**Description**	
Name	WALKINNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description
Name	WALKINMEDIA
Datatype	String
Description	Indicates the Walk in Media.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ADDRLINE1

Attribute	Description
Name	ADDRLINE1
Datatype	String
Description	Indicates the Address Line 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE2

Attribute	Description
Name	ADDRLINE2
Datatype	String
Description	Indicates the Address Line 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MSGDESC

Attribute	Description
Name	MSGDESC
Datatype	String
Description	Indicates the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC

Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Specifies the Internal Security Identification to be used.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	Description	
Name	TAGCCY	
Datatype	String	
Description	Specifies The TAG Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	Description	
Name	TAGAMNT	
Datatype	Number	
Description	Specifies The TAG Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>5</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>totalDigits</td><td>15</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String

Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String

Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String

Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String
Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR3

Attribute	Description
Name	BNFINSTCVR3
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR4

Attribute	Description
Name	BNFINSTCVR4
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR5

Attribute	Description
Name	BNFINSTCVR5
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR6

Attribute	Description
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST2

Attribute	Description	
Name	BENEF_INST2	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST3

Attribute	Description	
Name	BENEF_INST3	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST4

Attribute	Description	
Name	BENEF_INST4	
Datatype	String	
Description	Indicates the details of the institution in favour of which the payment is made can be entered	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String

Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description
Name	CLGNTW
Datatype	String
Description	Indicates Clearing network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CVRBY

Attribute	Description
Name	CVRBY

Datatype	String
Description	Indicates Cover by
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

COVER_REQ

Attribute	Description
Name	COVER_REQ
Datatype	String
Description	Indicates the Cover Required preference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

XPTACC

Attribute	Description
Name	XPTACC
Datatype	String
Description	Indicates External Party account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTBIC

Attribute	Description
Name	XPTBIC
Datatype	String
Description	Indicates External Party BIC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTCLGNTW

Attribute	Description
Name	XPTCLGNTW
Datatype	String

Description	Indicates External Party Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

XPTNAME

Attribute	Description
Name	XPTNAME
Datatype	String
Description	Indicates External Party Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

IBANACCNO

Attribute	Description
Name	IBANACCNO
Datatype	String
Description	Indicates International Bank Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String

Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6
Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5

Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP
Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 11 pattern: [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String
Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

AMTTAGDESC

Attribute	**Description**	
Name	AMTTAGDESC	
Datatype	String	
Description	Indicates Amount Tag Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

DISEXTBKCD

Attribute	**Description**	
Name	DISEXTBKCD	
Datatype	String	
Description	Indicates Bank Name of External party BIC code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	1

TOP

PAYBNK

Attribute	**Description**	
Name	PAYBNK	
Datatype	String	
Description	Indicates the Payable Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

PAYBRN

Attribute	**Description**
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000 minLength / 1

TOP

ENV_CONT2

Attribute	Description
Name	ENV_CONT2
Datatype	String
Description	Envelope Contents 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**	
Name	ENV_CONT5	
Datatype	String	
Description	Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35
	minLength	1

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Charge Application

Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength: 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description

Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.112.4.SE-SKTransfer-Modify-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sktransfer-Master-PK*
      - *FCCREF*
      - *SECTYCD*
      - *TXNDATE*
    - *Deal-Master*
      - *PRD*
      - *FCCREF*
      - *UREF*
      - *SECTYCD*
      - *TXNDATE*
      - *TRADEDT*
      - *DEALQTY*
      - *DSTLDT*
      - *PORTFOLIO*
      - *QUOTEBY*
      - *Deal-Detail*
        - *PORTFOLIO*
        - *SKLOC*

SKACC
SKLOCTO
SKACCTO
FRMTYPFROM
FRMTYPTO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format to modify the Full information relating the Rights and Warrants Expiry information.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sktransfer-Master-PK

Attribute	Description
Name	Sktransfer-Master-PK
Datatype	
Description	Indicates the Contract Reference Number, Security Code, Transaction Date.

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

TOP

Deal-Master

Attribute	Description

Name	Deal-Master
Datatype	
Description	Indicates FCUBS Deal Response details.

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Product Code.
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNDATE

Attribute	Description

Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

TRADEDT

Attribute	Description
Name	TRADEDT
Datatype	String
Description	Indicates the Trade Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

DEALQTY

Attribute	Description
Name	DEALQTY
Datatype	Number
Description	Indicates the Deal Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	String
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

QUOTEBY

Attribute	Description
Name	QUOTEBY
Datatype	String
Description	Indicates the Quote by.
Restrictions	**Restrictions** / **Description** enumeration / U,N length / 1

TOP

Deal-Detail

Attribute	Description
Name	Deal-Detail
Datatype	
Description	Indicates the Deal Detail.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String

Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SKLOCTO

Attribute	Description
Name	SKLOCTO
Datatype	String
Description	Indicates the SK Location To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACCTO

Attribute	Description
Name	SKACCTO
Datatype	String
Description	Indicates the SK Account To.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the From Type from.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the From Type To.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

2.113.QuerySKLocationChange

Query of Transfer Accross Safe Keeping Locations/Forms

2.113.1.SE-SKTransfer-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Deal-Master*
    - *FCCREF*
    - *SECTYCD*
    - *TXNDATE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format to query the Full information relating the Rights and Warrants Expiry information.

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	
Description	Includes Securities Safe Keeping Location Tranfer Deal Query Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Contract Reference Number.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String

Description	Indicates the Security Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	String
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

2.113.2.SE-SKTransfer-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Deal-Master*
      - *FCCREF*
      - *UREF*
      - *BRN*
      - *PRD*
      - *VERNO*
      - *LATVERNO*
      - *DEALREFNO*
      - *DEALREF*
      - *XREF*
      - *SRC*
      - *REVDREFNO*
      - *SECTYCD*
      - *MKTCD*
      - *SECTYDESC*
      - *MRKDESC*
      - *DEALQTY*
      - *TRADEDT*

PRCTYPE
DLVRFREEPAY
PRCQUOTE
DSTLDT
INTVALDT
RECVFREEPAY
INPUTPRC
YIELD
LCYPRC
LCYQTY
ORGDSTLDT
ABSPRICE
DEALTIME
MATDT
TXNDATE
QUOTEBY
SPOTPRCQT
SPOTPRCTYPE
SPOTINTVALDT
SPOTPRC
DISCOUNT
PREMIUM
FORWDPL
FACEDEAL
ADJDEALPRC
ABSWHT
ACTUALDSTLDT
PAYCCY
SCCY
RATEPCYSCY
SECSTTLMENT
SPOTDT
FORM
SECTYSERIES
AUTOMANDSTL
PRODDESC
BAREF
DEALTYPE
PRIORITY
DEALER
ISMAIND
REMARKS
LEGREF
PAYBRN

PAYACC
LEGREFTO
PAYBRNTO
PAYACCTO
SUBSYSTEMSTAT
Event-Log-Details
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *AUTHSTAT*
- *CONTSTAT*

Deal-Detail
- *FCCREF*
- *XREF*
- *PRD*
- *BRANCH*
- *DEALREFNO*
- *DEALREF*
- *VERSION*
- *LGPRDCODE*
- *LGDESC*
- *PORTFOLIO*
- *CPTY*
- *SKLOC*
- *SKACC*
- *SKLOCTO*
- *SKACCTO*
- *ACCOMLODGE*
- *AUTOMSTL*
- *LEGREF*
- *LEGDESC*
- *LEGUSERREF*
- *BRKID*
- *MSTLDT*
- *ORGMSTLDT*
- *CPTYDESC*
- *FRMTYPFROM*
- *FRMTYPTO*
- *UNEXPOSURE*
- *TOTEXPOSURE*
- *CLEANRISKLIMIT*
- *PSTLRISKLIMIT*
- *WALKINNAME*

- *WALKINMEDIA*
- *ADDRLINE1*
- *ADDRLINE2*
- *ADDRLINE3*
- *ADDRLINE4*
- *BUYSELL*
- *MSG*
- *MSGDESC*
- *SKLOCDESC*
- *SKLOCDESCTO*
- *PFDESC*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RATECOD*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*
  - *RULE*
  - *WAIVER*
  - *CONTREF*
- *Tran-Tax-Appln*
  - *CRRATESN*
  - *INTCOMP*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQINDICAT*
  - *CONTREF*
- *Tran-Tax-Liqd-Master*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
  - *CONTREF*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *FUNDMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *COSTCOD1*
- *COSTCOD2*
- *COSTCOD3*
- *COSTCOD4*
- *COSTCOD5*
- *LINKGRP*
- *CCY*
- *RTFLAG*

PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Settlement-Addl-Details
ACCBRN
ACC_CCY

ACC
AMTTAG
CUSTSPRD
ERIAMT
ERICCY
XRATE
GENMSG
NETACRSMOD
PAYRCV
RATECDDEFRD
SPRDDFN
TAG_CCY
DRCRIND
Settlement-Addl-Main
- *ACC_INST1*
- *ACC_INST2*
- *ACC_INST3*
- *ACC_INST4*
- *ACC_INST5*
- *ACC_INST6*
- *AGRID*
- *AMTTAG*
- *BNKPRIO*
- *BNFINSTCVR1*
- *BNFINSTCVR2*
- *BNFINSTCVR3*
- *BNFINSTCVR4*
- *BNFINSTCVR5*
- *BNFINSTCVR6*
- *BENEF_INST1*
- *BENEF_INST2*
- *BENEF_INST3*
- *BENEF_INST4*
- *BENEF_INST5*
- *BENEF_INST6*
- *CHGDET*
- *CLGNTW*
- *CVRBY*
- *COVER_REQ*
- *XPTACC*
- *XPTBIC*
- *XPTCLGNTW*
- *XPTNAME*
- *IBANACCNO*

INST_NO
INST_TYPE
INT_REIM_INST1
INT_REIM_INST2
INT_REIM_INST3
INT_REIM_INST4
INT_REIM_INST5
INT_REIM_INST6
INTMEDRY1
INTMEDRY2
INTMEDRY3
INTMEDRY4
INTMEDRY5
INTMEDRY6
ORDER_CUST1
ORDER_CUST2
ORDER_CUST3
ORDER_CUST4
ORDER_CUST5
ORDER_CUST6
ORDER_INST1
ORDER_INST2
ORDER_INST3
ORDER_INST4
ORDER_INST5
ORDER_INST6
OUR_CORRESP
PMNT_BY
PMNT_DETAILS1
PMNT_DETAILS2
PMNT_DETAILS3
PMNT_DETAILS4
POSTACCNG
RCVR_CORRESP1
RCVR_CORRESP2
RCVR_CORRESP3
RCVR_CORRESP4
RCVR_CORRESP5
RCVR_CORRESP6
RECEIVER
RTGSNW
RTGSPMNT
SNDR_INFO1
SNDR_INFO2

SNDR_INFO3
SNDR_INFO4
SNDR_INFO5
SNDR_INFO6
TRNFRTYP
ULT_BENEF1
ULT_BENEF2
ULT_BENEF3
ULT_BENEF4
ULT_BENEF5
ULT_BENEF6
AMTTAGDESC
DISEXTBKCD
PAYBNK
PAYBRN
WAVEINSTCHARG
BNKOPRCD
ENV_CONT1
ENV_CONT2
ENV_CONT3
ENV_CONT4
ENV_CONT5
Charge-Application
CHGCOMP
CRNESN
TGCCY
TGAMT
CHGCCY
CHGAMT
WAIVER
LIQINTR
DISACR
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format to query the Full information relating the Rights and Warrants Expiry information.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Deal-Master

Attribute	Description
Name	Deal-Master
Datatype	

Description	Includes Securities Safe Keeping Location Tranfer Deal Query Master type details

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UREF

Attribute	Description
Name	UREF
Datatype	String
Description	Indicates the User Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	Indicates the Version number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	Indicates the Latest Version number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** minInclusive / 0 totalDigits / 4

TOP

DEALREFNO

Attribute	Description
Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description

Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SRC

Attribute	Description
Name	SRC
Datatype	String
Description	Indicates the Source.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

REVDREFNO

Attribute	Description
Name	REVDREFNO
Datatype	String
Description	Indicates the Reversed Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECTYCD

Attribute	Description
Name	SECTYCD
Datatype	String
Description	Indicates the Security Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKTCD

Attribute	Description
Name	MKTCD
Datatype	String
Description	Indicates the Market Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECTYDESC

Attribute	**Description**	
Name	SECTYDESC	
Datatype	String	
Description	Indicates the security Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MRKDESC

Attribute	**Description**	
Name	MRKDESC	
Datatype	String	
Description	Indicates the Market Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DEALQTY

Attribute	**Description**	
Name	DEALQTY	
Datatype	Number	
Description	Indicates the Deal Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TRADEDT

Attribute	**Description**	
Name	TRADEDT	
Datatype	Date	
Description	Indicates the Trade Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRCTYPE

Attribute	Description
Name	PRCTYPE
Datatype	String
Description	Indicates the Interest. F - Flat, P - Plus Accured.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DLVRFREEPAY

Attribute	Description
Name	DLVRFREEPAY
Datatype	String
Description	Indicates the Deliver. F - Free, P - Against Payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRCQUOTE

Attribute	Description
Name	PRCQUOTE
Datatype	String
Description	Indicates the Price Quote.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DSTLDT

Attribute	Description
Name	DSTLDT
Datatype	Date
Description	Indicates the DSTL Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTVALDT

Attribute	Description
Name	INTVALDT

Datatype	Date
Description	Indicates the Interest Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECVFREEPAY

Attribute	Description
Name	RECVFREEPAY
Datatype	String
Description	Indicates the Receive. F - Free, P- Against Payment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INPUTPRC

Attribute	Description
Name	INPUTPRC
Datatype	Number
Description	Indicates the Input Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

YIELD

Attribute	Description
Name	YIELD
Datatype	String
Description	Indicates the Yield.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

LCYPRC

Attribute	Description
Name	LCYPRC
Datatype	Number
Description	Indicates the Price In Local Currency.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYQTY

Attribute	Description
Name	LCYQTY
Datatype	Number
Description	Indicates the Local Currency Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ORGDSTLDT

Attribute	Description
Name	ORGDSTLDT
Datatype	Date
Description	Indicates the Original DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSPRICE

Attribute	Description
Name	ABSPRICE
Datatype	Number
Description	Indicates the Absolute Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEALTIME

Attribute	Description
Name	DEALTIME
Datatype	Date
Description	Indicates the Deal Input Time.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	String
Description	Indicates the Maturity Date.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	Date	
Description	Indicates the Transaction Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QUOTEBY

Attribute	Description	
Name	QUOTEBY	
Datatype	String	
Description	Indicates the Quote By.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N
	length	1

TOP

SPOTPRCQT

Attribute	Description	
Name	SPOTPRCQT	
Datatype	String	
Description	Indicates the Price Quote.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPOTPRCTYPE

Attribute	Description	
Name	SPOTPRCTYPE	
Datatype	String	
Description	Indicates the Interest Quote.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SPOTINTVALDT

Attribute	Description
Name	SPOTINTVALDT
Datatype	Date
Description	Indicates the Interest Value Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPOTPRC

Attribute	Description
Name	SPOTPRC
Datatype	Number
Description	Indicates the Spot Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISCOUNT

Attribute	Description
Name	DISCOUNT
Datatype	Number
Description	Indicates the Discount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

PREMIUM

Attribute	Description
Name	PREMIUM
Datatype	Number
Description	Indicates the Premium.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FORWDPL

Attribute	Description
Name	FORWDPL
Datatype	Number
Description	Indicates the Forward P and L.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

FACEDEAL

Attribute	Description
Name	FACEDEAL
Datatype	Number
Description	Indicates the Deal Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ADJDEALPRC

Attribute	Description
Name	ADJDEALPRC
Datatype	Number
Description	Indicates the Adjusted Price.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ABSWHT

Attribute	Description
Name	ABSWHT
Datatype	Number
Description	Indicates the T Bill WHT.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

ACTUALDSTLDT

Attribute	Description
Name	ACTUALDSTLDT
Datatype	Date
Description	Indicates the Actual DSTL Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description	Indicates the Payment Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SCCY

Attribute	Description	
Name	SCCY	
Datatype	String	
Description	Indicates the Security Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RATEPCYSCY

Attribute	Description	
Name	RATEPCYSCY	
Datatype	Number	
Description	Indicates the Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

SECSTTLMENT

Attribute	Description	
Name	SECSTTLMENT	
Datatype	String	
Description	Indicates the Settlement SKL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SPOTDT

Attribute	Description
Name	SPOTDT
Datatype	Date
Description	Indicates the Spot Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FORM

Attribute	Description
Name	FORM
Datatype	String
Description	Indicates the Securities Format.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECTYSERIES

Attribute	Description
Name	SECTYSERIES
Datatype	String
Description	Indicates the Security Series.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

AUTOMANDSTL

Attribute	Description
Name	AUTOMANDSTL
Datatype	String
Description	Indicates the Auto DSTL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String

Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BAREF

Attribute	Description
Name	BAREF
Datatype	String
Description	Indicates the Placement/Loan Reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALTYPE

Attribute	Description
Name	DEALTYPE
Datatype	String
Description	Indicates the Deal Type. P - PRIMARY, S - SECONDARY
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	String
Description	Indicates the Priority. HIGH - HIGH, NORM - NORM, LOW - LOW
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALER

Attribute	Description
Name	DEALER
Datatype	String
Description	Indicates the Dealer.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISMAIND

Attribute	**Description**	
Name	ISMAIND	
Datatype	String	
Description	Indicates the Conforms to ISMA.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REMARKS

Attribute	**Description**	
Name	REMARKS	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LEGREF

Attribute	**Description**	
Name	LEGREF	
Datatype	String	
Description	Indicates the Leg Reference.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYBRN

Attribute	**Description**	
Name	PAYBRN	
Datatype	String	
Description	Indicates the Pay Branch.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PAYACC

Attribute	Description
Name	PAYACC
Datatype	String
Description	Indicates the Pay Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGREFTO

Attribute	Description
Name	LEGREFTO
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYBRNTO

Attribute	Description
Name	PAYBRNTO
Datatype	String
Description	Indicates the Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PAYACCTO

Attribute	Description
Name	PAYACCTO
Datatype	String
Description	Indicates the Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSTEMSTAT

Attribute	Description
Name	SUBSYSTEMSTAT
Datatype	String
Description	Indicates the Subsystem Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Event-Log-Details

Attribute	Description
Name	Event-Log-Details
Datatype	
Description	Includes the Event Log Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the Maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTSTAT

Attribute	**Description**	
Name	CONTSTAT	
Datatype	String	
Description	Indicates the Contract Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Deal-Detail

Attribute	**Description**	
Name	Deal-Detail	
Datatype		
Description	Includes the Deal Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	Indicates the Deal Reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates the External reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates the Poduct.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DEALREFNO

Attribute	Description

Name	DEALREFNO
Datatype	String
Description	Indicates the Deal reference number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DEALREF

Attribute	Description
Name	DEALREF
Datatype	String
Description	Indicates the Deal reference.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERSION

Attribute	Description
Name	VERSION
Datatype	String
Description	Indicates the Version.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGPRDCODE

Attribute	Description
Name	LGPRDCODE
Datatype	String
Description	Indicates the Leg Product.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LGDESC

Attribute	Description
Name	LGDESC
Datatype	String
Description	Indicates the Leg description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFOLIO

Attribute	Description
Name	PORTFOLIO
Datatype	String
Description	Indicates the Portfolio.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CPTY

Attribute	Description
Name	CPTY
Datatype	String
Description	Indicates the Counterparty.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SKLOC

Attribute	Description
Name	SKLOC
Datatype	String
Description	Indicates the SK Location.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKACC

Attribute	Description
Name	SKACC
Datatype	String
Description	Indicates the SK Account.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SKLOCTO

Attribute	**Description**	
Name	SKLOCTO	
Datatype	String	
Description	Indicates the SK Location.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKACCTO

Attribute	**Description**	
Name	SKACCTO	
Datatype	String	
Description	Indicates the SK Accounts.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCOMLODGE

Attribute	**Description**	
Name	ACCOMLODGE	
Datatype	String	
Description	Indicates the Accompany Withdraw.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTOMSTL

Attribute	**Description**	
Name	AUTOMSTL	
Datatype	String	
Description	Indicates the Auto MSTL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

LEGREF

Attribute	Description
Name	LEGREF
Datatype	String
Description	Indicates the Leg Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGDESC

Attribute	Description
Name	LEGDESC
Datatype	String
Description	Indicates the Leg Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LEGUSERREF

Attribute	Description
Name	LEGUSERREF
Datatype	String
Description	Indicates the Leg User Reference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BRKID

Attribute	Description
Name	BRKID
Datatype	String
Description	Indicates the Broker Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MSTLDT

Attribute	Description
Name	MSTLDT
Datatype	Date
Description	Indicates the MSTL Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGMSTLDT

Attribute	Description
Name	ORGMSTLDT
Datatype	Date
Description	Indicates the Actual MSTL Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTYDESC

Attribute	Description
Name	CPTYDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FRMTYPFROM

Attribute	Description
Name	FRMTYPFROM
Datatype	String
Description	Indicates the Type From.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRMTYPTO

Attribute	Description
Name	FRMTYPTO
Datatype	String
Description	Indicates the Type To.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UNEXPOSURE

Attribute	Description
Name	UNEXPOSURE
Datatype	String
Description	Indicates the Unexposure.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

TOTEXPOSURE

Attribute	Description
Name	TOTEXPOSURE
Datatype	String
Description	Indicates the To Exposure.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CLEANRISKLIMIT

Attribute	Description
Name	CLEANRISKLIMIT
Datatype	String
Description	Indicates the Clean Risk Limit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PSTLRISKLIMIT

Attribute	Description
Name	PSTLRISKLIMIT
Datatype	String
Description	Indicates the Track Pre-Settlement Risk Limit.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WALKINNAME

Attribute	Description	
Name	WALKINNAME	
Datatype	String	
Description	Indicates the Customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

WALKINMEDIA

Attribute	Description	
Name	WALKINMEDIA	
Datatype	String	
Description	Indicates the Walk in Media.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ADDRLINE1

Attribute	Description	
Name	ADDRLINE1	
Datatype	String	
Description	Indicates the Address Line 1.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE2

Attribute	Description	
Name	ADDRLINE2	
Datatype	String	
Description	Indicates the Address Line 2.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLINE3

Attribute	Description
Name	ADDRLINE3
Datatype	String
Description	Indicates the Address Line 3.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLINE4

Attribute	Description
Name	ADDRLINE4
Datatype	String
Description	Indicates the Address Line 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BUYSELL

Attribute	Description
Name	BUYSELL
Datatype	String
Description	Indicates whether Buy or sell.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

MSG

Attribute	Description
Name	MSG
Datatype	String
Description	Indicates the message.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MSGDESC

Attribute	Description
Name	MSGDESC

Datatype	String
Description	Indicates the message description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SKLOCDESC

Attribute	Description
Name	SKLOCDESC
Datatype	String
Description	Indicates the SK Location Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SKLOCDESCTO

Attribute	Description
Name	SKLOCDESCTO
Datatype	String
Description	Indicates the SK Location Description To.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PFDESC

Attribute	Description
Name	PFDESC
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Tax master

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FNDREFNO

Attribute	**Description**	
Name	FNDREFNO	
Datatype	String	
Description	Indicates the Fund Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSNO

Attribute	**Description**	
Name	VERSNO	
Datatype	Number	
Description	Specifies the Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Specifies the Internal Security Identification to be used.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TXTREF

Attribute	**Description**	
Name	TXTREF	
Datatype	String	
Description	Specifies the transaction reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description

Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description

Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String

Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	MIS Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Settlement-Addl-Details

Attribute	Description
Name	Settlement-Addl-Details
Datatype	
Description	Settlement Addtional Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates the FLEXCUBE Branch that has the account that sources funds of the deal
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	Indicates Account Currency
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account that sources the funds for the deal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></table>

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength: 25 minLength: 1

TOP

CUSTSPRD

Attribute	Description
Name	CUSTSPRD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 12 totalDigits: 24

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates the ERI Amount
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates the ERI currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate used between the bought and sold currencies for this deal
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

NETACRSMOD

Attribute	Description
Name	NETACRSMOD
Datatype	String
Description	Indicates Netting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

PAYRCV

Attribute	Description
Name	PAYRCV
Datatype	String
Description	Pay / Receive Indicator
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

RATECDDEFRD

Attribute	Description
Name	RATECDDEFRD
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

SPRDDFN

Attribute	Description
Name	SPRDDFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

TAG_CCY

Attribute	Description
Name	TAG_CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	This is Debit Credit Indicator.Specifies whether the leg is debited or credited.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1 pattern / [a-zA-Z_0-9]{1}

TOP

Settlement-Addl-Main

Attribute	Description
Name	Settlement-Addl-Main
Datatype	
Description	Indicates Settlement Additional Main details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC_INST1

Attribute	Description
Name	ACC_INST1
Datatype	String
Description	The Account With Institution 1 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST2

Attribute	Description
Name	ACC_INST2
Datatype	String
Description	The Account With Institution 2 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ACC_INST3

Attribute	Description
Name	ACC_INST3
Datatype	String
Description	The Account With Institution 3 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST4

Attribute	Description
Name	ACC_INST4
Datatype	String
Description	The Account With Institution 4 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST5

Attribute	Description
Name	ACC_INST5
Datatype	String
Description	The Account With Institution 5 may be a branch or affiliate of the Receiver, or of the Intermediary, or of the Beneficiary Institution, or an entirely different financial institution.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ACC_INST6

Attribute	Description
Name	ACC_INST6
Datatype	String
Description	Country to which the AWI belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

AGRID

Attribute	Description
Name	AGRID
Datatype	String

Description	Indicates Agreement Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates the deal amount. This is the amount that is being placed or borrowed as part for the deal
Restrictions	**Restrictions** / **Description** maxLength / 25 minLength / 1

TOP

BNKPRIO

Attribute	Description
Name	BNKPRIO
Datatype	String
Description	Indicates Banking Priority
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 1

TOP

BNFINSTCVR1

Attribute	Description
Name	BNFINSTCVR1
Datatype	String
Description	Indicates Beneficiary Institution for cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BNFINSTCVR2

Attribute	Description
Name	BNFINSTCVR2
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR3

Attribute	**Description**	
Name	BNFINSTCVR3	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR4

Attribute	**Description**	
Name	BNFINSTCVR4	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR5

Attribute	**Description**	
Name	BNFINSTCVR5	
Datatype	String	
Description	Indicates Beneficiary Institution for cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

BNFINSTCVR6

Attribute	**Description**
Name	BNFINSTCVR6
Datatype	String
Description	Indicates Beneficiary Institution for cover

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST1

Attribute	Description
Name	BENEF_INST1
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST2

Attribute	Description
Name	BENEF_INST2
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST3

Attribute	Description
Name	BENEF_INST3
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST4

Attribute	Description

Name	BENEF_INST4
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST5

Attribute	Description
Name	BENEF_INST5
Datatype	String
Description	Indicates the details of the institution in favour of which the payment is made can be entered
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

BENEF_INST6

Attribute	Description
Name	BENEF_INST6
Datatype	String
Description	Country to which the beneficiary institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Charge Details
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

CLGNTW

Attribute	Description	
Name	CLGNTW	
Datatype	String	
Description	Indicates Clearing network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

CVRBY

Attribute	Description	
Name	CVRBY	
Datatype	String	
Description	Indicates Cover by	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

COVER_REQ

Attribute	Description	
Name	COVER_REQ	
Datatype	String	
Description	Indicates the Cover Required preference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

XPTACC

Attribute	Description	
Name	XPTACC	
Datatype	String	
Description	Indicates External Party account	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTBIC

Attribute	Description	
Name	XPTBIC	
Datatype	String	
Description	Indicates External Party BIC	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTCLGNTW

Attribute	Description	
Name	XPTCLGNTW	
Datatype	String	
Description	Indicates External Party Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

XPTNAME

Attribute	Description	
Name	XPTNAME	
Datatype	String	
Description	Indicates External Party Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

IBANACCNO

Attribute	Description	
Name	IBANACCNO	
Datatype	String	
Description	Indicates International Bank Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	minLength	1

TOP

INST_NO

Attribute	Description
Name	INST_NO
Datatype	String
Description	Indicates the Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

INST_TYPE

Attribute	Description
Name	INST_TYPE
Datatype	String
Description	Indicates the Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 1

TOP

INT_REIM_INST1

Attribute	Description
Name	INT_REIM_INST1
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INT_REIM_INST2

Attribute	Description
Name	INT_REIM_INST2
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST3

Attribute	Description
Name	INT_REIM_INST3
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST4

Attribute	Description
Name	INT_REIM_INST4
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST5

Attribute	Description
Name	INT_REIM_INST5
Datatype	String
Description	Indicates the financial institution between the Sender¿s Correspondent and the Receiver¿s Correspondent through which the reimbursement of the transfer takes place
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

INT_REIM_INST6

Attribute	Description
Name	INT_REIM_INST6

Datatype	String
Description	Country to which the Intermediary remitter institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY1

Attribute	Description
Name	INTMEDRY1
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY2

Attribute	Description
Name	INTMEDRY2
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY3

Attribute	Description
Name	INTMEDRY3
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY4

Attribute	Description
Name	INTMEDRY4
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY5

Attribute	Description
Name	INTMEDRY5
Datatype	String
Description	Indicates that the payment refers to the financial institution between the `Receiver¿ and the `Account With Institution¿, through which the transfer must pass
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

INTMEDRY6

Attribute	Description
Name	INTMEDRY6
Datatype	String
Description	Country to which the intermediary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_CUST1

Attribute	Description
Name	ORDER_CUST1
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST2

Attribute	Description
Name	ORDER_CUST2
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST3

Attribute	Description
Name	ORDER_CUST3
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST4

Attribute	Description
Name	ORDER_CUST4
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

ORDER_CUST5

Attribute	Description
Name	ORDER_CUST5
Datatype	String
Description	The Ordering Customer refers to the customer ordering the transfer
Attributes	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_CUST6

Attribute	Description
Name	ORDER_CUST6
Datatype	String
Description	Country to which the ordering customer belongs
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST1

Attribute	Description
Name	ORDER_INST1
Datatype	String
Description	Indicates the first ordering Institution which is acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST2

Attribute	Description
Name	ORDER_INST2
Datatype	String
Description	Indicates the second ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ORDER_INST3

Attribute	Description
Name	ORDER_INST3
Datatype	String
Description	Indicates the third ordering Institution acting on behalf of itself or a customer to initiate the transaction

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST4

Attribute	Description
Name	ORDER_INST4
Datatype	String
Description	Indicates the fourth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST5

Attribute	Description
Name	ORDER_INST5
Datatype	String
Description	Indicates the fifth ordering Institution acting on behalf of itself or a customer to initiate the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ORDER_INST6

Attribute	Description
Name	ORDER_INST6
Datatype	String
Description	Country to which the ordering institution belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

OUR_CORRESP

Attribute	Description
Name	OUR_CORRESP

Datatype	String
Description	Indicates Our Correspondent.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 pattern / [a-zA-Z0-9]*

TOP

PMNT_BY

Attribute	Description
Name	PMNT_BY
Datatype	String
Description	Indicates the mode of making the payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

PMNT_DETAILS1

Attribute	Description
Name	PMNT_DETAILS1
Datatype	String
Description	Indicates the details of the first payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS2

Attribute	Description
Name	PMNT_DETAILS2
Datatype	String
Description	Indicates the details of the second payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

PMNT_DETAILS3

Attribute	Description
Name	PMNT_DETAILS3
Datatype	String

Description	Indicates the details of the third payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

PMNT_DETAILS4

Attribute	Description
Name	PMNT_DETAILS4
Datatype	String
Description	Indicates the details of the fourth payment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

POSTACCNG

Attribute	Description
Name	POSTACCNG
Datatype	String
Description	Indicates Posting Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; minLength / 1

TOP

RCVR_CORRESP1

Attribute	Description
Name	RCVR_CORRESP1
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

RCVR_CORRESP2

Attribute	Description
Name	RCVR_CORRESP2

Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP3

Attribute	Description
Name	RCVR_CORRESP3
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP4

Attribute	Description
Name	RCVR_CORRESP4
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP5

Attribute	Description
Name	RCVR_CORRESP5
Datatype	String
Description	Indicates the branch of the Receiver or another financial institution at which the funds will be made available to the Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RCVR_CORRESP6

Attribute	Description
Name	RCVR_CORRESP6
Datatype	String
Description	Country to which the receiver correspondent belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates the receiver.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 1

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates Real Time Gross Settlement Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates Real Time Gross Settlement payment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

SNDR_INFO1

Attribute	Description
Name	SNDR_INFO1
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO2

Attribute	Description
Name	SNDR_INFO2
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO3

Attribute	Description
Name	SNDR_INFO3
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO4

Attribute	Description
Name	SNDR_INFO4
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO5

Attribute	Description
Name	SNDR_INFO5
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

SNDR_INFO6

Attribute	Description
Name	SNDR_INFO6
Datatype	String
Description	Indicates the sender information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

TRNFRTYP

Attribute	Description
Name	TRNFRTYP
Datatype	String
Description	Indicates Transfer Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 minLength / 1

TOP

ULT_BENEF1

Attribute	Description
Name	ULT_BENEF1
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF2

Attribute	Description
Name	ULT_BENEF2
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF3

Attribute	Description
Name	ULT_BENEF3
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF4

Attribute	Description
Name	ULT_BENEF4
Datatype	String
Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

ULT_BENEF5

Attribute	Description
Name	ULT_BENEF5
Datatype	String

Description	Indicates the Ultimate Beneficiary refers to the Customer to whom the amount of the component is to be paid
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

ULT_BENEF6

Attribute	Description
Name	ULT_BENEF6
Datatype	String
Description	Country to which the ultimate beneficiary belongs
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

AMTTAGDESC

Attribute	Description
Name	AMTTAGDESC
Datatype	String
Description	Indicates Amount Tag Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

DISEXTBKCD

Attribute	Description
Name	DISEXTBKCD
Datatype	String
Description	Indicates Bank Name of External party BIC code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 1

TOP

PAYBNK

Attribute	Description
Name	PAYBNK

Datatype	String
Description	Indicates the Payable Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

PAYBRN

Attribute	Description
Name	PAYBRN
Datatype	String
Description	Indicates the Pay Branch.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAVEINSTCHARG

Attribute	Description
Name	WAVEINSTCHARG
Datatype	String
Description	Indicates the Waiving of Instrument charges maintaIned at ARC
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BNKOPRCD

Attribute	Description
Name	BNKOPRCD
Datatype	String
Description	Indicates Bank Operation Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 1

TOP

ENV_CONT1

Attribute	Description
Name	ENV_CONT1
Datatype	String
Description	Envelope Contents

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT2

Attribute	**Description**	
Name	ENV_CONT2	
Datatype	String	
Description	Envelope Contents 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT3

Attribute	**Description**	
Name	ENV_CONT3	
Datatype	String	
Description	Envelope Contents 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT4

Attribute	**Description**	
Name	ENV_CONT4	
Datatype	String	
Description	Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000
	minLength	1

TOP

ENV_CONT5

Attribute	**Description**
Name	ENV_CONT5
Datatype	String
Description	Envelope Contents 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35 minLength / 1

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Charge Application
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	The Charge Component Code required to calculate interest.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRNESN

Attribute	Description
Name	CRNESN
Datatype	Number
Description	Indicates the Creation ESN
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates the Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates the Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINTR

Attribute	Description
Name	LIQINTR
Datatype	String
Description	Indicates whether Liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACR

Attribute	Description
Name	DISACR
Datatype	String
Description	Indicates that discount accrual fees will be charged.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.114.AuthSEInstrument

Authorization of Securities Instrument Definition

2.114.1.SEInstrument-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Auth-Req-Full*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Authorization Of a Instr.

TOP

SEInstrument-Auth-Req-Full

Attribute	Description
Name	SEInstrument-Auth-Req-Full
Datatype	
Description	Authorization of Securities Instrument Definition Request Full Type.

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Securities ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9. %_]*</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Securitie Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9. %_]*</td></tr></table>

TOP

2.114.2.SEInstrument-Auth-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Auth-Req*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Authorization Of a Instr.

TOP

SEInstrument-Auth-Req

Attribute	Description
Name	SEInstrument-Auth-Req
Datatype	
Description	Authorization of Securities Instrument Definition Request Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Securities ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Securitie Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

2.114.3.SEInstrument-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Auth-Res-Full*
    - *SECID*
    - *SECREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Authorization Of a Instr.

TOP

Auth-Res-Full

Attribute	Description
Name	Auth-Res-Full
Datatype	
Description	Authorization of Securities Instrument Definition Full Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Securities ID

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Securitie Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.114.4.SEInstrument-Auth-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Auth-Res*
      - *SECID*
      - *SECREFNO*
    - *SEInstrument-Auth-Req*
      - *SECID*
      - *SECREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Authorization Of a Instr.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Auth-Res

Attribute	Description
Name	Auth-Res
Datatype	
Description	Authorization of Securities Instrument Definition Response Type

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Securities ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SECREFNO

Attribute	**Description**	
Name	SECREFNO	
Datatype	String	
Description	Securitie Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SEInstrument-Auth-Req

Attribute	**Description**
Name	SEInstrument-Auth-Req
Datatype	
Description	Authorization of Securities Instrument Definition Request Type

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Securities ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Securitie Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.115.CloseSEInstrument

Closure of Securities Instrument Definition

2.115.1.SEInstrument-Close-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Close-Req-Full*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Cancellation Or Reversal Of a Deal.

TOP

SEInstrument-Close-Req-Full

Attribute	Description
Name	SEInstrument-Close-Req-Full
Datatype	
Description	Closure of Securities Instrument Definition Request Full Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description

Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

2.115.2.SEInstrument-Close-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Close-Req*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Cancellation Or Reversal Of a Deal.

TOP

SEInstrument-Close-Req

Attribute	Description
Name	SEInstrument-Close-Req
Datatype	
Description	Closure of Securities Instrument Definition Request Type.

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

2.115.3.SEInstrument-Close-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master*
    - *XREF*
    - *SECID*
    - *ISINIDNTFR*
    - *SECDES*
    - *PROD*
    - *PRODDES*
    - *SECRTYP*
    - *SECREFNO*
    - *SECRSTAT*
    - *TRADSTAT*
    - *INTERRAT*
    - *MKTISS*
    - *MKTDES*
    - *ISSID*
    - *ISSDES*
    - *REGBEAR*
    - *FRMTYPE*
    - *QTYQUOT*

INTQUOT
FRACTQUANT
UDECIMAL
EQRED
REN
REDTYPE
REDEMPQUOT
CONFCORPACTION
CALLOPT
PUTOPT
SECCCY
PAYCCY
ISSSIZE
OSISSIZE
MINTRDQT
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
CURENTFV
REDPRICE
ISSSECID
MKTSECID
CNBSECID
REST
VOTRIT
COVERED
CONVBLE
BKACC
ISOCFICODE
ISITCCODE
ATTRBDES
COLLTYPE
DIREXPLINE
QUALRAT
REVPRICODE
PRICDES
MKTREV
COUPBASIS
DIVBASIS
WARRBASIS

RITBASIS
AUTOCORP
PRIQUOT
RATECODE
USBONDFORM
TBILLREINVPER
TBILLANNMETH
TBILLCOUNTNR
TBILLCOUNTDN
BNDREINVPER
BNDANNMETH
BNDDAYCOUNTNR
BNDDAYCOUNTDN
PREMDISCURRPE
DAYS
DAYIN
IDNTINARRAT1
IDNTINARRAT2
IDNTINARRAT3
IDNTINARRAT4
ATTRIBNARRAT1
ATTRIBNARRAT2
ATTRIBNARRAT3
ATTRIBNARRAT4
ATTRIBNARRAT5
ATTRIBNARRAT6
ATTRIBNARRAT7
ATTRIBNARRAT8
ATTRIBNARRAT9
ATTRIBNARRAT10
MINIRATE
MAXIRATE
Mis-Details
- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Tax-Master
FNDREFNO
VERSNO
SECID
TXTREF
SECREF
Issr-Tax-Assoc
CRRATESN
INTCOMP

RATECOD
WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Sec-Master
SECID
SECREFNO
Interest-Assoc
CRRATESN
INTCOMP
WAIVER
RATECODE
RATCODESC
TENCODE
TENCODESC
INTSPRD
INTRATE
FLTAMT
ACQAMT
INTCALCMET
QUOTREVIND
QUOTREVSPD
QUOTREVFLR
QUOTREVCEIL

Interest

- *PERCOUP*
- *ALLASYNCREV*
- *PERREV*
- *CAPT*
- *COUPFREQ*
- *ACCVALDATE*
- *COUPWEEK*
- *COUPPLTDATE*
- *CADHMNTHEND*
- *REVFREQ*
- *REVWEEK*
- *RADHMNTHEND*
- *RNDBASIS*
- *RATEBASIS*
- *CUMINTRAT*
- *ACCRNUMMETH*
- *ACCRDENMETH*
- *ACCRDENBASS*
- *ACRR366BASS*
- *ACCRINCLTODT*
- *LIQDNUMMETH*
- *LIQDDENMETH*
- *LIQDDENBASS*
- *LIQD366BASS*
- *ISSSIZE*
- *DOCSWFT*
- *ZEROINT*

Security-Series

- *SERIES*

Coupon-Sched

- *COUPSTDT*
- *COUPTYPE*
- *COUPENDT*
- *BASEFREQ*
- *WEEKDAY*
- *ADHMNTHEND*

Revision-Sched

- *REVSTDT*
- *REVTYPE*
- *REVENDT*
- *REVBASEFREQ*
- *REVWEEKDAY*
- *REVADHMONE*

Redemption
REDEVTDT
PERREDEM
REDPRI
DISPFRAC
CALLINDICAT
REDSERIES
Coupon-Period
PCD
NCD
COUPTYDES
VIRPREVDT2
VIRPREVDT1
VIRNEXDT1
VIRNEXDT2
Revision-Date-Master
REVTDATE
REVEFFDATE
Security-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Security-Hol-Ccy
SECURITYID
HOLCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Cancellation Or Reversal Of a Deal.

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Closure of Securities Instrument Definition Master Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

SECDES

Attribute	Description
Name	SECDES
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRODDES

Attribute	Description
Name	PRODDES
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SECRTYP

Attribute	Description
Name	SECRTYP
Datatype	String
Description	Indicates Security Type Bond : B Equity : E Rights : R Warrant : W Zero Coupon Bond : Z
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SECRSTAT

Attribute	Description
Name	SECRSTAT
Datatype	String
Description	Indicates Security Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TRADSTAT

Attribute	Description
Name	TRADSTAT
Datatype	String
Description	Indicates Trading Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTERRAT

Attribute	Description
Name	INTERRAT
Datatype	String
Description	Indicates Interest Type Floating : FLT Fixed : FXD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

MKTDES

Attribute	Description
Name	MKTDES
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

ISSDES

Attribute	Description
Name	ISSDES
Datatype	String
Description	Indicates Issuer Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String

Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

QTYQUOT

Attribute	Description
Name	QTYQUOT
Datatype	String
Description	Indicates Quantity Quotation UNITS : U NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

INTQUOT

Attribute	Description
Name	INTQUOT
Datatype	String
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,A,P

TOP

FRACTQUANT

Attribute	Description
Name	FRACTQUANT
Datatype	String
Description	Indicates Fractional Quantity Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDECIMAL

Attribute	Description
Name	UDECIMAL
Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description
Name	EQRED
Datatype	String
Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String
Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT
Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description
Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTRDQT

Attribute	Description
Name	MINTRDQT

Datatype	Number
Description	Indicates Min Trading Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates Lot Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDAT

Attribute	Description
Name	STTRADEDAT
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INFACEVAL

Attribute	**Description**	
Name	INFACEVAL	
Datatype	Number	
Description	Indicates Initial Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSPRICE

Attribute	**Description**	
Name	ISSPRICE	
Datatype	Number	
Description	Indicates Issue Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CURENTFV

Attribute	**Description**	
Name	CURENTFV	
Datatype	Number	
Description	Indicates Current Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REDPRICE

Attribute	**Description**	
Name	REDPRICE	
Datatype	Number	
Description	Indicates Redemption Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSSECID

Attribute	**Description**	
Name	ISSSECID	
Datatype	String	
Description	Indicates Issuer Security ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9_]*

TOP

MKTSECID

Attribute	Description
Name	MKTSECID
Datatype	String
Description	Indicates Market Security ID
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9_]*

TOP

CNBSECID

Attribute	Description
Name	CNBSECID
Datatype	String
Description	Indicates Central Bank Security ID
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9_]*

TOP

REST

Attribute	Description
Name	REST
Datatype	String
Description	Indicates Restricted Y for Yes; N for No
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

VOTRIT

Attribute	Description
Name	VOTRIT
Datatype	String

Description	Indicates Voting Rights Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVERED

Attribute	Description
Name	COVERED
Datatype	String
Description	Indicates Covered Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONVBLE

Attribute	Description
Name	CONVBLE
Datatype	String
Description	Indicates Convertible Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BKACC

Attribute	Description
Name	BKACC
Datatype	String
Description	Indicates Bankers Accept Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ISOCFICODE

Attribute	Description

Name	ISOCFICODE
Datatype	String
Description	Indicates ISO CFI Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	Description
Name	ISITCCODE
Datatype	String
Description	Indicates ISITC Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ATTRBDES

Attribute	Description
Name	ATTRBDES
Datatype	String
Description	Indicates Attribute Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description
Name	DIREXPLINE
Datatype	String
Description	Indicates Direct Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description
Name	QUALRAT
Datatype	String
Description	Indicates Quality Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0 pattern / [A-Za-z0-9]*

TOP

REVPRICODE

Attribute	Description
Name	REVPRICODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

PRICDES

Attribute	Description
Name	PRICDES
Datatype	String
Description	Indicates Price Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String

Description	Indicates Warrant Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

RITBASIS

Attribute	Description
Name	RITBASIS
Datatype	String
Description	Indicates Rights Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

AUTOCORP

Attribute	Description
Name	AUTOCORP
Datatype	String
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIQUOT

Attribute	Description
Name	PRIQUOT
Datatype	String
Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRE,PPD,YTM

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

USBONDFORM

Attribute	Description
Name	USBONDFORM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C

TOP

TBILLCOUNTNR

Attribute	**Description**	
Name	TBILLCOUNTNR	
Datatype	String	
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U

TOP

TBILLCOUNTDN

Attribute	**Description**	
Name	TBILLCOUNTDN	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H

TOP

BNDREINVPER

Attribute	**Description**	
Name	BNDREINVPER	
Datatype	String	
Description	Indicates Reinv. Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	0
	pattern	[0-9]*

TOP

BNDANNMETH

Attribute	Description
Name	BNDANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNDDAYCOUNTNR

Attribute	Description
Name	BNDDAYCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description
Name	BNDDAYCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

PREMDISCURRPE

Attribute	Description
Name	PREMDISCURRPE
Datatype	String
Description	Indicates Premium/Discount For Current Interest Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	Indicates No of Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIN

Attribute	Description
Name	DAYIN
Datatype	String
Description	Indicates Days Before Start of Next Coupon Period : B After Start of Previous Coupon Period : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IDNTINARRAT1

Attribute	Description
Name	IDNTINARRAT1
Datatype	String
Description	Indicates Identification Narrative 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT2

Attribute	Description
Name	IDNTINARRAT2
Datatype	String
Description	Indicates Identification Narrative 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

IDNTINARRAT3

Attribute	**Description**	
Name	IDNTINARRAT3	
Datatype	String	
Description	Indicates Identification Narrative 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

IDNTINARRAT4

Attribute	**Description**	
Name	IDNTINARRAT4	
Datatype	String	
Description	Indicates Identification Narrative 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT1

Attribute	**Description**	
Name	ATTRIBNARRAT1	
Datatype	String	
Description	Indicates Attribute Narrative 01	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT2

Attribute	**Description**	
Name	ATTRIBNARRAT2	
Datatype	String	
Description	Indicates Attribute Narrative 02	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT3

Attribute	**Description**	
Name	ATTRIBNARRAT3	
Datatype	String	
Description	Indicates Attribute Narrative 03	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT4

Attribute	**Description**	
Name	ATTRIBNARRAT4	
Datatype	String	
Description	Indicates Attribute Narrative 04	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT5

Attribute	**Description**	
Name	ATTRIBNARRAT5	
Datatype	String	
Description	Indicates Attribute Narrative 05	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT6

Attribute	**Description**	
Name	ATTRIBNARRAT6	
Datatype	String	
Description	Indicates Attribute Narrative 06	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT7

Attribute	**Description**	
Name	ATTRIBNARRAT7	
Datatype	String	
Description	Indicates Attribute Narrative 07	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT8

Attribute	**Description**	
Name	ATTRIBNARRAT8	
Datatype	String	
Description	Indicates Attribute Narrative 08	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT9

Attribute	**Description**	
Name	ATTRIBNARRAT9	
Datatype	String	
Description	Indicates Attribute Narrative 09	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT10

Attribute	**Description**	
Name	ATTRIBNARRAT10	
Datatype	String	
Description	Indicates Attribute Narrative 10	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

MINIRATE

Attribute	Description	
Name	MINIRATE	
Datatype	Number	
Description	Indicates Min Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXIRATE

Attribute	Description	
Name	MAXIRATE	
Datatype	Number	
Description	Indicates Max Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

Mis-Details

Attribute	Description	
Name	Mis-Details	
Datatype		
Description	Includes MIS details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Tax-Master

Attribute	**Description**	
Name	Tax-Master	
Datatype		
Description	Includes Tax Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FNDREFNO

Attribute	**Description**	
Name	FNDREFNO	
Datatype	String	
Description	Indicates the Fund Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSNO

Attribute	**Description**	
Name	VERSNO	
Datatype	Number	
Description	Specifies the Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description	
Name	CONTREF	
Datatype	String	
Description	Specifies The Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Tran-Tax-Appln

Attribute	Description	
Name	Tran-Tax-Appln	
Datatype		
Description	Specifies The Application Details Of Transaction Level Tax.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description

Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sec-Master

Attribute	**Description**	
Name	Sec-Master	
Datatype		
Description	Includes Security Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Indicates Security Id	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	**Description**	
Name	SECREFNO	
Datatype	String	
Description	Indicates Security Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Interest-Assoc

Attribute	**Description**	
Name	Interest-Assoc	
Datatype		
Description	Includes Interest Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

RATCODESC

Attribute	Description
Name	RATCODESC
Datatype	String
Description	Indicates Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TENCODE

Attribute	Description
Name	TENCODE
Datatype	String
Description	Indicates Tenor Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

TENCODESC

Attribute	Description
Name	TENCODESC
Datatype	String
Description	Indicates Tenor Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 33 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	Description
Name	FLTAMT
Datatype	Number
Description	Indicates Flat Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String
Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND

Datatype	String
Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String

Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PERREV

Attribute	Description
Name	PERREV
Datatype	String
Description	Indicates Periodic Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPT

Attribute	Description
Name	CAPT
Datatype	String
Description	Indicates Capitalization Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPFREQ

Attribute	Description

Name	COUPFREQ
Datatype	String
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFREQ

Attribute	Description
Name	REVFREQ
Datatype	String
Description	Indicates Revision Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	**Description**	
Name	RADHMNTHEND	
Datatype	String	
Description	Indicates Adhere To Month End Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASIS

Attribute	**Description**	
Name	RNDBASIS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,U

TOP

RATEBASIS

Attribute	**Description**	
Name	RATEBASIS	
Datatype	String	
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

CUMINTRAT

Attribute	**Description**
Name	CUMINTRAT

Datatype	Number
Description	Indicates Cumulative Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

ACCRNUMMETH

Attribute	Description
Name	ACCRNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

ACRR366BASS

Attribute	Description	
Name	ACRR366BASS	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

ACCRINCLTODT

Attribute	Description	
Name	ACCRINCLTODT	
Datatype	String	
Description	Indicates Include To Date Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMETH

Attribute	Description	
Name	LIQDNUMMETH	
Datatype	String	
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description

Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

LIQD366BASS

Attribute	Description
Name	LIQD366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWFT

Attribute	Description
Name	DOCSWFT
Datatype	String
Description	Indicates Document Method Swift Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINT

Attribute	Description
Name	ZEROINT
Datatype	String
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	Includes Security Series details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates SERIES
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	Includes Coupon Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COUPSTDT

Attribute	Description
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	Description
Name	COUPTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,C</td></tr></table>

TOP

COUPENDT

Attribute	Description
Name	COUPENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched

Datatype	
Description	Includes Revision Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASEFREQ

Attribute	Description
Name	REVBASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	Description
Name	REVWEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

REVADHMONE

Attribute	Description
Name	REVADHMONE
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption

Datatype	
Description	Includes Redemption details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REDEVTDT

Attribute	Description
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	Description
Name	PERREDEM
Datatype	Number
Description	Indicates % To Be Redeemed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRI

Attribute	Description
Name	REDPRI
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPFRAC

Attribute	Description
Name	DISPFRAC
Datatype	String
Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

CALLINDICAT

Attribute	Description
Name	CALLINDICAT
Datatype	String
Description	Indicates Call Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	Includes Coupon Period details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PCD

Attribute	Description
Name	PCD
Datatype	String
Description	Indicates Previous Coupon Date
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NCD

Attribute	Description
Name	NCD

Datatype	String
Description	Indicates Next Coupon Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COUPTYDES

Attribute	Description
Name	COUPTYDES
Datatype	String
Description	Indicates Coupon Period Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	String
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	String
Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	String
Description	Indicates Next Virtual First Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

VIRNEXDT2

Attribute	**Description**	
Name	VIRNEXDT2	
Datatype	String	
Description	Indicates Next Virtual Second Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Revision-Date-Master

Attribute	**Description**	
Name	Revision-Date-Master	
Datatype		
Description	Includes Revision Date Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REVTDATE

Attribute	**Description**	
Name	REVTDATE	
Datatype	Date	
Description	Indicates Event Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVEFFDATE

Attribute	**Description**	
Name	REVEFFDATE	
Datatype	Date	
Description	Indicates Effective Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Security-Event-Log

Attribute	**Description**

Name	Security-Event-Log
Datatype	
Description	Includes Security Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date TIme:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U For Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	Includes Security Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.115.4.SEInstrument-Close-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master*
      - *SECREFNO*
      - *SECID*
      - *PROD*
      - *MKTISS*
      - *ISSID*
      - *SECCCY*
      - *PAYCCY*
      - *ISSDATE*
      - *STINTDATE*
      - *STTRADEDATE*
      - *INFACEVAL*
    - *SEInstrument-Close-Req*
      - *SECID*
      - *SECREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Cancellation Or Reversal Of a Deal.

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Closure of Securities Instrument Definition Master Type

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates pay Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0

TOP

ISSDATE

Attribute	Description	
Name	ISSDATE	
Datatype	String	
Description	Indicates Issue date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32
	minLength	0

TOP

STINTDATE

Attribute	Description	
Name	STINTDATE	
Datatype	String	
Description	Indicates Start of Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32
	minLength	0

TOP

STTRADEDATE

Attribute	Description	
Name	STTRADEDATE	
Datatype	String	
Description	Indicates Start of Trading Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32
	minLength	0

TOP

INFACEVAL

Attribute	Description	
Name	INFACEVAL	
Datatype	Number	
Description	Indicates Initial Face Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

SEInstrument-Close-Req

Attribute	Description
Name	SEInstrument-Close-Req
Datatype	
Description	Closure of Securities Instrument Definition Request Type.

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.116.CreateSEInstrument

Creation of Securities Instrument

2.116.1.SEInstrument-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master*
    - *XREF*
    - *SECID*
    - *ISINIDNTFR*
    - *SECDES*
    - *PROD*
    - *PRODDES*
    - *SECRTYP*
    - *SECREFNO*
    - *SECRSTAT*
    - *TRADSTAT*
    - *INTERRAT*
    - *MKTISS*
    - *MKTDES*
    - *ISSID*
    - *ISSDES*

REGBEAR
FRMTYPE
QTYQUOT
INTQUOT
FRACTQUANT
UDECIMAL
EQRED
REN
REDTYPE
REDEMPQUOT
CONFCORPACTION
CALLOPT
PUTOPT
SECCCY
PAYCCY
ISSSIZE
OSISSIZE
MINTRDQT
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
CURENTFV
REDPRICE
ISSSECID
MKTSECID
CNBSECID
REST
VOTRIT
COVERED
CONVBLE
BKACC
ISOCFICODE
ISITCCODE
ATTRBDES
COLLTYPE
DIREXPLINE
QUALRAT
REVPRICODE
PRICDES
MKTREV

COUPBASIS
DIVBASIS
WARRBASIS
RITBASIS
AUTOCORP
PRIQUOT
RATECODE
USBONDFORM
TBILLREINVPER
TBILLANNMETH
TBILLCOUNTNR
TBILLCOUNTDN
BNDREINVPER
BNDANNMETH
BNDDAYCOUNTNR
BNDDAYCOUNTDN
PREMDISCURRPE
DAYS
DAYIN
IDNTINARRAT1
IDNTINARRAT2
IDNTINARRAT3
IDNTINARRAT4
ATTRIBNARRAT1
ATTRIBNARRAT2
ATTRIBNARRAT3
ATTRIBNARRAT4
ATTRIBNARRAT5
ATTRIBNARRAT6
ATTRIBNARRAT7
ATTRIBNARRAT8
ATTRIBNARRAT9
ATTRIBNARRAT10
MINIRATE
MAXIRATE
Mis-Details
- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

- *TXNMIS9*
- *TXNMIS10*
- *FUNDMIS1LBL1*
- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*

Issr-Tax-Assoc
CRRATESN
INTCOMP
RATECOD
WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Sec-Master
SECID
SECREFNO
Interest-Assoc
CRRATESN
INTCOMP
WAIVER
RATECODE
RATCODESC
TENCODE
TENCODESC
INTSPRD
INTRATE
FLTAMT
ACQAMT
INTCALCMET
QUOTREVIND

- *QUOTREVSPD*
- *QUOTREVFLR*
- *QUOTREVCEIL*

Interest

- *PERCOUP*
- *ALLASYNCREV*
- *PERREV*
- *CAPT*
- *COUPFREQ*
- *ACCVALDATE*
- *COUPWEEK*
- *COUPPLTDATE*
- *CADHMNTHEND*
- *REVFREQ*
- *REVWEEK*
- *RADHMNTHEND*
- *RNDBASIS*
- *RATEBASIS*
- *CUMINTRAT*
- *ACCRNUMMETH*
- *ACCRDENMETH*
- *ACCRDENBASS*
- *ACRR366BASS*
- *ACCRINCLTODT*
- *LIQDNUMMETH*
- *LIQDDENMETH*
- *LIQDDENBASS*
- *LIQD366BASS*
- *ISSSIZE*
- *DOCSWFT*
- *ZEROINT*

Security-Series

- *SERIES*

Coupon-Sched

- *COUPSTDT*
- *COUPTYPE*
- *COUPENDT*
- *BASEFREQ*
- *WEEKDAY*
- *ADHMNTHEND*

Revision-Sched

- *REVSTDT*
- *REVTYPE*
- *REVENDT*

REVBASEFREQ
REVWEEKDAY
REVADHMONE
Redemption
REDEVTDT
PERREDEM
REDPRI
DISPFRAC
CALLINDICAT
REDSERIES
Coupon-Period
PCD
NCD
COUPTYDES
VIRPREVDT2
VIRPREVDT1
VIRNEXDT1
VIRNEXDT2
Revision-Date-Master
REVTDATE
REVEFFDATE
Security-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Security-Hol-Ccy
SECURITYID
HOLCCY

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Creation Of the Instrumnet

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Creation of Securities Instrument Master Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID

Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

SECDES

Attribute	Description
Name	SECDES
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRODDES

Attribute	Description
Name	PRODDES
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SECRTYP

Attribute	Description
Name	SECRTYP
Datatype	String
Description	Indicates Security Type Bond : B Equity : E Rights : R Warrant : W Zero Coupon Bond : Z
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SECRSTAT

Attribute	Description
Name	SECRSTAT
Datatype	String
Description	Indicates Security Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TRADSTAT

Attribute	Description
Name	TRADSTAT
Datatype	String
Description	Indicates Trading Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTERRAT

Attribute	Description
Name	INTERRAT
Datatype	String
Description	Indicates Interest Type Floating : FLT Fixed : FXD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

MKTDES

Attribute	Description
Name	MKTDES
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

ISSDES

Attribute	Description
Name	ISSDES
Datatype	String
Description	Indicates Issuer Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String
Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

QTYQUOT

Attribute	Description
Name	QTYQUOT
Datatype	String

Description	Indicates Quantity Quotation UNITS : U NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

INTQUOT

Attribute	Description
Name	INTQUOT
Datatype	String
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,A,P

TOP

FRACTQUANT

Attribute	Description
Name	FRACTQUANT
Datatype	String
Description	Indicates Fractional Quantity Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDECIMAL

Attribute	Description
Name	UDECIMAL
Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description
Name	EQRED
Datatype	String

Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String
Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT
Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description

Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTRDQT

Attribute	Description
Name	MINTRDQT
Datatype	Number
Description	Indicates Min Trading Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates Lot Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDAT

Attribute	Description
Name	STTRADEDAT
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURENTFV

Attribute	Description
Name	CURENTFV
Datatype	Number
Description	Indicates Current Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSSECID

Attribute	Description
Name	ISSSECID
Datatype	String
Description	Indicates Issuer Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

MKTSECID

Attribute	Description
Name	MKTSECID
Datatype	String
Description	Indicates Market Security ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9_]*

TOP

CNBSECID

Attribute	Description
Name	CNBSECID
Datatype	String
Description	Indicates Central Bank Security ID
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9_]*

TOP

REST

Attribute	Description
Name	REST
Datatype	String
Description	Indicates Restricted Y for Yes; N for No
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

VOTRIT

Attribute	Description
Name	VOTRIT
Datatype	String
Description	Indicates Voting Rights Y for Yes; N for No
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TOP

COVERED

Attribute	Description
Name	COVERED
Datatype	String

Description	Indicates Covered Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONVBLE

Attribute	Description
Name	CONVBLE
Datatype	String
Description	Indicates Convertible Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BKACC

Attribute	Description
Name	BKACC
Datatype	String
Description	Indicates Bankers Accept Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ISOCFICODE

Attribute	Description
Name	ISOCFICODE
Datatype	String
Description	Indicates ISO CFI Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	Description
Name	ISITCCODE
Datatype	String
Description	Indicates ISITC Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

ATTRBDES

Attribute	Description
Name	ATTRBDES
Datatype	String
Description	Indicates Attribute Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description
Name	DIREXPLINE
Datatype	String
Description	Indicates Direct Exposure Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description
Name	QUALRAT
Datatype	String
Description	Indicates Quality Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0 pattern / [A-Za-z0-9]*

TOP

REVPRICODE

Attribute	Description
Name	REVPRICODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

PRICDES

Attribute	Description
Name	PRICDES
Datatype	String
Description	Indicates Price Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 30 minLength: 0 pattern: [A-Za-z0-9_]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String
Description	Indicates Warrant Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: P,H

TOP

RITBASIS

Attribute	Description
Name	RITBASIS

Datatype	String
Description	Indicates Rights Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

AUTOCORP

Attribute	Description
Name	AUTOCORP
Datatype	String
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIQUOT

Attribute	Description
Name	PRIQUOT
Datatype	String
Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRE,PPD,YTM

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

USBONDFORM

Attribute	Description
Name	USBONDFORM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C

TOP

TBILLCOUNTNR

Attribute	Description
Name	TBILLCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U

TOP

TBILLCOUNTDN

Attribute	**Description**	
Name	TBILLCOUNTDN	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H

TOP

BNDREINVPER

Attribute	**Description**	
Name	BNDREINVPER	
Datatype	String	
Description	Indicates Reinv. Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	0
	pattern	[0-9]*

TOP

BNDANNMETH

Attribute	**Description**	
Name	BNDANNMETH	
Datatype	String	
Description	Indicates Annualizing Method Simple : S Compound : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BNDDAYCOUNTNR

Attribute	**Description**

Name	BNDDAYCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description
Name	BNDDAYCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

PREMDISCURRPE

Attribute	Description
Name	PREMDISCURRPE
Datatype	String
Description	Indicates Premium/Discount For Current Interest Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	Indicates No of Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIN

Attribute	Description
Name	DAYIN
Datatype	String
Description	Indicates Days Before Start of Next Coupon Period : B After Start of Previous Coupon Period : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IDNTINARRAT1

Attribute	Description
Name	IDNTINARRAT1
Datatype	String
Description	Indicates Identification Narrative 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT2

Attribute	Description
Name	IDNTINARRAT2
Datatype	String
Description	Indicates Identification Narrative 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT3

Attribute	Description
Name	IDNTINARRAT3
Datatype	String
Description	Indicates Identification Narrative 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT4

Attribute	Description
Name	IDNTINARRAT4
Datatype	String
Description	Indicates Identification Narrative 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT1

Attribute	Description
Name	ATTRIBNARRAT1
Datatype	String
Description	Indicates Attribute Narrative 01
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT2

Attribute	Description
Name	ATTRIBNARRAT2
Datatype	String
Description	Indicates Attribute Narrative 02
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT3

Attribute	Description
Name	ATTRIBNARRAT3
Datatype	String
Description	Indicates Attribute Narrative 03
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT4

Attribute	Description
Name	ATTRIBNARRAT4
Datatype	String
Description	Indicates Attribute Narrative 04
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT5

Attribute	Description
Name	ATTRIBNARRAT5
Datatype	String
Description	Indicates Attribute Narrative 05
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT6

Attribute	Description
Name	ATTRIBNARRAT6
Datatype	String
Description	Indicates Attribute Narrative 06
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT7

Attribute	Description
Name	ATTRIBNARRAT7
Datatype	String
Description	Indicates Attribute Narrative 07
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT8

Attribute	Description	
Name	ATTRIBNARRAT8	
Datatype	String	
Description	Indicates Attribute Narrative 08	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT9

Attribute	Description	
Name	ATTRIBNARRAT9	
Datatype	String	
Description	Indicates Attribute Narrative 09	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

ATTRIBNARRAT10

Attribute	Description	
Name	ATTRIBNARRAT10	
Datatype	String	
Description	Indicates Attribute Narrative 10	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	pattern	[a-zA-Z0-9]

TOP

MINIRATE

Attribute	Description	
Name	MINIRATE	
Datatype	Number	
Description	Indicates Min Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

MAXIRATE

Attribute	Description
Name	MAXIRATE
Datatype	Number
Description	Indicates Max Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description

Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

VERSNO

Attribute	Description
Name	VERSNO
Datatype	Number
Description	Specifies the Version Number
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [a-zA-Z0-9_%. /]*

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description

Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description	Specifies The Rule.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description

Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description
Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sec-Master

Attribute	Description
Name	Sec-Master
Datatype	
Description	Includes Security Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z0-9]{16}

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	Includes Interest Association details
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** totalDigits: 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RATECODE

Attribute	**Description**	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

RATCODESC

Attribute	**Description**	
Name	RATCODESC	
Datatype	String	
Description	Indicates Rate Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

TENCODE

Attribute	**Description**
Name	TENCODE
Datatype	String
Description	Indicates Tenor Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

TENCODESC

Attribute	**Description**	
Name	TENCODESC	
Datatype	String	
Description	Indicates Tenor Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

INTSPRD

Attribute	**Description**	
Name	INTSPRD	
Datatype	String	
Description	Indicates Interest Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	33
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

INTRATE

Attribute	**Description**
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	**Description**	
Name	FLTAMT	
Datatype	Number	
Description	Indicates Flat Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String
Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND
Datatype	String
Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	Includes Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String
Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PERREV

Attribute	**Description**	
Name	PERREV	
Datatype	String	
Description	Indicates Periodic Revision Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPT

Attribute	**Description**	
Name	CAPT	
Datatype	String	
Description	Indicates Capitalization Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPFREQ

Attribute	**Description**	
Name	COUPFREQ	
Datatype	String	
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFREQ

Attribute	Description
Name	REVFREQ
Datatype	String
Description	Indicates Revision Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	Description
Name	RADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASIS

Attribute	**Description**	
Name	RNDBASIS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,U

TOP

RATEBASIS

Attribute	**Description**	
Name	RATEBASIS	
Datatype	String	
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

CUMINTRAT

Attribute	**Description**	
Name	CUMINTRAT	
Datatype	Number	
Description	Indicates Cumulative Interest Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	8
	totalDigits	13

TOP

ACCRNUMMETH

Attribute	**Description**
Name	ACCRNUMMETH

Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

ACRR366BASS

Attribute	Description
Name	ACRR366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ACCRINCLTODT

Attribute	Description
Name	ACCRINCLTODT
Datatype	String
Description	Indicates Include To Date Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDNUMMETH

Attribute	Description
Name	LIQDNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description
Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

LIQD366BASS

Attribute	Description
Name	LIQD366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWFT

Attribute	Description
Name	DOCSWFT
Datatype	String
Description	Indicates Document Method Swift Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINT

Attribute	Description
Name	ZEROINT
Datatype	String
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	Includes Security Series details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates SERIES
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	Includes Coupon Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COUPSTDT

Attribute	Description
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	Description
Name	COUPTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

COUPENDT

Attribute	Description
Name	COUPENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String
Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched
Datatype	
Description	Includes Revision Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASEFREQ

Attribute	Description
Name	REVBASEFREQ
Datatype	String
Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	Description
Name	REVWEEKDAY
Datatype	String

Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

REVADHMONE

Attribute	Description
Name	REVADHMONE
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	Includes Redemption details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REDEVTDT

Attribute	Description
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	Description
Name	PERREDEM
Datatype	Number
Description	Indicates % To Be Redeemed

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRI

Attribute	Description
Name	REDPRI
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPFRAC

Attribute	Description
Name	DISPFRAC
Datatype	String
Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

CALLINDICAT

Attribute	Description
Name	CALLINDICAT
Datatype	String
Description	Indicates Call Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	30
minLength	0
pattern	[A-Za-z0-9_]*

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	Includes Coupon Period details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

PCD

Attribute	Description
Name	PCD
Datatype	String
Description	Indicates Previous Coupon Date
Restrictions	

Restrictions	Description
maxLength	50

TOP

NCD

Attribute	Description
Name	NCD
Datatype	String
Description	Indicates Next Coupon Date
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

TOP

COUPTYDES

Attribute	Description
Name	COUPTYDES
Datatype	String
Description	Indicates Coupon Period Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	String
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	String
Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	String
Description	Indicates Next Virtual First Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

VIRNEXDT2

Attribute	Description
Name	VIRNEXDT2
Datatype	String
Description	Indicates Next Virtual Second Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Revision-Date-Master

Attribute	Description

Name	Revision-Date-Master
Datatype	
Description	Includes Revision Date Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVTDATE

Attribute	Description
Name	REVTDATE
Datatype	Date
Description	Indicates Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVEFFDATE

Attribute	Description
Name	REVEFFDATE
Datatype	Date
Description	Indicates Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Security-Event-Log

Attribute	Description
Name	Security-Event-Log
Datatype	
Description	Includes Security Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Maker Date Time:
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date TIme:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U For Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	Includes Security Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

2.116.2.SEInstrument-Create-Req-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
SEInstrument-Create-Req
XREF
SECID
PROD
MKTISS
ISSID
SECCCY
PAYCCY
ISSDATE
STINTDATE
STTRADEDATE
REDDATE
INFACEVAL
ISSPRICE
REDPRICE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Creation Of the Instrumnet

TOP

SEInstrument-Create-Req

Attribute	Description
Name	SEInstrument-Create-Req
Datatype	
Description	Creation of Securities Instrument Request Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9_]*

TOP

SECCCY

Attribute	**Description**	
Name	SECCCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

PAYCCY

Attribute	**Description**	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ISSDATE

Attribute	**Description**	
Name	ISSDATE	
Datatype	Date	
Description	Indicates Issue/Tearoff Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STINTDATE

Attribute	**Description**	
Name	STINTDATE	
Datatype	Date	
Description	Indicates Start of Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDATE

Attribute	Description
Name	STTRADEDATE
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.116.3.SEInstrument-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master*
    - *XREF*
    - *SECID*
    - *ISINIDNTFR*
    - *SECDES*
    - *PROD*
    - *PRODDES*
    - *SECRTYP*
    - *SECREFNO*
    - *SECRSTAT*
    - *TRADSTAT*
    - *INTERRAT*
    - *MKTISS*
    - *MKTDES*
    - *ISSID*
    - *ISSDES*
    - *REGBEAR*
    - *FRMTYPE*
    - *QTYQUOT*

INTQUOT
FRACTQUANT
UDECIMAL
EQRED
REN
REDTYPE
REDEMPQUOT
CONFCORPACTION
CALLOPT
PUTOPT
SECCCY
PAYCCY
ISSSIZE
OSISSIZE
MINTRDQT
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
CURENTFV
REDPRICE
ISSSECID
MKTSECID
CNBSECID
REST
VOTRIT
COVERED
CONVBLE
BKACC
ISOCFICODE
ISITCCODE
ATTRBDES
COLLTYPE
DIREXPLINE
QUALRAT
REVPRICODE
PRICDES
MKTREV
COUPBASIS
DIVBASIS
WARRBASIS

RITBASIS
AUTOCORP
PRIQUOT
RATECODE
USBONDFORM
TBILLREINVPER
TBILLANNMETH
TBILLCOUNTNR
TBILLCOUNTDN
BNDREINVPER
BNDANNMETH
BNDDAYCOUNTNR
BNDDAYCOUNTDN
PREMDISCURRPE
DAYS
DAYIN
IDNTINARRAT1
IDNTINARRAT2
IDNTINARRAT3
IDNTINARRAT4
ATTRIBNARRAT1
ATTRIBNARRAT2
ATTRIBNARRAT3
ATTRIBNARRAT4
ATTRIBNARRAT5
ATTRIBNARRAT6
ATTRIBNARRAT7
ATTRIBNARRAT8
ATTRIBNARRAT9
ATTRIBNARRAT10
MINIRATE
MAXIRATE
Mis-Details
- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*

RATECOD
WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Sec-Master
SECID
SECREFNO
Interest-Assoc
CRRATESN
INTCOMP
WAIVER
RATECODE
RATCODESC
TENCODE
TENCODESC
INTSPRD
INTRATE
FLTAMT
ACQAMT
INTCALCMET
QUOTREVIND
QUOTREVSPD
QUOTREVFLR
QUOTREVCEIL

Interest

- *PERCOUP*
- *ALLASYNCREV*
- *PERREV*
- *CAPT*
- *COUPFREQ*
- *ACCVALDATE*
- *COUPWEEK*
- *COUPPLTDATE*
- *CADHMNTHEND*
- *REVFREQ*
- *REVWEEK*
- *RADHMNTHEND*
- *RNDBASIS*
- *RATEBASIS*
- *CUMINTRAT*
- *ACCRNUMMETH*
- *ACCRDENMETH*
- *ACCRDENBASS*
- *ACRR366BASS*
- *ACCRINCLTODT*
- *LIQDNUMMETH*
- *LIQDDENMETH*
- *LIQDDENBASS*
- *LIQD366BASS*
- *ISSSIZE*
- *DOCSWFT*
- *ZEROINT*

Security-Series

- *SERIES*

Coupon-Sched

- *COUPSTDT*
- *COUPTYPE*
- *COUPENDT*
- *BASEFREQ*
- *WEEKDAY*
- *ADHMNTHEND*

Revision-Sched

- *REVSTDT*
- *REVTYPE*
- *REVENDT*
- *REVBASEFREQ*
- *REVWEEKDAY*
- *REVADHMONE*

Redemption
REDEVTDT
PERREDEM
REDPRI
DISPFRAC
CALLINDICAT
REDSERIES
Coupon-Period
PCD
NCD
COUPTYDES
VIRPREVDT2
VIRPREVDT1
VIRNEXDT1
VIRNEXDT2
Revision-Date-Master
REVTDATE
REVEFFDATE
Security-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Security-Hol-Ccy
SECURITYID
HOLCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Creation Of the Instrumnet

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Creation of Securities Instrument Master type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

SECDES

Attribute	Description
Name	SECDES
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRODDES

Attribute	Description
Name	PRODDES
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SECRTYP

Attribute	Description
Name	SECRTYP
Datatype	String
Description	Indicates Security Type Bond : B Equity : E Rights : R Warrant : W Zero Coupon Bond : Z
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SECRSTAT

Attribute	Description
Name	SECRSTAT
Datatype	String
Description	Indicates Security Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TRADSTAT

Attribute	Description	
Name	TRADSTAT	
Datatype	String	
Description	Indicates Trading Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

INTERRAT

Attribute	Description	
Name	INTERRAT	
Datatype	String	
Description	Indicates Interest Type Floating : FLT Fixed : FXD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTISS

Attribute	Description	
Name	MKTISS	
Datatype	String	
Description	Indicates Market Of Issue	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9_]*

TOP

MKTDES

Attribute	Description	
Name	MKTDES	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

ISSDES

Attribute	Description
Name	ISSDES
Datatype	String
Description	Indicates Issuer Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String
Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G

TOP

QTYQUOT

Attribute	**Description**	
Name	QTYQUOT	
Datatype	String	
Description	Indicates Quantity Quotation UNITS : U NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

INTQUOT

Attribute	**Description**	
Name	INTQUOT	
Datatype	String	
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,A,P

TOP

FRACTQUANT

Attribute	**Description**	
Name	FRACTQUANT	
Datatype	String	
Description	Indicates Fractional Quantity Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UDECIMAL

Attribute	**Description**
Name	UDECIMAL

Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description
Name	EQRED
Datatype	String
Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String
Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT

Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description
Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String

Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTRDQT

Attribute	Description
Name	MINTRDQT
Datatype	Number
Description	Indicates Min Trading Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates Lot Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDAT

Attribute	Description
Name	STTRADEDAT
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURENTFV

Attribute	Description
Name	CURENTFV
Datatype	Number
Description	Indicates Current Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISSSECID

Attribute	Description
Name	ISSSECID
Datatype	String
Description	Indicates Issuer Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

MKTSECID

Attribute	Description
Name	MKTSECID
Datatype	String
Description	Indicates Market Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

CNBSECID

Attribute	Description
Name	CNBSECID
Datatype	String
Description	Indicates Central Bank Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

REST

Attribute	Description
Name	REST
Datatype	String
Description	Indicates Restricted Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VOTRIT

Attribute	Description
Name	VOTRIT
Datatype	String
Description	Indicates Voting Rights Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVERED

Attribute	**Description**	
Name	COVERED	
Datatype	String	
Description	Indicates Covered Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVBLE

Attribute	**Description**	
Name	CONVBLE	
Datatype	String	
Description	Indicates Convertible Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BKACC

Attribute	**Description**	
Name	BKACC	
Datatype	String	
Description	Indicates Bankers Accept Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICODE

Attribute	**Description**
Name	ISOCFICODE
Datatype	String

Description	Indicates ISO CFI Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	Description
Name	ISITCCODE
Datatype	String
Description	Indicates ISITC Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ATTRBDES

Attribute	Description
Name	ATTRBDES
Datatype	String
Description	Indicates Attribute Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description
Name	DIREXPLINE
Datatype	String
Description	Indicates Direct Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description
Name	QUALRAT
Datatype	String
Description	Indicates Quality Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0 pattern / [A-Za-z0-9]*

TOP

REVPRICODE

Attribute	Description
Name	REVPRICODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

PRICDES

Attribute	Description
Name	PRICDES
Datatype	String
Description	Indicates Price Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String
Description	Indicates Warrant Basis POSITION : P HOLDINGS : H

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

RITBASIS

Attribute	Description
Name	RITBASIS
Datatype	String
Description	Indicates Rights Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

AUTOCORP

Attribute	Description
Name	AUTOCORP
Datatype	String
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIQUOT

Attribute	Description
Name	PRIQUOT
Datatype	String
Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRE,PPD,YTM

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

USBONDFORM

Attribute	Description
Name	USBONDFORM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	S,C

TOP

TBILLCOUNTNR

Attribute	Description	
Name	TBILLCOUNTNR	
Datatype	String	
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U

TOP

TBILLCOUNTDN

Attribute	Description	
Name	TBILLCOUNTDN	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H

TOP

BNDREINVPER

Attribute	Description	
Name	BNDREINVPER	
Datatype	String	
Description	Indicates Reinv. Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	0
	pattern	[0-9]*

TOP

BNDANNMETH

Attribute	Description
Name	BNDANNMETH
Datatype	String

Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNDDAYCOUNTNR

Attribute	Description
Name	BNDDAYCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description
Name	BNDDAYCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

PREMDISCURRPE

Attribute	Description
Name	PREMDISCURRPE
Datatype	String
Description	Indicates Premium/Discount For Current Interest Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	Indicates No of Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIN

Attribute	Description
Name	DAYIN
Datatype	String
Description	Indicates Days Before Start of Next Coupon Period : B After Start of Previous Coupon Period : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IDNTINARRAT1

Attribute	Description
Name	IDNTINARRAT1
Datatype	String
Description	Indicates Identification Narrative 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT2

Attribute	Description
Name	IDNTINARRAT2
Datatype	String
Description	Indicates Identification Narrative 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT3

Attribute	Description
Name	IDNTINARRAT3
Datatype	String
Description	Indicates Identification Narrative 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT4

Attribute	Description
Name	IDNTINARRAT4
Datatype	String
Description	Indicates Identification Narrative 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT1

Attribute	Description
Name	ATTRIBNARRAT1
Datatype	String
Description	Indicates Attribute Narrative 01
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT2

Attribute	Description
Name	ATTRIBNARRAT2
Datatype	String
Description	Indicates Attribute Narrative 02
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT3

Attribute	Description
Name	ATTRIBNARRAT3
Datatype	String
Description	Indicates Attribute Narrative 03
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT4

Attribute	Description
Name	ATTRIBNARRAT4
Datatype	String
Description	Indicates Attribute Narrative 04
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT5

Attribute	Description
Name	ATTRIBNARRAT5
Datatype	String
Description	Indicates Attribute Narrative 05
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT6

Attribute	Description
Name	ATTRIBNARRAT6
Datatype	String
Description	Indicates Attribute Narrative 06
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT7

Attribute	Description
Name	ATTRIBNARRAT7
Datatype	String
Description	Indicates Attribute Narrative 07
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT8

Attribute	Description
Name	ATTRIBNARRAT8
Datatype	String
Description	Indicates Attribute Narrative 08
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT9

Attribute	Description
Name	ATTRIBNARRAT9
Datatype	String
Description	Indicates Attribute Narrative 09
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT10

Attribute	Description
Name	ATTRIBNARRAT10
Datatype	String
Description	Indicates Attribute Narrative 10
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

MINIRATE

Attribute	Description
Name	MINIRATE
Datatype	Number
Description	Indicates Min Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXIRATE

Attribute	Description
Name	MAXIRATE
Datatype	Number
Description	Indicates Max Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Tax-Master

Attribute	**Description**	
Name	Tax-Master	
Datatype		
Description	Includes Tax Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FNDREFNO

Attribute	**Description**	
Name	FNDREFNO	
Datatype	String	
Description	Indicates the Fund Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSNO

Attribute	**Description**	
Name	VERSNO	
Datatype	Number	
Description	Specifies the Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RATECOD

Attribute	Description	
Name	RATECOD	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Tran-Tax-Liqd-Master

Attribute	Description

Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sec-Master

Attribute	**Description**	
Name	Sec-Master	
Datatype		
Description	Includes Security Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Indicates Security ID	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	**Description**	
Name	SECREFNO	
Datatype	String	
Description	Indicates Security Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Interest-Assoc

Attribute	**Description**	
Name	Interest-Assoc	
Datatype		
Description	Includes Interest Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

RATCODESC

Attribute	Description
Name	RATCODESC
Datatype	String
Description	Indicates Rate Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

TENCODE

Attribute	Description
Name	TENCODE
Datatype	String
Description	Indicates Tenor Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

TENCODESC

Attribute	Description
Name	TENCODESC
Datatype	String
Description	Indicates Tenor Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 33; minLength / 0; pattern / [A-Za-z0-9_]*

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	Description
Name	FLTAMT
Datatype	Number
Description	Indicates Flat Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String
Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND
Datatype	String

Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String

Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PERREV

Attribute	Description
Name	PERREV
Datatype	String
Description	Indicates Periodic Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPT

Attribute	Description
Name	CAPT
Datatype	String
Description	Indicates Capitalization Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPFREQ

Attribute	Description

Name	COUPFREQ
Datatype	String
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFREQ

Attribute	Description
Name	REVFREQ
Datatype	String
Description	Indicates Revision Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	**Description**	
Name	RADHMNTHEND	
Datatype	String	
Description	Indicates Adhere To Month End Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASIS

Attribute	**Description**	
Name	RNDBASIS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,U

TOP

RATEBASIS

Attribute	**Description**	
Name	RATEBASIS	
Datatype	String	
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

CUMINTRAT

Attribute	**Description**
Name	CUMINTRAT

Datatype	Number
Description	Indicates Cumulative Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

ACCRNUMMETH

Attribute	Description
Name	ACCRNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

ACRR366BASS

Attribute	Description
Name	ACRR366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ACCRINCLTODT

Attribute	Description
Name	ACCRINCLTODT
Datatype	String
Description	Indicates Include To Date Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDNUMMETH

Attribute	Description
Name	LIQDNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description

Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

LIQD366BASS

Attribute	Description
Name	LIQD366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWFT

Attribute	Description
Name	DOCSWFT
Datatype	String
Description	Indicates Document Method Swift Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINT

Attribute	Description
Name	ZEROINT
Datatype	String
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	Includes Security Series details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates SERIES
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	Includes Coupon Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COUPSTDT

Attribute	Description
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	Description
Name	COUPTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,C</td></tr></table>

TOP

COUPENDT

Attribute	Description
Name	COUPENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched

Datatype	
Description	Includes Revision Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASEFREQ

Attribute	Description
Name	REVBASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	Description
Name	REVWEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

REVADHMONE

Attribute	Description
Name	REVADHMONE
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption

Datatype	
Description	Includes Redemption details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REDEVTDT

Attribute	Description
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	Description
Name	PERREDEM
Datatype	Number
Description	Indicates % To Be Redeemed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRI

Attribute	Description
Name	REDPRI
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPFRAC

Attribute	Description
Name	DISPFRAC
Datatype	String
Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

CALLINDICAT

Attribute	Description
Name	CALLINDICAT
Datatype	String
Description	Indicates Call Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	Includes Coupon Period details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PCD

Attribute	Description
Name	PCD
Datatype	String
Description	Indicates Previous Coupon Date
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NCD

Attribute	Description
Name	NCD

Datatype	String
Description	Indicates Next Coupon Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COUPTYDES

Attribute	Description
Name	COUPTYDES
Datatype	String
Description	Indicates Coupon Period Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	String
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	String
Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	String
Description	Indicates Next Virtual First Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

VIRNEXDT2

Attribute	**Description**	
Name	VIRNEXDT2	
Datatype	String	
Description	Indicates Next Virtual Second Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Revision-Date-Master

Attribute	**Description**	
Name	Revision-Date-Master	
Datatype		
Description	Includes Revision Date Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REVTDATE

Attribute	**Description**	
Name	REVTDATE	
Datatype	Date	
Description	Indicates Event Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVEFFDATE

Attribute	**Description**	
Name	REVEFFDATE	
Datatype	Date	
Description	Indicates Effective Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Security-Event-Log

Attribute	**Description**

Name	Security-Event-Log
Datatype	
Description	Includes Security Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date TIme:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U For Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	Includes Security Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.116.4.SEInstrument-Create-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *SEInstrument-Create-Res*
      - *XREF*
      - *SECREFNO*
      - *SECID*
      - *PROD*
      - *MKTISS*
      - *ISSID*
      - *SECCCY*
      - *PAYCCY*
      - *ISSDATE*
      - *STINTDATE*
      - *STTRADEDATE*
      - *INFACEVAL*
    - *SEInstrument-Create-Req*
      - *XREF*
      - *SECID*
      - *PROD*
      - *MKTISS*

ISSID
SECCCY
PAYCCY
ISSDATE
STINTDATE
STTRADEDATE
REDDATE
INFACEVAL
ISSPRICE
REDPRICE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	**Description**	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Creation Of the Instrumnet

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

SEInstrument-Create-Res

Attribute	Description
Name	SEInstrument-Create-Res
Datatype	
Description	Creation of Securities Instrument Response Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength: 16 minLength: 0 pattern: [a-zA-Z0-9_%. /]*

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length: 4 pattern: [a-zA-Z0-9]{4}

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 16 pattern: [a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDATE

Attribute	Description
Name	STTRADEDATE
Datatype	Date
Description	Indicates Start of Trading Date

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEInstrument-Create-Req

Attribute	Description
Name	SEInstrument-Create-Req
Datatype	
Description	Creation of Securities Instrument Request Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code

Restrictions	**Restrictions**	**Description**
	length	4
	pattern	[a-zA-Z0-9]{4}

TOP

MKTISS

Attribute	Description	
Name	MKTISS	
Datatype	String	
Description	Indicates Market Of Issue	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description	
Name	ISSID	
Datatype	String	
Description	Indicates Issuer ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description	
Name	SECCCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></table>

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTRADEDATE

Attribute	Description
Name	STTRADEDATE
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Type
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning response Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.117.ModifySEInstrument

Modification of Securities Instrument

2.117.1.SEInstrument-Modify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Modify-Req-Full*
    - *XREF*
    - *SECID*
    - *ISINIDNTFR*
    - *PROD*
    - *MKTISS*
    - *ISSID*
    - *REGBEAR*
    - *FRMTYPE*
    - *QTYQUOT*
    - *PRIQUOT*
    - *INTQUOT*
    - *FRACTQUANT*
    - *DECIMAL*
    - *EQRED*
    - *REN*

CALLOPT
PUTOPT
SECCCY
PAYCCY
REDTYPE
REDEMPQUOT
CONFCORPACTION
ISSSIZE
OSISSIZE
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
REDPRICE
ISSSECID
MKTSECID
CNBSECID
ISOCFICODE
ISITCCODE
COLLTYPE
DIREXPLINE
REVPRICODE
MKTREV
QUALRAT
COUPBASIS
DIVBASIS
WARRBASIS
RITBASIS
AUTOCORP
REST
VOTRIT
CONVBLE
BKACC
ACCDISTYPE
RATECODE
BNDANNMETH
BNDREINVPER
BNDDAYCOUNTNR
BNDDAYCOUNTDN
TBILLREINVPER
TBILLANNMETH

TBILLCOUNTNR
TBILLCOUNTDN
CAPT
ACCVALDATE
COUPPLTDATE
SECSERIES
  SERIES
SECINTRST
  PERCOUP
  ALLASYNCREV
  PERREV
  COUPFREQ
  COUPWEEK
  CADHMNTHEND
  REVWEEK
  RADHMNTHEND
  RNDBASIS
  RATEBASIS
  ACCRNUMMETH
  ACCRDENMETH
  ACCRDENBASS
  ACRR366BASS
  ACCRINCLTODT
  LIQDNUMMETH
  LIQDDENMETH
  LIQDDENBASS
  LIQD366BASS
  LIQDINCLTODT
  ZEROINT
  HOLMAINT
    HOLCCY
SECCOUPON
  COUPSTDT
  COUPTYPE
  COUPENDT
  BASEFREQ
  WEEKDAY
  ADHMNTHEND
SECCOUPONPER
  PCD
  NCD
  VIRPREVDT2
  VIRPREVDT1
  VIRNEXDT2

- *VIRNEXDT1*

SECREVISION

- *REVSTDT*
- *REVTYPE*
- *REVENDT*
- *REVBASEFREQ*
- *REVWEEKDAY*

SECREVISIONPER

- *REVTDATE*
- *REVEFFDATE*

SECREDEM

- *REDEVTDT*
- *PERREDEM*
- *REDPRI*
- *DISPFRAC*
- *REDSERIES*

SECINT

- *INTCOMP*
- *WAIVER*
- *RATECODE*
- *TENCODE*
- *INTSPRD*
- *INTRATE*
- *FLTAMT*
- *ACQAMT*
- *INTCALCMET*
- *QUOTREVIND*
- *QUOTREVSPD*
- *QUOTREVFLR*
- *QUOTREVCEIL*

INSTRMIS

- *MISGRP*
- *RTFLAG*
- *LINKGRP*
- *POOLCD*
- *REFRTCD*
- *REFRTSPRD*
- *REFRTTYPE*
- *CALCMETH*
- *TXNMIS1*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
INSTRUDF
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Modification Of the Instrumnet

TOP

SEInstrument-Modify-Req-Full

Attribute	Description
Name	SEInstrument-Modify-Req-Full
Datatype	
Description	Includes Securities Instrument Modification Request Full type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9_]*</td></tr></table>

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String
Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

QTYQUOT

Attribute	Description
Name	QTYQUOT
Datatype	String
Description	Indicates Quantity Quotation UNITS : U NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRIQUOT

Attribute	Description
Name	PRIQUOT
Datatype	String

Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRE,PPD,YTM

TOP

INTQUOT

Attribute	Description
Name	INTQUOT
Datatype	String
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,A

TOP

FRACTQUANT

Attribute	Description
Name	FRACTQUANT
Datatype	String
Description	Indicates Fractional Quantity Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DECIMAL

Attribute	Description
Name	DECIMAL
Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description

Name	EQRED
Datatype	String
Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String
Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT
Datatype	String
Description	Indicates Redemption Quotation Percentage P Factor F Cash Flow C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description
Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action Yes Y No N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates Lot Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE

Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDAT

Attribute	Description
Name	STTRADEDAT
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REDPRICE

Attribute	**Description**	
Name	REDPRICE	
Datatype	Number	
Description	Indicates Redemption Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSSECID

Attribute	**Description**	
Name	ISSSECID	
Datatype	String	
Description	Indicates Issuer Security ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

MKTSECID

Attribute	**Description**	
Name	MKTSECID	
Datatype	String	
Description	Indicates Market Security ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

CNBSECID

Attribute	**Description**	
Name	CNBSECID	
Datatype	String	
Description	Indicates Central Bank Security ID	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ISOCFICODE

Attribute	Description
Name	ISOCFICODE
Datatype	String
Description	Indicates ISO CFI Code
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	6
minLength	0
pattern	[A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	Description
Name	ISITCCODE
Datatype	String
Description	Indicates ISITC Code
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	6
minLength	0
pattern	[A-Za-z0-9_]*

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30
minLength	0
pattern	[A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description
Name	DIREXPLINE

Datatype	String
Description	Indicates Direct Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

REVPRICODE

Attribute	Description
Name	REVPRICODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description
Name	QUALRAT
Datatype	String
Description	Indicates Quality Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0 pattern / [A-Za-z0-9]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String
Description	Indicates Warrant Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

RITBASIS

Attribute	Description
Name	RITBASIS
Datatype	String
Description	Indicates Rights Basis POSITION : P HOLDINGS : H

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H

TOP

AUTOCORP

Attribute	**Description**	
Name	AUTOCORP	
Datatype	String	
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REST

Attribute	**Description**	
Name	REST	
Datatype	String	
Description	Indicates Restricted Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VOTRIT

Attribute	**Description**	
Name	VOTRIT	
Datatype	String	
Description	Indicates Voting Rights Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVBLE

Attribute	**Description**
Name	CONVBLE
Datatype	String

Description	Indicates Convertible Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BKACC

Attribute	Description
Name	BKACC
Datatype	String
Description	Indicates Bankers Accept Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCDISTYPE

Attribute	Description
Name	ACCDISTYPE
Datatype	String
Description	Indicates T Bill Tax Accrual on Discount Advance : E Arrears : A N/A : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,A,N

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

BNDANNMETH

Attribute	Description
Name	BNDANNMETH
Datatype	Number
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNDREINVPER

Attribute	Description
Name	BNDREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

BNDDAYCOUNTNR

Attribute	Description
Name	BNDDAYCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description
Name	BNDDAYCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C

TOP

TBILLCOUNTNR

Attribute	Description
Name	TBILLCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

TBILLCOUNTDN

Attribute	Description
Name	TBILLCOUNTDN
Datatype	String

Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

CAPT

Attribute	Description
Name	CAPT
Datatype	String
Description	Indicates Capitalization Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B

TOP

SECSERIES

Attribute	Description
Name	SECSERIES
Datatype	
Description	Includes Security Series details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates SERIES
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

SECINTRST

Attribute	Description
Name	SECINTRST
Datatype	
Description	Includes Securities Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String
Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PERREV

Attribute	Description
Name	PERREV
Datatype	String
Description	Indicates Periodic Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPFREQ

Attribute	Description
Name	COUPFREQ
Datatype	String
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	Description
Name	RADHMNTHEND

Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDBASIS

Attribute	Description
Name	RNDBASIS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

RATEBASIS

Attribute	Description
Name	RATEBASIS
Datatype	String
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

ACCRNUMMETH

Attribute	Description
Name	ACCRNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

ACRR366BASS

Attribute	Description
Name	ACRR366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ACCRINCLTODT

Attribute	Description
Name	ACCRINCLTODT

Datatype	String
Description	Indicates Include To Date Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDNUMMETH

Attribute	Description
Name	LIQDNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description
Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

LIQD366BASS

Attribute	Description	
Name	LIQD366BASS	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

LIQDINCLTODT

Attribute	Description	
Name	LIQDINCLTODT	
Datatype	String	
Description	Indicates Liquidated Discount Include To Date Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ZEROINT

Attribute	Description	
Name	ZEROINT	
Datatype	String	
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOLMAINT

Attribute	Description
Name	HOLMAINT
Datatype	
Description	Includes Holiday Maintenance details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

SECCOUPON

Attribute	Description
Name	SECCOUPON
Datatype	
Description	Includes Security Coupon details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COUPSTDT

Attribute	Description
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	Description
Name	COUPTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

COUPENDT

Attribute	Description
Name	COUPENDT

Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String
Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String

Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCOUPONPER

Attribute	Description
Name	SECCOUPONPER
Datatype	
Description	Includes Security Coupon per details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PCD

Attribute	Description
Name	PCD
Datatype	Date
Description	Indicates Previous Coupon Date

TOP

NCD

Attribute	Description
Name	NCD
Datatype	Date
Description	Indicates Next Coupon Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	Date
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	Date

Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VIRNEXDT2

Attribute	Description
Name	VIRNEXDT2
Datatype	Date
Description	Indicates Next Virtual Second Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	Date
Description	Indicates Next Virtual First Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECREVISION

Attribute	Description
Name	SECREVISION
Datatype	
Description	Includes Security Revision details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASEFREQ

Attribute	Description
Name	REVBASEFREQ
Datatype	String
Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	Description
Name	REVWEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

SECREVISIONPER

Attribute	Description
Name	SECREVISIONPER
Datatype	
Description	Includes Security Revision Period details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVTDATE

Attribute	Description
Name	REVTDATE
Datatype	Date
Description	Indicates Event Date

TOP

REVEFFDATE

Attribute	Description
Name	REVEFFDATE
Datatype	Date
Description	Indicates Effective Date

TOP

SECREDEM

Attribute	Description
Name	SECREDEM
Datatype	
Description	Includes Security Redemption details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REDEVTDT

Attribute	Description
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	Description

Name	PERREDEM
Datatype	Number
Description	Indicates % To Be Redeemed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRI

Attribute	Description
Name	REDPRI
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPFRAC

Attribute	Description
Name	DISPFRAC
Datatype	String
Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

SECINT

Attribute	Description
Name	SECINT
Datatype	
Description	Includes Security Interest details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Indicates Interest Component

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

TENCODE

Attribute	Description	
Name	TENCODE	
Datatype	String	
Description	Indicates Tenor Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 33 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	Description
Name	FLTAMT
Datatype	Number
Description	Indicates Flat Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String

Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND
Datatype	String
Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRMIS

Attribute	Description
Name	INSTRMIS
Datatype	
Description	Includes Instrument MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates the MIS Group to which the instrument is linked
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the instrument
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates the Link Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Pool code element. This can be of type string
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates Interest Calculation Method
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	This is the transaction MIS 1 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	This is the transaction MIS 2 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	This is the transaction MIS 3 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	This is the transaction MIS 4 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	This is the transaction MIS 5 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	This is the transaction MIS 6 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	This is the transaction MIS 7 element
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	This is the transaction MIS 8 element
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	This is the transaction MIS 9 element
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	This is the transaction MIS 10 element
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	This is the component MIS 1 element.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	This is the component MIS 2 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	This is the component MIS 3 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	This is the component MIS 4 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	This is the component MIS 5 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	This is the component MIS 6 element.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	This is the component MIS 7 element.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	This is the component MIS 8 element.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	This is the component MIS 9 element.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	This is the component MIS 10 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	This is the cost code 1 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	This is the cost code 2 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	This is the cost code 3 element.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	This is the cost code 4 element.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	This is the cost code 5 element.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

INSTRUDF

Attribute	Description	
Name	INSTRUDF	
Datatype		
Description	Includes Instrument User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

2.117.2.SEInstrument-Modify-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Modify-Req*
    - *XREF*
    - *SECID*
    - *PROD*
    - *MKTISS*
    - *ISSID*
    - *SECCCY*
    - *PAYCCY*
    - *ISSDATE*
    - *STINTDATE*
    - *STTRADEDATE*
    - *INFACEVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Modification Of the Instrumnet

TOP

SEInstrument-Modify-Req

Attribute	Description
Name	SEInstrument-Modify-Req
Datatype	
Description	Includes Securities Instrument Modification Request type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_]*

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 pattern: [a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** length: 3 pattern: [A-Z]{3}

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

STTRADEDATE

Attribute	Description
Name	STTRADEDATE
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.117.3.SEInstrument-Modify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master*
    - *XREF*
    - *SECID*
    - *ISINIDNTFR*
    - *SECDES*
    - *PROD*
    - *PRODDES*
    - *SECRTYP*
    - *SECREFNO*
    - *SECRSTAT*
    - *TRADSTAT*
    - *INTERRAT*
    - *MKTISS*
    - *MKTDES*
    - *ISSID*
    - *ISSDES*
    - *REGBEAR*
    - *FRMTYPE*
    - *QTYQUOT*

INTQUOT
FRACTQUANT
UDECIMAL
EQRED
REN
REDTYPE
REDEMPQUOT
CONFCORPACTION
CALLOPT
PUTOPT
SECCCY
PAYCCY
ISSSIZE
OSISSIZE
MINTRDQT
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
CURENTFV
REDPRICE
ISSSECID
MKTSECID
CNBSECID
REST
VOTRIT
COVERED
CONVBLE
BKACC
ISOCFICODE
ISITCCODE
ATTRBDES
COLLTYPE
DIREXPLINE
QUALRAT
REVPRICODE
PRICDES
MKTREV
COUPBASIS
DIVBASIS
WARRBASIS

RITBASIS
AUTOCORP
PRIQUOT
RATECODE
USBONDFORM
TBILLREINVPER
TBILLANNMETH
TBILLCOUNTNR
TBILLCOUNTDN
BNDREINVPER
BNDANNMETH
BNDDAYCOUNTNR
BNDDAYCOUNTDN
PREMDISCURRPE
DAYS
DAYIN
IDNTINARRAT1
IDNTINARRAT2
IDNTINARRAT3
IDNTINARRAT4
ATTRIBNARRAT1
ATTRIBNARRAT2
ATTRIBNARRAT3
ATTRIBNARRAT4
ATTRIBNARRAT5
ATTRIBNARRAT6
ATTRIBNARRAT7
ATTRIBNARRAT8
ATTRIBNARRAT9
ATTRIBNARRAT10
MINIRATE
MAXIRATE
Mis-Details
- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Tax-Master
FNDREFNO
VERSNO
SECID
TXTREF
SECREF
Issr-Tax-Assoc
CRRATESN
INTCOMP

RATECOD
WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Sec-Master
SECID
SECREFNO
Interest-Assoc
CRRATESN
INTCOMP
WAIVER
RATECODE
RATCODESC
TENCODE
TENCODESC
INTSPRD
INTRATE
FLTAMT
ACQAMT
INTCALCMET
QUOTREVIND
QUOTREVSPD
QUOTREVFLR
QUOTREVCEIL

Interest

- *PERCOUP*
- *ALLASYNCREV*
- *PERREV*
- *CAPT*
- *COUPFREQ*
- *ACCVALDATE*
- *COUPWEEK*
- *COUPPLTDATE*
- *CADHMNTHEND*
- *REVFREQ*
- *REVWEEK*
- *RADHMNTHEND*
- *RNDBASIS*
- *RATEBASIS*
- *CUMINTRAT*
- *ACCRNUMMETH*
- *ACCRDENMETH*
- *ACCRDENBASS*
- *ACRR366BASS*
- *ACCRINCLTODT*
- *LIQDNUMMETH*
- *LIQDDENMETH*
- *LIQDDENBASS*
- *LIQD366BASS*
- *ISSSIZE*
- *DOCSWFT*
- *ZEROINT*

Security-Series

- *SERIES*

Coupon-Sched

- *COUPSTDT*
- *COUPTYPE*
- *COUPENDT*
- *BASEFREQ*
- *WEEKDAY*
- *ADHMNTHEND*

Revision-Sched

- *REVSTDT*
- *REVTYPE*
- *REVENDT*
- *REVBASEFREQ*
- *REVWEEKDAY*
- *REVADHMONE*

Redemption
REDEVTDT
PERREDEM
REDPRI
DISPFRAC
CALLINDICAT
REDSERIES
Coupon-Period
PCD
NCD
COUPTYDES
VIRPREVDT2
VIRPREVDT1
VIRNEXDT1
VIRNEXDT2
Revision-Date-Master
REVTDATE
REVEFFDATE
Security-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Security-Hol-Ccy
SECURITYID
HOLCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Modification Of the Instrumnet

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Includes Securities Instrument Modification Master type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

SECDES

Attribute	Description
Name	SECDES
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRODDES

Attribute	Description
Name	PRODDES
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SECRTYP

Attribute	Description
Name	SECRTYP
Datatype	String
Description	Indicates Security Type Bond : B Equity : E Rights : R Warrant : W Zero Coupon Bond : Z
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SECRSTAT

Attribute	Description
Name	SECRSTAT
Datatype	String
Description	Indicates Security Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TRADSTAT

Attribute	Description	
Name	TRADSTAT	
Datatype	String	
Description	Indicates Trading Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

INTERRAT

Attribute	Description	
Name	INTERRAT	
Datatype	String	
Description	Indicates Interest Type Floating : FLT Fixed : FXD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MKTISS

Attribute	Description	
Name	MKTISS	
Datatype	String	
Description	Indicates Market Of Issue	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9_]*

TOP

MKTDES

Attribute	Description	
Name	MKTDES	
Datatype	String	
Description	Indicates Market Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

ISSDES

Attribute	Description
Name	ISSDES
Datatype	String
Description	Indicates Issuer Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String
Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G

TOP

QTYQUOT

Attribute	**Description**	
Name	QTYQUOT	
Datatype	String	
Description	Indicates Quantity Quotation UNITS : U NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

INTQUOT

Attribute	**Description**	
Name	INTQUOT	
Datatype	String	
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,A,P

TOP

FRACTQUANT

Attribute	**Description**	
Name	FRACTQUANT	
Datatype	String	
Description	Indicates Fractional Quantity Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UDECIMAL

Attribute	**Description**
Name	UDECIMAL

Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description
Name	EQRED
Datatype	String
Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String
Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT

Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description
Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String

Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTRDQT

Attribute	Description
Name	MINTRDQT
Datatype	Number
Description	Indicates Min Trading Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates Lot Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDAT

Attribute	Description
Name	STTRADEDAT
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURENTFV

Attribute	Description
Name	CURENTFV
Datatype	Number
Description	Indicates Current Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISSSECID

Attribute	Description
Name	ISSSECID
Datatype	String
Description	Indicates Issuer Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[A-Za-z0-9_]*</td></tr></table>

TOP

MKTSECID

Attribute	Description
Name	MKTSECID
Datatype	String
Description	Indicates Market Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

CNBSECID

Attribute	Description
Name	CNBSECID
Datatype	String
Description	Indicates Central Bank Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

REST

Attribute	Description
Name	REST
Datatype	String
Description	Indicates Restricted Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VOTRIT

Attribute	Description
Name	VOTRIT
Datatype	String
Description	Indicates Voting Rights Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVERED

Attribute	**Description**	
Name	COVERED	
Datatype	String	
Description	Indicates Covered Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVBLE

Attribute	**Description**	
Name	CONVBLE	
Datatype	String	
Description	Indicates Convertible Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BKACC

Attribute	**Description**	
Name	BKACC	
Datatype	String	
Description	Indicates Bankers Accept Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICODE

Attribute	**Description**
Name	ISOCFICODE
Datatype	String

Description	Indicates ISO CFI Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	Description
Name	ISITCCODE
Datatype	String
Description	Indicates ISITC Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ATTRBDES

Attribute	Description
Name	ATTRBDES
Datatype	String
Description	Indicates Attribute Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description
Name	DIREXPLINE
Datatype	String
Description	Indicates Direct Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description
Name	QUALRAT
Datatype	String
Description	Indicates Quality Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0 pattern / [A-Za-z0-9]*

TOP

REVPRICODE

Attribute	Description
Name	REVPRICODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

PRICDES

Attribute	Description
Name	PRICDES
Datatype	String
Description	Indicates Price Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String
Description	Indicates Warrant Basis POSITION : P HOLDINGS : H

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H

TOP

RITBASIS

Attribute	**Description**	
Name	RITBASIS	
Datatype	String	
Description	Indicates Rights Basis POSITION : P HOLDINGS : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H

TOP

AUTOCORP

Attribute	**Description**	
Name	AUTOCORP	
Datatype	String	
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIQUOT

Attribute	**Description**	
Name	PRIQUOT	
Datatype	String	
Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PPR,PRE,PPD,YTM

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

USBONDFORM

Attribute	Description
Name	USBONDFORM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	S,C

TOP

TBILLCOUNTNR

Attribute	Description	
Name	TBILLCOUNTNR	
Datatype	String	
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U

TOP

TBILLCOUNTDN

Attribute	Description	
Name	TBILLCOUNTDN	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H

TOP

BNDREINVPER

Attribute	Description	
Name	BNDREINVPER	
Datatype	String	
Description	Indicates Reinv. Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	0
	pattern	[0-9]*

TOP

BNDANNMETH

Attribute	Description
Name	BNDANNMETH
Datatype	String

Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNDDAYCOUNTNR

Attribute	Description
Name	BNDDAYCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description
Name	BNDDAYCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

PREMDISCURRPE

Attribute	Description
Name	PREMDISCURRPE
Datatype	String
Description	Indicates Premium/Discount For Current Interest Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	Indicates No of Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIN

Attribute	Description
Name	DAYIN
Datatype	String
Description	Indicates Days Before Start of Next Coupon Period : B After Start of Previous Coupon Period : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IDNTINARRAT1

Attribute	Description
Name	IDNTINARRAT1
Datatype	String
Description	Indicates Identification Narrative 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT2

Attribute	Description
Name	IDNTINARRAT2
Datatype	String
Description	Indicates Identification Narrative 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT3

Attribute	Description
Name	IDNTINARRAT3
Datatype	String
Description	Indicates Identification Narrative 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT4

Attribute	Description
Name	IDNTINARRAT4
Datatype	String
Description	Indicates Identification Narrative 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT1

Attribute	Description
Name	ATTRIBNARRAT1
Datatype	String
Description	Indicates Attribute Narrative 01
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT2

Attribute	Description
Name	ATTRIBNARRAT2
Datatype	String
Description	Indicates Attribute Narrative 02
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT3

Attribute	Description
Name	ATTRIBNARRAT3
Datatype	String
Description	Indicates Attribute Narrative 03
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT4

Attribute	Description
Name	ATTRIBNARRAT4
Datatype	String
Description	Indicates Attribute Narrative 04
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT5

Attribute	Description
Name	ATTRIBNARRAT5
Datatype	String
Description	Indicates Attribute Narrative 05
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT6

Attribute	Description
Name	ATTRIBNARRAT6
Datatype	String
Description	Indicates Attribute Narrative 06
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT7

Attribute	Description
Name	ATTRIBNARRAT7
Datatype	String
Description	Indicates Attribute Narrative 07
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT8

Attribute	Description
Name	ATTRIBNARRAT8
Datatype	String
Description	Indicates Attribute Narrative 08
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT9

Attribute	Description
Name	ATTRIBNARRAT9
Datatype	String
Description	Indicates Attribute Narrative 09
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT10

Attribute	Description
Name	ATTRIBNARRAT10
Datatype	String
Description	Indicates Attribute Narrative 10
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

MINIRATE

Attribute	Description
Name	MINIRATE
Datatype	Number
Description	Indicates Min Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXIRATE

Attribute	Description
Name	MAXIRATE
Datatype	Number
Description	Indicates Max Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Tax-Master

Attribute	**Description**	
Name	Tax-Master	
Datatype		
Description	Includes Tax Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FNDREFNO

Attribute	**Description**	
Name	FNDREFNO	
Datatype	String	
Description	Indicates the Fund Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSNO

Attribute	**Description**	
Name	VERSNO	
Datatype	Number	
Description	Specifies the Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SECID

Attribute	Description	
Name	SECID	
Datatype	String	
Description	Indicates Security ID	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[a-zA-Z0-9_%. /]*

TOP

TXTREF

Attribute	Description	
Name	TXTREF	
Datatype	String	
Description	Specifies the transaction reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECREF

Attribute	Description	
Name	SECREF	
Datatype	String	
Description	Specifies The Security Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Issr-Tax-Assoc

Attribute	Description	
Name	Issr-Tax-Assoc	
Datatype		
Description	Specifies The Details Of issuer Tax.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RATECOD

Attribute	Description	
Name	RATECOD	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description

Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sec-Master

Attribute	**Description**	
Name	Sec-Master	
Datatype		
Description	Includes Security Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Indicates Security ID	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	**Description**	
Name	SECREFNO	
Datatype	String	
Description	Indicates Security Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Interest-Assoc

Attribute	**Description**	
Name	Interest-Assoc	
Datatype		
Description	Includes Interest Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

RATCODESC

Attribute	Description
Name	RATCODESC
Datatype	String
Description	Indicates Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TENCODE

Attribute	Description
Name	TENCODE
Datatype	String
Description	Indicates Tenor Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

TENCODESC

Attribute	Description
Name	TENCODESC
Datatype	String
Description	Indicates Tenor Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 33 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	Description
Name	FLTAMT
Datatype	Number
Description	Indicates Flat Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String
Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND
Datatype	String

Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String

Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PERREV

Attribute	Description
Name	PERREV
Datatype	String
Description	Indicates Periodic Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPT

Attribute	Description
Name	CAPT
Datatype	String
Description	Indicates Capitalization Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPFREQ

Attribute	Description

Name	COUPFREQ
Datatype	String
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFREQ

Attribute	Description
Name	REVFREQ
Datatype	String
Description	Indicates Revision Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	**Description**	
Name	RADHMNTHEND	
Datatype	String	
Description	Indicates Adhere To Month End Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASIS

Attribute	**Description**	
Name	RNDBASIS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,U

TOP

RATEBASIS

Attribute	**Description**	
Name	RATEBASIS	
Datatype	String	
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

CUMINTRAT

Attribute	**Description**
Name	CUMINTRAT

Datatype	Number
Description	Indicates Cumulative Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

ACCRNUMMETH

Attribute	Description
Name	ACCRNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

ACRR366BASS

Attribute	Description	
Name	ACRR366BASS	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

ACCRINCLTODT

Attribute	Description	
Name	ACCRINCLTODT	
Datatype	String	
Description	Indicates Include To Date Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMETH

Attribute	Description	
Name	LIQDNUMMETH	
Datatype	String	
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description

Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

LIQD366BASS

Attribute	Description
Name	LIQD366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWFT

Attribute	Description
Name	DOCSWFT
Datatype	String
Description	Indicates Document Method Swift Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINT

Attribute	Description
Name	ZEROINT
Datatype	String
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	Includes Security Series details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates SERIES
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	Includes Coupon Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COUPSTDT

Attribute	Description
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	Description
Name	COUPTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

COUPENDT

Attribute	Description
Name	COUPENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched

Datatype	
Description	Includes Revision Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASEFREQ

Attribute	Description
Name	REVBASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	Description
Name	REVWEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

REVADHMONE

Attribute	Description
Name	REVADHMONE
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption

Datatype	
Description	Includes Redemption details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REDEVTDT

Attribute	Description
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	Description
Name	PERREDEM
Datatype	Number
Description	Indicates % To Be Redeemed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRI

Attribute	Description
Name	REDPRI
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPFRAC

Attribute	Description
Name	DISPFRAC
Datatype	String
Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

CALLINDICAT

Attribute	Description
Name	CALLINDICAT
Datatype	String
Description	Indicates Call Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	Includes Coupon Period details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PCD

Attribute	Description
Name	PCD
Datatype	String
Description	Indicates Previous Coupon Date
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NCD

Attribute	Description
Name	NCD

Datatype	String
Description	Indicates Next Coupon Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COUPTYDES

Attribute	Description
Name	COUPTYDES
Datatype	String
Description	Indicates Coupon Period Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	String
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	String
Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	String
Description	Indicates Next Virtual First Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

VIRNEXDT2

Attribute	**Description**	
Name	VIRNEXDT2	
Datatype	String	
Description	Indicates Next Virtual Second Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Revision-Date-Master

Attribute	**Description**	
Name	Revision-Date-Master	
Datatype		
Description	Includes Revision Date Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REVTDATE

Attribute	**Description**	
Name	REVTDATE	
Datatype	Date	
Description	Indicates Event Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVEFFDATE

Attribute	**Description**	
Name	REVEFFDATE	
Datatype	Date	
Description	Indicates Effective Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Security-Event-Log

Attribute	**Description**

Name	Security-Event-Log
Datatype	
Description	Includes Security Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date TIme:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U For Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	Includes Security Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.117.4.SEInstrument-Modify-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *SEInstrument-Modify-Res*
      - *XREF*
      - *SECREFNO*
      - *SECID*
      - *PROD*
      - *MKTISS*
      - *ISSID*
      - *SECCCY*
      - *PAYCCY*
      - *ISSDATE*
      - *STINTDATE*
      - *STTRADEDATE*
      - *INFACEVAL*
    - *SEInstrument-Modify-Req*
      - *XREF*
      - *SECID*
      - *PROD*
      - *MKTISS*

ISSID
SECCCY
PAYCCY
ISSDATE
STINTDATE
STTRADEDATE
INFACEVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Modification Of the Instrumnet

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

SEInstrument-Modify-Res

Attribute	Description
Name	SEInstrument-Modify-Res
Datatype	
Description	Includes Securities Instrument Modification Response type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SECID

Attribute	Description

Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	

Restrictions	Description
maxLength	16
minLength	0
pattern	[a-zA-Z0-9_]*

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	

Restrictions	Description
length	4
pattern	[a-zA-Z0-9]{4}

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16
pattern	[a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9
pattern	[a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

PAYCCY

Attribute	**Description**	
Name	PAYCCY	
Datatype	String	
Description	Indicates Payment Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ISSDATE

Attribute	**Description**	
Name	ISSDATE	
Datatype	Date	
Description	Indicates Issue/Tearoff Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STINTDATE

Attribute	**Description**	
Name	STINTDATE	
Datatype	Date	
Description	Indicates Start of Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDATE

Attribute	**Description**	
Name	STTRADEDATE	
Datatype	Date	
Description	Indicates Start of Trading Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SEInstrument-Modify-Req

Attribute	Description
Name	SEInstrument-Modify-Req
Datatype	
Description	Includes Securities Instrument Modification Request type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9_]*</td></tr></table>

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></table>

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDATE

Attribute	Description
Name	STTRADEDATE
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.118.QuerySEInstr

Query of Securities Instrument Definition

2.118.1.SEInstrument-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Query-Req*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Query Of a Instr.

TOP

SEInstrument-Query-Req

Attribute	Description
Name	SEInstrument-Query-Req
Datatype	
Description	Includes Securities Instrument Query Request type details

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0; pattern / [a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.118.2.SEInstrument-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master*
      - *XREF*
      - *SECID*
      - *ISINIDNTFR*
      - *SECDES*
      - *PROD*
      - *PRODDES*
      - *SECRTYP*
      - *SECREFNO*
      - *SECRSTAT*
      - *TRADSTAT*
      - *INTERRAT*
      - *MKTISS*
      - *MKTDES*
      - *ISSID*
      - *ISSDES*
      - *REGBEAR*
      - *FRMTYPE*

QTYQUOT
INTQUOT
FRACTQUANT
UDECIMAL
EQRED
REN
REDTYPE
REDEMPQUOT
CONFCORPACTION
CALLOPT
PUTOPT
SECCCY
PAYCCY
ISSSIZE
OSISSIZE
MINTRDQT
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
CURENTFV
REDPRICE
ISSSECID
MKTSECID
CNBSECID
REST
VOTRIT
COVERED
CONVBLE
BKACC
ISOCFICODE
ISITCCODE
ATTRBDES
COLLTYPE
DIREXPLINE
QUALRAT
REVPRICODE
PRICDES
MKTREV
COUPBASIS
DIVBASIS

WARRBASIS
RITBASIS
AUTOCORP
PRIQUOT
RATECODE
USBONDFORM
TBILLREINVPER
TBILLANNMETH
TBILLCOUNTNR
TBILLCOUNTDN
BNDREINVPER
BNDANNMETH
BNDDAYCOUNTNR
BNDDAYCOUNTDN
PREMDISCURRPE
DAYS
DAYIN
IDNTINARRAT1
IDNTINARRAT2
IDNTINARRAT3
IDNTINARRAT4
ATTRIBNARRAT1
ATTRIBNARRAT2
ATTRIBNARRAT3
ATTRIBNARRAT4
ATTRIBNARRAT5
ATTRIBNARRAT6
ATTRIBNARRAT7
ATTRIBNARRAT8
ATTRIBNARRAT9
ATTRIBNARRAT10
MINIRATE
MAXIRATE
Mis-Details
- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*

CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10

FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Tax-Master
FNDREFNO
VERSNO
SECID
TXTREF
SECREF
Issr-Tax-Assoc
CRRATESN

INTCOMP
RATECOD
WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Sec-Master
SECID
SECREFNO
Interest-Assoc
CRRATESN
INTCOMP
WAIVER
RATECODE
RATCODESC
TENCODE
TENCODESC
INTSPRD
INTRATE
FLTAMT
ACQAMT
INTCALCMET
QUOTREVIND
QUOTREVSPD
QUOTREVFLR

QUOTREVCEIL

Interest

PERCOUP

ALLASYNCREV

PERREV

CAPT

COUPFREQ

ACCVALDATE

COUPWEEK

COUPPLTDATE

CADHMNTHEND

REVFREQ

REVWEEK

RADHMNTHEND

RNDBASIS

RATEBASIS

CUMINTRAT

ACCRNUMMETH

ACCRDENMETH

ACCRDENBASS

ACRR366BASS

ACCRINCLTODT

LIQDNUMMETH

LIQDDENMETH

LIQDDENBASS

LIQD366BASS

ISSSIZE

DOCSWFT

ZEROINT

Security-Series

SERIES

Coupon-Sched

COUPSTDT

COUPTYPE

COUPENDT

BASEFREQ

WEEKDAY

ADHMNTHEND

Revision-Sched

REVSTDT

REVTYPE

REVENDT

REVBASEFREQ

REVWEEKDAY

REVADHMONE
Redemption
REDEVTDT
PERREDEM
REDPRI
DISPFRAC
CALLINDICAT
REDSERIES
Coupon-Period
PCD
NCD
COUPTYDES
VIRPREVDT2
VIRPREVDT1
VIRNEXDT1
VIRNEXDT2
Revision-Date-Master
REVTDATE
REVEFFDATE
Security-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Security-Hol-Ccy
SECURITYID
HOLCCY
SEInstrument-Query-Req
SECID
SECREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Creation Of the Instrumnet

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Includes Securities Instrument Query Master type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

SECDES

Attribute	Description
Name	SECDES
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRODDES

Attribute	Description
Name	PRODDES
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SECRTYP

Attribute	Description
Name	SECRTYP
Datatype	String
Description	Indicates Security Type Bond : B Equity : E Rights : R Warrant : W Zero Coupon Bond : Z
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SECRSTAT

Attribute	Description
Name	SECRSTAT
Datatype	String
Description	Indicates Security Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TRADSTAT

Attribute	Description
Name	TRADSTAT
Datatype	String
Description	Indicates Trading Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTERRAT

Attribute	Description
Name	INTERRAT
Datatype	String
Description	Indicates Interest Type Floating : FLT Fixed : FXD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

MKTDES

Attribute	Description
Name	MKTDES
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

ISSDES

Attribute	Description
Name	ISSDES
Datatype	String
Description	Indicates Issuer Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String
Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

QTYQUOT

Attribute	Description
Name	QTYQUOT
Datatype	String
Description	Indicates Quantity Quotation UNITS : U NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

INTQUOT

Attribute	Description
Name	INTQUOT
Datatype	String
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,A,P

TOP

FRACTQUANT

Attribute	Description
Name	FRACTQUANT
Datatype	String

Description	Indicates Fractional Quantity Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UDECIMAL

Attribute	Description
Name	UDECIMAL
Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description
Name	EQRED
Datatype	String
Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String

Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT
Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description
Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT

Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINTRDQT

Attribute	**Description**	
Name	MINTRDQT	
Datatype	Number	
Description	Indicates Min Trading Size	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOTSIZE

Attribute	**Description**	
Name	LOTSIZE	
Datatype	Number	
Description	Indicates Lot Size	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSDATE

Attribute	**Description**	
Name	ISSDATE	
Datatype	Date	
Description	Indicates Issue/Tearoff Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STINTDATE

Attribute	**Description**	
Name	STINTDATE	
Datatype	Date	
Description	Indicates Start of Interest Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDAT

Attribute	**Description**	
Name	STTRADEDAT	
Datatype	Date	
Description	Indicates Start of Trading Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURENTFV

Attribute	Description
Name	CURENTFV
Datatype	Number
Description	Indicates Current Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSSECID

Attribute	Description
Name	ISSSECID
Datatype	String
Description	Indicates Issuer Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

MKTSECID

Attribute	Description
Name	MKTSECID
Datatype	String
Description	Indicates Market Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

CNBSECID

Attribute	Description
Name	CNBSECID
Datatype	String
Description	Indicates Central Bank Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

REST

Attribute	Description
Name	REST
Datatype	String
Description	Indicates Restricted Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VOTRIT

Attribute	Description
Name	VOTRIT
Datatype	String
Description	Indicates Voting Rights Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVERED

Attribute	Description
Name	COVERED
Datatype	String
Description	Indicates Covered Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONVBLE

Attribute	Description
Name	CONVBLE
Datatype	String
Description	Indicates Convertible Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BKACC

Attribute	Description
Name	BKACC
Datatype	String
Description	Indicates Bankers Accept Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICODE

Attribute	**Description**	
Name	ISOCFICODE	
Datatype	String	
Description	Indicates ISO CFI Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	**Description**	
Name	ISITCCODE	
Datatype	String	
Description	Indicates ISITC Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

ATTRBDES

Attribute	**Description**	
Name	ATTRBDES	
Datatype	String	
Description	Indicates Attribute Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

COLLTYPE

Attribute	**Description**
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description	
Name	DIREXPLINE	
Datatype	String	
Description	Indicates Direct Exposure Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description	
Name	QUALRAT	
Datatype	String	
Description	Indicates Quality Rating	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3
	minLength	0
	pattern	[A-Za-z0-9]*

TOP

REVPRICODE

Attribute	Description	
Name	REVPRICODE	
Datatype	String	
Description	Indicates Revaluation Price Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

PRICDES

Attribute	Description
Name	PRICDES
Datatype	String
Description	Indicates Price Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String
Description	Indicates Warrant Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

RITBASIS

Attribute	Description
Name	RITBASIS
Datatype	String
Description	Indicates Rights Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

AUTOCORP

Attribute	Description
Name	AUTOCORP
Datatype	String
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIQUOT

Attribute	Description
Name	PRIQUOT
Datatype	String

Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRE,PPD,YTM

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

USBONDFORM

Attribute	Description
Name	USBONDFORM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C

TOP

TBILLCOUNTNR

Attribute	Description
Name	TBILLCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

TBILLCOUNTDN

Attribute	Description
Name	TBILLCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

BNDREINVPER

Attribute	Description
Name	BNDREINVPER
Datatype	String
Description	Indicates Reinv. Period Days

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	0
	pattern	[0-9]*

TOP

BNDANNMETH

Attribute	Description	
Name	BNDANNMETH	
Datatype	String	
Description	Indicates Annualizing Method Simple : S Compound : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BNDDAYCOUNTNR

Attribute	Description	
Name	BNDDAYCOUNTNR	
Datatype	String	
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description	
Name	BNDDAYCOUNTDN	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H

TOP

PREMDISCURRPE

Attribute	Description
Name	PREMDISCURRPE
Datatype	String
Description	Indicates Premium/Discount For Current Interest Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	Indicates No of Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIN

Attribute	Description
Name	DAYIN
Datatype	String
Description	Indicates Days Before Start of Next Coupon Period : B After Start of Previous Coupon Period : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IDNTINARRAT1

Attribute	Description
Name	IDNTINARRAT1
Datatype	String
Description	Indicates Identification Narrative 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT2

Attribute	Description
Name	IDNTINARRAT2
Datatype	String
Description	Indicates Identification Narrative 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT3

Attribute	Description
Name	IDNTINARRAT3
Datatype	String
Description	Indicates Identification Narrative 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT4

Attribute	Description
Name	IDNTINARRAT4
Datatype	String
Description	Indicates Identification Narrative 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT1

Attribute	Description
Name	ATTRIBNARRAT1
Datatype	String
Description	Indicates Attribute Narrative 01
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT2

Attribute	Description
Name	ATTRIBNARRAT2
Datatype	String
Description	Indicates Attribute Narrative 02
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT3

Attribute	Description
Name	ATTRIBNARRAT3
Datatype	String
Description	Indicates Attribute Narrative 03
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT4

Attribute	Description
Name	ATTRIBNARRAT4
Datatype	String
Description	Indicates Attribute Narrative 04
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT5

Attribute	Description
Name	ATTRIBNARRAT5
Datatype	String
Description	Indicates Attribute Narrative 05
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT6

Attribute	Description
Name	ATTRIBNARRAT6
Datatype	String
Description	Indicates Attribute Narrative 06
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT7

Attribute	Description
Name	ATTRIBNARRAT7
Datatype	String
Description	Indicates Attribute Narrative 07
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT8

Attribute	Description
Name	ATTRIBNARRAT8
Datatype	String
Description	Indicates Attribute Narrative 08
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT9

Attribute	Description
Name	ATTRIBNARRAT9
Datatype	String
Description	Indicates Attribute Narrative 09
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT10

Attribute	Description
Name	ATTRIBNARRAT10
Datatype	String
Description	Indicates Attribute Narrative 10
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

MINIRATE

Attribute	Description
Name	MINIRATE
Datatype	Number
Description	Indicates Min Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXIRATE

Attribute	Description
Name	MAXIRATE
Datatype	Number
Description	Indicates Max Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS6

Attribute	**Description**

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE

Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Tax-Master

Attribute	Description
Name	Tax-Master
Datatype	
Description	Includes Tax Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FNDREFNO

Attribute	Description
Name	FNDREFNO
Datatype	String
Description	Indicates the Fund Reference No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSNO

Attribute	**Description**	
Name	VERSNO	
Datatype	Number	
Description	Specifies the Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Indicates Security ID	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[a-zA-Z0-9_%. /]*

TOP

TXTREF

Attribute	**Description**	
Name	TXTREF	
Datatype	String	
Description	Specifies the transaction reference number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECREF

Attribute	**Description**	
Name	SECREF	
Datatype	String	
Description	Specifies The Security Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	Specifies The Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP

Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description	Specifies The TAG Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description	Specifies The TAG Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** fractionDigits: 3 totalDigits: 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description** minOccurs: 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description	
Name	CONTREF	
Datatype	String	
Description	Specifies The Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Tran-Tax-Liqd-Master

Attribute	Description	
Name	Tran-Tax-Liqd-Master	
Datatype		
Description	Specifies The Liquidation Details Of Transaction Level Tax.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description	
Name	TAXCCY	
Datatype	String	
Description	Specifies The Tax Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sec-Master

Attribute	Description
Name	Sec-Master
Datatype	
Description	Includes Security Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	Description
Name	SECREFNO

Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	Includes Interest Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

RATCODESC

Attribute	Description
Name	RATCODESC
Datatype	String
Description	Indicates Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TENCODE

Attribute	Description
Name	TENCODE
Datatype	String
Description	Indicates Tenor Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

TENCODESC

Attribute	Description
Name	TENCODESC
Datatype	String
Description	Indicates Tenor Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 33 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	Description
Name	FLTAMT
Datatype	Number
Description	Indicates Flat Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String

Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND
Datatype	String
Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	Includes Interest details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String
Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PERREV

Attribute	Description
Name	PERREV
Datatype	String
Description	Indicates Periodic Revision Y for Yes; N for No
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CAPT

Attribute	Description
Name	CAPT
Datatype	String
Description	Indicates Capitalization Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPFREQ

Attribute	Description
Name	COUPFREQ
Datatype	String
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFREQ

Attribute	Description
Name	REVFREQ
Datatype	String

Description	Indicates Revision Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	Description
Name	RADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDBASIS

Attribute	Description
Name	RNDBASIS
Datatype	String
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,U

TOP

RATEBASIS

Attribute	Description
Name	RATEBASIS
Datatype	String
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

CUMINTRAT

Attribute	Description
Name	CUMINTRAT
Datatype	Number
Description	Indicates Cumulative Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

ACCRNUMMETH

Attribute	Description
Name	ACCRNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String

Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

ACRR366BASS

Attribute	Description
Name	ACRR366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ACCRINCLTODT

Attribute	Description
Name	ACCRINCLTODT
Datatype	String
Description	Indicates Include To Date Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDNUMMETH

Attribute	Description
Name	LIQDNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description
Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

LIQD366BASS

Attribute	Description
Name	LIQD366BASS
Datatype	String

Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWFT

Attribute	Description
Name	DOCSWFT
Datatype	String
Description	Indicates Document Method Swift Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINT

Attribute	Description
Name	ZEROINT
Datatype	String
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	Includes Security Series details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SERIES

Attribute	**Description**	
Name	SERIES	
Datatype	String	
Description	Indicates SERIES	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30
	minLength	0
	pattern	[A-Za-z0-9_]*

TOP

Coupon-Sched

Attribute	**Description**	
Name	Coupon-Sched	
Datatype		
Description	Includes Coupon Schedules details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COUPSTDT

Attribute	**Description**
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	**Description**	
Name	COUPTYPE	
Datatype	String	
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

COUPENDT

Attribute	Description
Name	COUPENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String
Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched
Datatype	
Description	Includes Revision Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASEFREQ

Attribute	**Description**	
Name	REVBASEFREQ	
Datatype	String	
Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	**Description**	
Name	REVWEEKDAY	
Datatype	String	
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7

TOP

REVADHMONE

Attribute	**Description**
Name	REVADHMONE
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Redemption

Attribute	**Description**	
Name	Redemption	
Datatype		
Description	Includes Redemption details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REDEVTDT

Attribute	**Description**
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	**Description**	
Name	PERREDEM	
Datatype	Number	
Description	Indicates % To Be Redeemed	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REDPRI

Attribute	**Description**	
Name	REDPRI	
Datatype	Number	
Description	Indicates Redemption Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISPFRAC

Attribute	**Description**
Name	DISPFRAC
Datatype	String

Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

CALLINDICAT

Attribute	Description
Name	CALLINDICAT
Datatype	String
Description	Indicates Call Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	Includes Coupon Period details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PCD

Attribute	Description

Name	PCD
Datatype	String
Description	Indicates Previous Coupon Date
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

NCD

Attribute	Description
Name	NCD
Datatype	String
Description	Indicates Next Coupon Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COUPTYDES

Attribute	Description
Name	COUPTYDES
Datatype	String
Description	Indicates Coupon Period Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	String
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	String
Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	String
Description	Indicates Next Virtual First Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

VIRNEXDT2

Attribute	Description
Name	VIRNEXDT2
Datatype	String
Description	Indicates Next Virtual Second Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	Includes Revision Date Master details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVTDATE

Attribute	Description
Name	REVTDATE
Datatype	Date
Description	Indicates Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVEFFDATE

Attribute	Description

Name	REVEFFDATE
Datatype	Date
Description	Indicates Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Security-Event-Log

Attribute	Description
Name	Security-Event-Log
Datatype	
Description	Includes Security Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date TIme:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U For Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	Includes Security Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

SEInstrument-Query-Req

Attribute	Description
Name	SEInstrument-Query-Req
Datatype	
Description	Includes Securities Instrument Query Request type details

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.119.ReopenSEInstrument

Reopen Securities Instrument Definition

2.119.1.SEInstrument-Reopen-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Reopen-Req-Full*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Reopen of Instrument.

TOP

SEInstrument-Reopen-Req-Full

Attribute	Description
Name	SEInstrument-Reopen-Req-Full
Datatype	
Description	Includes Securities Instrument Reopen Request Full type details

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description

Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

2.119.2.SEInstrument-Reopen-Req-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *SEInstrument-Reopen-Req*
  - *SECID*
  - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Reopen Of a Deal.

TOP

SEInstrument-Reopen-Req

Attribute	Description
Name	SEInstrument-Reopen-Req
Datatype	
Description	Includes Securities Instrument Reopen Request type details

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

2.119.3.SEInstrument-Reopen-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master*
    - *XREF*
    - *SECID*
    - *ISINIDNTFR*
    - *SECDES*
    - *PROD*
    - *PRODDES*
    - *SECRTYP*
    - *SECREFNO*
    - *SECRSTAT*
    - *TRADSTAT*
    - *INTERRAT*
    - *MKTISS*
    - *MKTDES*
    - *ISSID*
    - *ISSDES*
    - *REGBEAR*
    - *FRMTYPE*
    - *QTYQUOT*

INTQUOT
FRACTQUANT
UDECIMAL
EQRED
REN
REDTYPE
REDEMPQUOT
CONFCORPACTION
CALLOPT
PUTOPT
SECCCY
PAYCCY
ISSSIZE
OSISSIZE
MINTRDQT
LOTSIZE
ISSDATE
STINTDATE
STTRADEDAT
REDDATE
INFACEVAL
ISSPRICE
CURENTFV
REDPRICE
ISSSECID
MKTSECID
CNBSECID
REST
VOTRIT
COVERED
CONVBLE
BKACC
ISOCFICODE
ISITCCODE
ATTRBDES
COLLTYPE
DIREXPLINE
QUALRAT
REVPRICODE
PRICDES
MKTREV
COUPBASIS
DIVBASIS
WARRBASIS

RITBASIS
AUTOCORP
PRIQUOT
RATECODE
USBONDFORM
TBILLREINVPER
TBILLANNMETH
TBILLCOUNTNR
TBILLCOUNTDN
BNDREINVPER
BNDANNMETH
BNDDAYCOUNTNR
BNDDAYCOUNTDN
PREMDISCURRPE
DAYS
DAYIN
IDNTINARRAT1
IDNTINARRAT2
IDNTINARRAT3
IDNTINARRAT4
ATTRIBNARRAT1
ATTRIBNARRAT2
ATTRIBNARRAT3
ATTRIBNARRAT4
ATTRIBNARRAT5
ATTRIBNARRAT6
ATTRIBNARRAT7
ATTRIBNARRAT8
ATTRIBNARRAT9
ATTRIBNARRAT10
MINIRATE
MAXIRATE
Mis-Details
- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Tax-Master

- *FNDREFNO*
- *VERSNO*
- *SECID*
- *TXTREF*
- *SECREF*
- *Issr-Tax-Assoc*
  - *CRRATESN*
  - *INTCOMP*

RATECOD
WAIVER
CONTREF
Tran-Tax-Assoc
CRRATESN
INTCOMP
RULE
WAIVER
CONTREF
Tran-Tax-Appln
CRRATESN
INTCOMP
TAGCCY
TAGAMNT
TAXCCY
TAXAMNT
WAIVER
LIQINDICAT
CONTREF
Tran-Tax-Liqd-Master
INTCOMP
TAXCCY
TAXAMNT
CONTREF
Sec-Master
SECID
SECREFNO
Interest-Assoc
CRRATESN
INTCOMP
WAIVER
RATECODE
RATCODESC
TENCODE
TENCODESC
INTSPRD
INTRATE
FLTAMT
ACQAMT
INTCALCMET
QUOTREVIND
QUOTREVSPD
QUOTREVFLR
QUOTREVCEIL

Interest

- *PERCOUP*
- *ALLASYNCREV*
- *PERREV*
- *CAPT*
- *COUPFREQ*
- *ACCVALDATE*
- *COUPWEEK*
- *COUPPLTDATE*
- *CADHMNTHEND*
- *REVFREQ*
- *REVWEEK*
- *RADHMNTHEND*
- *RNDBASIS*
- *RATEBASIS*
- *CUMINTRAT*
- *ACCRNUMMETH*
- *ACCRDENMETH*
- *ACCRDENBASS*
- *ACRR366BASS*
- *ACCRINCLTODT*
- *LIQDNUMMETH*
- *LIQDDENMETH*
- *LIQDDENBASS*
- *LIQD366BASS*
- *ISSSIZE*
- *DOCSWFT*
- *ZEROINT*

Security-Series

- *SERIES*

Coupon-Sched

- *COUPSTDT*
- *COUPTYPE*
- *COUPENDT*
- *BASEFREQ*
- *WEEKDAY*
- *ADHMNTHEND*

Revision-Sched

- *REVSTDT*
- *REVTYPE*
- *REVENDT*
- *REVBASEFREQ*
- *REVWEEKDAY*
- *REVADHMONE*

Redemption
REDEVTDT
PERREDEM
REDPRI
DISPFRAC
CALLINDICAT
REDSERIES
Coupon-Period
PCD
NCD
COUPTYDES
VIRPREVDT2
VIRPREVDT1
VIRNEXDT1
VIRNEXDT2
Revision-Date-Master
REVTDATE
REVEFFDATE
Security-Event-Log
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
AUTHSTAT
CONTSTAT
Security-Hol-Ccy
SECURITYID
HOLCCY
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Reopen Of a Instrument.

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Includes Securities Instrument Reopen Master type details

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	Indicates External Reference Number

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

ISINIDNTFR

Attribute	Description
Name	ISINIDNTFR
Datatype	String
Description	Indicates ISIN Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 12 pattern / [a-zA-Z0-9_]*

TOP

SECDES

Attribute	Description
Name	SECDES
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

PRODDES

Attribute	Description
Name	PRODDES
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

SECRTYP

Attribute	Description
Name	SECRTYP
Datatype	String
Description	Indicates Security Type Bond : B Equity : E Rights : R Warrant : W Zero Coupon Bond : Z
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

SECRSTAT

Attribute	Description
Name	SECRSTAT
Datatype	String
Description	Indicates Security Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TRADSTAT

Attribute	Description
Name	TRADSTAT
Datatype	String
Description	Indicates Trading Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTERRAT

Attribute	Description
Name	INTERRAT
Datatype	String
Description	Indicates Interest Type Floating : FLT Fixed : FXD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market Of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9_]*

TOP

MKTDES

Attribute	Description
Name	MKTDES
Datatype	String
Description	Indicates Market Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

ISSDES

Attribute	Description
Name	ISSDES
Datatype	String
Description	Indicates Issuer Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates Registered/Bearer REGISTERED : R BEARER : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYPE

Attribute	Description
Name	FRMTYPE
Datatype	String
Description	Indicates Form Type SCRIP BASED : S IMMOBILIZED : I DEMAT : D COMBINATION : C SGL : G

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G

TOP

QTYQUOT

Attribute	**Description**	
Name	QTYQUOT	
Datatype	String	
Description	Indicates Quantity Quotation UNITS : U NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

INTQUOT

Attribute	**Description**	
Name	INTQUOT	
Datatype	String	
Description	Indicates Interest Quotation FLAT : F PLUS ACCRUED : P	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,A,P

TOP

FRACTQUANT

Attribute	**Description**	
Name	FRACTQUANT	
Datatype	String	
Description	Indicates Fractional Quantity Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UDECIMAL

Attribute	**Description**
Name	UDECIMAL

Datatype	Number
Description	Indicates Decimals
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EQRED

Attribute	Description
Name	EQRED
Datatype	String
Description	Indicates Equated Redemption Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REN

Attribute	Description
Name	REN
Datatype	String
Description	Indicates Renouncable Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYPE

Attribute	Description
Name	REDTYPE
Datatype	String
Description	Indicates Redemption Type Quantity : Q Series : S Bullet : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT

Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

CONFCORPACTION

Attribute	Description
Name	CONFCORPACTION
Datatype	String
Description	Indicates Confirmation Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates Call Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates Put Option Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String

Description	Indicates Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZE

Attribute	Description
Name	OSISSIZE
Datatype	Number
Description	Indicates O/S Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTRDQT

Attribute	Description
Name	MINTRDQT
Datatype	Number
Description	Indicates Min Trading Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates Lot Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	Date
Description	Indicates Issue/Tearoff Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	Date
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDAT

Attribute	Description
Name	STTRADEDAT
Datatype	Date
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDDATE

Attribute	Description
Name	REDDATE
Datatype	Date
Description	Indicates Redemption/Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRICE

Attribute	Description
Name	ISSPRICE
Datatype	Number
Description	Indicates Issue Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURENTFV

Attribute	Description
Name	CURENTFV
Datatype	Number
Description	Indicates Current Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRICE

Attribute	Description
Name	REDPRICE
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSSECID

Attribute	Description
Name	ISSSECID
Datatype	String
Description	Indicates Issuer Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

MKTSECID

Attribute	Description
Name	MKTSECID
Datatype	String
Description	Indicates Market Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

CNBSECID

Attribute	Description
Name	CNBSECID
Datatype	String
Description	Indicates Central Bank Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

REST

Attribute	Description
Name	REST
Datatype	String
Description	Indicates Restricted Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VOTRIT

Attribute	Description
Name	VOTRIT
Datatype	String
Description	Indicates Voting Rights Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVERED

Attribute	**Description**	
Name	COVERED	
Datatype	String	
Description	Indicates Covered Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVBLE

Attribute	**Description**	
Name	CONVBLE	
Datatype	String	
Description	Indicates Convertible Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BKACC

Attribute	**Description**	
Name	BKACC	
Datatype	String	
Description	Indicates Bankers Accept Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICODE

Attribute	**Description**
Name	ISOCFICODE
Datatype	String

Description	Indicates ISO CFI Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ISITCCODE

Attribute	Description
Name	ISITCCODE
Datatype	String
Description	Indicates ISITC Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

ATTRBDES

Attribute	Description
Name	ATTRBDES
Datatype	String
Description	Indicates Attribute Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

COLLTYPE

Attribute	Description
Name	COLLTYPE
Datatype	String
Description	Indicates Collateral Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

DIREXPLINE

Attribute	Description
Name	DIREXPLINE
Datatype	String
Description	Indicates Direct Exposure Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

QUALRAT

Attribute	Description
Name	QUALRAT
Datatype	String
Description	Indicates Quality Rating
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0 pattern / [A-Za-z0-9]*

TOP

REVPRICODE

Attribute	Description
Name	REVPRICODE
Datatype	String
Description	Indicates Revaluation Price Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

PRICDES

Attribute	Description
Name	PRICDES
Datatype	String
Description	Indicates Price Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MKTREV

Attribute	Description
Name	MKTREV
Datatype	String
Description	Indicates Market for Revaluation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	Indicates Coupon Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

DIVBASIS

Attribute	Description
Name	DIVBASIS
Datatype	String
Description	Indicates Dividend Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

WARRBASIS

Attribute	Description
Name	WARRBASIS
Datatype	String
Description	Indicates Warrant Basis POSITION : P HOLDINGS : H

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

RITBASIS

Attribute	Description
Name	RITBASIS
Datatype	String
Description	Indicates Rights Basis POSITION : P HOLDINGS : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H

TOP

AUTOCORP

Attribute	Description
Name	AUTOCORP
Datatype	String
Description	Indicates Auto Initiation of Corporate Action Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIQUOT

Attribute	Description
Name	PRIQUOT
Datatype	String
Description	Indicates Price Quotation PRICE : PRI PREMIUM OR DISCOUNT : PRM PRICE1 : PPR PREMIUM OR DISCOUNT1 : PPM YIELD MATURITY : YTM
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PPR,PRE,PPD,YTM

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

USBONDFORM

Attribute	Description
Name	USBONDFORM
Datatype	String
Description	Indicates Use Bond Formula Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPER

Attribute	Description
Name	TBILLREINVPER
Datatype	String
Description	Indicates Reinv. Period Days
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0 pattern / [0-9]*

TOP

TBILLANNMETH

Attribute	Description
Name	TBILLANNMETH
Datatype	String
Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	S,C

TOP

TBILLCOUNTNR

Attribute	Description	
Name	TBILLCOUNTNR	
Datatype	String	
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U

TOP

TBILLCOUNTDN

Attribute	Description	
Name	TBILLCOUNTDN	
Datatype	String	
Description	Indicates Day Count Method Denominator 360 : L 365 : H	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H

TOP

BNDREINVPER

Attribute	Description	
Name	BNDREINVPER	
Datatype	String	
Description	Indicates Reinv. Period Days	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4
	minLength	0
	pattern	[0-9]*

TOP

BNDANNMETH

Attribute	Description
Name	BNDANNMETH
Datatype	String

Description	Indicates Annualizing Method Simple : S Compound : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNDDAYCOUNTNR

Attribute	Description
Name	BNDDAYCOUNTNR
Datatype	String
Description	Indicates Day Count Method Numerator Actual : A 30EURO : E 30US : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U

TOP

BNDDAYCOUNTDN

Attribute	Description
Name	BNDDAYCOUNTDN
Datatype	String
Description	Indicates Day Count Method Denominator 360 : L 365 : H
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H

TOP

PREMDISCURRPE

Attribute	Description
Name	PREMDISCURRPE
Datatype	String
Description	Indicates Premium/Discount For Current Interest Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DAYS

Attribute	Description
Name	DAYS
Datatype	Number
Description	Indicates No of Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIN

Attribute	Description
Name	DAYIN
Datatype	String
Description	Indicates Days Before Start of Next Coupon Period : B After Start of Previous Coupon Period : A
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

IDNTINARRAT1

Attribute	Description
Name	IDNTINARRAT1
Datatype	String
Description	Indicates Identification Narrative 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT2

Attribute	Description
Name	IDNTINARRAT2
Datatype	String
Description	Indicates Identification Narrative 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT3

Attribute	Description
Name	IDNTINARRAT3
Datatype	String
Description	Indicates Identification Narrative 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

IDNTINARRAT4

Attribute	Description
Name	IDNTINARRAT4
Datatype	String
Description	Indicates Identification Narrative 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT1

Attribute	Description
Name	ATTRIBNARRAT1
Datatype	String
Description	Indicates Attribute Narrative 01
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT2

Attribute	Description
Name	ATTRIBNARRAT2
Datatype	String
Description	Indicates Attribute Narrative 02
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT3

Attribute	Description
Name	ATTRIBNARRAT3
Datatype	String
Description	Indicates Attribute Narrative 03
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT4

Attribute	Description
Name	ATTRIBNARRAT4
Datatype	String
Description	Indicates Attribute Narrative 04
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT5

Attribute	Description
Name	ATTRIBNARRAT5
Datatype	String
Description	Indicates Attribute Narrative 05
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT6

Attribute	Description
Name	ATTRIBNARRAT6
Datatype	String
Description	Indicates Attribute Narrative 06
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT7

Attribute	Description
Name	ATTRIBNARRAT7
Datatype	String
Description	Indicates Attribute Narrative 07
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT8

Attribute	Description
Name	ATTRIBNARRAT8
Datatype	String
Description	Indicates Attribute Narrative 08
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT9

Attribute	Description
Name	ATTRIBNARRAT9
Datatype	String
Description	Indicates Attribute Narrative 09
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

ATTRIBNARRAT10

Attribute	Description
Name	ATTRIBNARRAT10
Datatype	String
Description	Indicates Attribute Narrative 10
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105 pattern / [a-zA-Z0-9]

TOP

MINIRATE

Attribute	Description
Name	MINIRATE
Datatype	Number
Description	Indicates Min Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

MAXIRATE

Attribute	Description
Name	MAXIRATE
Datatype	Number
Description	Indicates Max Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	Includes MIS details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9 minLength: 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	Includes User Defined Fields details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	**Description**	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2
	minLength	0

TOP

Tax-Master

Attribute	**Description**	
Name	Tax-Master	
Datatype		
Description	Includes Tax Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FNDREFNO

Attribute	**Description**	
Name	FNDREFNO	
Datatype	String	
Description	Indicates the Fund Reference No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

VERSNO

Attribute	**Description**	
Name	VERSNO	
Datatype	Number	
Description	Specifies the Version Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

TXTREF

Attribute	Description
Name	TXTREF
Datatype	String
Description	Specifies the transaction reference number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREF

Attribute	Description
Name	SECREF
Datatype	String
Description	Specifies The Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Issr-Tax-Assoc

Attribute	Description
Name	Issr-Tax-Assoc
Datatype	
Description	Specifies The Details Of issuer Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description	
Name	CRRATESN	
Datatype	Number	
Description	Specifies The Creation ESN.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	4

TOP

INTCOMP

Attribute	Description	
Name	INTCOMP	
Datatype	String	
Description	Displays the interest component.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

RATECOD

Attribute	Description	
Name	RATECOD	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Specifies Whether the Component Should Be Waived Off.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONTREF

Attribute	Description

Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Assoc

Attribute	Description
Name	Tran-Tax-Assoc
Datatype	
Description	Specifies The Association Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Specifies The Rule.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Tran-Tax-Appln

Attribute	Description
Name	Tran-Tax-Appln
Datatype	
Description	Specifies The Application Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Specifies The TAG Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	Specifies The TAG Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQINDICAT

Attribute	Description
Name	LIQINDICAT
Datatype	String
Description	Specifies whether to be liquidated or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Tran-Tax-Liqd-Master

Attribute	Description

Name	Tran-Tax-Liqd-Master
Datatype	
Description	Specifies The Liquidation Details Of Transaction Level Tax.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Specifies The Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	Specifies The Tax Amount.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONTREF

Attribute	Description
Name	CONTREF
Datatype	String
Description	Specifies The Contract Reference Number.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Sec-Master

Attribute	**Description**	
Name	Sec-Master	
Datatype		
Description	Includes Security Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	**Description**	
Name	SECID	
Datatype	String	
Description	Indicates Security ID	
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0
	pattern	[a-zA-Z0-9_%. /]*

TOP

SECREFNO

Attribute	**Description**	
Name	SECREFNO	
Datatype	String	
Description	Indicates Security Reference Number	
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

Interest-Assoc

Attribute	**Description**	
Name	Interest-Assoc	
Datatype		
Description	Includes Interest Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	Specifies The Creation ESN.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	Displays the interest component.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Specifies Whether the Component Should Be Waived Off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Indicates Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

RATCODESC

Attribute	Description
Name	RATCODESC
Datatype	String
Description	Indicates Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

TENCODE

Attribute	Description
Name	TENCODE
Datatype	String
Description	Indicates Tenor Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

TENCODESC

Attribute	Description
Name	TENCODESC
Datatype	String
Description	Indicates Tenor Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	String
Description	Indicates Interest Spread
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 33 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

INTRATE

Attribute	Description
Name	INTRATE
Datatype	Number
Description	Indicates Interest Rate

TOP

FLTAMT

Attribute	Description
Name	FLTAMT
Datatype	Number
Description	Indicates Flat Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQAMT

Attribute	Description
Name	ACQAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTCALCMET

Attribute	Description
Name	INTCALCMET
Datatype	String
Description	Indicates Interest Method 30(Euro)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(Euro)/365 : 4 30(US)/365 : 5 Actual/365 : 6 30(Euro)/Actual : 7 30(US)/Actual : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

TOP

QUOTREVIND

Attribute	Description
Name	QUOTREVIND
Datatype	String

Description	Indicates Index
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVSPD

Attribute	Description
Name	QUOTREVSPD
Datatype	String
Description	Indicates Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVFLR

Attribute	Description
Name	QUOTREVFLR
Datatype	String
Description	Indicates Floor
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QUOTREVCEIL

Attribute	Description
Name	QUOTREVCEIL
Datatype	String
Description	Indicates Ceiling
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	Includes Interest details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PERCOUP

Attribute	Description
Name	PERCOUP
Datatype	String

Description	Indicates Periodic Coupon Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLASYNCREV

Attribute	Description
Name	ALLASYNCREV
Datatype	String
Description	Indicates Allow Asynchronous Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PERREV

Attribute	Description
Name	PERREV
Datatype	String
Description	Indicates Periodic Revision Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPT

Attribute	Description
Name	CAPT
Datatype	String
Description	Indicates Capitalization Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPFREQ

Attribute	Description

Name	COUPFREQ
Datatype	String
Description	Indicates Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

ACCVALDATE

Attribute	Description
Name	ACCVALDATE
Datatype	String
Description	Indicates Accounting Value Date Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

COUPPLTDATE

Attribute	Description
Name	COUPPLTDATE
Datatype	String
Description	Indicates Coupon Plotting Ignore : I Forward : F Backward : B
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CADHMNTHEND

Attribute	Description
Name	CADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFREQ

Attribute	Description
Name	REVFREQ
Datatype	String
Description	Indicates Revision Frequency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3

TOP

REVWEEK

Attribute	Description
Name	REVWEEK
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7

TOP

RADHMNTHEND

Attribute	**Description**	
Name	RADHMNTHEND	
Datatype	String	
Description	Indicates Adhere To Month End Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASIS

Attribute	**Description**	
Name	RNDBASIS	
Datatype	String	
Description	Indicates Rounding Basis PER UNIT : U PER NOMINAL : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,U

TOP

RATEBASIS

Attribute	**Description**	
Name	RATEBASIS	
Datatype	String	
Description	Indicates Rate Basis PER ANNUM : A PER COUPON PERIOD : C	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

CUMINTRAT

Attribute	**Description**
Name	CUMINTRAT

Datatype	Number
Description	Indicates Cumulative Interest Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 8 totalDigits / 13

TOP

ACCRNUMMETH

Attribute	Description
Name	ACCRNUMMETH
Datatype	String
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

ACCRDENMETH

Attribute	Description
Name	ACCRDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

ACCRDENBASS

Attribute	Description
Name	ACCRDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,C

TOP

ACRR366BASS

Attribute	Description	
Name	ACRR366BASS	
Datatype	String	
Description	Indicates 366 Basis Leap Year : Y Leap Date : D	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D

TOP

ACCRINCLTODT

Attribute	Description	
Name	ACCRINCLTODT	
Datatype	String	
Description	Indicates Include To Date Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMETH

Attribute	Description	
Name	LIQDNUMMETH	
Datatype	String	
Description	Indicates Numerator Method 30-EURO : 30-EURO 30-US : 30-US ACTUAL : ACTUAL 30-ISDA : 30-ISDA 30-PSA : 30-PSA ACTUAL-JAPANESE : ACTUAL-JAPANESE	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE

TOP

LIQDDENMETH

Attribute	Description

Name	LIQDDENMETH
Datatype	String
Description	Indicates Denominator Method 360 : 360 365 : 365 ACTUAL : ACTUAL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL

TOP

LIQDDENBASS

Attribute	Description
Name	LIQDDENBASS
Datatype	String
Description	Indicates Denominator Basis PER ANNUM : A PER COUPON PERIOD : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C

TOP

LIQD366BASS

Attribute	Description
Name	LIQD366BASS
Datatype	String
Description	Indicates 366 Basis Leap Year : Y Leap Date : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D

TOP

ISSSIZE

Attribute	Description
Name	ISSSIZE
Datatype	Number
Description	Indicates Issue Size
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWFT

Attribute	Description
Name	DOCSWFT
Datatype	String
Description	Indicates Document Method Swift Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ZEROINT

Attribute	Description
Name	ZEROINT
Datatype	String
Description	Indicates Zero Interest During Ex Period Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	Includes Security Series details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates SERIES
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	Includes Coupon Schedules details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COUPSTDT

Attribute	Description
Name	COUPSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

COUPTYPE

Attribute	Description
Name	COUPTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,C</td></tr></table>

TOP

COUPENDT

Attribute	Description
Name	COUPENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BASEFREQ

Attribute	Description
Name	BASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

WEEKDAY

Attribute	Description
Name	WEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

ADHMNTHEND

Attribute	Description
Name	ADHMNTHEND
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched

Datatype	
Description	Includes Revision Schedules details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REVSTDT

Attribute	Description
Name	REVSTDT
Datatype	Date
Description	Indicates Base Start Date

TOP

REVTYPE

Attribute	Description
Name	REVTYPE
Datatype	String
Description	Indicates Discrete/Continuous DISCRETE : D CONTINUOUS : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

REVENDT

Attribute	Description
Name	REVENDT
Datatype	Date
Description	Indicates Base End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASEFREQ

Attribute	Description
Name	REVBASEFREQ
Datatype	String

Description	Indicates Base Frequency WEEKLY : W MONTHLY : 1M BI-MONTHLY : 2M QUARTERLY : 3M ONCE IN 4 MONTHS : 4M ONCE IN 5 MONTHS : 5M SEMI-ANNUALLY : 6M ONCE IN 7 MONTHS : 7M ONCE IN 8 MONTHS : 8M ONCE IN 9 MONTHS : 9M ONCE IN 10 MONTHS :10M ONCE IN 11 MONTHS :11M ANNUALLY : 12M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M

TOP

REVWEEKDAY

Attribute	Description
Name	REVWEEKDAY
Datatype	String
Description	Indicates Week Day Monday : 1 Tuesday : 2 Wednesday : 3 Thursday : 4 Friday : 5 Saturday : 6 Sunday : 7
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7

TOP

REVADHMONE

Attribute	Description
Name	REVADHMONE
Datatype	String
Description	Indicates Adhere To Month End Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption

Datatype	
Description	Includes Redemption details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

REDEVTDT

Attribute	Description
Name	REDEVTDT
Datatype	Date
Description	Indicates Event Date

TOP

PERREDEM

Attribute	Description
Name	PERREDEM
Datatype	Number
Description	Indicates % To Be Redeemed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRI

Attribute	Description
Name	REDPRI
Datatype	Number
Description	Indicates Redemption Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPFRAC

Attribute	Description
Name	DISPFRAC
Datatype	String
Description	Indicates Disposition of Fractions RETAIN : RN ROUND UP : RU ROUND DOWN : RD ROUND STANDARD : RS
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS

TOP

CALLINDICAT

Attribute	Description
Name	CALLINDICAT
Datatype	String
Description	Indicates Call Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDSERIES

Attribute	Description
Name	REDSERIES
Datatype	String
Description	Indicates Series
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30 minLength / 0 pattern / [A-Za-z0-9_]*

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	Includes Coupon Period details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PCD

Attribute	Description
Name	PCD
Datatype	String
Description	Indicates Previous Coupon Date
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

NCD

Attribute	Description
Name	NCD

Datatype	String
Description	Indicates Next Coupon Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

COUPTYDES

Attribute	Description
Name	COUPTYDES
Datatype	String
Description	Indicates Coupon Period Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT2

Attribute	Description
Name	VIRPREVDT2
Datatype	String
Description	Indicates Previous Virtual Second Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRPREVDT1

Attribute	Description
Name	VIRPREVDT1
Datatype	String
Description	Indicates Previous Virtual First Date
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

VIRNEXDT1

Attribute	Description
Name	VIRNEXDT1
Datatype	String
Description	Indicates Next Virtual First Date

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

VIRNEXDT2

Attribute	**Description**	
Name	VIRNEXDT2	
Datatype	String	
Description	Indicates Next Virtual Second Date	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Revision-Date-Master

Attribute	**Description**	
Name	Revision-Date-Master	
Datatype		
Description	Includes Revision Date Master details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REVTDATE

Attribute	**Description**	
Name	REVTDATE	
Datatype	Date	
Description	Indicates Event Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVEFFDATE

Attribute	**Description**	
Name	REVEFFDATE	
Datatype	Date	
Description	Indicates Effective Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Security-Event-Log

Attribute	**Description**

Name	Security-Event-Log
Datatype	
Description	Includes Security Event Log details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Checker Date TIme:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status A for Authorized; U For Unauthorized
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONTSTAT

Attribute	Description
Name	CONTSTAT
Datatype	String
Description	Indicates Contract Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	Includes Security Holiday Currency details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0 pattern / [a-zA-Z0-9_%. /]*

TOP

HOLCCY

Attribute	Description
Name	HOLCCY
Datatype	String
Description	Indicates Holiday Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.119.4.SEInstrument-Reopen-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master*
      - *SECREFNO*
      - *SECID*
      - *PROD*
      - *MKTISS*
      - *ISSID*
      - *SECCCY*
      - *PAYCCY*
      - *ISSDATE*
      - *STINTDATE*
      - *STTRADEDATE*
      - *INFACEVAL*
    - *SEInstrument-Reopen-Req*
      - *SECID*
      - *SECREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Reopen Of a Instrument.

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Security-Master

Attribute	Description
Name	Security-Master
Datatype	
Description	Includes Securities Instrument Reopen Master type details

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

PROD

Attribute	Description
Name	PROD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4 minLength / 0

TOP

MKTISS

Attribute	Description
Name	MKTISS
Datatype	String
Description	Indicates Market of Issue
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	Indicates Issuer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z0-9_]*

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0

TOP

PAYCCY

Attribute	Description
Name	PAYCCY
Datatype	String
Description	Indicates pay Currency Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3 minLength / 0

TOP

ISSDATE

Attribute	Description
Name	ISSDATE
Datatype	String
Description	Indicates Issue date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32 minLength / 0

TOP

STINTDATE

Attribute	Description
Name	STINTDATE
Datatype	String
Description	Indicates Start of Interest Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32 minLength / 0

TOP

STTRADEDATE

Attribute	Description
Name	STTRADEDATE
Datatype	String
Description	Indicates Start of Trading Date
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32 minLength / 0

TOP

INFACEVAL

Attribute	Description
Name	INFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

SEInstrument-Reopen-Req

Attribute	Description
Name	SEInstrument-Reopen-Req
Datatype	
Description	Includes Securities Instrument Reopen Request type details

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.120.DeleteSEInstrument

Deletion of Securities Instrument Definition

2.120.1.SEInstrument-delete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Delete-Req-Full*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Delete Of a Deal.

TOP

SEInstrument-Delete-Req-Full

Attribute	Description
Name	SEInstrument-Delete-Req-Full
Datatype	
Description	Deletion of Securities Instrument Definition Request Full Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description

Name	SECREFNO
Datatype	String
Description	Indicates Security Response
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

2.120.2.SEInstrument-delete-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *SEInstrument-Delete-Req*
    - *SECID*
    - *SECREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Delete Of a Instr.

TOP

SEInstrument-Delete-Req

Attribute	Description
Name	SEInstrument-Delete-Req
Datatype	
Description	Deletion of Securities Instrument Definition Request Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	0

TOP

2.120.3.SEInstrument-delete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Delete-Res*
    - *SECID*
    - *SECREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Delete Of a Inst.

TOP

Delete-Res

Attribute	Description
Name	Delete-Res
Datatype	
Description	Deletion of Securities Instrument Definition Response Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.120.4.SEInstrument-delete-Res-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Delete-Res*
      - *SECID*
      - *SECREFNO*
    - *SEInstrument-Delete-Req*
      - *SECID*
      - *SECREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Delete Of a Instr.

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Delete-Res

Attribute	Description
Name	Delete-Res
Datatype	
Description	Deletion of Securities Instrument Definition Response Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0

TOP

SEInstrument-Delete-Req

Attribute	Description
Name	SEInstrument-Delete-Req
Datatype	
Description	Deletion of Securities Instrument Definition Request Type

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 0

TOP

SECREFNO

Attribute	Description

Name	SECREFNO
Datatype	String
Description	Indicates Security Response Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.121.AuthorizePortfolioProduct

Authorization of Securities Portfolio Product

2.121.1.SP-AuthorizePortfolioProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*

INSPRDALW
TXT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*

TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG
TBDACCRFREQ
TBDACCRSTDY
TBDACCRSTMTH
LMTTRCKFRBNDS
LMTTRCKFREQUITIES
LMTTRCKFRRIGHTS
LMTTRCKFRWRNTS
LMTTRCKFRTBILLS
RLZDREVLMETH
RLZDREVLFLG
RLZDREVLSTDY
RLZDREVLSTMTH
RLZDREVLFREQ
ACCRTBDWTFLG
ACCRPRMMETH
ACCRDISCMETH
WIIPDLPURINT
LCOM
EXRATTYP
BNKRSACPTCE
CNTRAHLDNGTYPE
CNTRAHLDNGALWD
STMTHLDNGREQFLG
STMTHLDNGFREQ
STMTHLDNGSTDY
STMTHLDNGSTMTH
STMTTXNSTDY
CCYRATTYPDESC
Product-Class-Link
CLASCD
TXT_CLASS_DESC
Class

COMP
STPASSN
TAXTYP
BORNBY
CASHOUTFLWINDI
NETCONSINDI
CONSPLUSMIN
SWFTQUAL
EVNTASSN
EVNTAPPLN
EVNTLIQDN
BASAMTTAG
DFLTRULE
DFLTWAIV
ALLWRULAMND
AMNDAFTRASSN
ALLWAMTAMND
AMNDAFTRAPPLN
RULEDESC
Product-Scheme
PRDORMRKTCD
SCHME
Pfolioprod-Restrictions
SECPRDCD
PRDDESC
Pfolio-Prod-Secaccess
SECID
PRDCD
SECDESC
ACCSALWDFLG
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL

STPASOCIATN
ADVCHG
CAPTLIZE
DISCACCRAPLB
PROPREQD
DISCNTBASIS
DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD
EVENTDESC
Accounting-Entries
ACCRLCD
AMTTAG
DRCRINDICTR
TRNCD
NETINDICTR
MISHD
REVALPRGL
REVALLSGL
REVALRTCD
REVALTXNCD
HOLTREAT
REVALREQD
RATE_TYPE_INDICATOR
Advices
MSGTYP
DESC
GENTIME
SUPRS

- PRIOR
- CHGREQD

Role-To-Head-Mapping
- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Prod-Cust-Restrictions
- CATGLIS
- CLASCD
- Cust-Categories
  - CATGDSAW
  - DESCRIPTION
- Customers
  - CSTID
  - CUSTNAME
  - ALWD

Branch-Ccy-Restrictions
- CCYLST
- BRNLST
- CLASCD
- CLASDESC
- Branch-List
  - BRNDISALOW
  - BRNNAME
- Ccy-List
  - BGTDLCCY
  - CCYNAME

UDFDETAILS
- FLDNAM
- FLDVAL

Product-Mis-Details
- MISGRP
- POOLCD
- CSTCD1
- CSTCD2
- CSTCD4
- CSTCD5
- Default-Mis-Codes
  - MISCLS
  - MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	Indicates full Product details in FCUBS Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates Preferred Rate Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Time when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Portfolio-Product

Attribute	**Description**	
Name	Portfolio-Product	
Datatype		
Description	Product Portfolio Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFOLIOTYP

Attribute	**Description**	
Name	PFOLIOTYP	
Datatype	String	
Description	Indicates Portfolio Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CRPSACCFLG

Attribute	Description	
Name	CRPSACCFLG	
Datatype	String	
Description	Indicates Corpus Account Flag Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRWTHLDTXFLG

Attribute	Description	
Name	ACCRWTHLDTXFLG	
Datatype	String	
Description	Indicates Accrue Withholding Tax For Coupons Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STMTTXNREQFLG

Attribute	Description	
Name	STMTTXNREQFLG	
Datatype	String	
Description	Indicates Statement Of Transaction Reqd Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNFREQ

Attribute	Description	
Name	TXNFREQ	
Datatype	String	
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendment Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Detail Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Product Scheme
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.121.2.SP-AuthorizePortfolioProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Contains Input Only Request of Authorize Portfolio Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.121.3.SP-AuthorizePortfolioProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*
    - *INSPRDALW*
    - *TXT_CLASS_DESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*
- *TXNSTMTH*
- *CORPNTCEFLG*
- *CORPNOTCEDY*

- *CORPNOTCEDYTYP*
- *CORPAUTOLIQFLG*
- *RKYREQDFLG*
- *RKYPFOLIOID*
- *RKYPFOLIOCUST*
- *RKYPFOLIOCCY*
- *BKRGHTSFLG*
- *BKWRNTIVFLG*
- *TBDACCRFLG*
- *TBDACCRFREQ*
- *TBDACCRSTDY*
- *TBDACCRSTMTH*
- *LMTTRCKFRBNDS*
- *LMTTRCKFREQUITIES*
- *LMTTRCKFRRIGHTS*
- *LMTTRCKFRWRNTS*
- *LMTTRCKFRTBILLS*
- *RLZDREVLMETH*
- *RLZDREVLFLG*
- *RLZDREVLSTDY*
- *RLZDREVLSTMTH*
- *RLZDREVLFREQ*
- *ACCRTBDWTFLG*
- *ACCRPRMMETH*
- *ACCRDISCMETH*
- *WIIPDLPURINT*
- *LCOM*
- *EXRATTYP*
- *BNKRSACPTCE*
- *CNTRAHLDNGTYPE*
- *CNTRAHLDNGALWD*
- *STMTHLDNGREQFLG*
- *STMTHLDNGFREQ*
- *STMTHLDNGSTDY*
- *STMTHLDNGSTMTH*
- *STMTTXNSTDY*
- *CCYRATTYPDESC*

Product-Class-Link

- *CLASCD*
- *TXT_CLASS_DESC*
- *Class*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*

- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *RULEDESC*

Product-Scheme

- *PRDORMRKTCD*
- *SCHME*

Pfolioprod-Restrictions

- *SECPRDCD*
- *PRDDESC*

Pfolio-Prod-Secaccess

- *SECID*
- *PRDCD*
- *SECDESC*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*

- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
    - DESCRIPTION
  - Customers
    - CSTID
    - CUSTNAME
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - CLASDESC
  - Branch-List
    - BRNDISALOW
    - BRNNAME
  - Ccy-List
    - BGTDLCCY
    - CCYNAME
- UDFDETAILS
  - FLDNAM
  - FLDVAL
- Product-Mis-Details
  - MISGRP
  - POOLCD
  - CSTCD1
  - CSTCD2
  - CSTCD4
  - CSTCD5
  - Default-Mis-Codes
    - MISCLS
    - MISCD

FCUBS_ERROR_RESP

- ERROR
  - ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicate FCUBS Response Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description

Name	Cstms-Product-Full
Datatype	
Description	Indicate FCUBS Portfolio Product Full Response with Fields and their values.

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	**Description**	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PFOLIOTYP

Attribute	Description
Name	PFOLIOTYP
Datatype	String
Description	Indicates Portfolio Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String

Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRFLG

Attribute	**Description**	
Name	INTACCRFLG	
Datatype	String	
Description	Indicates Interest Accruals Allowed Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTACCRFREQ

Attribute	**Description**	
Name	INTACCRFREQ	
Datatype	String	
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	**Description**	
Name	INTACCRSTDY	
Datatype	Number	
Description	Indicates Interest Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRSTMTH

Attribute	**Description**
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendment Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Detail Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Product Scheme
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWIFTQLF

Attribute	Description	
Name	SWIFTQLF	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	**Description**	
Name	EVNTAPPLIDESC	
Datatype	String	
Description	Indicates Event Application Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	**Description**	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Branch Currency Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.121.4.SP-AuthorizePortfolioProduct-Res-PK-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *CHOICE*
  - *Cstms-Product-PK*
    - *PRDCD*
  - *Cstms-Product-IO*
    - *PRDCD*
- *FCUBS_ERROR_RESP*
  - *ERROR*
    - *ECODE*
    - *EDESC*
- *FCUBS_WARNING_RESP*
  - *WARNING*
    - *WCODE*
    - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	Contains Primary Key Response of Authorize Portfolio Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Contains Input Only Response of Authorize Portfolio Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.122.AuthorizeSecuritiesPortfolio

AuthorizeSecuritiesPortfolio

2.122.1.SP-AuthorizeSecuritiesPortfolio-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRDIS

Attribute	**Description**	
Name	ACRDIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRDCM

Attribute	**Description**	
Name	ACRDCM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRMD

Attribute	**Description**	
Name	ACRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	**Description**	
Name	ACRFD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTACC

Attribute	Description	
Name	CUSTACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCDS

Attribute	Description	
Name	CUSTACCDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASACBA

Attribute	Description	
Name	ASACBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,,A

TOP

PORTFSM

Attribute	Description	
Name	PORTFSM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description	
Name	PRDDSAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDSALDS

Attribute	Description	
Name	PRDDSALDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepfseac

Attribute	Description	
Name	Sepfseac	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	Description	
Name	SECID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECPRDCD

Attribute	Description

Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHSST

Attribute	Description
Name	AUTHSST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description

Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTN

Attribute	Description
Name	PARTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	**Description**	
Name	Sepma2	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description

Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.122.2.SP-AuthorizeSecuritiesPortfolio-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-IO*
    - *PORTFID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.122.3.SP-AuthorizeSecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN

BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID
  SKLC
Serth
  PORTFID

- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*

- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*

- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVSTM

Attribute	**Description**	
Name	REVSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REREV

Attribute	**Description**	
Name	REREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

REDVM

Attribute	**Description**	
Name	REDVM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,M,X,

TOP

LOCMBA

Attribute	**Description**	
Name	LOCMBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,D,H,A,</td></tr></table>

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,F,,M</td></tr></table>

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	B,F,,M

TOP

RIGHT

Attribute	Description	
Name	RIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

WARR

Attribute	Description	
Name	WARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	**Description**	
Name	INACRF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,D,Q,H,A,

TOP

INTACRSTD

Attribute	**Description**	
Name	INTACRSTD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACRM

Attribute	**Description**	
Name	INTACRM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRCD

Attribute	**Description**	
Name	EXRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	**Description**
Name	PRDDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFID

Attribute	**Description**
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POREF

Attribute	**Description**
Name	POREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	**Description**
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	**Description**	
Name	SHRTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTDS

Attribute	**Description**	
Name	PORTDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Seprskm

Attribute	**Description**	
Name	Seprskm	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLCID

Attribute	**Description**	
Name	SKLCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String

Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

MEDDS

Attribute	**Description**	
Name	MEDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description	
Name	REREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECCD

Attribute	Description	
Name	SECCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Acaae

Attribute	Description	
Name	Acaae	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRREF

Attribute	Description	
Name	TRREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ACBRN

Attribute	Description

Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description

Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	Description	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.122.4.SP-AuthorizeSecuritiesPortfolio-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-PK*
      - *PORTFID*
    - *Sepm-IO*
      - *PORTFID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-PK

Attribute	Description
Name	Sepm-PK
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.123.CloseSecuritiesPortfolio

CloseSecuritiesPortfolio

2.123.1.SP-CloseSecuritiesPortfolio-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	**Description**	
Name	INACCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTACC

Attribute	**Description**	
Name	CUSTACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACCDS

Attribute	**Description**	
Name	CUSTACCDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ASACBA

Attribute	**Description**	
Name	ASACBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,,A

TOP

PORTFSM

Attribute	**Description**	
Name	PORTFSM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,D,W,

TOP

BRIGHT

Attribute	Description	
Name	BRIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BWARRNT

Attribute	Description	
Name	BWARRNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

AULFC

Attribute	Description	
Name	AULFC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CRPACC

Attribute	Description	
Name	CRPACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description

Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHSST

Attribute	Description
Name	AUTHSST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description

Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTN

Attribute	Description
Name	PARTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	**Description**	
Name	Sepma2	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description

Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.123.2.SP-CloseSecuritiesPortfolio-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-IO*
    - *PORTFID*
    - *Misdetails*
      - *CONREFNO*
    - *TXNUDFDETAILS*
      - *FLDNAME*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.123.3.SP-CloseSecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN

BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID
  SKLC
Serth
  PORTFID

- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*

- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*

- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVSTM

Attribute	**Description**	
Name	REVSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REREV

Attribute	**Description**	
Name	REREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

REDVM

Attribute	**Description**	
Name	REDVM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,M,X,

TOP

LOCMBA

Attribute	**Description**	
Name	LOCMBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,D,H,A,</td></tr></table>

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,F,,M</td></tr></table>

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	B,F,,M

TOP

RIGHT

Attribute	Description	
Name	RIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

WARR

Attribute	Description	
Name	WARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description	
Name	FDACRME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	Description	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	**Description**	
Name	INACRF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,D,Q,H,A,

TOP

INTACRSTD

Attribute	**Description**	
Name	INTACRSTD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACRM

Attribute	**Description**	
Name	INTACRM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRCD

Attribute	**Description**	
Name	EXRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDS

Attribute	**Description**	
Name	PRDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POREF

Attribute	**Description**	
Name	POREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFTYP

Attribute	**Description**	
Name	PORTFTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	**Description**	
Name	SHRTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTDS

Attribute	**Description**	
Name	PORTDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Seprskm

Attribute	**Description**	
Name	Seprskm	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLCID

Attribute	**Description**	
Name	SKLCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,L,,H,A,R,S

TOP

AUTHSST

Attribute	**Description**	
Name	AUTHSST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,,A

TOP

RST

Attribute	**Description**	
Name	RST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONAUTH

Attribute	**Description**	
Name	ONAUTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MODN

Attribute	**Description**	
Name	MODN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

MEDDS

Attribute	**Description**	
Name	MEDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description

Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description

Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.123.4.SP-CloseSecuritiesPortfolio-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-PK*
      - *PORTFID*
    - *Sepm-IO*
      - *PORTFID*
      - *Misdetails*
        - *CONREFNO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-PK

Attribute	Description
Name	Sepm-PK
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.124.CreatePortfolioProduct

Creation of Securities Portfolio Product

2.124.1.SP-CreatePortfolioProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*

INSPRDALW
TXT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*

TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG
TBDACCRFREQ
TBDACCRSTDY
TBDACCRSTMTH
LMTTRCKFRBNDS
LMTTRCKFREQUITIES
LMTTRCKFRRIGHTS
LMTTRCKFRWRNTS
LMTTRCKFRTBILLS
RLZDREVLMETH
RLZDREVLFLG
RLZDREVLSTDY
RLZDREVLSTMTH
RLZDREVLFREQ
ACCRTBDWTFLG
ACCRPRMMETH
ACCRDISCMETH
WIIPDLPURINT
LCOM
EXRATTYP
BNKRSACPTCE
CNTRAHLDNGTYPE
CNTRAHLDNGALWD
STMTHLDNGREQFLG
STMTHLDNGFREQ
STMTHLDNGSTDY
STMTHLDNGSTMTH
STMTTXNSTDY
CCYRATTYPDESC
Product-Class-Link
CLASCD
TXT_CLASS_DESC
Class

COMP
STPASSN
TAXTYP
BORNBY
CASHOUTFLWINDI
NETCONSINDI
CONSPLUSMIN
SWFTQUAL
EVNTASSN
EVNTAPPLN
EVNTLIQDN
BASAMTTAG
DFLTRULE
DFLTWAIV
ALLWRULAMND
AMNDAFTRASSN
ALLWAMTAMND
AMNDAFTRAPPLN
RULEDESC
Product-Scheme
PRDORMRKTCD
SCHME
Pfolioprod-Restrictions
SECPRDCD
PRDDESC
Pfolio-Prod-Secaccess
SECID
PRDCD
SECDESC
ACCSALWDFLG
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL

- STPASOCIATN
- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS

PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
UDFDETAILS
FLDNAM
FLDVAL
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	This contains the Full details for cstms-product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates Preferred Rate Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Portfolio-Product

Attribute	**Description**	
Name	Portfolio-Product	
Datatype		
Description	Product Portfolio Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFOLIOTYP

Attribute	**Description**	
Name	PFOLIOTYP	
Datatype	String	
Description	Indicates Portfolio Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendment Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Detail Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Product Scheme
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description	
Name	ACCRLCD	
Datatype	String	
Description	Indicates the Role code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Branch Currency Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.124.2.SP-CreatePortfolioProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *INSPRDALW*
    - *Portfolio-Product*
      - *PFOLIOCOSTMTHD*
      - *ACCRPRMFLG*

ACCRDISCFLG
DPRACCRMETH
DPRACCRFREQ
DPRACCRSTDY
DPRACCRSTMTH
BKDPMETH
ACCRRDMPRMFLG
RPRACCRFLG
RPRACCRMETH
RPRACCRSTDY
RPRACCRSTMTH
FWDNPLACCRFLG
FWDNPLACCRMETH
FWDNPLACCRFREQ
FWDNPLACCRSTDY
FWDNPLACCRSTMTH
INTACCRFLG
INTACCRFREQ
INTACCRSTDY
INTACCRSTMTH
REVALFLG
REVALMETH
REVALFREQ
REVALSTDY
REVALSTMTH
UNSETDLRVLFLG
SHTPOSALWDFLG
CRPSACCFLG
ACCRWTHLDTXFLG
STMTTXNREQFLG
TXNFREQ
TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG
TBDACCRFREQ

TBDACCRSTDY
TBDACCRSTMTH
LMTTRCKFRBNDS
LMTTRCKFREQUITIES
LMTTRCKFRRIGHTS
LMTTRCKFRWRNTS
LMTTRCKFRTBILLS
RLZDREVLMETH
RLZDREVLFLG
RLZDREVLSTDY
RLZDREVLSTMTH
RLZDREVLFREQ
ACCRTBDWTFLG
ACCRPRMMETH
ACCRDISCMETH
WIIPDLPURINT
LCOM
EXRATTYP
BNKRSACPTCE
CNTRAHLDNGTYPE
CNTRAHLDNGALWD
STMTHLDNGREQFLG
STMTHLDNGFREQ
STMTHLDNGSTDY
STMTHLDNGSTMTH
STMTTXNSTDY
Product-Class-Link
Class
STPASSN
DFLTRULE
DFLTWAIV
ALLWRULAMND
AMNDAFTRASSN
ALLWAMTAMND
AMNDAFTRAPPLN
Pfolioprod-Restrictions
SECPRDCD
Pfolio-Prod-Secaccess
SECID
ACCSALWDFLG
Product-Charges
Charge-Details
SETTCCY
DFTWAIV

- ALWRULAMND
- AMNDAFTRASSOC
- ALWAMTAMND
- AMNDAFTRAPPL
- STPASOCIATN
- ADVCHG
- DISCACCRAPLB
- DISCNTBASIS
- DFTRULE
- COMPNT

Product-Events

- CLASCD
- Event-Details
  - EVNTCD
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Role-To-Head-Mapping

- CLASCD
- Mapping-Details
  - ACCTRL
  - ACCTHD
  - STAT

Prod-Cust-Restrictions

- CATGLIS
- CLASCD
- Cust-Categories

CATGDSAW
Customers
CSTID
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
UDFDETAILS
FLDNAM
FLDVAL
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates full Product Details in FCUBS Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDSTRTDT

Attribute	Description	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	Description	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	Description	
Name	PRDRMRKS	
Datatype	String	
Description	Indiactes Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NRMLRTVARI

Attribute	Description	
Name	NRMLRTVARI	
Datatype	Number	
Description	Indicates Normal Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	Description	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	Description	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	Description	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	Description	
Name	PRDGRPDESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSPRDALW

Attribute	Description	
Name	INSPRDALW	
Datatype	String	
Description	Indicates Instrument Product Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number

Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String

Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String
Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRSTMTH

Attribute	**Description**
Name	INTACCRSTMTH
Datatype	Number
Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	**Description**
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	**Description**
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ

Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description

Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W,

TOP

CORPAUTOLIQFLG

Attribute	Description
Name	CORPAUTOLIQFLG
Datatype	String
Description	Indicates Auto Liquidate For Corporate Actions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYREQDFLG

Attribute	Description
Name	RKYREQDFLG
Datatype	String
Description	Indicates Rekey For Authorization Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYPFOLIOID

Attribute	Description
Name	RKYPFOLIOID
Datatype	String
Description	Indicates Rekey Fields For Portfolio Identification Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCUST

Attribute	Description
Name	RKYPFOLIOCUST
Datatype	String
Description	Indicates Rekey Fields For Portfolio Customer Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description

Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String
Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number

Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description
Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number

Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Class

Attribute	Description
Name	Class
Datatype	
Description	Class Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Component Details Stop Association Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendment Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Pfolioprod-Restrictions

Attribute	Description
Name	Pfolioprod-Restrictions
Datatype	
Description	Security Restrictions
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Pfolio-Prod-Secaccess

Attribute	Description

Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Events

Attribute	**Description**	
Name	Product-Events	
Datatype		
Description	Product Events	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD

Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	**Description**	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	**Description**	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	**Description**	
Name	STAT	
Datatype	String	
Description	Indicates the status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String

Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description	
Name	CCYLST	
Datatype	String	
Description	Indicates Currency List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	Description	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	Description	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description

Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	**Description**	
Name	FLDNAM	
Datatype	String	
Description	Indicates the Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates the Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150
	minLength	0

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Product MIS Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description

Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.124.3.SP-CreatePortfolioProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*
    - *INSPRDALW*
    - *TXT_CLASS_DESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*
- *TXNSTMTH*
- *CORPNTCEFLG*
- *CORPNOTCEDY*

- *CORPNOTCEDYTYP*
- *CORPAUTOLIQFLG*
- *RKYREQDFLG*
- *RKYPFOLIOID*
- *RKYPFOLIOCUST*
- *RKYPFOLIOCCY*
- *BKRGHTSFLG*
- *BKWRNTIVFLG*
- *TBDACCRFLG*
- *TBDACCRFREQ*
- *TBDACCRSTDY*
- *TBDACCRSTMTH*
- *LMTTRCKFRBNDS*
- *LMTTRCKFREQUITIES*
- *LMTTRCKFRRIGHTS*
- *LMTTRCKFRWRNTS*
- *LMTTRCKFRTBILLS*
- *RLZDREVLMETH*
- *RLZDREVLFLG*
- *RLZDREVLSTDY*
- *RLZDREVLSTMTH*
- *RLZDREVLFREQ*
- *ACCRTBDWTFLG*
- *ACCRPRMMETH*
- *ACCRDISCMETH*
- *WIIPDLPURINT*
- *LCOM*
- *EXRATTYP*
- *BNKRSACPTCE*
- *CNTRAHLDNGTYPE*
- *CNTRAHLDNGALWD*
- *STMTHLDNGREQFLG*
- *STMTHLDNGFREQ*
- *STMTHLDNGSTDY*
- *STMTHLDNGSTMTH*
- *STMTTXNSTDY*
- *CCYRATTYPDESC*

Product-Class-Link

- *CLASCD*
- *TXT_CLASS_DESC*
- *Class*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*

- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *RULEDESC*

Product-Scheme

- *PRDORMRKTCD*
- *SCHME*

Pfolioprod-Restrictions

- *SECPRDCD*
- *PRDDESC*

Pfolio-Prod-Secaccess

- *SECID*
- *PRDCD*
- *SECDESC*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*

- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS
    - PRIOR
    - CHGREQD

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
    - DESCRIPTION
  - Customers
    - CSTID
    - CUSTNAME
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - CLASDESC
  - Branch-List
    - BRNDISALOW
    - BRNNAME
  - Ccy-List
    - BGTDLCCY
    - CCYNAME
- UDFDETAILS
  - FLDNAM
  - FLDVAL
- Product-Mis-Details
  - MISGRP
  - POOLCD
  - CSTCD1
  - CSTCD2
  - CSTCD4
  - CSTCD5
  - Default-Mis-Codes
    - MISCLS
    - MISCD

FCUBS_ERROR_RESP

- ERROR
  - ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description

Name	Cstms-Product-Full
Datatype	
Description	Indicates full Product details in FCUBS Response.

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	**Description**	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFOLIOTYP

Attribute	Description
Name	PFOLIOTYP
Datatype	String
Description	Indicates Portfolio Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String

Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRFLG

Attribute	**Description**	
Name	INTACCRFLG	
Datatype	String	
Description	Indicates Interest Accruals Allowed Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTACCRFREQ

Attribute	**Description**	
Name	INTACCRFREQ	
Datatype	String	
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	**Description**	
Name	INTACCRSTDY	
Datatype	Number	
Description	Indicates Interest Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRSTMTH

Attribute	**Description**
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description	Indicates Amend After Application Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Detail Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Scheme

Attribute	**Description**	
Name	Product-Scheme	
Datatype		
Description	Product Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	**Description**	
Name	EVNTAPPLIDESC	
Datatype	String	
Description	Indicates Event Application Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	**Description**	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.124.4.SP-CreatePortfolioProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-PK*
      - *PRDCD*
    - *Cstms-Product-IO*
      - *PRDCD*
      - *PRDTYP*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RATTYPPREFRD*
      - *PRDTYPDESC*
      - *PRDGRPDESC*
      - *INSPRDALW*

Portfolio-Product

- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*
- *TXNSTMTH*
- *CORPNTCEFLG*
- *CORPNOTCEDY*
- *CORPNOTCEDYTYP*
- *CORPAUTOLIQFLG*
- *RKYREQDFLG*
- *RKYPFOLIOID*
- *RKYPFOLIOCUST*
- *RKYPFOLIOCCY*
- *BKRGHTSFLG*

- BKWRNTIVFLG
- TBDACCRFLG
- TBDACCRFREQ
- TBDACCRSTDY
- TBDACCRSTMTH
- LMTTRCKFRBNDS
- LMTTRCKFREQUITIES
- LMTTRCKFRRIGHTS
- LMTTRCKFRWRNTS
- LMTTRCKFRTBILLS
- RLZDREVLMETH
- RLZDREVLFLG
- RLZDREVLSTDY
- RLZDREVLSTMTH
- RLZDREVLFREQ
- ACCRTBDWTFLG
- ACCRPRMMETH
- ACCRDISCMETH
- WIIPDLPURINT
- LCOM
- EXRATTYP
- BNKRSACPTCE
- CNTRAHLDNGTYPE
- CNTRAHLDNGALWD
- STMTHLDNGREQFLG
- STMTHLDNGFREQ
- STMTHLDNGSTDY
- STMTHLDNGSTMTH
- STMTTXNSTDY

Product-Class-Link

- Class
  - STPASSN
  - DFLTRULE
  - DFLTWAIV
  - ALLWRULAMND
  - AMNDAFTRASSN
  - ALLWAMTAMND
  - AMNDAFTRAPPLN

Pfolioprod-Restrictions

- SECPRDCD

Pfolio-Prod-Secaccess

- SECID
- ACCSALWDFLG

Product-Charges

- *Charge-Details*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *DISCACCRAPLB*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*
- *Product-Events*
  - *CLASCD*
  - *Event-Details*
    - *EVNTCD*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*
      - *MISHD*
      - *REVALPRGL*
      - *REVALLSGL*
      - *REVALRTCD*
      - *REVALTXNCD*
      - *HOLTREAT*
      - *REVALREQD*
      - *RATE_TYPE_INDICATOR*
    - *Advices*
      - *MSGTYP*
      - *GENTIME*
      - *SUPRS*
      - *PRIOR*
      - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *Mapping-Details*
    - *ACCTRL*
    - *ACCTHD*
    - *STAT*
- *Prod-Cust-Restrictions*

CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
UDFDETAILS
FLDNAM
FLDVAL
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	Indicates Product Code.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates Product details.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates Preferred Rate Type
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	Description	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	Description	
Name	PRDGRPDESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INSPRDALW

Attribute	Description	
Name	INSPRDALW	
Datatype	String	
Description	Indicates Instrument Product Allowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

Portfolio-Product

Attribute	Description	
Name	Portfolio-Product	
Datatype		
Description	Product Portfolio Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Class

Attribute	Description
Name	Class
Datatype	
Description	Class Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Component Details Stop Association Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description	Indicates Default Waiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description	Indicates Amend After Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Pfolioprod-Restrictions

Attribute	Description
Name	Pfolioprod-Restrictions
Datatype	
Description	Security Restrictions
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID

Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	**Description**	
Name	DISCNTBASIS	
Datatype	String	
Description	Indicates Discount Basis Inflow : I Outflow : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	Product Events

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Event-Details

Attribute	**Description**	
Name	Event-Details	
Datatype		
Description	Indicates Event Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

EVNTCD

Attribute	**Description**	
Name	EVNTCD	
Datatype	String	
Description	Indicates the event code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Accounting-Entries

Attribute	**Description**	
Name	Accounting-Entries	
Datatype		
Description	Accounting Entry Details for Events	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR

Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	**Description**	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	**Description**	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	**Description**	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers

Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	Description	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description

Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	**Description**	
Name	MISTYP	
Datatype	String	
Description	Indicates MIS type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

KYID

Attribute	**Description**	
Name	KYID	
Datatype	String	
Description	Indicates Key ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS error list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.125.CreateSecuritiesPortfolio

CreateSecuritiesPortfolio

2.125.1.SP-CreateSecuritiesPortfolio-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	**Description**	
Name	INACCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,,A

TOP

PORTFSM

Attribute	Description
Name	PORTFSM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description	
Name	PRDDSAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDSALDS

Attribute	Description	
Name	PRDDSALDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepfseac

Attribute	Description	
Name	Sepfseac	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	Description	
Name	SECID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECPRDCD

Attribute	Description

Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHSST

Attribute	Description
Name	AUTHSST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description

Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTN

Attribute	Description
Name	PARTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	**Description**	
Name	Sepma2	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description

Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

OVMSG

Attribute	**Description**	
Name	OVMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.125.2.SP-CreateSecuritiesPortfolio-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-IO*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN
CURR

CUST
SHTN
CUSTACBR
CUSTACC
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Seprskm
  SKLCID
  SKLC
Serth
  RLTH
  RLTHDS
Serth2
  SECPRD
  SECDS
  RLTHDT
  RLTHDSD
Serth3
  INSEID
  INTSEDS
  RLTHCL
  RLTHDSC
Sepfsepm
  SPSECID
  SPPRCD

Sesepd

- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVDS*
- *SECCD*

Cscea

- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTLANG*
- *CHRD*
- *ADVDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,D,A,</td></tr></table>

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVSTM

Attribute	Description
Name	REVSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	**Description**	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	**Description**	
Name	FDACRME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRCD

Attribute	**Description**	
Name	EXRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

RS

Attribute	**Description**	
Name	RS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MODN

Attribute	**Description**	
Name	MODN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNID

Attribute	**Description**	
Name	FUNID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHTN

Attribute	**Description**	
Name	SHTN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACBR

Attribute	**Description**	
Name	CUSTACBR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACC

Attribute	**Description**	
Name	CUSTACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ASACBA

Attribute	**Description**	
Name	ASACBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	N,,A

TOP

PORTFSM

Attribute	Description	
Name	PORTFSM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,D,W,

TOP

BRIGHT

Attribute	Description	
Name	BRIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BWARRNT

Attribute	Description	
Name	BWARRNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

AULFC

Attribute	Description	
Name	AULFC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>W,C,</td></tr></table>

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRDT

Attribute	**Description**	
Name	ACRDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRFR

Attribute	**Description**	
Name	ACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,D,Q,H,A,

TOP

ACRSDAY

Attribute	**Description**	
Name	ACRSDAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACRSM

Attribute	**Description**	
Name	ACRSM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description

Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ADVDS

Attribute	Description
Name	ADVDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REEVSN

Attribute	**Description**	
Name	REEVSN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVVALDT

Attribute	**Description**	
Name	EVVALDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REREFNO

Attribute	**Description**	
Name	REREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECCD

Attribute	**Description**	
Name	SECCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.125.3.SP-CreateSecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN

BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID
  SKLC
Serth
  PORTFID

- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*

- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*

- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVSTM

Attribute	**Description**	
Name	REVSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REREV

Attribute	**Description**	
Name	REREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

REDVM

Attribute	**Description**	
Name	REDVM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,M,X,

TOP

LOCMBA

Attribute	**Description**	
Name	LOCMBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,D,H,A,</td></tr></table>

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,F,,M</td></tr></table>

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	B,F,,M

TOP

RIGHT

Attribute	Description	
Name	RIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

WARR

Attribute	Description	
Name	WARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	**Description**	
Name	INACRF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,D,Q,H,A,

TOP

INTACRSTD

Attribute	**Description**	
Name	INTACRSTD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACRM

Attribute	**Description**	
Name	INTACRM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRCD

Attribute	**Description**	
Name	EXRCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDS

Attribute	**Description**	
Name	PRDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

POREF

Attribute	**Description**	
Name	POREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFTYP

Attribute	**Description**	
Name	PORTFTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	**Description**	
Name	SHRTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTDS

Attribute	**Description**	
Name	PORTDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Seprskm

Attribute	**Description**	
Name	Seprskm	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLCID

Attribute	**Description**	
Name	SKLCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,L,,H,A,R,S

TOP

AUTHSST

Attribute	**Description**	
Name	AUTHSST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,,A

TOP

RST

Attribute	**Description**	
Name	RST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONAUTH

Attribute	**Description**	
Name	ONAUTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MODN

Attribute	**Description**	
Name	MODN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute**: minOccurs; **Description**: 0
Restrictions	**Restrictions**: maxLength; **Description**: 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

MEDDS

Attribute	**Description**	
Name	MEDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description

Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Csco

Attribute	**Description**	
Name	Csco	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

OVMSG

Attribute	**Description**	
Name	OVMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**

Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	**Description**	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	**Description**	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	**Description**	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.125.4.SP-CreateSecuritiesPortfolio-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-PK*
      - *PORTFID*
    - *Sepm-IO*
      - *ACCRHTB*
      - *STHDR*
      - *STATEMENTHOLDFREQUENCY*
      - *STHSD*
      - *STATEMENTSTARTMONTH*
      - *PRVHSN*
      - *STTXR*
      - *TXNS_STATEMENT_DAY*
      - *STTXSM*
      - *PREVSSN*
      - *ACCRP*
      - *ACCRPM*
      - *ACRDIS*
      - *ACRDCM*
      - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP

PORTFDS
BRN
CURR
CUST
SHTN
CUSTACBR
CUSTACC
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Seprskm
  SKLCID
  SKLC
Serth
  RLTH
  RLTHDS
Serth2
  SECPRD
  SECDS
  RLTHDT
  RLTHDSD
Serth3
  INSEID
  INTSEDS
  RLTHCL
  RLTHDSC

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVDS*
- *SECCD*

Cscea

- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*

- PRTLANG
- CHRD
- ADVDS

Sepel

- MOD
- CNTREF
- MKID
- MKDTSTMP
- CHKID
- CHKDTSTMP
- EVSQNO
- EVDT
- EVCD
- CONTST
- AUTHST
- NVIND
- REEVSN
- EVVALDT
- REREFNO
- SECCD
- Acaae
  - TRREF
  - ACBRN
  - ACN
  - ACCY
  - DRCIN
  - TRCD
  - FCAMT
  - EXRT
  - LCAMT
  - TRDT
  - VALDT
- Csco
  - OVMSG

Misdetails

- CONREFNO
- LATESN
- MISGRP
- RELACC
- RELETED_REFERENCE
- MISHEAD
- RATEFLG
- POOLCD
- REFINANCE_RATE

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails

Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-PK

Attribute	Description
Name	Sepm-PK
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVSTM

Attribute	Description
Name	REVSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,M,X,</td></tr></table>

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	**Description**	
Name	FDACRME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACBR

Attribute	**Description**	
Name	CUSTACBR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACC

Attribute	**Description**	
Name	CUSTACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ASACBA

Attribute	**Description**	
Name	ASACBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,,A

TOP

PORTFSM

Attribute	**Description**	
Name	PORTFSM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	L,F,D,W,

TOP

BRIGHT

Attribute	Description	
Name	BRIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BWARRNT

Attribute	Description	
Name	BWARRNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

AULFC

Attribute	Description	
Name	AULFC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CRPACC

Attribute	Description	
Name	CRPACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>W,C,</td></tr></table>

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRFR

Attribute	**Description**	
Name	ACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,D,Q,H,A,

TOP

ACRSDAY

Attribute	**Description**	
Name	ACRSDAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACRSM

Attribute	**Description**	
Name	ACRSM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECALL

Attribute	**Description**	
Name	SECALL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfseac

Attribute	Description

Name	Sepfseac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Cscea

Attribute	Description

Name	Cscea
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>0</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description

Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TRCD

Attribute	**Description**
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	**Description**
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	**Description**
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	**Description**
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	**Description**
Name	TRDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,X,F,P</td></tr></table>

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails

Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.126.DeletePortfolioProduct

Deletion of Securities Portfolio Product

2.126.1.SP-DeletePortfolioProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*

INSPRDALW
TXT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*

TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG
TBDACCRFREQ
TBDACCRSTDY
TBDACCRSTMTH
LMTTRCKFRBNDS
LMTTRCKFREQUITIES
LMTTRCKFRRIGHTS
LMTTRCKFRWRNTS
LMTTRCKFRTBILLS
RLZDREVLMETH
RLZDREVLFLG
RLZDREVLSTDY
RLZDREVLSTMTH
RLZDREVLFREQ
ACCRTBDWTFLG
ACCRPRMMETH
ACCRDISCMETH
WIIPDLPURINT
LCOM
EXRATTYP
BNKRSACPTCE
CNTRAHLDNGTYPE
CNTRAHLDNGALWD
STMTHLDNGREQFLG
STMTHLDNGFREQ
STMTHLDNGSTDY
STMTHLDNGSTMTH
STMTTXNSTDY
CCYRATTYPDESC
Product-Class-Link
CLASCD
TXT_CLASS_DESC
Class

COMP
STPASSN
TAXTYP
BORNBY
CASHOUTFLWINDI
NETCONSINDI
CONSPLUSMIN
SWFTQUAL
EVNTASSN
EVNTAPPLN
EVNTLIQDN
BASAMTTAG
DFLTRULE
DFLTWAIV
ALLWRULAMND
AMNDAFTRASSN
ALLWAMTAMND
AMNDAFTRAPPLN
RULEDESC
Product-Scheme
PRDORMRKTCD
SCHME
Pfolioprod-Restrictions
SECPRDCD
PRDDESC
Pfolio-Prod-Secaccess
SECID
PRDCD
SECDESC
ACCSALWDFLG
Product-Charges
Charge-Details
CHGTYP
THRDPTYTY
DRCRTYPE
NTCNSINDI
NETCONSPLSMINS
SWIFTQLF
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND
AMNDAFTRAPPL

- STPASOCIATN
- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS

PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
UDFDETAILS
FLDNAM
FLDVAL
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	Indicates full Product details.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates Preferred Rate Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Time when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Portfolio-Product

Attribute	**Description**	
Name	Portfolio-Product	
Datatype		
Description	Product Portfolio Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFOLIOTYP

Attribute	**Description**	
Name	PFOLIOTYP	
Datatype	String	
Description	Indicates Portfolio Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CRPSACCFLG

Attribute	Description	
Name	CRPSACCFLG	
Datatype	String	
Description	Indicates Corpus Account Flag Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRWTHLDTXFLG

Attribute	Description	
Name	ACCRWTHLDTXFLG	
Datatype	String	
Description	Indicates Accrue Withholding Tax For Coupons Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STMTTXNREQFLG

Attribute	Description	
Name	STMTTXNREQFLG	
Datatype	String	
Description	Indicates Statement Of Transaction Reqd Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNFREQ

Attribute	Description	
Name	TXNFREQ	
Datatype	String	
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description	Indicates Amend After Application Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Detail Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Scheme

Attribute	**Description**	
Name	Product-Scheme	
Datatype		
Description	Product Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Product Events	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.126.2.SP-DeletePortfolioProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates Product Code in FCUBS Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.126.3.SP-DeletePortfolioProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*
    - *INSPRDALW*
    - *TXT_CLASS_DESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*
- *TXNSTMTH*
- *CORPNTCEFLG*
- *CORPNOTCEDY*

- *CORPNOTCEDYTYP*
- *CORPAUTOLIQFLG*
- *RKYREQDFLG*
- *RKYPFOLIOID*
- *RKYPFOLIOCUST*
- *RKYPFOLIOCCY*
- *BKRGHTSFLG*
- *BKWRNTIVFLG*
- *TBDACCRFLG*
- *TBDACCRFREQ*
- *TBDACCRSTDY*
- *TBDACCRSTMTH*
- *LMTTRCKFRBNDS*
- *LMTTRCKFREQUITIES*
- *LMTTRCKFRRIGHTS*
- *LMTTRCKFRWRNTS*
- *LMTTRCKFRTBILLS*
- *RLZDREVLMETH*
- *RLZDREVLFLG*
- *RLZDREVLSTDY*
- *RLZDREVLSTMTH*
- *RLZDREVLFREQ*
- *ACCRTBDWTFLG*
- *ACCRPRMMETH*
- *ACCRDISCMETH*
- *WIIPDLPURINT*
- *LCOM*
- *EXRATTYP*
- *BNKRSACPTCE*
- *CNTRAHLDNGTYPE*
- *CNTRAHLDNGALWD*
- *STMTHLDNGREQFLG*
- *STMTHLDNGFREQ*
- *STMTHLDNGSTDY*
- *STMTHLDNGSTMTH*
- *STMTTXNSTDY*
- *CCYRATTYPDESC*

Product-Class-Link

- *CLASCD*
- *TXT_CLASS_DESC*
- *Class*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*

- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *RULEDESC*

Product-Scheme

- *PRDORMRKTCD*
- *SCHME*

Pfolioprod-Restrictions

- *SECPRDCD*
- *PRDDESC*

Pfolio-Prod-Secaccess

- *SECID*
- *PRDCD*
- *SECDESC*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*

- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
    - DESCRIPTION
  - Customers
    - CSTID
    - CUSTNAME
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - CLASDESC
  - Branch-List
    - BRNDISALOW
    - BRNNAME
  - Ccy-List
    - BGTDLCCY
    - CCYNAME
- UDFDETAILS
  - FLDNAM
  - FLDVAL
- Product-Mis-Details
  - MISGRP
  - POOLCD
  - CSTCD1
  - CSTCD2
  - CSTCD4
  - CSTCD5
  - Default-Mis-Codes
    - MISCLS
    - MISCD

FCUBS_ERROR_RESP

- ERROR
  - ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description

Name	Cstms-Product-Full
Datatype	
Description	This contains the full details of the Product.

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	**Description**	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PFOLIOTYP

Attribute	Description
Name	PFOLIOTYP
Datatype	String
Description	Indicates Portfolio Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String

Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRFLG

Attribute	**Description**	
Name	INTACCRFLG	
Datatype	String	
Description	Indicates Interest Accruals Allowed Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTACCRFREQ

Attribute	**Description**	
Name	INTACCRFREQ	
Datatype	String	
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	**Description**	
Name	INTACCRSTDY	
Datatype	Number	
Description	Indicates Interest Accrual Start Day	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRSTMTH

Attribute	**Description**
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description	Indicates Amend After Application Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Detail Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Scheme

Attribute	**Description**	
Name	Product-Scheme	
Datatype		
Description	Product Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Product Events	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description	
Name	ACCRLCD	
Datatype	String	
Description	Indicates the Role code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	Description	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Branch Currency Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	This contains the error response.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.126.4.SP-DeletePortfolioProduct-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Cstms-Product-PK
PRDCD
Cstms-Product-IO
PRDCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	Contain Primary Key Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Contain Primary Key Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contain FCUBS Error List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contain FCUBS Warning List.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.127.DeleteSecuritiesPortfolio

DeleteSecuritiesPortfolio

2.127.1.SP-DeleteSecuritiesPortfolio-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRDIS

Attribute	**Description**	
Name	ACRDIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRDCM

Attribute	**Description**	
Name	ACRDCM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRMD

Attribute	**Description**	
Name	ACRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	**Description**	
Name	ACRFD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUST

Attribute	**Description**	
Name	CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHTN

Attribute	**Description**	
Name	SHTN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACBR

Attribute	**Description**	
Name	CUSTACBR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACBRDS

Attribute	**Description**	
Name	CUSTACBRDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,,A

TOP

PORTFSM

Attribute	Description
Name	PORTFSM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description

Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHSST

Attribute	Description
Name	AUTHSST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description

Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTN

Attribute	Description
Name	PARTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	**Description**	
Name	Sepma2	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACN

Attribute	Description

Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	Description	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	Description	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.127.2.SP-DeleteSecuritiesPortfolio-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-IO*
    - *PORTFID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.127.3.SP-DeleteSecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN

BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID
  SKLC
Serth
  PORTFID

- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*

- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*

- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,D,H,A,</td></tr></table>

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,F,,M</td></tr></table>

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	B,F,,M

TOP

RIGHT

Attribute	Description	
Name	RIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

WARR

Attribute	Description	
Name	WARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	**Description**
Name	PRDDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFID

Attribute	**Description**
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POREF

Attribute	**Description**
Name	POREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	**Description**
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	**Description**	
Name	SHRTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTDS

Attribute	**Description**	
Name	PORTDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Seprskm

Attribute	**Description**	
Name	Seprskm	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLCID

Attribute	**Description**	
Name	SKLCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

MEDDS

Attribute	**Description**	
Name	MEDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description

Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description

Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	**Description**	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.127.4.SP-DeleteSecuritiesPortfolio-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-PK*
      - *PORTFID*
    - *Sepm-IO*
      - *PORTFID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-PK

Attribute	Description
Name	Sepm-PK
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.128.ModifyPortfolioProduct

Modification of Securities Portfolio Product

2.128.1.SP-ModifyPortfolioProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*

INSPRDALW
TXT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*

TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG
TBDACCRFREQ
TBDACCRSTDY
TBDACCRSTMTH
LMTTRCKFRBNDS
LMTTRCKFREQUITIES
LMTTRCKFRRIGHTS
LMTTRCKFRWRNTS
LMTTRCKFRTBILLS
RLZDREVLMETH
RLZDREVLFLG
RLZDREVLSTDY
RLZDREVLSTMTH
RLZDREVLFREQ
ACCRTBDWTFLG
ACCRPRMMETH
ACCRDISCMETH
WIIPDLPURINT
LCOM
EXRATTYP
BNKRSACPTCE
CNTRAHLDNGTYPE
CNTRAHLDNGALWD
STMTHLDNGREQFLG
STMTHLDNGFREQ
STMTHLDNGSTDY
STMTHLDNGSTMTH
STMTTXNSTDY
CCYRATTYPDESC
Product-Class-Link
CLASCD
TXT_CLASS_DESC
Class

- *COMP*
- *STPASSN*
- *TAXTYP*
- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *RULEDESC*

Product-Scheme

- *PRDORMRKTCD*
- *SCHME*

Pfolioprod-Restrictions

- *SECPRDCD*
- *PRDDESC*

Pfolio-Prod-Secaccess

- *SECID*
- *PRDCD*
- *SECDESC*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*

- STPASOCIATN
- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS

- PRIOR
- CHGREQD

Role-To-Head-Mapping
- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC

Prod-Cust-Restrictions
- CATGLIS
- CLASCD
- Cust-Categories
  - CATGDSAW
  - DESCRIPTION
- Customers
  - CSTID
  - CUSTNAME
  - ALWD

Branch-Ccy-Restrictions
- CCYLST
- BRNLST
- CLASCD
- CLASDESC
- Branch-List
  - BRNDISALOW
  - BRNNAME
- Ccy-List
  - BGTDLCCY
  - CCYNAME

UDFDETAILS
- FLDNAM
- FLDVAL

Product-Mis-Details
- MISGRP
- POOLCD
- CSTCD1
- CSTCD2
- CSTCD4
- CSTCD5
- Default-Mis-Codes
  - MISCLS
  - MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Request Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	Indicates FCUBS Full Request to Modify the Portfolio Product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indiactes Product Remarks
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates Preferred Rate Type
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates Product Type Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC

Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Specifies the User Id who has created\last modified the record.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates Date and Time when the User has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the User Id who has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description	Indicates Transaction Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Portfolio-Product

Attribute	**Description**	
Name	Portfolio-Product	
Datatype		
Description	Product Portfolio Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFOLIOTYP

Attribute	**Description**	
Name	PFOLIOTYP	
Datatype	String	
Description	Indicates Portfolio Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,W,

TOP

CORPAUTOLIQFLG

Attribute	**Description**	
Name	CORPAUTOLIQFLG	
Datatype	String	
Description	Indicates Auto Liquidate For Corporate Actions Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYREQDFLG

Attribute	**Description**	
Name	RKYREQDFLG	
Datatype	String	
Description	Indicates Rekey For Authorization Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RKYPFOLIOID

Attribute	**Description**	
Name	RKYPFOLIOID	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Identification Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCUST

Attribute	**Description**	
Name	RKYPFOLIOCUST	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Customer Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Class

Attribute	Description
Name	Class
Datatype	
Description	Class Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Component Details Stop Association Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	Indicates Tax Type Withholding "W", Others "O"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description	Indicates Amend After Application Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Detail Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Scheme

Attribute	**Description**	
Name	Product-Scheme	
Datatype		
Description	Product Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	Indicates Component Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	**Description**	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	**Description**	
Name	MSGTYP	
Datatype	String	
Description	Indicates the message type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Specifies the message description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

GENTIME

Attribute	**Description**	
Name	GENTIME	
Datatype	String	
Description	Indicates generation time.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.128.2.SP-ModifyPortfolioProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *CLASCD*
    - *INSPRDALW*
    - *MODNO*
    - *Portfolio-Product*
      - *PFOLIOCOSTMTHD*
      - *ACCRPRMFLG*
      - *ACCRDISCFLG*

DPRACCRMETH
DPRACCRFREQ
DPRACCRSTDY
DPRACCRSTMTH
BKDPMETH
ACCRRDMPRMFLG
RPRACCRFLG
RPRACCRMETH
RPRACCRSTDY
RPRACCRSTMTH
FWDNPLACCRFLG
FWDNPLACCRMETH
FWDNPLACCRFREQ
FWDNPLACCRSTDY
FWDNPLACCRSTMTH
INTACCRFLG
INTACCRFREQ
INTACCRSTDY
INTACCRSTMTH
REVALFLG
REVALMETH
REVALFREQ
REVALSTDY
REVALSTMTH
UNSETDLRVLFLG
SHTPOSALWDFLG
SHTHLDALWDFLG
CRPSACCFLG
ACCRWTHLDTXFLG
STMTTXNREQFLG
TXNFREQ
TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
SECALWDFLG
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG

- *TBDACCRFREQ*
- *TBDACCRSTDY*
- *TBDACCRSTMTH*
- *LMTTRCKFRBNDS*
- *LMTTRCKFREQUITIES*
- *LMTTRCKFRRIGHTS*
- *LMTTRCKFRWRNTS*
- *LMTTRCKFRTBILLS*
- *CORPACTREQD*
- *TRCKACCRINT*
- *RLZDREVLMETH*
- *RLZDREVLFLG*
- *RLZDREVLSTDY*
- *RLZDREVLSTMTH*
- *RLZDREVLFREQ*
- *ACCRTBDWTFLG*
- *ACCRPRMMETH*
- *ACCRDISCMETH*
- *WIIPDLPURINT*
- *LCOM*
- *EXRATTYP*
- *BNKRSACPTCE*
- *CNTRAHLDNGTYPE*
- *CNTRAHLDNGALWD*
- *STMTHLDNGREQFLG*
- *STMTHLDNGFREQ*
- *STMTHLDNGSTDY*
- *STMTHLDNGSTMTH*
- *STMTTXNSTDY*

Product-Class-Link

- *CLASCD*
- *Class*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*
  - *EVNTAPPLN*
  - *EVNTLIQDN*
  - *BASAMTTAG*

- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*

Pfolioprod-Restrictions

- *SECPRDCD*

Pfolio-Prod-Secaccess

- *SECID*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *DFTRULE*
  - *COMPNT*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
  - *Advices*
    - *MSGTYP*
    - *SUPRS*
    - *PRIOR*

CHGREQD

Role-To-Head-Mapping

CLASCD

Mapping-Details

ACCTRL

ACCTHD

STAT

Prod-Cust-Restrictions

CATGLIS

CLASCD

Cust-Categories

CATGDSAW

Customers

CSTID

ALWD

Branch-Ccy-Restrictions

CCYLST

BRNLST

CLASCD

Branch-List

BRNDISALOW

Ccy-List

BGTDLCCY

SOLDCCY

UDFDETAILS

FLDNAM

FLDVAL

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates full Product details in FCUBS Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	Description	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	Description	
Name	PRDRMRKS	
Datatype	String	
Description	Indiactes Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NRMLRTVARI

Attribute	Description	
Name	NRMLRTVARI	
Datatype	Number	
Description	Indicates Normal Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXRTVARI

Attribute	Description	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	Description	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

INSPRDALW

Attribute	Description	
Name	INSPRDALW	
Datatype	String	
Description	Indicates Instrument Product Allowed Disallowed "D"; Allowed "A".	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number

Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String

Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String
Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACCRSTMTH

Attribute	**Description**
Name	INTACCRSTMTH
Datatype	Number
Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	**Description**
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	**Description**
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	**Description**
Name	REVALFREQ

Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTHLDALWDFLG

Attribute	Description
Name	SHTHLDALWDFLG
Datatype	String
Description	Indicates Short Holding Allowed Flag yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description

Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W,

TOP

CORPAUTOLIQFLG

Attribute	Description
Name	CORPAUTOLIQFLG
Datatype	String
Description	Indicates Auto Liquidate For Corporate Actions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYREQDFLG

Attribute	Description
Name	RKYREQDFLG
Datatype	String
Description	Indicates Rekey For Authorization Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYPFOLIOID

Attribute	Description
Name	RKYPFOLIOID
Datatype	String
Description	Indicates Rekey Fields For Portfolio Identification Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCUST

Attribute	Description
Name	RKYPFOLIOCUST
Datatype	String
Description	Indicates Rekey Fields For Portfolio Customer Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALWDFLG

Attribute	Description
Name	SECALWDFLG
Datatype	String
Description	Indicates Security Allowed Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description

Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description

Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String
Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates Corporate Action Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TRCKACCRINT

Attribute	Description
Name	TRCKACCRINT
Datatype	String
Description	Indicates Track Accrued Intereset
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Class

Attribute	Description
Name	Class
Datatype	
Description	Class Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Component Details Stop Association Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	Indicates Tax Type Withholding "W", Others "O"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV

Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendment Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Pfolioprod-Restrictions

Attribute	Description
Name	Pfolioprod-Restrictions
Datatype	
Description	Security Restrictions
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String

Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description

Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD

Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String

Description	Indicates accounting role.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restriction
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID

Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	Description

Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.128.3.SP-ModifyPortfolioProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRDGRPDESC*
    - *CLASCD*
    - *INSPRDALW*
    - *TXT_CLASS_DESC*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*
- *TXNSTMTH*
- *CORPNTCEFLG*
- *CORPNOTCEDY*

- CORPNOTCEDYTYP
- CORPAUTOLIQFLG
- RKYREQDFLG
- RKYPFOLIOID
- RKYPFOLIOCUST
- RKYPFOLIOCCY
- BKRGHTSFLG
- BKWRNTIVFLG
- TBDACCRFLG
- TBDACCRFREQ
- TBDACCRSTDY
- TBDACCRSTMTH
- LMTTRCKFRBNDS
- LMTTRCKFREQUITIES
- LMTTRCKFRRIGHTS
- LMTTRCKFRWRNTS
- LMTTRCKFRTBILLS
- RLZDREVLMETH
- RLZDREVLFLG
- RLZDREVLSTDY
- RLZDREVLSTMTH
- RLZDREVLFREQ
- ACCRTBDWTFLG
- ACCRPRMMETH
- ACCRDISCMETH
- WIIPDLPURINT
- LCOM
- EXRATTYP
- BNKRSACPTCE
- CNTRAHLDNGTYPE
- CNTRAHLDNGALWD
- STMTHLDNGREQFLG
- STMTHLDNGFREQ
- STMTHLDNGSTDY
- STMTHLDNGSTMTH
- STMTTXNSTDY
- CCYRATTYPDESC

Product-Class-Link

- CLASCD
- TXT_CLASS_DESC
- Class
  - COMP
  - STPASSN
  - TAXTYP

- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *RULEDESC*

Product-Scheme

- *PRDORMRKTCD*
- *SCHME*

Pfolioprod-Restrictions

- *SECPRDCD*
- *PRDDESC*

Pfolio-Prod-Secaccess

- *SECID*
- *PRDCD*
- *SECDESC*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*

- *DISCACCRAPLB*
- *PROPREQD*
- *DISCNTBASIS*
- *DFTRULE*
- *COMPNT*
- *EVNTFRASSC*
- *EVNTFRAPPL*
- *EVNTFRLIQ*
- *BASISAMNTTAG*
- *BASICAMTTGDESC*
- *ACCRREQD*
- *COMPNENTDESC*
- *EVNTASSCTDESC*
- *EVNTAPPLIDESC*
- *EVNTLIQDDESC*
- *RULDESC*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- CLASCD
- CLASDESC
- Mapping-Details
  - ACCTRL
  - ROLDESC
  - ACCTHD
  - GLDESC
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
    - DESCRIPTION
  - Customers
    - CSTID
    - CUSTNAME
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - CLASDESC
  - Branch-List
    - BRNDISALOW
    - BRNNAME
  - Ccy-List
    - BGTDLCCY
    - CCYNAME
- UDFDETAILS
  - FLDNAM
  - FLDVAL
- Product-Mis-Details
  - MISGRP
  - POOLCD
  - CSTCD1
  - CSTCD2
  - CSTCD4
  - CSTCD5
  - Default-Mis-Codes
    - MISCLS
    - MISCD

FCUBS_ERROR_RESP

- ERROR
  - ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Contain FCUBS Complete Response of Portfolio Product.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Cstms-Product-Full

Attribute	Description

Name	Cstms-Product-Full
Datatype	
Description	Indicate FCUBS Full Response Fields and their Values.

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	Description	
Name	PRDTYP	
Datatype	String	
Description	Indicates Product Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description	Indicates Product Description	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description	Indicates Product Slogan	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description	Indicates Product Group	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDSTRTDT

Attribute	Description	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates Product Start Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	Description	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	Description	
Name	PRDRMRKS	
Datatype	String	
Description	Indiactes Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates Normal Rate Variance

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	**Description**	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	Indicates Product Group Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number

Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PFOLIOTYP

Attribute	Description
Name	PFOLIOTYP
Datatype	String
Description	Indicates Portfolio Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String

Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W,

TOP

CORPAUTOLIQFLG

Attribute	Description
Name	CORPAUTOLIQFLG
Datatype	String
Description	Indicates Auto Liquidate For Corporate Actions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYREQDFLG

Attribute	Description
Name	RKYREQDFLG
Datatype	String
Description	Indicates Rekey For Authorization Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYPFOLIOID

Attribute	Description
Name	RKYPFOLIOID
Datatype	String
Description	Indicates Rekey Fields For Portfolio Identification Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCUST

Attribute	Description
Name	RKYPFOLIOCUST
Datatype	String
Description	Indicates Rekey Fields For Portfolio Customer Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RKYPFOLIOCCY

Attribute	Description	
Name	RKYPFOLIOCCY	
Datatype	String	
Description	Indicates Rekey Fields For Portfolio Currency Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BKRGHTSFLG

Attribute	Description	
Name	BKRGHTSFLG	
Datatype	String	
Description	Indicates Book Intrinsic Value Rights Flag Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BKWRNTIVFLG

Attribute	Description	
Name	BKWRNTIVFLG	
Datatype	String	
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TBDACCRFLG

Attribute	Description	
Name	TBDACCRFLG	
Datatype	String	
Description	Indicates Accrue Discount For Treasury Bills Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String

Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE
Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description

Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC
Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Class

Attribute	**Description**	
Name	Class	
Datatype		
Description	Class Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMP

Attribute	**Description**	
Name	COMP	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSN

Attribute	**Description**	
Name	STPASSN	
Datatype	String	
Description	Indicates Component Details Stop Association Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TAXTYP

Attribute	**Description**	
Name	TAXTYP	
Datatype	String	
Description	Indicates Tax Type Withholding "W", Others "O"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description
Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG

Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

DFLTWAIV

Attribute	Description
Name	DFLTWAIV
Datatype	String
Description	Indicates Default Waiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRAPPLN

Attribute	**Description**	
Name	AMNDAFTRAPPLN	
Datatype	String	
Description	Indicates Amend After Application Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RULEDESC

Attribute	**Description**	
Name	RULEDESC	
Datatype	String	
Description	Indicates Rule Detail Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Scheme

Attribute	**Description**	
Name	Product-Scheme	
Datatype		
Description	Product Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDORMRKTCD

Attribute	Description	
Name	PRDORMRKTCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SCHME

Attribute	Description	
Name	SCHME	
Datatype	String	
Description	Indicates Tax Scheme	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Pfolioprod-Restrictions

Attribute	Description	
Name	Pfolioprod-Restrictions	
Datatype		
Description	Security Restrictions	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECPRDCD

Attribute	Description	
Name	SECPRDCD	
Datatype	String	
Description	Indicates Product Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**	
Name	ADVCHG	
Datatype	String	
Description	Indicates Advice Charge Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CAPTLIZE

Attribute	**Description**	
Name	CAPTLIZE	
Datatype	String	
Description	Indicates Captilize Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISCACCRAPLB

Attribute	**Description**	
Name	DISCACCRAPLB	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String

Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String

Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	**Description**	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	**Description**	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	**Description**	
Name	EVNTAPPLIDESC	
Datatype	String	
Description	Indicates Event Application Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

RULDESC

Attribute	Description	
Name	RULDESC	
Datatype	String	
Description	Indicates rule Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Product-Events

Attribute	Description	
Name	Product-Events	
Datatype		
Description	Product Events	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC

Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD

Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

GLDESC

Attribute	Description	
Name	GLDESC	
Datatype	String	
Description	Indicates GL description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Product Customer Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description	
Name	Branch-Ccy-Restrictions	
Datatype		
Description	Branch Currency Restriction	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	**Description**	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains FCUBS Error List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains FCUBS Warning List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.128.4.SP-ModifyPortfolioProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-PK*
      - *PRDCD*
    - *Cstms-Product-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RATTYPPREFRD*
      - *CLASCD*
      - *INSPRDALW*
      - *MODNO*
      - *Portfolio-Product*

PFOLIOCOSTMTHD
ACCRPRMFLG
ACCRDISCFLG
DPRACCRMETH
DPRACCRFREQ
DPRACCRSTDY
DPRACCRSTMTH
BKDPMETH
ACCRRDMPRMFLG
RPRACCRFLG
RPRACCRMETH
RPRACCRSTDY
RPRACCRSTMTH
FWDNPLACCRFLG
FWDNPLACCRMETH
FWDNPLACCRFREQ
FWDNPLACCRSTDY
FWDNPLACCRSTMTH
INTACCRFLG
INTACCRFREQ
INTACCRSTDY
INTACCRSTMTH
REVALFLG
REVALMETH
REVALFREQ
REVALSTDY
REVALSTMTH
UNSETDLRVLFLG
SHTPOSALWDFLG
SHTHLDALWDFLG
CRPSACCFLG
ACCRWTHLDTXFLG
STMTTXNREQFLG
TXNFREQ
TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
SECALWDFLG

- *BKRGHTSFLG*
- *BKWRNTIVFLG*
- *TBDACCRFLG*
- *TBDACCRFREQ*
- *TBDACCRSTDY*
- *TBDACCRSTMTH*
- *LMTTRCKFRBNDS*
- *LMTTRCKFREQUITIES*
- *LMTTRCKFRRIGHTS*
- *LMTTRCKFRWRNTS*
- *LMTTRCKFRTBILLS*
- *CORPACTREQD*
- *TRCKACCRINT*
- *RLZDREVLMETH*
- *RLZDREVLFLG*
- *RLZDREVLSTDY*
- *RLZDREVLSTMTH*
- *RLZDREVLFREQ*
- *ACCRTBDWTFLG*
- *ACCRPRMMETH*
- *ACCRDISCMETH*
- *WIIPDLPURINT*
- *LCOM*
- *EXRATTYP*
- *BNKRSACPTCE*
- *CNTRAHLDNGTYPE*
- *CNTRAHLDNGALWD*
- *STMTHLDNGREQFLG*
- *STMTHLDNGFREQ*
- *STMTHLDNGSTDY*
- *STMTHLDNGSTMTH*
- *STMTTXNSTDY*

Product-Class-Link

- *CLASCD*
- *Class*
  - *COMP*
  - *STPASSN*
  - *TAXTYP*
  - *BORNBY*
  - *CASHOUTFLWINDI*
  - *NETCONSINDI*
  - *CONSPLUSMIN*
  - *SWFTQUAL*
  - *EVNTASSN*

- EVNTAPPLN
- EVNTLIQDN
- BASAMTTAG
- DFLTRULE
- DFLTWAIV
- ALLWRULAMND
- AMNDAFTRASSN
- ALLWAMTAMND
- AMNDAFTRAPPLN

Pfolioprod-Restrictions
- SECPRDCD

Pfolio-Prod-Secaccess
- SECID
- ACCSALWDFLG

Product-Charges
- Charge-Details
  - SETTCCY
  - DFTWAIV
  - ALWRULAMND
  - AMNDAFTRASSOC
  - ALWAMTAMND
  - AMNDAFTRAPPL
  - STPASOCIATN
  - ADVCHG
  - DFTRULE
  - COMPNT

Product-Events
- CLASCD
- Event-Details
  - EVNTCD
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
  - Advices

MSGTYP
SUPRS
PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
Mapping-Details
ACCTRL
ACCTHD
STAT
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
UDFDETAILS
FLDNAM
FLDVAL
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-PK

Attribute	Description
Name	Cstms-Product-PK
Datatype	
Description	Indicates Product Code.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates FCUBS Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDESC

Attribute	Description
Name	PRDDESC

Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates Product End Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description	
Name	PRDRMRKS	
Datatype	String	
Description	Indiactes Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NRMLRTVARI

Attribute	Description	
Name	NRMLRTVARI	
Datatype	Number	
Description	Indicates Normal Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXRTVARI

Attribute	Description	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates Preferred Rate Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

INSPRDALW

Attribute	**Description**	
Name	INSPRDALW	
Datatype	String	
Description	Indicates Instrument Product Allowed Disallowed "D"; Allowed "A".	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	totalDigits	22

TOP

Portfolio-Product

Attribute	**Description**	
Name	Portfolio-Product	
Datatype		
Description	Product Portfolio Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG
Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String

Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String

Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String
Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number

Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SHTHLDALWDFLG

Attribute	Description	
Name	SHTHLDALWDFLG	
Datatype	String	
Description	Indicates Short Holding Allowed Flag yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CRPSACCFLG

Attribute	Description	
Name	CRPSACCFLG	
Datatype	String	
Description	Indicates Corpus Account Flag Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRWTHLDTXFLG

Attribute	Description	
Name	ACCRWTHLDTXFLG	
Datatype	String	
Description	Indicates Accrue Withholding Tax For Coupons Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STMTTXNREQFLG

Attribute	Description	
Name	STMTTXNREQFLG	
Datatype	String	
Description	Indicates Statement Of Transaction Reqd Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number
Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number

Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W,

TOP

CORPAUTOLIQFLG

Attribute	Description
Name	CORPAUTOLIQFLG
Datatype	String
Description	Indicates Auto Liquidate For Corporate Actions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYREQDFLG

Attribute	Description
Name	RKYREQDFLG
Datatype	String
Description	Indicates Rekey For Authorization Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYPFOLIOID

Attribute	Description
Name	RKYPFOLIOID
Datatype	String
Description	Indicates Rekey Fields For Portfolio Identification Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCUST

Attribute	Description
Name	RKYPFOLIOCUST
Datatype	String
Description	Indicates Rekey Fields For Portfolio Customer Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SECALWDFLG

Attribute	Description
Name	SECALWDFLG
Datatype	String
Description	Indicates Security Allowed Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String
Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES
Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String

Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

CORPACTREQD

Attribute	Description
Name	CORPACTREQD
Datatype	String
Description	Indicates Corporate Action Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TRCKACCRINT

Attribute	Description
Name	TRCKACCRINT
Datatype	String
Description	Indicates Track Accrued Intereset
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH

Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLFREQ

Attribute	Description
Name	RLZDREVLFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	Description
Name	ACCRTBDWTFLG
Datatype	String
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRPRMMETH

Attribute	Description
Name	ACCRPRMMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

ACCRDISCMETH

Attribute	Description
Name	ACCRDISCMETH
Datatype	String
Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

BNKRSACPTCE

Attribute	**Description**	
Name	BNKRSACPTCE	
Datatype	String	
Description	Indicates Bankers Acceptance Issue Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CNTRAHLDNGTYPE

Attribute	**Description**	
Name	CNTRAHLDNGTYPE	
Datatype	String	
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,E,

TOP

CNTRAHLDNGALWD

Attribute	**Description**	
Name	CNTRAHLDNGALWD	
Datatype	String	
Description	Indicates Contra Holding Validate Allowed Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STMTHLDNGREQFLG

Attribute	**Description**	
Name	STMTHLDNGREQFLG	
Datatype	String	
Description	Indicates Statement Of Holdings Required yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String
Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number

Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Class

Attribute	Description
Name	Class
Datatype	
Description	Class Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description

Name	STPASSN
Datatype	String
Description	Indicates Component Details Stop Association Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	Indicates Tax Type Withholding "W", Others "O"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONSPLUSMIN

Attribute	**Description**	
Name	CONSPLUSMIN	
Datatype	String	
Description	Indicates Add "A" /Subtract "S"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,S,

TOP

SWFTQUAL

Attribute	**Description**	
Name	SWFTQUAL	
Datatype	String	
Description	Indicates Swift Qualifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTASSN

Attribute	**Description**	
Name	EVNTASSN	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTAPPLN

Attribute	**Description**	
Name	EVNTAPPLN	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTLIQDN

Attribute	Description	
Name	EVNTLIQDN	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASAMTTAG

Attribute	Description	
Name	BASAMTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

DFLTRULE

Attribute	Description	
Name	DFLTRULE	
Datatype	String	
Description	Indicates Default Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DFLTWAIV

Attribute	Description	
Name	DFLTWAIV	
Datatype	String	
Description	Indicates Default Waiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWRULAMND

Attribute	Description
Name	ALLWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRASSN

Attribute	Description
Name	AMNDAFTRASSN
Datatype	String
Description	Indicates Amend After Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALLWAMTAMND

Attribute	Description
Name	ALLWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendment Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Pfolioprod-Restrictions

Attribute	Description
Name	Pfolioprod-Restrictions
Datatype	
Description	Security Restrictions
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	
Description	Security Product Security Access
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

Product-Charges

Attribute	**Description**	
Name	Product-Charges	
Datatype		
Description	Product Charges	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charge-Details

Attribute	**Description**	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description

Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Role-To-Head-Mapping

Attribute	**Description**	
Name	Role-To-Head-Mapping	
Datatype		
Description	Role To Head Mapping	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	**Description**	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	**Description**	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restriction
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String

Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description

Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

KYID

Attribute	Description	
Name	KYID	
Datatype	String	
Description	Indicates Key ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Indicates FCUBS Error list.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.129.ModifySecuritiesPortfolio

ModifySecuritiesPortfolio

2.129.1.SP-ModifySecuritiesPortfolio-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRDIS

Attribute	**Description**	
Name	ACRDIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRDCM

Attribute	**Description**	
Name	ACRDCM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRMD

Attribute	**Description**	
Name	ACRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	**Description**	
Name	ACRFD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	**Description**	
Name	INACCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUST

Attribute	**Description**	
Name	CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHTN

Attribute	**Description**	
Name	SHTN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACBR

Attribute	**Description**	
Name	CUSTACBR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACBRDS

Attribute	**Description**	
Name	CUSTACBRDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,,A

TOP

PORTFSM

Attribute	Description
Name	PORTFSM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description	
Name	PRDDSAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDSALDS

Attribute	Description	
Name	PRDDSALDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepfseac

Attribute	Description	
Name	Sepfseac	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SECID

Attribute	Description	
Name	SECID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECPRDCD

Attribute	Description

Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHSST

Attribute	Description
Name	AUTHSST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description

Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTN

Attribute	Description
Name	PARTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	**Description**	
Name	Sepma2	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description

Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	**Description**	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	**Description**	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.129.2.SP-ModifySecuritiesPortfolio-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-IO*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
ONCEAUTH
MODN
FUNDREF
PORTFID
PORTFDS
SHTN
BRIGHT
BWARRNT
AULFC

CRPACC
SHRTA
ACCRWTC
BANKAT
CONTHA
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
CHKID
CHKSTMP
AUTHSTAT
SUBSYSSTAT
SE_REPOPROHOLD
Sesepd
- *SECALLD*

Misdetails
- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRPM

Attribute	**Description**	
Name	ACCRPM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRDIS

Attribute	**Description**	
Name	ACRDIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACRDCM

Attribute	**Description**	
Name	ACRDCM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,S,Y,

TOP

ACRMD

Attribute	**Description**	
Name	ACRMD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVSTM

Attribute	Description
Name	REVSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,M,X,</td></tr></table>

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	**Description**	
Name	FDACRME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDREF

Attribute	Description
Name	FUNDREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BRIGHT

Attribute	Description
Name	BRIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONTHA

Attribute	**Description**	
Name	CONTHA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

2.129.3.SP-ModifySecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN

BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID
  SKLC
Serth
  PORTFID

- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*

- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*

- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVSTM

Attribute	**Description**	
Name	REVSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REREV

Attribute	**Description**	
Name	REREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

REDVM

Attribute	**Description**	
Name	REDVM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,M,X,

TOP

LOCMBA

Attribute	**Description**	
Name	LOCMBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,D,H,A,</td></tr></table>

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,F,,M</td></tr></table>

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	B,F,,M

TOP

RIGHT

Attribute	Description	
Name	RIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

WARR

Attribute	Description	
Name	WARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INACRF

Attribute	**Description**
Name	INACRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

INTACRSTD

Attribute	**Description**
Name	INTACRSTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACRM

Attribute	**Description**
Name	INTACRM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRCD

Attribute	**Description**
Name	EXRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	**Description**
Name	PRDDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFID

Attribute	**Description**
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POREF

Attribute	**Description**
Name	POREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	**Description**
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	**Description**	
Name	SHRTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTDS

Attribute	**Description**	
Name	PORTDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Seprskm

Attribute	**Description**	
Name	Seprskm	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLCID

Attribute	**Description**	
Name	SKLCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

MEDDS

Attribute	**Description**	
Name	MEDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description

Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description

Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	**Description**	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	**Description**	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	**Description**	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.129.4.SP-ModifySecuritiesPortfolio-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-PK*
      - *PORTFID*
    - *Sepm-IO*
      - *ACCRHTB*
      - *STHDR*
      - *STATEMENTHOLDFREQUENCY*
      - *STHSD*
      - *STATEMENTSTARTMONTH*
      - *PRVHSN*
      - *STTXR*
      - *TXNS_STATEMENT_DAY*
      - *STTXSM*
      - *PREVSSN*
      - *ACCRP*
      - *ACCRPM*
      - *ACRDIS*
      - *ACRDCM*
      - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
ONCEAUTH
MODN
FUNDREF
PORTFID
PORTFDS
SHTN

BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONTHA
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
CHKID
CHKSTMP
AUTHSTAT
SUBSYSSTAT
SE_REPOPROHOLD
Sesepd
  SECALLD
Misdetails
  CONREFNO
  MISGRP
  RELACC
  RELETED_REFERENCE
  MISHEAD
  RATEFLG
  POOLCD
  REFINANCE_RATE
  REFRATETYP
  PROCALCMTH
  REFXRATE
  REFSPREAD
  REFRATECD
  COSTCD1
  COSTCD2
  COSTCD3
  COSTCD4
  COSTCD5
  TXNMIS1

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-PK

Attribute	Description
Name	Sepm-PK
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	**Description**	
Name	INACCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDREF

Attribute	Description
Name	FUNDREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BWARRNT

Attribute	Description
Name	BWARRNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONTHA

Attribute	**Description**	
Name	CONTHA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,O,U,

TOP

CORPAR

Attribute	**Description**	
Name	CORPAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECALLD

Attribute	Description
Name	SECALLD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	**Description**	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	**Description**	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.130.QueryPortfolioProduct

Query for Securities Portfolio Product

2.130.1.SP-QueryPortfolioProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cstms-Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates full Product details in FCUBS Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.130.2.SP-QueryPortfolioProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cstms-Product-IO*
      - *PRDCD*
    - *Cstms-Product-Full*
      - *PRDCD*
      - *PRDTYP*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RATTYPPREFRD*
      - *PRDTYPDESC*
      - *PRDGRPDESC*
      - *CLASCD*

INSPRDALW
TXT_CLASS_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Portfolio-Product
- *PFOLIOTYP*
- *PFOLIOCOSTMTHD*
- *ACCRPRMFLG*
- *ACCRDISCFLG*
- *DPRACCRMETH*
- *DPRACCRFREQ*
- *DPRACCRSTDY*
- *DPRACCRSTMTH*
- *BKDPMETH*
- *ACCRRDMPRMFLG*
- *RPRACCRFLG*
- *RPRACCRMETH*
- *RPRACCRSTDY*
- *RPRACCRSTMTH*
- *FWDNPLACCRFLG*
- *FWDNPLACCRMETH*
- *FWDNPLACCRFREQ*
- *FWDNPLACCRSTDY*
- *FWDNPLACCRSTMTH*
- *INTACCRFLG*
- *INTACCRFREQ*
- *INTACCRSTDY*
- *INTACCRSTMTH*
- *REVALFLG*
- *REVALMETH*
- *REVALFREQ*
- *REVALSTDY*
- *REVALSTMTH*
- *UNSETDLRVLFLG*
- *SHTPOSALWDFLG*
- *CRPSACCFLG*
- *ACCRWTHLDTXFLG*
- *STMTTXNREQFLG*
- *TXNFREQ*

TXNSTMTH
CORPNTCEFLG
CORPNOTCEDY
CORPNOTCEDYTYP
CORPAUTOLIQFLG
RKYREQDFLG
RKYPFOLIOID
RKYPFOLIOCUST
RKYPFOLIOCCY
BKRGHTSFLG
BKWRNTIVFLG
TBDACCRFLG
TBDACCRFREQ
TBDACCRSTDY
TBDACCRSTMTH
LMTTRCKFRBNDS
LMTTRCKFREQUITIES
LMTTRCKFRRIGHTS
LMTTRCKFRWRNTS
LMTTRCKFRTBILLS
RLZDREVLMETH
RLZDREVLFLG
RLZDREVLSTDY
RLZDREVLSTMTH
RLZDREVLFREQ
ACCRTBDWTFLG
ACCRPRMMETH
ACCRDISCMETH
WIIPDLPURINT
LCOM
EXRATTYP
BNKRSACPTCE
CNTRAHLDNGTYPE
CNTRAHLDNGALWD
STMTHLDNGREQFLG
STMTHLDNGFREQ
STMTHLDNGSTDY
STMTHLDNGSTMTH
STMTTXNSTDY
CCYRATTYPDESC
Product-Class-Link
CLASCD
TXT_CLASS_DESC
Class

- *COMP*
- *STPASSN*
- *TAXTYP*
- *BORNBY*
- *CASHOUTFLWINDI*
- *NETCONSINDI*
- *CONSPLUSMIN*
- *SWFTQUAL*
- *EVNTASSN*
- *EVNTAPPLN*
- *EVNTLIQDN*
- *BASAMTTAG*
- *DFLTRULE*
- *DFLTWAIV*
- *ALLWRULAMND*
- *AMNDAFTRASSN*
- *ALLWAMTAMND*
- *AMNDAFTRAPPLN*
- *RULEDESC*

Product-Scheme

- *PRDORMRKTCD*
- *SCHME*

Pfolioprod-Restrictions

- *SECPRDCD*
- *PRDDESC*

Pfolio-Prod-Secaccess

- *SECID*
- *PRDCD*
- *SECDESC*
- *ACCSALWDFLG*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*

- STPASOCIATN
- ADVCHG
- CAPTLIZE
- DISCACCRAPLB
- PROPREQD
- DISCNTBASIS
- DFTRULE
- COMPNT
- EVNTFRASSC
- EVNTFRAPPL
- EVNTFRLIQ
- BASISAMNTTAG
- BASICAMTTGDESC
- ACCRREQD
- COMPNENTDESC
- EVNTASSCTDESC
- EVNTAPPLIDESC
- EVNTLIQDDESC
- RULDESC

Product-Events

- CLASCD
- CLASDESC
- Event-Details
  - EVNTCD
  - EVENTDESC
  - Accounting-Entries
    - ACCRLCD
    - AMTTAG
    - DRCRINDICTR
    - TRNCD
    - NETINDICTR
    - MISHD
    - REVALPRGL
    - REVALLSGL
    - REVALRTCD
    - REVALTXNCD
    - HOLTREAT
    - REVALREQD
    - RATE_TYPE_INDICATOR
  - Advices
    - MSGTYP
    - DESC
    - GENTIME
    - SUPRS

PRIOR
CHGREQD
Role-To-Head-Mapping
CLASCD
CLASDESC
Mapping-Details
ACCTRL
ROLDESC
ACCTHD
GLDESC
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
UDFDETAILS
FLDNAM
FLDVAL
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cstms-Product-IO

Attribute	Description
Name	Cstms-Product-IO
Datatype	
Description	Indicates IO Product Code for query portfolio product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Cstms-Product-Full

Attribute	Description
Name	Cstms-Product-Full
Datatype	
Description	Indicates full Request details for query portfolio Product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDTYP

Attribute	Description

Name	PRDTYP
Datatype	String
Description	Indicates Product Type
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates Product Slogan
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates Product Group
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates Product Start Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates Product End Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description	Indiactes Product Remarks	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NRMLRTVARI

Attribute	**Description**	
Name	NRMLRTVARI	
Datatype	Number	
Description	Indicates Normal Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

MAXRTVARI

Attribute	**Description**	
Name	MAXRTVARI	
Datatype	Number	
Description	Indicates Maximum Rate Variance	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**
Name	RTCODEPRFERD
Datatype	String
Description	Indicates Preferred rate Code Mid Rate "M"; Buy /Sell Rate "B"

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates Preferred Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates Product Type Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRDGRPDESC

Attribute	**Description**	
Name	PRDGRPDESC	
Datatype	String	
Description	Indicates Product Group Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INSPRDALW

Attribute	Description
Name	INSPRDALW
Datatype	String
Description	Indicates Instrument Product Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Specifies the User Id who has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates Transaction Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Portfolio-Product

Attribute	Description
Name	Portfolio-Product
Datatype	
Description	Product Portfolio Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFOLIOTYP

Attribute	Description
Name	PFOLIOTYP
Datatype	String
Description	Indicates Portfolio Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PFOLIOCOSTMTHD

Attribute	Description
Name	PFOLIOCOSTMTHD
Datatype	String
Description	Indicates Portfolio Costing Method Deal Matching "D" LIFO "L" FIFO "F" Weighted Average "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,L,F,W,

TOP

ACCRPRMFLG

Attribute	Description
Name	ACCRPRMFLG

Datatype	String
Description	Indicates Accrue Premium Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRDISCFLG

Attribute	Description
Name	ACCRDISCFLG
Datatype	String
Description	Indicates Accrue Discount Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DPRACCRMETH

Attribute	Description
Name	DPRACCRMETH
Datatype	String
Description	Indicates Premium/Discount Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

DPRACCRFREQ

Attribute	Description
Name	DPRACCRFREQ
Datatype	String
Description	Indicates Premium/Discount Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

DPRACCRSTDY

Attribute	Description
Name	DPRACCRSTDY
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DPRACCRSTMTH

Attribute	Description
Name	DPRACCRSTMTH
Datatype	Number
Description	Indicates Premium/Discount Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BKDPMETH

Attribute	Description
Name	BKDPMETH
Datatype	String
Description	Indicates Book Discount/Premium Accounting Basis Accrual "A", Non Accrual "N"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,N,

TOP

ACCRRDMPRMFLG

Attribute	Description
Name	ACCRRDMPRMFLG
Datatype	String
Description	Indicates Redemption Premium Accrue Redemption Flag Yes/ No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RPRACCRFLG

Attribute	Description
Name	RPRACCRFLG
Datatype	String
Description	Indicates Redemption Premium Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

RPRACCRMETH

Attribute	Description
Name	RPRACCRMETH
Datatype	String
Description	Indicates Redemption Premium Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

RPRACCRSTDY

Attribute	Description
Name	RPRACCRSTDY
Datatype	Number
Description	Indicates Redemption Premium Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RPRACCRSTMTH

Attribute	Description
Name	RPRACCRSTMTH
Datatype	Number

Description	Indicates Redemption Premium Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRFLG

Attribute	Description
Name	FWDNPLACCRFLG
Datatype	String
Description	Indicates Forward Profit/Loss Accrual
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FWDNPLACCRMETH

Attribute	Description
Name	FWDNPLACCRMETH
Datatype	String
Description	Indicates Forward Profit Accrual Method 30(Euro)/360 "A" 30(US)/360 "B" Actual/360 "C" 30(Euro)/365 "D" 30(US)/365 "E" Actual/365 "F" 30(Euro)/Actual "G" 30(US)/Actual "H" Actual/Actual "I"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,B,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDNPLACCRFREQ

Attribute	Description
Name	FWDNPLACCRFREQ
Datatype	String
Description	Indicates Forward Profit Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

FWDNPLACCRSTDY

Attribute	Description
Name	FWDNPLACCRSTDY
Datatype	Number
Description	Indicates Forward Profit Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDNPLACCRSTMTH

Attribute	Description
Name	FWDNPLACCRSTMTH
Datatype	Number
Description	Indicates Forward Profit Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRFLG

Attribute	Description
Name	INTACCRFLG
Datatype	String
Description	Indicates Interest Accruals Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTACCRFREQ

Attribute	Description
Name	INTACCRFREQ
Datatype	String

Description	Indicates Interest Accruals Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

INTACCRSTDY

Attribute	Description
Name	INTACCRSTDY
Datatype	Number
Description	Indicates Interest Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACCRSTMTH

Attribute	Description
Name	INTACCRSTMTH
Datatype	Number
Description	Indicates Interest Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALFLG

Attribute	Description
Name	REVALFLG
Datatype	String
Description	Indicates Revaluation Of Settled Positions Yes/NO
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVALMETH

Attribute	Description
Name	REVALMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,E,

TOP

REVALFREQ

Attribute	Description
Name	REVALFREQ
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

REVALSTDY

Attribute	Description
Name	REVALSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTMTH

Attribute	Description
Name	REVALSTMTH
Datatype	Number

Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UNSETDLRVLFLG

Attribute	Description
Name	UNSETDLRVLFLG
Datatype	String
Description	Indicates Revaluation Of Unsettled Positions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SHTPOSALWDFLG

Attribute	Description
Name	SHTPOSALWDFLG
Datatype	String
Description	Indicates Short Position Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CRPSACCFLG

Attribute	Description
Name	CRPSACCFLG
Datatype	String
Description	Indicates Corpus Account Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRWTHLDTXFLG

Attribute	Description
Name	ACCRWTHLDTXFLG
Datatype	String
Description	Indicates Accrue Withholding Tax For Coupons Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTTXNREQFLG

Attribute	Description
Name	STMTTXNREQFLG
Datatype	String
Description	Indicates Statement Of Transaction Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNFREQ

Attribute	Description
Name	TXNFREQ
Datatype	String
Description	Indicates Transaction Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TXNSTMTH

Attribute	Description
Name	TXNSTMTH
Datatype	Number

Description	Indicates Transaction Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNTCEFLG

Attribute	Description
Name	CORPNTCEFLG
Datatype	String
Description	Indicates Corporate Notice Action Reqd Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPNOTCEDY

Attribute	Description
Name	CORPNOTCEDY
Datatype	Number
Description	Indicates Corporate Action Notice Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNOTCEDYTYP

Attribute	Description
Name	CORPNOTCEDYTYP
Datatype	String
Description	Indicates Corporate Action Notice Day Type Calender Days "C", Working Days "W"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,W,

TOP

CORPAUTOLIQFLG

Attribute	Description
Name	CORPAUTOLIQFLG

Datatype	String
Description	Indicates Auto Liquidate For Corporate Actions Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYREQDFLG

Attribute	Description
Name	RKYREQDFLG
Datatype	String
Description	Indicates Rekey For Authorization Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RKYPFOLIOID

Attribute	Description
Name	RKYPFOLIOID
Datatype	String
Description	Indicates Rekey Fields For Portfolio Identification Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCUST

Attribute	Description
Name	RKYPFOLIOCUST
Datatype	String
Description	Indicates Rekey Fields For Portfolio Customer Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RKYPFOLIOCCY

Attribute	Description
Name	RKYPFOLIOCCY
Datatype	String
Description	Indicates Rekey Fields For Portfolio Currency Yes/No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKRGHTSFLG

Attribute	Description
Name	BKRGHTSFLG
Datatype	String
Description	Indicates Book Intrinsic Value Rights Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BKWRNTIVFLG

Attribute	Description
Name	BKWRNTIVFLG
Datatype	String
Description	Indicates Book Intrinsic Value Warrants Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFLG

Attribute	Description
Name	TBDACCRFLG
Datatype	String
Description	Indicates Accrue Discount For Treasury Bills Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TBDACCRFREQ

Attribute	Description
Name	TBDACCRFREQ
Datatype	String
Description	Indicates Treasury Bill Accrual Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

TBDACCRSTDY

Attribute	Description
Name	TBDACCRSTDY
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBDACCRSTMTH

Attribute	Description
Name	TBDACCRSTMTH
Datatype	Number
Description	Indicates Treasury Bill Accrual Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTTRCKFRBNDS

Attribute	Description
Name	LMTTRCKFRBNDS
Datatype	String
Description	Indicates Limits Tracking Bonds Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFREQUITIES

Attribute	Description
Name	LMTTRCKFREQUITIES

Datatype	String
Description	Indicates Limits Tracking Equities Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRRIGHTS

Attribute	Description
Name	LMTTRCKFRRIGHTS
Datatype	String
Description	Indicates Limits Tracking Rights Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRWRNTS

Attribute	Description
Name	LMTTRCKFRWRNTS
Datatype	String
Description	Indicates Limits Tracking Warrants Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

LMTTRCKFRTBILLS

Attribute	Description
Name	LMTTRCKFRTBILLS
Datatype	String
Description	Indicates Limits Tracking Treasury Bills Market Price "M" Book Value "B" Face Value "F"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,F,

TOP

RLZDREVLMETH

Attribute	Description
Name	RLZDREVLMETH
Datatype	String
Description	Indicates Revaluation Of Positions -- Revaluation Method MTM-BV "M" LOCOM "L" MTM-EIM "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,L,X,

TOP

RLZDREVLFLG

Attribute	Description
Name	RLZDREVLFLG
Datatype	String
Description	Indicates Revaluation Of Positions -- Realized Revaluation Flag Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RLZDREVLSTDY

Attribute	Description
Name	RLZDREVLSTDY
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RLZDREVLSTMTH

Attribute	Description
Name	RLZDREVLSTMTH
Datatype	Number
Description	Indicates Revaluation Of Positions -- Revaluation Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RLZDREVLFREQ

Attribute	**Description**	
Name	RLZDREVLFREQ	
Datatype	String	
Description	Indicates Revaluation Of Positions -- Revaluation Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,M,Q,H,A,

TOP

ACCRTBDWTFLG

Attribute	**Description**	
Name	ACCRTBDWTFLG	
Datatype	String	
Description	Accrue Withholding Tax For Treasury-Bill Disc Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRPRMMETH

Attribute	**Description**	
Name	ACCRPRMMETH	
Datatype	String	
Description	Indicates Premium/Discount Accrue Premium Method Straight Line "S" Exponential "E" Constant Yield "Y"	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,E,Y,

TOP

ACCRDISCMETH

Attribute	**Description**
Name	ACCRDISCMETH
Datatype	String

Description	Indicates Premium/Discount Accrue Discount Method Straight Line "S" Exponential "E" Constant Yield "Y"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,E,Y,

TOP

WIIPDLPURINT

Attribute	Description
Name	WIIPDLPURINT
Datatype	String
Description	Indicates Wipe Deal Purchase Interest. Sale and Coupon "B" Sale "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,S,

TOP

LCOM

Attribute	Description
Name	LCOM
Datatype	String
Description	Indicates Revaluation Of Positions -- Locom Holding Cost "H" Acquisition Cost "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,A,

TOP

EXRATTYP

Attribute	Description
Name	EXRATTYP
Datatype	String
Description	Indicates Exchange Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

BNKRSACPTCE

Attribute	Description
Name	BNKRSACPTCE

Datatype	String
Description	Indicates Bankers Acceptance Issue Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CNTRAHLDNGTYPE

Attribute	Description
Name	CNTRAHLDNGTYPE
Datatype	String
Description	Indicates Contra Holding Validate When Online "O", End Of Transaction Input "E"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,E,

TOP

CNTRAHLDNGALWD

Attribute	Description
Name	CNTRAHLDNGALWD
Datatype	String
Description	Indicates Contra Holding Validate Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STMTHLDNGREQFLG

Attribute	Description
Name	STMTHLDNGREQFLG
Datatype	String
Description	Indicates Statement Of Holdings Required yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STMTHLDNGFREQ

Attribute	Description
Name	STMTHLDNGFREQ
Datatype	String

Description	Indicates Holding Statement Frequency Daily "D" Monthly "M" Quarterly "Q" Half Yearly "H" Yearly "A"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

STMTHLDNGSTDY

Attribute	Description
Name	STMTHLDNGSTDY
Datatype	Number
Description	Indicates Holding Statement Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTHLDNGSTMTH

Attribute	Description
Name	STMTHLDNGSTMTH
Datatype	Number
Description	Indicates Holding Statement Start Month January "1" February "2" March "3" April "4" May "5" June "6" July "7" August "8" September "9" October "10" November "11" December "12"
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STMTTXNSTDY

Attribute	Description
Name	STMTTXNSTDY
Datatype	Number
Description	Indicates Transaction Start Day
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYRATTYPDESC

Attribute	Description
Name	CCYRATTYPDESC

Datatype	String
Description	Indicates Revaluation Exchange Rate Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Product Class Link
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Class

Attribute	Description
Name	Class
Datatype	
Description	Class Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSN

Attribute	Description
Name	STPASSN
Datatype	String
Description	Indicates Component Details Stop Association Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAXTYP

Attribute	Description
Name	TAXTYP
Datatype	String
Description	Indicates Tax Type Withholding "W", Others "O"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,O,

TOP

BORNBY

Attribute	Description
Name	BORNBY
Datatype	String
Description	Indicates Borne By Customer Bank "B", Customer "C"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,

TOP

CASHOUTFLWINDI

Attribute	Description
Name	CASHOUTFLWINDI
Datatype	String
Description	Indicates Cash Outflow Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NETCONSINDI

Attribute	Description
Name	NETCONSINDI
Datatype	String
Description	Indicates Net Consideration Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONSPLUSMIN

Attribute	Description
Name	CONSPLUSMIN
Datatype	String
Description	Indicates Add "A" /Subtract "S"
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWFTQUAL

Attribute	Description
Name	SWFTQUAL
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTASSN

Attribute	Description

Name	EVNTASSN
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTAPPLN

Attribute	Description
Name	EVNTAPPLN
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTLIQDN

Attribute	Description
Name	EVNTLIQDN
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASAMTTAG

Attribute	Description
Name	BASAMTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

DFLTRULE

Attribute	Description
Name	DFLTRULE
Datatype	String
Description	Indicates Default Rule

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

DFLTWAIV

Attribute	**Description**	
Name	DFLTWAIV	
Datatype	String	
Description	Indicates Default Waiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWRULAMND

Attribute	**Description**	
Name	ALLWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AMNDAFTRASSN

Attribute	**Description**	
Name	AMNDAFTRASSN	
Datatype	String	
Description	Indicates Amend After Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ALLWAMTAMND

Attribute	**Description**	
Name	ALLWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendment Yes/No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AMNDAFTRAPPLN

Attribute	Description
Name	AMNDAFTRAPPLN
Datatype	String
Description	Indicates Amend After Application Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	Indicates Rule Detail Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Scheme

Attribute	Description
Name	Product-Scheme
Datatype	
Description	Product Scheme
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDORMRKTCD

Attribute	Description
Name	PRDORMRKTCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	Indicates Tax Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Pfolioprod-Restrictions

Attribute	Description
Name	Pfolioprod-Restrictions
Datatype	
Description	Security Restrictions
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates Product Description
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Pfolio-Prod-Secaccess

Attribute	Description
Name	Pfolio-Prod-Secaccess
Datatype	

Description	Security Product Security Access
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDESC

Attribute	Description
Name	SECDESC
Datatype	String
Description	Indicates Security Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCSALWDFLG

Attribute	Description
Name	ACCSALWDFLG
Datatype	String
Description	Indicates Security Product Security Access Allowed Yes/No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	Product Charges
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWAMTAMND

Attribute	**Description**	
Name	ALWAMTAMND	
Datatype	String	
Description	Indicates Allow Amount Amendement Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRAPPL

Attribute	**Description**	
Name	AMNDAFTRAPPL	
Datatype	String	
Description	Indicates Amend After Application Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	**Description**	
Name	STPASOCIATN	
Datatype	String	
Description	Indicates Stop Association Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ADVCHG

Attribute	**Description**
Name	ADVCHG
Datatype	String

Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description

Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL

Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTASSCTDESC

Attribute	Description	
Name	EVNTASSCTDESC	
Datatype	String	
Description	Indicates Event Association Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	Description	
Name	EVNTAPPLIDESC	
Datatype	String	
Description	Indicates Event Application Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

EVNTLIQDDESC

Attribute	Description	
Name	EVNTLIQDDESC	
Datatype	String	
Description	Indicates Event Liquidation Description	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	Product Events
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTTAG

Attribute	**Description**	
Name	AMTTAG	
Datatype	String	
Description	Indicates amount tag.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DRCRINDICTR

Attribute	**Description**	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	D,C

TOP

TRNCD

Attribute	**Description**	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

NETINDICTR

Attribute	**Description**	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description	
Name	REVALPRGL	
Datatype	String	
Description	Indicates reval profit GL.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALLSGL

Attribute	Description	
Name	REVALLSGL	
Datatype	String	
Description	Indicates reval loss GL	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description	
Name	REVALRTCD	
Datatype	String	
Description	Indicates reval rate code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

REVALTXNCD

Attribute	Description	
Name	REVALTXNCD	
Datatype	String	
Description	Indicates reval transaction code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Specifies the message description.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,A</td></tr></table>

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	Role To Head Mapping
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ROLDESC

Attribute	Description	
Name	ROLDESC	
Datatype	String	
Description	Indicates role description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCTHD

Attribute	Description

Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Product Customer Restriction
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Branch Currency Restriction
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

BRNLST

Attribute	**Description**	
Name	BRNLST	
Datatype	String	
Description	Indicates Branch Restrictions	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	**Description**	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CCYNAME

Attribute	Description

Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Product MIS Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	Description	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>100</td></tr></table>

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String

Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.131.QuerySEBonusDefn

Query for Securities Stock Dividend

2.131.1.SP-QuerySEBonusDefn-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stock-Dividend-IO*
    - *INTACTID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stock-Dividend-IO

Attribute	Description
Name	Stock-Dividend-IO
Datatype	
Description	Includes Securities Stock Dividend Bonus Definition Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.131.2.SP-QuerySEBonusDefn-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stock-Dividend-IO*
      - *INTACTID*
    - *Stock-Dividend-Full*
      - *INTACTID*
      - *EXTACTID*
      - *INTSECID*
      - *ANNOUNCEMENTDT*
      - *EVENTDT*
      - *RECDT*
      - *ISSUERREF*
      - *RESULTNTSECID*
      - *RESULTNTRATIONUM*
      - *RESULTNTRATIODENOM*
      - *DISPOSEFRAC*
      - *STKCSHOPTN*
      - *STKTOCSHACTID*
      - *STKTOCSHPRC*
      - *EXERCISEENDDT*

ISSUERPAYMNTCCY
EXCHRATEFIXDT
EXCHRATE
CONFIRMED
CONFIRMEDDT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Event-Narrative
INTACTID
EVENTNARTV01
EVENTNARTV02
EVENTNARTV03
EVENTNARTV04
EVENTNARTV05
EVENTNARTV06
EVENTNARTV07
EVENTNARTV08
EVENTNARTV09
EVENTNARTV10
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stock-Dividend-IO

Attribute	Description
Name	Stock-Dividend-IO
Datatype	
Description	Includes Securities Stock Dividend Bonus Definition Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Stock-Dividend-Full

Attribute	Description
Name	Stock-Dividend-Full
Datatype	
Description	Includes Securities Stock Dividend Bonus Definition Query Full type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTACTID

Attribute	Description
Name	EXTACTID
Datatype	String
Description	Indicates External Action Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates Internal Security ID

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ANNOUNCEMENTDT

Attribute	Description
Name	ANNOUNCEMENTDT
Datatype	Date
Description	Indicates the Announcement Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTDT

Attribute	Description
Name	EVENTDT
Datatype	Date
Description	Indicates Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECDT

Attribute	Description
Name	RECDT
Datatype	Date
Description	Indicates Record Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUERREF

Attribute	Description
Name	ISSUERREF
Datatype	String
Description	Indicates Issuer Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESULTNTSECID

Attribute	Description
Name	RESULTNTSECID

Datatype	String
Description	Indicates Resultant Security ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RESULTNTRATIONUM

Attribute	Description
Name	RESULTNTRATIONUM
Datatype	Number
Description	Indicates Resultant Ratio Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESULTNTRATIODENOM

Attribute	Description
Name	RESULTNTRATIODENOM
Datatype	Number
Description	Indicates Resultant Ratio Denominator
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISPOSEFRAC

Attribute	Description
Name	DISPOSEFRAC
Datatype	String
Description	Indicates Dispose Fraction Round Standard : RS RETAIN : RN Round Up : RU Round Down : RD
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RD,RN,RS,RU,

TOP

STKCSHOPTN

Attribute	Description
Name	STKCSHOPTN
Datatype	String
Description	Indicates Stock To Cash Convertion Option Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STKTOCSHACTID

Attribute	**Description**	
Name	STKTOCSHACTID	
Datatype	String	
Description	Indicates Stock To Cash Action Identification	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

STKTOCSHPRC

Attribute	**Description**	
Name	STKTOCSHPRC	
Datatype	Number	
Description	Indicates Stock To Cash Price	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXERCISEENDDT

Attribute	**Description**	
Name	EXERCISEENDDT	
Datatype	Date	
Description	Indicates End of Exercise Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSUERPAYMNTCCY

Attribute	**Description**	
Name	ISSUERPAYMNTCCY	
Datatype	String	
Description	Indicates Issuer Pay Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXCHRATEFIXDT

Attribute	Description
Name	EXCHRATEFIXDT
Datatype	Date
Description	Indicates Exchange Rate Fixing Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONFIRMEDDT

Attribute	Description
Name	CONFIRMEDDT
Datatype	Date
Description	Indicates Confirmed Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization status
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Event-Narrative

Attribute	Description
Name	Event-Narrative
Datatype	
Description	Includes Event Narrative details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTNARTV01

Attribute	**Description**	
Name	EVENTNARTV01	
Datatype	String	
Description	Indicates Event Narrative 01	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV02

Attribute	**Description**	
Name	EVENTNARTV02	
Datatype	String	
Description	Indicates Event Narrative 02	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV03

Attribute	**Description**	
Name	EVENTNARTV03	
Datatype	String	
Description	Indicates Event Narrative 03	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV04

Attribute	**Description**	
Name	EVENTNARTV04	
Datatype	String	
Description	Indicates Event Narrative 04	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV05

Attribute	Description
Name	EVENTNARTV05
Datatype	String
Description	Indicates Event Narrative 05
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV06

Attribute	Description
Name	EVENTNARTV06
Datatype	String
Description	Indicates Event Narrative 06
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV07

Attribute	Description
Name	EVENTNARTV07
Datatype	String
Description	Indicates Event Narrative 07
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV08

Attribute	Description
Name	EVENTNARTV08
Datatype	String
Description	Indicates Event Narrative 08
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV09

Attribute	Description	
Name	EVENTNARTV09	
Datatype	String	
Description	Indicates Event Narrative 09	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV10

Attribute	Description	
Name	EVENTNARTV10	
Datatype	String	
Description	Indicates Event Narrative 10	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.132.QuerySECashDefinition

QuerySECashDefinition

2.132.1.SP-QuerySECashDefinition-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stcrpactdue-IO*
    - *BRANCH_CODE*
    - *SE_INTERNAL_ACTION_ID*
    - *REFERENCE_NO*
    - *SK_LOCATION*
    - *SK_ACCOUNT*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Stcrpactdue-IO

Attribute	Description
Name	Stcrpactdue-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SK_LOCATION

Attribute	Description
Name	SK_LOCATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SK_ACCOUNT

Attribute	Description
Name	SK_ACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.132.2.SP-QuerySECashDefinition-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stcrpactdue-IO*
      - *BRANCH_CODE*
      - *SE_INTERNAL_ACTION_ID*
      - *REFERENCE_NO*
      - *SK_LOCATION*
      - *SK_ACCOUNT*
    - *Stcrpactdue-Full*
      - *SE_ADJ_BONUS_ENCASH*
      - *BRANCH_CODE*
      - *SE_INTERNAL_ACTION_ID*
      - *REFERENCE_NO*
      - *SK_LOCATION*
      - *SK_ACCOUNT*
      - *SECURITY_ID*
      - *PORTFOLIO_ID*
      - *EVENT_DATE*
      - *SE_SECQTY*
      - *INITIALBONUSDUE*

SE_RESID_BONUS_DUE
BONUSENCASHED
SE_RELTD_INTACTID
RECORD_DATE
SECURITY_DESCRIPTION
PORTFOLIO_DESCRIPTION
LOCDESC
SE_RESULTANT_SECURITY_ID
BRANCH_DESC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stcrpactdue-IO

Attribute	Description
Name	Stcrpactdue-IO
Datatype	
Description	

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SK_LOCATION

Attribute	**Description**	
Name	SK_LOCATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SK_ACCOUNT

Attribute	**Description**	
Name	SK_ACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Stcrpactdue-Full

Attribute	**Description**
Name	Stcrpactdue-Full
Datatype	
Description	

TOP

SE_ADJ_BONUS_ENCASH

Attribute	Description
Name	SE_ADJ_BONUS_ENCASH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SK_LOCATION

Attribute	Description
Name	SK_LOCATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SK_ACCOUNT

Attribute	**Description**	
Name	SK_ACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SECURITY_ID

Attribute	**Description**	
Name	SECURITY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFOLIO_ID

Attribute	**Description**	
Name	PORTFOLIO_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENT_DATE

Attribute	**Description**	
Name	EVENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SE_SECQTY

Attribute	Description
Name	SE_SECQTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INITIALBONUSDUE

Attribute	Description
Name	INITIALBONUSDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_RESID_BONUS_DUE

Attribute	Description
Name	SE_RESID_BONUS_DUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BONUSENCASHED

Attribute	Description
Name	BONUSENCASHED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SE_RELTD_INTACTID

Attribute	Description
Name	SE_RELTD_INTACTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RECORD_DATE

Attribute	Description	
Name	RECORD_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SECURITY_DESCRIPTION

Attribute	Description	
Name	SECURITY_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PORTFOLIO_DESCRIPTION

Attribute	Description	
Name	PORTFOLIO_DESCRIPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LOCDESC

Attribute	Description	
Name	LOCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SE_RESULTANT_SECURITY_ID

Attribute	Description
Name	SE_RESULTANT_SECURITY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BRANCH_DESC

Attribute	Description
Name	BRANCH_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.133.QuerySECashDefn

Query for Bonus To Cash Conversion Maintenance

2.133.1.SP-QuerySECashDefn-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Corp-Actions-Due-IO*
    - *BRNCODE*
    - *INTACTID*
    - *REFNO*
    - *SKLOCID*
    - *SKAC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String

Description	
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Corp-Actions-Due-IO

Attribute	Description
Name	Corp-Actions-Due-IO
Datatype	
Description	Includes Securities Cash Definition Corporate Actions Due Query Input Only type details

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	Indicates Safe keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.133.2.SP-QuerySECashDefn-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Corp-Actions-Due-IO*
      - *BRNCODE*
      - *INTACTID*
      - *REFNO*
      - *SKLOCID*
      - *SKAC*
    - *Corp-Actions-Due-Full*
      - *BRNCODE*
      - *INTACTID*
      - *REFNO*
      - *REFNOTYPE*
      - *SKLOCID*
      - *SKAC*
      - *SECID*
      - *PFID*
      - *CORPACTTYPE*
      - *CORPACTDT*
      - *BASISUNTNOM*

COUPAMTDUE
INITDVDAMTDUE
INITBNSDUE
REINVSTDDVD
REINVSTDBNS
RESIDDVDAMTDUE
RESIDBNSAMTDUE
CURBONUSENCSHD
CSHSTKOPTN
STKCSHOPTN
RIGHTSDUE
WRNTSDUE
RIGHTSEXRCSD
WRNTSEXRCSD
INITNVALDT
COLLTNVALDT
LIQVALDT
INITNSTATFLG
COLLTNSTATFLG
LIQSTATFLG
INITNTXNDT
COLLTNTXNDT
LIQTXNDT
INITNAUTOMANUFLG
COLLTNAUTOMANUFLG
LIQAUTOMANUFLG
CORPACTCCY
RDMPTDUE
ADVICEGENRTD
AUTODEALREF
CAEVNTNOTFYDCN
CONVOPTNEXRCSD
PFPRD
PFTYPE
PFCIF
PFCCY
QUANTQUOT
SECCCY
CURFACEVAL
DVDBASIS
SERIES
RECDT
ISSUERPAYMNTCCY
ISSUERPAYMNTACBRN

ISSUERPAYMNTACNO
ISSUERPAYMNTEXCHRT
SKCIF
POSSKREFNO
BASISBALTYPE
DVDRT
DVDAMTPERUNT
POPLTNPOSSKESN
POPLTNPOSESN
POPLTNTXNDT
POPLTNVALDT
PREVADJSEQNO
INITNPROCSDT
COLLTNPROCSDT
LIQPROCSDT
INITNPOSSKESN
INITNPOSESN
COLLTNPOSSKESN
COLLTNPOSESN
LIQPOSSKESN
LIQPOSESN
PFPAYMNTACBRN
PFPAYMNTACNO
PFREFNO
SECREFNO
INITFACEVAL
RESLTNTSECID
RESLTNTSECQTYQUOT
RESLTNTSECCCY
RESLTNTSECCFV
STKTOCSHPRC
STKTOCSHAMT
ADJBNSENCSHD
PREVMANUEVNT
RLTDINTRNLACTID
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Corp-Actions-Due-IO

Attribute	Description
Name	Corp-Actions-Due-IO
Datatype	
Description	Includes Securities Cash Definition Corporate Actions Due Query Input Only type details

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	Indicates Safe keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Corp-Actions-Due-Full

Attribute	Description
Name	Corp-Actions-Due-Full
Datatype	
Description	Includes Securities Cash Definition Corporate Actions Due Query Full type details

TOP

BRNCODE

Attribute	Description
Name	BRNCODE
Datatype	String
Description	Indicates Branch Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REFNO

Attribute	Description
Name	REFNO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REFNOTYPE

Attribute	Description
Name	REFNOTYPE
Datatype	String
Description	Indicates Reference Number Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

SKLOCID

Attribute	Description
Name	SKLOCID
Datatype	String
Description	Indicates Safe Keeping Location Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKAC

Attribute	Description
Name	SKAC
Datatype	String
Description	Indicates Safe keeping Account
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	Indicates Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PFID

Attribute	Description
Name	PFID
Datatype	String
Description	Indicates Portfolio Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CORPACTTYPE

Attribute	Description
Name	CORPACTTYPE
Datatype	String
Description	Indicates Corporate Action Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPACTDT

Attribute	Description
Name	CORPACTDT
Datatype	Date
Description	Indicates Corporate Action Event Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISUNTNOM

Attribute	Description
Name	BASISUNTNOM
Datatype	Number
Description	Indicates Security Quantity
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COUPAMTDUE

Attribute	Description
Name	COUPAMTDUE
Datatype	Number
Description	Indicates Coupon Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INITDVDAMTDUE

Attribute	Description
Name	INITDVDAMTDUE
Datatype	Number
Description	Indicates Initial Divivdend Amount Due
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INITBNSDUE

Attribute	Description
Name	INITBNSDUE
Datatype	Number
Description	Indicates Initial Bonus
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REINVSTDDVD

Attribute	Description
Name	REINVSTDDVD
Datatype	Number
Description	Indicates Reinvested Dividend
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REINVSTDBNS

Attribute	Description

Name	REINVSTDBNS
Datatype	Number
Description	Indicates Reinvested Bonus
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESIDDVDAMTDUE

Attribute	Description
Name	RESIDDVDAMTDUE
Datatype	Number
Description	Indicates Residual Divivdend Amount Due
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESIDBNSAMTDUE

Attribute	Description
Name	RESIDBNSAMTDUE
Datatype	Number
Description	Indicates Residual Bonus
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURBONUSENCSHD

Attribute	Description
Name	CURBONUSENCSHD
Datatype	Number
Description	Indicates Bonus Encashed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CSHSTKOPTN

Attribute	Description
Name	CSHSTKOPTN
Datatype	String
Description	Indicates Cash Stock Option
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STKCSHOPTN

Attribute	Description

Name	STKCSHOPTN
Datatype	String
Description	Indicates Stock Cash Option
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RIGHTSDUE

Attribute	Description
Name	RIGHTSDUE
Datatype	Number
Description	Indicates Rights Due
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WRNTSDUE

Attribute	Description
Name	WRNTSDUE
Datatype	Number
Description	Indicates Warrants Due
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RIGHTSEXRCSD

Attribute	Description
Name	RIGHTSEXRCSD
Datatype	Number
Description	Indicates Rights Exercised
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WRNTSEXRCSD

Attribute	Description
Name	WRNTSEXRCSD
Datatype	Number
Description	Indicates Warrants Exercised
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INITNVALDT

Attribute	Description

Name	INITNVALDT
Datatype	Date
Description	Indicates Initiation Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTNVALDT

Attribute	Description
Name	COLLTNVALDT
Datatype	Date
Description	Indicates Collection Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQVALDT

Attribute	Description
Name	LIQVALDT
Datatype	Date
Description	Indicates Liquidation Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INITNSTATFLG

Attribute	Description
Name	INITNSTATFLG
Datatype	String
Description	Indicates Initiation Status Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLTNSTATFLG

Attribute	Description
Name	COLLTNSTATFLG
Datatype	String
Description	Indicates Collection Status Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQSTATFLG

Attribute	Description
Name	LIQSTATFLG
Datatype	String
Description	Indicates Liquidation Status Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INITNTXNDT

Attribute	Description
Name	INITNTXNDT
Datatype	Date
Description	Indicates Initiation Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTNTXNDT

Attribute	Description
Name	COLLTNTXNDT
Datatype	Date
Description	Indicates Collection Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQTXNDT

Attribute	Description
Name	LIQTXNDT
Datatype	Date
Description	Indicates Liquidation Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INITNAUTOMANUFLG

Attribute	Description
Name	INITNAUTOMANUFLG
Datatype	String
Description	Indicates Initiation Auto Manual Flag
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLTNAUTOMANUFLG

Attribute	Description
Name	COLLTNAUTOMANUFLG
Datatype	String
Description	Indicates Collection Auto Manual Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQAUTOMANUFLG

Attribute	Description
Name	LIQAUTOMANUFLG
Datatype	String
Description	Indicates Liquidation Auto Manual Flag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CORPACTCCY

Attribute	Description
Name	CORPACTCCY
Datatype	String
Description	Indicates Corporate Actions Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RDMPTDUE

Attribute	Description
Name	RDMPTDUE
Datatype	Number
Description	Indicates Redemption Due
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADVICEGENRTD

Attribute	Description
Name	ADVICEGENRTD
Datatype	String
Description	Indicates Advice Generated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTODEALREF

Attribute	Description
Name	AUTODEALREF
Datatype	String
Description	Indicates Auto Deal Reference
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CAEVNTNOTFYDCN

Attribute	Description
Name	CAEVNTNOTFYDCN
Datatype	String
Description	Indicates Caevent Notify DCN
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONVOPTNEXRCSD

Attribute	Description
Name	CONVOPTNEXRCSD
Datatype	String
Description	Indicates Conv Option Exercised
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PFPRD

Attribute	Description
Name	PFPRD

Datatype	String
Description	Indicates Portfolio Product
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PFTYPE

Attribute	Description
Name	PFTYPE
Datatype	String
Description	Indicates Portfolio Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PFCIF

Attribute	Description
Name	PFCIF
Datatype	String
Description	Indicates Portfolio CIF
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PFCCY

Attribute	Description
Name	PFCCY
Datatype	String
Description	Indicates Portfolio Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

QUANTQUOT

Attribute	Description
Name	QUANTQUOT
Datatype	String
Description	Indicates Quantity Quotation

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SECCCY

Attribute	**Description**	
Name	SECCCY	
Datatype	String	
Description	Indicates Security Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CURFACEVAL

Attribute	**Description**	
Name	CURFACEVAL	
Datatype	Number	
Description	Indicates Current Face value	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DVDBASIS

Attribute	**Description**	
Name	DVDBASIS	
Datatype	String	
Description	Indicates Dividend Basis	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

SERIES

Attribute	**Description**	
Name	SERIES	
Datatype	String	
Description	Indicates Series	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

RECDT

Attribute	Description
Name	RECDT
Datatype	Date
Description	Indicates Record Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUERPAYMNTCCY

Attribute	Description
Name	ISSUERPAYMNTCCY
Datatype	String
Description	Indicates Issuer payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSUERPAYMNTACBRN

Attribute	Description
Name	ISSUERPAYMNTACBRN
Datatype	String
Description	Indicates Issuer payment Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSUERPAYMNTACNO

Attribute	Description
Name	ISSUERPAYMNTACNO
Datatype	String
Description	Indicates Issuer payment Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ISSUERPAYMNTEXCHRT

Attribute	Description
Name	ISSUERPAYMNTEXCHRT

Datatype	Number
Description	Indicates Issuer payment Exchange rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SKCIF

Attribute	Description
Name	SKCIF
Datatype	String
Description	Indicates Safe Keeping CIF
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

POSSKREFNO

Attribute	Description
Name	POSSKREFNO
Datatype	String
Description	Indicates Position Safe keeping Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BASISBALTYPE

Attribute	Description
Name	BASISBALTYPE
Datatype	String
Description	Indicates Basis Balance Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DVDRT

Attribute	Description
Name	DVDRT
Datatype	Number
Description	Indicates Dividend Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DVDAMTPERUNT

Attribute	Description
Name	DVDAMTPERUNT
Datatype	Number
Description	Indicates Dividend Amount Per Unit
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POPLTNPOSSKESN

Attribute	Description
Name	POPLTNPOSSKESN
Datatype	Number
Description	Indicates Population Position Safe Keeping ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POPLTNPOSESN

Attribute	Description
Name	POPLTNPOSESN
Datatype	Number
Description	Indicates Population Position ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POPLTNTXNDT

Attribute	Description
Name	POPLTNTXNDT
Datatype	Date
Description	Indicates Population Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POPLTNVALDT

Attribute	Description
Name	POPLTNVALDT
Datatype	Date
Description	Indicates Population Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVADJSEQNO

Attribute	Description
Name	PREVADJSEQNO
Datatype	String
Description	Indicates Pervious Adjustment Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INITNPROCSDT

Attribute	Description
Name	INITNPROCSDT
Datatype	Date
Description	Indicates Initiation Processing Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTNPROCSDT

Attribute	Description
Name	COLLTNPROCSDT
Datatype	Date
Description	Indicates Collection Processing Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQPROCSDT

Attribute	Description
Name	LIQPROCSDT
Datatype	Date
Description	Indicates Liquidation Processing Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INITNPOSSKESN

Attribute	Description
Name	INITNPOSSKESN
Datatype	Number
Description	Indicates Initiation Position Safe Keeping ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INITNPOSESN

Attribute	Description
Name	INITNPOSESN
Datatype	Number
Description	Indicates Initiation Position ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTNPOSSKESN

Attribute	Description
Name	COLLTNPOSSKESN
Datatype	Number
Description	Indicates Collection Position Safe Keeping ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTNPOSESN

Attribute	Description
Name	COLLTNPOSESN
Datatype	Number
Description	Indicates Collection Position ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQPOSSKESN

Attribute	Description
Name	LIQPOSSKESN
Datatype	Number
Description	Indicates Liquidation Position Safe Keeping ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQPOSESN

Attribute	Description
Name	LIQPOSESN
Datatype	Number
Description	Indicates Liquidation Position ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PFPAYMNTACBRN

Attribute	Description
Name	PFPAYMNTACBRN
Datatype	String
Description	Indicates Portfolio Payment Account Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PFPAYMNTACNO

Attribute	Description
Name	PFPAYMNTACNO
Datatype	String
Description	Indicates Portfolio Payment Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PFREFNO

Attribute	Description
Name	PFREFNO
Datatype	String
Description	Indicates Portfolio Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECREFNO

Attribute	Description
Name	SECREFNO
Datatype	String
Description	Indicates Security Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INITFACEVAL

Attribute	Description

Name	INITFACEVAL
Datatype	Number
Description	Indicates Initial Face Value
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESLTNTSECID

Attribute	Description
Name	RESLTNTSECID
Datatype	String
Description	Indicates Resultant Security Id
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RESLTNTSECQTYQUOT

Attribute	Description
Name	RESLTNTSECQTYQUOT
Datatype	String
Description	Indicates Resultant Security Quantity Quotation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RESLTNTSECCCY

Attribute	Description
Name	RESLTNTSECCCY
Datatype	String
Description	Indicates Resultant Security Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RESLTNTSECCFV

Attribute	Description
Name	RESLTNTSECCFV
Datatype	Number
Description	Indicates Resultant Security CFV
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STKTOCSHPRC

Attribute	Description
Name	STKTOCSHPRC
Datatype	Number
Description	Indicates Stock To Cash Price
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STKTOCSHAMT

Attribute	Description
Name	STKTOCSHAMT
Datatype	Number
Description	Indicates Stock To Cash Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJBNSENCSHD

Attribute	Description
Name	ADJBNSENCSHD
Datatype	Number
Description	Indicates Adjusted bonus Encashed
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVMANUEVNT

Attribute	Description
Name	PREVMANUEVNT
Datatype	String
Description	Indicates Previous Manual Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

RLTDINTRNLACTID

Attribute	Description
Name	RLTDINTRNLACTID
Datatype	String
Description	Indicates Related internal Action Id
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	**Description**	
Name	MAKERID	
Datatype	String	
Description	Indicates Maker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	**Description**	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Maker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	**Description**	
Name	CHECKERID	
Datatype	String	
Description	Indicates Checker ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	**Description**	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Checker Date Time:	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.134.QuerySECouponDefn

Query for Coupon

2.134.1.SP-QuerySECouponDefn-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Coupon-IO*
    - *INTACTID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Coupon-IO

Attribute	Description
Name	Coupon-IO
Datatype	
Description	Includes Securities Coupon Definition Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.134.2.SP-QuerySECouponDefn-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Coupon-IO*
      - *INTACTID*
    - *Coupon-Full*
      - *INTACTID*
      - *EXTACTID*
      - *INTSECID*
      - *EVENTDT*
      - *RECDT*
      - *ISSUERREF*
      - *ISSUERPAYMNTCCY*
      - *EXCHRATEFIXDT*
      - *EXCHRATE*
      - *CONFIRMED*
      - *CONFIRMEDDT*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*

MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Event_Narrative
INTACTID
EVENTNARTV01
EVENTNARTV02
EVENTNARTV03
EVENTNARTV04
EVENTNARTV05
EVENTNARTV06
EVENTNARTV07
EVENTNARTV08
EVENTNARTV09
EVENTNARTV10
Seccorat
INTACTID
INTSECID
ISSUERPAYMNTCCY
Caevent_Tax_Xrate
INTACTID
TAXCOMPONENT
TAXCCY
SECCCY
TAXCOMPUTATIONXRATE
ISSUERPAYMNTCCY
ISSUERPAYMNTXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Coupon-IO

Attribute	Description
Name	Coupon-IO
Datatype	
Description	Includes Securities Coupon Definition Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Coupon-Full

Attribute	Description
Name	Coupon-Full
Datatype	
Description	Includes Securities Coupon Definition Query Full type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTACTID

Attribute	Description
Name	EXTACTID
Datatype	String
Description	Indicates the External Action Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates the Internal Security ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTDT

Attribute	**Description**	
Name	EVENTDT	
Datatype	Date	
Description	Indicates the Event Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECDT

Attribute	**Description**	
Name	RECDT	
Datatype	Date	
Description	Indicates the Record Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSUERREF

Attribute	**Description**	
Name	ISSUERREF	
Datatype	String	
Description	Indicates the Issuer Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISSUERPAYMNTCCY

Attribute	**Description**	
Name	ISSUERPAYMNTCCY	
Datatype	String	
Description	Indicates the Issuer Payment Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXCHRATEFIXDT

Attribute	Description
Name	EXCHRATEFIXDT
Datatype	Date
Description	Indicates the Exchange Rate Fixing Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates the Confirmed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONFIRMEDDT

Attribute	Description
Name	CONFIRMEDDT
Datatype	Date
Description	Indicates the Confirmed Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the Maker Date Stamp	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Checker ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Event_Narrative

Attribute	Description
Name	Event_Narrative
Datatype	
Description	Includes the Event Narrative Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTNARTV01

Attribute	Description	
Name	EVENTNARTV01	
Datatype	String	
Description	Indicates the Event Narrative 01.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV02

Attribute	Description	
Name	EVENTNARTV02	
Datatype	String	
Description	Indicates the Event Narrative 02.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV03

Attribute	Description	
Name	EVENTNARTV03	
Datatype	String	
Description	Indicates the Event Narrative 03.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV04

Attribute	Description	
Name	EVENTNARTV04	
Datatype	String	
Description	Indicates the Event Narrative 04.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV05

Attribute	Description	
Name	EVENTNARTV05	
Datatype	String	
Description	Indicates the Event Narrative 05.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV06

Attribute	Description	
Name	EVENTNARTV06	
Datatype	String	
Description	Indicates the Event Narrative 06.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV07

Attribute	Description	
Name	EVENTNARTV07	
Datatype	String	
Description	Indicates the Event Narrative 07.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV08

Attribute	Description	
Name	EVENTNARTV08	
Datatype	String	
Description	Indicates the Event Narrative 08.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV09

Attribute	Description
Name	EVENTNARTV09
Datatype	String
Description	Indicates the Event Narrative 09.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV10

Attribute	Description
Name	EVENTNARTV10
Datatype	String
Description	Indicates the Event Narrative 10.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Seccorat

Attribute	Description
Name	Seccorat
Datatype	
Description	Includes the security commodity rate details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates the Internal Security ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISSUERPAYMNTCCY

Attribute	**Description**	
Name	ISSUERPAYMNTCCY	
Datatype	String	
Description	Indicates the Issuer Payment Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Caevent_Tax_Xrate

Attribute	**Description**	
Name	Caevent_Tax_Xrate	
Datatype		
Description	Includes the CA Event Tax Exchange Rate.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTACTID

Attribute	**Description**	
Name	INTACTID	
Datatype	String	
Description	Indicates the Internal Action ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TAXCOMPONENT

Attribute	**Description**	
Name	TAXCOMPONENT	
Datatype	String	
Description	Indicates the Tax Component.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	Indicates the Tax Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SECCCY

Attribute	Description
Name	SECCCY
Datatype	String
Description	Indicates the Security Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXCOMPUTATIONXRATE

Attribute	Description
Name	TAXCOMPUTATIONXRATE
Datatype	Number
Description	Indicates the Tax computation Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUERPAYMNTCCY

Attribute	Description
Name	ISSUERPAYMNTCCY
Datatype	String
Description	Indicates the Issuer Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSUERPAYMNTXRATE

Attribute	Description
Name	ISSUERPAYMNTXRATE

Datatype	Number
Description	Indicates the Issuer Payment Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.135.QuerySECpnDefinition

QuerySECpnDefinition

2.135.1.SP-QuerySECpnDefinition-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Sec-IO*
  - *INAD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sec-IO

Attribute	Description
Name	Sec-IO
Datatype	
Description	

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.135.2.SP-QuerySECpnDefinition-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sec-IO*
      - *INAD*
    - *Sec-Full*
      - *INAD*
      - *EXAD*
      - *INSD*
      - *EVDT*
      - *RCDT*
      - *ISREF*
      - *ISPC*
      - *EXRFDT*
      - *EXRT*
      - *CONF*
      - *CONFDT*
      - *CCNA*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*

CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Senar
INAD
ENAR1
ENAR2
ENAR3
ENAR4
ENAR5
ENAR6
ENAR7
ENAR8
ENAR9
ENAR10
Itds
INAD
INSD
ISPC
Sctx
TACOMP
TAXCC
TACER
ISPCC
ISPER
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sec-IO

Attribute	Description
Name	Sec-IO
Datatype	
Description	

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sec-Full

Attribute	Description
Name	Sec-Full
Datatype	
Description	

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXAD

Attribute	Description
Name	EXAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSD

Attribute	Description
Name	INSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RCDT

Attribute	Description
Name	RCDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISREF

Attribute	Description
Name	ISREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISPC

Attribute	Description
Name	ISPC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

EXRFDT

Attribute	Description
Name	EXRFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONFDT

Attribute	Description
Name	CONFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CCNA

Attribute	Description
Name	CCNA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Senar

Attribute	Description	
Name	Senar	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INAD

Attribute	Description	
Name	INAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ENAR1

Attribute	Description
Name	ENAR1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ENAR2

Attribute	Description
Name	ENAR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ENAR3

Attribute	Description
Name	ENAR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ENAR4

Attribute	Description
Name	ENAR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ENAR5

Attribute	Description
Name	ENAR5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ENAR6

Attribute	**Description**	
Name	ENAR6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ENAR7

Attribute	**Description**	
Name	ENAR7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ENAR8

Attribute	**Description**	
Name	ENAR8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ENAR9

Attribute	**Description**	
Name	ENAR9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ENAR10

Attribute	Description
Name	ENAR10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Itds

Attribute	Description
Name	Itds
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSD

Attribute	Description
Name	INSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISPC

Attribute	Description
Name	ISPC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Sctx

Attribute	Description
Name	Sctx
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TACOMP

Attribute	Description
Name	TACOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCC

Attribute	Description
Name	TAXCC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TACER

Attribute	Description
Name	TACER
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISPCC

Attribute	Description
Name	ISPCC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISPER

Attribute	Description
Name	ISPER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE

Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.136.QuerySECpnDividend

QuerySECpnDividend

2.136.1.SP-QuerySECpnDividend-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Scd-IO*
    - *INAD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Scd-IO

Attribute	Description
Name	Scd-IO
Datatype	
Description	

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.136.2.SP-QuerySECpnDividend-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Scd-IO*
      - *INAD*
    - *Scd-Full*
      - *INAD*
      - *EXAD*
      - *INSD*
      - *ANDT*
      - *EVDT*
      - *REDT*
      - *ISREF*
      - *DVTYP*
      - *DVRT*
      - *DVAMT*
      - *ISPC*
      - *EXRFD*
      - *EXRT*
      - *DISFR*
      - *CONF*

CONFDT
SECC
SECDS
CCNA
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Sena
INAD
EVNR1
EVNR2
EVNR3
EVNR4
EVNR5
EVNR6
EVNR7
EVNR8
EVNR9
EVNR10
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Scd-IO

Attribute	Description
Name	Scd-IO
Datatype	
Description	

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Scd-Full

Attribute	Description
Name	Scd-Full
Datatype	
Description	

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXAD

Attribute	Description
Name	EXAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSD

Attribute	Description
Name	INSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ANDT

Attribute	Description
Name	ANDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REDT

Attribute	Description
Name	REDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

ISREF

Attribute	Description
Name	ISREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

DVTYP

Attribute	Description
Name	DVTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,R,A</td></tr></table>

TOP

DVRT

Attribute	Description
Name	DVRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DVAMT

Attribute	Description
Name	DVAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISPC

Attribute	Description
Name	ISPC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRFD

Attribute	Description
Name	EXRFD
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISFR

Attribute	Description
Name	DISFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,RN,RU,RD,RS

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONFDT

Attribute	Description
Name	CONFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECC

Attribute	Description
Name	SECC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECDS

Attribute	Description
Name	SECDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CCNA

Attribute	Description
Name	CCNA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Sena

Attribute	Description
Name	Sena
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INAD

Attribute	Description
Name	INAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVNR1

Attribute	Description
Name	EVNR1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNR2

Attribute	Description
Name	EVNR2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNR3

Attribute	Description
Name	EVNR3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNR4

Attribute	Description
Name	EVNR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNR5

Attribute	Description
Name	EVNR5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNR6

Attribute	Description
Name	EVNR6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNR7

Attribute	Description
Name	EVNR7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNR8

Attribute	Description
Name	EVNR8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNR9

Attribute	Description
Name	EVNR9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNR10

Attribute	Description
Name	EVNR10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.137.QuerySEDividend

Query for Cash Dividend Definition

2.137.1.SP-QuerySEDividend-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cash-Dividend-IO*
    - *INTACTID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Cash-Dividend-IO

Attribute	Description
Name	Cash-Dividend-IO
Datatype	
Description	Includes Securities Cash Dividend Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.137.2.SP-QuerySEDividend-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cash-Dividend-IO*
      - *INTACTID*
    - *Cash-Dividend-Full*
      - *INTACTID*
      - *EXTACTID*
      - *INTSECID*
      - *ANNOUNCEMNTDT*
      - *EVENTDT*
      - *RECDT*
      - *ISSUERREF*
      - *DVDTYPE*
      - *DVDRATE*
      - *DVDAMT*
      - *ISSUERPAYMNTCCY*
      - *EXCHRATEFIXDT*
      - *EXCHRATE*
      - *DISPOSEFRAC*
      - *CONFIRMED*

CONFIRMEDDT
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Event_Narrative
INTACTID
EVENTNARTV01
EVENTNARTV02
EVENTNARTV03
EVENTNARTV04
EVENTNARTV05
EVENTNARTV06
EVENTNARTV07
EVENTNARTV08
EVENTNARTV09
EVENTNARTV10
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cash-Dividend-IO

Attribute	Description
Name	Cash-Dividend-IO
Datatype	
Description	Includes Securities Cash Dividend Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Cash-Dividend-Full

Attribute	Description
Name	Cash-Dividend-Full
Datatype	
Description	Includes Securities Cash Dividend Query Full type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTACTID

Attribute	Description
Name	EXTACTID
Datatype	String
Description	Indicates External Action Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates Internal Security ID

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ANNOUNCEMNTDT

Attribute	**Description**	
Name	ANNOUNCEMNTDT	
Datatype	Date	
Description	Indicates Announcement Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVENTDT

Attribute	**Description**	
Name	EVENTDT	
Datatype	Date	
Description	Indicates Event Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RECDT

Attribute	**Description**	
Name	RECDT	
Datatype	Date	
Description	Indicates Record Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSUERREF

Attribute	**Description**	
Name	ISSUERREF	
Datatype	String	
Description	Indicates Issuer Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

DVDTYPE

Attribute	**Description**
Name	DVDTYPE

Datatype	String
Description	Indicates Dividend Type AMOUNT : A RATE : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,R,

TOP

DVDRATE

Attribute	Description
Name	DVDRATE
Datatype	Number
Description	Indicates Dividend Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DVDAMT

Attribute	Description
Name	DVDAMT
Datatype	Number
Description	Indicates Dividend Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUERPAYMNTCCY

Attribute	Description
Name	ISSUERPAYMNTCCY
Datatype	String
Description	Indicates Issuer Payment Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCHRATEFIXDT

Attribute	Description
Name	EXCHRATEFIXDT
Datatype	Date
Description	Indicates Exchange Rate Fixing Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISPOSEFRAC

Attribute	Description
Name	DISPOSEFRAC
Datatype	String
Description	Indicates Dispose Fractions ROUND STANDARD : RS ROUND UP : RU ROUND DOWN : RD RETAIN : RN
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RD,RN,RS,RU,

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates Confirmed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONFIRMEDDT

Attribute	Description
Name	CONFIRMEDDT
Datatype	Date
Description	Indicates Confirmed Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO

Datatype	Number
Description	Indicates Modification Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates Authorization Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates Once Authorization status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Event_Narrative

Attribute	Description
Name	Event_Narrative
Datatype	
Description	Includes Event Narrative details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACTID

Attribute	Description	
Name	INTACTID	
Datatype	String	
Description	Indicates Internal Action ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTNARTV01

Attribute	Description	
Name	EVENTNARTV01	
Datatype	String	
Description	Indicates Event Narrative 01	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV02

Attribute	Description	
Name	EVENTNARTV02	
Datatype	String	
Description	Indicates Event Narrative 02	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV03

Attribute	Description	
Name	EVENTNARTV03	
Datatype	String	
Description	Indicates Event Narrative 03	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV04

Attribute	Description
Name	EVENTNARTV04
Datatype	String
Description	Indicates Event Narrative 04
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVENTNARTV05

Attribute	Description
Name	EVENTNARTV05
Datatype	String
Description	Indicates Event Narrative 05
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVENTNARTV06

Attribute	Description
Name	EVENTNARTV06
Datatype	String
Description	Indicates Event Narrative 06
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVENTNARTV07

Attribute	Description
Name	EVENTNARTV07
Datatype	String
Description	Indicates Event Narrative 07
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVENTNARTV08

Attribute	Description
Name	EVENTNARTV08

Datatype	String
Description	Indicates Event Narrative 08
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV09

Attribute	Description
Name	EVENTNARTV09
Datatype	String
Description	Indicates Event Narrative 09
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV10

Attribute	Description
Name	EVENTNARTV10
Datatype	String
Description	Indicates Event Narrative 10
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	Includes User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	2
minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.138.QuerySEIntRateRevision

QuerySEIntRateRevision

2.138.1.SP-QuerySEIntRateRevision-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Setms-Interest-Revision-IO*
  - *SE_INTERNAL_ACTION_ID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Setms-Interest-Revision-IO

Attribute	Description
Name	Setms-Interest-Revision-IO
Datatype	
Description	

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>64</td></tr></table>

TOP

2.138.2.SP-QuerySEIntRateRevision-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Setms-Interest-Revision-IO*
      - *SE_INTERNAL_ACTION_ID*
    - *Setms-Interest-Revision-Full*
      - *SE_INTERNAL_ACTION_ID*
      - *SE_EXTERNAL_ACTION_ID*
      - *SE_INTERNAL_SECURITY_ID*
      - *SE_ISSUER_REFERENCE*
      - *SE_INTEREST_COMPONENT*
      - *SE_ANNOUNCEMENT_DATE*
      - *EVENT_DATE*
      - *EFFECTIVE_DATE*
      - *SE_REV_RATE*
      - *CONFIRMED*
      - *SE_CONFIRMATION_DATE*
      - *SE_AUTO_MANUAL*
      - *SE_MIS_RATE*
      - *SE_SECURITY_DESCRIPTION*
      - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Int-Rev-History
SE_INTERNAL_ACTION_ID
SE_INTERNAL_SECURITY_ID
SE_INTEREST_COMPONENT
EFF_DATE
SE_REV_RATE
MAKER_ID
MAKER_DT_STAMP
CHECKER_ID
CHECKER_DT_STAMP
Event-Narr
SE_INTERNAL_ACTION_ID
SE_BLANK_NARR1
SE_BLANK_NARR2
SE_BLANK_NARR3
SE_BLANK_NARR4
SE_BLANK_NARR5
SE_BLANK_NARR6
SE_BLANK_NARR7
SE_BLANK_NARR8
SE_BLANK_NARR9
SE_BLANK_NARR10
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Setms-Interest-Revision-IO

Attribute	Description
Name	Setms-Interest-Revision-IO
Datatype	
Description	

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

Setms-Interest-Revision-Full

Attribute	Description
Name	Setms-Interest-Revision-Full
Datatype	
Description	

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

SE_EXTERNAL_ACTION_ID

Attribute	Description
Name	SE_EXTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

SE_INTERNAL_SECURITY_ID

Attribute	Description
Name	SE_INTERNAL_SECURITY_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	64

TOP

SE_ISSUER_REFERENCE

Attribute	**Description**	
Name	SE_ISSUER_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	64

TOP

SE_INTEREST_COMPONENT

Attribute	**Description**	
Name	SE_INTEREST_COMPONENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

SE_ANNOUNCEMENT_DATE

Attribute	**Description**	
Name	SE_ANNOUNCEMENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EVENT_DATE

Attribute	**Description**	
Name	EVENT_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SE_REV_RATE

Attribute	Description
Name	SE_REV_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SE_CONFIRMATION_DATE

Attribute	Description
Name	SE_CONFIRMATION_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SE_AUTO_MANUAL

Attribute	Description
Name	SE_AUTO_MANUAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M</td></tr></table>

TOP

SE_MIS_RATE

Attribute	Description
Name	SE_MIS_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SE_SECURITY_DESCRIPTION

Attribute	Description
Name	SE_SECURITY_DESCRIPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Int-Rev-History

Attribute	Description
Name	Int-Rev-History
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SE_INTERNAL_ACTION_ID

Attribute	Description
Name	SE_INTERNAL_ACTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

SE_INTERNAL_SECURITY_ID

Attribute	Description
Name	SE_INTERNAL_SECURITY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

SE_INTEREST_COMPONENT

Attribute	Description
Name	SE_INTEREST_COMPONENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 40

TOP

EFF_DATE

Attribute	Description
Name	EFF_DATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SE_REV_RATE

Attribute	Description
Name	SE_REV_RATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

MAKER_ID

Attribute	Description
Name	MAKER_ID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>48</td></tr></table>

TOP

MAKER_DT_STAMP

Attribute	Description
Name	MAKER_DT_STAMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHECKER_ID

Attribute	Description
Name	CHECKER_ID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	48

TOP

CHECKER_DT_STAMP

Attribute	**Description**	
Name	CHECKER_DT_STAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Event-Narr

Attribute	**Description**	
Name	Event-Narr	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SE_INTERNAL_ACTION_ID

Attribute	**Description**	
Name	SE_INTERNAL_ACTION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	64

TOP

SE_BLANK_NARR1

Attribute	**Description**	
Name	SE_BLANK_NARR1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	420

TOP

SE_BLANK_NARR2

Attribute	Description
Name	SE_BLANK_NARR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

TOP

SE_BLANK_NARR3

Attribute	Description
Name	SE_BLANK_NARR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

TOP

SE_BLANK_NARR4

Attribute	Description
Name	SE_BLANK_NARR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

TOP

SE_BLANK_NARR5

Attribute	Description
Name	SE_BLANK_NARR5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

TOP

SE_BLANK_NARR6

Attribute	Description
Name	SE_BLANK_NARR6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

TOP

SE_BLANK_NARR7

Attribute	Description
Name	SE_BLANK_NARR7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

TOP

SE_BLANK_NARR8

Attribute	Description
Name	SE_BLANK_NARR8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

TOP

SE_BLANK_NARR9

Attribute	Description
Name	SE_BLANK_NARR9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

TOP

SE_BLANK_NARR10

Attribute	Description
Name	SE_BLANK_NARR10

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 420

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates the Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates the Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.139.QuerySERWExpiry

Query for Rights/Warrants Expiry Event

2.139.1.SP-QuerySERWExpiry-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Expiry-IO*
    - *INTACTID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about IORequest

TOP

Expiry-IO

Attribute	Description
Name	Expiry-IO
Datatype	
Description	Includes Securities Rights/Warrants Expiry Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.139.2.SP-QuerySERWExpiry-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Expiry-IO*
      - *INTACTID*
    - *Expiry-Full*
      - *INTACTID*
      - *EXTACTID*
      - *INTSECID*
      - *EVENTDT*
      - *EOTRDDT*
      - *CONFIRMED*
      - *CONFIRMEDDT*
      - *ISSUERREF*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH
Event_Narrative
INTACTID
EVENTNARTV01
EVENTNARTV02
EVENTNARTV03
EVENTNARTV04
EVENTNARTV05
EVENTNARTV06
EVENTNARTV07
EVENTNARTV08
EVENTNARTV09
EVENTNARTV10
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This xsd Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Expiry-IO

Attribute	Description
Name	Expiry-IO
Datatype	
Description	Includes Securities Rights/Warrants Expiry Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Expiry-Full

Attribute	Description
Name	Expiry-Full
Datatype	
Description	Includes Securities Rights/Warrants Expiry Query Full type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTACTID

Attribute	Description
Name	EXTACTID
Datatype	String
Description	Indicates External Action Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates Internal Security ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTDT

Attribute	Description
Name	EVENTDT
Datatype	Date
Description	Indicates Event Date

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EOTRDDT

Attribute	**Description**	
Name	EOTRDDT	
Datatype	Date	
Description	Indicates the End of Trading Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONFIRMED

Attribute	**Description**	
Name	CONFIRMED	
Datatype	String	
Description	Indicates Confirmed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CONFIRMEDDT

Attribute	**Description**	
Name	CONFIRMEDDT	
Datatype	Date	
Description	Indicates Confirmed Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSUERREF

Attribute	**Description**	
Name	ISSUERREF	
Datatype	String	
Description	Indicates Issuer Reference	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	**Description**
Name	MAKERID

Datatype	String
Description	Indicates Maker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Maker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates Checker ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates Checker Date Time:
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECSTAT

Attribute	**Description**	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorization status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Event_Narrative

Attribute	**Description**	
Name	Event_Narrative	
Datatype		
Description	Includes Event Narrative details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates Internal Action ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTNARTV01

Attribute	Description
Name	EVENTNARTV01
Datatype	String
Description	Indicates Event Narrative 01
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV02

Attribute	Description
Name	EVENTNARTV02
Datatype	String
Description	Indicates Event Narrative 02
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV03

Attribute	Description
Name	EVENTNARTV03
Datatype	String
Description	Indicates Event Narrative 03
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV04

Attribute	Description
Name	EVENTNARTV04

Datatype	String
Description	Indicates Event Narrative 04
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV05

Attribute	Description
Name	EVENTNARTV05
Datatype	String
Description	Indicates Event Narrative 05
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV06

Attribute	Description
Name	EVENTNARTV06
Datatype	String
Description	Indicates Event Narrative 06
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV07

Attribute	Description
Name	EVENTNARTV07
Datatype	String
Description	Indicates Event Narrative 07
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVENTNARTV08

Attribute	Description
Name	EVENTNARTV08
Datatype	String
Description	Indicates Event Narrative 08

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV09

Attribute	**Description**	
Name	EVENTNARTV09	
Datatype	String	
Description	Indicates Event Narrative 09	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV10

Attribute	**Description**	
Name	EVENTNARTV10	
Datatype	String	
Description	Indicates Event Narrative 10	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

UDFDETAILS

Attribute	**Description**	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.140.QuerySERateRevision

Query for Interest Rate Revision

2.140.1.SP-QuerySERateRevision-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Interest-Revision-IO*
    - *INTACTID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Interest-Revision-IO

Attribute	Description
Name	Interest-Revision-IO
Datatype	
Description	Includes Securities Rate Interest revision Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.140.2.SP-QuerySERateRevision-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Interest-Revision-IO*
      - *INTACTID*
    - *Interest-Revision-Full*
      - *INTACTID*
      - *EXTACTID*
      - *INTSECID*
      - *ISSUERREF*
      - *INTRSTCOMPONT*
      - *ANNOUNCEMENTDT*
      - *EVENTDT*
      - *EFFECTIVEDT*
      - *REVISIONRATE*
      - *CONFIRMED*
      - *CONFIRMEDDT*
      - *MISREFRATE*
      - *AUTOORMANUAL*
      - *MAKERID*
      - *MAKERDTSTAMP*

- *CHECKERID*
- *CHECKERDTSTAMP*
- *MODNO*
- *AUTHSTAT*
- *RECSTAT*
- *ONCEAUTH*
- *Interest-Rev-His*
  - *INTACTID*
  - *INTSECID*
  - *INTCOMPONENT*
  - *EFFDT*
  - *REVRATE*
  - *MAKERID*
  - *MAKERDTSTAMP*
  - *CHECKERID*
  - *CHECKERDTSTAMP*
  - *MODNO*
- *Event-Narrative*
  - *INTACTID*
  - *EVENTNARTV01*
  - *EVENTNARTV02*
  - *EVENTNARTV03*
  - *EVENTNARTV04*
  - *EVENTNARTV05*
  - *EVENTNARTV06*
  - *EVENTNARTV07*
  - *EVENTNARTV08*
  - *EVENTNARTV09*
  - *EVENTNARTV10*
- *UDFDETAILS*
  - *FUNCTIONID*
  - *FIELD_NAME*
  - *DATATYPE*
  - *FIELD_VALUE*
  - *VAL_TYPE*

FCUBS_ERROR_RESP

- *ERROR*
  - *ECODE*
  - *EDESC*

FCUBS_WARNING_RESP

- *WARNING*
  - *WCODE*
  - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Interest-Revision-IO

Attribute	Description
Name	Interest-Revision-IO
Datatype	
Description	Includes Securities Rate Interest revision Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Interest-Revision-Full

Attribute	Description
Name	Interest-Revision-Full
Datatype	
Description	Includes Securities Rate Interest revision Query Full type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTACTID

Attribute	Description
Name	EXTACTID
Datatype	String
Description	Indicates the External Action Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates the Internal Security ID.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERREF

Attribute	Description
Name	ISSUERREF
Datatype	String
Description	Indicates the Issuer Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTRSTCOMPONT

Attribute	Description
Name	INTRSTCOMPONT
Datatype	String
Description	Indicates the interest Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

ANNOUNCEMENTDT

Attribute	Description
Name	ANNOUNCEMENTDT
Datatype	Date
Description	Indicates the Announcement Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENTDT

Attribute	Description
Name	EVENTDT

Datatype	Date
Description	Indicates the Event Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates the Effective Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVISIONRATE

Attribute	Description
Name	REVISIONRATE
Datatype	Number
Description	Indicates the Revision Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates the Confirmed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CONFIRMEDDT

Attribute	Description
Name	CONFIRMEDDT
Datatype	Date
Description	Indicates the Confirmed Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISREFRATE

Attribute	Description
Name	MISREFRATE

Datatype	Number
Description	Indicates the reference Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTOORMANUAL

Attribute	Description
Name	AUTOORMANUAL
Datatype	String
Description	Indicates whether Auto or Manual.A - Auto, M - Manual.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Interest-Rev-His

Attribute	Description
Name	Interest-Rev-His
Datatype	
Description	Includes the Interest Revision History.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates the Internal Security ID.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INTCOMPONENT

Attribute	Description
Name	INTCOMPONENT
Datatype	String

Description	Indicates the Interest Component.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	Indicates the Effective Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVRATE

Attribute	Description
Name	REVRATE
Datatype	Number
Description	Indicates the Revision Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Event-Narrative

Attribute	Description
Name	Event-Narrative
Datatype	
Description	Includes the Event Narrative Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTNARTV01

Attribute	Description	
Name	EVENTNARTV01	
Datatype	String	
Description	Indicates the Event Narrative 01.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV02

Attribute	Description	
Name	EVENTNARTV02	
Datatype	String	
Description	Indicates the Event Narrative 02.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV03

Attribute	Description	
Name	EVENTNARTV03	
Datatype	String	
Description	Indicates the Event Narrative 03.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV04

Attribute	Description	
Name	EVENTNARTV04	
Datatype	String	
Description	Indicates the Event Narrative 04.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV05

Attribute	Description
Name	EVENTNARTV05
Datatype	String
Description	Indicates the Event Narrative 05.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV06

Attribute	Description
Name	EVENTNARTV06
Datatype	String
Description	Indicates the Event Narrative 06.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV07

Attribute	Description
Name	EVENTNARTV07
Datatype	String
Description	Indicates the Event Narrative 07.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV08

Attribute	Description
Name	EVENTNARTV08
Datatype	String
Description	Indicates the Event Narrative 08.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVENTNARTV09

Attribute	Description	
Name	EVENTNARTV09	
Datatype	String	
Description	Indicates the Event Narrative 09	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV10

Attribute	Description	
Name	EVENTNARTV10	
Datatype	String	
Description	Indicates the Event Narrative 10.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.141.QuerySERedemptionDefn

QuerySERedemptionDefn

2.141.1.SP-QuerySERedemptionDefn-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Ser-IO*
  - *IACD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Ser-IO

Attribute	Description
Name	Ser-IO
Datatype	
Description	

TOP

IACD

Attribute	Description
Name	IACD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.141.2.SP-QuerySERedemptionDefn-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Ser-IO*
      - *IACD*
    - *Ser-Full*
      - *INSD*
      - *EVD*
      - *SER*
      - *PCTBR*
      - *REDPR*
      - *DOF*
      - *REDTYP*
      - *CAIN*
      - *IACD*
      - *EACD*
      - *ANDT*
      - *RECDAT*
      - *EOTD*
      - *ROTD*
      - *ISR*

ISPC
ERFDAT
EXRT
CONDT
CONFI
REDQUA
SECDES
CCYN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Sen
IACD
EVNA1
EVNA2
EVNA3
EVNA4
EVNA5
EVNA6
EVNA7
EVNA8
EVNA9
EVNA10
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength: 8 pattern: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** enumeration: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 128 pattern: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Ser-IO

Attribute	Description
Name	Ser-IO
Datatype	
Description	

TOP

IACD

Attribute	Description
Name	IACD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Ser-Full

Attribute	Description
Name	Ser-Full
Datatype	
Description	

TOP

INSD

Attribute	Description
Name	INSD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVD

Attribute	Description
Name	EVD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

SER

Attribute	Description
Name	SER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PCTBR

Attribute	Description
Name	PCTBR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPR

Attribute	Description
Name	REDPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOF

Attribute	Description
Name	DOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RS,RN,RU,RD

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / B,Q,S

TOP

CAIN

Attribute	Description
Name	CAIN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

IACD

Attribute	Description
Name	IACD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EACD

Attribute	Description
Name	EACD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ANDT

Attribute	Description
Name	ANDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RECDAT

Attribute	Description
Name	RECDAT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EOTD

Attribute	Description
Name	EOTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

ROTD

Attribute	Description
Name	ROTD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISR

Attribute	Description
Name	ISR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISPC

Attribute	Description
Name	ISPC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ERFDAT

Attribute	Description
Name	ERFDAT
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDT

Attribute	Description
Name	CONDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFI

Attribute	Description
Name	CONFI
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDQUA

Attribute	Description
Name	REDQUA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

SECDES

Attribute	Description
Name	SECDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

CCYN

Attribute	Description
Name	CCYN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Sen

Attribute	Description
Name	Sen
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

IACD

Attribute	Description
Name	IACD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

EVNA1

Attribute	Description
Name	EVNA1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNA2

Attribute	Description
Name	EVNA2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNA3

Attribute	Description
Name	EVNA3

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNA4

Attribute	Description
Name	EVNA4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNA5

Attribute	Description
Name	EVNA5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNA6

Attribute	Description
Name	EVNA6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

EVNA7

Attribute	Description
Name	EVNA7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVNA8

Attribute	**Description**	
Name	EVNA8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVNA9

Attribute	**Description**	
Name	EVNA9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVNA10

Attribute	**Description**	
Name	EVNA10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.142.QuerySERedmDefn

Query for Securities Corporate Action Maintenance - Redemption

2.142.1.SP-QuerySERedmDefn-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Redemption-IO*
    - *INTACTID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

TOP

Redemption-IO

Attribute	Description
Name	Redemption-IO
Datatype	
Description	Includes Securities Redemption Definition Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.142.2.SP-QuerySERedmDefn-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Redemption-IO*
      - *INTACTID*
    - *Redemption-Full*
      - *INTSECID*
      - *EVENTDT*
      - *SERIES*
      - *PCTTOBREDMD*
      - *REDEMPQUOT*
      - *REDMPTPRC*
      - *DISPOFRAC*
      - *REDMPTTYPE*
      - *CALLINDICATOR*
      - *FINALREDMPTINDCTR*
      - *INTACTID*
      - *EXTACTID*
      - *ANNOUNCEMNTDT*
      - *RECDT*
      - *EOTRDDT*

RESTARTOFTRDDT
ISSUERREF
ISSUERPAYMNTCCY
EXCHRATEFIXDT
EXCHRATE
CONFIRMEDDT
CONFIRMED
AUTOORMANUAL
ALPLADJNEEDED
MAKERID
MAKERDTSTAMP
CHECKERID
CHECKERDTSTAMP
MODNO
AUTHSTAT
RECSTAT
ONCEAUTH
Event-Narrative
INTACTID
EVENTNARTV01
EVENTNARTV02
EVENTNARTV03
EVENTNARTV04
EVENTNARTV05
EVENTNARTV06
EVENTNARTV07
EVENTNARTV08
EVENTNARTV09
EVENTNARTV10
UDFDETAILS
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Redemption-IO

Attribute	Description
Name	Redemption-IO
Datatype	
Description	Includes Securities Redemption Definition Query Input Only type details

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Redemption-Full

Attribute	Description
Name	Redemption-Full
Datatype	
Description	Includes Securities Redemption Definition Query Full type details

TOP

INTSECID

Attribute	Description
Name	INTSECID
Datatype	String
Description	Indicates the Security ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTDT

Attribute	Description
Name	EVENTDT
Datatype	Date
Description	Indicates the Event Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERIES

Attribute	Description
Name	SERIES
Datatype	String
Description	Indicates the Series.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

PCTTOBREDMD

Attribute	Description
Name	PCTTOBREDMD
Datatype	Number
Description	Indicates the Percentage to be Redeemed.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDEMPQUOT

Attribute	Description
Name	REDEMPQUOT
Datatype	String
Description	Indicates Redemption Quotation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C

TOP

REDMPTPRC

Attribute	Description
Name	REDMPTPRC
Datatype	Number
Description	Indicates the Redemption Percentage.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DISPOFRAC

Attribute	Description
Name	DISPOFRAC
Datatype	String
Description	Indicates the Dispose Fractions. RS - ROUND STANDARD,RN - RETAIN,RU - ROUND UP,RD - ROUND DOWN

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	RD,RN,RS,RU,

TOP

REDMPTTYPE

Attribute	**Description**	
Name	REDMPTTYPE	
Datatype	String	
Description	Indicates the Redemption Type. B - Bullet,Q - Quantity,S - Series.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,Q,S,

TOP

CALLINDICATOR

Attribute	**Description**	
Name	CALLINDICATOR	
Datatype	String	
Description	Indicates the Call Indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FINALREDMPTINDCTR

Attribute	**Description**	
Name	FINALREDMPTINDCTR	
Datatype	String	
Description	Indicates the Final redemption Indicator.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTACTID

Attribute	**Description**	
Name	INTACTID	
Datatype	String	
Description	Indicates the Internal Action ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EXTACTID

Attribute	Description
Name	EXTACTID
Datatype	String
Description	Indicates the External Action Identification.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ANNOUNCEMNTDT

Attribute	Description
Name	ANNOUNCEMNTDT
Datatype	Date
Description	Indicates the Announcement Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RECDT

Attribute	Description
Name	RECDT
Datatype	Date
Description	Indicates the Record Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EOTRDDT

Attribute	Description
Name	EOTRDDT
Datatype	Date
Description	Indicates the End of Trading Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESTARTOFTRDDT

Attribute	Description
Name	RESTARTOFTRDDT
Datatype	Date
Description	Indicates the Restart of Trading Date.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSUERREF

Attribute	Description
Name	ISSUERREF
Datatype	String
Description	Indicates the Issuer Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERPAYMNTCCY

Attribute	Description
Name	ISSUERPAYMNTCCY
Datatype	String
Description	Indicates the Issuer Payment Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXCHRATEFIXDT

Attribute	Description
Name	EXCHRATEFIXDT
Datatype	Date
Description	Indicates the Exchange Rate Fixing Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFIRMEDDT

Attribute	Description
Name	CONFIRMEDDT

Datatype	Date
Description	Indicates the Confirmed Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	Indicates the Confirmed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTOORMANUAL

Attribute	Description
Name	AUTOORMANUAL
Datatype	String
Description	Indicates whether Auto or Manual.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ALPLADJNEEDED

Attribute	Description
Name	ALPLADJNEEDED
Datatype	String
Description	Indicates the Needed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the maker ID.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the Maker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the Checker ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Indicates the Once Auth.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Event-Narrative

Attribute	Description
Name	Event-Narrative
Datatype	
Description	Includes the Event Narrative Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTACTID

Attribute	Description
Name	INTACTID
Datatype	String
Description	Indicates the Internal Action ID.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

EVENTNARTV01

Attribute	Description	
Name	EVENTNARTV01	
Datatype	String	
Description	Indicates the Event Narrative 01.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV02

Attribute	Description	
Name	EVENTNARTV02	
Datatype	String	
Description	Indicates the Event Narrative 02.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV03

Attribute	Description	
Name	EVENTNARTV03	
Datatype	String	
Description	Indicates the Event Narrative 03.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV04

Attribute	Description	
Name	EVENTNARTV04	
Datatype	String	
Description	Indicates the Event Narrative 04.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV05

Attribute	Description	
Name	EVENTNARTV05	
Datatype	String	
Description	Indicates the Event Narrative 05.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV06

Attribute	Description	
Name	EVENTNARTV06	
Datatype	String	
Description	Indicates the Event Narrative 06.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV07

Attribute	Description	
Name	EVENTNARTV07	
Datatype	String	
Description	Indicates the Event Narrative 07.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV08

Attribute	Description	
Name	EVENTNARTV08	
Datatype	String	
Description	Indicates the Event Narrative 08.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV09

Attribute	Description	
Name	EVENTNARTV09	
Datatype	String	
Description	Indicates the Event Narrative 09.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EVENTNARTV10

Attribute	Description	
Name	EVENTNARTV10	
Datatype	String	
Description	Indicates the Event Narrative 10.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes the UDF Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2 Restrictions: minLength — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes FCUBS Error Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes FCUBS Warning Response details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.143.QuerySecuritiesPortfolio

QuerySecuritiesPortfolio

2.143.1.SP-QuerySecuritiesPortfolio-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Sepm-IO*
  - *PORTFID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.143.2.SP-QuerySecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-IO*
      - *PORTFID*
    - *Sepm-Full*
      - *ACCRHTB*
      - *STHDR*
      - *STATEMENTHOLDFREQUENCY*
      - *STHSD*
      - *STATEMENTSTARTMONTH*
      - *PRVHSN*
      - *STTXR*
      - *TXNS_STATEMENT_DAY*
      - *STTXSM*
      - *PREVSSN*
      - *ACCRP*
      - *ACCRPM*
      - *ACRDIS*
      - *ACRDCM*
      - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description	
Name	REDVM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,M,X,

TOP

LOCMBA

Attribute	Description	
Name	LOCMBA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	H,,A

TOP

RERAF

Attribute	Description	
Name	RERAF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description	
Name	REREVALSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description	
Name	FDACRME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRNDS

Attribute	**Description**	
Name	BRNDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURR

Attribute	**Description**	
Name	CURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CURRDS

Attribute	**Description**	
Name	CURRDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUST

Attribute	**Description**	
Name	CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,F,D,W,</td></tr></table>

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BWARRNT

Attribute	Description
Name	BWARRNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,O,U,

TOP

CORPAR

Attribute	**Description**	
Name	CORPAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

NOTDAY

Attribute	**Description**	
Name	NOTDAY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description

Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description

Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N,</td></tr></table>

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST

Attribute	Description	
Name	CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MKID

Attribute	Description	
Name	MKID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MKDTSTMP

Attribute	Description	
Name	MKDTSTMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKID

Attribute	Description	
Name	CHKID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

EVSQNO

Attribute	Description	
Name	EVSQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EVDS

Attribute	Description	
Name	EVDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

SECCD

Attribute	Description	
Name	SECCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Cscea

Attribute	Description	
Name	Cscea	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Seprma

Attribute	Description
Name	Seprma
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS3

Attribute	Description
Name	COMMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	**Description**	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	**Description**	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	**Description**	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.144.ReopenSecuritiesPortfolio

ReopenSecuritiesPortfolio

2.144.1.SP-ReopenSecuritiesPortfolio-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*

ACRFD
ACRSTDD
ACCRSTMD
ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF

PORTFTYP
PORTFDS
BRN
BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID

- *SKLC*

Serth

- *PORTFID*
- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*

- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*
- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*

- *EVSQNO*
- *EVDT*
- *EVCD*
- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*

TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2

COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STHDR

Attribute	Description
Name	STHDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / M,Q,D,H,A,

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,F,,M

TOP

RIGHT

Attribute	Description
Name	RIGHT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

WARR

Attribute	Description
Name	WARR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,,M

TOP

TBILL

Attribute	Description
Name	TBILL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,F,M,

TOP

FWDACRL

Attribute	Description
Name	FWDACRL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	**Description**	
Name	FWDACRFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	**Description**	
Name	FWDACRSDT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FWDACRSTM

Attribute	**Description**	
Name	FWDACRSTM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INACCR

Attribute	**Description**	
Name	INACCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

INACRF

Attribute	Description
Name	INACRF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

INTACRSTD

Attribute	Description
Name	INTACRSTD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTACRM

Attribute	Description
Name	INTACRM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

EXRCD

Attribute	Description
Name	EXRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	Description
Name	PRDDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

POREF

Attribute	Description
Name	POREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUST

Attribute	**Description**	
Name	CUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHTN

Attribute	**Description**	
Name	SHTN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CUSTACBR

Attribute	**Description**	
Name	CUSTACBR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTACBRDS

Attribute	**Description**	
Name	CUSTACBRDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,,A

TOP

PORTFSM

Attribute	Description
Name	PORTFSM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

SHRTA

Attribute	Description
Name	SHRTA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRWTC

Attribute	Description
Name	ACCRWTC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

BANKAT

Attribute	Description
Name	BANKAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

CONT_HOLD_VAL

Attribute	Description
Name	CONT_HOLD_VAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,O,U,</td></tr></table>

TOP

CORPAR

Attribute	Description
Name	CORPAR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTDS

Attribute	Description
Name	PORTDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Seprskm

Attribute	Description
Name	Seprskm
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SKLCID

Attribute	Description
Name	SKLCID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECPRDCD

Attribute	Description

Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>V,L,,H,A,R,S</td></tr></table>

TOP

AUTHSST

Attribute	Description
Name	AUTHSST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

SECCD

Attribute	Description

Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

TOP

PARTN

Attribute	Description
Name	PARTN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

MEDDS

Attribute	Description
Name	MEDDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	**Description**	
Name	Sepma2	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description

Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Csco

Attribute	Description
Name	Csco
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

OVMSG

Attribute	Description
Name	OVMSG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description

Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	**Description**	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	**Description**	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	**Description**	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	**Description**	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	**Description**	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	**Description**	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

2.144.2.SP-ReopenSecuritiesPortfolio-Req-IO-MSG.xsd

FCUBS_HEADER
- *SOURCE*
- *UBSCOMP*
- *MSGID*
- *CORRELID*
- *USERID*
- *BRANCH*
- *MODULEID*
- *SERVICE*
- *OPERATION*
- *SOURCE_OPERATION*
- *SOURCE_USERID*
- *DESTINATION*
- *MULTITRIPID*
- *FUNCTIONID*
- *ACTION*
- *MSGSTAT*
- *PASSWORD*
- *ADDL*
  - *PARAM*
    - *NAME*
    - *VALUE*

FCUBS_BODY
- *Sepm-IO*
  - *PORTFID*
  - *Misdetails*
    - *CONREFNO*
  - *TXNUDFDETAILS*
    - *FLDNAME*
    - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.144.3.SP-ReopenSecuritiesPortfolio-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Sepm-Full*
    - *ACCRHTB*
    - *STHDR*
    - *STATEMENTHOLDFREQUENCY*
    - *STHSD*
    - *STATEMENTSTARTMONTH*
    - *PRVHSN*
    - *STTXR*
    - *TXNS_STATEMENT_DAY*
    - *STTXSM*
    - *PREVSSN*
    - *ACCRP*
    - *ACCRPM*
    - *ACRDIS*
    - *ACRDCM*
    - *ACRMD*
    - *ACRFD*
    - *ACRSTDD*
    - *ACCRSTMD*

ACRDP
ACUTR
ACRFQR
ACRSDR
ACRSMR
REVSP
USEER
REVL
REVM
REVFR
RESDAY
REVSTM
REREV
REDVM
LOCMBA
RERAF
REREVALSDT
REVALSTM
BOND
EQUIT
RIGHT
WARR
TBILL
FWDACRL
FDACRME
FWDACRFR
FWDACRSDT
FWDACRSTM
INACCR
INACRF
INTACRSTD
INTACRM
EXRCD
EXRTDS
RS
MODN
FUNID
PRCD
PRDDS
PORTFID
POREF
PORTFTYP
PORTFDS
BRN

BRNDS
CURR
CURRDS
CUST
SHTN
CUSTACBR
CUSTACBRDS
CUSTACC
CUSTACCDS
ASACBA
PORTFSM
BRIGHT
BWARRNT
AULFC
CRPACC
SHRTA
ACCRWTC
BANKAT
CONT_HOLD_VAL
CORPAR
NOTDAY
NOTDTYP
CORAR
ACRDT
ACRFR
ACRSDAY
ACRSM
MKID
MKSTMP
CHKID
CHKSTMP
TXNSTAT
AUTHSTAT
SECALL
STATEMENTFREQUENCY
SE_REPOPROHOLD
Sepskm
  PORTFID
  PORTDS
Seprskm
  SKLCID
  SKLC
Serth
  PORTFID

- *PORTFDS*
- *RLTH*
- *RLTHDS*

Serth2

- *SECPRD*
- *SECDS*
- *RLTHDT*
- *RLTHDSD*

Serth3

- *INSEID*
- *INTSEDS*
- *RLTHCL*
- *RLTHDSC*

Sepfspm

- *PORTFID*
- *PORTFDS*

Sepfsepm

- *SPSECID*
- *SPPRCD*

Sesepd

- *PORTFID*
- *PORTFDS*
- *SECALLD*

Sesepds

- *PRDDSAC*
- *PRDDSALDS*

Sepfseac

- *SECID*
- *SECPRDCD*
- *SECDS*
- *ALLD*

Seprms

- *PRD*
- *PORTFID*
- *PRREF*
- *PORTFTYP*
- *PORTFDS*
- *BRN*
- *CURR*
- *CUST*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHDTSTMP*

- *CONTST*
- *AUTHSST*
- *RST*
- *ONAUTH*
- *MODN*
- *TEMPST*

Cscev

- *EVENTCD*
- *EVSQNO*
- *EVDS*
- *SECCD*

Cscea

- *MSGTYP*
- *SUPP*
- *PRRT*
- *MOD*
- *ADDR*
- *ADR2*
- *ADR3*
- *ADR4*
- *PARTTYP*
- *MED*
- *PRTID*
- *PARTN*
- *PRTLANG*
- *CHRD*
- *ADVDS*
- *MEDDS*

Seprma

- *PORTFID*
- *PORTFDS*

Sepma2

- *PORTFID*
- *PORTFDS*

Sepel

- *MOD*
- *CNTREF*
- *MKID*
- *MKDTSTMP*
- *CHKID*
- *CHKDTSTMP*
- *EVSQNO*
- *EVDT*
- *EVCD*

- *CONTST*
- *AUTHST*
- *NVIND*
- *REEVSN*
- *EVVALDT*
- *REREFNO*
- *SECCD*
- *Acaae*
  - *TRREF*
  - *ACBRN*
  - *ACN*
  - *ACCY*
  - *DRCIN*
  - *TRCD*
  - *FCAMT*
  - *EXRT*
  - *LCAMT*
  - *TRDT*
  - *VALDT*
- *Csco*
  - *OVMSG*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*

TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5

COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Sepm-Full

Attribute	Description
Name	Sepm-Full
Datatype	
Description	

TOP

ACCRHTB

Attribute	Description
Name	ACCRHTB
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

STHDR

Attribute	Description
Name	STHDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

STATEMENTHOLDFREQUENCY

Attribute	Description
Name	STATEMENTHOLDFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,D,Q,H,A,

TOP

STHSD

Attribute	Description
Name	STHSD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRVHSN

Attribute	Description
Name	PRVHSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTXR

Attribute	Description
Name	STTXR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

TXNS_STATEMENT_DAY

Attribute	Description
Name	TXNS_STATEMENT_DAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

STTXSM

Attribute	Description
Name	STTXSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREVSSN

Attribute	Description
Name	PREVSSN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRP

Attribute	Description
Name	ACCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACCRPM

Attribute	Description
Name	ACCRPM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRDIS

Attribute	Description
Name	ACRDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDCM

Attribute	Description
Name	ACRDCM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,S,Y,

TOP

ACRMD

Attribute	Description
Name	ACRMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,D,A,E,F,G,H,I,X,Y,Z,

TOP

ACRFD

Attribute	Description
Name	ACRFD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,H,A,,D</td></tr></table>

TOP

ACRSTDD

Attribute	Description
Name	ACRSTDD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACCRSTMD

Attribute	Description
Name	ACCRSTMD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRDP

Attribute	Description
Name	ACRDP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACUTR

Attribute	Description
Name	ACUTR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

ACRFQR

Attribute	Description
Name	ACRFQR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

ACRSDR

Attribute	Description
Name	ACRSDR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRSMR

Attribute	Description
Name	ACRSMR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSP

Attribute	Description
Name	REVSP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

USEER

Attribute	Description
Name	USEER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

REVL

Attribute	Description
Name	REVL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,P,

TOP

REVM

Attribute	Description
Name	REVM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,E,M,

TOP

REVFR

Attribute	Description
Name	REVFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,D,A,

TOP

RESDAY

Attribute	Description
Name	RESDAY
Datatype	Number
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVSTM

Attribute	Description
Name	REVSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REREV

Attribute	Description
Name	REREV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

REDVM

Attribute	Description
Name	REDVM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,M,X,

TOP

LOCMBA

Attribute	Description
Name	LOCMBA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / H,,A

TOP

RERAF

Attribute	Description
Name	RERAF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,Q,D,H,A,</td></tr></table>

TOP

REREVALSDT

Attribute	Description
Name	REREVALSDT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVALSTM

Attribute	Description
Name	REVALSTM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BOND

Attribute	Description
Name	BOND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>B,F,,M</td></tr></table>

TOP

EQUIT

Attribute	Description
Name	EQUIT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	enumeration	B,F,,M

TOP

RIGHT

Attribute	Description	
Name	RIGHT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

WARR

Attribute	Description	
Name	WARR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,,M

TOP

TBILL

Attribute	Description	
Name	TBILL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,F,M,

TOP

FWDACRL

Attribute	Description	
Name	FWDACRL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

FDACRME

Attribute	Description
Name	FDACRME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,C,D,E,F,G,H,I,X,Y,Z,

TOP

FWDACRFR

Attribute	Description
Name	FWDACRFR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,Q,H,A,,D

TOP

FWDACRSDT

Attribute	Description
Name	FWDACRSDT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FWDACRSTM

Attribute	Description
Name	FWDACRSTM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INACCR

Attribute	Description
Name	INACCR
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

INACRF

Attribute	**Description**
Name	INACRF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,D,Q,H,A,

TOP

INTACRSTD

Attribute	**Description**
Name	INTACRSTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTACRM

Attribute	**Description**
Name	INTACRM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRCD

Attribute	**Description**
Name	EXRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

EXRTDS

Attribute	Description
Name	EXRTDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RS

Attribute	Description
Name	RS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FUNID

Attribute	Description
Name	FUNID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PRCD

Attribute	Description
Name	PRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDS

Attribute	**Description**
Name	PRDDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PORTFID

Attribute	**Description**
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

POREF

Attribute	**Description**
Name	POREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFTYP

Attribute	**Description**
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNDS

Attribute	Description
Name	BRNDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CURRDS

Attribute	Description
Name	CURRDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHTN

Attribute	Description
Name	SHTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTACBR

Attribute	Description
Name	CUSTACBR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTACBRDS

Attribute	Description
Name	CUSTACBRDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CUSTACC

Attribute	Description
Name	CUSTACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

CUSTACCDS

Attribute	Description
Name	CUSTACCDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ASACBA

Attribute	Description
Name	ASACBA
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,,A</td></tr></table>

TOP

PORTFSM

Attribute	Description
Name	PORTFSM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,D,W,

TOP

BRIGHT

Attribute	Description
Name	BRIGHT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

BWARRNT

Attribute	Description
Name	BWARRNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

AULFC

Attribute	Description
Name	AULFC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

CRPACC

Attribute	Description
Name	CRPACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

SHRTA

Attribute	**Description**	
Name	SHRTA	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

ACCRWTC

Attribute	**Description**	
Name	ACCRWTC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

BANKAT

Attribute	**Description**	
Name	BANKAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,Y

TOP

CONT_HOLD_VAL

Attribute	**Description**	
Name	CONT_HOLD_VAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / E,O,U,

TOP

CORPAR

Attribute	Description
Name	CORPAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

NOTDAY

Attribute	Description
Name	NOTDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOTDTYP

Attribute	Description
Name	NOTDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,C,

TOP

CORAR

Attribute	Description
Name	CORAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

ACRDT

Attribute	Description
Name	ACRDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

TOP

ACRFR

Attribute	Description
Name	ACRFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M,D,Q,H,A,</td></tr></table>

TOP

ACRSDAY

Attribute	Description
Name	ACRSDAY
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ACRSM

Attribute	Description
Name	ACRSM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MKSTMP

Attribute	Description
Name	MKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKSTMP

Attribute	Description
Name	CHKSTMP
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SECALL

Attribute	Description
Name	SECALL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,Q,H,A,,D

TOP

SE_REPOPROHOLD

Attribute	Description
Name	SE_REPOPROHOLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

TOP

Sepskm

Attribute	Description
Name	Sepskm
Datatype	
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTDS

Attribute	**Description**	
Name	PORTDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Seprskm

Attribute	**Description**	
Name	Seprskm	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SKLCID

Attribute	**Description**	
Name	SKLCID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SKLC

Attribute	Description
Name	SKLC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

TOP

Serth

Attribute	Description
Name	Serth
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

RLTH

Attribute	Description
Name	RLTH
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDS

Attribute	Description
Name	RLTHDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Serth2

Attribute	Description
Name	Serth2
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SECPRD

Attribute	Description
Name	SECPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RLTHDT

Attribute	Description
Name	RLTHDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RLTHDSD

Attribute	Description
Name	RLTHDSD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Serth3

Attribute	Description
Name	Serth3
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSEID

Attribute	Description
Name	INSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INTSEDS

Attribute	Description
Name	INTSEDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

RLTHCL

Attribute	Description
Name	RLTHCL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RLTHDSC

Attribute	Description
Name	RLTHDSC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Sepfspm

Attribute	Description
Name	Sepfspm
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Sepfsepm

Attribute	Description
Name	Sepfsepm
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SPSECID

Attribute	Description
Name	SPSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SPPRCD

Attribute	Description
Name	SPPRCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Sesepd

Attribute	Description
Name	Sesepd
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SECALLD

Attribute	Description
Name	SECALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Sesepds

Attribute	Description
Name	Sesepds
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PRDDSAC

Attribute	Description
Name	PRDDSAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDDSALDS

Attribute	Description
Name	PRDDSALDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepfseac

Attribute	Description
Name	Sepfseac
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECID

Attribute	Description
Name	SECID
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SECPRDCD

Attribute	Description
Name	SECPRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECDS

Attribute	Description
Name	SECDS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALLD

Attribute	Description
Name	ALLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N,

TOP

Seprms

Attribute	Description
Name	Seprms
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRREF

Attribute	Description
Name	PRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PORTFTYP

Attribute	Description
Name	PORTFTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CURR

Attribute	Description
Name	CURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

MKID

Attribute	Description
Name	MKID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHDTSTMP

Attribute	Description
Name	CHDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTST

Attribute	Description
Name	CONTST
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHSST

Attribute	Description
Name	AUTHSST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,,A

TOP

RST

Attribute	Description
Name	RST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONAUTH

Attribute	Description
Name	ONAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MODN

Attribute	Description
Name	MODN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPST

Attribute	Description
Name	TEMPST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Cscev

Attribute	Description
Name	Cscev
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 0

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVDS

Attribute	Description
Name	EVDS
Datatype	String

Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	0

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	0

TOP

Cscea

Attribute	Description
Name	Cscea
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

TOP

SUPP

Attribute	Description
Name	SUPP
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / N,Y

TOP

PRRT

Attribute	Description
Name	PRRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR2

Attribute	Description
Name	ADR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADR3

Attribute	Description
Name	ADR3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ADR4

Attribute	Description
Name	ADR4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

PARTTYP

Attribute	Description
Name	PARTTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MED

Attribute	Description
Name	MED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

TOP

PRTID

Attribute	Description
Name	PRTID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTN

Attribute	Description
Name	PARTN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

PRTLANG

Attribute	Description
Name	PRTLANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRD

Attribute	Description
Name	CHRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ADVDS

Attribute	Description
Name	ADVDS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

MEDDS

Attribute	**Description**	
Name	MEDDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	0

TOP

Seprma

Attribute	**Description**	
Name	Seprma	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PORTFID

Attribute	**Description**	
Name	PORTFID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

PORTFDS

Attribute	**Description**	
Name	PORTFDS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Sepma2

Attribute	Description
Name	Sepma2
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

PORTFDS

Attribute	Description
Name	PORTFDS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

Sepel

Attribute	Description
Name	Sepel
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MOD

Attribute	Description
Name	MOD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CNTREF

Attribute	Description
Name	CNTREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MKID

Attribute	Description
Name	MKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MKDTSTMP

Attribute	Description
Name	MKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKID

Attribute	Description
Name	CHKID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTSTMP

Attribute	Description
Name	CHKDTSTMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EVSQNO

Attribute	Description
Name	EVSQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVDT

Attribute	Description
Name	EVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVCD

Attribute	Description
Name	EVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CONTST

Attribute	Description
Name	CONTST

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,L,,H,A,R,S

TOP

AUTHST

Attribute	Description
Name	AUTHST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

NVIND

Attribute	Description
Name	NVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REEVSN

Attribute	Description
Name	REEVSN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVVALDT

Attribute	Description
Name	EVVALDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REREFNO

Attribute	Description
Name	REREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECCD

Attribute	Description
Name	SECCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 0

TOP

Acaae

Attribute	Description
Name	Acaae
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRREF

Attribute	Description
Name	TRREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ACBRN

Attribute	Description

Name	ACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACN

Attribute	Description
Name	ACN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCY

Attribute	Description
Name	ACCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRCIN

Attribute	Description
Name	DRCIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TRCD

Attribute	Description
Name	TRCD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FCAMT

Attribute	Description
Name	FCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRT

Attribute	Description
Name	EXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCAMT

Attribute	Description
Name	LCAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRDT

Attribute	Description
Name	TRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Csco

Attribute	**Description**	
Name	Csco	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

OVMSG

Attribute	**Description**	
Name	OVMSG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4000

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**

Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.144.4.SP-ReopenSecuritiesPortfolio-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Sepm-PK*
      - *PORTFID*
    - *Sepm-IO*
      - *PORTFID*
      - *Misdetails*
        - *CONREFNO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Sepm-PK

Attribute	Description
Name	Sepm-PK
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Sepm-IO

Attribute	Description
Name	Sepm-IO
Datatype	
Description	

TOP

PORTFID

Attribute	Description
Name	PORTFID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.145.AuthorizeSecInstrument

AuthorizeSecInstrument

2.145.1.SS-AuthorizeSecInstrument-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

- *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTTIME

Attribute	**Description**	
Name	CHECKERDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

ISSDT

Attribute	**Description**	
Name	ISSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

STINTDT

Attribute	**Description**	
Name	STINTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDT

Attribute	**Description**
Name	STTRADEDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	**Description**	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	**Description**	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	**Description**	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

RITBASS

Attribute	Description	
Name	RITBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

AUTOCRP

Attribute	Description	
Name	AUTOCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCDISTYP

Attribute	Description	
Name	ACCDISTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECRSTATUS

Attribute	**Description**	
Name	SECRSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,P,R,S,

TOP

TRADSTATUS

Attribute	**Description**	
Name	TRADSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

INTERESTTYPE

Attribute	**Description**	
Name	INTERESTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

CALLOPTION

Attribute	**Description**	
Name	CALLOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUESIZE

Attribute	**Description**	
Name	ISSUESIZE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description	
Name	ACCRDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description	
Name	ACCRDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

ACRR366BSS

Attribute	Description	
Name	ACRR366BSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D,

TOP

ACCRINCLDT

Attribute	Description	
Name	ACCRINCLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	Description	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description
Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description

Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCOUPFREQ

Attribute	Description
Name	BCOUPFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description
Name	ACCVALDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	30

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description

Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Revision-Sched

Attribute	Description

Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description	
Name	REVWEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description	
Name	REVADHMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Redemption

Attribute	Description	
Name	Redemption	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREDEVTDT

Attribute	Description	
Name	BREDEVTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.145.2.SS-AuthorizeSecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *SECURITYID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.145.3.SS-AuthorizeSecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*

VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6

BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*

BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE

- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption

- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master

- *BREVDT*
- *REVEFFDT*

Interest-Assoc

- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1

- *BSECID*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*

- *CRRATESN*
- *TAGCCY*
- *TAGAMNT*
- *TAXCCY*
- *TAXAMNT*
- *WAIVER*
- *LIQDINDICAT*

Liqdmaster

- *INTCOMP*
- *TAXCCY*
- *TAXAMNT*

Issrtax

- *INTCOMP*
- *CRRATESN*
- *RATECOD*
- *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESTRICTED

Attribute	**Description**	
Name	RESTRICTED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VOTRT

Attribute	**Description**	
Name	VOTRT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVER

Attribute	**Description**	
Name	COVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVERBLE

Attribute	**Description**	
Name	CONVERBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BBKACC

Attribute	Description	
Name	BBKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICD

Attribute	Description	
Name	ISOCFICD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISITCCD

Attribute	Description	
Name	ISITCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ATTRIBDES

Attribute	Description	
Name	ATTRIBDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COLLATYPE

Attribute	Description	
Name	COLLATYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

DIREXPLIN

Attribute	Description	
Name	DIREXPLIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BQUALRAT

Attribute	Description	
Name	BQUALRAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVPRICOD

Attribute	Description	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT9

Attribute	**Description**	
Name	BATTRIBNARRAT9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT10

Attribute	**Description**	
Name	BATTRIBNARRAT10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REDQUOT

Attribute	**Description**	
Name	REDQUOT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,F,C,

TOP

CONFCORP

Attribute	**Description**	
Name	CONFCORP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,E,R,W,Z</td></tr></table>

TOP

SECREFERNO

Attribute	Description
Name	SECREFERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,P,R,S,</td></tr></table>

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,I,</td></tr></table>

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	**Description**	
Name	QTYQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

PRIQUT

Attribute	**Description**	
Name	PRIQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	**Description**	
Name	INTQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCOUPSTDT

Attribute	**Description**	
Name	BCOUPSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BCOUPTYPE

Attribute	**Description**	
Name	BCOUPTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BCOUPENDT

Attribute	**Description**	
Name	BCOUPENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BBASEFREQ

Attribute	**Description**	
Name	BBASEFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description
Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Revision-Sched

Attribute	**Description**	
Name	Revision-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**
Name	REVBASFREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BACQAMT

Attribute	Description
Name	BACQAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	Description	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RATECOD

Attribute	**Description**	
Name	RATECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-PK*
      - *SECURITYID*
    - *Security-Master-IO*
      - *SECURITYID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-PK

Attribute	Description
Name	Security-Master-PK
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.146.AuthorizeSecurityProduct

Authorization of Securities Security Product

2.146.1.SS-AuthorizeSecurityProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*

- CCY
- POSOVDLMT
- NGOVDLMT
- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Indicates FCUBS Request data.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description

Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String
Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the Maker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the Checker.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the transaction Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Security-Product

Attribute	Description	
Name	Security-Product	
Datatype		
Description	Includes the Security Product Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates the Product Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ

Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REDMTYP

Attribute	Description
Name	REDMTYP
Datatype	String
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B,

TOP

MINTRDQTY

Attribute	Description
Name	MINTRDQTY
Datatype	Number
Description	Indicates the Minimum Tradable Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

VTNGRGHTS

Attribute	**Description**	
Name	VTNGRGHTS	
Datatype	String	
Description	Indicates the Voting Rights.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BNKRSACPTNCE

Attribute	**Description**	
Name	BNKRSACPTNCE	
Datatype	String	
Description	Indicates the Bankers Acceptance Issue.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REGBEAR

Attribute	**Description**	
Name	REGBEAR	
Datatype	String	
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description	
Name	CLTRLTYP	
Datatype	String	
Description	Indicates the Collateral Type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TNRUNT

Attribute	Description	
Name	TNRUNT	
Datatype	String	
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Y,

TOP

MINTNR

Attribute	Description	
Name	MINTNR	
Datatype	Number	
Description	Indicates the Minimum Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXTNR

Attribute	Description	
Name	MAXTNR	
Datatype	Number	
Description	Indicates the Maximium Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN

Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

DTPLHOLTRT

Attribute	**Description**	
Name	DTPLHOLTRT	
Datatype	String	
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,,

TOP

DTAMNDLMT

Attribute	**Description**	
Name	DTAMNDLMT	
Datatype	Number	
Description	Indicates the Coupon Date Amendment Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description	Indicates the Market Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRCECDDESC

Attribute	**Description**	
Name	PRCECDDESC	
Datatype	String	
Description	Indicates the Price Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description

Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description

Name	PRIMARYINTRSTINDI
Datatype	String
Description	Indicates the primary interest.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASICAMNTTAG

Attribute	**Description**	
Name	BASICAMNTTAG	
Datatype	String	
Description	Indicates the Basic Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTCATG

Attribute	**Description**	
Name	BASICAMTCATG	
Datatype	String	
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,X,N

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,X,S

TOP

FLTRTTYP

Attribute	**Description**	
Name	FLTRTTYP	
Datatype	String	
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTSRCDESC

Attribute	Description
Name	DFTRTSRCDESC
Datatype	String
Description	Indicates the Rate Source Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCDDESC

Attribute	Description
Name	DFTTNRCDDESC
Datatype	String
Description	Indicates the Tenor Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC

Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	

Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.146.2.SS-AuthorizeSecurityProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicates Product Code in Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

2.146.3.SS-AuthorizeSecurityProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*
  - *CCY*
  - *POSOVDLMT*
  - *NGOVDLMT*

- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

- CATGLIS
- CLASCD
- Cust-Categories

CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Contains Full Details of Authorize Security Product Response

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	**Description**	
Name	PRDTYP	
Datatype	String	
Description	Indicates the Product Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Product Description.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description	Indicates the Product Slogan.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates the Product Group.	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates the Rate Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates the Product Type Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	**Description**	
Name	PRODUCT_GROUP_DESCRIPTION	
Datatype	String	
Description	Indicates the Product Group Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	**Description**	
Name	RESTRCTION	
Datatype	String	
Description	Indicates the Restricted.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRED

Attribute	**Description**	
Name	CVRED	
Datatype	String	
Description	Indicates the Covered.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	**Description**	
Name	QTYQUOTN	
Datatype	String	
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

PRCEQUOTN

Attribute	**Description**	
Name	PRCEQUOTN	
Datatype	String	
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	**Description**	
Name	INTQUOTN	
Datatype	String	
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

AUTINITNCORPACT

Attribute	**Description**	
Name	AUTINITNCORPACT	
Datatype	String	
Description	Indicates the Auto Initiation Of Corporate Action.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRCECDDESC

Attribute	Description
Name	PRCECDDESC

Datatype	String
Description	Indicates the Price Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number

Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Interest

Attribute	Description

Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description	
Name	PRIMARYINTRSTINDI	
Datatype	String	
Description	Indicates the primary interest.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRALREQ

Attribute	Description	
Name	ACRALREQ	
Datatype	String	
Description	Indicates the Accrual Required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPONINDI

Attribute	Description	
Name	COUPONINDI	
Datatype	String	
Description	Incdicates the Coupon Indicator. Y-Yes, N-No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LEGTYP

Attribute	Description	
Name	LEGTYP	
Datatype	String	
Description	Indicates the Leg Type. I- In, O- Out.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,X,N</td></tr></table>

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,X,S</td></tr></table>

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP

Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTSRCDESC

Attribute	Description
Name	DFTRTSRCDESC
Datatype	String
Description	Indicates the Rate Source Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCDDESC

Attribute	Description
Name	DFTTNRCDDESC
Datatype	String
Description	Indicates the Tenor Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Currency-Rates

Attribute	Description	
Name	Currency-Rates	
Datatype		
Description	Includes the Currency Rates.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENTCCY

Attribute	Description	
Name	COMPNENTCCY	
Datatype	String	
Description	Indicates the component Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINRAT

Attribute	Description

Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the Class Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD

Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description

Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.146.4.SS-AuthorizeSecurityProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-PK*
      - *PRDCD*
    - *Product-IO*
      - *PRDCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-PK

Attribute	Description
Name	Product-PK
Datatype	
Description	Contains Primary Key Response of Authorize Security Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Contains Input Only Response of Authorize Security Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.147.CloseSecInstrument

CloseSecInstrument

2.147.1.SS-CloseSecInstrument-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

- *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTTIME

Attribute	**Description**	
Name	CHECKERDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

ISSDT

Attribute	**Description**	
Name	ISSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

STINTDT

Attribute	**Description**	
Name	STINTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDT

Attribute	**Description**
Name	STTRADEDT

Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	**Description**	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	**Description**	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	**Description**	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECRSTATUS

Attribute	**Description**	
Name	SECRSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,P,R,S,

TOP

TRADSTATUS

Attribute	**Description**	
Name	TRADSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

INTERESTTYPE

Attribute	**Description**	
Name	INTERESTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

CALLOPTION

Attribute	**Description**	
Name	CALLOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUESIZE

Attribute	**Description**	
Name	ISSUESIZE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	Description	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description
Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description

Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCOUPFREQ

Attribute	Description
Name	BCOUPFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description
Name	ACCVALDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	**Description**
Name	ADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Coupon-Period

Attribute	**Description**
Name	Coupon-Period
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BPCD

Attribute	**Description**
Name	BPCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNCD

Attribute	**Description**
Name	BNCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	**Description**

Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Revision-Sched

Attribute	Description

Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>RN,RU,RD,RS,</td></tr></table>

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.147.2.SS-CloseSecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *SECURITYID*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *TXNUDFDETAILS*
      - *FLDNAME*
      - *FLDVAL*
    - *Misdetails*
      - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.147.3.SS-CloseSecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*

VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6

BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*

BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE

- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption

- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master

- *BREVDT*
- *REVEFFDT*

Interest-Assoc

- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1

- *BSECID*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*

- *CRRATESN*
- *TAGCCY*
- *TAGAMNT*
- *TAXCCY*
- *TAXAMNT*
- *WAIVER*
- *LIQDINDICAT*

Liqdmaster

- *INTCOMP*
- *TAXCCY*
- *TAXAMNT*

Issrtax

- *INTCOMP*
- *CRRATESN*
- *RATECOD*
- *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESTRICTED

Attribute	**Description**	
Name	RESTRICTED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VOTRT

Attribute	**Description**	
Name	VOTRT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVER

Attribute	**Description**	
Name	COVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVERBLE

Attribute	**Description**	
Name	CONVERBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BBKACC

Attribute	Description	
Name	BBKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICD

Attribute	Description	
Name	ISOCFICD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISITCCD

Attribute	Description	
Name	ISITCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ATTRIBDES

Attribute	Description	
Name	ATTRIBDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COLLATYPE

Attribute	Description	
Name	COLLATYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

DIREXPLIN

Attribute	Description	
Name	DIREXPLIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BQUALRAT

Attribute	Description	
Name	BQUALRAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVPRICOD

Attribute	Description	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	**Description**	
Name	USEBONDFORM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TBILLREINVPR

Attribute	**Description**	
Name	TBILLREINVPR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNMTH

Attribute	**Description**	
Name	TBILLANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

TBILLCNTNR

Attribute	**Description**	
Name	TBILLCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT5

Attribute	**Description**	
Name	BATTRIBNARRAT5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT6

Attribute	**Description**	
Name	BATTRIBNARRAT6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT7

Attribute	**Description**	
Name	BATTRIBNARRAT7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT8

Attribute	**Description**	
Name	BATTRIBNARRAT8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C,

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,E,R,W,Z</td></tr></table>

TOP

SECREFERNO

Attribute	Description
Name	SECREFERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,P,R,S,</td></tr></table>

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,I,</td></tr></table>

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	**Description**	
Name	QTYQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

PRIQUT

Attribute	**Description**	
Name	PRIQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	**Description**	
Name	INTQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCOUPTYDES

Attribute	**Description**	
Name	BCOUPTYDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BVIRPREVDT2

Attribute	**Description**	
Name	BVIRPREVDT2	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BVIRPREVDT1

Attribute	**Description**	
Name	BVIRPREVDT1	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BVIRNEXDT1

Attribute	**Description**	
Name	BVIRNEXDT1	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BVIRNEXDT2

Attribute	**Description**
Name	BVIRNEXDT2
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Revision-Sched

Attribute	**Description**	
Name	Revision-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**
Name	REVBASFREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BACQAMT

Attribute	Description
Name	BACQAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	**Description**	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	**Description**	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RATECOD

Attribute	**Description**	
Name	RATECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.147.4.SS-CloseSecInstrument-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-PK*
      - *SECURITYID*
    - *Security-Master-IO*
      - *SECURITYID*
      - *Taxheadmaster*
        - *REFERENCE_NO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
      - *Misdetails*
        - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-PK

Attribute	Description
Name	Security-Master-PK
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.148.CreateSecInstrument

CreateSecInstrument

2.148.1.SS-CreateSecInstrument-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

- *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTTIME

Attribute	**Description**	
Name	CHECKERDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

ISSDT

Attribute	**Description**	
Name	ISSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

STINTDT

Attribute	**Description**	
Name	STINTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDT

Attribute	**Description**
Name	STTRADEDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	**Description**	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	**Description**	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	**Description**	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

RITBASS

Attribute	Description	
Name	RITBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

AUTOCRP

Attribute	Description	
Name	AUTOCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCDISTYP

Attribute	Description	
Name	ACCDISTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECRSTATUS

Attribute	**Description**	
Name	SECRSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,P,R,S,

TOP

TRADSTATUS

Attribute	**Description**	
Name	TRADSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

INTERESTTYPE

Attribute	**Description**	
Name	INTERESTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description	
Name	LCLMRKTISUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISSUERID

Attribute	Description	
Name	ISSUERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ISSUERDES

Attribute	Description	
Name	ISSUERDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REGORBEAR

Attribute	Description	
Name	REGORBEAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

CALLOPTION

Attribute	**Description**	
Name	CALLOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUESIZE

Attribute	**Description**	
Name	ISSUESIZE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	**Description**	
Name	ACCRDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	**Description**	
Name	ACCRDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

ACRR366BSS

Attribute	**Description**	
Name	ACRR366BSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D,

TOP

ACCRINCLDT

Attribute	**Description**	
Name	ACCRINCLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	Description	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description
Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description

Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCOUPFREQ

Attribute	Description
Name	BCOUPFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description
Name	ACCVALDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	**Description**	
Name	COUPPLTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

CADHMNTHND

Attribute	**Description**	
Name	CADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVFRQ

Attribute	**Description**	
Name	REVFRQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	**Description**
Name	Security-Hol-Ccy
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	30

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	**Description**	
Name	ADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Coupon-Period

Attribute	**Description**	
Name	Coupon-Period	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BPCD

Attribute	**Description**	
Name	BPCD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BNCD

Attribute	**Description**	
Name	BNCD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCOUPTYDES

Attribute	**Description**

Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Revision-Sched

Attribute	Description

Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description	
Name	REVWEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description	
Name	REVADHMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Redemption

Attribute	Description	
Name	Redemption	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREDEVTDT

Attribute	Description	
Name	BREDEVTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	**Description**	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.148.2.SS-CreateSecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*
    - *VOTRT*
    - *COVER*
    - *CONVERBLE*
    - *BBKACC*
    - *ISOCFICD*

ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT

CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
LCLMRKTISUE
ISSUERID
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*
- *ACCRNUMMTH*
- *ACCRDENMTH*
- *ACCRDENBSS*
- *ACRR366BSS*
- *ACCRINCLDT*
- *LIQDNUMMTH*
- *LIQDDENMTH*
- *LIQDDENBSS*
- *BREVWEEK*
- *RADHMNTHND*
- *RNDBASS*
- *BPERCOUP*
- *ALLASNCREV*
- *BPERREV*

BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE
BREVENDT
REVBASFREQ
REVWEKDAY
REVADHMON
Redemption
BREDEVTDT
BPERRED
BREDPRI
BDISPFRAC
BCALLINDCAT
BREDSERIES
Revision-Date-Master
REVEFFDT
Interest-Assoc
BACQAMT
BFLTAMT

- *BINCLACMET*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BTENCODE*
- *BWAIVER*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
- *Issrtax*
  - *INTCOMP*
  - *RATECOD*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*

COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

INFACVAL

Attribute	**Description**	
Name	INFACVAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSPRIC

Attribute	**Description**	
Name	ISSPRIC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REDPRIC

Attribute	**Description**	
Name	REDPRIC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISSSEID

Attribute	**Description**	
Name	ISSSEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MKTSEID

Attribute	**Description**
Name	MKTSEID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVERBLE

Attribute	**Description**	
Name	CONVERBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BBKACC

Attribute	**Description**	
Name	BBKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICD

Attribute	**Description**	
Name	ISOCFICD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISITCCD

Attribute	**Description**	
Name	ISITCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REVPRICOD

Attribute	Description	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BPRICDES

Attribute	Description	
Name	BPRICDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	Description	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	Description	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,E,U,</td></tr></table>

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,H,X,</td></tr></table>

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,

TOP

MINRATES

Attribute	**Description**	
Name	MINRATES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXRATES

Attribute	**Description**	
Name	MAXRATES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BIDNTINARRAT1

Attribute	**Description**	
Name	BIDNTINARRAT1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT2

Attribute	**Description**	
Name	BIDNTINARRAT2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT8

Attribute	**Description**	
Name	BATTRIBNARRAT8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT9

Attribute	**Description**	
Name	BATTRIBNARRAT9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT10

Attribute	**Description**	
Name	BATTRIBNARRAT10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REDQUOT

Attribute	**Description**	
Name	REDQUOT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	P,F,C,

TOP

CONFCORP

Attribute	Description	
Name	CONFCORP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURITYID

Attribute	Description	
Name	SECURITYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISINIDENTFR

Attribute	Description	
Name	ISINIDENTFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SECURITYDESC

Attribute	Description	
Name	SECURITYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,I,D,C,G,</td></tr></table>

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,N,</td></tr></table>

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,PRI,PRM,PPR,PPM,YTM</td></tr></table>

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Q,S,B,

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,D,</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**	
Name	REVBASFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BREDPRI

Attribute	**Description**	
Name	BREDPRI	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BDISPFRAC

Attribute	**Description**	
Name	BDISPFRAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	**Description**	
Name	BCALLINDCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BREDSERIES

Attribute	**Description**	
Name	BREDSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9,-1,-2,0</td></tr></table>

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BWAIVER

Attribute	Description
Name	BWAIVER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNUDFDETAILS

Attribute	Description

Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description	
Name	REFSPREAD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATECD

Attribute	Description	
Name	REFRATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COSTCD1

Attribute	Description	
Name	COSTCD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	**Description**	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.148.3.SS-CreateSecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*

VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6

BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*

BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE

- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption

- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master

- *BREVDT*
- *REVEFFDT*

Interest-Assoc

- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1

- *BSECID*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*

- *CRRATESN*
- *TAGCCY*
- *TAGAMNT*
- *TAXCCY*
- *TAXAMNT*
- *WAIVER*
- *LIQDINDICAT*

Liqdmaster

- *INTCOMP*
- *TAXCCY*
- *TAXAMNT*

Issrtax

- *INTCOMP*
- *CRRATESN*
- *RATECOD*
- *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESTRICTED

Attribute	**Description**
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VOTRT

Attribute	**Description**
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVER

Attribute	**Description**
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONVERBLE

Attribute	**Description**
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BBKACC

Attribute	Description	
Name	BBKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICD

Attribute	Description	
Name	ISOCFICD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISITCCD

Attribute	Description	
Name	ISITCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ATTRIBDES

Attribute	Description	
Name	ATTRIBDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COLLATYPE

Attribute	Description	
Name	COLLATYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

DIREXPLIN

Attribute	Description	
Name	DIREXPLIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BQUALRAT

Attribute	Description	
Name	BQUALRAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVPRICOD

Attribute	Description	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	**Description**	
Name	USEBONDFORM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TBILLREINVPR

Attribute	**Description**	
Name	TBILLREINVPR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNMTH

Attribute	**Description**	
Name	TBILLANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

TBILLCNTNR

Attribute	**Description**	
Name	TBILLCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT5

Attribute	**Description**	
Name	BATTRIBNARRAT5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT6

Attribute	**Description**	
Name	BATTRIBNARRAT6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT7

Attribute	**Description**	
Name	BATTRIBNARRAT7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT8

Attribute	**Description**	
Name	BATTRIBNARRAT8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT9

Attribute	**Description**	
Name	BATTRIBNARRAT9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT10

Attribute	**Description**	
Name	BATTRIBNARRAT10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REDQUOT

Attribute	**Description**	
Name	REDQUOT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,F,C,

TOP

CONFCORP

Attribute	**Description**	
Name	CONFCORP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURITYID

Attribute	Description	
Name	SECURITYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISINIDENTFR

Attribute	Description	
Name	ISINIDENTFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SECURITYDESC

Attribute	Description	
Name	SECURITYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,E,R,W,Z</td></tr></table>

TOP

SECREFERNO

Attribute	Description
Name	SECREFERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,P,R,S,</td></tr></table>

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,I,</td></tr></table>

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	**Description**	
Name	QTYQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

PRIQUT

Attribute	**Description**	
Name	PRIQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	**Description**	
Name	INTQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCOUPSTDT

Attribute	**Description**	
Name	BCOUPSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BCOUPTYPE

Attribute	**Description**	
Name	BCOUPTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BCOUPENDT

Attribute	**Description**	
Name	BCOUPENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BBASEFREQ

Attribute	**Description**	
Name	BBASEFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description
Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Revision-Sched

Attribute	**Description**	
Name	Revision-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**
Name	REVBASFREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BACQAMT

Attribute	Description
Name	BACQAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	**Description**	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	**Description**	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RATECOD

Attribute	**Description**	
Name	RATECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.148.4.SS-CreateSecInstrument-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-PK*
      - *SECURITYID*
    - *Security-Master-IO*
      - *AUTHSTAT*
      - *ISSDT*
      - *STINTDT*
      - *STTRADEDT*
      - *REDDT*
      - *SECURITYCCY*
      - *INFACVAL*
      - *ISSPRIC*
      - *REDPRIC*
      - *ISSSEID*
      - *MKTSEID*
      - *CNBSEID*
      - *RESTRICTED*
      - *VOTRT*
      - *COVER*

CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8

BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
LCLMRKTISUE
ISSUERID
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*
- *ACCRNUMMTH*
- *ACCRDENMTH*
- *ACCRDENBSS*
- *ACRR366BSS*
- *ACCRINCLDT*
- *LIQDNUMMTH*
- *LIQDDENMTH*
- *LIQDDENBSS*
- *BREVWEEK*
- *RADHMNTHND*
- *RNDBASS*

BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE
BREVENDT
REVBASFREQ
REVWEKDAY
REVADHMON
Redemption
BREDEVTDT
BPERRED
BREDPRI
BDISPFRAC
BCALLINDCAT
BREDSERIES
Revision-Date-Master
REVEFFDT

- *Interest-Assoc*
  - *BACQAMT*
  - *BFLTAMT*
  - *BINCLACMET*
  - *BINTRATE*
  - *BINTSPRD*
  - *BQUOTREVCEIL*
  - *BQUOTREVFLR*
  - *BQUOTREVIND*
  - *SPRD*
  - *BRATECODE*
  - *BTENCODE*
  - *BWAIVER*
- *Taxheadmaster*
  - *REFERENCE_NO*
  - *Assoc*
    - *INTCOMP*
    - *CRRATEESN*
    - *RULE*
    - *WAIVER*
  - *Appln*
    - *INTCOMP*
    - *CRRATESN*
    - *WAIVER*
    - *LIQDINDICAT*
  - *Liqdmaster*
    - *INTCOMP*
  - *Issrtax*
    - *INTCOMP*
    - *RATECOD*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*

PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-PK

Attribute	Description
Name	Security-Master-PK
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,U,A</td></tr></table>

TOP

ISSDT

Attribute	Description

Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INFACVAL

Attribute	Description

Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONVERBLE

Attribute	Description

Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H,

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H,

TOP

WARRBASS

Attribute	Description	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

RITBASS

Attribute	Description	
Name	RITBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

AUTOCRP

Attribute	Description	
Name	AUTOCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCDISTYP

Attribute	Description	
Name	ACCDISTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,C,</td></tr></table>

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

TBILLCNTDN

Attribute	**Description**	
Name	TBILLCNTDN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H,X,

TOP

BNDREINVPR

Attribute	**Description**	
Name	BNDREINVPR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BNDANNMTH

Attribute	**Description**	
Name	BNDANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

BNDDAYCNTNR

Attribute	**Description**	
Name	BNDDAYCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,F,C,

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURITYID

Attribute	**Description**	
Name	SECURITYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISINIDENTFR

Attribute	**Description**	
Name	ISINIDENTFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SECURITYDESC

Attribute	**Description**	
Name	SECURITYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRODUCT

Attribute	**Description**	
Name	PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

LCLMRKTISUE

Attribute	Description	
Name	LCLMRKTISUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISSUERID

Attribute	Description	
Name	ISSUERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REGORBEAR

Attribute	Description	
Name	REGORBEAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	Description	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUESIZE

Attribute	**Description**	
Name	ISSUESIZE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OSISSIZ

Attribute	**Description**	
Name	OSISSIZ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,D,</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>360,365,ACTUAL,364,</td></tr></table>

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,C,</td></tr></table>

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,D,</td></tr></table>

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDNUMMTH

Attribute	Description
Name	LIQDNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description
Name	LIQDDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description
Name	LIQDDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

BREVWEEK

Attribute	Description
Name	BREVWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	**Description**	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	**Description**	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	**Description**	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	**Description**	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description	
Name	BCOUPWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description	
Name	COUPPLTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

CADHMNTHND

Attribute	Description	
Name	CADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVFRQ

Attribute	Description	
Name	REVFRQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description	
Name	Security-Hol-Ccy	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BCOUPTYPE

Attribute	**Description**	
Name	BCOUPTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BCOUPENDT

Attribute	**Description**	
Name	BCOUPENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BBASEFREQ

Attribute	**Description**	
Name	BBASEFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	**Description**	
Name	COUPWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description

Name	REVADHMON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDISPFRAC

Attribute	Description	
Name	BDISPFRAC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description	
Name	BCALLINDCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BREDSERIES

Attribute	Description	
Name	BREDSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Revision-Date-Master

Attribute	Description	
Name	Revision-Date-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTRATE

Attribute	Description
Name	BINTRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Issrtax

Attribute	Description

Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description	
Name	REFINANCE_RATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFRATETYP

Attribute	Description	
Name	REFRATETYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,X,F,P

TOP

PROCALCMTH

Attribute	Description	
Name	PROCALCMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.149.CreateSecurityProduct

Creation of Securities Security Product

2.149.1.SS-CreateSecurityProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*

- CCY
- POSOVDLMT
- NGOVDLMT
- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Request Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description

Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String
Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the Maker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the Checker.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the transaction Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Security-Product

Attribute	Description	
Name	Security-Product	
Datatype		
Description	Includes the Security Product Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates the Product Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ

Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REDMTYP

Attribute	Description
Name	REDMTYP
Datatype	String
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Q,S,B,

TOP

MINTRDQTY

Attribute	Description
Name	MINTRDQTY
Datatype	Number
Description	Indicates the Minimum Tradable Quantity.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

VTNGRGHTS

Attribute	**Description**	
Name	VTNGRGHTS	
Datatype	String	
Description	Indicates the Voting Rights.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BNKRSACPTNCE

Attribute	**Description**	
Name	BNKRSACPTNCE	
Datatype	String	
Description	Indicates the Bankers Acceptance Issue.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REGBEAR

Attribute	**Description**	
Name	REGBEAR	
Datatype	String	
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN

Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

DTPLHOLTRT

Attribute	**Description**	
Name	DTPLHOLTRT	
Datatype	String	
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,,

TOP

DTAMNDLMT

Attribute	**Description**	
Name	DTAMNDLMT	
Datatype	Number	
Description	Indicates the Coupon Date Amendment Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description	Indicates the Market Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRCECDDESC

Attribute	**Description**	
Name	PRCECDDESC	
Datatype	String	
Description	Indicates the Price Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description

Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description

Name	PRIMARYINTRSTINDI
Datatype	String
Description	Indicates the primary interest.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASICAMNTTAG

Attribute	**Description**	
Name	BASICAMNTTAG	
Datatype	String	
Description	Indicates the Basic Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTCATG

Attribute	**Description**	
Name	BASICAMTCATG	
Datatype	String	
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,X,N

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,X,S

TOP

FLTRTTYP

Attribute	**Description**	
Name	FLTRTTYP	
Datatype	String	
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTSRCDESC

Attribute	Description
Name	DFTRTSRCDESC
Datatype	String
Description	Indicates the Rate Source Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCDDESC

Attribute	Description
Name	DFTTNRCDDESC
Datatype	String
Description	Indicates the Tenor Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC

Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	

Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.149.2.SS-CreateSecurityProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-IO*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *Security-Product*
      - *HOLCHQREQ*
      - *INTRATETYP*
      - *LCLMRKTISUE*

RNCBLE
FRCQTYALWD
DCMLS
LOTSIZE
CALLOPT
PUTOPT
REDMTYP
MINTRDQTY
RESTRCTION
CVRED
CVRTBLE
VTNGRGHTS
BNKRSACPTNCE
REGBEAR
FRMTYP
CLTRLTYP
TNRUNT
MINTNR
MAXTNR
QTYQUOTN
PRCEQUOTN
INTQUOTN
AUTINITNCORPACT
CPNACTVLHOLTRT
DTPLHOLTRT
DTAMNDLMT
NOOFDAYS
DAYIND
REVALUATION_PRICE_CODE
Product-Variance
CCY
POSOVDLMT
NGOVDLMT
POSEXLMT
NGEXLMT
Product-Interest
Component-Details
COMPNENT
STPASSCIATN
PRIMARYINTRSTINDI
ACRALREQ
COUPONINDI
LEGTYP
EVNTFRASSOC

- *BASICAMNTTAG*
- *BASICAMTCATG*
- *RTTYP*
- *FLTRTTYP*
- *FLATAMNTPRUNIT*
- *DFTRTCD*
- *DFTRTSRC*
- *DFTTNRCD*
- *DFTWAIVER*
- *AMNDAFTRASSOCIAT*
- *ALLWRTTYPAMEND*
- *ALLWRTAMEND*
- *ALLWRTCDAMEND*
- *Currency-Rates*
  - *COMPNENTCCY*
  - *MINRAT*
  - *MAXRT*
  - *DFTRT*
  - *MINSPREAD*
  - *MAXSPREAD*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
- *Customers*
  - *CSTID*
  - *ALWD*

Branch-Ccy-Restrictions

- *CCYLST*
- *BRNLST*
- *CLASCD*
- *Branch-List*
  - *BRNDISALOW*
- *Ccy-List*
  - *BGTDLCCY*
  - *SOLDCCY*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Contains Input Only Request of Create Security Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String
Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.FXD - Fixed, FLT - Floating.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALLOPT

Attribute	**Description**	
Name	CALLOPT	
Datatype	String	
Description	Indicates the Call Option.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PUTOPT

Attribute	**Description**	
Name	PUTOPT	
Datatype	String	
Description	Indicates the Put Option	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description

Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN
Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description

Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes the Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description
Name	PRIMARYINTRSTINDI
Datatype	String

Description	Indicates the primary interest.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASICAMNTTAG

Attribute	Description	
Name	BASICAMNTTAG	
Datatype	String	
Description	Indicates the Basic Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTCATG

Attribute	Description	
Name	BASICAMTCATG	
Datatype	String	
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,X,N

TOP

RTTYP

Attribute	Description	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,X,S

TOP

FLTRTTYP

Attribute	Description	
Name	FLTRTTYP	
Datatype	String	
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND

Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID

Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Includes the Product MIS Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes

Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

2.149.3.SS-CreateSecurityProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*
  - *CCY*
  - *POSOVDLMT*
  - *NGOVDLMT*

- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

- CATGLIS
- CLASCD
- Cust-Categories

CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Indicates full FCUBS Response data.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	**Description**	
Name	PRDTYP	
Datatype	String	
Description	Indicates the Product Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Product Description.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description	Indicates the Product Slogan.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates the Product Group.	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates the Rate Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates the Product Type Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	**Description**	
Name	PRODUCT_GROUP_DESCRIPTION	
Datatype	String	
Description	Indicates the Product Group Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	**Description**	
Name	RESTRCTION	
Datatype	String	
Description	Indicates the Restricted.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRED

Attribute	**Description**	
Name	CVRED	
Datatype	String	
Description	Indicates the Covered.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	**Description**	
Name	QTYQUOTN	
Datatype	String	
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

PRCEQUOTN

Attribute	**Description**	
Name	PRCEQUOTN	
Datatype	String	
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	**Description**	
Name	INTQUOTN	
Datatype	String	
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

AUTINITNCORPACT

Attribute	**Description**	
Name	AUTINITNCORPACT	
Datatype	String	
Description	Indicates the Auto Initiation Of Corporate Action.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRCECDDESC

Attribute	Description
Name	PRCECDDESC

Datatype	String
Description	Indicates the Price Code Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number

Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Interest

Attribute	Description

Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description	
Name	PRIMARYINTRSTINDI	
Datatype	String	
Description	Indicates the primary interest.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRALREQ

Attribute	Description	
Name	ACRALREQ	
Datatype	String	
Description	Indicates the Accrual Required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPONINDI

Attribute	Description	
Name	COUPONINDI	
Datatype	String	
Description	Incdicates the Coupon Indicator. Y-Yes, N-No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LEGTYP

Attribute	Description	
Name	LEGTYP	
Datatype	String	
Description	Indicates the Leg Type. I- In, O- Out.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,X,N</td></tr></table>

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,X,S</td></tr></table>

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP

Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTRTSRCDESC

Attribute	**Description**	
Name	DFTRTSRCDESC	
Datatype	String	
Description	Indicates the Rate Source Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFTTNRCD

Attribute	**Description**	
Name	DFTTNRCD	
Datatype	String	
Description	Indicates the Default Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTTNRCDDESC

Attribute	**Description**	
Name	DFTTNRCDDESC	
Datatype	String	
Description	Indicates the Tenor Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFTWAIVER

Attribute	**Description**	
Name	DFTWAIVER	
Datatype	String	
Description	Indicates the Default Waiver.Y-Yes, N-No.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Currency-Rates

Attribute	Description	
Name	Currency-Rates	
Datatype		
Description	Includes the Currency Rates.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENTCCY

Attribute	Description	
Name	COMPNENTCCY	
Datatype	String	
Description	Indicates the component Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINRAT

Attribute	Description

Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the Class Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Customers

Attribute	Description	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description
Name	ALWD

Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description

Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Indicates FCUBS Error list.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.149.4.SS-CreateSecurityProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-PK*
      - *PRDCD*
    - *Product-IO*
      - *PRDCD*
      - *PRDTYP*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RATTYPPREFRD*
      - *PRDTYPDESC*
      - *PRODUCT_GROUP_DESCRIPTION*
      - *Security-Product*

- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *NOOFDAYS*
- *DAYIND*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*
  - *CCY*
  - *POSOVDLMT*
  - *NGOVDLMT*
  - *POSEXLMT*
  - *NGEXLMT*

Product-Interest

- *Component-Details*
  - *COMPNENT*
  - *STPASSCIATN*
  - *PRIMARYINTRSTINDI*
  - *ACRALREQ*

- COUPONINDI
- LEGTYP
- EVNTFRASSOC
- BASICAMNTTAG
- BASICAMTCATG
- RTTYP
- FLTRTTYP
- FLATAMNTPRUNIT
- DFTRTCD
- DFTRTSRC
- DFTTNRCD
- DFTWAIVER
- AMNDAFTRASSOCIAT
- ALLWRTTYPAMEND
- ALLWRTAMEND
- ALLWRTCDAMEND
- Currency-Rates
  - COMPNENTCCY
  - MINRAT
  - MAXRT
  - DFTRT
  - MINSPREAD
  - MAXSPREAD
- Prod-Cust-Restrictions
  - CATGLIS
  - CLASCD
  - Cust-Categories
    - CATGDSAW
  - Customers
    - CSTID
    - ALWD
- Branch-Ccy-Restrictions
  - CCYLST
  - BRNLST
  - CLASCD
  - Branch-List
    - BRNDISALOW
  - Ccy-List
    - BGTDLCCY
    - SOLDCCY
- Product-Fields
  - Field-Details
    - FLDNUM
    - FLDNAME

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-PK

Attribute	Description
Name	Product-PK
Datatype	
Description	Contains Primary Key Response of Create Security Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Contains Input Only Response of Create Security Product

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description

Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String

Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.FXD - Fixed, FLT - Floating.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PUTOPT

Attribute	**Description**	
Name	PUTOPT	
Datatype	String	
Description	Indicates the Put Option	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	**Description**	
Name	RESTRCTION	
Datatype	String	
Description	Indicates the Restricted.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description

Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN
Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Component-Details

Attribute	**Description**	
Name	Component-Details	
Datatype		
Description	Includes the Component Details.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates the Component.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

STPASSCIATN

Attribute	**Description**	
Name	STPASSCIATN	
Datatype	String	
Description	Indicates the Stop Association.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIMARYINTRSTINDI

Attribute	**Description**	
Name	PRIMARYINTRSTINDI	
Datatype	String	
Description	Indicates the primary interest.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASICAMNTTAG

Attribute	Description

Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,X,N

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,X,S

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP
Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFTRTCD

Attribute	**Description**	
Name	DFTRTCD	
Datatype	String	
Description	Indicates the Default Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTRTSRC

Attribute	**Description**	
Name	DFTRTSRC	
Datatype	String	
Description	Indicates the Default Rate Source.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTTNRCD

Attribute	**Description**	
Name	DFTTNRCD	
Datatype	String	
Description	Indicates the Default Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTWAIVER

Attribute	**Description**	
Name	DFTWAIVER	
Datatype	String	
Description	Indicates the Default Waiver.Y-Yes, N-No.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MINSPREAD

Attribute	**Description**	
Name	MINSPREAD	
Datatype	Number	
Description	Indicates the Minimum Spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	**Description**	
Name	MAXSPREAD	
Datatype	Number	
Description	Indicates the Maximum Spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Prod-Cust-Restrictions

Attribute	**Description**	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes the Product Customer Restriction.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Customers

Attribute	**Description**	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	**Description**	
Name	CSTID	
Datatype	String	
Description	Indicates Customer ID	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Includes the Product MIS Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	Description

Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Contains error details

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Contains warning details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.150.DeleteSecInstrument

DeleteSecInstrument

2.150.1.SS-DeleteSecInstrument-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

- *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTTIME

Attribute	**Description**	
Name	CHECKERDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

ISSDT

Attribute	**Description**	
Name	ISSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

STINTDT

Attribute	**Description**	
Name	STINTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDT

Attribute	**Description**
Name	STTRADEDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	**Description**	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	**Description**	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	**Description**	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

RITBASS

Attribute	Description	
Name	RITBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

AUTOCRP

Attribute	Description	
Name	AUTOCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCDISTYP

Attribute	Description	
Name	ACCDISTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECRSTATUS

Attribute	**Description**	
Name	SECRSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,P,R,S,

TOP

TRADSTATUS

Attribute	**Description**	
Name	TRADSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

INTERESTTYPE

Attribute	**Description**	
Name	INTERESTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description	
Name	LCLMRKTISUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISSUERID

Attribute	Description	
Name	ISSUERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ISSUERDES

Attribute	Description	
Name	ISSUERDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REGORBEAR

Attribute	Description	
Name	REGORBEAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

CALLOPTION

Attribute	**Description**	
Name	CALLOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUESIZE

Attribute	**Description**	
Name	ISSUESIZE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	Description	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description
Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description

Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCOUPFREQ

Attribute	Description
Name	BCOUPFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description
Name	ACCVALDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	**Description**	
Name	COUPPLTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

CADHMNTHND

Attribute	**Description**	
Name	CADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVFRQ

Attribute	**Description**	
Name	REVFRQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	**Description**
Name	Security-Hol-Ccy
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BHOLCCY

Attribute	**Description**	
Name	BHOLCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Security-Series

Attribute	**Description**	
Name	Security-Series	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BSERIES

Attribute	**Description**	
Name	BSERIES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Coupon-Sched

Attribute	**Description**	
Name	Coupon-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	**Description**	
Name	ADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Coupon-Period

Attribute	**Description**	
Name	Coupon-Period	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BPCD

Attribute	**Description**	
Name	BPCD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BNCD

Attribute	**Description**	
Name	BNCD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCOUPTYDES

Attribute	**Description**

Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Revision-Sched

Attribute	Description

Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BESN

Attribute	Description	
Name	BESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCRRATESN

Attribute	Description	
Name	BCRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BFLTAMT

Attribute	Description	
Name	BFLTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BINCLACMET

Attribute	Description	
Name	BINCLACMET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description	
Name	BINTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.150.2.SS-DeleteSecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *SECURITYID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.150.3.SS-DeleteSecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*

VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6

BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*

BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE

- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption

- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master

- *BREVDT*
- *REVEFFDT*

Interest-Assoc

- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1

- *BSECID*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*

- *CRRATESN*
- *TAGCCY*
- *TAGAMNT*
- *TAXCCY*
- *TAXAMNT*
- *WAIVER*
- *LIQDINDICAT*

Liqdmaster

- *INTCOMP*
- *TAXCCY*
- *TAXAMNT*

Issrtax

- *INTCOMP*
- *CRRATESN*
- *RATECOD*
- *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESTRICTED

Attribute	**Description**	
Name	RESTRICTED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VOTRT

Attribute	**Description**	
Name	VOTRT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVER

Attribute	**Description**	
Name	COVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVERBLE

Attribute	**Description**	
Name	CONVERBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BBKACC

Attribute	Description	
Name	BBKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICD

Attribute	Description	
Name	ISOCFICD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISITCCD

Attribute	Description	
Name	ISITCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ATTRIBDES

Attribute	Description	
Name	ATTRIBDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	**Description**	
Name	USEBONDFORM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TBILLREINVPR

Attribute	**Description**	
Name	TBILLREINVPR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNMTH

Attribute	**Description**	
Name	TBILLANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

TBILLCNTNR

Attribute	**Description**	
Name	TBILLCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT5

Attribute	**Description**	
Name	BATTRIBNARRAT5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT6

Attribute	**Description**	
Name	BATTRIBNARRAT6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT7

Attribute	**Description**	
Name	BATTRIBNARRAT7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT8

Attribute	**Description**	
Name	BATTRIBNARRAT8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,F,C,

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,E,R,W,Z</td></tr></table>

TOP

SECREFERNO

Attribute	Description
Name	SECREFERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,P,R,S,</td></tr></table>

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,I,</td></tr></table>

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	**Description**	
Name	QTYQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

PRIQUT

Attribute	**Description**	
Name	PRIQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	**Description**	
Name	INTQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description
Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Revision-Sched

Attribute	**Description**	
Name	Revision-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**
Name	REVBASFREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Revision-Date-Master

Attribute	**Description**	
Name	Revision-Date-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVDT

Attribute	**Description**	
Name	BREVDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

REVEFFDT

Attribute	**Description**	
Name	REVEFFDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Interest-Assoc

Attribute	**Description**	
Name	Interest-Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BACQAMT

Attribute	**Description**
Name	BACQAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	Description	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RATECOD

Attribute	**Description**	
Name	RATECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.150.4.SS-DeleteSecInstrument-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-PK*
      - *SECURITYID*
    - *Security-Master-IO*
      - *SECURITYID*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-PK

Attribute	Description
Name	Security-Master-PK
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.151.DeleteSecurityProduct

Deletion of Securities Security Product

2.151.1.SS-DeleteSecurityProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*

- CCY
- POSOVDLMT
- NGOVDLMT
- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Indicates FCUBS Full Request For Deleting Security Product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description

Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String
Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the Maker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the Checker.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the transaction Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Security-Product

Attribute	Description	
Name	Security-Product	
Datatype		
Description	Includes the Security Product Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates the Product Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ

Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DCMLS

Attribute	**Description**	
Name	DCMLS	
Datatype	Number	
Description	Indicates the Decimals.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOTSIZE

Attribute	**Description**	
Name	LOTSIZE	
Datatype	Number	
Description	Indicates the Lot Size.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALLOPT

Attribute	**Description**	
Name	CALLOPT	
Datatype	String	
Description	Indicates the Call Option.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PUTOPT

Attribute	**Description**	
Name	PUTOPT	
Datatype	String	
Description	Indicates the Put Option.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	Description
Name	REDMTYP
Datatype	String
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B,

TOP

MINTRDQTY

Attribute	Description
Name	MINTRDQTY
Datatype	Number
Description	Indicates the Minimum Tradable Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

VTNGRGHTS

Attribute	**Description**	
Name	VTNGRGHTS	
Datatype	String	
Description	Indicates the Voting Rights.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BNKRSACPTNCE

Attribute	**Description**	
Name	BNKRSACPTNCE	
Datatype	String	
Description	Indicates the Bankers Acceptance Issue.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REGBEAR

Attribute	**Description**	
Name	REGBEAR	
Datatype	String	
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN

Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

DTPLHOLTRT

Attribute	**Description**	
Name	DTPLHOLTRT	
Datatype	String	
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,,

TOP

DTAMNDLMT

Attribute	**Description**	
Name	DTAMNDLMT	
Datatype	Number	
Description	Indicates the Coupon Date Amendment Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MRKTDESC

Attribute	**Description**	
Name	MRKTDESC	
Datatype	String	
Description	Indicates the Market Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRCECDDESC

Attribute	**Description**	
Name	PRCECDDESC	
Datatype	String	
Description	Indicates the Price Code Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description

Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description

Name	PRIMARYINTRSTINDI
Datatype	String
Description	Indicates the primary interest.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASICAMNTTAG

Attribute	**Description**	
Name	BASICAMNTTAG	
Datatype	String	
Description	Indicates the Basic Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTCATG

Attribute	**Description**	
Name	BASICAMTCATG	
Datatype	String	
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,X,N

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,X,S

TOP

FLTRTTYP

Attribute	**Description**	
Name	FLTRTTYP	
Datatype	String	
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTSRCDESC

Attribute	Description
Name	DFTRTSRCDESC
Datatype	String
Description	Indicates the Rate Source Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCDDESC

Attribute	Description
Name	DFTTNRCDDESC
Datatype	String
Description	Indicates the Tenor Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC

Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	

Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.151.2.SS-DeleteSecurityProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicates FCUBS IO Request For deleting the Security Product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

2.151.3.SS-DeleteSecurityProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*
  - *CCY*
  - *POSOVDLMT*
  - *NGOVDLMT*

- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

- CATGLIS
- CLASCD
- Cust-Categories

CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Indicates Full Response For Deleting the Security Product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	**Description**	
Name	PRDTYP	
Datatype	String	
Description	Indicates the Product Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Product Description.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description	Indicates the Product Slogan.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates the Product Group.	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates the Rate Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates the Product Type Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	**Description**	
Name	PRODUCT_GROUP_DESCRIPTION	
Datatype	String	
Description	Indicates the Product Group Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

HOLCHQREQ

Attribute	Description	
Name	HOLCHQREQ	
Datatype	String	
Description	Indicates whether Holiday Check is Required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

INTRATETYP

Attribute	Description	
Name	INTRATETYP	
Datatype	String	
Description	Indicates the Interest Rate type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description	
Name	LCLMRKTISUE	
Datatype	String	
Description	Indicates the Market Of Issue.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

RNCBLE

Attribute	Description	
Name	RNCBLE	
Datatype	String	
Description	Indicates the Renouncable.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	**Description**	
Name	RESTRCTION	
Datatype	String	
Description	Indicates the Restricted.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRED

Attribute	**Description**	
Name	CVRED	
Datatype	String	
Description	Indicates the Covered.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN
Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRCECDDESC

Attribute	Description
Name	PRCECDDESC

Datatype	String
Description	Indicates the Price Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number

Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Interest

Attribute	Description

Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description	
Name	PRIMARYINTRSTINDI	
Datatype	String	
Description	Indicates the primary interest.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRALREQ

Attribute	Description	
Name	ACRALREQ	
Datatype	String	
Description	Indicates the Accrual Required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPONINDI

Attribute	Description	
Name	COUPONINDI	
Datatype	String	
Description	Incdicates the Coupon Indicator. Y-Yes, N-No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LEGTYP

Attribute	Description	
Name	LEGTYP	
Datatype	String	
Description	Indicates the Leg Type. I- In, O- Out.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,X,N</td></tr></table>

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,X,S</td></tr></table>

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP

Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTRTSRCDESC

Attribute	Description	
Name	DFTRTSRCDESC	
Datatype	String	
Description	Indicates the Rate Source Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFTTNRCD

Attribute	Description	
Name	DFTTNRCD	
Datatype	String	
Description	Indicates the Default Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTTNRCDDESC

Attribute	Description	
Name	DFTTNRCDDESC	
Datatype	String	
Description	Indicates the Tenor Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFTWAIVER

Attribute	Description	
Name	DFTWAIVER	
Datatype	String	
Description	Indicates the Default Waiver.Y-Yes, N-No.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Currency-Rates

Attribute	Description	
Name	Currency-Rates	
Datatype		
Description	Includes the Currency Rates.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENTCCY

Attribute	Description	
Name	COMPNENTCCY	
Datatype	String	
Description	Indicates the component Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINRAT

Attribute	Description

Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the Class Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Customers

Attribute	Description	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description
Name	ALWD

Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNUM

Attribute	**Description**	
Name	FLDNUM	
Datatype	Number	
Description	Indicates Field Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Includes the Product MIS Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**

Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Indicates FCUBS Error List.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.151.4.SS-DeleteSecurityProduct-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Product-PK
PRDCD
Product-IO
PRDCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-PK

Attribute	Description
Name	Product-PK
Datatype	
Description	Indicates Product Code in FCUBS Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicates IO Product Code for delete in FCUBS Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.152.ModifySecInstrument

ModifySecInstrument

2.152.1.SS-ModifySecInstrument-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

- *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTTIME

Attribute	**Description**	
Name	CHECKERDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

ISSDT

Attribute	**Description**	
Name	ISSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

STINTDT

Attribute	**Description**	
Name	STINTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDT

Attribute	**Description**
Name	STTRADEDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	**Description**	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	**Description**	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	**Description**	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

RITBASS

Attribute	Description	
Name	RITBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

AUTOCRP

Attribute	Description	
Name	AUTOCRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACCDISTYP

Attribute	Description	
Name	ACCDISTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

RATECD

Attribute	Description	
Name	RATECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECRSTATUS

Attribute	**Description**	
Name	SECRSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,P,R,S,

TOP

TRADSTATUS

Attribute	**Description**	
Name	TRADSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

INTERESTTYPE

Attribute	**Description**	
Name	INTERESTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B,

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	**Description**	
Name	ACCRDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	**Description**	
Name	ACCRDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

ACRR366BSS

Attribute	**Description**	
Name	ACRR366BSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D,

TOP

ACCRINCLDT

Attribute	**Description**	
Name	ACCRINCLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	Description	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description
Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description

Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCOUPFREQ

Attribute	Description
Name	BCOUPFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description
Name	ACCVALDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	**Description**	
Name	COUPPLTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

CADHMNTHND

Attribute	**Description**	
Name	CADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVFRQ

Attribute	**Description**	
Name	REVFRQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	**Description**
Name	Security-Hol-Ccy
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description

Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Revision-Sched

Attribute	Description

Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description	
Name	REVWEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description	
Name	REVADHMON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Redemption

Attribute	Description	
Name	Redemption	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREDEVTDT

Attribute	Description	
Name	BREDEVTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPFUN

Attribute	**Description**	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS1

Attribute	**Description**	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS2

Attribute	**Description**	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS1

Attribute	**Description**	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS2

Attribute	**Description**	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS3

Attribute	**Description**	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.152.2.SS-ModifySecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *ISSSEID*
    - *CNBSEID*
    - *ISOCFICD*
    - *ISITCCD*
    - *ATTRIBDES*
    - *BQUALRAT*
    - *REVPRICOD*
    - *BMKTREV*
    - *USEBONDFORM*
    - *TBILLREINVPR*
    - *TBILLANNMTH*
    - *TBILLCNTNR*
    - *TBILLCNTDN*
    - *BNDREINVPR*
    - *BNDANNMTH*
    - *BNDDAYCNTNR*
    - *BNDDAYCNTDN*
    - *PREMDISCURR*

BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
LCLMRKTISUE
ISSUERID
REGORBEAR
FORMTYPE
FRACTQUNT
BUDECIMAL
RENOUNCE
REDTYP
PUTOPTION
PAYMENTCCY
OSISSIZ
MINTDQT
LOTSIZ
Taxheadmaster
  REFERENCE_NO
TXNUDFDETAILS
  FLDNAME
  FLDVAL
Misdetails
  CONREFNO
  MISGRP

RELACC
RELETED_REFERENCE
MISHEAD
RATEFLG
POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFXRATE
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5

FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ATTRIBDES

Attribute	**Description**	
Name	ATTRIBDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BQUALRAT

Attribute	**Description**	
Name	BQUALRAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVPRICOD

Attribute	**Description**	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,H,X,</td></tr></table>

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,C,</td></tr></table>

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,E,U,</td></tr></table>

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H,X,

TOP

PREMDISCURR

Attribute	**Description**	
Name	PREMDISCURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BDAYS

Attribute	**Description**	
Name	BDAYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BDAYIN

Attribute	**Description**	
Name	BDAYIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A,

TOP

MINRATES

Attribute	**Description**	
Name	MINRATES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT1

Attribute	**Description**	
Name	BATTRIBNARRAT1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT2

Attribute	**Description**	
Name	BATTRIBNARRAT2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT3

Attribute	**Description**	
Name	BATTRIBNARRAT3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT4

Attribute	**Description**	
Name	BATTRIBNARRAT4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,F,C,

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISSUERID

Attribute	Description
Name	ISSUERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RENOUNCE

Attribute	**Description**	
Name	RENOUNCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REDTYP

Attribute	**Description**	
Name	REDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,1,2,3,4,5,6,7,8,9</td></tr></table>

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD2

Attribute	**Description**	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

2.152.3.SS-ModifySecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*

VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6

BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*

BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE

- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption

- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master

- *BREVDT*
- *REVEFFDT*

Interest-Assoc

- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1

- *BSECID*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*

- *CRRATESN*
- *TAGCCY*
- *TAGAMNT*
- *TAXCCY*
- *TAXAMNT*
- *WAIVER*
- *LIQDINDICAT*

Liqdmaster

- *INTCOMP*
- *TAXCCY*
- *TAXAMNT*

Issrtax

- *INTCOMP*
- *CRRATESN*
- *RATECOD*
- *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESTRICTED

Attribute	**Description**	
Name	RESTRICTED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VOTRT

Attribute	**Description**	
Name	VOTRT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVER

Attribute	**Description**	
Name	COVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVERBLE

Attribute	**Description**	
Name	CONVERBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BBKACC

Attribute	Description	
Name	BBKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ISOCFICD

Attribute	Description	
Name	ISOCFICD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

ISITCCD

Attribute	Description	
Name	ISITCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

ATTRIBDES

Attribute	Description	
Name	ATTRIBDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	**Description**	
Name	USEBONDFORM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TBILLREINVPR

Attribute	**Description**	
Name	TBILLREINVPR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNMTH

Attribute	**Description**	
Name	TBILLANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

TBILLCNTNR

Attribute	**Description**	
Name	TBILLCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT5

Attribute	**Description**	
Name	BATTRIBNARRAT5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT6

Attribute	**Description**	
Name	BATTRIBNARRAT6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT7

Attribute	**Description**	
Name	BATTRIBNARRAT7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT8

Attribute	**Description**	
Name	BATTRIBNARRAT8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT9

Attribute	**Description**	
Name	BATTRIBNARRAT9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT10

Attribute	**Description**	
Name	BATTRIBNARRAT10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REDQUOT

Attribute	**Description**	
Name	REDQUOT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,F,C,

TOP

CONFCORP

Attribute	**Description**	
Name	CONFCORP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURITYID

Attribute	Description	
Name	SECURITYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISINIDENTFR

Attribute	Description	
Name	ISINIDENTFR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SECURITYDESC

Attribute	Description	
Name	SECURITYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRODUCT

Attribute	Description	
Name	PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,E,R,W,Z</td></tr></table>

TOP

SECREFERNO

Attribute	Description
Name	SECREFERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,P,R,S,</td></tr></table>

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,I,</td></tr></table>

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	**Description**	
Name	QTYQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

PRIQUT

Attribute	**Description**	
Name	PRIQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	**Description**	
Name	INTQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCOUPSTDT

Attribute	**Description**	
Name	BCOUPSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BCOUPTYPE

Attribute	**Description**	
Name	BCOUPTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BCOUPENDT

Attribute	**Description**	
Name	BCOUPENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BBASEFREQ

Attribute	**Description**	
Name	BBASEFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description
Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Revision-Sched

Attribute	**Description**	
Name	Revision-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**
Name	REVBASFREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Revision-Date-Master

Attribute	**Description**	
Name	Revision-Date-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVDT

Attribute	**Description**	
Name	BREVDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

REVEFFDT

Attribute	**Description**	
Name	REVEFFDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Interest-Assoc

Attribute	**Description**	
Name	Interest-Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BACQAMT

Attribute	**Description**
Name	BACQAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	**Description**	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	**Description**	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RATECOD

Attribute	**Description**	
Name	RATECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.152.4.SS-ModifySecInstrument-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-PK*
      - *SECURITYID*
    - *Security-Master-IO*
      - *ISSSEID*
      - *CNBSEID*
      - *ISOCFICD*
      - *ISITCCD*
      - *ATTRIBDES*
      - *BQUALRAT*
      - *REVPRICOD*
      - *BMKTREV*
      - *USEBONDFORM*
      - *TBILLREINVPR*
      - *TBILLANNMTH*
      - *TBILLCNTNR*
      - *TBILLCNTDN*
      - *BNDREINVPR*
      - *BNDANNMTH*

BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
LCLMRKTISUE
ISSUERID
REGORBEAR
FORMTYPE
FRACTQUNT
BUDECIMAL
RENOUNCE
REDTYP
PUTOPTION
PAYMENTCCY
OSISSIZ
MINTDQT
LOTSIZ
Taxheadmaster
  REFERENCE_NO
TXNUDFDETAILS
  FLDNAME
  FLDVAL

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*

FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-PK

Attribute	Description
Name	Security-Master-PK
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT2

Attribute	**Description**	
Name	BIDNTINARRAT2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT3

Attribute	**Description**	
Name	BIDNTINARRAT3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT4

Attribute	**Description**	
Name	BIDNTINARRAT4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT1

Attribute	**Description**	
Name	BATTRIBNARRAT1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

FRACTQUNT

Attribute	**Description**	
Name	FRACTQUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BUDECIMAL

Attribute	**Description**	
Name	BUDECIMAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RENOUNCE

Attribute	**Description**	
Name	RENOUNCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Q,S,B,

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	16

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.153.ModifySecurityProduct

Modification of Securities Security Product

2.153.1.SS-ModifySecurityProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*

- CCY
- POSOVDLMT
- NGOVDLMT
- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Request Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description

Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String
Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	**Description**	
Name	MAKERSTAMP	
Datatype	String	
Description	Indicates the Maker date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	**Description**	
Name	CHECKER	
Datatype	String	
Description	Indicates the Checker.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates the Checker Date Stamp.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description	Indicates the transaction Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates the Authorisation Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Security-Product

Attribute	Description	
Name	Security-Product	
Datatype		
Description	Includes the Security Product Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description	Indicates the Product Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ

Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DCMLS

Attribute	**Description**	
Name	DCMLS	
Datatype	Number	
Description	Indicates the Decimals.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOTSIZE

Attribute	**Description**	
Name	LOTSIZE	
Datatype	Number	
Description	Indicates the Lot Size.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CALLOPT

Attribute	**Description**	
Name	CALLOPT	
Datatype	String	
Description	Indicates the Call Option.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PUTOPT

Attribute	**Description**	
Name	PUTOPT	
Datatype	String	
Description	Indicates the Put Option.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	Description
Name	REDMTYP
Datatype	String
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Q,S,B,

TOP

MINTRDQTY

Attribute	Description
Name	MINTRDQTY
Datatype	Number
Description	Indicates the Minimum Tradable Quantity.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

VTNGRGHTS

Attribute	**Description**	
Name	VTNGRGHTS	
Datatype	String	
Description	Indicates the Voting Rights.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BNKRSACPTNCE

Attribute	**Description**	
Name	BNKRSACPTNCE	
Datatype	String	
Description	Indicates the Bankers Acceptance Issue.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REGBEAR

Attribute	**Description**	
Name	REGBEAR	
Datatype	String	
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B

TOP

FRMTYP

Attribute	**Description**	
Name	FRMTYP	
Datatype	String	
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYQUOTN

Attribute	Description
Name	QTYQUOTN

Datatype	String
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRCECDDESC

Attribute	Description
Name	PRCECDDESC
Datatype	String
Description	Indicates the Price Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description

Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description

Name	PRIMARYINTRSTINDI
Datatype	String
Description	Indicates the primary interest.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASICAMNTTAG

Attribute	**Description**	
Name	BASICAMNTTAG	
Datatype	String	
Description	Indicates the Basic Amount Tag.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

BASICAMTCATG

Attribute	**Description**	
Name	BASICAMTCATG	
Datatype	String	
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,X,N

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,X,S

TOP

FLTRTTYP

Attribute	**Description**	
Name	FLTRTTYP	
Datatype	String	
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTSRCDESC

Attribute	Description
Name	DFTRTSRCDESC
Datatype	String
Description	Indicates the Rate Source Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCDDESC

Attribute	Description
Name	DFTTNRCDDESC
Datatype	String
Description	Indicates the Tenor Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC

Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION

Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	

Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	**Description**	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.153.2.SS-ModifySecurityProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *MODNO*
    - *Security-Product*
      - *ORDPREF*
      - *HOLCHQREQ*
      - *INTRATETYP*
      - *LCLMRKTISUE*
      - *RNCBLE*

- FRCQTYALWD
- DCMLS
- LOTSIZE
- CALLOPT
- PUTOPT
- REDMTYP
- MINTRDQTY
- RESTRCTION
- CVRED
- CVRTBLE
- VTNGRGHTS
- BNKRSACPTNCE
- REGBEAR
- FRMTYP
- CLTRLTYP
- TNRUNT
- MINTNR
- MAXTNR
- QTYQUOTN
- PRCEQUOTN
- INTQUOTN
- AUTINITNCORPACT
- CPNACTVLHOLTRT
- DTPLHOLTRT
- DTAMNDLMT
- NOOFDAYS
- DAYIND
- REVALUATION_PRICE_CODE
- Product-Variance
  - CCY
  - POSOVDLMT
  - NGOVDLMT
  - POSEXLMT
  - NGEXLMT

Product-Interest

- Component-Details
  - COMPNENT
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG

- *BASICAMTCATG*
- *RTTYP*
- *FLTRTTYP*
- *FLATAMNTPRUNIT*
- *DFTRTCD*
- *DFTRTSRC*
- *DFTTNRCD*
- *DFTWAIVER*
- *AMNDAFTRASSOCIAT*
- *ALLWRTTYPAMEND*
- *ALLWRTAMEND*
- *ALLWRTCDAMEND*
- *Currency-Rates*
  - *COMPNENTCCY*
  - *MINRAT*
  - *MAXRT*
  - *DFTRT*
  - *MINSPREAD*
  - *MAXSPREAD*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*
- *Cust-Categories*
  - *CATGDSAW*
- *Customers*
  - *CSTID*
  - *ALWD*

Branch-Ccy-Restrictions

- *CCYLST*
- *BRNLST*
- *CLASCD*
- *Branch-List*
  - *BRNDISALOW*
- *Ccy-List*
  - *BGTDLCCY*
  - *SOLDCCY*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	Indicates FCUBS Request Header.

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicate FCUBS IO Request to Modify the Security Product.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description	Indicates the Product Start Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	**Description**	
Name	PRDENDDT	
Datatype	Date	
Description	Indicates the Product End Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description	Indicates the Product Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

NRMLRTVARI

Attribute	**Description**	
Name	NRMLRTVARI	
Datatype	Number	
Description	Indicates the Overide Limit.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXRTVARI

Attribute	**Description**
Name	MAXRTVARI

Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORDPREF

Attribute	Description
Name	ORDPREF
Datatype	String
Description	Indicates the order preference.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.FXD - Fixed, FLT - Floating.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REDMTYP

Attribute	Description
Name	REDMTYP
Datatype	String
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B,

TOP

MINTRDQTY

Attribute	Description
Name	MINTRDQTY
Datatype	Number
Description	Indicates the Minimum Tradable Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR

Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXTNR

Attribute	**Description**	
Name	MAXTNR	
Datatype	Number	
Description	Indicates the Maximium Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	**Description**	
Name	QTYQUOTN	
Datatype	String	
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

PRCEQUOTN

Attribute	**Description**	
Name	PRCEQUOTN	
Datatype	String	
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	**Description**	
Name	INTQUOTN	
Datatype	String	
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number

Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description
Name	PRIMARYINTRSTINDI
Datatype	String
Description	Indicates the primary interest.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ

Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description
Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,X,N

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,X,S

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP
Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFTRTCD

Attribute	Description	
Name	DFTRTCD	
Datatype	String	
Description	Indicates the Default Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTRTSRC

Attribute	Description	
Name	DFTRTSRC	
Datatype	String	
Description	Indicates the Default Rate Source.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTTNRCD

Attribute	Description	
Name	DFTTNRCD	
Datatype	String	
Description	Indicates the Default Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTWAIVER

Attribute	Description	
Name	DFTWAIVER	
Datatype	String	
Description	Indicates the Default Waiver.Y-Yes, N-No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPREAD

Attribute	Description	
Name	MINSPREAD	
Datatype	Number	
Description	Indicates the Minimum Spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXSPREAD

Attribute	Description	
Name	MAXSPREAD	
Datatype	Number	
Description	Indicates the Maximum Spread.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description	Includes the Product Customer Restriction.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	Description	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Branch-List

Attribute	**Description**	
Name	Branch-List	
Datatype		
Description	Indicates Branch List	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	**Description**	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	**Description**	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	**Description**	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Includes the Product MIS Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	Description	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	Description	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD5

Attribute	Description	
Name	CSTCD5	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	Description	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISTYP

Attribute	Description

Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

2.153.3.SS-ModifySecurityProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Full*
    - *PRDCD*
    - *PRDTYP*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDGRP*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDRMRKS*
    - *NRMLRTVARI*
    - *MAXRTVARI*
    - *RTCODEPRFERD*
    - *RATTYPPREFRD*
    - *PRDTYPDESC*
    - *PRODUCT_GROUP_DESCRIPTION*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*
  - *CCY*
  - *POSOVDLMT*
  - *NGOVDLMT*

- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

- CATGLIS
- CLASCD
- Cust-Categories

CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Contain FCUBS Security Product Full Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDTYP

Attribute	**Description**	
Name	PRDTYP	
Datatype	String	
Description	Indicates the Product Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	2

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description	Indicates the Product Description.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description	Indicates the Product Slogan.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDGRP

Attribute	**Description**	
Name	PRDGRP	
Datatype	String	
Description	Indicates the Product Group.	
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RTCODEPRFERD

Attribute	**Description**	
Name	RTCODEPRFERD	
Datatype	String	
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,M,B

TOP

RATTYPPREFRD

Attribute	**Description**	
Name	RATTYPPREFRD	
Datatype	String	
Description	Indicates the Rate Type.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

PRDTYPDESC

Attribute	**Description**	
Name	PRDTYPDESC	
Datatype	String	
Description	Indicates the Product Type Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	**Description**	
Name	PRODUCT_GROUP_DESCRIPTION	
Datatype	String	
Description	Indicates the Product Group Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates the Maker date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	**Description**	
Name	RESTRCTION	
Datatype	String	
Description	Indicates the Restricted.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRED

Attribute	**Description**	
Name	CVRED	
Datatype	String	
Description	Indicates the Covered.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	**Description**	
Name	QTYQUOTN	
Datatype	String	
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

PRCEQUOTN

Attribute	**Description**	
Name	PRCEQUOTN	
Datatype	String	
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	**Description**	
Name	INTQUOTN	
Datatype	String	
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

AUTINITNCORPACT

Attribute	**Description**	
Name	AUTINITNCORPACT	
Datatype	String	
Description	Indicates the Auto Initiation Of Corporate Action.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRCECDDESC

Attribute	Description
Name	PRCECDDESC

Datatype	String
Description	Indicates the Price Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number

Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Interest

Attribute	Description

Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates the component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description	
Name	PRIMARYINTRSTINDI	
Datatype	String	
Description	Indicates the primary interest.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRALREQ

Attribute	Description	
Name	ACRALREQ	
Datatype	String	
Description	Indicates the Accrual Required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPONINDI

Attribute	Description	
Name	COUPONINDI	
Datatype	String	
Description	Incdicates the Coupon Indicator. Y-Yes, N-No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LEGTYP

Attribute	Description	
Name	LEGTYP	
Datatype	String	
Description	Indicates the Leg Type. I- In, O- Out.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>25</td></tr></table>

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,X,N</td></tr></table>

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,X,S</td></tr></table>

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP

Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT
Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTRTSRCDESC

Attribute	**Description**	
Name	DFTRTSRCDESC	
Datatype	String	
Description	Indicates the Rate Source Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFTTNRCD

Attribute	**Description**	
Name	DFTTNRCD	
Datatype	String	
Description	Indicates the Default Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DFTTNRCDDESC

Attribute	**Description**	
Name	DFTTNRCDDESC	
Datatype	String	
Description	Indicates the Tenor Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DFTWAIVER

Attribute	**Description**	
Name	DFTWAIVER	
Datatype	String	
Description	Indicates the Default Waiver.Y-Yes, N-No.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates the Event Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Currency-Rates

Attribute	Description	
Name	Currency-Rates	
Datatype		
Description	Includes the Currency Rates.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENTCCY

Attribute	Description	
Name	COMPNENTCCY	
Datatype	String	
Description	Indicates the component Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

MINRAT

Attribute	Description

Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CATGLIS

Attribute	**Description**	
Name	CATGLIS	
Datatype	String	
Description	Indicates Category List	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the Class Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	Description	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Customers

Attribute	Description	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description
Name	ALWD

Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNUM

Attribute	**Description**	
Name	FLDNUM	
Datatype	Number	
Description	Indicates Field Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Mis-Details

Attribute	**Description**	
Name	Product-Mis-Details	
Datatype		
Description	Includes the Product MIS Details.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description	Indicates MIS group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**

Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Default-Mis-Codes

Attribute	**Description**	
Name	Default-Mis-Codes	
Datatype		
Description	Indicates Default MIS Codes	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	**Description**	
Name	MISCLS	
Datatype	String	
Description	Indicates MIS class.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

MISCD

Attribute	**Description**	
Name	MISCD	
Datatype	String	
Description	Indicates MIS code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

FCUBS_ERROR_RESP

Attribute	**Description**	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Indicates FCUBS Error List.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning List.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.153.4.SS-ModifySecurityProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-PK*
      - *PRDCD*
    - *Product-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RATTYPPREFRD*
      - *MODNO*
      - *Security-Product*
        - *ORDPREF*
        - *HOLCHQREQ*

- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *NOOFDAYS*
- *DAYIND*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*
  - *CCY*
  - *POSOVDLMT*
  - *NGOVDLMT*
  - *POSEXLMT*
  - *NGEXLMT*

Product-Interest

- *Component-Details*
  - *COMPNENT*
  - *STPASSCIATN*
  - *PRIMARYINTRSTINDI*
  - *ACRALREQ*
  - *COUPONINDI*

LEGTYP
EVNTFRASSOC
BASICAMNTTAG
BASICAMTCATG
RTTYP
FLTRTTYP
FLATAMNTPRUNIT
DFTRTCD
DFTRTSRC
DFTTNRCD
DFTWAIVER
AMNDAFTRASSOCIAT
ALLWRTTYPAMEND
ALLWRTAMEND
ALLWRTCDAMEND
Currency-Rates
COMPNENTCCY
MINRAT
MAXRT
DFTRT
MINSPREAD
MAXSPREAD
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details

MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-PK

Attribute	Description
Name	Product-PK
Datatype	
Description	Indicates FCUBS Primary key Response .

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicates FCUBS IO Response .

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDSTRTDT

Attribute	Description

Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTCODEPRFERD

Attribute	Description

Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORDPREF

Attribute	Description
Name	ORDPREF
Datatype	String
Description	Indicates the order preference.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.FXD - Fixed, FLT - Floating.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS
Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REDMTYP

Attribute	**Description**	
Name	REDMTYP	
Datatype	String	
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

MINTRDQTY

Attribute	**Description**	
Name	MINTRDQTY	
Datatype	Number	
Description	Indicates the Minimum Tradable Quantity.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RESTRCTION

Attribute	**Description**	
Name	RESTRCTION	
Datatype	String	
Description	Indicates the Restricted.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRED

Attribute	**Description**	
Name	CVRED	
Datatype	String	
Description	Indicates the Covered.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS
Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TNRUNT

Attribute	Description
Name	TNRUNT
Datatype	String
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

TOP

MINTNR

Attribute	Description
Name	MINTNR
Datatype	Number
Description	Indicates the Minimum Tenor.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTNR

Attribute	Description
Name	MAXTNR
Datatype	Number
Description	Indicates the Maximium Tenor.

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	**Description**	
Name	QTYQUOTN	
Datatype	String	
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

PRCEQUOTN

Attribute	**Description**	
Name	PRCEQUOTN	
Datatype	String	
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	**Description**	
Name	INTQUOTN	
Datatype	String	
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,P,

TOP

AUTINITNCORPACT

Attribute	**Description**	
Name	AUTINITNCORPACT	
Datatype	String	
Description	Indicates the Auto Initiation Of Corporate Action.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description
Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

REVALUATION_PRICE_CODE

Attribute	**Description**	
Name	REVALUATION_PRICE_CODE	
Datatype	String	
Description	Indicates the Revaluation Price Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Product-Variance

Attribute	**Description**	
Name	Product-Variance	
Datatype		
Description	Includes the Product Variance.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description	Indicates the Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

POSOVDLMT

Attribute	**Description**	
Name	POSOVDLMT	
Datatype	Number	
Description	Indicates the Minimum Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	Indicates the Component.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

STPASSCIATN

Attribute	Description
Name	STPASSCIATN
Datatype	String
Description	Indicates the Stop Association.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIMARYINTRSTINDI

Attribute	Description
Name	PRIMARYINTRSTINDI
Datatype	String
Description	Indicates the primary interest.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRALREQ

Attribute	Description
Name	ACRALREQ
Datatype	String
Description	Indicates the Accrual Required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COUPONINDI

Attribute	Description

Name	COUPONINDI
Datatype	String
Description	Incdicates the Coupon Indicator. Y-Yes, N-No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LEGTYP

Attribute	Description
Name	LEGTYP
Datatype	String
Description	Indicates the Leg Type. I- In, O- Out.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,O

TOP

EVNTFRASSOC

Attribute	Description
Name	EVNTFRASSOC
Datatype	String
Description	Indicates the Event For Asscoation.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,X,N

TOP

RTTYP

Attribute	**Description**	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,X,S

TOP

FLTRTTYP

Attribute	**Description**	
Name	FLTRTTYP	
Datatype	String	
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P,

TOP

FLATAMNTPRUNIT

Attribute	**Description**	
Name	FLATAMNTPRUNIT	
Datatype	String	
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DFTRTCD

Attribute	**Description**	
Name	DFTRTCD	
Datatype	String	
Description	Indicates the Default Rate Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description

Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description

Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description

Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disallowed	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SOLDCCY

Attribute	Description	
Name	SOLDCCY	
Datatype	String	
Description	Indicates Sold Currency.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Product-Fields

Attribute	Description

Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4

Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning List.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.154.QuerySecInstrument

QuerySecInstrument

2.154.1.SS-QuerySecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *SECURITYID*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.154.2.SS-QuerySecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-IO*
      - *SECURITYID*
    - *Security-Master-Full*
      - *MAKER*
      - *MAKDTTIME*
      - *CHECKERID*
      - *CHECKERDTTIME*
      - *AUTHSTAT*
      - *ISSDT*
      - *STINTDT*
      - *STTRADEDT*
      - *REDDT*
      - *SECURITYCCY*
      - *INFACVAL*
      - *ISSPRIC*
      - *CURRENTFV*
      - *REDPRIC*
      - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

WAIVER

Appln

INTCOMP

CRRATESN

TAGCCY

TAGAMNT

TAXCCY

TAXAMNT

WAIVER

LIQDINDICAT

Liqdmaster

INTCOMP

TAXCCY

TAXAMNT

Issrtax

INTCOMP

CRRATESN

RATECOD

WAIVER

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BQUALRAT

Attribute	**Description**	
Name	BQUALRAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVPRICOD

Attribute	**Description**	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BPRICDES

Attribute	**Description**	
Name	BPRICDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	Description	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	Description	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	Description	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

RITBASS

Attribute	Description	
Name	RITBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,C,</td></tr></table>

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,E,U,</td></tr></table>

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>L,H,X,</td></tr></table>

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BNDANNMTH

Attribute	**Description**	
Name	BNDANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

BNDDAYCNTNR

Attribute	**Description**	
Name	BNDDAYCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

BNDDAYCNTDN

Attribute	**Description**	
Name	BNDDAYCNTDN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,H,X,

TOP

PREMDISCURR

Attribute	**Description**	
Name	PREMDISCURR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT2

Attribute	Description	
Name	BIDNTINARRAT2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT3

Attribute	Description	
Name	BIDNTINARRAT3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BIDNTINARRAT4

Attribute	Description	
Name	BIDNTINARRAT4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT1

Attribute	Description	
Name	BATTRIBNARRAT1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,F,C,

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

SECURITYDESC

Attribute	**Description**	
Name	SECURITYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

PRODUCT

Attribute	**Description**	
Name	PRODUCT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SECURITYP

Attribute	**Description**	
Name	SECURITYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,P,R,S,

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I,

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,N,</td></tr></table>

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,PRI,PRM,PPR,PPM,YTM</td></tr></table>

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>F,P,</td></tr></table>

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Q,S,B,

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,D,</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATEBASS

Attribute	**Description**	
Name	RATEBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BCUMINTRAT

Attribute	**Description**	
Name	BCUMINTRAT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRNUMMTH

Attribute	**Description**	
Name	ACCRNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	**Description**	
Name	ACCRDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description	
Name	ACCRDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

ACRR366BSS

Attribute	Description	
Name	ACRR366BSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D,

TOP

ACCRINCLDT

Attribute	Description	
Name	ACCRINCLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description
Name	LIQDDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description
Name	LIQDDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BREVWEEK

Attribute	Description
Name	BREVWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description

Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description
Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	**Description**	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	**Description**	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	**Description**	
Name	BCOUPWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	**Description**	
Name	COUPPLTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	30

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BCOUPENDT

Attribute	**Description**	
Name	BCOUPENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BBASEFREQ

Attribute	**Description**	
Name	BBASEFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	**Description**	
Name	COUPWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	**Description**	
Name	ADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BCOUPTYDES

Attribute	Description
Name	BCOUPTYDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Revision-Sched

Attribute	Description
Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**	
Name	REVBASFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	**Description**	
Name	REVWEKDAY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVDT

Attribute	Description

Name	BREVDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	1

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description

Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description

Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BSECID

Attribute	**Description**	
Name	BSECID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Security-Hol-Ccy1

Attribute	**Description**	
Name	Security-Hol-Ccy1	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BSECID

Attribute	**Description**	
Name	BSECID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	**Description**	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	**Description**	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	**Description**	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>5</td></tr></table>

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	**Description**	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	**Description**	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	**Description**	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	**Description**	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.155.QuerySecurityProduct

Query for Securities Security Product

2.155.1.SS-QuerySecurityProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
nillable	true

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	

Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicates the Product Code in FCUBS Request.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

TOP

2.155.2.SS-QuerySecurityProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-IO*
      - *PRDCD*
    - *Product-Full*
      - *PRDCD*
      - *PRDTYP*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDGRP*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDRMRKS*
      - *NRMLRTVARI*
      - *MAXRTVARI*
      - *RTCODEPRFERD*
      - *RATTYPPREFRD*
      - *PRDTYPDESC*
      - *PRODUCT_GROUP_DESCRIPTION*
      - *MAKER*

MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Security-Product
- *PRDCD*
- *HOLCHQREQ*
- *INTRATETYP*
- *LCLMRKTISUE*
- *RNCBLE*
- *FRCQTYALWD*
- *DCMLS*
- *LOTSIZE*
- *CALLOPT*
- *PUTOPT*
- *REDMTYP*
- *MINTRDQTY*
- *RESTRCTION*
- *CVRED*
- *CVRTBLE*
- *VTNGRGHTS*
- *BNKRSACPTNCE*
- *REGBEAR*
- *FRMTYP*
- *CLTRLTYP*
- *TNRUNT*
- *MINTNR*
- *MAXTNR*
- *QTYQUOTN*
- *PRCEQUOTN*
- *INTQUOTN*
- *AUTINITNCORPACT*
- *CPNACTVLHOLTRT*
- *DTPLHOLTRT*
- *DTAMNDLMT*
- *MRKTDESC*
- *PRCECDDESC*
- *NOOFDAYS*
- *DAYIND*
- *TXT_CLASS_DESC*
- *REVALUATION_PRICE_CODE*
- *Product-Variance*

- CCY
- POSOVDLMT
- NGOVDLMT
- POSEXLMT
- NGEXLMT

Product-Class-Link

- CLASCD
- CLASS_DESC

Product-Interest

- Component-Details
  - COMPNENT
  - COMPDESC
  - STPASSCIATN
  - PRIMARYINTRSTINDI
  - ACRALREQ
  - COUPONINDI
  - LEGTYP
  - EVNTFRASSOC
  - BASICAMNTTAG
  - BASICAMTCATG
  - RTTYP
  - FLTRTTYP
  - FLATAMNTPRUNIT
  - DFTRTCD
  - DFTRTCDDESC
  - DFTRTSRC
  - DFTRTSRCDESC
  - DFTTNRCD
  - DFTTNRCDDESC
  - DFTWAIVER
  - AMNDAFTRASSOCIAT
  - ALLWRTTYPAMEND
  - ALLWRTAMEND
  - ALLWRTCDAMEND
  - EVNTDESC
  - DESCRIPTION
  - Currency-Rates
    - COMPNENTCCY
    - MINRAT
    - MAXRT
    - DFTRT
    - MINSPREAD
    - MAXSPREAD

Prod-Cust-Restrictions

CATGLIS
CLASCD
Cust-Categories
CATGDSAW
DESCRIPTION
Customers
CSTID
CUSTNAME
ALWD
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
CLASDESC
Branch-List
BRNDISALOW
BRNNAME
Ccy-List
BGTDLCCY
CCYNAME
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISCLS
MISCD
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration; Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-IO

Attribute	Description
Name	Product-IO
Datatype	
Description	Indicates the Product Code in FCUBS Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Product-Full

Attribute	Description
Name	Product-Full
Datatype	
Description	Indicates full Product details in FCUBS Response.

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	Indicates the Product Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	Indicates the Product Description.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	Indicates the Product Slogan.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	Indicates the Product Group.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	Indicates the Product Start Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT

Datatype	Date
Description	Indicates the Product End Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	Indicates the Product Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	Indicates the Overide Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	Indicates the Stop Limit.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	Indicates the Rate Code Prefered. M - Mid Rate, B - Buy / Sell Rate
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,M,B

TOP

RATTYPPREFRD

Attribute	Description
Name	RATTYPPREFRD
Datatype	String
Description	Indicates the Rate Type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	Indicates the Product Type Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PRODUCT_GROUP_DESCRIPTION

Attribute	Description
Name	PRODUCT_GROUP_DESCRIPTION
Datatype	String
Description	Indicates the Product Group Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	Indicates the Maker.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates the Maker date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	Indicates the Checker.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates the Checker Date Stamp.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the transaction Status.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Indicates the Authorisation Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Security-Product

Attribute	Description
Name	Security-Product
Datatype	
Description	Includes the Security Product Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

HOLCHQREQ

Attribute	Description
Name	HOLCHQREQ
Datatype	String
Description	Indicates whether Holiday Check is Required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRATETYP

Attribute	Description
Name	INTRATETYP
Datatype	String
Description	Indicates the Interest Rate type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / FXD,FLT,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	Indicates the Market Of Issue.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

RNCBLE

Attribute	Description
Name	RNCBLE
Datatype	String
Description	Indicates the Renouncable.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRCQTYALWD

Attribute	Description
Name	FRCQTYALWD
Datatype	String
Description	Indicates the Fractional Quantity Allowed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DCMLS

Attribute	Description
Name	DCMLS

Datatype	Number
Description	Indicates the Decimals.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LOTSIZE

Attribute	Description
Name	LOTSIZE
Datatype	Number
Description	Indicates the Lot Size.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CALLOPT

Attribute	Description
Name	CALLOPT
Datatype	String
Description	Indicates the Call Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PUTOPT

Attribute	Description
Name	PUTOPT
Datatype	String
Description	Indicates the Put Option.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REDMTYP

Attribute	Description
Name	REDMTYP
Datatype	String
Description	Indicates the Redemption Type.Q - Quanity, S - Series, B - Bullet
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Q,S,B,

TOP

MINTRDQTY

Attribute	Description
Name	MINTRDQTY
Datatype	Number
Description	Indicates the Minimum Tradable Quantity.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RESTRCTION

Attribute	Description
Name	RESTRCTION
Datatype	String
Description	Indicates the Restricted.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRED

Attribute	Description
Name	CVRED
Datatype	String
Description	Indicates the Covered.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CVRTBLE

Attribute	Description
Name	CVRTBLE
Datatype	String
Description	Indicates the Convertible.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

VTNGRGHTS

Attribute	Description
Name	VTNGRGHTS

Datatype	String
Description	Indicates the Voting Rights.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BNKRSACPTNCE

Attribute	Description
Name	BNKRSACPTNCE
Datatype	String
Description	Indicates the Bankers Acceptance Issue.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REGBEAR

Attribute	Description
Name	REGBEAR
Datatype	String
Description	Indicates the Registered/Bearer. R - Registered, B - Bearer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B

TOP

FRMTYP

Attribute	Description
Name	FRMTYP
Datatype	String
Description	Indicates the Form Type. S - Scrip Based, I - Immobilized, D - Dematerialized, C - Combination, G - Sgl.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,I,D,C,G

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	Indicates the Collateral Type.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TNRUNT

Attribute	**Description**	
Name	TNRUNT	
Datatype	String	
Description	Indicates the Tenor Unit. D - Days, W - Weeks, M - Months, Y - Years.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,W,M,Y,

TOP

MINTNR

Attribute	**Description**	
Name	MINTNR	
Datatype	Number	
Description	Indicates the Minimum Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAXTNR

Attribute	**Description**	
Name	MAXTNR	
Datatype	Number	
Description	Indicates the Maximium Tenor.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYQUOTN

Attribute	**Description**	
Name	QTYQUOTN	
Datatype	String	
Description	Indicates the Quantity Quotation. U - Units, N - Nominal.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N

TOP

PRCEQUOTN

Attribute	Description
Name	PRCEQUOTN
Datatype	String
Description	Indicates the Price Quotation. PRI - Price, PRM - Discount Or Premium, PPR - %Price, PPM - %Discount or Premium, YTM - Yield To Maturity.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / PRI,PRM,PPR,PPM,YTM

TOP

INTQUOTN

Attribute	Description
Name	INTQUOTN
Datatype	String
Description	Indicates the Interest Quotation. F - Flat, P - Accrued.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

AUTINITNCORPACT

Attribute	Description
Name	AUTINITNCORPACT
Datatype	String
Description	Indicates the Auto Initiation Of Corporate Action.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CPNACTVLHOLTRT

Attribute	Description
Name	CPNACTVLHOLTRT
Datatype	String
Description	Indicates the Actual Value Date. I - Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

DTPLHOLTRT

Attribute	Description

Name	DTPLHOLTRT
Datatype	String
Description	Indicates the Coupon Plotting. I- Ignore, F - Forward, B - Backward.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,F,,

TOP

DTAMNDLMT

Attribute	Description
Name	DTAMNDLMT
Datatype	Number
Description	Indicates the Coupon Date Amendment Limit.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MRKTDESC

Attribute	Description
Name	MRKTDESC
Datatype	String
Description	Indicates the Market Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRCECDDESC

Attribute	Description
Name	PRCECDDESC
Datatype	String
Description	Indicates the Price Code Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOOFDAYS

Attribute	Description
Name	NOOFDAYS
Datatype	Number
Description	Indicates the number of Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DAYIND

Attribute	Description
Name	DAYIND
Datatype	String
Description	Indicates the Day Indicator. B - Before Start Of Next Coupon Period, A - After Start Of Next Coupon Period.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

TXT_CLASS_DESC

Attribute	Description
Name	TXT_CLASS_DESC
Datatype	String
Description	Indicates the Text Class Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REVALUATION_PRICE_CODE

Attribute	Description
Name	REVALUATION_PRICE_CODE
Datatype	String
Description	Indicates the Revaluation Price Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Product-Variance

Attribute	Description
Name	Product-Variance
Datatype	
Description	Includes the Product Variance.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates the Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

POSOVDLMT

Attribute	Description
Name	POSOVDLMT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NGOVDLMT

Attribute	Description
Name	NGOVDLMT
Datatype	Number
Description	Indicates the Maximum Rate.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

POSEXLMT

Attribute	Description
Name	POSEXLMT
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NGEXLMT

Attribute	Description
Name	NGEXLMT
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Product-Class-Link

Attribute	Description
Name	Product-Class-Link
Datatype	
Description	Includes the Product Class Link Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASS_DESC

Attribute	Description
Name	CLASS_DESC
Datatype	String
Description	Indicates the Class Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Product-Interest

Attribute	Description
Name	Product-Interest
Datatype	
Description	Includes the Product Interest.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Component-Details

Attribute	Description
Name	Component-Details
Datatype	
Description	Includes Component Details.

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	**Description**	
Name	COMPNENT	
Datatype	String	
Description	Indicates the Component.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPDESC

Attribute	**Description**	
Name	COMPDESC	
Datatype	String	
Description	Indicates the component Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

STPASSCIATN

Attribute	**Description**	
Name	STPASSCIATN	
Datatype	String	
Description	Indicates the Stop Association.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIMARYINTRSTINDI

Attribute	**Description**	
Name	PRIMARYINTRSTINDI	
Datatype	String	
Description	Indicates the primary interest.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACRALREQ

Attribute	Description	
Name	ACRALREQ	
Datatype	String	
Description	Indicates the Accrual Required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COUPONINDI

Attribute	Description	
Name	COUPONINDI	
Datatype	String	
Description	Incdicates the Coupon Indicator. Y-Yes, N-No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LEGTYP

Attribute	Description	
Name	LEGTYP	
Datatype	String	
Description	Indicates the Leg Type. I- In, O- Out.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,O

TOP

EVNTFRASSOC

Attribute	Description	
Name	EVNTFRASSOC	
Datatype	String	
Description	Indicates the Event For Asscoation.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BASICAMNTTAG

Attribute	Description
Name	BASICAMNTTAG
Datatype	String
Description	Indicates the Basic Amount Tag.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTCATG

Attribute	Description
Name	BASICAMTCATG
Datatype	String
Description	Indicates the Amount Category. D-OverDue, X-Expected, N-Normal.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,X,N

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type. F-Floating, X-Fixed, S-Special.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,X,S

TOP

FLTRTTYP

Attribute	Description
Name	FLTRTTYP
Datatype	String
Description	Indicates the Floating Rate Type. A-Automatic, P-Periodic.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

FLATAMNTPRUNIT

Attribute	Description
Name	FLATAMNTPRUNIT

Datatype	String
Description	Indicates the Flat Amount Per Unit. Y-Yes, N-No.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DFTRTCD

Attribute	Description
Name	DFTRTCD
Datatype	String
Description	Indicates the Default Rate Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTRTCDDESC

Attribute	Description
Name	DFTRTCDDESC
Datatype	String
Description	Indicates the Rate Code Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DFTRTSRC

Attribute	Description
Name	DFTRTSRC
Datatype	String
Description	Indicates the Default Rate Source.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DFTRTSRCDESC

Attribute	Description
Name	DFTRTSRCDESC
Datatype	String
Description	Indicates the Rate Source Description.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTTNRCD

Attribute	Description
Name	DFTTNRCD
Datatype	String
Description	Indicates the Default Tenor.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DFTTNRCDDESC

Attribute	Description
Name	DFTTNRCDDESC
Datatype	String
Description	Indicates the Tenor Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DFTWAIVER

Attribute	Description
Name	DFTWAIVER
Datatype	String
Description	Indicates the Default Waiver.Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOCIAT

Attribute	Description
Name	AMNDAFTRASSOCIAT
Datatype	String
Description	Indicates the Amend After Assocation. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTTYPAMEND

Attribute	Description
Name	ALLWRTTYPAMEND
Datatype	String
Description	Indicates the Allow Rate Type Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTAMEND

Attribute	Description
Name	ALLWRTAMEND
Datatype	String
Description	Indcates the Allow Rate Amend. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALLWRTCDAMEND

Attribute	Description
Name	ALLWRTCDAMEND
Datatype	String
Description	Indicates the Allow Rate Code Amendment. Y-Yes, N-No.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates the Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Currency-Rates

Attribute	Description
Name	Currency-Rates
Datatype	
Description	Includes the Currency Rates.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNENTCCY

Attribute	Description
Name	COMPNENTCCY
Datatype	String
Description	Indicates the component Currency.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MINRAT

Attribute	Description
Name	MINRAT
Datatype	Number
Description	Indicates the Minimum Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRT

Attribute	Description
Name	MAXRT
Datatype	Number

Description	Indicates the Maximum Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DFTRT

Attribute	Description
Name	DFTRT
Datatype	Number
Description	Indicates the Default Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPREAD

Attribute	Description
Name	MINSPREAD
Datatype	Number
Description	Indicates the Minimum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXSPREAD

Attribute	Description
Name	MAXSPREAD
Datatype	Number
Description	Indicates the Maximum Spread.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	Includes the Product Customer Restriction.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,A

TOP

CLASCD

Attribute	**Description**	
Name	CLASCD	
Datatype	String	
Description	Indicates the Class Code.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Cust-Categories

Attribute	**Description**	
Name	Cust-Categories	
Datatype		
Description	Indicates Customer Categories	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CATGDSAW

Attribute	**Description**	
Name	CATGDSAW	
Datatype	String	
Description	Indicates code of customer category	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

DESCRIPTION

Attribute	**Description**	
Name	DESCRIPTION	
Datatype	String	
Description	Indicates the Description.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Branch-Ccy-Restrictions

Attribute	Description

Name	Branch-Ccy-Restrictions
Datatype	
Description	Includes the Branch Currency Restrictions.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates the Class Code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Description
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	Includes the Product Fields.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	Includes the Product MIS Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes

Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Indicates FCUBS Error list.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Indicates FCUBS Warning list.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.156.ReopenSecInstrument

ReopenSecInstrument

2.156.1.SS-ReopenSecInstrument-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*

MKTSEID
CNBSEID
RESTRICTED
VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3

BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6
BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
  BLIQD366BASS
  ISSUESIZE

DOCSWIFT
BZEROINT
RATEBASS
BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2

Revision-Sched
- *BREVSTDT*
- *BREVTYPE*
- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption
- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master
- *BREVDT*
- *REVEFFDT*

Interest-Assoc
- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1
- *BSECID*

Taxheadmaster
- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*

- *WAIVER*
- *Appln*
  - *INTCOMP*
  - *CRRATESN*
  - *TAGCCY*
  - *TAGAMNT*
  - *TAXCCY*
  - *TAXAMNT*
  - *WAIVER*
  - *LIQDINDICAT*
- *Liqdmaster*
  - *INTCOMP*
  - *TAXCCY*
  - *TAXAMNT*
- *Issrtax*
  - *INTCOMP*
  - *CRRATESN*
  - *RATECOD*
  - *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*

TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4

COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERDTTIME

Attribute	**Description**	
Name	CHECKERDTTIME	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

ISSDT

Attribute	**Description**	
Name	ISSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

STINTDT

Attribute	**Description**	
Name	STINTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STTRADEDT

Attribute	**Description**
Name	STTRADEDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RESTRICTED

Attribute	Description
Name	RESTRICTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

VOTRT

Attribute	Description
Name	VOTRT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COVER

Attribute	Description
Name	COVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CONVERBLE

Attribute	Description
Name	CONVERBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

COLLATYPE

Attribute	Description
Name	COLLATYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

DIREXPLIN

Attribute	Description
Name	DIREXPLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

BQUALRAT

Attribute	Description
Name	BQUALRAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REVPRICOD

Attribute	Description
Name	REVPRICOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BMKTREV

Attribute	**Description**	
Name	BMKTREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

COUPBASIS

Attribute	**Description**	
Name	COUPBASIS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

DIVBASS

Attribute	**Description**	
Name	DIVBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,H,

TOP

WARRBASS

Attribute	**Description**	
Name	WARRBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USEBONDFORM

Attribute	Description
Name	USEBONDFORM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TBILLREINVPR

Attribute	Description
Name	TBILLREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TBILLANNMTH

Attribute	Description
Name	TBILLANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

TBILLCNTNR

Attribute	Description
Name	TBILLCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BATTRIBNARRAT5

Attribute	Description
Name	BATTRIBNARRAT5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT6

Attribute	Description
Name	BATTRIBNARRAT6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT7

Attribute	Description
Name	BATTRIBNARRAT7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT8

Attribute	Description
Name	BATTRIBNARRAT8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT9

Attribute	Description
Name	BATTRIBNARRAT9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BATTRIBNARRAT10

Attribute	Description
Name	BATTRIBNARRAT10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

REDQUOT

Attribute	Description
Name	REDQUOT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,F,C,</td></tr></table>

TOP

CONFCORP

Attribute	Description
Name	CONFCORP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

SECURITYID

Attribute	Description
Name	SECURITYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,B,E,R,W,Z

TOP

SECREFERNO

Attribute	**Description**	
Name	SECREFERNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SECRSTATUS

Attribute	**Description**	
Name	SECRSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	E,P,R,S,

TOP

TRADSTATUS

Attribute	**Description**	
Name	TRADSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,I,

TOP

INTERESTTYPE

Attribute	**Description**	
Name	INTERESTTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description	
Name	LCLMRKTISUE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ISSUERID

Attribute	Description	
Name	ISSUERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ISSUERDES

Attribute	Description	
Name	ISSUERDES	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REGORBEAR

Attribute	Description	
Name	REGORBEAR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	Description
Name	FORMTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / S,I,D,C,G,

TOP

QTYQUT

Attribute	Description
Name	QTYQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

PRIQUT

Attribute	Description
Name	PRIQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	Description
Name	INTQUT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Q,S,B,

TOP

CALLOPTION

Attribute	**Description**	
Name	CALLOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PUTOPTION

Attribute	**Description**	
Name	PUTOPTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PAYMENTCCY

Attribute	**Description**	
Name	PAYMENTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUESIZE

Attribute	**Description**	
Name	ISSUESIZE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description	
Name	ACCRDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description	
Name	ACCRDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

ACRR366BSS

Attribute	Description	
Name	ACRR366BSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,D,

TOP

ACCRINCLDT

Attribute	Description	
Name	ACCRINCLDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	Description	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	Description	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	Description	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	Description	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description
Name	RADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDBASS

Attribute	Description
Name	RNDBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,N,

TOP

BPERCOUP

Attribute	Description
Name	BPERCOUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALLASNCREV

Attribute	Description
Name	ALLASNCREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BPERREV

Attribute	Description

Name	BPERREV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCAPT

Attribute	Description
Name	BCAPT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BCOUPFREQ

Attribute	Description
Name	BCOUPFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description
Name	ACCVALDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	**Description**	
Name	COUPPLTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

CADHMNTHND

Attribute	**Description**	
Name	CADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVFRQ

Attribute	**Description**	
Name	REVFRQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	**Description**
Name	Security-Hol-Ccy
Datatype	
Description	

Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	1

Restrictions	

Restrictions	Description
maxLength	30

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BCOUPSTDT

Attribute	Description
Name	BCOUPSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BCOUPTYPE

Attribute	Description
Name	BCOUPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BCOUPENDT

Attribute	Description
Name	BCOUPENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BBASEFREQ

Attribute	Description
Name	BBASEFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

ADHMNTHND

Attribute	**Description**	
Name	ADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Coupon-Period

Attribute	**Description**	
Name	Coupon-Period	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BPCD

Attribute	**Description**	
Name	BPCD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BNCD

Attribute	**Description**	
Name	BNCD	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BCOUPTYDES

Attribute	**Description**

Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Revision-Sched

Attribute	Description

Name	Revision-Sched
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVSTDT

Attribute	Description
Name	BREVSTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

BREVTYPE

Attribute	Description
Name	BREVTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

BREVENDT

Attribute	Description
Name	BREVENDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVBASFREQ

Attribute	Description
Name	REVBASFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BACQAMT

Attribute	Description
Name	BACQAMT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Taxheadmaster

Attribute	**Description**	
Name	Taxheadmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REFERENCE_NO

Attribute	**Description**	
Name	REFERENCE_NO	
Datatype	String	
Description	Indicates Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Assoc

Attribute	**Description**	
Name	Assoc	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	Description
Name	CRRATEESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Appln

Attribute	Description
Name	Appln
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

TAGCCY

Attribute	**Description**	
Name	TAGCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAGAMNT

Attribute	**Description**	
Name	TAGAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

LIQDINDICAT

Attribute	Description
Name	LIQDINDICAT
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Liqdmaster

Attribute	Description
Name	Liqdmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TAXCCY

Attribute	**Description**	
Name	TAXCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Issrtax

Attribute	**Description**	
Name	Issrtax	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	**Description**	
Name	INTCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

RATECOD

Attribute	Description
Name	RATECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

RATEFLG

Attribute	Description
Name	RATEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPTXN

Attribute	**Description**	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	**Description**	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	**Description**	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS1

Attribute	Description
Name	COMMIS1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS6

Attribute	**Description**	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.156.2.SS-ReopenSecInstrument-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-IO*
    - *SECURITYID*
    - *Taxheadmaster*
      - *REFERENCE_NO*
    - *TXNUDFDETAILS*
      - *FLDNAME*
      - *FLDVAL*
    - *Misdetails*
      - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

2.156.3.SS-ReopenSecInstrument-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Security-Master-Full*
    - *MAKER*
    - *MAKDTTIME*
    - *CHECKERID*
    - *CHECKERDTTIME*
    - *AUTHSTAT*
    - *ISSDT*
    - *STINTDT*
    - *STTRADEDT*
    - *REDDT*
    - *SECURITYCCY*
    - *INFACVAL*
    - *ISSPRIC*
    - *CURRENTFV*
    - *REDPRIC*
    - *ISSSEID*
    - *MKTSEID*
    - *CNBSEID*
    - *RESTRICTED*

VOTRT
COVER
CONVERBLE
BBKACC
ISOCFICD
ISITCCD
ATTRIBDES
COLLATYPE
DIREXPLIN
BQUALRAT
REVPRICOD
BPRICDES
BMKTREV
COUPBASIS
DIVBASS
WARRBASS
RITBASS
AUTOCRP
ACCDISTYP
RATECD
USEBONDFORM
TBILLREINVPR
TBILLANNMTH
TBILLCNTNR
TBILLCNTDN
BNDREINVPR
BNDANNMTH
BNDDAYCNTNR
BNDDAYCNTDN
PREMDISCURR
BDAYS
BDAYIN
MINRATES
MAXRATES
BIDNTINARRAT1
BIDNTINARRAT2
BIDNTINARRAT3
BIDNTINARRAT4
BATTRIBNARRAT1
BATTRIBNARRAT2
BATTRIBNARRAT3
BATTRIBNARRAT4
BATTRIBNARRAT5
BATTRIBNARRAT6

BATTRIBNARRAT7
BATTRIBNARRAT8
BATTRIBNARRAT9
BATTRIBNARRAT10
REDQUOT
CONFCORP
SECURITYID
ISINIDENTFR
SECURITYDESC
PRODUCT
SECURITYP
SECREFERNO
SECRSTATUS
TRADSTATUS
INTERESTTYPE
LCLMRKTISUE
ISSUERID
ISSUERDES
REGORBEAR
FORMTYPE
QTYQUT
PRIQUT
INTQUT
FRACTQUNT
BUDECIMAL
BEQRED
RENOUNCE
REDTYP
CALLOPTION
PUTOPTION
PAYMENTCCY
ISSUESIZE
OSISSIZ
MINTDQT
LOTSIZ
TXNSTAT
PRODUCTDES
MARKTDESC
Interest
- *BLIQD366BASS*
- *ISSUESIZE*
- *DOCSWIFT*
- *BZEROINT*
- *RATEBASS*

BCUMINTRAT
ACCRNUMMTH
ACCRDENMTH
ACCRDENBSS
ACRR366BSS
ACCRINCLDT
LIQDNUMMTH
LIQDDENMTH
LIQDDENBSS
BREVWEEK
RADHMNTHND
RNDBASS
BPERCOUP
ALLASNCREV
BPERREV
BCAPT
BCOUPFREQ
ACCVALDT
BCOUPWEEK
COUPPLTDT
CADHMNTHND
REVFRQ
Security-Hol-Ccy
BHOLCCY
Security-Series
BSERIES
Coupon-Sched
BCOUPSTDT
BCOUPTYPE
BCOUPENDT
BBASEFREQ
COUPWEEK
ADHMNTHND
Coupon-Period
BPCD
BNCD
BCOUPTYDES
BVIRPREVDT2
BVIRPREVDT1
BVIRNEXDT1
BVIRNEXDT2
Revision-Sched
BREVSTDT
BREVTYPE

- *BREVENDT*
- *REVBASFREQ*
- *REVWEKDAY*
- *REVADHMON*

Redemption

- *BREDEVTDT*
- *BPERRED*
- *BREDPRI*
- *BDISPFRAC*
- *BCALLINDCAT*
- *BREDSERIES*

Revision-Date-Master

- *BREVDT*
- *REVEFFDT*

Interest-Assoc

- *BACQAMT*
- *BESN*
- *BCRRATESN*
- *BFLTAMT*
- *BINCLACMET*
- *BINTCOMP*
- *BINTRATE*
- *BINTSPRD*
- *BQUOTREVCEIL*
- *BQUOTREVFLR*
- *BQUOTREVIND*
- *SPRD*
- *BRATECODE*
- *BRATCODESC*
- *BTENCODE*
- *BTENCODESC*
- *BWAIVER*
- *BSECID*

Security-Hol-Ccy1

- *BSECID*

Taxheadmaster

- *REFERENCE_NO*
- *Assoc*
  - *INTCOMP*
  - *CRRATEESN*
  - *RULE*
  - *WAIVER*
- *Appln*
  - *INTCOMP*

- *CRRATESN*
- *TAGCCY*
- *TAGAMNT*
- *TAXCCY*
- *TAXAMNT*
- *WAIVER*
- *LIQDINDICAT*

Liqdmaster

- *INTCOMP*
- *TAXCCY*
- *TAXAMNT*

Issrtax

- *INTCOMP*
- *CRRATESN*
- *RATECOD*
- *WAIVER*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*

TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7

COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Security-Master-Full

Attribute	Description
Name	Security-Master-Full
Datatype	
Description	

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHECKERID

Attribute	Description

Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTTIME

Attribute	Description
Name	CHECKERDTTIME
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

STINTDT

Attribute	Description
Name	STINTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STTRADEDT

Attribute	Description
Name	STTRADEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REDDT

Attribute	Description
Name	REDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECURITYCCY

Attribute	Description
Name	SECURITYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INFACVAL

Attribute	Description
Name	INFACVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSPRIC

Attribute	Description
Name	ISSPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CURRENTFV

Attribute	Description
Name	CURRENTFV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REDPRIC

Attribute	Description
Name	REDPRIC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSSEID

Attribute	Description
Name	ISSSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MKTSEID

Attribute	Description
Name	MKTSEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CNBSEID

Attribute	Description
Name	CNBSEID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RESTRICTED

Attribute	**Description**	
Name	RESTRICTED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

VOTRT

Attribute	**Description**	
Name	VOTRT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COVER

Attribute	**Description**	
Name	COVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CONVERBLE

Attribute	**Description**	
Name	CONVERBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BBKACC

Attribute	Description
Name	BBKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ISOCFICD

Attribute	Description
Name	ISOCFICD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

ISITCCD

Attribute	Description
Name	ISITCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

ATTRIBDES

Attribute	Description
Name	ATTRIBDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COLLATYPE

Attribute	Description	
Name	COLLATYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

DIREXPLIN

Attribute	Description	
Name	DIREXPLIN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

BQUALRAT

Attribute	Description	
Name	BQUALRAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

REVPRICOD

Attribute	Description	
Name	REVPRICOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

BPRICDES

Attribute	Description
Name	BPRICDES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

TOP

BMKTREV

Attribute	Description
Name	BMKTREV
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

COUPBASIS

Attribute	Description
Name	COUPBASIS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

DIVBASS

Attribute	Description
Name	DIVBASS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,H,</td></tr></table>

TOP

WARRBASS

Attribute	Description
Name	WARRBASS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

RITBASS

Attribute	Description
Name	RITBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,H,

TOP

AUTOCRP

Attribute	Description
Name	AUTOCRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACCDISTYP

Attribute	Description
Name	ACCDISTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I,

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

USEBONDFORM

Attribute	**Description**	
Name	USEBONDFORM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TBILLREINVPR

Attribute	**Description**	
Name	TBILLREINVPR	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TBILLANNMTH

Attribute	**Description**	
Name	TBILLANNMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,C,

TOP

TBILLCNTNR

Attribute	**Description**	
Name	TBILLCNTNR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,E,U,

TOP

TBILLCNTDN

Attribute	Description
Name	TBILLCNTDN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

BNDREINVPR

Attribute	Description
Name	BNDREINVPR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BNDANNMTH

Attribute	Description
Name	BNDANNMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,

TOP

BNDDAYCNTNR

Attribute	Description
Name	BNDDAYCNTNR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,E,U,

TOP

BNDDAYCNTDN

Attribute	Description
Name	BNDDAYCNTDN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,H,X,

TOP

PREMDISCURR

Attribute	Description
Name	PREMDISCURR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BDAYS

Attribute	Description
Name	BDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDAYIN

Attribute	Description
Name	BDAYIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A,

TOP

MINRATES

Attribute	Description
Name	MINRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRATES

Attribute	Description
Name	MAXRATES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BIDNTINARRAT1

Attribute	Description
Name	BIDNTINARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT2

Attribute	Description
Name	BIDNTINARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT3

Attribute	Description
Name	BIDNTINARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BIDNTINARRAT4

Attribute	Description
Name	BIDNTINARRAT4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT1

Attribute	Description
Name	BATTRIBNARRAT1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT2

Attribute	Description
Name	BATTRIBNARRAT2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT3

Attribute	Description
Name	BATTRIBNARRAT3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BATTRIBNARRAT4

Attribute	Description
Name	BATTRIBNARRAT4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT5

Attribute	**Description**	
Name	BATTRIBNARRAT5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT6

Attribute	**Description**	
Name	BATTRIBNARRAT6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT7

Attribute	**Description**	
Name	BATTRIBNARRAT7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT8

Attribute	**Description**	
Name	BATTRIBNARRAT8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT9

Attribute	**Description**	
Name	BATTRIBNARRAT9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BATTRIBNARRAT10

Attribute	**Description**	
Name	BATTRIBNARRAT10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REDQUOT

Attribute	**Description**	
Name	REDQUOT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,F,C,

TOP

CONFCORP

Attribute	**Description**	
Name	CONFCORP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ISINIDENTFR

Attribute	Description
Name	ISINIDENTFR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

SECURITYDESC

Attribute	Description
Name	SECURITYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

SECURITYP

Attribute	Description
Name	SECURITYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>,B,E,R,W,Z</td></tr></table>

TOP

SECREFERNO

Attribute	Description
Name	SECREFERNO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

SECRSTATUS

Attribute	Description
Name	SECRSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,P,R,S,</td></tr></table>

TOP

TRADSTATUS

Attribute	Description
Name	TRADSTATUS
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,I,</td></tr></table>

TOP

INTERESTTYPE

Attribute	Description
Name	INTERESTTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / FLT,FXD,

TOP

LCLMRKTISUE

Attribute	Description
Name	LCLMRKTISUE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ISSUERID

Attribute	Description
Name	ISSUERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ISSUERDES

Attribute	Description
Name	ISSUERDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

REGORBEAR

Attribute	Description
Name	REGORBEAR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,

TOP

FORMTYPE

Attribute	**Description**	
Name	FORMTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	S,I,D,C,G,

TOP

QTYQUT

Attribute	**Description**	
Name	QTYQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

PRIQUT

Attribute	**Description**	
Name	PRIQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,PRI,PRM,PPR,PPM,YTM

TOP

INTQUT

Attribute	**Description**	
Name	INTQUT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / F,P,

TOP

FRACTQUNT

Attribute	Description
Name	FRACTQUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

BUDECIMAL

Attribute	Description
Name	BUDECIMAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BEQRED

Attribute	Description
Name	BEQRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RENOUNCE

Attribute	Description
Name	RENOUNCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REDTYP

Attribute	Description
Name	REDTYP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Q,S,B,</td></tr></table>

TOP

CALLOPTION

Attribute	Description
Name	CALLOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PUTOPTION

Attribute	Description
Name	PUTOPTION
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

PAYMENTCCY

Attribute	Description
Name	PAYMENTCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSISSIZ

Attribute	Description
Name	OSISSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTDQT

Attribute	Description
Name	MINTDQT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOTSIZ

Attribute	Description
Name	LOTSIZ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,O,K,V,A,H,

TOP

PRODUCTDES

Attribute	Description
Name	PRODUCTDES

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MARKTDESC

Attribute	Description
Name	MARKTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Interest

Attribute	Description
Name	Interest
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BLIQD366BASS

Attribute	Description
Name	BLIQD366BASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,D,

TOP

ISSUESIZE

Attribute	Description
Name	ISSUESIZE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCSWIFT

Attribute	Description
Name	DOCSWIFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BZEROINT

Attribute	Description
Name	BZEROINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATEBASS

Attribute	Description
Name	RATEBASS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,C,

TOP

BCUMINTRAT

Attribute	Description
Name	BCUMINTRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRNUMMTH

Attribute	Description
Name	ACCRNUMMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

ACCRDENMTH

Attribute	Description
Name	ACCRDENMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 360,365,ACTUAL,364,

TOP

ACCRDENBSS

Attribute	Description
Name	ACCRDENBSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,C,

TOP

ACRR366BSS

Attribute	Description
Name	ACRR366BSS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,D,

TOP

ACCRINCLDT

Attribute	Description
Name	ACCRINCLDT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDNUMMTH

Attribute	**Description**	
Name	LIQDNUMMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	30-EURO,30-US,ACTUAL,30-ISDA,30-PSA,ACTUAL-JAPANESE,

TOP

LIQDDENMTH

Attribute	**Description**	
Name	LIQDDENMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	360,365,ACTUAL,364,

TOP

LIQDDENBSS

Attribute	**Description**	
Name	LIQDDENBSS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,C,

TOP

BREVWEEK

Attribute	**Description**	
Name	BREVWEEK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	enumeration	1,2,3,4,5,6,7,

TOP

RADHMNTHND

Attribute	Description	
Name	RADHMNTHND	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RNDBASS

Attribute	Description	
Name	RNDBASS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	U,N,

TOP

BPERCOUP

Attribute	Description	
Name	BPERCOUP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALLASNCREV

Attribute	Description	
Name	ALLASNCREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BPERREV

Attribute	Description	
Name	BPERREV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCAPT

Attribute	Description	
Name	BCAPT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

BCOUPFREQ

Attribute	Description	
Name	BCOUPFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

ACCVALDT

Attribute	Description	
Name	ACCVALDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,F,B,

TOP

BCOUPWEEK

Attribute	Description
Name	BCOUPWEEK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,

TOP

COUPPLTDT

Attribute	Description
Name	COUPPLTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,F,B,

TOP

CADHMNTHND

Attribute	Description
Name	CADHMNTHND
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVFRQ

Attribute	Description
Name	REVFRQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

Security-Hol-Ccy

Attribute	Description
Name	Security-Hol-Ccy
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BHOLCCY

Attribute	Description
Name	BHOLCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

Security-Series

Attribute	Description
Name	Security-Series
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BSERIES

Attribute	Description
Name	BSERIES
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

Coupon-Sched

Attribute	Description
Name	Coupon-Sched
Datatype	
Description	

Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BCOUPSTDT

Attribute	**Description**	
Name	BCOUPSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BCOUPTYPE

Attribute	**Description**	
Name	BCOUPTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BCOUPENDT

Attribute	**Description**	
Name	BCOUPENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BBASEFREQ

Attribute	**Description**	
Name	BBASEFREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

COUPWEEK

Attribute	Description
Name	COUPWEEK
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,</td></tr></table>

TOP

ADHMNTHND

Attribute	Description
Name	ADHMNTHND
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TOP

Coupon-Period

Attribute	Description
Name	Coupon-Period
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BPCD

Attribute	Description
Name	BPCD
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BNCD

Attribute	Description
Name	BNCD
Datatype	Date
Description	

Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCOUPTYDES

Attribute	Description
Name	BCOUPTYDES
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BVIRPREVDT2

Attribute	Description
Name	BVIRPREVDT2
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRPREVDT1

Attribute	Description
Name	BVIRPREVDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT1

Attribute	Description
Name	BVIRNEXDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BVIRNEXDT2

Attribute	Description
Name	BVIRNEXDT2
Datatype	Date
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Revision-Sched

Attribute	**Description**	
Name	Revision-Sched	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

BREVSTDT

Attribute	**Description**	
Name	BREVSTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

BREVTYPE

Attribute	**Description**	
Name	BREVTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	D,C,

TOP

BREVENDT

Attribute	**Description**	
Name	BREVENDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REVBASFREQ

Attribute	**Description**
Name	REVBASFREQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,1M,2M,3M,4M,5M,6M,7M,8M,9M,10M,11M,12M,

TOP

REVWEKDAY

Attribute	Description
Name	REVWEKDAY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,

TOP

REVADHMON

Attribute	Description
Name	REVADHMON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Redemption

Attribute	Description
Name	Redemption
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREDEVTDT

Attribute	Description
Name	BREDEVTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BPERRED

Attribute	Description
Name	BPERRED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BREDPRI

Attribute	Description
Name	BREDPRI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BDISPFRAC

Attribute	Description
Name	BDISPFRAC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / RN,RU,RD,RS,

TOP

BCALLINDCAT

Attribute	Description
Name	BCALLINDCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BREDSERIES

Attribute	Description
Name	BREDSERIES
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Revision-Date-Master

Attribute	Description
Name	Revision-Date-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BREVDT

Attribute	Description
Name	BREVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REVEFFDT

Attribute	Description
Name	REVEFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Interest-Assoc

Attribute	Description
Name	Interest-Assoc
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BACQAMT

Attribute	Description
Name	BACQAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BESN

Attribute	Description
Name	BESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCRRATESN

Attribute	Description
Name	BCRRATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BFLTAMT

Attribute	Description
Name	BFLTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINCLACMET

Attribute	Description
Name	BINCLACMET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9,-1,-2,0

TOP

BINTCOMP

Attribute	Description
Name	BINTCOMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BINTRATE

Attribute	Description
Name	BINTRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BINTSPRD

Attribute	Description
Name	BINTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVCEIL

Attribute	Description
Name	BQUOTREVCEIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVFLR

Attribute	Description
Name	BQUOTREVFLR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BQUOTREVIND

Attribute	Description
Name	BQUOTREVIND

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPRD

Attribute	Description
Name	SPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRATECODE

Attribute	Description
Name	BRATECODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BRATCODESC

Attribute	Description
Name	BRATCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BTENCODE

Attribute	Description
Name	BTENCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BTENCODESC

Attribute	Description
Name	BTENCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BWAIVER

Attribute	Description
Name	BWAIVER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Security-Hol-Ccy1

Attribute	Description
Name	Security-Hol-Ccy1
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BSECID

Attribute	Description
Name	BSECID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Assoc

Attribute	Description
Name	Assoc
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATEESN

Attribute	**Description**	
Name	CRRATEESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	**Description**	
Name	RULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Appln

Attribute	**Description**	
Name	Appln	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

CRRATESN

Attribute	Description
Name	CRRATESN
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAGAMNT

Attribute	Description
Name	TAGAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TAXAMNT

Attribute	**Description**	
Name	TAXAMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDINDICAT

Attribute	**Description**	
Name	LIQDINDICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Liqdmaster

Attribute	**Description**	
Name	Liqdmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TAXCCY

Attribute	Description
Name	TAXCCY
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TOP

TAXAMNT

Attribute	Description
Name	TAXAMNT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Issrtax

Attribute	Description
Name	Issrtax
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

INTCOMP

Attribute	Description
Name	INTCOMP
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CRRATESN

Attribute	**Description**	
Name	CRRATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

RATECOD

Attribute	**Description**	
Name	RATECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNUDFDETAILS

Attribute	**Description**	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	**Description**	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	**Description**	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	**Description**	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	**Description**	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	**Description**	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	**Description**	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	**Description**	
Name	COMPMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS4

Attribute	**Description**	
Name	COMPMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS5

Attribute	**Description**	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	**Description**	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	**Description**	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	**Description**	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	**Description**	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	**Description**	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	**Description**	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	**Description**	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	**Description**	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	**Description**	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	**Description**	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	**Description**	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.156.4.SS-ReopenSecInstrument-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Security-Master-PK*
      - *SECURITYID*
    - *Security-Master-IO*
      - *SECURITYID*
      - *Taxheadmaster*
        - *REFERENCE_NO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
      - *Misdetails*
        - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Security-Master-PK

Attribute	Description
Name	Security-Master-PK
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Security-Master-IO

Attribute	Description
Name	Security-Master-IO
Datatype	
Description	

TOP

SECURITYID

Attribute	Description
Name	SECURITYID
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TOP

Taxheadmaster

Attribute	Description
Name	Taxheadmaster
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	

Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	
Restrictions	

Attribute	Description
minOccurs	1

Restrictions	Description
maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

Securities Service
[August] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.